
aiohttp-apispec

Feb 14, 2019

Contents:

1	Guide	3
1.1	Usage	3
1.2	Installation	5
1.3	API Reference	6
	Python Module Index	9

Build and document REST APIs with aiohttp and apispec

aiohttp-apispec key features:

- `docs`, `use_kwargs` and `marshal_with` decorators to add swagger spec support out of the box
- `validation_middleware` middleware to enable validating with marshmallow schemas from those decorators

aiohttp-apispec api is fully inspired by flask-apispec library

1.1 Usage

1.1.1 Quickstart

```
from aiohttp_apispec import (docs,
                             use_kwargs,
                             marshal_with,
                             setup_aiohttp_apispec)

from aiohttp import web
from marshmallow import Schema, fields

class RequestSchema(Schema):
    id = fields.Int()
    name = fields.Str(description='name')
    bool_field = fields.Bool()

class ResponseSchema(Schema):
    msg = fields.Str()
    data = fields.Dict()

@docs(tags=['mytag'],
      summary='Test method summary',
      description='Test method description')
@use_kwargs(RequestSchema(strict=True))
@marshal_with(ResponseSchema(), 200)
async def index(request):
    return web.json_response({'msg': 'done',
                             'data': {}})
```

(continues on next page)

(continued from previous page)

```

# Class based views are also supported:
class TheView(web.View):
    @docs(
        tags=['mytag'],
        summary='View method summary',
        description='View method description',
    )
    @use_kwargs(RequestSchema(strict=True))
    def delete(self):
        return web.json_response({
            'msg': 'done',
            'data': {'name': self.request['data']['name']},
        })

app = web.Application()
app.router.add_post('/v1/test', index)
app.router.add_view('/v1/view', TheView)

# init docs with all parameters, usual for ApiSpec
setup_aiohttp_apispec(app=app, title="My Documentation", version="v1")

# find it on 'http://localhost:8080/api/docs/api-docs'
web.run_app(app)

```

1.1.2 Adding validation middleware

```

from aiohttp_apispec import validation_middleware

...

app.middlewares.append(validation_middleware)

```

Now you can access all validated data in route from `request['data']` like so:

```

@docs(tags=['mytag'],
      summary='Test method summary',
      description='Test method description')
@use_kwargs(RequestSchema(strict=True))
@marshal_with(ResponseSchema(), 200)
async def index(request):
    uid = request['data']['id']
    name = request['data']['name']
    return web.json_response(
        {'msg': 'done',
         'data': {'info': f'name - {name}, id - {uid}'}}
    )

```

You can change Request's 'data' param to another with `request_data_name` argument of `setup_aiohttp_apispec` function:

```

setup_aiohttp_apispec(app=app,
                      request_data_name='validated_data',

```

(continues on next page)

(continued from previous page)

```

        title='My Documentation',
        version='v1',
        url='/api/docs/api-docs')
...

@use_kwargs(RequestSchema(strict=True))
async def index(request):
    uid = request['validated_data']['id']
    ...

```

If you want to catch validation errors you should write your own middleware and catch `web.HTTPClientError`, `json.JSONDecodeError` and so on. Like this:

```

@web.middleware
async def my_middleware(request, handler):
    try:
        return await handler(request)
    except web.HTTPClientError:
        return web.json_response(status=400)

app.middlewares.extend([
    my_middleware, # Catch exception by your own, format it and respond to client
    validation_middleware,
])

```

1.1.3 Build swagger web client

`aiohttp-apispec` adds `swagger_dict` parameter to `aiohttp` web application after initialization (with `setup_aiohttp_apispec` function). So you can use it easily with `aiohttp_swagger` library:

```

from aiohttp_apispec import setup_aiohttp_apispec
from aiohttp_swagger import setup_swagger

def create_app(app):
    setup_aiohttp_apispec(app)

    async def swagger(app):
        setup_swagger(
            app=app, swagger_url='/api/doc', swagger_info=app['swagger_dict']
        )
    app.on_startup.append(swagger)
    # now we can access swagger client on '/api/doc' url
    ...
    return app

```

Now we can access swagger client on `/api/doc` url

1.2 Installation

```
$ pip install -U aiohttp-apispec
```

1.3 API Reference

`aiohttp_apispec.setup_aiohttp_apispec` (*app*: `aiohttp.web_app.Application`, *, *title*: *str* = 'API documentation', *version*: *str* = '0.0.1', *url*: *str* = '/api/docs/api-docs', *request_data_name*: *str* = 'data', ***kwargs*) → None

aiohttp-apispec extension.

Usage:

```
from aiohttp_apispec import docs, use_kwargs, setup_aiohttp_apispec
from aiohttp import web
from marshmallow import Schema, fields

class RequestSchema(Schema):
    id = fields.Int()
    name = fields.Str(description='name')
    bool_field = fields.Bool()

@docs(tags=['mytag'],
      summary='Test method summary',
      description='Test method description')
@use_kwargs(RequestSchema)
async def index(request):
    return web.json_response({'msg': 'done', 'data': {}})

app = web.Application()
app.router.add_post('/v1/test', index)

# init docs with all parameters, usual for ApiSpec
setup_aiohttp_apispec(app=app,
                      title='My Documentation',
                      version='v1',
                      url='/api/docs/api-docs')

# now we can find it on 'http://localhost:8080/api/docs/api-docs'
web.run_app(app)
```

Parameters

- **app** (*Application*) – aiohttp web app
- **title** (*str*) – API title
- **version** (*str*) – API version
- **url** (*str*) – url for swagger spec in JSON format
- **request_data_name** (*str*) – name of the key in Request object

where validated data will be placed by validation_middleware ('data' by default) :param kwargs: any apispec.APISpec kwargs

`aiohttp_apispec.docs` (***kwargs*)

Annotate the decorated view function with the specified Swagger attributes.

Usage:

```

from aiohttp import web

@docs(tags=['my_tag'],
      summary='Test method summary',
      description='Test method description',
      parameters=[{
          'in': 'header',
          'name': 'X-Request-ID',
          'schema': {'type': 'string', 'format': 'uuid'},
          'required': 'true'
      }
    ])
async def index(request):
    return web.json_response({'msg': 'done', 'data': {}})

```

`aiohttp_apispec.use_kwargs` (*schema*, *locations=None*, ***kwargs*)

Add request info into the swagger spec and prepare injection keyword arguments from the specified webargs arguments into the decorated view function in request['data'] for validation_middleware validation middleware.

Usage:

```

from aiohttp import web
from marshmallow import Schema, fields

class RequestSchema(Schema):
    id = fields.Int()
    name = fields.Str(description='name')

@use_kwargs(RequestSchema(strict=True))
async def index(request):
    # aiohttp_apispec_middleware should be used for it
    data = request['data']
    return web.json_response({'name': data['name'],
                             'id': data['id']})

```

Parameters

- **schema** – Schema class or instance
- **locations** – Default request locations to parse

`aiohttp_apispec.marshall_with` (*schema*, *code=200*, *required=False*, *description=None*)

Add response info into the swagger spec

Usage:

```

from aiohttp import web
from marshmallow import Schema, fields

class ResponseSchema(Schema):
    msg = fields.Str()
    data = fields.Dict()

@marshall_with(ResponseSchema(), 200)
async def index(request):
    return web.json_response({'msg': 'done', 'data': {}})

```

Parameters

- **description** (*str*) – response description
- **required** (*bool*) –
- **schema** – Schema class or instance
- **code** (*int*) – HTTP response code

`aiohttp_apispec.validation_middleware` (*request: aiohttp.web_request.Request, handler*) → `aiohttp.web_response.Response`

Validation middleware for aiohttp web app

Usage:

```
app.middlewares.append(validation_middleware)
```

a

`aiohttp_apispec`, 6

A

`aiohhttp_apispec` (module), 6

D

`docs()` (in module `aiohhttp_apispec`), 6

M

`marshal_with()` (in module `aiohhttp_apispec`), 7

S

`setup_aiohhttp_apispec()` (in module `aiohhttp_apispec`), 6

U

`use_kwargs()` (in module `aiohhttp_apispec`), 7

V

`validation_middleware()` (in module `aiohhttp_apispec`), 8