
alot Documentation

Release 0.5.1

Patrick Totzke

January 30, 2017

1	Installation	3
2	Usage	5
2.1	Commandline invocation	5
2.2	First Steps	6
2.3	Commands	6
2.4	Cryptography	13
3	Configuration	17
3.1	Config options	17
3.2	Accounts	26
3.3	Contacts Completion	29
3.4	Key Bindings	30
3.5	Hooks	32
3.6	Theming	35
4	API and Development	39
4.1	Overview	39
4.2	Contributing	39
4.3	Email Database	40
4.4	User Interface	49
4.5	User Settings	59
4.6	Utils	65
4.7	Commands	68
4.8	Crypto	76
5	FAQ	79
6	Manpage	81
6.1	Synopsis	81
6.2	Description	82
6.3	Usage	82
6.4	See Also	82
	Python Module Index	83

Alot is a terminal-based mail user agent for the notmuch mail system. It features a modular and command prompt driven interface to provide a full MUA experience as an alternative to the Emacs mode shipped with notmuch.

Installation

dependencies

Alot depends on recent versions of notmuch and urwid. Note that due to restrictions on argparse and subprocess, you need to run '3.0' > python '2.7' (see *faq*). A full list of dependencies is below:

- [libmagic](#) and [python bindings](#), 5.04
- [configobj](#), 4.7.0
- [twisted](#), 10.2.0:
- [libnotmuch](#) and it's python bindings, 0.13
- [urwid toolkit](#), 1.1.0
- [urwidtrees](#), 1.0
- [PyGPGME](#) 0.2

Note: urwidtrees was only recently detached from alot and is not widely available as a separate package. You can install it e.g., via `pip` directly from github:

```
pip install --user https://github.com/pazz/urwidtrees/archive/master.zip
```

On debian/ubuntu the rest are packaged as:

```
python-setuptools python-magic python-configobj python-twisted python-notmuch python-urwid python-gpgme
```

On fedora/redhat these are packaged as:

```
python-setuptools python-magic python-configobj python-twisted python-notmuch python-urwid pygpgme
```

Alot uses [mailcap](#) to look up mime-handler for inline rendering and opening of attachments. For a full description of the maicap protocol consider the manpage *mailcap(5)* or [RFC 1524](#). To avoid surprises you should at least have an inline renderer (copiousoutput) set up for *text/html*, i.e. have something like this in your `~/.mailcap`:

```
text/html; w3m -dump -o document_charset=%{charset} '%s'; nametemplate=%s.html; copiousoutput
```

get and install alot

You can use `pip` to install directly from GitHub:

```
$ pip install --user https://github.com/pazz/alot/archive/master.zip
```

Don't have pip installed? Just download and extract, then run:

```
python setup.py install --user
```

Make sure `~/local/bin` is in your `PATH`. For system-wide installation omit the `-user` flag and call with the respective permissions.

generate manual and manpage

To generate the documentation you need [sphinx](#), *1.07* installed. Go to `docs/` and do a:

```
make html
make man
```

to generate the user manual and a man page. Both will end up in their respective subfolders in `docs/build`.

Usage

2.1 Commandline invocation

```
alot [-r] [-c CONFIGFILE] [-n NOTMUCHCONFIGFILE] [-C {1,16,256}] [-p DB_PATH]
      [-d {debug,info,warning,error}] [-l LOGFILE] [-v] [-h] [command]
```

Options

- r, --read-only** open db in read only mode
- c, --config=FILENAME** config file (default: ~/.config/alot/config)
- n, --notmuch-config=FILENAME** notmuch config (default: \$NOTMUCH_CONFIG or ~/.notmuch-config)
- C, --colour-mode=COLOUR** terminal colour mode (default: 256). Must be 1, 16 or 256
- p, --mailindex-path=PATH** path to notmuch index
- d, --debug-level=LEVEL** debug log (default: info). Must be one of debug,info,warning or error
- l, --logfile=FILENAME** logfile (default: /dev/null)
- v, --version** Display version string and exit
- h, --help** Display help and exit

UNIX Signals

SIGUSR1 Refreshes the current buffer. Useful for telling alot to refresh the view from a mail downloader e.g. Offlineimap.

Subcommands

search start in a search buffer using the querystring provided as parameter. See also the SEARCH SYNTAX section of notmuch(1) and the output of *alot search -help*.

compose compose a new message See the output of *alot compose -help* for more info on parameters.

pyshell start the interactive python shell inside alot See the output of *alot pyshell -help* for more info on parameters.

2.2 First Steps

The arrow keys, *page-up/down*, *j*, *k* and *Space* can be used to move the focus. *Escape* cancels prompts and *Enter* selects. Hit `:` at any time and type in commands to the prompt.

The interface shows one buffer at a time, you can use *Tab* and *Shift-Tab* to switch between them, close the current buffer with *d* and list them all with `;`.

The buffer type or *mode* (displayed at the bottom left) determines which prompt commands are available. Usage information on any command can be listed by typing *help YOURCOMMAND* to the prompt; The key bindings for the current mode are listed upon pressing `?`.

2.3 Commands

Alot interprets user input as command line strings given via its prompt or *bound to keys* in the config. Command lines are semi-colon separated command strings, each of which starts with a command name and possibly followed by arguments.

See the sections below for which commands are available in which (UI) mode. *global* commands are available independently of the mode.

Global Commands globally available commands

Commands in search mode commands available when showing thread search results

Commands in thread mode commands available while displaying a thread

Commands in envelope mode commands during message composition

Commands in bufferlist mode commands while listing active buffers

Commands in taglist mode commands while listing all tagstrings present in the notmuch database

2.3.1 Global Commands

The following commands are available globally

bclose

close a buffer

optional arguments

—**redraw** redraw current buffer after command has finished.

—**force** never ask for confirmation.

bprevious

focus previous buffer

search

open a new search buffer

argument search string

optional arguments

—**sort** sort order. Valid choices are: ‘oldest_first’, ‘newest_first’, ‘message_id’, ‘unsorted’.

repeat

Repeats the command executed last time

prompt

prompts for commandline and interprets it upon select

argument initial content

help

display help for a command. Use 'bindings' to display all keybindings interpreted in current mode.'

argument command or 'bindings'

buffer

focus buffer with given index

argument buffer index to focus

move

move focus in current buffer

argument up, down, [half]page up, [half]page down, first

shellescape

run external command

argument command line to execute

optional arguments

—**spawn** run in terminal window.

—**thread** run in separate thread.

—**refocus** refocus current buffer after command has finished.

refresh

refresh the current buffer

pyshell

open an interactive python shell for introspection

compose

compose a new email

argument None

optional arguments

—**sender** sender.

—**template** path to a template message file.

—**subject** subject line.

—**to** recipients.

—**cc** copy to.

—**bcc** blind copy to.

—**attach** attach files.

—**omit_signature** do not add signature.

—**spawn** spawn editor in new terminal.

exit

Shut down cleanly.

The `_prompt` variable is for internal use only, it's used to control prompting to close without sending, and is used by the `BufferCloseCommand` if settings change after yielding to the UI.

flush

flush write operations or retry until committed

bufferlist

open a list of active buffers

call

Executes python code

argument python command string to call

bnext

focus next buffer

taglist

opens taglist buffer

optional arguments

—**tags** tags to display.

2.3.2 Commands in *search* mode

The following commands are available in search mode

sort

set sort order

argument sort order. valid choices are: 'oldest_first', 'newest_first', 'message_id', 'unsorted'.

untag

remove tags from all messages in the thread that match the query

argument comma separated list of tags

optional arguments

—**no-flush** postpone a writeout to the index (Defaults to: 'True').

—**all** retag all messages in search result.

move

move focus in search buffer

argument last

retag

set tags of all messages in the thread that match the current query

argument comma separated list of tags

optional arguments

—**no-flush** postpone a writeout to the index (Defaults to: 'True').

—**all** retag all messages in search result.

refineprompt

prompt to change this buffers querystring

tag

add tags to all messages in the thread that match the current query

argument comma separated list of tags

optional arguments

—**no-flush** postpone a writeout to the index (Defaults to: ‘True’).

—**all** retag all messages in search result.

refine

refine query

argument search string

optional arguments

—**sort** sort order. Valid choices are: ‘oldest_first’, ‘newest_first’, ‘message_id’, ‘unsorted’.

retagprompt

prompt to retag selected threads’ tags

toggletags

flip presence of tags on this thread. A tag is considered present if at least one message contained in this thread is tagged with it. In that case this command will remove the tag from every message in the thread.

argument comma separated list of tags

optional arguments

—**no-flush** postpone a writeout to the index (Defaults to: ‘True’).

select

open thread in a new buffer

2.3.3 Commands in *thread* mode

The following commands are available in thread mode

pipeto

pipe message(s) to stdin of a shellcommand

argument shellcommand to pipe to

optional arguments

—**all** pass all messages.

—**format** output format. Valid choices are: ‘raw’, ‘decoded’, ‘id’, ‘filepath’ (Defaults to: ‘raw’).

—**separately** call command once for each message.

—**background** don’t stop the interface.

—**add_tags** add ‘Tags’ header to the message.

—**shell** let the shell interpret the command.

—**notify_stdout** display cmd’s stdout as notification.

—**field_key** mailcap field key for decoding (Defaults to: ‘copiousoutput’).

editnew

edit message in as new

optional arguments

—**spawn** open editor in new window.

move

move focus in current buffer

argument up, down, page up, page down, first, last

untag

remove tags from message(s)

argument comma separated list of tags

optional arguments

—**all** tag all messages in thread.

—**no-flush** postpone a writeout to the index (Defaults to: 'True').

toggleheaders

display all headers

argument query used to filter messages to affect

print

print message(s)

optional arguments

—**all** print all messages.

—**raw** pass raw mail string.

—**separately** call print command once for each message.

—**add_tags** add 'Tags' header to the message.

bounce

directly re-send selected message

togglesource

display message source

argument query used to filter messages to affect

retag

set message(s) tags.

argument comma separated list of tags

optional arguments

—**all** tag all messages in thread.

—**no-flush** postpone a writeout to the index (Defaults to: 'True').

fold

fold message(s)

argument query used to filter messages to affect

tag

add tags to message(s)

argument comma separated list of tags

optional arguments

—**all** tag all messages in thread.

—**no-flush** postpone a writeout to the index (Defaults to: 'True').

remove

remove message(s) from the index

optional arguments

—**all** remove whole thread.

unfold

unfold message(s)

argument query used to filter messages to affect

forward

forward message

optional arguments

—**attach** attach original mail.

—**spawn** open editor in new window.

reply

reply to message

optional arguments

—**all** reply to all.

—**list** reply to list.

—**spawn** open editor in new window.

save

save attachment(s)

argument path to save to

optional arguments

—**all** save all attachments.

toggletags

flip presence of tags on message(s)

argument comma separated list of tags

optional arguments

—**all** tag all messages in thread.

—**no-flush** postpone a writeout to the index (Defaults to: 'True').

select

select focussed element. The fired action depends on the focus:

- if message summary, this toggles visibility of the message,
- if attachment line, this opens the attachment

2.3.4 Commands in *envelope* mode

The following commands are available in envelope mode

unencrypt

remove request to encrypt message before sending

set

set header value

positional arguments 0: header to refine 1: value

optional arguments

—**append** keep previous values.

encrypt

request encryption of message before sendout

argument keyid of the key to encrypt with

optional arguments

—**trusted** only add trusted keys.

togglesign

toggle sign status

argument which key id to use

toggleheaders

toggle display of all headers

edit

edit mail

optional arguments

—**spawn** spawn editor in new terminal.

—**refocus** refocus envelope after editing (Defaults to: 'True').

send

send mail

sign

mark mail to be signed before sending

argument which key id to use

attach

attach files to the mail

argument file(s) to attach (accepts wildcards)

unattach

remove attachments from current envelope

argument which attached file to remove

rmencrypt

do not encrypt to given recipient key

argument keyid of the key to encrypt with

refine

prompt to change the value of a header

argument header to refine

toggleencrypt

toggle if message should be encrypted before sendout

argument keyid of the key to encrypt with

optional arguments

—**trusted** only add trusted keys.

save

save draft

unsign

mark mail not to be signed before sending

unset

remove header field

argument header to refine

2.3.5 Commands in *bufferlist* mode

The following commands are available in *bufferlist* mode

close

close focussed buffer

open

focus selected buffer

2.3.6 Commands in *taglist* mode

The following commands are available in *taglist* mode

select

search for messages with selected tag

2.4 Cryptography

Alot has built in support for constructing signed and/or encrypted mails according to PGP/MIME ([RFC 3156](#), [RFC 3156](#)) via gnupg. It does however rely on a running *gpg-agent* to handle password entries.

Note: You need to have *gpg-agent* running to use GPG with alot!

gpg-agent will handle passphrase entry in a secure and configurable way, and it will cache your passphrase for some time so you don't have to enter it over and over again. For details on how to set this up we refer to [gnupg's manual](#).

Signing outgoing emails

You can use the commands *sign*, *unsign* and *togglesign* in envelope mode to determine if you want this mail signed and if so, which key to use. To specify the key to use you may pass a hint string as argument to the *sign* or *togglesign* command. This hint would typically be a fingerprint or an email address associated (by gnupg) with a key.

Signing (and hence passwd entry) will be done at most once shortly before a mail is sent.

In case no key is specified, alot will leave the selection of a suitable key to gnupg so you can influence that by setting the *default-key* option in `~/ .gnupg/gpg.conf` accordingly.

You can set the default to-sign bit and the key to use for each *account* individually using the options *sign_by_default* and *gpg_key*.

Encrypt outgoing emails

You can use the commands *encrypt*, *unencrypt* and *toggleencrypt* and in envelope mode to ask alot to encrypt the mail before sending. The *encrypt* command accepts an optional hint string as argument to determine the key of the recipient.

You can set the default to-encrypt bit for each *account* individually using the option *encrypt_by_default*.

Note: If you want to access encrypt mail later it is useful to add yourself to the list of recipients when encrypting with gpg (not the recipients whom mail is actually send to). The simplest way to do this is to use the *encrypt-to* option in the `~/ .gnupg/gpg.conf`. But you might have to specify the correct encryption subkey otherwise gpg seems to throw an error.

2.4.1 Commands

Alot interprets user input as command line strings given via its prompt or *bound to keys* in the config. Command lines are semi-colon separated command strings, each of which starts with a command name and possibly followed by arguments.

See the sections below for which commands are available in which (UI) mode. *global* commands are available independently of the mode.

Global Commands globally available commands

Commands in search mode commands available when showing thread search results

Commands in thread mode commands available while displaying a thread

Commands in envelope mode commands during message composition

Commands in bufferlist mode commands while listing active buffers

Commands in taglist mode commands while listing all tagstrings present in the notmuch database

The arrow keys, *page-up/down*, *j*, *k* and *Space* can be used to move the focus. *Escape* cancels prompts and *Enter* selects. Hit `:` at any time and type in commands to the prompt.

The interface shows one buffer at a time, you can use *Tab* and *Shift-Tab* to switch between them, close the current buffer with *d* and list them all with `;`.

The buffer type or *mode* (displayed at the bottom left) determines which prompt commands are available. Usage information on any command can be listed by typing *help YOURCOMMAND* to the prompt; The key bindings for the current mode are listed upon pressing `?`.

```
alot [-r] [-c CONFIGFILE] [-n NOTMUCHCONFIGFILE] [-C {1,16,256}] [-p DB_PATH]
      [-d {debug,info,warning,error}] [-l LOGFILE] [-v] [-h] [command]
```

Options

-r, --read-only open db in read only mode

-c, --config=FILENAME config file (default: `~/ .config/alot/config`)

-n, --notmuch-config=FILENAME notmuch config (default: `$NOTMUCH_CONFIG` or `~/ .notmuch-config`)

- C, --colour-mode=COLOUR** terminal colour mode (default: 256). Must be 1, 16 or 256
- p, --mailindex-path=PATH** path to notmuch index
- d, --debug-level=LEVEL** debug log (default: info). Must be one of debug,info,warning or error
- l, --logfile=FILENAME** logfile (default: /dev/null)
- v, --version** Display version string and exit
- h, --help** Display help and exit

UNIX Signals

SIGUSR1 Refreshes the current buffer. Useful for telling alot to refresh the view from a mail downloader e.g. Offlineimap.

Subcommands

search start in a search buffer using the querystring provided as parameter. See also the SEARCH SYNTAX section of notmuch(1) and the output of *alot search -help*.

compose compose a new message See the output of *alot compose -help* for more info on parameters.

pyshell start the interactive python shell inside alot See the output of *alot pyshell -help* for more info on parameters.

2.4.2 Cryptography

Alot has built in support for constructing signed and/or encrypted mails according to PGP/MIME ([RFC 3156](#), [RFC 3156](#)) via gnupg. It does however rely on a running *gpg-agent* to handle password entries.

Note: You need to have *gpg-agent* running to use GPG with alot!

gpg-agent will handle passphrase entry in a secure and configurable way, and it will cache your passphrase for some time so you don't have to enter it over and over again. For details on how to set this up we refer to [gnupg's manual](#).

Signing outgoing emails

You can use the commands *sign*, *unsign* and *togglesign* in envelope mode to determine if you want this mail signed and if so, which key to use. To specify the key to use you may pass a hint string as argument to the *sign* or *togglesign* command. This hint would typically be a fingerprint or an email address associated (by gnupg) with a key.

Signing (and hence passwd entry) will be done at most once shortly before a mail is sent.

In case no key is specified, alot will leave the selection of a suitable key to gnupg so you can influence that by setting the *default-key* option in `~/ .gnupg/gpg.conf` accordingly.

You can set the default to-sign bit and the key to use for each *account* individually using the options *sign_by_default* and *gpg_key*.

Encrypt outgoing emails

You can use the commands *encrypt*, *unencrypt* and *toggleencrypt* and in envelope mode to ask alot to encrypt the mail before sending. The *encrypt* command accepts an optional hint string as argument to determine the key of the recipient.

You can set the default to-encrypt bit for each *account* individually using the option *encrypt_by_default*.

Note: If you want to access encrypt mail later it is useful to add yourself to the list of recipients when encrypting with `gpg` (not the recipients whom mail is actually send to). The simplest way to do this is to use the *encrypt-to* option in the `~/ .gnupg/gpg.conf`. But you might have to specify the correct encryption subkey otherwise `gpg` seems to throw an error.

Configuration

Alot reads a config file in “INI” syntax: It consists of key-value pairs that use “=” as separator and ‘#’ is comment-prefixes. Sections and subsections are defined using square brackets.

The default location for the config file is `~/.config/alot/config`.

All configs are optional, but if you want to send mails you need to specify at least one *account* in your config.

3.1 Config options

The following lists all available config options with their type and default values. The type of an option is used to validate a given value. For instance, if the type says “boolean” you may only provide “True” or “False” as values in your config file, otherwise alot will complain on startup. Strings *may* be quoted but do not need to be.

ask_subject

Type boolean

Default True

attachment_prefix

directory prefix for downloading attachments

Type string

Default “~”

auto_remove_unread

automatically remove ‘unread’ tag when focussing messages in thread mode

Type boolean

Default True

auto_replyto_mailinglist

Automatically switch to list reply mode if appropriate

Type boolean

Default False

bounce_force_address

Always use the accounts main address when constructing “Resent-From” headers for bounces. Set this to False to use the address string as received in the original message.

Type boolean

Default False

bounce_force_realname

Always use the proper realname when constructing “Resent-From” headers for bounces. Set this to False to use the realname string as received in the original message.

Type boolean

Default True

bufferclose_focus_offset

offset of next focused buffer if the current one gets closed

Type integer

Default -1

bufferlist_statusbar

Format of the status-bar in bufferlist mode. This is a pair of strings to be left and right aligned in the status-bar that may contain variables:

- {buffer_no}*: index of this buffer in the global buffer list
- {total_messages}*: total numer of messages indexed by notmuch
- {pending_writes}*: number of pending write operations to the index

Type mixed_list

Default [{buffer_no}: bufferlist], {input_queue} total messages: {total_messages}

bug_on_exit

confirm exit

Type boolean

Default False

colourmode

number of colours to use

Type option, one of ['1', '16', '256']

Default 256

complete_matching_abook_only

in case more than one account has an address book: Set this to True to make tab completion for recipients during compose only look in the abook of the account matching the sender address

Type boolean

Default False

compose_ask_tags

prompt for initial tags when compose

Type boolean

Default False

displayed_headers

headers that get displayed by default

Type string list

Default From, To, Cc, Bcc, Subject

edit_headers_blacklist

see *edit_headers_whitelist*

Type string list

Default Content-Type, MIME-Version, References, In-Reply-To

edit_headers_whitelist

Which header fields should be editable in your editor used are those that match the whitelist and don't match the blacklist. in both cases '*' may be used to indicate all fields.

Type string list

Default *,

editor_cmd

editor command if unset, alot will first try the EDITOR env variable, then /usr/bin/editor

Type string

Default None

editor_in_thread

call editor in separate thread. In case your editor doesn't run in the same window as alot, setting true here will make alot non-blocking during edits

Type boolean

Default False

editor_spawn

use terminal_command to spawn a new terminal for the editor? equivalent to always providing the *-spawn=yes* parameter to compose/edit commands

Type boolean

Default False

editor_writes_encoding

file encoding used by your editor

Type string

Default “UTF-8”

envelope_headers_blacklist

headers that are hidden in envelope buffers by default

Type string list

Default In-Reply-To, References

envelope_statusbar

Format of the status-bar in envelope mode. This is a pair of strings to be left and right aligned in the status-bar. Apart from the global variables listed at *bufferlist_statusbar* these strings may contain variables:

- {to}*: To-header of the envelope

Type mixed_list

Default [{buffer_no}: envelope], {input_queue} total messages: {total_messages}

flush_retry_timeout

timeout in seconds after a failed attempt to writeout the database is repeated. Set to 0 for no retry.

Type integer

Default 5

followup_to

When one of the recipients of an email is a subscribed mailing list, set the “Mail-Followup-To” header to the list of recipients without yourself

Type boolean

Default False

forward_force_address

Always use the accounts main address when constructing “From” headers for forwards. Set this to False to use the address string as received in the original message.

Type boolean

Default False

forward_force_realname

Always use the proper realname when constructing “From” headers for forwards. Set this to False to use the realname string as received in the original message.

Type boolean

Default True

forward_subject_prefix

String prepended to subject header on forward only if original subject doesn't start with 'Fwd:' or this prefix

Type string

Default "Fwd: "

handle_mouse

enable mouse support - mouse tracking will be handled by urwid

Type boolean

Default False

history_size

The number of command line history entries to save

Note: You can set this to -1 to save *all* entries to disk but the history file might get *very* long.

Type integer

Default 50

honor_followup_to

When group-reply-ing to an email that has the "Mail-Followup-To" header set, use the content of this header as the new "To" header and leave the "Cc" header empty

Type boolean

Default False

hooksfile

where to look up hooks

Type string

Default "~/config/alot/hooks.py"

initial_command

initial command when none is given as argument:

Type string

Default "search tag:inbox AND NOT tag:killed"

input_timeout

timeout in (floating point) seconds until partial input is cleared

Type float

Default 1.0

mailinglists

The list of addresses associated to the mailinglists you are subscribed to

Type string list

Default ,

msg_summary_hides_threadwide_tags

In a thread buffer, hide from messages summaries tags that are common to all messages in that thread.

Type boolean

Default True

notify_timeout

time in secs to display status messages

Type integer

Default 2

periodic_hook_frequency

The number of seconds to wait between calls to the loop_hook

Type integer

Default 300

prefer_plaintext

prefer plaintext alternatives over html content in multipart/alternative

Type boolean

Default False

print_cmd

how to print messages: this specifies a shell command used for printing. threads/messages are piped to this command as plain text. muttprint/a2ps works nicely

Type string

Default None

prompt_suffix

Suffix of the prompt used when waiting for user input

Type string

Default ”:”

quit_on_last_bclose

shut down when the last buffer gets closed

Type boolean

Default False

quote_prefix

String prepended to line when quoting

Type string

Default "> "

reply_account_header_priority

The list of headers to match to determine sending account for a reply. Headers are searched in the order in which they are specified here, and the first header containing a match is used. If multiple accounts match in that header, the one defined first in the account block is used.

Type string list

Default From, To, Cc, Envelope-To, X-Envelope-To, Delivered-To

reply_force_address

Always use the accounts main address when constructing "From" headers for replies. Set this to False to use the address string as received in the original message.

Type boolean

Default False

reply_force_realname

Always use the proper realname when constructing "From" headers for replies. Set this to False to use the realname string as received in the original message.

Type boolean

Default True

reply_subject_prefix

String prepended to subject header on reply only if original subject doesn't start with 'Re:' or this prefix

Type string

Default "Re: "

search_statusbar

Format of the status-bar in search mode. This is a pair of strings to be left and right aligned in the status-bar. Apart from the global variables listed at [bufferlist_statusbar](#) these strings may contain variables:

- {querystring}*: search string
- {result_count}*: number of matching messages

•*{result_count_positive}*: ‘s’ if result count is greater than 0.

Type mixed_list

Default [{buffer_no}: search] for “{querystring}”, {input_queue} {result_count} of {total_messages} messages

search_threads_sort_order

default sort order of results in a search

Type option, one of [‘oldest_first’, ‘newest_first’, ‘message_id’, ‘unsorted’]

Default newest_first

show_statusbar

display status-bar at the bottom of the screen?

Type boolean

Default True

tabwidth

number of spaces used to replace tab characters

Type integer

Default 8

taglist_statusbar

Format of the status-bar in taglist mode. This is a pair of strings to be left and right aligned in the status-bar. These strings may contain variables listed at *bufferlist_statusbar* that will be substituted accordingly.

Type mixed_list

Default [{buffer_no}: taglist], {input_queue} total messages: {total_messages}

template_dir

templates directory that contains your message templates. It will be used if you give *compose -template* a filename without a path prefix.

Type string

Default “\$XDG_CONFIG_HOME/alot/templates”

terminal_cmd

set terminal command used for spawning shell commands

Type string

Default “x-terminal-emulator -e”

theme

name of the theme to use

Type string

Default None

themes_dir

directory containing theme files

Type string

Default None

thread_authors_me

Word to replace own addresses with. Works in combination with *thread_authors_replace_me*

Type string

Default “Me”

thread_authors_order_by

When constructing the unique list of thread authors, order by date of author’s first or latest message in thread

Type option, one of [‘first_message’, ‘latest_message’]

Default first_message

thread_authors_replace_me

Replace own email addresses with “me” in author lists Uses own addresses and aliases in all configured accounts.

Type boolean

Default True

thread_statusbar

Format of the status-bar in thread mode. This is a pair of strings to be left and right aligned in the status-bar. Apart from the global variables listed at *bufferlist_statusbar* these strings may contain variables:

- {tid}*: thread id
- {subject}*: subject line of the thread
- {authors}*: abbreviated authors string for this thread
- {message_count}*: number of contained messages

Type mixed_list

Default [{buffer_no}: thread] {subject}, {input_queue} total messages: {total_messages}

thread_subject

What should be considered to be “the thread subject”. Valid values are:

- ‘notmuch’ (the default), will use the thread subject from notmuch, which depends on the selected sorting method

- ‘oldest’ will always use the subject of the oldest message in the thread as the thread subject

Type option, one of [‘oldest’, ‘notmuch’]

Default notmuch

timestamp_format

timestamp format in `strftime` format syntax

Type string

Default None

user_agent

value of the User-Agent header used for outgoing mails. setting this to the empty string will cause alot to omit the header all together. The string ‘{version}’ will be replaced by the version string of the running instance.

Type string

Default “alot/{version}”

3.2 Accounts

In order to be able to send mails, you have to define at least one account subsection in your config: There needs to be a section “accounts”, and each subsection, indicated by double square brackets defines an account.

Here is an example configuration

```
[accounts]
  [[work]]
    realname = Bruce Wayne
    address = b.wayne@wayneenterprises.com
    alias_regexp = b.wayne\+.\+@wayneenterprises.com
    pgp_key = D7D6C5AA
    sendmail_command = msmtpl --account=wayne -t
    sent_box = maildir:///home/bruce/mail/work/Sent
    draft_box = maildir:///home/bruce/mail/work/Drafts

  [[secret]]
    realname = Batman
    address = batman@batcave.org
    aliases = batman@batmobile.org,
    sendmail_command = msmtpl --account=batman -t
    signature = ~/.batman.vcf
    signature_as_attachment = True
```

Warning: Sending mails is only supported via a sendmail shell command for now. If you want to use a sendmail command different from `sendmail -t`, specify it as `sendmail_command`.

The following entries are interpreted at the moment:

address

your main email address

Type string

realname

used to format the (proposed) From-header in outgoing mails

Type string

aliases

used to clear your addresses/ match account when formatting replies

Type string list

Default ,

alias_regexp

a regex for catching further aliases (like + extensions).

Type string

Default None

sendmail_command

sendmail command. This is the shell command used to send out mails via the sendmail protocol

Type string

Default “sendmail -t”

sent_box

where to store outgoing mails, e.g. *maildir:///home/you/mail/Sent*. You can use mbox, maildir, mh, babyl and mmdf in the protocol part of the URL.

Note: If you want to add outgoing mails automatically to the notmuch index you must use maildir in a path within your notmuch database path.

Type mail_container

Default None

draft_box

where to store draft mails, e.g. *maildir:///home/you/mail/Drafts*. You can use mbox, maildir, mh, babyl and mmdf in the protocol part of the URL.

Note: You will most likely want drafts indexed by notmuch to be able to later access them within alot. This currently only works for maildir containers in a path below your notmuch database path.

Type mail_container

Default None

sent_tags

list of tags to automatically add to outgoing messages

Type string list

Default sent,

signature

path to signature file that gets attached to all outgoing mails from this account, optionally renamed to *signature_filename*.

Type string

Default None

signature_as_attachment

attach signature file if set to True, append its content (mimetype text) to the body text if set to False.

Type boolean

Default False

signature_filename

signature file's name as it appears in outgoing mails if *signature_as_attachment* is set to True

Type string

Default None

sign_by_default

Outgoing messages will be GPG signed by default if this is set to True.

Type boolean

Default False

encrypt_by_default

Alot will try to GPG encrypt outgoing messages by default when this is set to *all* or *trusted*. If set to *all* the message will be encrypted for all recipients for who a key is available in the key ring. If set to *trusted* it will be encrypted to all recipients if a trusted key is available for all recipients (one where the user id for the key is signed with a trusted signature).

Note: If the message will not be encrypted by default you can still use the *toggleencrypt*, *encrypt* and *unencrypt* commands to encrypt it.

Note: The values *True* and *False* are interpreted as *all* and *none* respectively. They are kept for backwards compatibility to give users a change to migrate to the new option type. They might become deprecated in future versions.

Type option, one of ['all', 'none', 'trusted', 'True', 'False', 'true', 'false', 'Yes', 'No', 'yes', 'no', '1', '0']

Default none

gpg_key

The GPG key ID you want to use with this account. If unset, alot will use your default key.

Type string

Default None

3.3 Contacts Completion

For each *account* you can define an address book by providing a subsection named *abook*. Crucially, this section needs an option *type* that specifies the type of the address book. The only types supported at the moment are “shellcommand” and “abook”. Both respect the *ignorecase* option which defaults to *True* and results in case insensitive lookups.

shellcommand

Address books of this type use a shell command in combination with a regular expression to look up contacts.

The value of *command* will be called with the search prefix as only argument for lookups. Its output is searched for email-name pairs using the regular expression given as *regex*, which must include named groups “email” and “name” to match the email address and realname parts respectively. See below for an example that uses *abook*

```
[accounts]
  [[youraccount]]
    # ...
    [[abook]]
      type = shellcommand
      command = abook --mutt-query
      regex = '^ (?P<email>[^@]+@[^\t]+) \t+ (?P<name>[^\t]+) '
      ignorecase = True
```

See [here](#) for alternative lookup commands. The few others I have tested so far are:

goobook for cached google contacts lookups. Works with the above default regex

```
command = goobook query
regex = '^ (?P<email>[^@]+@[^\t]+) \t+ (?P<name>[^\t]+) '
```

nottoomuch-addresses completes contacts found in the notmuch index:

```
command = nottoomuch-addresses.sh
regex = \" (?P<name>.)+ \"\s*<( ?P<email>.*+?@.*+?)>
```

notmuch-abook completes contacts found in database of notmuch-abook:

```
command = notmuch_abook.py lookup
regex = ^ ( (?P<name>[^\s+<]*) \s+< )? (?P<email>[^@]+?@[^\t]+)?>$
```

notmuch address Since version *0.19*, notmuch itself offers a subcommand *address*, that returns email addresses found in the notmuch index. Combined with the *date*: syntax to query for mails within a certain timeframe, this allows to search for all recently used contacts:

```
command = 'notmuch address --format=json --output=recipients date:1Y.. AND from:my@address.c
regexp = '\[?{"name": "(?P<name>.*)", "address": "(?P<email>.+)", "name-addr": ".*"}[, \]]?'
shellcommand_external_filtering = False
```

Don't hesitate to send me your custom *regexp* values to list them here.

abook

Address books of this type directly parse `abooks` contact files. You may specify a path using the “`abook_contacts_file`” option, which defaults to `~/ .abook/addressbook`. To use the default path, simply do this:

```
[accounts]
[[youraccount]]
# ...
[[[abook]]]
    type = abook
```

3.4 Key Bindings

If you want to bind a command to a key you can do so by adding the pair to the `[bindings]` section. This will introduce a *global* binding, that works in all modes. To make a binding specific to a mode you have to add the pair under the subsection named like the mode. For instance, if you want to bind `T` to open a new search for threads tagged with ‘`todo`’, and be able to toggle this tag in search mode, you'd add this to your config

```
[bindings]
T = search tag:todo

[[[search]]]
t = toggletags todo
```

Known modes are:

- envelope
- search
- thread
- taglist
- bufferlist

Have a look at the [urwid User Input documentation](#) on how key strings are formatted.

3.4.1 Default bindings

User-defined bindings are combined with the default bindings listed below.

```
up = move up
down = move down
page up = move page up
page down = move page down
mouse press 4 = move up
mouse press 5 = move down
j = move down
k = move up
'g g' = move first
```

```

G = move last
' ' = move page down
'ctrl d' = move halfpage down
'ctrl u' = move halfpage up
@ = refresh
? = help bindings
I = search tag:inbox AND NOT tag:killed
'#' = taglist
shift tab = bprevious
U = search tag:unread
tab = bnext
\ = prompt 'search '
d = bclose
$ = flush
m = compose
o = prompt 'search '
q = exit
';' = bufferlist
':' = prompt
. = repeat

```

[bufferlist]

```

x = close
enter = open

```

[search]

```

enter = select
a = toggletags inbox
& = toggletags killed
! = toggletags flagged
s = toggletags unread
l = retagprompt
O = refineprompt
| = refineprompt

```

[envelope]

```

a = prompt 'attach ~/ '
y = send
P = save
s = 'refine Subject'
f = prompt 'set From '
t = 'refine To'
b = 'refine Bcc'
c = 'refine Cc'
S = togglesign
enter = edit
'g f' = togglesource

```

[taglist]

```

enter = select

```

[thread]

```

enter = select
C = fold *
E = unfold *
c = fold
e = unfold
< = fold

```

```

> = unfold
'g f' = togglesource
H = toggleheaders
P = print --all --separately --add_tags
S = save --all
g = reply --all
f = forward
p = print --add_tags
n = editnew
b= bounce
s = save
r = reply
| = prompt 'pipeto '

'g j' = move next sibling
'g k' = move previous sibling
'g h' = move parent
'g l' = move first reply
' ' = move next

```

In prompts the following hardcoded bindings are available.

Key	Function
Ctrl-f/b	Moves the cursor one character to the right/left
Alt-f/b Shift-right/left	Moves the cursor one word to the right/left
Ctrl-a/e	Moves the cursor to the beginning/end of the line
Ctrl-d	Deletes the character under the cursor
Alt-d	Deletes everything from the cursor to the end of the current or next word
Alt-Delete/Backspace	Deletes everything from the cursor to the beginning of the current or previous
Ctrl-w	word
Ctrl-k	Deletes everything from the cursor to the end of the line
Ctrl-u	Deletes everything from the cursor to the beginning of the line

3.4.2 Overwriting defaults

To disable a global binding you can redefine it in your config to point to an empty command string. For example, to add a new global binding for key *a*, which is bound to *toggletags inbox* in search mode by default, you can remap it as follows.

```

[bindings]
a = NEW GLOBAL COMMAND

[[search]]
a =

```

If you omit the last two lines, *a* will still be bound to the default binding in search mode.

3.5 Hooks

Hooks are python callables that live in a module specified by *hooksfile* in the config. Per default this points to `~/ .config/alot/hooks.py`.

Pre/Post Command Hooks

For every *COMMAND* in mode *MODE*, the callables `pre_MODE_COMMAND()` and `post_MODE_COMMAND()` – if defined – will be called before and after the command is applied respectively. In addition callables `pre_global_COMMAND()` and `post_global_COMMAND()` can be used. They will be called if no specific hook function for a mode is defined. The signature for the pre-send hook in envelope mode for example looks like this:

`pre_envelope_send(ui=None, dbm=None, cmd=None)`

Parameters

- **ui** (`alot.ui.UI`) – the main user interface
- **dbm** (`alot.db.manager.DBManager`) – a database manager
- **cmd** (`alot.commands.Command`) – the Command instance that is being called

Consider this pre-hook for the exit command, that logs a personalized goodbye message:

```
import logging
from alot.settings import settings
def pre_global_exit(**kwargs):
    accounts = settings.get_accounts()
    if accounts:
        logging.info('goodbye, %s!' % accounts[0].realname)
    else:
        logging.info('goodbye!')
```

Other Hooks

Apart from command pre- and posthooks, the following hooks will be interpreted:

reply_prefix (*realname*, *address*, *timestamp*[, *ui=None*, *dbm=None*])

Is used to reformat the first indented line in a reply message. This defaults to ‘Quoting %s (%s)n’ % (realname, timestamp)’ unless this hook is defined

Parameters

- **realname** (*str*) – name or the original sender
- **address** (*str*) – address of the sender
- **timestamp** (`datetime.datetime`) – value of the Date header of the replied message

Return type `string`

forward_prefix (*realname*, *address*, *timestamp*[, *ui=None*, *dbm=None*])

Is used to reformat the first indented line in a inline forwarded message. This defaults to ‘Forwarded message from %s (%s)n’ % (realname, timestamp)’ if this hook is undefined

Parameters

- **realname** (*str*) – name or the original sender
- **address** (*str*) – address of the sender
- **timestamp** (`datetime.datetime`) – value of the Date header of the replied message

Return type `string`

pre_edit_translate (*text* [, *ui= None, dbm=None*])

Used to manipulate a message's text *before* the editor is called. The text might also contain some header lines, depending on the settings *edit_headers_whitelist* and *edit_header_blacklist*.

Parameters **text** (*str*) – text representation of mail as displayed in the interface and as sent to the editor

Return type *str*

post_edit_translate (*text* [, *ui= None, dbm=None*])

used to manipulate a message's text *after* the editor is called, also see *pre_edit_translate*

Parameters **text** (*str*) – text representation of mail as displayed in the interface and as sent to the editor

Return type *str*

text_quote (*message*)

used to transform a message into a quoted one

Parameters **message** (*str*) – message to be quoted

Return type *str*

timestamp_format (*timestamp*)

represents given timestamp as string

Parameters **timestamp** (*datetime*) – timestamp to represent

Return type *str*

touch_external_cmdlist (*cmd, shell=shell, spawn=spawn, thread=thread*)

used to change external commands according to given flags shortly before they are called.

Parameters

- **cmd** (*list of str*) – command to be called
- **shell** (*bool*) – is this to be interpreted by the shell?
- **spawn** (*bool*) – should be spawned in new terminal/environment
- **threads** – should be called in new thread

Returns triple of amended command list, shell and thread flags

Return type list of *str*, *bool*, *bool*

reply_subject (*subject*)

used to reformat the subject header on reply

Parameters **subject** (*str*) – subject to reformat

Return type *str*

forward_subject (*subject*)

used to reformat the subject header on forward

Parameters **subject** (*str*) – subject to reformat

Return type *str*

pre_buffer_open (*ui= None, dbm=None, buf=buf*)

run before a new buffer is opened

Parameters **buf** (*alot.buffer.Buffer*) – buffer to open

post_buffer_open (*ui=None, dbm=None, buf=buf*)

run after a new buffer is opened

Parameters **buf** (*alot.buffer.Buffer*) – buffer to open

pre_buffer_close (*ui=None, dbm=None, buf=buf*)

run before a buffer is closed

Parameters **buf** (*alot.buffer.Buffer*) – buffer to open

post_buffer_close (*ui=None, dbm=None, buf=buf, success=success*)

run after a buffer is closed

Parameters

- **buf** (*alot.buffer.Buffer*) – buffer to open
- **success** (*boolean*) – true if successfully closed buffer

pre_buffer_focus (*ui=None, dbm=None, buf=buf*)

run before a buffer is focused

Parameters **buf** (*alot.buffer.Buffer*) – buffer to open

post_buffer_focus (*ui=None, dbm=None, buf=buf, success=success*)

run after a buffer is focused

Parameters

- **buf** (*alot.buffer.Buffer*) – buffer to open
- **success** (*boolean*) – true if successfully focused buffer

exit ()

run just before the program exits

sanitize_attachment_filename (*filename=None, prefix='', suffix=''*)

returns *prefix* and *suffix* for a sanitized filename to use while opening an attachment. The *prefix* and *suffix* are used to open a file named *prefix* + *XXXXXX* + *suffix* in a temporary directory.

Parameters

- **filename** (*str or None*) – filename provided in the email (can be None)
- **prefix** (*str*) – prefix string as found on mailcap
- **suffix** (*str*) – suffix string as found on mailcap

Returns tuple of *prefix* and *suffix*

Return type (str, str)

loop_hook (*ui=None*)

Run on a period controlled by *_periodic_hook_frequency*

Parameters **ui** (*alot.ui.UI*) – the main user interface

3.6 Theming

Alot can be run in 1, 16 or 256 colour mode. The requested mode is determined by the command-line parameter *-C* or read from option *colourmode* config value. The default is 256, which scales down depending on how many colours your terminal supports.

Most parts of the user interface can be individually coloured to your liking. To make it easier to switch between or share different such themes, they are defined in separate files (see below for the exact format). To specify the theme to use, set the *theme* config option to the name of a theme-file. A file by that name will be looked up in the path given by the *themes_dir* config setting which defaults to `~/.config/alot/themes/`.

3.6.1 Theme Files

contain a section for each *MODE* plus “help” for the bindings-help overlay and “global” for globally used themables like footer, prompt etc. Each such section defines colour *attributes* for the parts that can be themed. The names of the themables should be self-explanatory. Have a look at the default theme file at `alot/defaults/default.theme` and the config spec `alot/defaults/default.theme` for the exact format.

3.6.2 Colour Attributes

Attributes are *sextuples* of *urwid Attribute strings* that specify foreground and background for mono, 16 and 256-colour modes respectively. For mono-mode only the flags *blink*, *standup*, *underline* and *bold* are available, 16c mode supports these in combination with the colour names:

brown	dark red	dark magenta	dark blue	dark cyan	dark green
yellow	light red	light magenta	light blue	light cyan	light green
black	dark gray	light gray	white		

In high-colour mode, you may use the above plus grayscales *g0* to *g100* and colour codes given as *#* followed by three hex values. See [here](#) and [here](#) for more details on the interpreted values. A colour picker that makes choosing colours easy can be found in `alot/extra/colour_picker.py`.

As an example, check the setting below that makes the footer line appear as underlined bold red text on a bright green background:

```
[[global]]
#name      mono fg      mono bg      16c fg      16c bg      256c fg
#          |          | |          |          |
#          v          v v          v          v
footer = 'bold,underline', '|', 'light red, bold, underline', 'light green', 'light red, bold, under
```

3.6.3 Highlighting Thread lines in Search Mode

The subsection ‘[[threadline]]’ of the ‘[search]’ section in *Theme Files* determines how to present a thread: here, *attributes* ‘normal’ and ‘focus’ provide fallback/spacer themes and ‘parts’ is a (string) list of displayed subwidgets. Possible part strings are:

- date
- mailcount
- tags
- authors
- subject

For every listed part there must be a subsection with the same name, defining

normal *attribute* used for this part if unfocussed

focus *attribute* used for this part if focussed

width tuple indicating the width of the part. This is either (*fit*, *min*, *max*) to force the widget to be at least *min* and at most *max* characters wide, or (*weight*, *n*) which makes it share remaining space with other ‘weight’ parts.

alignment how to place the content string if the widget space is larger. This must be one of ‘right’, ‘left’ or ‘center’.

To “highlight” some thread lines (use different attributes than the defaults found in the ‘[[threadline]]’ section), one can define sections with prefix ‘threadline’. Each one of those can redefine any part of the structure outlined above, the rest defaults to values defined in ‘[[threadline]]’.

The section used to theme a particular thread is the first one (in file-order) that matches the criteria defined by its ‘query’ and ‘tagged_with’ values:

- If ‘query’ is defined, the thread must match that querystring.
- If ‘tagged_with’ is defined, its value (string list) must be a subset of the accumulated tags of all messages in the thread.

Note: that ‘tagged_with = A,B’ is different from ‘query = “is:A AND is:B”’: the latter will match only if the thread contains a single message that is both tagged with A and B.

Moreover, note that if both query and tagged_with is undefined, this section will always match and thus overwrite the defaults.

The example below shows how to highlight unread threads: The date-part will be bold red if the thread has unread messages and flagged messages and just bold if the thread has unread but no flagged messages:

```
[search]
# default threadline
[[threadline]]
normal = 'default','default','default','default','#6d6','default'
focus = 'standout','default','light gray','dark gray','white','#68a'
parts = date,mailcount,tags,authors,subject
[[[date]]]
normal = 'default','default','light gray','default','g58','default'
focus = 'standout','default','light gray','dark gray','g89','#68a'
width = 'fit',10,10
# ...

# highlight threads containing unread and flagged messages
[[threadline-flagged-unread]]
tagged_with = 'unread','flagged'
[[[date]]]
normal = 'default','default','light red,bold','default','light red,bold','default'

# highlight threads containing unread messages
[[threadline-unread]]
query = 'is:unread'
[[[date]]]
normal = 'default','default','light gray,bold','default','g58,bold','default'
```

3.6.4 Custom Tagstring Formatting

One can specify how a particular tagstring is displayed throughout the interface. To use this feature, add a section [tags] to you alot config (not the theme file) and for each tag you want to customize, add a subsection named after the tag. Such a subsection may define

normal *attribute* used if unfocussed

focus *attribute* used if focussed

translated fixed string representation for this tag. The tag can be hidden from view, if the key *translated* is set to `''`, the empty string.

translation a pair of strings that define a regular substitution to compute the string representation on the fly using *re.sub*. This only really makes sense if one uses a regular expression to match more than one tagstring (see below).

The following will make alot display the “todo” tag as “TODO” in white on red.

```
[tags]
[[todo]]
normal = '', '', 'white', 'light red', 'white', '#d66'
translated = TODO
```

Utf-8 symbols are welcome here, see e.g. <http://panmental.de/symbols/info.htm> for some fancy symbols. I personally display my maildir flags like this:

```
[tags]

[[flagged]]
translated =
normal = '', '', 'light red', '', 'light red', ''
focus = '', '', 'light red', '', 'light red', ''

[[unread]]
translated =

[[replied]]
translated =

[[encrypted]]
translated =
```

You may use regular expressions in the tagstring subsections to theme multiple tagstrings at once (first match wins). If you do so, you can use the *translation* option to specify a string substitution that will rename a matching tagstring. *translation* takes a comma separated *pair* of strings that will be fed to *re.sub()*. For instance, to theme all your *nmbug* tagstrings and especially colour tag *notmuch::bug* red, do the following:

```
[[notmuch::bug]]
translated = 'nm:bug'
normal = "", "", "light red, bold", "light blue", "light red, bold", "#88d"

[[notmuch::.*]]
translation = 'notmuch:.(*)', 'nm:\1'
normal = "", "", "white", "light blue", "#fff", "#88d"
```

API and Development

4.1 Overview

The main component is `alot.ui.UI`, which provides methods for user input and notifications, sets up the widget tree and maintains the list of active buffers. When you start up `alot`, `init.py` initializes logging, parses settings and commandline args and instantiates the `UI` instance of that gets passes around later. From its constructor this instance starts the `urwidmainloop` that takes over.

Apart from the central `UI`, there are two other “managers” responsible for core functionalities, also set up in `init.py`:

- `ui.dbman`: a `DBManager` to access the email database and
- `alot.settings.settings`: a `SettingsManager` to access user settings

Every user action, triggered either by key bindings or via the command prompt, is given as commandline string that gets *translated* to a `Command` object which is then *applied*. Different actions are defined as subclasses of `Command`, which live in `alot/commands/MODE.py`, where `MODE` is the name of the mode (`Buffer` type) they are used in.

4.2 Contributing

Development is coordinated entirely via the projects [github page](#) especially the [issue tracker](#).

You can send patches to notmuch’s mailing list but pull requests on github are preferred. Here are a few more things you should know and check before you send pull requests:

- Follow [PEP 8](#). This means in particular a maximum linewidth of 79 and no trailing white spaces. If in doubt, use an Automatic tool ([0], [1], [2]) to verify your code.
- Document! Needless to say, we want readable and well documented code. Moreover,
 - use [sphinx directives](#) to document the parameters and return values of your methods so that we maintain up-to-date API docs.
 - Make sure your patch doesn’t break the API docs. The build service at [readthedocs.org](#) is fragile when it comes to new import statements in our code.
 - If you implemented a new feature, update the user manual in `/docs/user` accordingly.

4.3 Email Database

The python bindings to libnotmuch define `notmuch.Thread` and `notmuch.Message`, which unfortunately are very fragile. Alot defines the wrapper classes `alot.db.Thread` and `alot.db.Message` that use an `manager.DBManager` instance to transparently provide persistent objects.

`alot.db.Message` moreover contains convenience methods to extract information about the message like reformatted header values, a summary, decoded and interpreted body text and a list of `Attachments`.

The central `UI` instance carries around a `DBManager` object that is used for any lookups or modifications of the email base. `DBManager` can directly look up `Thread` and `Message` objects and is able to postpone/cache/retry writing operations in case the Xapian index is locked by another process.

4.3.1 Database Manager

class `alot.db.manager.DBManager` (*path=None, ro=False*)

Keeps track of your index parameters, maintains a write-queue and lets you look up threads and messages directly to the persistent wrapper classes.

Parameters

- **path** (*str*) – absolute path to the notmuch index
- **ro** (*bool*) – open the index in read-only mode

add_message (*path, tags=None, afterwards=None*)

Adds a file to the notmuch index.

Parameters

- **path** (*str*) – path to the file
- **tags** (*list of str*) – tagstrings to add
- **afterwards** (*callable or None*) – callback to trigger after adding

async (*cbl, fun*)

return a pair (pipe, process) so that the process writes `fun(a)` to the pipe for each element `a` in the iterable returned by the callable `cbl`.

Parameters

- **cbl** (*callable*) – a function returning something iterable
- **fun** (*callable*) – an unary translation function

Return type (`multiprocessing.Pipe`, `multiprocessing.Process`)

count_messages (*querystring*)

returns number of messages that match `querystring`

count_threads (*querystring*)

returns number of threads that match `querystring`

flush ()

write out all queued write-commands in order, each one in a separate `atomic` transaction.

If this fails the current action is rolled back, stays in the write queue and an exception is raised. You are responsible to retry flushing at a later time if you want to ensure that the cached changes are applied to the database.

Exception `DatabaseROError` if db is opened read-only

Exception *DatabaseLockedError* if db is locked

get_all_tags ()

returns all tagsstrings used in the database :rtype: list of str

get_message (*mid*)

returns *Message* with given message id (str)

get_thread (*tid*)

returns *Thread* with given thread id (str)

get_threads (*querystring*, *sort*='newest_first')

asynchronously look up thread ids matching *querystring*.

Parameters

- **querystring** (*str*.) – The query string to use for the lookup
- **sort** – Sort order. one of ['oldest_first', 'newest_first', 'message_id', 'unsorted']

Returns a pipe together with the process that asynchronously writes to it.

Return type (*multiprocessing.Pipe*, *multiprocessing.Process*)

kill_search_processes ()

terminate all search processes that originate from this managers *get_threads* () .

query (*querystring*)

creates *notmuch.Query* objects on demand

Parameters **querystring** – The query string to use for the lookup

Returns *notmuch.Query* – the query object.

remove_message (*message*, *afterwards*=None)

Remove a message from the notmuch index

Parameters

- **message** (*Message*) – message to remove
- **afterwards** (*callable* or *None*) – callback to trigger after removing

tag (*querystring*, *tags*, *afterwards*=None, *remove_rest*=False)

add tags to messages matching *querystring*. This appends a tag operation to the write queue and raises *DatabaseROError* if in read only mode.

Parameters

- **querystring** (*str*) – notmuch search string
- **tags** (*list of str*) – a list of tags to be added
- **afterwards** (*callable*) – callback that gets called after successful application of this tagging operation
- **remove_rest** (*bool*) – remove tags from matching messages before tagging

Exception *DatabaseROError*

Note: This only adds the requested operation to the write queue. You need to call *DBManager.flush* () to actually write out.

untag (*querystring*, *tags*, *afterwards=None*)

removes tags from messages that match *querystring*. This appends an untag operation to the write queue and raises *DatabaseROError* if in read only mode.

Parameters

- **querystring** (*str*) – notmuch search string
- **tags** (*list of str*) – a list of tags to be added
- **afterwards** (*callable*) – callback that gets called after successful application of this tagging operation

Exception *DatabaseROError*

Note: This only adds the requested operation to the write queue. You need to call `DBManager.flush()` to actually write out.

4.3.2 Errors

class `alot.db.errors.DatabaseError`

class `alot.db.errors.DatabaseROError`
cannot write to read-only database

class `alot.db.errors.DatabaseLockedError`
cannot write to locked index

class `alot.db.errors.NonexistentObjectError`
requested thread or message does not exist in the index

4.3.3 Wrapper

class `alot.db.Thread` (*dbman*, *thread*)

A wrapper around a notmuch mailthread (`notmuch.database.Thread`) that ensures persistence of the thread: It can be safely read multiple times, its manipulation is done via a `alot.db.DBManager` and it can directly provide contained messages as `Message`.

Parameters

- **dbman** (`DBManager`) – db manager that is used for further lookups
- **thread** (`notmuch.database.Thread`) – the wrapped thread

add_tags (*tags*, *afterwards=None*, *remove_rest=False*)
add *tags* to all messages in this thread

Note: This only adds the requested operation to this objects `DBManager`'s write queue. You need to call `DBManager.flush` to actually write out.

Parameters

- **tags** (*list of str*) – a list of tags to be added
- **afterwards** (*callable*) – callback that gets called after successful application of this tagging operation

- **remove_rest** (*bool*) – remove all other tags

get_authors ()

returns a list of authors (name, addr) of the messages. The authors are ordered by msg date and unique (by name/addr).

Return type list of (str, str)

get_authors_string (*own_addrs=None, replace_own=None*)

returns a string of comma-separated authors Depending on settings, it will substitute “me” for author name if address is user’s own.

Parameters

- **own_addrs** (*list of str*) – list of own email addresses to replace
- **replace_own** (*bool*) – whether or not to actually do replacement

Return type str

get_messages ()

returns all messages in this thread as dict mapping all contained messages to their direct responses.

Return type dict mapping Message to a list of Message.

get_newest_date ()

returns date header of newest message in this thread as *datetime*

get_oldest_date ()

returns date header of oldest message in this thread as *datetime*

get_replies_to (*msg*)

returns all replies to the given message contained in this thread.

Parameters **msg** (Message) – parent message to look up

Returns list of Message or None

get_subject ()

returns subject string

get_tags (*intersection=False*)

returns tagsstrings attached to this thread

Parameters **intersection** (*bool*) – return tags present in all contained messages instead of in at least one (union)

Return type set of str

get_thread_id ()

returns id of this thread

get_toplevel_messages ()

returns all toplevel messages contained in this thread. This are all the messages without a parent message (identified by ‘in-reply-to’ or ‘references’ header.

Return type list of Message

get_total_messages ()

returns number of contained messages

matches (*query*)

Check if this thread matches the given notmuch query.

Parameters **query** (*string*) – The query to check against

Returns True if this thread matches the given query, False otherwise

Return type bool

refresh (*thread=None*)
refresh thread metadata from the index

remove_tags (*tags, afterwards=None*)
remove *tags* (list of str) from all messages in this thread

Note: This only adds the requested operation to this objects `DBManager`'s write queue. You need to call `DBManager.flush` to actually write out.

Parameters

- **tags** (*list of str*) – a list of tags to be added
- **afterwards** (*callable*) – callback that gets called after successful application of this tagging operation

class `alot.db.Message` (*dbman, msg, thread=None*)
a persistent notmuch message object. It it uses a `DBManager` for cached manipulation and lazy lookups.

Parameters

- **dbman** (*alot.db.DBManager*) – db manager that is used for further lookups
- **msg** (*notmuch.database.Message*) – the wrapped message
- **thread** (*Thread or None*) – this messages thread (will be looked up later if *None*)

accumulate_body ()
returns bodystring extracted from this mail

add_tags (*tags, afterwards=None, remove_rest=False*)
adds tags to message

Note: This only adds the requested operation to this objects `DBManager`'s write queue. You need to call `flush()` to write out.

Parameters

- **tags** (*list of str*) – a list of tags to be added
- **afterwards** (*callable*) – callback that gets called after successful application of this tagging operation
- **remove_rest** (*bool*) – remove all other tags

get_attachments ()
returns messages attachments

Derived from the leaves of the email mime tree that and are not part of [RFC 2015](#) syntax for encrypted/signed mails and either have `Content-Disposition attachment` or have `Content-Disposition inline` but specify a filename (as parameter to `Content-Disposition`).

Return type list of Attachment

get_author()
returns realname and address of this messages author

Return type (str,str)

get_date()
returns Date header value as `datetime`

get_datestring()
returns reformated datestring for this message.

It uses `SettingsManager.represent_datetime()` to represent this messages *Date* header

Return type str

get_email()
returns `email.Message` for this message

get_filename()
returns absolute path of message files location

get_headers_string(headers)
returns subset of this messages headers as human-readable format: all header values are decoded, the resulting string has one line “KEY: VALUE” for each requested header present in the mail.

Parameters headers (*list of str*) – headers to extract

get_message_id()
returns messages id (str)

get_message_parts()
yield all body parts of this message

get_replies()
returns replies to this message as list of `Message`

get_tags()
returns tags attached to this message as list of strings

get_thread()
returns the *Thread* this msg belongs to

get_thread_id()
returns id (str) of the thread this message belongs to

has_replies()
returns true if this message has at least one reply

matches(querystring)
tests if this messages is in the resultset for *querystring*

remove_tags(tags, afterwards=None)
remove tags from message

Note: This only adds the requested operation to this objects `DBManager`'s write queue. You need to call `flush()` to actually out.

Parameters

- **tags** (*list of str*) – a list of tags to be added

- **afterwards** (*callable*) – callback that gets called after successful application of this tagging operation

4.3.4 Other Structures

class `alot.db.attachment.Attachment` (*emailpart*)
represents a mail attachment

Parameters **emailpart** (`email.message.Message`) – a non-multipart email that is the attachment

get_content_type ()
mime type of the attachment part

get_data ()
return data blob from wrapped file

get_filename ()
return name of attached file. If the content-disposition header contains no file name, this returns *None*

get_mime_representation ()
returns mime part that constitutes this attachment

get_size ()
returns attachments size in bytes

save (*path*)
save the attachment to disk. Uses `get_filename()` in case path is a directory

write (*fhandle*)
writes content to a given filehandle

class `alot.db.envelope.Envelope` (*template=None, bodytext=None, headers=None, attachments=None, sign=False, sign_key=None, encrypt=False, tags=None*)

a message that is not yet sent and still editable. It holds references to unencoded! body text and mail headers among other things. Envelope implements the python container API for easy access of header values. So `e['To']`, `e['To'] = 'foo@bar.baz'` and `'e.get_all('To')` would work for an envelope *e*..

Parameters

- **template** (*str*) – if not *None*, the envelope will be initialised by parsing this string before setting any other values given to this constructor.
- **bodytext** (*str*) – text used as body part
- **headers** (*dict (str -> [unicode])*) – unencoded header values
- **attachments** (list of *Attachment*) – file attachments to include
- **tags** (list of *str*) – tags to add after successful sendout and saving this msg

add (*key, value*)
add header value

attach (*attachment, filename=None, ctype=None*)
attach a file

Parameters

- **attachment** (*Attachment* or *str*) – File to attach, given as *Attachment* object or path to a file.

- **filename** – filename to use in content-disposition. Will be ignored if *path* matches multiple files
- **ctype** (*str*) – force content-type to be used for this attachment

construct_mail ()

compiles the information contained in this envelope into a `email.Message`.

get (*key*, *fallback=None*)

secure getter for header values that allows specifying a *fallback* return string (defaults to None). This returns the first matching value and doesn't raise KeyErrors

get_all (*key*, *fallback=None*)

returns all header values for given key

parse_template (*tmp*, *reset=False*, *only_body=False*)

parses a template or user edited string to fills this envelope.

Parameters

- **tmp** (*str*) – the string to parse.
- **reset** (*bool*) – remove previous envelope content

attachments = None

list of *Attachments*

body = None

mail body as unicode string

headers = None

dict containing the mail headers (a list of strings for each header key)

tags = []

tags to add after successful sendout

tmpfile = None

template text for initial content

4.3.5 Utilities

`alot.db.utils.add_signature_headers` (*mail*, *sigs*, *error_msg*)

Add pseudo headers to the mail indicating whether the signature verification was successful.

Parameters

- **mail** – `email.message.Message` the message to entitle
- **sigs** – list of `gpgme.Signature`
- **error_msg** – *str* containing an error message, the empty string indicating no error

`alot.db.utils.decode_header` (*header*, *normalize=False*)

decode a header value to a unicode string

values are usually a mixture of different substrings encoded in quoted printable using different encodings. This turns it into a single unicode string

Parameters

- **header** (*str*) – the header value
- **normalize** (*bool*) – replace trailing spaces after newlines

Return type `unicode`

`alot.db.utils.encode_header` (*key*, *value*)
encodes a unicode string as a valid header value

Parameters

- **key** (*str*) – the header field this value will be stored in
- **value** (*unicode*) – the value to be encoded

`alot.db.utils.extract_body` (*mail*, *types=None*, *field_key='copiousoutput'*)
returns a body text string for given mail. If *types* is *None*, *text/** is used: The exact preferred type is specified by the `prefer_plaintext` config option which defaults to `text/html`.

Parameters

- **mail** (*email.Message*) – the mail to use
- **types** (*list of str*) – mime content types to use for body string

`alot.db.utils.extract_headers` (*mail*, *headers=None*)
returns subset of this messages headers as human-readable format: all header values are decoded, the resulting string has one line “KEY: VALUE” for each requested header present in the mail.

Parameters

- **mail** (*email.Message*) – the mail to use
- **headers** (*list of str*) – headers to extract

`alot.db.utils.get_params` (*mail*, *failobj=None*, *header='content-type'*, *unquote=True*)
Get Content-Type parameters as dict.

RFC 2045 specifies that parameter names are case-insensitive, so we normalize them here.

Parameters

- **mail** – `email.message.Message`
- **failobj** – object to return if no such header is found
- **header** – the header to search for parameters, default
- **unquote** – unquote the values

Returns a *dict* containing the parameters

`alot.db.utils.message_from_file` (*handle*)
Reads a mail from the given file-like object and returns an email object, very much like `email.message_from_file`. In addition to that OpenPGP encrypted data is detected and decrypted. If this succeeds, any mime messages found in the recovered plaintext message are added to the returned message object.

Parameters **handle** – a file-like object

Returns `email.message.Message` possibly augmented with decrypted data

`alot.db.utils.message_from_string` (*s*)
Reads a mail from the given string. This is the equivalent of `email.message_from_string()` which does nothing but to wrap the given string in a `StringIO` object and to call `email.message_from_file()`. Please refer to the documentation of `message_from_file()` for details.

4.4 User Interface

Alot sets up a widget tree and a `mainloop` in the constructor of `alot.ui.UI`. The visible area is a `urwid.Frame`, where the footer is used as a status line and the body part displays the currently active `alot.buffer.Buffer`.

To be able to bind keystrokes and translate them to `Commands`, keypresses are *not* propagated down the widget tree as is customary in urwid. Instead, the root widget given to urwid's `mainloop` is a custom wrapper (`alot.ui.Inputwrap`) that interprets key presses. A dedicated `SendKeypressCommand` can be used to trigger key presses to the wrapped root widget and thereby accessing standard urwid behaviour.

In order to keep the interface non-blocking and react to events like terminal size changes, alot makes use of twisted's `deferred` - a framework that makes it easy to deal with callbacks. Many commands in alot make use of `inline callbacks`, which allow you to treat deferred-returning functions almost like synchronous functions. Consider the following example of a function that prompts for some input and acts on it:

```
from twisted.internet import defer

@defer.inlineCallbacks
def greet(ui): # ui is instance of alot.ui.UI
    name = yield ui.prompt('pls enter your name')
    ui.notify('your name is: ' + name)
```

4.4.1 UI - the main component

class `alot.ui.UI` (*dbman*, *initialcmdline*)

This class integrates all components of alot and offers methods for user interaction like `prompt()`, `notify()` etc. It handles the urwid widget tree and `mainloop` (we use twisted) and is responsible for opening, closing and focussing buffers.

Parameters

- **dbman** – DBManager
- **initialcmdline** (*str*) – commandline applied after setting up interface
- **colourmode** (*int in [1, 16, 256]*) – determines which theme to chose

apply_command (*cmd*)

applies a command

This calls the pre and post hooks attached to the command, as well as `cmd.apply()`.

Parameters **cmd** (*Command*) – an applicable command

apply_commandline (*cmdline*)

interprets a command line string

i.e., splits it into separate command strings, instantiates `Commands` accordingly and applies then in sequence.

Parameters **cmdline** (*str*) – command line to interpret

buffer_close (*buf*, *redraw=True*)

closes given `Buffer`.

This it removes it from the bufferlist and calls its `cleanup()` method.

buffer_focus (*buf*, *redraw=True*)

focus given `Buffer`.

buffer_open (*buf*)
register and focus new *Buffer*.

build_statusbar ()
construct and return statusbar widget

choice (*message*, *choices=None*, *select=None*, *cancel=None*, *msg_position='above'*)
prompt user to make a choice.

Parameters

- **message** (*unicode*) – string to display before list of choices
- **choices** (*dict: keymap->choice (both str)*) – dict of possible choices
- **select** (*str*) – choice to return if enter/return is hit. Ignored if set to *None*.
- **cancel** (*str*) – choice to return if escape is hit. Ignored if set to *None*.
- **msg_position** (*str*) – determines if *message* is above or left of the prompt. Must be *above* or *left*.

Return type `twisted.defer.Deferred`

cleanup ()
Do the final clean up before shutting down.

clear_notify (*messages*)
Clears notification popups. Call this to get rid of messages that don't time out.

Parameters **messages** – The popups to remove. This should be exactly what *notify()* returned when creating the popup

static exit ()
shuts down user interface without cleaning up. Use a *alot.commands.globals.ExitCommand* for a clean shutdown.

get_buffers_of_type (*t*)
returns currently open buffers for a given subclass of *Buffer*.

Parameters **t** (*alot.buffers.Buffer*) – Buffer class

Return type *list*

get_deep_focus (*startfrom=None*)
return the bottom most focussed widget of the widget tree

handle_signal (*signum*, *frame*)
handles UNIX signals

This function currently just handles SIGUSR1. It could be extended to handle more

Parameters

- **signum** – The signal number (see man 7 signal)
- **frame** – The execution frame (<https://docs.python.org/2/reference/datamodel.html#frame-objects>)

notify (*message*, *priority='normal'*, *timeout=0*, *block=False*)
opens notification popup.

Parameters

- **message** (*str*) – message to print

- **priority** (*str*) – priority string, used to format the popup: currently, ‘normal’ and ‘error’ are defined. If you use ‘X’ here, the attribute ‘global_notify_X’ is used to format the popup.
- **timeout** (*int*) – seconds until message disappears. Defaults to the value of ‘notify_timeout’ in the general config section. A negative value means never time out.
- **block** (*bool*) – this notification blocks until a keypress is made

Returns an urwid widget (this notification) that can be handed to `clear_notify()` for removal

prompt (*prefix, text=u’, completer=None, tab=0, history=None*)

prompt for text input. This returns a `Deferred` that calls back with the input string.

Parameters

- **prefix** (*str*) – text to print before the input field
- **text** (*str*) – initial content of the input field
- **completer** (*alot.completion.Completer()*) – completion object to use
- **tab** (*int*) – number of tabs to press initially (to select completion results)
- **history** (*list of str*) – history to be used for up/down keys

Return type `twisted.defer.Deferred`

show_as_root_until_keypress (*w, key, afterwards=None*)

Replaces root widget by given `urwid.Widget` and makes the UI ignore all further commands apart from cursor movement. If later on *key* is pressed, the old root widget is reset, callable *afterwards* is called and normal behaviour is resumed.

update (*redraw=True*)

redraw interface

buffers = None

list of active buffers

commandprompthistory = None

history of the command line prompt

current_buffer = None

points to currently active *Buffer*

db_was_locked = None

flag used to prevent multiple ‘index locked’ notifications

dbman = None

Database Manager (*DBManager*)

input_queue = None

stores partial keyboard input

last_commandline = None

saves the last executed commandline

mode = None

interface mode identifier - type of current buffer

recipienthistory = None

history of the recipients prompt

senderhistory = None
history of the sender prompt

4.4.2 Buffers

A buffer defines a view to your data. It knows how to render itself, to interpret keypresses and is visible in the “body” part of the widget frame. Different modes are defined by subclasses of the following base class.

class `alot.buffer.Buffer(ui, widget)`
Abstract base class for buffers.

cleanup()
called before buffer is closed

get_info()
return dict of meta infos about this buffer. This can be requested to be displayed in the statusbar.

rebuild()
tells the buffer to (re)construct its visible content.

Available modes are:

Mode	Buffer Subclass
search	<i>SearchBuffer</i>
thread	<i>ThreadBuffer</i>
bufferlist	<i>BufferlistBuffer</i>
taglist	<i>TagListBuffer</i>
envelope	<i>EnvelopeBuffer</i>

class `alot.buffer.BufferlistBuffer(ui, filterfun=<function <lambda>>)`
lists all active buffers

focus_first()
Focus the first line in the buffer list.

get_selected_buffer()
returns currently selected *Buffer* element from list

index_of(b)
returns the index of *Buffer* *b* in the global list of active buffers.

class `alot.buffer.EnvelopeBuffer(ui, envelope)`
message composition mode

toggle_all_headers()
toggles visibility of all envelope headers

class `alot.buffer.SearchBuffer(ui, initialquery='', sort_order=None)`
shows a result list of threads for a query

get_selected_thread()
returns currently selected *Thread*

get_selected_threadline()
returns currently focussed `alot.widgets.ThreadlineWidget` from the result list.

kill_filler_process()
terminates the process that fills this buffers *PipeWalker*.

class `alot.buffer.ThreadBuffer(ui, thread)`
displays a thread as a tree of messages

Parameters

- **ui** (*UI*) – main UI
- **thread** (*Thread*) – thread to display

collapse (*msgpos*)

collapse message at given position

collapse_all ()

collapse all messages in thread

expand (*msgpos*)

expand message at given position

expand_all ()

expand all messages in thread

focus_first ()

set focus to first message of thread

focus_first_reply ()

move focus to first reply to currently focussed message

focus_last_reply ()

move focus to last reply to currently focussed message

focus_next ()

focus next message in depth first order

focus_next_matching (*querystring*)

focus next matching message in depth first order

focus_next_sibling ()

focus next sibling of currently focussed message in thread tree

focus_next_unfolded ()

focus next unfolded message in depth first order

focus_parent ()

move focus to parent of currently focussed message

focus_prev ()

focus previous message in depth first order

focus_prev_matching (*querystring*)

focus previous matching message in depth first order

focus_prev_sibling ()

focus previous sibling of currently focussed message in thread tree

focus_prev_unfolded ()

focus previous unfolded message in depth first order

focus_property (*prop, direction*)

does a walk in the given direction and focuses the first message tree that matches the given property

focus_selected_message ()

focus the summary line of currently focussed message

get_focus ()

Get the focus from the underlying body widget.

get_messagetree_positions ()

returns a Generator to walk through all positions of MessageTree in the ThreadTree of this buffer.

get_selected_message ()
returns focussed Message

get_selected_message_position ()
returns position of focussed message in the thread tree

get_selected_messagetree ()
returns currently focussed MessageTree

get_selected_mid ()
returns Message ID of focussed message

get_selected_thread ()
returns the displayed *Thread*

messagetree_at_position (*pos*)
get MessageTree for given position

messagetrees ()
returns a Generator of all MessageTree in the ThreadTree of this buffer.

refresh ()
refresh and flush caches of Thread tree

set_focus (*pos*)
Set the focus in the underlying body widget.

unfold_matching (*querystring*, *focus_first=True*)
expand all messages that match a given querystring.

Parameters

- **querystring** (*str*) – query to match
- **focus_first** (*bool*) – set the focus to the first matching message

class `alot.buffer.TagListBuffer` (*ui*, *alltags=None*, *filtfun=<function <lambda>>*)
lists all tagstrings present in the notmuch database

focus_first ()
Focus the first line in the tag list.

get_selected_tag ()
returns selected tagstring

4.4.3 Widgets

What follows is a list of the non-standard urwid widgets used in alot. Some of them respect [user settings](#), themes in particular.

utils

Utility Widgets not specific to alot

class `alot.widgets.utils.AttrFlipWidget` (*w*, *maps*, *init_map='normal'*)
An AttrMap that can remember attributes to set

globals

This contains alot-specific `urwid.Widget` used in more than one mode.

class `alot.widgets.globals.AttachmentWidget` (*attachment, selectable=True*)
 one-line summary of an *Attachment*.

class `alot.widgets.globals.CompleteEdit` (*completer, on_exit, on_error=None, edit_text=u'', history=None, **kwargs*)

This is a vamped-up `urwid.Edit` widget that allows for tab-completion using *Completer* objects

These widgets are meant to be used as user input prompts and hence react to ‘return’ key presses by calling a ‘on_exit’ callback that processes the current text value.

The interpretation of some keypresses is hard-wired:

enter calls ‘on_exit’ callback with current value

esc/ctrl g calls ‘on_exit’ with value *None*, which can be interpreted as cancelation

tab calls the completer and tabs forward in the result list

shift tab tabs backward in the result list

up/down move in the local input history

ctrl f/b moves cursor one character to the right/left

meta f/b shift right/left moves the cursor one word to the right/left

ctrl a/e moves cursor to the beginning/end of the input

ctrl d deletes the character under the cursor

meta d deletes everything from the cursor to the end of the next word

meta delete/backspace ctrl w deletes everything from the cursor to the beginning of the current word

ctrl k deletes everything from the cursor to the end of the input

ctrl u deletes everything from the cursor to the beginning of the input

Parameters

- **completer** (`alot.completion.Completer`) – completer to use
- **on_exit** (*callable*) – “enter”-callback that interprets the input (str)
- **on_error** (*callback*) – callback that handles `alot.errors.CompletionErrors`
- **edit_text** (*str*) – initial text
- **history** (*list or str*) – initial command history

class `alot.widgets.globals.HeadersList` (*headerslist, key_attr, value_attr, gaps_attr=None*)
 renders a pile of header values as key/value list

Parameters

- **headerslist** (*list of (str, str)*) – list of key/value pairs to display
- **key_attr** (`urwid.AttrSpec`) – theming attribute to use for keys
- **value_attr** (`urwid.AttrSpec`) – theming attribute to use for values
- **gaps_attr** (`urwid.AttrSpec`) – theming attribute to wrap lines in

class `alot.widgets.globals.TagWidget` (*tag, fallback_normal=None, fallback_focus=None*)
text widget that renders a tagstring.

It looks up the string it displays in the *tags* section of the config as well as custom theme settings for its tag.

bufferlist

Widgets specific to Bufferlist mode

class `alot.widgets.bufferlist.BufferlineWidget` (*buffer*)
selectable text widget that represents a *Buffer* in the *BufferlistBuffer*.

search

Widgets specific to search mode

class `alot.widgets.search.ThreadlineWidget` (*tid, dbman*)
selectable line widget that represents a *Thread* in the *SearchBuffer*.

thread

Widgets specific to thread mode

class `alot.widgets.thread.DictList` (*content, key_attr, value_attr, gaps_attr=None*)
SimpleTree that displays key-value pairs.

The structure will obey the Tree API but will not actually be a tree but a flat list: It contains one top-level node (displaying the k/v pair in Columns) per pair. That is, the root will be the first pair, its siblings will be the other pairs and *firstlast_child* will always be *None*.

Parameters

- **headerslist** (*list of (str, str)*) – list of key/value pairs to display
- **key_attr** (*urwid.AttrSpec*) – theming attribute to use for keys
- **value_attr** (*urwid.AttrSpec*) – theming attribute to use for values
- **gaps_attr** (*urwid.AttrSpec*) – theming attribute to wrap lines in

class `alot.widgets.thread.FocusableText` (*txt, att, att_focus*)
Selectable Text used for nodes in our example

class `alot.widgets.thread.MessageSummaryWidget` (*message, even=True*)
one line summary of a *Message*.

Parameters

- **message** (*alot.db.Message*) – a message
- **even** (*bool*) – even entry in a pile of messages? Used for theming.

class `alot.widgets.thread.MessageTree` (*message, odd=True*)
Tree that displays contents of a single *alot.db.Message*.

Its root node is a *MessageSummaryWidget*, and its child nodes reflect the messages content (parts for headers/attachments etc).

Collapsing this message corresponds to showing the summary only.

Parameters

- **message** (`alot.db.Message`) – Message to display
- **odd** (`bool`) – theme summary widget as if this is an odd line (in the message-pile)

collapse_if_matches (*querystring*)

collapse (and show summary only) if the `alot.db.Message` matches given *querystring*

class `alot.widgets.thread.ThreadTree` (*thread*)

Tree that parses a given `alot.db.Thread` into a tree of `MessageTrees` that display this threads individual messages. As `MessageTrees` are *not* urwid widgets themselves this is to be used in combination with `NestedTree` only.

4.4.4 Completion

`alot.ui.UI.prompt()` allows tab completion using a `Completer` object handed as ‘completer’ parameter. `alot.completion` defines several subclasses for different occasions like completing email addresses from an `AddressBook`, `notmuch` tagstrings. Some of these actually build on top of each other; the `QueryCompleter` for example uses a `TagsCompleter` internally to allow tagstring completion after “is:” or “tag:” keywords when typing a `notmuch` querystring.

All these classes override the method `complete()`, which for a given string and cursor position in that string returns a list of tuples (`completed_string`, `new_cursor_position`) that are taken to be the completed values. Note that `completed_string` does not need to have the original string as prefix. `complete()` may rise `alot.errors.CompletionError` exceptions.

class `alot.completion.AbooksCompleter` (*abooks*, *addressesonly=False*)
completes a contact from given address books

Parameters

- **abooks** (list of `AddressBook`) – used to look up email addresses
- **addressesonly** (`bool`) – only insert address, not the realname of the contact

class `alot.completion.AccountCompleter` (***kwargs*)
completes users’ own mailaddresses

class `alot.completion.ArgparseOptionCompleter` (*parser*)
completes option parameters for a given `argparse.Parser`

Parameters *parser* (`argparse.ArgumentParser`) – the option parser we look up parameter and choices from

class `alot.completion.CommandCompleter` (*dbman*, *mode*, *currentbuffer=None*)
completes one command consisting of command name and parameters

Parameters

- **dbman** (`DBManager`) – used to look up available tagstrings
- **mode** (`str`) – mode identifier
- **currentbuffer** (`Buffer`) – currently active buffer. If defined, this will be used to dynamically extract possible completion strings

class `alot.completion.CommandLineCompleter` (*dbman*, *mode*, *currentbuffer=None*)
completes command lines: semicolon separated command strings

Parameters

- **dbman** (`DBManager`) – used to look up available tagstrings
- **mode** (`str`) – mode identifier

- **currentbuffer** (*Buffer*) – currently active buffer. If defined, this will be used to dynamically extract possible completion strings

static get_context (*line, pos*)

computes start and end position of substring of line that is the command string under given position

class `alot.completion.CommandNameCompleter` (*mode*)

completes command names

Parameters **mode** (*str*) – mode identifier

class `alot.completion.Completer`

base class for completers

complete (*original, pos*)

returns a list of completions and cursor positions for the string *original* from position *pos* on.

Parameters

- **original** (*str*) – the string to complete
- **pos** (*int*) – starting position to complete from

Returns pairs of completed string and cursor position in the new string

Return type list of (str, int)

Raises `CompletionError`

relevant_part (*original, pos, sep=' '*)

calculates the subword in a *sep*-splitted list of substrings of *original* that *pos* is in.

class `alot.completion.ContactsCompleter` (*abooks, addressesonly=False*)

completes contacts from given address books

Parameters

- **abooks** (list of `AddressBook`) – used to look up email addresses
- **addressesonly** (*bool*) – only insert address, not the realname of the contact

class `alot.completion.CryptoKeyCompleter` (*private=False*)

completion for gpg keys

Parameters **private** (*bool*) – return private keys

class `alot.completion.MultipleSelectionCompleter` (*completer, separator=', '*)

Meta-Completer that turns any Completer into one that deals with a list of completion strings using the wrapped Completer. This allows for example to easily construct a completer for comma separated recipient-lists using a `ContactsCompleter`.

Parameters

- **completer** (`Completer`) – completer to use for individual substrings
- **separator** (*str*) – separator used to split the completion string into substrings to be fed to *completer*.

relevant_part (*original, pos*)

calculates the subword of *original* that *pos* is in

class `alot.completion.PathCompleter`

completion for paths

class `alot.completion.QueryCompleter` (*dbman*)

completion for a notmuch query string

Parameters `dbman` (DBManager) – used to look up available tagstrings

class `alot.completion.StringlistCompleter` (*resultlist*, *ignorecase=True*,
match_anywhere=False)
completer for a fixed list of strings

Parameters

- **resultlist** (*list of str*) – strings used for completion
- **liberal** (*bool*) – match case insensitive and not prefix-only

class `alot.completion.TagCompleter` (*dbman*)
complete a tagstring

Parameters `dbman` (DBManager) – used to look up available tagstrings

class `alot.completion.TagsCompleter` (*dbman*)
completion for a comma separated list of tagstrings

Parameters `dbman` (DBManager) – used to look up available tagstrings

4.5 User Settings

Alot sets up a `SettingsManager` to access user settings defined in different places uniformly. There are four types of user settings:

what?	location	accessible via
alot config	<code>~/.config/alot/config</code> or given by command option <code>-c</code> .	<code>SettingsManager.get()</code>
hooks – user provided python code	<code>~/.config/alot/hooks.py</code> or as given by the <code>hooksfile</code> config value	<code>SettingsManager.get_hook()</code>
notmuch config	<code>~/.notmuchrc</code> or given by command option <code>-n</code>	<code>SettingsManager.get_notmuch_setting()</code>
mailcap – defines shellcommands to handle mime types	<code>~/.mailcap (/etc/mailcap)</code>	<code>SettingsManager.mailcap_find_match()</code>

4.5.1 Settings Manager

class `alot.settings.manager.SettingsManager` (*alot_rc=None*, *notmuch_rc=None*)
Organizes user settings

Parameters

- **alot_rc** (*str*) – path to alot’s config file
- **notmuch_rc** (*str*) – path to notmuch’s config file

get (*key*, *fallback=None*)
look up global config values from alot’s config

Parameters

- **key** (*str*) – key to look up
- **fallback** (*str*) – fallback returned if key is not present

Returns config value with type as specified in the spec-file

get_account_by_address (*address*)

returns `Account` for a given email address (`str`)

Parameters **address** (*string*) – address to look up

Return type `Account` or `None`

get_accounts ()

returns known accounts

Return type list of `Account`

get_addressbooks (*order=None, append_remaining=True*)

returns list of all defined `AddressBook` objects

get_addresses ()

returns addresses of known accounts including all their aliases

get_hook (*key*)

return hook (*callable*) identified by *key*

get_keybinding (*mode, key*)

look up keybinding from *MODE-maps* sections

Parameters

- **mode** (*str*) – mode identifier
- **key** (*str*) – urwid-style key identifier

Returns a command line to be applied upon keypress

Return type `str`

get_keybindings (*mode*)

look up keybindings from *MODE-maps* sections

Parameters **mode** (*str*) – mode identifier

Returns dictionaries of key-cmd for global and specific mode

Return type 2-tuple of dicts

get_main_addresses ()

returns addresses of known accounts without its aliases

get_notmuch_setting (*section, key, fallback=None*)

look up config values from notmuch's config

Parameters

- **section** (*str*) – key is in
- **key** (*str*) – key to look up
- **fallback** (*str*) – fallback returned if key is not present

Returns config value with type as specified in the spec-file

get_tagstring_representation (*tag, onebelow_normal=None, onebelow_focus=None*)

looks up user's preferred way to represent a given tagstring.

Parameters

- **tag** (*str*) – tagstring
- **onebelow_normal** (*urwid.AttrSpec*) – attribute that shines through if unfocused

- **onebelow_focus** (*urwid.AttrSpec*) – attribute that shines through if focussed

If *onebelow_normal* or *onebelow_focus* is given these attributes will be used as fallbacks for fg/bg values ‘’ and ‘default’.

This returns a dictionary mapping

normal to *urwid.AttrSpec* used if unfocussed

focussed to *urwid.AttrSpec* used if focussed

translated to an alternative string representation

get_theming_attribute (*mode, name, part=None*)

looks up theming attribute

Parameters

- **mode** (*str*) – ui-mode (e.g. *search*, ‘thread’...)
- **name** (*str*) – identifier of the attribute

Return type *urwid.AttrSpec*

get_threadline_theming (*thread*)

looks up theming info a threadline displaying a given thread. This wraps around *get_threadline_theming()*, filling in the current colour mode.

Parameters **thread** (*alot.db.thread.Thread*) – thread to theme

mailcap_find_match (**args, **kwargs*)

Propagates *mailcap.find_match()* but caches the mailcap (first argument)

read_config (*path*)

parse alot’s config file from path

read_notmuch_config (*path*)

parse notmuch’s config file from path

represent_datetime (*d*)

turns a given datetime obj into a unicode string representation. This will:

1. look if a fixed ‘timestamp_format’ is given in the config
2. check if a ‘timestamp_format’ hook is defined
3. use *pretty_datetime()* as fallback

set (*key, value*)

setter for global config values

Parameters

- **key** (*str*) – config option identifies
- **value** (depends on the specfile *alot.rc.spec*) – option to set

4.5.2 Errors

exception *alot.settings.errors.ConfigError*

could not parse user config

4.5.3 Utils

`alot.settings.utils.read_config` (*configpath=None, specpath=None, checks=None*)
get a (validated) config object for given config file path.

Parameters

- **configpath** (*str*) – path to config-file
- **specpath** (*str*) – path to spec-file
- **checks** (*dict str->callable,*) – custom checks to use for validator. see [validate docs](#)

Raises *ConfigError*

Return type *configobj.ConfigObj*

`alot.settings.utils.resolve_att` (*a, fallback*)
replace “ and ‘default’ by fallback values

4.5.4 Themes

class `alot.settings.theme.Theme` (*path*)
Colour theme

Parameters **path** (*str*) – path to theme file

Raises *ConfigError*

get_attribute (*colourmode, mode, name, part=None*)
returns requested attribute

Parameters

- **mode** (*str*) – ui-mode (e.g. *search*, ‘thread’...)
- **name** (*str*) – of the attribute
- **colourmode** (*int*) – colour mode; in [1, 16, 256]

Return type *urwid.AttrSpec*

get_threadline_theming (*thread, colourmode*)
look up how to display a Threadline widget in search mode for a given thread.

Parameters

- **thread** (*alot.db.thread.Thread*) – Thread to theme Threadline for
- **colourmode** (*int*) – colourmode to use, one of 1,16,256.

This will return a dict mapping

normal to *urwid.AttrSpec*,

focus to *urwid.AttrSpec*,

parts to a list of strings indentifying subwidgets to be displayed in this order.

Moreover, for every part listed this will map ‘part’ to a dict mapping

normal to *urwid.AttrSpec*,

focus to *urwid.AttrSpec*,

width to a tuple indicating the width of the subpart. This is either (*'fit', min, max*) to force the widget to be at least *min* and at most *max* characters wide, or (*'weight', n*) which makes it share remaining space with other *'weight'* parts.

alignment where to place the content if shorter than the widget. This is either *'right'*, *'left'* or *'center'*.

4.5.5 Accounts

```
class alot.account.Account (address=None, aliases=None, alias_regexp=None, realname=None,
                             gpg_key=None, signature=None, signature_filename=None, sig-
                             nature_as_attachment=False, sent_box=None, sent_tags=None,
                             draft_box=None, draft_tags=None, abook=None, sign_by_default=False,
                             encrypt_by_default=u'none', **_)
```

Datastructure that represents an email account. It manages this account's settings, can send and store mails to maildirs (drafts/send).

Note: This is an abstract class that leaves `send_mail()` unspecified. See `SendmailAccount` for a subclass that uses a sendmail command to send out mails.

get_addresses()

return all email addresses connected to this account, in order of their importance

send_mail(mail)

sends given mail

Parameters mail (`email.message.Message` or string) – the mail to send

Returns a `Deferred` that errs back with a class:`SendingMailFailed`, containing a reason string if an error occurred.

store_draft_mail(mail)

stores mail (`email.message.Message` or str) as draft if `draft_box` is set.

static store_mail(mbx, mail)

stores given mail in mailbox. If mailbox is maildir, set the S-flag and return path to newly added mail. Otherwise this will return `None`.

Parameters

- **mbx** (`mailbox.Mailbox`) – mailbox to use
- **mail** (`email.message.Message` or str) – the mail to store

Returns absolute path of mail-file for Maildir or `None` if mail was successfully stored

Return type str or `None`

Raises `StoreMailError`

store_sent_mail(mail)

stores mail (`email.message.Message` or str) in send-store if `sent_box` is set.

abook = None

addressbook (`addressbook.AddressBook`) managing this accounts contacts

address = None

this accounts main email address

alias_regexp = []
regex matching alternative addresses

aliases = []
list of alternative addresses

gpg_key = None
gpg fingerprint for this account's private key

realname = None
real name used to format from-headers

signature = None
signature to append to outgoing mails

signature_as_attachment = None
attach signature file instead of appending its content to body text

signature_filename = None
filename of signature file in attachment

class `alot.account.SendmailAccount` (*cmd*, ***kwargs*)
Account that pipes a message to a *sendmail* shell command for sending

Parameters *cmd* (*str*) – sendmail command to use for this account

send_mail (*mail*)
Pipe the given mail to the configured sendmail command. Display a short message on success or a notification on error. :param mail: the mail to send out :type mail: str :returns: the deferred that calls the sendmail command :rtype: *twisted.internet.defer.Deferred*

4.5.6 Addressbooks

class `alot.addressbook.AddressBook` (*ignorecase=True*)
can look up email addresses and realnames for contacts.

Note: This is an abstract class that leaves *get_contacts()* unspecified. See *AbookAddressBook* and *ExternalAddressbook* for implementations.

get_contacts ()
list all contacts tuples in this abook as (name, email) tuples

lookup (*query=''*)
looks up all contacts where name or address match query

class `alot.addressbook.abook.AbookAddressBook` (*path='~/abook/addressbook'*, ***kwargs*)
AddressBook that parses abook's config/database files

Parameters *path* (*str*) – path to abook addressbook file

class `alot.addressbook.external.ExternalAddressbook` (*commandline*, *regex*, *reflags=0*, *external_filtering=True*, ***kwargs*)
AddressBook that parses a shell command's output

Parameters

- **commandline** (*str*) – commandline
- **regex** (*str*) – regular expression used to match contacts in *commands* output to stdout. Must define subparts named “email” and “name”.

- **reflags** (*str*) – flags to use with regular expression. Use the constants defined in `re` here (*re.IGNORECASE* etc.)
- **external_filtering** (*bool*) – if True the command is fired with the given search string as parameter and the result is not filtered further. If set to False, the command is fired without additional parameters and the result list is filtered according to the search string.

4.6 Utils

`alot.helper.RFC3156_canonicalize` (*text*)

Canonicalizes plain text (MIME-encoded usually) according to RFC3156.

This function works as follows (in that order):

1. Convert all line endings to `\r\n` (DOS line endings).
2. Ensure the text ends with a newline (`\r\n`).
3. Encode all occurrences of “From ” at the beginning of a line to “From=20” in order to prevent other mail programs to replace this with “> From” (to avoid MBox conflicts) and thus invalidate the signature.

Parameters `text` – text to canonicalize (already encoded as quoted-printable)

Return type `str`

`alot.helper.call_cmd` (*cmdlist*, *stdin=None*)

get a shell commands output, error message and return value and immediately return.

Warning: This returns with the first screen content for interactive commands.

Parameters

- **cmdlist** (*list of str*) – shellcommand to call, already splitted into a list accepted by `subprocess.Popen()`
- **stdin** (*str*) – string to pipe to the process

Returns triple of stdout, stderr, return value of the shell command

Return type `str, str, int`

`alot.helper.call_cmd_async` (*cmdlist*, *stdin=None*, *env=None*)

get a shell commands output, error message and return value as a deferred.

Parameters **stdin** (*str*) – string to pipe to the process

Returns deferred that calls back with triple of stdout, stderr and return value of the shell command

Return type `twisted.internet.defer.Deferred`

`alot.helper.email_as_string` (*mail*)

Converts the given message to a string, without mangling “From” lines (like `as_string()` does).

Parameters **mail** – email to convert to string

Return type `str`

`alot.helper.guess_encoding` (*blob*)

uses file magic to determine the encoding of the given data blob.

Parameters **blob** (*data*) – file content as read by `file.read()`

Returns encoding

Return type `str`

`alot.helper.guess_mimetype(blob)`

uses file magic to determine the mime-type of the given data blob.

Parameters `blob` (*data*) – file content as read by `file.read()`

Returns mime-type, falls back to ‘application/octet-stream’

Return type `str`

`alot.helper.humanize_size(size)`

Create a nice human readable representation of the given number (understood as bytes) using the “KiB” and “MiB” suffixes to indicate kibibytes and mebibytes. A kibibyte is defined as 1024 bytes (as opposed to a kilobyte which is 1000 bytes) and a mebibyte is 1024**2 bytes (as opposed to a megabyte which is 1000**2 bytes).

Parameters `size` (*int*) – the number to convert

Returns the human readable representation of size

Return type `str`

`alot.helper.libmagic_version_at_least(version)`

checks if the libmagic library installed is more recent than a given version.

Parameters `version` – minimum version expected in the form `XYX` (i.e. 5.14 -> 514) with `XYX >= 513`

`alot.helper.mailto_to_envelope(mailto_str)`

Interpret mailto-string into a `alot.db.envelope.Envelope`

`alot.helper.mimewrap(path, filename=None, ctype=None)`

Take the contents of the given path and wrap them into an email MIME part according to the content type. The content type is auto detected from the actual file contents and the file name if it is not given.

Parameters

- **path** (*str*) – the path to the file contents
- **filename** (*str or None*) – the file name to use in the generated MIME part
- **ctype** (*str or None*) – the content type of the file contents in path

Returns the message MIME part storing the data from path

Return type subclasses of `email.mime.base.MIMEBase`

`alot.helper.parse_mailcap_namemplate(template='%s')`

this returns a prefix and suffix to be used in the tempfile module for a given mailcap namemplate string

`alot.helper.parse_mailto(mailto_str)`

Interpret mailto-string

Parameters `mailto_str` (*str*) – the string to interpret. Must conform to :rfc:2368.

Returns the header fields and the body found in the mailto link as a tuple of length two

Return type `tuple(dict(str->list(str)), str)`

`alot.helper.pretty_datetime(d)`

translates `datetime d` to a “sup-style” human readable string.

```

>>> now = datetime.now()
>>> now.strftime('%c')
'Sat 31 Mar 2012 14:47:26 '
>>> pretty_datetime(now)
u'just now'
>>> pretty_datetime(now - timedelta(minutes=1))
u'1min ago'
>>> pretty_datetime(now - timedelta(hours=5))
u'5h ago'
>>> pretty_datetime(now - timedelta(hours=12))
u'02:54am'
>>> pretty_datetime(now - timedelta(days=1))
u'yest 02pm'
>>> pretty_datetime(now - timedelta(days=2))
u'Thu 02pm'
>>> pretty_datetime(now - timedelta(days=7))
u'Mar 24'
>>> pretty_datetime(now - timedelta(days=356))
u'Apr 2011'

```

`alot.helper.shell_quote` (*text*)

Escape the given text for passing it to the shell for interpretation. The resulting string will be parsed into one “word” (in the sense used in the shell documentation, see `sh(1)`) by the shell.

Parameters `text` (*str*) – the text to quote

Returns the quoted text

Return type `str`

`alot.helper.shorten` (*string*, *maxlen*)

shortens string if longer than maxlen, appending ellipsis

`alot.helper.shorten_author_string` (*authors_string*, *maxlength*)

Parse a list of authors concatenated as a text string (comma separated) and smartly adjust them to maxlength.

- 1) If the complete list of sender names does not fit in maxlength, it tries to shorten names by using only the first part of each.
- 2) If the list is still too long, hide authors according to the following priority:
 - First author is always shown (if too long is shorten with ellipsis)
 - If possible, last author is also shown (if too long, uses ellipsis)
 - If there are more than 2 authors in the thread, show the maximum of them. More recent senders have higher priority.
 - If it is finally necessary to hide any author, an ellipsis between first and next authors is added.

`alot.helper.split_commandline` (*s*, *comments=False*, *posix=True*)

splits semi-colon separated commandlines

`alot.helper.split_commandstring` (*cmdstring*)

split command string into a list of strings to pass on to `subprocess.Popen` and the like. This simply calls `shlex.split` but works also with unicode bytestrings.

`alot.helper.string_decode` (*string*, *enc='ascii'*)

safely decodes string to unicode bytestring, respecting *enc* as a hint.

`alot.helper.string_sanitize` (*string*, *tab_width=8*)

strips, and replaces non-printable characters

Parameters `tab_width` (int or *None*) – number of spaces to replace tabs with. Read from *globals.tabwidth* setting if *None*

```
>>> string_sanitize('foo\rbar ', 8)
'foobar '
>>> string_sanitize('foo\tbar', 8)
'foo   bar'
>>> string_sanitize('foo\t\tbar', 8)
'foo           bar'
```

`alot.helper.tag_cmp(a, b)`

Sorting tags using this function puts all tags of length 1 at the beginning. This groups all tags mapped to unicode characters.

4.7 Commands

User actions are represented by *Command* objects that can then be triggered by `alot.ui.UI.apply_command()`. Command-line strings given by the user via the prompt or key bindings can be translated to *Command* objects using `alot.commands.commandfactory()`. Specific actions are defined as subclasses of *Command* and can be registered to a global command pool using the `registerCommand` decorator.

Note: that the return value of `commandfactory()` depends on the current *mode* the user interface is in. The mode identifier is a string that is uniquely defined by the currently focuses *Buffer*.

Note: The names of the commands available to the user in any given mode do not correspond one-to-one to these subclasses. You can register a *Command* multiple times under different names, with different forced constructor parameters and so on. See for instance the definition of *BufferFocusCommand* in ‘`commands/globals.py`’:

```
@registerCommand(MODE, 'bprevious', forced={'offset': -1},
                 help='focus previous buffer')
@registerCommand(MODE, 'bnext', forced={'offset': +1},
                 help='focus next buffer')
class BufferFocusCommand(Command):
    def __init__(self, buffer=None, offset=0, **kwargs):
    ...
```

class `alot.commands.Command`
base class for commands

apply (*caller*)
code that gets executed when this command is applied

class `alot.commands.CommandParseError`
could not parse commandline string

class `alot.commands.CommandArgumentParser` (**args, **kwargs*)
ArgumentParser that raises *CommandParseError* instead of printing to *sys.stderr*

`alot.commands.commandfactory(cmdline, mode='global')`
parses *cmdline* and constructs a *Command*.

Parameters

- **cmdline** (*str*) – command line to interpret

- **mode** (*str*) – mode identifier

`alot.commands.lookup_command(cmdname, mode)`

returns commandclass, argparser and forced parameters used to construct a command for *cmdname* when called in *mode*.

Parameters

- **cmdname** (*str*) – name of the command to look up
- **mode** (*str*) – mode identifier

Return type (*Command*, *ArgumentParser*, *dict(str->dict)*)

`alot.commands.lookup_parser(cmdname, mode)`

returns the *CommandArgumentParser* used to construct a command for *cmdname* when called in *mode*.

class `alot.commands.registerCommand(mode, name, help=None, usage=None, forced=None, arguments=None)`

Decorator used to register a *Command* as handler for command *name* in *mode* so that it can be looked up later using *lookup_command()*.

Consider this example that shows how a *Command* class definition is decorated to register it as handler for ‘save’ in mode ‘thread’ and add boolean and string arguments:

```
@registerCommand('thread', 'save', arguments=[
    (['--all'], {'action': 'store_true', 'help': 'save all'}),
    (['path'], {'nargs': '?', 'help': 'path to save to'})],
    help='save attachment(s)')
class SaveAttachmentCommand(Command):
    pass
```

Parameters

- **mode** (*str*) – mode identifier
- **name** (*str*) – command name to register as
- **help** (*str*) – help string summarizing what this command does
- **usage** (*str*) – overrides the auto generated usage string
- **forced** (*dict (str->str)*) – keyword parameter used for commands constructor
- **arguments** (*list of (list of str, dict (str->str))*) – list of arguments given as pairs (args, kwargs) accepted by `argparse.ArgumentParser.add_argument()`.

4.7.1 Globals

class `alot.commands.globals.BufferCloseCommand(buffer=None, force=False, redraw=True, **kwargs)`

close a buffer

Parameters

- **buffer** (*alot.buffers.Buffer*) – the buffer to close or None for current
- **force** (*bool*) – force buffer close

class `alot.commands.globals.BufferFocusCommand(buffer=None, index=None, offset=0, **kwargs)`

focus a *Buffer*

Parameters

- **buffer** (*alot.buffers.Buffer*) – the buffer to focus or None
- **index** (*int*) – index (in bufferlist) of the buffer to focus.
- **offset** (*int*) – position of the buffer to focus relative to the currently focussed one. This is used only if *buffer* is set to *None*

class `alot.commands.globals.CallCommand` (*command*, ***kwargs*)
Executes python code

Parameters **command** (*str*) – python command string to call

class `alot.commands.globals.ComposeCommand` (*envelope=None*, *headers=None*, *template=None*, *sender=u'*, *subject=u'*, *to=None*, *cc=None*, *bcc=None*, *attach=None*, *omit_signature=False*, *spawn=None*, *rest=None*, *encrypt=False*, ***kwargs*)

compose a new email

Parameters

- **envelope** (*Envelope*) – use existing envelope
- **headers** (*dict (str->str)*) – forced header values
- **template** (*str*) – name of template to parse into the envelope after creation. This should be the name of a file in your `template_dir`
- **sender** (*str*) – From-header value
- **subject** (*str*) – Subject-header value
- **to** (*str*) – To-header value
- **cc** (*str*) – Cc-header value
- **bcc** (*str*) – Bcc-header value
- **attach** (*str*) – Path to files to be attached (globable)
- **omit_signature** (*bool*) – do not attach/append signature
- **spawn** (*bool*) – force spawning of editor in a new terminal
- **rest** (*list (str)*) – remaining parameters. These can start with ‘mailto’ in which case it is interpreted as mailto string. Otherwise it will be interpreted as recipients (to) header
- **encrypt** (*bool*) – if the email should be encrypted

class `alot.commands.globals.EditCommand` (*path*, *spawn=None*, *thread=None*, ***kwargs*)
edit a file

Parameters

- **path** (*str*) – path to the file to be edited
- **spawn** (*bool*) – force running editor in a new terminal
- **thread** (*bool*) – run asynchronously, don’t block alot

class `alot.commands.globals.ExitCommand` (*_prompt=True*, ***kwargs*)
Shut down cleanly.

The `_prompt` variable is for internal use only, it’s used to control prompting to close without sending, and is used by the `BufferCloseCommand` if settings change after yielding to the UI.

class `alot.commands.globals.ExternalCommand` (*cmd*, *stdin=None*, *shell=False*, *spawn=False*, *refocus=True*, *thread=False*, *on_success=None*, ***kwargs*)

run external command

Parameters

- **cmd** (*list* or *str*) – the command to call
- **stdin** (*file* or *str*) – input to pipe to the process
- **spawn** (*bool*) – run command in a new terminal
- **shell** (*bool*) – let shell interpret command string
- **thread** (*bool*) – run asynchronously, don't block alot
- **refocus** (*bool*) – refocus calling buffer after cmd termination
- **on_success** (*callable*) – code to execute after command successfully exited

class `alot.commands.globals.FlushCommand` (*callback=None*, *silent=False*, ***kwargs*)
flush write operations or retry until committed

Parameters **callback** (*callable*) – function to call after successful writeout

class `alot.commands.globals.HelpCommand` (*commandname=''*, ***kwargs*)
display help for a command. Use 'bindings' to display all keybindings interpreted in current mode.'

Parameters **commandname** (*str*) – command to document

class `alot.commands.globals.MoveCommand` (*movement=None*, ***kwargs*)
move in widget

class `alot.commands.globals.OpenBufferlistCommand` (*filtfun=<function <lambda>>*, ***kwargs*)

open a list of active buffers

Parameters **filtfun** (*callable (str->bool)*) – filter to apply to displayed list

class `alot.commands.globals.PromptCommand` (*startswith=''*, ***kwargs*)
prompts for commandline and interprets it upon select

Parameters **startswith** (*str*) – initial content of the prompt widget

class `alot.commands.globals.PythonShellCommand`
open an interactive python shell for introspection

class `alot.commands.globals.RefreshCommand`
refresh the current buffer

class `alot.commands.globals.RepeatCommand` (***kwargs*)
Repeats the command executed last time

class `alot.commands.globals.SearchCommand` (*query*, *sort=None*, ***kwargs*)
open a new search buffer

Parameters

- **query** (*str*) – notmuch querystring
- **sort** (*str*) – how to order results. Must be one of 'oldest_first', 'newest_first', 'message_id' or 'unsorted'.

class `alot.commands.globals.TagListCommand` (*filtfun=<function <lambda>>*, *tags=None*, ***kwargs*)

opens taglist buffer

Parameters `filtfun` (*callable (str->bool)*) – filter to apply to displayed list

4.7.2 Envelope

class `alot.commands.envelope.AttachCommand` (*path=None, **kwargs*)
attach files to the mail

Parameters `path` (*str*) – files to attach (globable string)

class `alot.commands.envelope.EditCommand` (*envelope=None, spawn=None, refocus=True, **kwargs*)
edit mail

Parameters

- **envelope** (*Envelope*) – email to edit
- **spawn** (*bool*) – force spawning of editor in a new terminal
- **refocus** – m

class `alot.commands.envelope.RefineCommand` (*key='', **kwargs*)
prompt to change the value of a header

Parameters `key` (*str*) – key of the header to change

class `alot.commands.envelope.SaveCommand`
save draft

class `alot.commands.envelope.SendCommand` (*mail=None, envelope=None, **kwargs*)
send mail

Parameters

- **mail** – email to send
- **envelope** (*alot.db.envelope.envelope*) – envelope to use to construct the outgoing mail. This will be ignored in case the mail parameter is set.

class `alot.commands.envelope.SetCommand` (*key, value, append=False, **kwargs*)
set header value

Parameters

- **key** (*str*) – key of the header to change
- **value** (*str*) – new value

class `alot.commands.envelope.SignCommand` (*action=None, keyid=None, **kwargs*)
toggle signing this email

Parameters

- **action** (*str*) – whether to sign/unsig/toggle
- **keyid** (*str*) – which key id to use

class `alot.commands.envelope.ToggleHeaderCommand`
toggle display of all headers

class `alot.commands.envelope.UnattachCommand` (*hint=None, **kwargs*)
remove attachments from current envelope

Parameters `hint` (*str*) – which attached file to remove

class `alot.commands.envelope.UnsetCommand` (*key*, ***kwargs*)
remove header field

Parameters **key** (*str*) – key of the header to remove

4.7.3 Bufferlist

class `alot.commands.bufferlist.BufferCloseCommand`
close focussed buffer

class `alot.commands.bufferlist.BufferFocusCommand`
focus selected buffer

4.7.4 Search

class `alot.commands.search.OpenThreadCommand` (*thread=None*, ***kwargs*)
open thread in a new buffer

Parameters **thread** (*Thread*) – thread to open (Uses focussed thread if unset)

class `alot.commands.search.RefineCommand` (*query=None*, *sort=None*, ***kwargs*)
refine the querystring of this buffer

Parameters **query** (*list of str*) – new querystring given as list of strings as returned by `argparse`

class `alot.commands.search.RefinePromptCommand`
prompt to change this buffers querystring

class `alot.commands.search.RetagPromptCommand`
prompt to retag selected threads' tags

class `alot.commands.search.TagCommand` (*tags=u''*, *action='add'*, *allmessages=False*, *flush=True*, ***kwargs*)
manipulate message tags

Parameters

- **tags** (*str*) – comma separated list of tagstrings to set
- **action** (*str*) – adds tags if 'add', removes them if 'remove', adds tags and removes all other if 'set' or toggle individually if 'toggle'
- **all** (*bool*) – tag all messages in search result
- **flush** (*bool*) – imediately write out to the index

4.7.5 Taglist

class `alot.commands.taglist.TaglistSelectCommand`
search for messages with selected tag

4.7.6 Thread

class `alot.commands.thread.BounceMailCommand` (*message=None*, ***kwargs*)
directly re-send selected message

Parameters **message** (*alot.db.message.Message*) – message to bounce (defaults to selected message)

```
class alot.commands.thread.ChangeDisplaymodeCommand (query=None,          visible=None,
                                                    raw=None,          all_headers=None,
                                                    **kwargs)
```

fold or unfold messages

Parameters

- **query** (*str*) – notmuch query string used to filter messages to affect
- **visible** (*True, False, 'toggle' or None*) – unfold if *True*, fold if *False*, ignore if *None*
- **raw** (*True, False, 'toggle' or None*) – display raw message text.
- **all_headers** (*True, False, 'toggle' or None*) – show all headers (only visible if not in raw mode)

```
class alot.commands.thread.EditNewCommand (message=None, spawn=None, **kwargs)
edit message in as new
```

Parameters

- **message** (*alot.db.message.Message*) – message to reply to (defaults to selected message)
- **spawn** (*bool*) – force spawning of editor in a new terminal

```
class alot.commands.thread.ForwardCommand (message=None, attach=True, spawn=None,
                                           **kwargs)
```

forward message

Parameters

- **message** (*alot.db.message.Message*) – message to forward (defaults to selected message)
- **attach** (*bool*) – attach original mail instead of inline quoting its body
- **spawn** (*bool*) – force spawning of editor in a new terminal

```
class alot.commands.thread.OpenAttachmentCommand (attachment, **kwargs)
displays an attachment according to mailcap
```

Parameters **attachment** (*Attachment*) – attachment to open

```
class alot.commands.thread.PipeCommand (cmd, all=False, separately=False, background=False,
                                       shell=False, notify_stdout=False, format='raw',
                                       add_tags=False, noop_msg='no command
                                       specified', confirm_msg='', done_msg=None,
                                       field_key='copiousoutput', **kwargs)
```

pipe message(s) to stdin of a shellcommand

Parameters

- **cmd** (*str or list of str*) – shellcommand to open
- **all** (*bool*) – pipe all, not only selected message
- **separately** (*bool*) – call command once per message
- **background** (*bool*) – do not suspend the interface
- **notify_stdout** (*bool*) – display command's stdout as notification message
- **shell** – let the shell interpret the command

- **add_tags** (*bool*) – add ‘Tags’ header to the message
- **noop_msg** (*str*) – error notification to show if *cmd* is empty
- **confirm_msg** (*str*) – confirmation question to ask (continues directly if unset)
- **done_msg** (*str*) – notification message to show upon success
- **field_key** (*str*) – malcap field key for decoding

```
class alot.commands.thread.PrintCommand (all=False,      separately=False,      raw=False,
                                         add_tags=False, **kwargs)
    print message(s)
```

Parameters

- **all** (*bool*) – print all, not only selected messages
- **separately** (*bool*) – call print command once per message
- **raw** (*bool*) – pipe raw message string to print command
- **add_tags** (*bool*) – add ‘Tags’ header to the message

```
class alot.commands.thread.RemoveCommand (all=False, **kwargs)
    remove message(s) from the index
```

Parameters **all** (*bool*) – remove all messages from thread, not just selected one

```
class alot.commands.thread.ReplyCommand (message=None,    all=False,    listreply=None,
                                         spawn=None, **kwargs)
    reply to message
```

Parameters

- **message** (*alot.db.message.Message*) – message to reply to (defaults to selected message)
- **all** (*bool*) – group reply; copies recipients from Bcc/Cc/To to the reply
- **listreply** (*bool*) – reply to list; autodetect if unset and enabled in config
- **spawn** (*bool*) – force spawning of editor in a new terminal

```
static clear_my_address (my_addresses, value)
    return recipient header without the addresses in my_addresses
```

Parameters

- **my_addresses** (*list (str)*) – a list of my email addresses (no real name part)
- **value** (*list (str)*) – a list of recipient or sender strings (with or without real names as taken from email headers)

Returns a new, potentially shortened list

Return type list(str)

```
static ensure_unique_address (recipients)
    clean up a list of name,address pairs so that no address appears multiple times.
```

```
class alot.commands.thread.SaveAttachmentCommand (all=False, path=None, **kwargs)
    save attachment(s)
```

Parameters

- **all** (*bool*) – save all, not only selected attachment
- **path** (*str*) – path to write to. if *all* is set, this must be a directory.

`class` `alot.commands.thread.TagCommand` (`tags=u''`, `action='add'`, `all=False`, `flush=True`,
`**kwargs`)

manipulate message tags

Parameters

- **tags** (*str*) – comma separated list of tagstrings to set
- **action** (*str*) – adds tags if ‘add’, removes them if ‘remove’, adds tags and removes all other if ‘set’ or toggle individually if ‘toggle’
- **all** (*bool*) – tag all messages in thread
- **flush** (*bool*) – immediately write out to the index

`class` `alot.commands.thread.ThreadSelectCommand`

select focussed element. The fired action depends on the focus: - if message summary, this toggles visibility of the message, - if attachment line, this opens the attachment

`alot.commands.thread.determine_sender` (*mail*, `action='reply'`)

Inspect a given mail to reply/forward/bounce and find the most appropriate account to act from and construct a suitable From-Header to use.

Parameters

- **mail** (*email.message.Message*) – the email to inspect
- **action** (*str*) – intended use case: one of “reply”, “forward” or “bounce”

4.8 Crypto

`alot.crypto.RFC3156_micalg_from_algo` (*hash_algo*)

Converts a GPGME hash algorithm name to one conforming to RFC3156.

GPGME returns hash algorithm names such as “SHA256”, but RFC3156 says that programs need to use names such as “pgp-sha256” instead.

Parameters `hash_algo` – GPGME `hash_algo`

Return type `str`

`alot.crypto.check_uid_validity` (*key*, *email*)

Check that a the email belongs to the given key. Also check the trust level of this connection. Only if the trust level is high enough (≥ 4) the email is assumed to belong to the key.

Parameters

- **key** (*gpgme.Key*) – the GPG key to which the email should belong
- **email** (*str*) – the email address that should belong to the key

Returns whether the key can be assumed to belong to the given email

Return type `bool`

`alot.crypto.decrypt_verify` (*encrypted*)

Decrypts the given ciphertext string and returns both the signatures (if any) and the plaintext.

Parameters `encrypted` – the mail to decrypt

Returns a tuple (sigs, plaintext) with sigs being a list of a `gpgme.Signature` and plaintext is a `str` holding the decrypted mail

Raises `GPGProblem` if the decryption fails

`alot.crypto.detached_signature_for` (*plaintext_str*, *key=None*)
Signs the given plaintext string and returns the detached signature.

A detached signature in GPG speak is a separate blob of data containing a signature for the specified plaintext.

Parameters

- **plaintext_str** – text to sign
- **key** – `gpgme_key_t` object representing the key to use

Return type tuple of `gpgme.NewSignature` array and `str`

`alot.crypto.encrypt` (*plaintext_str*, *keys=None*)
Encrypts the given plaintext string and returns a PGP/MIME compatible string

Parameters

- **plaintext_str** – the mail to encrypt
- **key** – `gpgme_key_t` object representing the key to use

Return type a string holding the encrypted mail

`alot.crypto.get_key` (*keyid*, *validate=False*, *encrypt=False*, *sign=False*, *signed_only=False*)
Gets a key from the keyring by filtering for the specified keyid, but only if the given keyid is specific enough (if it matches multiple keys, an exception will be thrown).

If `validate` is `True` also make sure that returned key is not invalid, revoked or expired. In addition if `encrypt` or `sign` is `True` also validate that key is valid for that action. For example only keys with private key can sign. If `signed_only` is `True` make sure that the user id can be trusted to belong to the key (is signed). This last check will only work if the keyid is part of the user id associated with the key, not if it is part of the key fingerprint.

Parameters

- **keyid** (*str*) – filter term for the keyring (usually a key ID)
- **validate** (*bool*) – validate that returned keyid is valid
- **encrypt** (*bool*) – when validating confirm that returned key can encrypt
- **sign** (*bool*) – when validating confirm that returned key can sign
- **signed_only** (*bool*) – only return keys whose uid is signed (trusted to belong to the key)

Return type `gpgme.Key`

`alot.crypto.hash_key` (*key*)
Returns a hash of the given key. This is a workaround for <https://bugs.launchpad.net/pygpgme/+bug/1089865> and can be removed if the missing feature is added to `pygpgme`.

Parameters **key** (*gpgme.Key*) – the key we want a hash of

Returns a hash of the key

Return type `str`

`alot.crypto.list_keys` (*hint=None*, *private=False*)
Returns a list of all keys containing keyid.

Parameters

- **keyid** – The part we search for
- **private** – Whether secret keys are listed

Return type `list`

`alot.crypto.validate_key` (*key*, *sign=False*, *encrypt=False*)

Assert that a key is valid and optionally that it can be used for signing or encrypting. Raise `GPGProblem` otherwise.

Parameters

- **key** (*gpgme.Key*) – the GPG key to check
- **sign** (*bool*) – whether the key should be able to sign
- **encrypt** (*bool*) – whether the key should be able to encrypt

`alot.crypto.verify_detached` (*message*, *signature*)

Verifies whether the message is authentic by checking the signature.

Parameters

- **message** – the message as *str*
- **signature** – a *str* containing an OpenPGP signature

Returns a list of `gpgme.Signature`

Raises `GPGProblem` if the verification fails

1. Why reinvent the wheel? Why not extend an existing MUA to work nicely with notmuch?

alot makes use of existing solutions where possible: It does not fetch, send or edit mails; it lets `notmuch` handle your mailindex and uses a `toolkit` to render its display. You are responsible for `automatic initial tagging`.

This said, there are few CLI MUAs that could be easily and naturally adapted to using notmuch. Rebuilding an interface from scratch using `friendly and extensible tools` seemed easier and more promising.

Update: see `mutt-kz` for a fork of mutt..

2. What's with the snotty name?

It's not meant to be presumptuous. I like the dichotomy; I like to picture the look on someone's face who reads the `User-Agent` header "notmuch/alot"; I like cookies; I like [this comic strip](#).

3. I want feature X!

Me too! Feel free to file a new or comment on existing `issues` if you don't want/have the time/know how to implement it yourself. Be verbose as to how it should look or work when it's finished and give it some thought how you think we should implement it. We'll discuss it from there.

4. Why are the default key bindings so counter-intuitive?

Be aware that the bindings for all modes are `fully configurable`. That said, I choose the bindings to be natural for me. I use `vim` and `pentadactyl` a lot. However, I'd be interested in discussing the defaults. If you think your bindings are more intuitive or better suited as defaults for some reason, don't hesitate to send me your config. The same holds for the theme settings you use. Tell me. Let's improve the defaults.

5. Help! I don't see `text/html` content!

better: How do I properly set up an inline renderer for `text/html`? Try `w3m` and put the following into your `~/.mailcap`:

```
text/html; w3m -dump -o document_charset=%{charset} '%s'; nametemplate=%s.html; copiousoutp
```

Most `text based browsers` have a dump mode that can be used here.

6. Why are you doing \$THIS not \$THAT way?

Lazyness and Ignorance: In most cases I simply did not or still don't know a better solution. I try to outsource as much as I can to well established libraries and be it only to avoid having to read rfc's. But there are lots of tasks I implemented myself, possibly overlooking a ready made and available

solution. Twisted is such a feature-rich but gray area in my mind for example. If you think you know how to improve the current implementation let me know!

The few exceptions to above stated rule are the following:

- CLI option parsing is done using *twisted.usage.Options*, and not (as e.g. in-app command parsing) via *argparse*. The reason is that *argparse* does not yet offer optional subcommands.
- The modules *cmd* and *cmd2*, that handle all sorts of convenience around command objects hate *urwid*: They are painfully strongly coupled to user in/output via *stdin* and *out*.
- *notmuch reply* is not used to format reply messages because 1. it is not offered by *notmuch*'s library but is a feature of the CLI. This means we would have to call the *notmuch* binary, something that is avoided where possible. 2. As there is no *notmuch forward* equivalent, this (very similar) functionality would have to be re-implemented anyway.

7. Why doesn't alot run on python3?

Because it builds on libraries that don't (yet):

- `configobj`
- `twisted`

Alot itself can be converted to py3k syntax automatically using `2to3` and I will push those changes as soon as the libs are ready.

6.1 Synopsis

```
alot [-r] [-c CONFIGFILE] [-n NOTMUCHCONFIGFILE] [-C {1,16,256}] [-p DB_PATH]
      [-d {debug,info,warning,error}] [-l LOGFILE] [-v] [-h] [command]
```

Options

- r, --read-only** open db in read only mode
- c, --config=FILENAME** config file (default: ~/.config/alot/config)
- n, --notmuch-config=FILENAME** notmuch config (default: \$NOTMUCH_CONFIG or ~/.notmuch-config)
- C, --colour-mode=COLOUR** terminal colour mode (default: 256). Must be 1, 16 or 256
- p, --mailindex-path=PATH** path to notmuch index
- d, --debug-level=LEVEL** debug log (default: info). Must be one of debug,info,warning or error
- l, --logfile=FILENAME** logfile (default: /dev/null)
- v, --version** Display version string and exit
- h, --help** Display help and exit

UNIX Signals

SIGUSR1 Refreshes the current buffer. Useful for telling alot to refresh the view from a mail downloader e.g. Offlineimap.

Subcommands

search start in a search buffer using the querystring provided as parameter. See also the SEARCH SYNTAX section of notmuch(1) and the output of *alot search -help*.

compose compose a new message See the output of *alot compose -help* for more info on parameters.

pyshell start the interactive python shell inside alot See the output of *alot pyshell -help* for more info on parameters.

6.2 Description

Alot is a terminal-based mail user agent for the notmuch mail system. It features a modular and command prompt driven interface to provide a full MUA experience as an alternative to the Emacs mode shipped with notmuch.

6.3 Usage

The arrow keys, *page-up/down*, *j*, *k* and *Space* can be used to move the focus. *Escape* cancels prompts and *Enter* selects. Hit *:* at any time and type in commands to the prompt.

The interface shows one buffer at a time, you can use *Tab* and *Shift-Tab* to switch between them, close the current buffer with *d* and list them all with *;*.

The buffer type or *mode* (displayed at the bottom left) determines which prompt commands are available. Usage information on any command can be listed by typing *help YOURCOMMAND* to the prompt; The key bindings for the current mode are listed upon pressing *?*.

6.4 See Also

notmuch (1)

Alot is a terminal-based mail user agent for the notmuch mail system. It features a modular and command prompt driven interface to provide a full MUA experience as an alternative to the Emacs mode shipped with notmuch.

a

- alot, 39
- alot.account, 63
- alot.addressbook, 64
- alot.addressbook.abook, 64
- alot.addressbook.external, 64
- alot.buffers, 52
- alot.commands, 68
- alot.commands.bufferlist, 73
- alot.commands.envelope, 72
- alot.commands.globals, 69
- alot.commands.search, 73
- alot.commands.taglist, 73
- alot.commands.thread, 73
- alot.completion, 57
- alot.crypto, 76
- alot.db, 40
- alot.db.errors, 42
- alot.db.utils, 47
- alot.helper, 65
- alot.settings.errors, 61
- alot.settings.manager, 59
- alot.settings.utils, 62
- alot.ui, 49
- alot.utils, 68
- alot.widgets.bufferlist, 56
- alot.widgets.globals, 55
- alot.widgets.search, 56
- alot.widgets.thread, 56
- alot.widgets.utils, 54

A

abook (alot.account.Account attribute), 63
 AbookAddressBook (class in alot.addressbook.abook), 64
 AbooksCompleter (class in alot.completion), 57
 Account (class in alot.account), 63
 AccountCompleter (class in alot.completion), 57
 accumulate_body() (alot.db.Message method), 44
 add() (alot.db.envelope.Envelope method), 46
 add_message() (alot.db.manager.DBManager method), 40
 add_signature_headers() (in module alot.db.utils), 47
 add_tags() (alot.db.Message method), 44
 add_tags() (alot.db.Thread method), 42
 address (alot.account.Account attribute), 63
 AddressBook (class in alot.addressbook), 64
 alias_regexp (alot.account.Account attribute), 63
 aliases (alot.account.Account attribute), 64
 alot (module), 39
 alot.account (module), 63
 alot.addressbook (module), 64
 alot.addressbook.abook (module), 64
 alot.addressbook.external (module), 64
 alot.buffer (module), 52
 alot.commands (module), 68
 alot.commands.bufferlist (module), 73
 alot.commands.envelope (module), 72
 alot.commands.globals (module), 69
 alot.commands.search (module), 73
 alot.commands.taglist (module), 73
 alot.commands.thread (module), 73
 alot.completion (module), 57
 alot.crypto (module), 76
 alot.db (module), 40
 alot.db.errors (module), 42
 alot.db.utils (module), 47
 alot.helper (module), 65
 alot.settings.errors (module), 61
 alot.settings.manager (module), 59
 alot.settings.utils (module), 62

alot.ui (module), 49
 alot.utils (module), 68
 alot.widgets.bufferlist (module), 56
 alot.widgets.globals (module), 55
 alot.widgets.search (module), 56
 alot.widgets.thread (module), 56
 alot.widgets.utils (module), 54
 apply() (alot.commands.Command method), 68
 apply_command() (alot.ui.UI method), 49
 apply_commandline() (alot.ui.UI method), 49
 ArgparseOptionCompleter (class in alot.completion), 57
 async() (alot.db.manager.DBManager method), 40
 attach() (alot.db.envelope.Envelope method), 46
 AttachCommand (class in alot.commands.envelope), 72
 Attachment (class in alot.db.attachment), 46
 attachments (alot.db.envelope.Envelope attribute), 47
 AttachmentWidget (class in alot.widgets.globals), 55
 AttrFlipWidget (class in alot.widgets.utils), 54

B

body (alot.db.envelope.Envelope attribute), 47
 BounceMailCommand (class in alot.commands.thread), 73
 Buffer (class in alot.buffer), 52
 buffer_close() (alot.ui.UI method), 49
 buffer_focus() (alot.ui.UI method), 49
 buffer_open() (alot.ui.UI method), 49
 BufferCloseCommand (class in alot.commands.bufferlist), 73
 BufferCloseCommand (class in alot.commands.globals), 69
 BufferFocusCommand (class in alot.commands.bufferlist), 73
 BufferFocusCommand (class in alot.commands.globals), 69
 BufferlineWidget (class in alot.widgets.bufferlist), 56
 BufferlistBuffer (class in alot.buffer), 52
 buffers (alot.ui.UI attribute), 51
 build_statusbar() (alot.ui.UI method), 50

C

call_cmd() (in module alot.helper), 65
 call_cmd_async() (in module alot.helper), 65
 CallCommand (class in alot.commands.globals), 70
 ChangeDisplaymodeCommand (class in alot.commands.thread), 74
 check_uid_validity() (in module alot.crypto), 76
 choice() (alot.ui.UI method), 50
 cleanup() (alot.buffers.Buffer method), 52
 cleanup() (alot.ui.UI method), 50
 clear_my_address() (alot.commands.thread.ReplyCommand static method), 75
 clear_notify() (alot.ui.UI method), 50
 collapse() (alot.buffers.ThreadBuffer method), 53
 collapse_all() (alot.buffers.ThreadBuffer method), 53
 collapse_if_matches() (alot.widgets.thread.MessageTree method), 57
 Command (class in alot.commands), 68
 CommandArgumentParser (class in alot.commands), 68
 CommandCompleter (class in alot.completion), 57
 commandfactory() (in module alot.commands), 68
 CommandLineCompleter (class in alot.completion), 57
 CommandNameCompleter (class in alot.completion), 58
 CommandParseError (class in alot.commands), 68
 commandpromphistory (alot.ui.UI attribute), 51
 complete() (alot.completion.Completer method), 58
 CompleteEdit (class in alot.widgets.globals), 55
 Completer (class in alot.completion), 58
 ComposeCommand (class in alot.commands.globals), 70
 ConfigError, 61
 construct_mail() (alot.db.envelope.Envelope method), 47
 ContactsCompleter (class in alot.completion), 58
 count_messages() (alot.db.manager.DBManager method), 40
 count_threads() (alot.db.manager.DBManager method), 40
 CryptoKeyCompleter (class in alot.completion), 58
 current_buffer (alot.ui.UI attribute), 51

D

DatabaseError (class in alot.db.errors), 42
 DatabaseLockedError (class in alot.db.errors), 42
 DatabaseROError (class in alot.db.errors), 42
 db_was_locked (alot.ui.UI attribute), 51
 dbman (alot.ui.UI attribute), 51
 DBManager (class in alot.db.manager), 40
 decode_header() (in module alot.db.utils), 47
 decrypt_verify() (in module alot.crypto), 76
 detached_signature_for() (in module alot.crypto), 76
 determine_sender() (in module alot.commands.thread), 76
 DictList (class in alot.widgets.thread), 56

E

EditCommand (class in alot.commands.envelope), 72
 EditCommand (class in alot.commands.globals), 70
 EditNewCommand (class in alot.commands.thread), 74
 EDITOR, 19
 email_as_string() (in module alot.helper), 65
 encode_header() (in module alot.db.utils), 48
 encrypt() (in module alot.crypto), 77
 ensure_unique_address() (alot.commands.thread.ReplyCommand static method), 75
 Envelope (class in alot.db.envelope), 46
 EnvelopeBuffer (class in alot.buffers), 52
 environment variable
 EDITOR, 19
 PATH, 4
 exit() (alot.ui.UI static method), 50
 exit() (built-in function), 35
 ExitCommand (class in alot.commands.globals), 70
 expand() (alot.buffers.ThreadBuffer method), 53
 expand_all() (alot.buffers.ThreadBuffer method), 53
 ExternalAddressbook (class in alot.addressbook.external), 64
 ExternalCommand (class in alot.commands.globals), 70
 extract_body() (in module alot.db.utils), 48
 extract_headers() (in module alot.db.utils), 48

F

flush() (alot.db.manager.DBManager method), 40
 FlushCommand (class in alot.commands.globals), 71
 focus_first() (alot.buffers.BufferlistBuffer method), 52
 focus_first() (alot.buffers.TagListBuffer method), 54
 focus_first() (alot.buffers.ThreadBuffer method), 53
 focus_first_reply() (alot.buffers.ThreadBuffer method), 53
 focus_last_reply() (alot.buffers.ThreadBuffer method), 53
 focus_next() (alot.buffers.ThreadBuffer method), 53
 focus_next_matching() (alot.buffers.ThreadBuffer method), 53
 focus_next_sibling() (alot.buffers.ThreadBuffer method), 53
 focus_next_unfolded() (alot.buffers.ThreadBuffer method), 53
 focus_parent() (alot.buffers.ThreadBuffer method), 53
 focus_prev() (alot.buffers.ThreadBuffer method), 53
 focus_prev_matching() (alot.buffers.ThreadBuffer method), 53
 focus_prev_sibling() (alot.buffers.ThreadBuffer method), 53
 focus_prev_unfolded() (alot.buffers.ThreadBuffer method), 53
 focus_property() (alot.buffers.ThreadBuffer method), 53
 focus_selected_message() (alot.buffers.ThreadBuffer method), 53

FocusableText (class in `alot.widgets.thread`), 56
 forward_prefix() (built-in function), 33
 forward_subject() (built-in function), 34
 ForwardCommand (class in `alot.commands.thread`), 74

G

get() (`alot.db.envelope.Envelope` method), 47
 get() (`alot.settings.manager.SettingsManager` method), 59
 get_account_by_address()
 (`alot.settings.manager.SettingsManager`
 method), 59
 get_accounts() (`alot.settings.manager.SettingsManager`
 method), 60
 get_addressbooks() (`alot.settings.manager.SettingsManager`
 method), 60
 get_addresses() (`alot.account.Account` method), 63
 get_addresses() (`alot.settings.manager.SettingsManager`
 method), 60
 get_all() (`alot.db.envelope.Envelope` method), 47
 get_all_tags() (`alot.db.manager.DBManager` method), 41
 get_attachments() (`alot.db.Message` method), 44
 get_attribute() (`alot.settings.theme.Theme` method), 62
 get_author() (`alot.db.Message` method), 44
 get_authors() (`alot.db.Thread` method), 43
 get_authors_string() (`alot.db.Thread` method), 43
 get_buffers_of_type() (`alot.ui.UI` method), 50
 get_contacts() (`alot.addressbook.AddressBook` method),
 64
 get_content_type() (`alot.db.attachment.Attachment`
 method), 46
 get_context() (`alot.completion.CommandLineCompleter`
 static method), 58
 get_data() (`alot.db.attachment.Attachment` method), 46
 get_date() (`alot.db.Message` method), 45
 get_datestring() (`alot.db.Message` method), 45
 get_deep_focus() (`alot.ui.UI` method), 50
 get_email() (`alot.db.Message` method), 45
 get_filename() (`alot.db.attachment.Attachment` method),
 46
 get_filename() (`alot.db.Message` method), 45
 get_focus() (`alot.buffers.ThreadBuffer` method), 53
 get_headers_string() (`alot.db.Message` method), 45
 get_hook() (`alot.settings.manager.SettingsManager`
 method), 60
 get_info() (`alot.buffers.Buffer` method), 52
 get_key() (in module `alot.crypto`), 77
 get_keybinding() (`alot.settings.manager.SettingsManager`
 method), 60
 get_keybindings() (`alot.settings.manager.SettingsManager`
 method), 60
 get_main_addresses() (`alot.settings.manager.SettingsManager`
 method), 60
 get_message() (`alot.db.manager.DBManager` method), 41
 get_message_id() (`alot.db.Message` method), 45
 get_message_parts() (`alot.db.Message` method), 45
 get_messages() (`alot.db.Thread` method), 43
 get_messagetree_positions() (`alot.buffers.ThreadBuffer`
 method), 53
 get_mime_representation()
 (`alot.db.attachment.Attachment` method),
 46
 get_newest_date() (`alot.db.Thread` method), 43
 get_notmuch_setting() (`alot.settings.manager.SettingsManager`
 method), 60
 get_oldest_date() (`alot.db.Thread` method), 43
 get_params() (in module `alot.db.utils`), 48
 get_replies() (`alot.db.Message` method), 45
 get_replies_to() (`alot.db.Thread` method), 43
 get_selected_buffer() (`alot.buffers.BufferlistBuffer`
 method), 52
 get_selected_message() (`alot.buffers.ThreadBuffer`
 method), 53
 get_selected_message_position()
 (`alot.buffers.ThreadBuffer` method), 54
 get_selected_messagetree() (`alot.buffers.ThreadBuffer`
 method), 54
 get_selected_mid() (`alot.buffers.ThreadBuffer` method),
 54
 get_selected_tag() (`alot.buffers.TagListBuffer` method),
 54
 get_selected_thread() (`alot.buffers.SearchBuffer`
 method), 52
 get_selected_thread() (`alot.buffers.ThreadBuffer`
 method), 54
 get_selected_threadline() (`alot.buffers.SearchBuffer`
 method), 52
 get_size() (`alot.db.attachment.Attachment` method), 46
 get_subject() (`alot.db.Thread` method), 43
 get_tags() (`alot.db.Message` method), 45
 get_tags() (`alot.db.Thread` method), 43
 get_tagstring_representation()
 (`alot.settings.manager.SettingsManager`
 method), 60
 get_theming_attribute() (`alot.settings.manager.SettingsManager`
 method), 61
 get_thread() (`alot.db.manager.DBManager` method), 41
 get_thread() (`alot.db.Message` method), 45
 get_thread_id() (`alot.db.Message` method), 45
 get_thread_id() (`alot.db.Thread` method), 43
 get_threadline_theming()
 (`alot.settings.manager.SettingsManager`
 method), 61
 get_threadline_theming() (`alot.settings.theme.Theme`
 method), 62
 get_threads() (`alot.db.manager.DBManager` method), 41
 get_toplevel_messages() (`alot.db.Thread` method), 43
 get_total_messages() (`alot.db.Thread` method), 43
 gpg_key (`alot.account.Account` attribute), 64

guess_encoding() (in module alot.helper), 65
guess_mimetype() (in module alot.helper), 66

H

handle_signal() (alot.ui.UI method), 50
has_replies() (alot.db.Message method), 45
hash_key() (in module alot.crypto), 77
headers (alot.db.envelope.Envelope attribute), 47
HeadersList (class in alot.widgets.globals), 55
HelpCommand (class in alot.commands.globals), 71
humanize_size() (in module alot.helper), 66

I

index_of() (alot.buffers.BufferlistBuffer method), 52
input_queue (alot.ui.UI attribute), 51

K

kill_filler_process() (alot.buffers.SearchBuffer method), 52
kill_search_processes() (alot.db.manager.DBManager method), 41

L

last_commandline (alot.ui.UI attribute), 51
libmagic_version_at_least() (in module alot.helper), 66
list_keys() (in module alot.crypto), 77
lookup() (alot.addressbook.AddressBook method), 64
lookup_command() (in module alot.commands), 69
lookup_parser() (in module alot.commands), 69
loop_hook() (built-in function), 35

M

mailcap_find_match() (alot.settings.manager.SettingsManager method), 61
mailto_to_envelope() (in module alot.helper), 66
matches() (alot.db.Message method), 45
matches() (alot.db.Thread method), 43
Message (class in alot.db), 44
message_from_file() (in module alot.db.utils), 48
message_from_string() (in module alot.db.utils), 48
MessageSummaryWidget (class in alot.widgets.thread), 56
MessageTree (class in alot.widgets.thread), 56
messagetree_at_position() (alot.buffers.ThreadBuffer method), 54
messagetrees() (alot.buffers.ThreadBuffer method), 54
mimewrap() (in module alot.helper), 66
mode (alot.ui.UI attribute), 51
MoveCommand (class in alot.commands.globals), 71
MultipleSelectionCompleter (class in alot.completion), 58

N

NonexistantObjectError (class in alot.db.errors), 42

notify() (alot.ui.UI method), 50

O

OpenAttachmentCommand (class in alot.commands.thread), 74
OpenBufferlistCommand (class in alot.commands.globals), 71
OpenThreadCommand (class in alot.commands.search), 73

P

parse_mailcap_nametemplate() (in module alot.helper), 66
parse_mailto() (in module alot.helper), 66
parse_template() (alot.db.envelope.Envelope method), 47
PATH, 4
PathCompleter (class in alot.completion), 58
PipeCommand (class in alot.commands.thread), 74
post_buffer_close() (built-in function), 35
post_buffer_focus() (built-in function), 35
post_buffer_open() (built-in function), 34
post_edit_translate() (built-in function), 34
pre_buffer_close() (built-in function), 35
pre_buffer_focus() (built-in function), 35
pre_buffer_open() (built-in function), 34
pre_edit_translate() (built-in function), 33
pre_envelope_send() (built-in function), 33
pretty_datetime() (in module alot.helper), 66
PrintCommand (class in alot.commands.thread), 75
prompt() (alot.ui.UI method), 51
PromptCommand (class in alot.commands.globals), 71
Python Enhancement Proposals
PEP 8, 39
PythonShellCommand (class in alot.commands.globals), 71

Q

query() (alot.db.manager.DBManager method), 41
QueryCompleter (class in alot.completion), 58

R

read_config() (alot.settings.manager.SettingsManager method), 61
read_config() (in module alot.settings.utils), 62
read_notmuch_config() (alot.settings.manager.SettingsManager method), 61
realname (alot.account.Account attribute), 64
rebuild() (alot.buffers.Buffer method), 52
recipienthistory (alot.ui.UI attribute), 51
RefineCommand (class in alot.commands.envelope), 72
RefineCommand (class in alot.commands.search), 73
RefinePromptCommand (class in alot.commands.search), 73
refresh() (alot.buffers.ThreadBuffer method), 54

- refresh() (alot.db.Thread method), 44
- RefreshCommand (class in alot.commands.globals), 71
- registerCommand (class in alot.commands), 69
- relevant_part() (alot.completion.Completer method), 58
- relevant_part() (alot.completion.MultipleSelectionCompleter method), 58
- remove_message() (alot.db.manager.DBManager method), 41
- remove_tags() (alot.db.Message method), 45
- remove_tags() (alot.db.Thread method), 44
- RemoveCommand (class in alot.commands.thread), 75
- RepeatCommand (class in alot.commands.globals), 71
- reply_prefix() (built-in function), 33
- reply_subject() (built-in function), 34
- ReplyCommand (class in alot.commands.thread), 75
- represent_datetime() (alot.settings.manager.SettingsManager method), 61
- resolve_att() (in module alot.settings.utils), 62
- RetagPromptCommand (class in alot.commands.search), 73
- RFC
- RFC 1524, 3
 - RFC 2015, 44
 - RFC 3156, 13, 15
- RFC3156_canonicalize() (in module alot.helper), 65
- RFC3156_micalg_from_algo() (in module alot.crypto), 76
- ## S
- sanitize_attachment_filename() (built-in function), 35
- save() (alot.db.attachment.Attachment method), 46
- SaveAttachmentCommand (class in alot.commands.thread), 75
- SaveCommand (class in alot.commands.envelope), 72
- SearchBuffer (class in alot.buffers), 52
- SearchCommand (class in alot.commands.globals), 71
- send_mail() (alot.account.Account method), 63
- send_mail() (alot.account.SendmailAccount method), 64
- SendCommand (class in alot.commands.envelope), 72
- senderhistory (alot.ui.UI attribute), 51
- SendmailAccount (class in alot.account), 64
- set() (alot.settings.manager.SettingsManager method), 61
- set_focus() (alot.buffers.ThreadBuffer method), 54
- SetCommand (class in alot.commands.envelope), 72
- SettingsManager (class in alot.settings.manager), 59
- shell_quote() (in module alot.helper), 67
- shorten() (in module alot.helper), 67
- shorten_author_string() (in module alot.helper), 67
- show_as_root_until_keypress() (alot.ui.UI method), 51
- signature (alot.account.Account attribute), 64
- signature_as_attachment (alot.account.Account attribute), 64
- signature_filename (alot.account.Account attribute), 64
- SignCommand (class in alot.commands.envelope), 72
- split_commandline() (in module alot.helper), 67
- split_commandstring() (in module alot.helper), 67
- store_draft_mail() (alot.account.Account method), 63
- store_mail() (alot.account.Account static method), 63
- store_sent_mail() (alot.account.Account method), 63
- string_decode() (in module alot.helper), 67
- string_sanitize() (in module alot.helper), 67
- StringlistCompleter (class in alot.completion), 59
- ## T
- tag() (alot.db.manager.DBManager method), 41
- tag_cmp() (in module alot.helper), 68
- TagCommand (class in alot.commands.search), 73
- TagCommand (class in alot.commands.thread), 75
- TagCompleter (class in alot.completion), 59
- TagListBuffer (class in alot.buffers), 54
- TagListCommand (class in alot.commands.globals), 71
- TaglistSelectCommand (class in alot.commands.taglist), 73
- tags (alot.db.envelope.Envelope attribute), 47
- TagsCompleter (class in alot.completion), 59
- TagWidget (class in alot.widgets.globals), 55
- text_quote() (built-in function), 34
- Theme (class in alot.settings.theme), 62
- Thread (class in alot.db), 42
- ThreadBuffer (class in alot.buffers), 52
- ThreadlineWidget (class in alot.widgets.search), 56
- ThreadSelectCommand (class in alot.commands.thread), 76
- ThreadTree (class in alot.widgets.thread), 57
- timestamp_format() (built-in function), 34
- tmpfile (alot.db.envelope.Envelope attribute), 47
- toggle_all_headers() (alot.buffers.EnvelopeBuffer method), 52
- ToggleHeaderCommand (class in alot.commands.envelope), 72
- touch_external_cmdlist() (built-in function), 34
- ## U
- UI (class in alot.ui), 49
- UnattachCommand (class in alot.commands.envelope), 72
- unfold_matching() (alot.buffers.ThreadBuffer method), 54
- UnsetCommand (class in alot.commands.envelope), 72
- untag() (alot.db.manager.DBManager method), 41
- update() (alot.ui.UI method), 51
- ## V
- validate_key() (in module alot.crypto), 77
- verify_detached() (in module alot.crypto), 78
- ## W
- write() (alot.db.attachment.Attachment method), 46