

---

# Clickable Documentation

*Release 5.0.0*

**Brian Douglass**

**Oct 03, 2018**



---

## Contents

---

<b>1</b>	<b>Using Clickable</b>	<b>3</b>
<b>2</b>	<b>Install Via Pip (Recommended)</b>	<b>17</b>
<b>3</b>	<b>Install Via PPA (Ubuntu)</b>	<b>19</b>
<b>4</b>	<b>Install Via AUR (Arch Linux)</b>	<b>21</b>
<b>5</b>	<b>Getting Started</b>	<b>23</b>
<b>6</b>	<b>Code Editor Integrations</b>	<b>25</b>
<b>7</b>	<b>Issues and Feature Requests</b>	<b>27</b>



Build and compile Ubuntu Touch apps easily from the command line. Deploy your apps to your Ubuntu Touch device for testing or test them on any desktop Linux distribution. Get logs for debugging and directly access a terminal on your device.

Clickable is fully Open Source and can be found on [GitLab](#). Clickable is developed by [Brian Douglass](#) with a huge thank you to all the [contributors](#).



## 1.1 Install

### 1.1.1 Install Via Pip (Recommended)

- Install docker, adb, and pip3
- Run (may need sudo): `pip3 install git+https://gitlab.com/clickable/clickable.git`

### 1.1.2 Install Via PPA (Ubuntu)

- Add the PPA to your system: `sudo add-apt-repository ppa:bhdouglass/clickable`
- Update your package list: `sudo apt-get update`
- Install clickable: `sudo apt-get install clickable`

### 1.1.3 Install Via AUR (Arch Linux)

- Using your favorite AUR helper, install the `clickable` package
- Example: `pacaur -S clickable`

## 1.2 Getting Started

- Run `clickable create` to get started with a new app.
- Choose from the list of *app templates*.
- Provide all the needed information about your new app.
- When the app has finished generating, enter the newly created directory containing your app.

- Run `clickable` to compile your app and install it on your phone.

## 1.2.1 Getting Logs

To get logs from you app simply run `clickable logs`. This will give you output from C++ (`QDebug()` << "message") or from QML (`console.log("message")`) in addition to any errors or warnings.

## 1.2.2 Running on the Desktop

Running the app on the desktop just requires you to run `clickable desktop`. This is not as complete as running the app on your phone, but it can help speed up development.

## 1.2.3 Accessing Your Device

If you need to access a terminal on your Ubuntu Touch device you can use `clickable shell` to open up a terminal to your device from your computer. This is a replacement for the old `phablet-shell` command.

## 1.2.4 Ubuntu Touch SDK Api Docs

For more information about the Ubuntu Touch QML or HTML SDK check out the [docs over at UBports](#).

## 1.2.5 Run Automatic Review

Apps submitted to the OpenStore will undergo automatic review, to test your app before submitting it, run `clickable review` after you've compiled a click. This runs the `click-review` command against your click within the clickable container (no need to install it on your computer).

## 1.2.6 Publishing to the OpenStore

If this is your first time publishing to the OpenStore, you need to [signup for an account](#). You can signup with your GitHub, GitLab, or Ubuntu account.

If your app is new to the OpenStore you must first create your app by entering the name from your `manifest.json` and the app's title on the [OpenStore's submission page](#).

If your app already exists you can use the `clickable publish` command to upload your compiled click file to the OpenStore. In order to publish to the OpenStore you need to grab your [api key from the OpenStore](#). After you have your api key you need to let Clickable know about it. You can either pass it as an argument every time: `clickable publish --apikey XYZ` Or you can set it as an environment variable: `export OPENSTORE_API_KEY=XYZ` (you can add this to your `~/.bashrc` to keep it set).

# 1.3 Usage

## 1.3.1 Getting Started

You can get started with using clickable with an existing Ubuntu Touch app. You can use clickable with apps generated from the old Ubuntu Touch SDK IDE or you can start fresh by running `clickable create`.

To run the default set of sub-commands, simply run `clickable` in the root directory of your app's code. Clickable with attempt to auto detect the *build template* and other configuration options, if you need more advanced usage options read the *clickable.json format guide*.

Running the default sub-commands will:

1. Clean the build directory (by default the build directory is `./build/`)
2. Compile the app
3. Build the click package (can be found in the build directory)
4. Install the app on your phone (By default this uses adb, see below if you want to use ssh)
5. Kill the running app on the phone
6. Launch the app on your phone

### 1.3.2 Connecting to a device over ssh

By default the device is connected to via adb. If you want to access a device over ssh you need to either specify the device IP address on the command line (ex: `clickable logs --ssh 192.168.1.10`) or you can use the `CLICKABLE_SSH` env var.

### 1.3.3 Multiple connected devices

By default clickable assumes that there is only one device connected to your computer via adb. If you have multiple devices attached to your computer you can specify which device to install/launch/etc on by using the flag `--serial-number` or `-s` for short. You can get the serial number by running `clickable devices`.

## 1.4 Commands

From the root directory of your project you have the following sub-commands available:

You can combine the commands together like `clickable build click_build install launch`

### 1.4.1 `clickable`

Runs the default sub-commands specified in the "default" config

### 1.4.2 `clickable desktop`

Compile and run the app on the desktop.

Note: ArchLinux user might need to run `xhost +local:clickable` before using desktop mode.

### 1.4.3 `clickable create`

Generate a new app from a list of *app template options*.

```
clickable create <app template name>
```

Generate a new app from an *app template* by name.

#### 1.4.4 `clickable shell`

Opens a shell on the device via ssh. This is similar to the `phablet-shell` command.

#### 1.4.5 `clickable clean`

Cleans out the build dir.

#### 1.4.6 `clickable build`

Builds the project using the specified template, build dir, and build commands.

#### 1.4.7 `clickable click-build`

Takes the built files and compiles them into a click package (you can find it in the build dir).

```
clickable click-build --output=/path/to/some/directory
```

Takes the built files and compiles them into a click package, outputting the compiled click to the directory specified by `--output`.

#### 1.4.8 `clickable review`

Takes the built click package and runs `click-review` against it. This allows you to review your click without installing `click-review` on your computer.

#### 1.4.9 `clickable install`

Takes a built click package and installs it on a device.

```
clickable install --click ./path/to/click/app.click
```

Installs the specified click package on the device

#### 1.4.10 `clickable launch`

Launches the app on a device.

```
clickable launch <app name>
```

Launches the specified app on a device.

#### 1.4.11 `clickable logs`

Follow the apps log file on the device.

#### 1.4.12 `clickable log`

Dumps the apps log file on the device.

### 1.4.13 `clickable publish`

Publish your click app to the OpenStore. Check the *Getting started doc* for more info.

### 1.4.14 `clickable run "some command"`

Runs an arbitrary command in the clickable container.

### 1.4.15 `clickable update`

Update the docker container for use with clickable.

### 1.4.16 `clickable no-lock`

Turns off the device's display timeout.

### 1.4.17 `clickable writable-image`

Make your Ubuntu Touch device's rootfs writable. This replaces to old `phablet-config writable-image` command.

### 1.4.18 `clickable devices`

Lists the serial numbers and model names for attached devices. Useful when multiple devices are attached and you need to know what to use for the `-s` argument.

### 1.4.19 `clickable <custom command>`

Runs a custom command specified in the "scripts" config

### 1.4.20 `clickable <any command> --container-mode`

Runs all builds commands on the current machine and not in a container. This is useful from running clickable from within a container.

### 1.4.21 `clickable desktop --nvidia`

Use clickable's desktop mode with proprietary Nvidia drivers. This requires `nvidia-docker` to be installed and setup. Please note, only version 1 of `nvidia-docker` is supported at this time (version 2 does not support OpenGL).

## 1.5 `clickable.json` Format

Example:

```
{
  "template": "cmake",
  "scripts": {
    "test": "make test"
  },
  "dependencies": [
    "libpoppler-qt5-dev"
  ]
}
```

### 1.5.1 arch

Optional, the default is armhf. You may also specify this as a cli arg (ex: `--arch="armhf"`)

### 1.5.2 prebuild

Optional, a custom command to run before a build.

### 1.5.3 template

Optional, see *build template* for the full list of options. If left blank the template will be auto detected.

### 1.5.4 build

Optional, a custom command to run instead of the default build. If using the *custom* template this is required.

### 1.5.5 postbuild

Optional, a custom command to execute after build and before click build.

### 1.5.6 launch

Optional, a custom command to launch the app.

### 1.5.7 dir

Optional, a custom build directory. Defaults to `./build/`

### 1.5.8 kill

Optional, a custom process name to kill (useful for killing the running app, then relaunching it). If left blank the process name will be assumed.

### 1.5.9 scripts

Optional, an object detailing custom commands to run. For example:

```
{
  "test": "make test",
  "echo": "echo Hello World"
}
```

### 1.5.10 lxd

Optional, whether or not to use a lxd container to build the app. Default is to use docker to build the app. LXD is deprecated and its support will be removed in a future version of clickable.

### 1.5.11 default

Optional, a list of space separated sub-commands to run when no sub-commands are specified. Defaults to `clean build click-build install launch`.

### 1.5.12 dependencies

Optional, a list of dependencies that will be installed in the build container. These will be assumed to be *dependencies:arch* unless *specificDependencies* is set to *true*.

### 1.5.13 docker\_image

Optional, the name of a docker image to use. When building a custom docker image it's recommended to use one of the Clickable images as a base. You can find them on [Docker Hub](#).

### 1.5.14 ignore

Optional, a list of files to ignore when building a *pure* template Example:

```
"ignore": [
  ".clickable",
  ".git",
  ".gitignore",
  ".gitmodules"
]
```

### 1.5.15 make\_jobs

Optional, the number of jobs to use when running make, equivalent to make's *-j* option. If left blank this defaults to the number of cpus your computer has.

### 1.5.16 gopath

Optional, the gopath on the host machine. If left blank, the `GOPATH` env var will be used.

### 1.5.17 build\_args

Optional, arguments to pass to qmake or cmake. Ex: CONFIG+=ubuntu

## 1.6 Environment Variables

Environment variables will override values in the clickable.json and can be overridden by command line arguments.

### 1.6.1 CLICKABLE\_ARCH

Overrides the clickable.json's *arch*.

### 1.6.2 CLICKABLE\_TEMPLATE

Overrides the clickable.json's *template*.

### 1.6.3 CLICKABLE\_DIR

Overrides the clickable.json's *dir*.

### 1.6.4 CLICKABLE\_LXD

Overrides the clickable.json's *lxd*.

### 1.6.5 CLICKABLE\_DEFAULT

Overrides the clickable.json's *default*.

### 1.6.6 CLICKABLE\_MAKE\_JOBS

Overrides the clickable.json's *make\_jobs*.

### 1.6.7 GOPATH

Overrides the clickable.json's *gopath*.

### 1.6.8 CLICKABLE\_DOCKER\_IMAGE

Overrides the clickable.json's *docker\_image*.

### 1.6.9 CLICKABLE\_BUILD\_ARGS

Overrides the clickable.json's *build\_args*.

### 1.6.10 OPENSTORE\_API\_KEY

Your api key for *publishing to the OpenStore*.

### 1.6.11 CLICKABLE\_CONTAINER\_MODE

Same as *-container-mode*.

### 1.6.12 CLICKABLE\_SERIAL\_NUMBER

Same as *-serial-number*.

### 1.6.13 CLICKABLE\_SSH

Same as *-ssh*.

### 1.6.14 CLICKABLE\_OUTPUT

Override the output directory for the resulting click file

### 1.6.15 CLICKABLE\_NVIDIA

Same as *-nvidia*.

### 1.6.16 CLICKABLE\_VIVID

Same as *--vivid*

## 1.7 App Templates

### 1.7.1 Pure QML App (built using CMake)

An app template that is setup for a purely QML app. It includes a CMake setup to allow for easy translations.

Check it out on [GitLab](#).

### 1.7.2 C++/QML App (built using CMake)

An app template that is setup for a QML app with a C++ plugin. It includes a CMake setup to allow for easy translation.

Check it out on [GitLab](#).

### 1.7.3 Python/QML App (built using CMake)

An app template that is setup for an app using Python with QML. It includes a CMake setup to allow for easy translation.

Check it out on [GitLab](#).

### 1.7.4 HTML App

An app template that is setup for a local HTML app.

Check it out on [GitLab](#).

### 1.7.5 Simple Webapp

An app template that is setup as a thin wrapper around an existing website.

Check it out on [GitLab](#).

### 1.7.6 Go/QML App

An app template that is setup for a QML app with a Go backend.

Check it out on [GitLab](#).

## 1.8 Build Templates

### 1.8.1 pure-qml-qmake

A purely qml qmake project.

### 1.8.2 qmake

A project that builds using qmake (has more than just QML).

### 1.8.3 pure-qml-cmake

A purely qml cmake project

### 1.8.4 cmake

A project that builds using cmake (has more than just QML)

### 1.8.5 custom

A custom build command will be used.

## 1.8.6 cordova

A project that builds using cordova

## 1.8.7 pure

A project that does not need to be compiled. All files in the project root will be copied into the click.

## 1.8.8 python

A project that uses python and does not need to be compiled.

## 1.8.9 go

A project that uses go version 1.6.

# 1.9 Continuous Integration

## 1.9.1 Clickable CI Docker Images

Two docker images are available for easily using Clickable with a continuous integration setup. They can be found on Docker hub: `clickable/ci-15.04-armhf` and `clickable/ci-16.04-armhf` for vivid/15.04 and xenial/16.04 respectively. The images come with Clickable pre installed and already setup in container mode.

## 1.9.2 GitLab Example

With GitLab's CI solution it is trivial to add Clickable building and publish to your click apps. For an example of this in action, check out the [Clickable GitLab example app](#).

To implement this in your own repository, create a `.gitlab-ci.yml`:

```
build_vivid:
  image: clickable/ci-15.04-armhf
  script:
    - clickable --vivid clean build click-build review publish

build_xenial:
  image: clickable/ci-16.04-armhf
  script:
    - clickable clean build click-build review publish
```

After that's setup, the last step is to add the environment variable `OPENSTORE_API_KEY` to your GitLab project (You can find your OpenStore api key when you log into the OpenStore).

## 1.10 Changelog

### 1.10.1 Changes in v5.0.0

- **New features**
  - Xenial by default (use `--vivid` to compile for 15.04)
  - Major code refactor
  - **More environment variables**
    - \* `CLICKABLE_ARCH` - Overrides the `clickable.json`'s `arch`
    - \* `CLICKABLE_TEMPLATE` - Overrides the `clickable.json`'s `template`
    - \* `CLICKABLE_DIR` - Overrides the `clickable.json`'s `dir`
    - \* `CLICKABLE_LXD` - Overrides the `clickable.json`'s `lxd`
    - \* `CLICKABLE_DEFAULT` - Overrides the `clickable.json`'s `default`
    - \* `CLICKABLE_MAKE_JOBS` - Overrides the `clickable.json`'s `make_jobs`
    - \* `GOPATH` - Overrides the `clickable.json`'s `gopath`
    - \* `CLICKABLE_DOCKER_IMAGE` - Overrides the `clickable.json`'s `docker_image`
    - \* `CLICKABLE_BUILD_ARGS` - Overrides the `clickable.json`'s `build_args`
    - \* `OPENSTORE_API_KEY` - Your api key for publishing to the OpenStore
    - \* `CLICKABLE_CONTAINER_MODE` - Same as `--container-mode`
    - \* `CLICKABLE_SERIAL_NUMBER` - Same as `--serial-number`
    - \* `CLICKABLE_SSH` - Same as `--ssh`
    - \* `CLICKABLE_OUTPUT` - Override the output directory for the resulting click file
    - \* `CLICKABLE_NVIDIA` - Same as `--nvidia`
    - \* `CLICKABLE_VIVID` - Same as `--vivid`
- **Removed**
  - Chroot support has been removed, docker containers are recommended going forward
- **clickable.json**
  - **Removed**
    - \* `package` - automatically grabbed from the `manifest.json`
    - \* `app` - automatically grabbed from the `manifest.json`
    - \* `sdk` - Replaced by `docker_image` and the `--vivid` argument
    - \* `premake` - Use `prebuild`
    - \* `ssh` - Use the `--ssh` argument
- **Commands**
  - **New**
    - \* `log` - Dumps the full log file from the app
    - \* `desktop` - Replaces `--desktop` to run the app in desktop mode

**- Changed**

- \* `init` - Changed to `create` (`init` will still work)
- \* `update-docker` - Changed to `update`

**- Removed**

- \* `kill` - Changed to be part of the `launch` command
- \* `setup-docker` - Automatically detected and run when using `docker`
- \* `display-on` - Not very useful

**• Command line arguments**

**- New**

- \* `--vivid` - Compile the app for 15.04
- \* `--docker-image` - Compile the app using a specific `docker` image

**- Changed**

- \* `--serial-number` - Replaces `--device-serial-number`
- \* `--ssh` - Replaces `--ip`

**- Removed**

- \* `--desktop` - Use the new `desktop` command
- \* `--xenial` - Xenial is now the default
- \* `--sdk` - Use `--vivid` or `--docker-image`
- \* `--device` - Use `shell`
- \* `--template` - Use the `CLICKABLE_TEMPLATE` env var
- \* `--click` - Specify the path to the click after the `install` command: `clickable install /path/to/click`
- \* `--app` - Specify the app name after the `launch` command: `clickable launch app.name`
- \* `--name` - Specify the app template after the `create` command: `clickable create pure-qml-cmake`



## CHAPTER 2

---

### Install Via Pip (Recommended)

---

- Install docker, adb, and pip3
- Run (may need sudo): `pip3 install git+https://gitlab.com/clickable/clickable.git`



## CHAPTER 3

---

### Install Via PPA (Ubuntu)

---

- Add the PPA to your system: `sudo add-apt-repository ppa:bhdouglass/clickable`
- Update your package list: `sudo apt-get update`
- Install clickable: `sudo apt-get install clickable`



## CHAPTER 4

---

### Install Via AUR (Arch Linux)

---

- Using your favorite AUR helper, install the `clickable` package
- Example: `pacaur -S clickable`



## CHAPTER 5

---

### Getting Started

---

*Read the getting started guide to get started developing with clickable.*



## CHAPTER 6

---

### Code Editor Integrations

---

Use clickable with the [Atom Editor](#) by installing `atom-build-clickable` made by Stefano.



## CHAPTER 7

---

### Issues and Feature Requests

---

If you run into any problems using clickable or have any feature requests you can find clickable on [GitLab](#).