

---

# Dask Yarn

Dec 14, 2018



---

## Contents

---

<b>1</b>	<b>Install</b>	<b>3</b>
1.1	Quickstart . . . . .	3
1.2	Managing Python Environments . . . . .	6
1.3	Configuration . . . . .	8
1.4	Submitting Applications . . . . .	8
1.5	Deploying on Amazon EMR . . . . .	10
1.6	API Docs . . . . .	12
1.7	CLI Docs . . . . .	15



Dask-Yarn deploys Dask on **YARN** clusters, such as are found in traditional Hadoop installations. Dask-Yarn provides an easy interface to quickly start, scale, and stop Dask clusters natively from Python.

```
from dask_yarn import YarnCluster
from dask.distributed import Client

# Create a cluster where each worker has two cores and eight GiB of memory
cluster = YarnCluster(environment='environment.tar.gz',
                     worker_vcores=2,
                     worker_memory="8GiB")
# Scale out to ten such workers
cluster.scale(10)

# Connect to the cluster
client = Client(cluster)
```

Dask-Yarn uses **Skein**, a Pythonic library to create and deploy YARN applications.



Dask-Yarn is designed to only require installation on an edge node. To install, use one of the following methods:

### Install with Conda:

```
conda install -c conda-forge dask-yarn
```

### Install with Pip:

```
pip install dask-yarn
```

### Install from Source:

Dask-Yarn is available on [github](#) and can always be installed from source.

```
pip install git+https://github.com/dask/dask-yarn.git
```

## 1.1 Quickstart

Dask-Yarn is designed to be used like any other python library - install it locally and use it in your code (either interactively, or as part of an application). As long as the computer you're deploying on has access to the YARN cluster (usually an edge node), everything should work fine.

### 1.1.1 Install Dask-Yarn on an Edge Node

Dask-Yarn is designed to be used from an edge node. To install, use either [conda](#) or [pip](#) to create a new environment and install `dask-yarn` on the edge node.

#### Conda Environments:

Create a new conda environment with `dask-yarn` installed. You may also want to add any other packages you rely on for your work.

```
$ conda create -n my_env dask-yarn      # Create an environment
$ conda activate my_env                 # Activate the environment
```

### Virtual Environments:

Create a new virtual environment with `dask-yarn` installed. You may also want to add any other packages you rely on for your work.

```
$ python -m venv my_env                 # Create an environment using venv
$ source my_env/bin/activate            # Activate the environment
$ pip install dask-yarn                 # Install some packages
```

## 1.1.2 Package your environment for Distribution

We need to ensure that the libraries used on the Yarn cluster are the same as what you are using locally. By default, `dask-yarn` handles this by distributing a packaged python environment to the Yarn cluster as part of the applications. This is typically handled using

- `conda-pack` for Conda environments
- `venv-pack` for virtual environments

See *Managing Python Environments* for more information.

### Conda Environments:

If you haven't already installed `conda-pack`, you'll need to do so now. You can either install it in the environment to be packaged, or your root environment (where it will be available to use in all environments).

```
$ conda install -c conda-forge conda-pack # Install conda-pack
$ conda-pack                             # Package environment
Collecting packages...
Packing environment at '/home/username/miniconda/envs/my_env' to 'my_env.tar.gz'
[#####] | 100% Completed | 12.2s
```

### Virtual Environments:

If you haven't already installed `venv-pack`, you'll need to do so now.

```
$ pip install venv-pack                 # Install venv-pack
$ venv-pack                             # Package environment
Collecting packages...
Packing environment at '/home/username/my-env' to 'my-env.tar.gz'
[#####] | 100% Completed | 8.3s
```

## 1.1.3 Kinit (Optional)

If your cluster is configured to use Kerberos for authentication, you need to make sure you have an active ticket-granting-ticket before continuing:

```
$ kinit
```

## 1.1.4 Usage

To start a YARN cluster, create an instance of `YarnCluster`. This constructor takes several parameters, leave them empty to use the defaults defined in the `Configuration`.

```
from dask_yarn import YarnCluster
from dask.distributed import Client

# Create a cluster where each worker has two cores and eight GiB of memory
cluster = YarnCluster(environment='environment.tar.gz',
                      worker_vcores=2,
                      worker_memory="8GiB")

# Connect to the cluster
client = Client(cluster)
```

By default no workers are started on cluster creation. To change the number of workers, use the `YarnCluster.scale()` method. When scaling up, new workers will be requested from YARN. When scaling down, workers will be intelligently selected and scaled down gracefully, freeing up resources.

```
# Scale up to 10 workers
cluster.scale(10)

# ...

# Scale back down to 2 workers
cluster.scale(2)
```

Alternatively, if you're working interactively in a Jupyter Notebook or JupyterLab, you can use the provided graphical interface to change the cluster size.

In [2]: `cluster`

## YarnCluster

**Workers** 2

Workers

Scale

**Cores** 4

**Memory** 8.58 GB

**Dashboard:** </proxy/41977/status>

Normally the cluster will persist until the `YarnCluster` object is deleted. To be more explicit about when the cluster is shutdown, you can either use the cluster as a context manager, or manually call `YarnCluster.shutdown()`.

```
# Use ``YarnCluster`` as a context manager
with YarnCluster(...) as cluster:
    # The cluster will remain active inside this block,
    # and will be shutdown when the context exits.

# Or manually call `shutdown`
```

(continues on next page)

(continued from previous page)

```
cluster = YarnCluster(...)
# ...
cluster.shutdown()
```

## 1.2 Managing Python Environments

We need to ensure that the libraries used on the Yarn cluster are the same as what you are using locally. There are a few ways to specify this:

- The path to an archived environment (either `conda` or `virtual` environments)
- The path to a `Conda` environment (as `conda:///...`)
- The path to a `virtual environment` (as `venv:///...`)
- The path to a python executable (as `python:///...`)

Note that when not using an archive, the provided path must be valid on all nodes in the cluster.

### 1.2.1 Using Archived Python Environments

The most common way to use `dask-yarn` is to distribute an archived Python environment throughout the YARN cluster as part of the application. Packaging the environment for distribution is typically handled using

- `conda-pack` for `Conda` environments
- `venv-pack` for `virtual environments`

These environments can contain any Python packages you might need, but require `dask-yarn` (and its dependencies) at a minimum.

#### Archiving Conda Environments Using Conda-Pack

You can package a `conda` environment using `conda-pack`.

```
$ conda create -n my-env dask-yarn scikit-learn          # Create an environment
$ conda activate my-env                                # Activate the environment
$ conda-pack                                           # Package environment
Collecting packages...
Packing environment at '/home/username/miniconda/envs/my-env' to 'my-env.tar.gz'
[#####] | 100% Completed | 12.2s
```

#### Archiving Virtual Environments Using Venv-Pack

You can package a virtual environment using `venv-pack`. The virtual environment can be created using either `venv` or `virtualenv`. Note that the python linked to in the virtual environment must exist and be accessible on every node in the YARN cluster. If the environment was created with a different Python, you can change the link path using the `--python-prefix` flag. For more information see the [venv-pack documentation](#).

```

$ python -m venv my_env # Create an environment using venv
$ python -m virtualenv my_env # Or create an environment using
→virtualenv

$ source my_env/bin/activate # Activate the environment

$ pip install dask-yarn scikit-learn # Install some packages

$ venv-pack # Package environment
Collecting packages...
Packing environment at '/home/username/my-env' to 'my-env.tar.gz'
[#####] | 100% Completed | 8.3s

```

## Specifying the Archived Environment

You can now start a cluster with the packaged environment by passing the path to the constructor, e.g. `YarnCluster(environment='my-env.tar.gz', ...)`.

Note that if the environment is a local file, the archive will be automatically uploaded to a temporary directory on HDFS before starting the application. If you find yourself reusing the same environment multiple times, you may want to upload the environment to HDFS once beforehand to avoid repeating this process for each cluster (the environment is then specified as `hdfs:///path/to/my-env.tar.gz`).

After startup you may want to verify that your versions match with the following:

```

from dask_yarn import YarnCluster
from dask.distributed import Client

cluster = YarnCluster(environment='my-env.tar.gz')
client = Client(cluster)
client.get_versions(check=True) # check that versions match between all nodes

```

## 1.2.2 Using Python Environments Local to Each Node

Alternatively, you can specify the path to a conda environment, virtual environment, or Python executable that is already found on each node:

```

from dask_yarn import YarnCluster

# Use a conda environment at /path/to/my/conda/env
cluster = YarnCluster(environment='conda:///path/to/my/conda/env')

# Use a virtual environment at /path/to/my/virtual/env
cluster = YarnCluster(environment='venv:///path/to/my/virtual/env')

# Use a Python executable at /path/to/my/python
cluster = YarnCluster(environment='python:///path/to/my/python')

```

As before, these environments can have any Python packages, but must include `dask-yarn` (and its dependencies) at a minimum. It's also *very important* that these environments are uniform across all nodes; mismatched environments can lead to hard to diagnose issues. To check this, you can use the `Client.get_versions` method:

```

from dask.distributed import Client

```

(continues on next page)

```
client = Client(cluster)
client.get_versions(check=True) # check that versions match between all nodes
```

## 1.3 Configuration

Specifying all parameters to the `YarnCluster` constructor every time may be error prone, especially when sharing this workflow with new users. Alternatively, you can provide defaults in a configuration file, traditionally held in `~/ .config/dask/yarn.yaml` or `/etc/dask/yarn.yaml`. Note that this configuration is *optional*, and only changes the defaults when not specified in the constructor.

### Example:

```
# /home/username/.config/dask/yarn.yaml
yarn:
  name: dask # Application name
  queue: default # Yarn queue to deploy to

  environment: /path/to/my-env.tar.gz

  tags: [] # List of strings to tag applications

  scheduler: # Specifications of scheduler container
    vcores: 1
    memory: 4GiB

  worker: # Specifications of worker containers
    vcores: 2
    memory: 8GiB
    count: 0 # Number of workers to start on initialization
    restarts: -1 # Allowed number of restarts, -1 for unlimited
```

Users can now create `YarnClusters` without specifying any additional information.

```
from dask_yarn import YarnCluster

cluster = YarnCluster()
cluster.scale(20)
```

For more information on Dask configuration see the [Dask configuration documentation](#).

## 1.4 Submitting Applications

**Warning:** The submission API is experimental and may change between versions

Sometimes you have Dask Application you want to deploy completely on YARN, without having a corresponding process running on an edge node. This may come up with production applications deployed automatically, or long running jobs you don't want to consume edge node resources.

To handle these cases, `dask-yarn` provides a [CLI Docs](#) that can be used to submit applications to be run on the YARN cluster asynchronously. There are three commands that may be useful here:

- `dask-yarn submit`: submit an application to the YARN cluster
- `dask-yarn status`: check on the status of an application
- `dask-yarn kill`: kill a running application

### 1.4.1 Submitting an Application

To prepare an application to be submitted using `dask-yarn submit`, you need to change the creation of your `YarnCluster` from using the constructor to using `YarnCluster.from_current()`.

```
# Replace this
cluster = YarnCluster(...)

# with this
cluster = YarnCluster.from_current()
```

This is because the script won't be run until the cluster is already created - at that point configuration passed to the `YarnCluster` constructor won't be useful. Cluster configuration is instead passed via the `dask-yarn submit` CLI (note that as before, the cluster can be scaled dynamically after creation).

```
# Submit `myscript.py` to run on a dask cluster with 8 workers,
# each with 2 cores and 4 GiB
$ dask-yarn submit \
  --environment my_env.tar.gz \
  --worker-count 8 \
  --worker-vccores 2 \
  --worker-memory 4GiB \
  myscript.py

application_1538148161343_0051
```

This outputs a YARN Application ID, which can be used with other YARN tools.

### 1.4.2 Checking Application Status

Submitted application status can be checked using the YARN Web UI, or programmatically using `dask-yarn status`. This command takes one parameter - the application id.

```
$ dask-yarn status application_1538148161343_0051
APPLICATION_ID      NAME      STATE      STATUS      CONTAINERS
↪VCORES      MEMORY      RUNTIME
application_1538148161343_0051      dask      RUNNING      UNDEFINED      9      17
↪          33792          6m
```

### 1.4.3 Killing a Running Application

Submitted applications normally run until completion. If you need to terminate one before then, you can use the `dask-yarn kill` command. This command takes one parameter - the application id.

```
$ dask-yarn kill application_1538148161343_0051
```

### 1.4.4 Accessing the Application Logs

Application logs can be retrieved a few ways:

- The logs of running applications can be viewed using the [Skein Web UI](#) (dask-yarn is built using [Skein](#)).
- The logs of completed applications can be viewed using the `yarn logs` command.

```
$ yarn logs --applicationId application_1538148161343_0051
```

## 1.5 Deploying on Amazon EMR

[Amazon Elastic MapReduce](#) (EMR) is a web service for creating a cloud-hosted Hadoop cluster.

Dask-Yarn works out-of-the-box on Amazon EMR, following the [Quickstart](#) as written should get you up and running fine. We recommend doing the installation step as part of a [bootstrap action](#).

For a curated installation, we also provide an [example bootstrap action](#) for installing Dask and Jupyter on cluster startup. This script is heavily commented, and can be used as an example if you need a more customized installation.

Here we provide a brief walkthrough of a workflow we've found useful when deploying Dask on Amazon EMR:

### 1.5.1 Configure the EMR Cluster

The EMR documentation contains an example showing how to [configure and start an EMR cluster](#). We recommend referencing their documentation. A few notes on recommended settings:

- If you plan to use a [bootstrap action](#), you'll need to follow the [Go to advanced options](#) link on the [Create Cluster](#) page - this feature is not available under [Quick Options](#).
- When choosing which applications to install, `dask-yarn` only requires a Hadoop installation, all other applications are optional depending on your workflow.

While this configuration can take some time and thought, the next time you want to start a Dask cluster on EMR you can [clone this cluster](#) to reuse the configuration.

### 1.5.2 Add a Bootstrap Action

To make installation on a clean cluster easier, we recommend scripting the installation as part of a [bootstrap action](#). For a curated install, we provide an [example bootstrap action](#) that you may use. This script does the following:

- Installs [miniconda](#).
- Installs `dask`, `distributed`, `dask-yarn`, `pyarrow`, and `s3fs`. This list of packages can be extended using the `--conda-packages` flag.
- Packages the environment with `conda-pack` for distribution to the workers.
- Optionally installs and starts a [Jupyter Notebook](#) server running on port 8888. This can be disabled with the `--no-jupyter` flag. The password for the notebook server can be set with the `--password` option, the default is `dask-user`.

If you require a more customized install than this, you may wish to provide your own script. The [example script](#) is heavily commented, and should hopefully provide enough of a reference for your use.

To use the script, follow AWS's documentation on [using bootstrap actions](#). You'll need to upload the script to an S3 bucket accessible to your project first.

### 1.5.3 Start the EMR Cluster

Once you've finished configuring your cluster, you can start it with the `Create Cluster` button. This may take a while (~10 mins), depending on your settings.

### 1.5.4 Connect to the EMR Cluster

Once the cluster is running, you'll want to connect to it. Depending on your `EC2 security groups` settings, you may have direct access to the cluster, or you may need to start an `ssh tunnel` (default). For either of these you'll need to know the public DNS name of your master node. This address looks like `ec2-###-##-##-###.compute-1.amazonaws.com`, and can be found by following [the AWS documentation](#).

#### Direct Access

If you have direct access to the cluster, you should be able to access the resource-manager WebUI at `<public-dns-name>:8088`. If you used our provided bootstrap action, the Jupyter Notebook should be available at `<public-dns-name>:8888`.

#### Using an SSH Tunnel

If you don't have direct access, you'll need to start an SSH tunnel to access the Web UIs or the Jupyter Notebook. For more information, see the [AWS documentation](#).

If you used our provided bootstrap action, the Jupyter Notebook should be available at `<public-dns-name>:8888`, and can be accessed by starting a SSH tunnel via:

```
$ ssh -i ~/mykeypair.pem -L 8888:<public-dns-name>:8888 hadoop@<public-dns-name>
```

where `~/mykeypair.pem` is your `.pem` file, and `<public-dns-name>` is the public DNS name of your master node.

### 1.5.5 Create a Dask Cluster

At this point you should have access to a running EMR cluster, with Dask and its dependencies installed. To create a new Dask cluster running inside the EMR cluster, create an instance of `YarnCluster`. If you didn't use our bootstrap action, you'll also need to provide a path to your packaged environment (see [Managing Python Environments](#) for more information).

```
from dask_yarn import YarnCluster
from dask.distributed import Client

# Create a cluster in local deploy mode, to have access to the dashboard
cluster = YarnCluster(deploy_mode='local')

# Connect to the cluster
client = Client(cluster)
```

By default no workers are started on cluster creation. To change the number of workers, use the `YarnCluster.scale()` method. When scaling up, new workers will be requested from YARN. When scaling down, workers will be intelligently selected and scaled down gracefully, freeing up resources.

```
# Scale up to 10 workers
cluster.scale(10)

# ...
```

(continues on next page)

(continued from previous page)

```
# Scale back down to 2 workers
cluster.scale(2)
```

If you're working interactively in a [Jupyter Notebook](#) you can also use the provided graphical interface to change the cluster size.

In [2]: `cluster`

## YarnCluster

<b>Workers</b>	2	<b>Workers</b>	2	<input type="button" value="Scale"/>
<b>Cores</b>	4			
<b>Memory</b>	8.58 GB			
<b>Dashboard:</b> <a href="/proxy/41977/status">/proxy/41977/status</a>				

If you used our bootstrap action, and start your cluster with `deploy_mode='local'`, the [dask dashboard](#) will also be available, and the link included in the cluster widget above.

### 1.5.6 Shutdown the EMR Cluster

You can start, scale, and stop many *Dask* clusters within a single EMR cluster. When you're finally done doing your work, you'll want to shutdown the whole EMR cluster to conserve resources. See the [AWS documentation](#) for more information.

## 1.6 API Docs

```
class dask_yarn.YarnCluster(environment=None, n_workers=None, worker_vcores=None,
                             worker_memory=None, worker_restarts=None, worker_env=None,
                             scheduler_vcores=None, scheduler_memory=None, de-
                             ploy_mode=None, name=None, queue=None, tags=None,
                             user=None, skein_client=None)
```

Start a Dask cluster on YARN.

You can define default values for this in Dask's `yarn.yaml` configuration file. See <http://docs.dask.org/en/latest/configuration.html> for more information.

### Parameters

**environment** [str, optional]

**The Python environment to use. Can be one of the following:**

- A path to an archived Python environment
- A path to a conda environment, specified as `conda:///...`
- A path to a virtual environment, specified as `venv:///...`

- A path to a python executable, specified as `python:///...`

Note that if not an archive, the paths specified must be valid on all nodes in the cluster.

- n\_workers** [int, optional] The number of workers to initially start.
- worker\_vcores** [int, optional] The number of virtual cores to allocate per worker.
- worker\_memory** [str, optional] The amount of memory to allocate per worker. Accepts a unit suffix (e.g. '2 GiB' or '4096 MiB'). Will be rounded up to the nearest MiB.
- worker\_restarts** [int, optional] The maximum number of worker restarts to allow before failing the application. Default is unlimited.
- worker\_env** [dict, optional] A mapping of environment variables to their values. These will be set in the worker containers before starting the dask workers.
- scheduler\_vcores** [int, optional] The number of virtual cores to allocate per scheduler.
- scheduler\_memory** [str, optional] The amount of memory to allocate to the scheduler. Accepts a unit suffix (e.g. '2 GiB' or '4096 MiB'). Will be rounded up to the nearest MiB.
- deploy\_mode** [{ 'remote', 'local' }, optional] The deploy mode to use. If 'remote', the scheduler will be deployed in a YARN container. If 'local', the scheduler will run locally, which can be nice for debugging. Default is 'remote'.
- name** [str, optional] The application name.
- queue** [str, optional] The queue to deploy to.
- tags** [sequence, optional] A set of strings to use as tags for this application.
- user** [str, optional] The user to submit the application on behalf of. Default is the current user - submitting as a different user requires user permissions, see the YARN documentation for more information.
- skein\_client** [skein.Client, optional] The `skein.Client` to use. If not provided, one will be started.

## Examples

```
>>> cluster = YarnCluster(environment='my-env.tar.gz', ...)
>>> cluster.scale(10)
```

**close** (\*\*kwargs)

Close this cluster. An alias for `shutdown`.

**See also:**

`shutdown`

**dashboard\_link**

Link to the dask dashboard. None if dashboard isn't running

**classmethod from\_application\_id** (app\_id, skein\_client=None)

Connect to an existing `YarnCluster` with a given application id.

### Parameters

**app\_id** [str] The existing cluster's application id.

**skein\_client** [skein.Client] The `skein.Client` to use. If not provided, one will be started.

**Returns****YarnCluster****classmethod** `from_current()`Connect to an existing `YarnCluster` from inside the cluster.**Returns****YarnCluster****classmethod** `from_specification(spec, skein_client=None)`

Start a dask cluster from a skein specification.

**Parameters****spec** [`skein.ApplicationSpec`, dict, or filename] The application specification to use. Must define at least one service: `'dask.worker'`. If no `'dask.scheduler'` service is defined, a scheduler will be started locally.**skein\_client** [`skein.Client`, optional] The `skein.Client` to use. If not provided, one will be started.**scale** (*n*)Scale cluster to *n* workers.**Parameters****n** [`int`] Target number of workers**Examples**

```
>>> cluster.scale(10) # scale cluster to ten workers
```

**scale\_down** (*workers*)

Retire the selected workers.

**Parameters****workers: list** List of addresses of workers to close.**scale\_up** (*n*, *workers=None*)Ensure there are atleast *n* dask workers available for this cluster.No-op if *n* is less than the current number of workers.**Examples**

```
>>> cluster.scale_up(20) # ask for twenty workers
```

**shutdown** (*status='SUCCEEDED'*, *diagnostics=None*)

Shutdown the application.

**Parameters****status** [`'SUCCEEDED'`, `'FAILED'`, `'KILLED'`], optional] The yarn application exit status.**diagnostics** [`str`, optional] The application exit message, usually used for diagnosing failures. Can be seen in the YARN Web UI for completed applications under “diagnostics”. If not provided, a default will be used.

**workers ()**

A list of all currently running worker containers.

## 1.7 CLI Docs

**Warning:** The CLI is experimental and may change between versions

### 1.7.1 dask-yarn

Deploy Dask on Apache YARN

```
usage: dask-yarn [--help] [--version] command ...
```

**--help, -h**

Show this help message then exit

**--version**

Show version then exit

#### dask-yarn kill

Kill a Dask application

```
usage: dask-yarn kill [--help] APP_ID
```

**app\_id**

The application id

**--help, -h**

Show this help message then exit

#### dask-yarn services

Manage Dask services

```
usage: dask-yarn services [--help] command ...
```

**--help, -h**

Show this help message then exit

#### dask-yarn services client

Start a Dask client process

```
usage: dask-yarn services client [--help] script [args...]
```

**script**

Path to a Python script to run.

**args**

Any additional arguments to forward to *script*

## Dask Yarn

---

**--help, -h**

Show this help message then exit

### dask-yarn services scheduler

Start a Dask scheduler process

```
usage: dask-yarn services scheduler [--help]
```

**--help, -h**

Show this help message then exit

### dask-yarn services worker

Start a Dask worker process

```
usage: dask-yarn services worker [--nthreads NTHREADS]
                                [--memory_limit MEMORY_LIMIT] [--help]
```

**--nthreads** <nthreads>

Number of threads. Defaults to number of vcores in container

**--memory\_limit** <memory\_limit>

Maximum memory available to the worker. This can be an integer (in bytes), a string (like '5 GiB' or '500 MiB'), or 0 (no memory management). Defaults to the container memory limit.

**--help, -h**

Show this help message then exit

### dask-yarn status

Check the status of a submitted Dask application

```
usage: dask-yarn status [--help] APP_ID
```

**app\_id**

The application id

**--help, -h**

Show this help message then exit

### dask-yarn submit

Submit a Dask application to a YARN cluster

```
usage: dask-yarn submit [--name NAME] [--queue QUEUE] [--user USER]
                        [--tags TAGS] [--environment ENVIRONMENT]
                        [--deploy-mode DEPLOY_MODE]
                        [--worker-count WORKER_COUNT]
                        [--worker-vcores WORKER_VCORES]
                        [--worker-memory WORKER_MEMORY]
                        [--worker-restarts WORKER_RESTARTS]
                        [--worker-env WORKER_ENV]
                        [--client-vcores CLIENT_VCORES]
```

(continues on next page)

(continued from previous page)

```

[--client-memory CLIENT_MEMORY]
[--client-env CLIENT_ENV]
[--scheduler-vcores SCHEDULER_VCORES]
[--scheduler-memory SCHEDULER_MEMORY]
[--temporary-security-credentials] [--help]
script [args...]

```

**script**

Path to a python script to run on the client

**args**

Any additional arguments to forward to *script*

**--name** <name>

The application name

**--queue** <queue>

The queue to deploy to

**--user** <user>

The user to submit the application on behalf of. Default is the current user - submitting as a different user requires proxy-user permissions.

**--tags** <tags>

A comma-separated list of strings to use as tags for this application.

**--environment** <environment>

Path to the Python environment to use. See the docs for more information

**--deploy-mode** <deploy\_mode>

Either 'remote' (default) or 'local'. If 'remote', the scheduler and client will be deployed in a YARN container. If 'local', they will be run locally.

**--worker-count** <worker\_count>

The number of workers to initially start.

**--worker-vcores** <worker\_vcores>

The number of virtual cores to allocate per worker.

**--worker-memory** <worker\_memory>

The amount of memory to allocate per worker. Accepts a unit suffix (e.g. '2 GiB' or '4096 MiB'). Will be rounded up to the nearest MiB.

**--worker-restarts** <worker\_restarts>

The maximum number of worker restarts to allow before failing the application. Default is unlimited.

**--worker-env** <worker\_env>

Environment variables to set on the workers. Pass a key-value pair like `--worker-env key=val`. May be used more than once.

**--client-vcores** <client\_vcores>

The number of virtual cores to allocate for the client.

**--client-memory** <client\_memory>

The amount of memory to allocate for the client. Accepts a unit suffix (e.g. '2 GiB' or '4096 MiB'). Will be rounded up to the nearest MiB.

**--client-env** <client\_env>

Environment variables to set on the client. Pass a key-value pair like `--client-env key=val`. May be used more than once.

**--scheduler-vcores** <scheduler\_vcores>

The number of virtual cores to allocate for the scheduler.

**--scheduler-memory** <scheduler\_memory>

The amount of memory to allocate for the scheduler. Accepts a unit suffix (e.g. '2 GiB' or '4096 MiB'). Will be rounded up to the nearest MiB.

**--temporary-security-credentials**

Instead of using a consistent set of TLS credentials for all clusters, create a fresh set just for this application.

**--help, -h**

Show this help message then exit

## Symbols

- client-env <client\_env>
  - dask-yarn-submit command line option, 17
- client-memory <client\_memory>
  - dask-yarn-submit command line option, 17
- client-vccores <client\_vccores>
  - dask-yarn-submit command line option, 17
- deploy-mode <deploy\_mode>
  - dask-yarn-submit command line option, 17
- environment <environment>
  - dask-yarn-submit command line option, 17
- help, -h
  - dask-yarn command line option, 15
  - dask-yarn-kill command line option, 15
  - dask-yarn-services command line option, 15
  - dask-yarn-services-client command line option, 15
  - dask-yarn-services-scheduler command line option, 16
  - dask-yarn-services-worker command line option, 16
  - dask-yarn-status command line option, 16
  - dask-yarn-submit command line option, 18
- memory\_limit <memory\_limit>
  - dask-yarn-services-worker command line option, 16
- name <name>
  - dask-yarn-submit command line option, 17
- nthreads <nthreads>
  - dask-yarn-services-worker command line option, 16
- queue <queue>
  - dask-yarn-submit command line option, 17
- scheduler-memory <scheduler\_memory>
  - dask-yarn-submit command line option, 18
- scheduler-vccores <scheduler\_vccores>
  - dask-yarn-submit command line option, 17
- tags <tags>
  - dask-yarn-submit command line option, 17
- temporary-security-credentials
  - dask-yarn-submit command line option, 18
- user <user>
  - dask-yarn-submit command line option, 17

- version
  - dask-yarn command line option, 15
- worker-count <worker\_count>
  - dask-yarn-submit command line option, 17
- worker-env <worker\_env>
  - dask-yarn-submit command line option, 17
- worker-memory <worker\_memory>
  - dask-yarn-submit command line option, 17
- worker-restarts <worker\_restarts>
  - dask-yarn-submit command line option, 17
- worker-vccores <worker\_vccores>
  - dask-yarn-submit command line option, 17

## A

- app\_id
  - dask-yarn-kill command line option, 15
  - dask-yarn-status command line option, 16
- args
  - dask-yarn-services-client command line option, 15
  - dask-yarn-submit command line option, 17

## C

- close() (dask\_yarn.YarnCluster method), 13

## D

- dashboard\_link (dask\_yarn.YarnCluster attribute), 13
- dask-yarn command line option
  - help, -h, 15
  - version, 15
- dask-yarn-kill command line option
  - help, -h, 15
  - app\_id, 15
- dask-yarn-services command line option
  - help, -h, 15
- dask-yarn-services-client command line option
  - help, -h, 15
  - args, 15
  - script, 15
- dask-yarn-services-scheduler command line option

-help, -h, 16

dask-yarn-services-worker command line option

-help, -h, 16

-memory\_limit <memory\_limit>, 16

-nthreads <nthreads>, 16

dask-yarn-status command line option

-help, -h, 16

app\_id, 16

dask-yarn-submit command line option

-client-env <client\_env>, 17

-client-memory <client\_memory>, 17

-client-vcores <client\_vcores>, 17

-deploy-mode <deploy\_mode>, 17

-environment <environment>, 17

-help, -h, 18

-name <name>, 17

-queue <queue>, 17

-scheduler-memory <scheduler\_memory>, 18

-scheduler-vcores <scheduler\_vcores>, 17

-tags <tags>, 17

-temporary-security-credentials, 18

-user <user>, 17

-worker-count <worker\_count>, 17

-worker-env <worker\_env>, 17

-worker-memory <worker\_memory>, 17

-worker-restarts <worker\_restarts>, 17

-worker-vcores <worker\_vcores>, 17

args, 17

script, 17

## F

from\_application\_id() (dask\_yarn.YarnCluster class method), 13

from\_current() (dask\_yarn.YarnCluster class method), 14

from\_specification() (dask\_yarn.YarnCluster class method), 14

## S

scale() (dask\_yarn.YarnCluster method), 14

scale\_down() (dask\_yarn.YarnCluster method), 14

scale\_up() (dask\_yarn.YarnCluster method), 14

script

dask-yarn-services-client command line option, 15

dask-yarn-submit command line option, 17

shutdown() (dask\_yarn.YarnCluster method), 14

## W

workers() (dask\_yarn.YarnCluster method), 15

## Y

YarnCluster (class in dask\_yarn), 12