

---

# **django-rest-auth Documentation**

*Release 0.3.0*

**Tivix Inc.**

**Oct 03, 2017**



---

# Contents

---

<b>1</b>	<b>Contents</b>	<b>3</b>
1.1	Introduction . . . . .	3
1.2	Installation . . . . .	4
1.3	API endpoints . . . . .	7
1.4	Configuration . . . . .	8
1.5	Demo project . . . . .	9
1.6	FAQ . . . . .	10
1.7	Changelog . . . . .	11



**Warning:** Updating django-rest-auth from version **0.3.3** is highly recommended because of a security issue in PasswordResetConfirmation validation method.

---

**Note:** django-rest-auth from v0.3.3 supports django-rest-framework v3.0

---



## Introduction

Since the introduction of `django-rest-framework`, Django apps have been able to serve up app-level REST API endpoints. As a result, we saw a lot of instances where developers implemented their own REST registration API endpoints here and there, snippets, and so on. We aim to solve this demand by providing `django-rest-auth`, a set of REST API endpoints to handle User Registration and Authentication tasks. By having these API endpoints, your client apps such as AngularJS, iOS, Android, and others can communicate to your Django backend site independently via REST APIs for User Management. Of course, we'll add more API endpoints as we see the demand.

## Features

- User Registration with activation
- Login/Logout
- Retrieve/Update the Django User model
- Password change
- Password reset via e-mail
- Social Media authentication

## Apps structure

- `rest_auth` has basic auth functionality like login, logout, password reset and password change
- `rest_auth.registration` has logic related with registration and social media authentication

## Angular app

- Tivix has also created angular module which uses API endpoints from this app - [angular-django-registration-auth](#)

## Demo project

- You can also check our *Demo Project* which is using jQuery on frontend.

## Installation

1. Install package:

```
pip install django-rest-auth
```

2. Add `rest_auth` app to `INSTALLED_APPS` in your `django settings.py`:

```
INSTALLED_APPS = (  
    ...,  
    'rest_framework',  
    'rest_framework.authtoken',  
    ...,  
    'rest_auth'  
)
```

---

**Note:** This project depends on `django-rest-framework` library, so install it if you haven't done yet. Make sure also you have installed `rest_framework` and `rest_framework.authtoken` apps

---

3. Add `rest_auth` urls:

```
urlpatterns = [  
    ...,  
    url(r'^rest-auth/', include('rest_auth.urls'))  
)
```

4. Migrate your database

```
python manage.py migrate
```

You're good to go now!

## Registration (optional)

1. If you want to enable standard registration process you will need to install `django-allauth` by using `pip install django-rest-auth[with_social]`.
2. Add `django.contrib.sites`, `allauth`, `allauth.account` and `rest_auth.registration` apps to `INSTALLED_APPS` in your `django settings.py`:
3. Add `SITE_ID = 1` to your `django settings.py`

```
INSTALLED_APPS = (  
    ...,  
    'django.contrib.sites',  
    'allauth',  
    'allauth.account',  
    'rest_auth.registration',  
)
```



```
SITE_ID = 1
```

### 3. Add rest\_auth.registration urls:

```
urlpatterns = [
    ...,
    url(r'^rest-auth/', include('rest_auth.urls')),
    url(r'^rest-auth/registration/', include('rest_auth.registration.urls'))
]
```

## Social Authentication (optional)

Using django-allauth, django-rest-auth provides helpful class for creating social media authentication view.

**Note:** Points 1 and 2 are related to django-allauth configuration, so if you have already configured social authentication, then please go to step 3. See django-allauth documentation for more details.

1. Add allauth.socialaccount and allauth.socialaccount.providers.facebook or allauth.socialaccount.providers.twitter apps to INSTALLED\_APPS in your django settings.py:

```
INSTALLED_APPS = (
    ...,
    'rest_framework',
    'rest_framework.authtoken',
    'rest_auth'
    ...,
    'django.contrib.sites',
    'allauth',
    'allauth.account',
    'rest_auth.registration',
    ...,
    'allauth.socialaccount',
    'allauth.socialaccount.providers.facebook',
    'allauth.socialaccount.providers.twitter',
)
```

2. Add Social Application in django admin panel

### Facebook

3. Create new view as a subclass of rest\_auth.registration.views.SocialLoginView with FacebookOAuth2Adapter adapter as an attribute:

```
from allauth.socialaccount.providers.facebook.views import FacebookOAuth2Adapter
from rest_auth.registration.views import SocialLoginView

class FacebookLogin(SocialLoginView):
    adapter_class = FacebookOAuth2Adapter
```

4. Create url for FacebookLogin view:

```
urlpatterns += [
    ...,
    url(r'^rest-auth/facebook/$', FacebookLogin.as_view(), name='fb_login')
]
```

### Twitter

If you are using Twitter for your social authentication, it is a bit different since Twitter uses OAuth 1.0.

3. Create new view as a subclass of `rest_auth.views.LoginView` with `TwitterOAuthAdapter` adapter and `TwitterLoginSerializer` as an attribute:

```
from allauth.socialaccount.providers.twitter.views import TwitterOAuthAdapter
from rest_auth.views import LoginView
from rest_auth.social_serializers import TwitterLoginSerializer

class TwitterLogin(LoginView):
    serializer_class = TwitterLoginSerializer
    adapter_class = TwitterOAuthAdapter
```

4. Create url for TwitterLogin view:

```
urlpatterns += [
    ...,
    url(r'^rest-auth/twitter/$', TwitterLogin.as_view(), name='twitter_login')
]
```

---

**Note:** Starting from v0.21.0, django-allauth has dropped support for context processors. Check out <http://django-allauth.readthedocs.org/en/latest/changelog.html#from-0-21-0> for more details.

---

### JWT Support (optional)

By default `django-rest-auth` uses Django's Token-based authentication. If you want to use JWT authentication, follow these steps:

1. **Install `django-rest-framework-jwt`**
  - `django-rest-framework-jwt` is currently the only supported JWT library.
2. **The `JWT_PAYLOAD_HANDLER` and `JWT_ENCODE_HANDLER` settings are imported from the `django-rest-framework-jwt` package.**
  - Refer to the library's documentation for information on using different encoders.
3. Add the following configuration value to your settings file to enable JWT authentication.

```
REST_USE_JWT = True
```

## API endpoints

### Basic

- /rest-auth/login/ (POST)

- username
- email
- password

Returns Token key

- /rest-auth/logout/ (POST)

---

**Note:** `ACCOUNT_LOGOUT_ON_GET = True` to allow logout using GET - this is the exact same configuration from allauth. NOT recommended, see: <http://django-allauth.readthedocs.io/en/latest/views.html#logout>

---

- /rest-auth/password/reset/ (POST)

- email

- /rest-auth/password/reset/confirm/ (POST)

- uid
- token
- new\_password1
- new\_password2

---

**Note:** uid and token are sent in email after calling /rest-auth/password/reset/

---

- /rest-auth/password/change/ (POST)

- new\_password1
- new\_password2
- old\_password

---

**Note:** `OLD_PASSWORD_FIELD_ENABLED = True` to use old\_password.

---

---

**Note:** `LOGOUT_ON_PASSWORD_CHANGE = False` to keep the user logged in after password change

---

- /rest-auth/user/ (GET, PUT, PATCH)

- username
- first\_name

- last\_name

Returns pk, username, email, first\_name, last\_name

## Registration

- /rest-auth/registration/ (POST)
  - username
  - password1
  - password2
  - email
- /rest-auth/registration/verify-email/ (POST)
  - key

## Social Media Authentication

Basing on example from installation section *Installation*

- /rest-auth/facebook/ (POST)
  - access\_token
  - code

---

**Note:** access\_token OR code can be used as standalone arguments, see [https://github.com/Tivix/django-rest-auth/blob/master/rest\\_auth/registration/views.py](https://github.com/Tivix/django-rest-auth/blob/master/rest_auth/registration/views.py)

---

- /rest-auth/twitter/ (POST)
  - access\_token
  - token\_secret

## Configuration

### • REST\_AUTH\_SERIALIZERS

You can define your custom serializers for each endpoint without overriding urls and views by adding REST\_AUTH\_SERIALIZERS dictionary in your django settings. Possible key values:

- LOGIN\_SERIALIZER - serializer class in rest\_auth.views.LoginView, default value rest\_auth.serializers.LoginSerializer
- TOKEN\_SERIALIZER - response for successful authentication in rest\_auth.views.LoginView, default value rest\_auth.serializers.TokenSerializer
- JWT\_SERIALIZER - (Using REST\_USE\_JWT=True) response for successful authentication in rest\_auth.views.LoginView, default value rest\_auth.serializers.JWTSerializer

- `USER_DETAILS_SERIALIZER` - serializer class in `rest_auth.views.UserDetailsView`, default value `rest_auth.serializers.UserDetailsSerializer`
- `PASSWORD_RESET_SERIALIZER` - serializer class in `rest_auth.views.PasswordResetView`, default value `rest_auth.serializers.PasswordResetSerializer`
- `PASSWORD_RESET_CONFIRM_SERIALIZER` - serializer class in `rest_auth.views.PasswordResetConfirmView`, default value `rest_auth.serializers.PasswordResetConfirmSerializer`
- `PASSWORD_CHANGE_SERIALIZER` - serializer class in `rest_auth.views.PasswordChangeView`, default value `rest_auth.serializers.PasswordChangeSerializer`

Example configuration:

```
REST_AUTH_SERIALIZERS = {
    'LOGIN_SERIALIZER': 'path.to.custom.LoginSerializer',
    'TOKEN_SERIALIZER': 'path.to.custom.TokenSerializer',
    ...
}
```

#### • `REST_AUTH_REGISTER_SERIALIZERS`

You can define your custom serializers for registration endpoint. Possible key values:

- `REGISTER_SERIALIZER` - serializer class in `rest_auth.registration.views.RegisterView`, default value `rest_auth.registration.serializers.RegisterSerializer`

---

**Note:** The custom `REGISTER_SERIALIZER` must define a `def save(self, request)` method that returns a user model instance

---

- `REST_AUTH_TOKEN_MODEL` - model class for tokens, default value `rest_framework.authtoken.models`
- `REST_AUTH_TOKEN_CREATOR` - callable to create tokens, default value `rest_auth.utils.default_create_token`.
- `REST_SESSION_LOGIN` - Enable session login in Login API view (default: True)
- `REST_USE_JWT` - Enable JWT Authentication instead of Token/Session based. This is built on top of `django-rest-framework-jwt` <http://getblimp.github.io/django-rest-framework-jwt/>, which must also be installed. (default: False)
- `OLD_PASSWORD_FIELD_ENABLED` - set it to True if you want to have old password verification on password change endpoint (default: False)
- `LOGOUT_ON_PASSWORD_CHANGE` - set to False if you want to keep the current user logged in after a password change

## Demo project

The idea of creating demo project was to show how you can potentially use `django-rest-auth` app with jQuery on frontend. Do these steps to make it running (ideally in `virtualenv`).

```
cd /tmp
git clone https://github.com/Tivix/django-rest-auth.git
cd django-rest-auth/demo/
pip install -r requirements.pip
python manage.py migrate --settings=demo.settings --noinput
python manage.py runserver --settings=demo.settings
```

Now, go to <http://127.0.0.1:8000/> in your browser.

## FAQ

1. Why `account_confirm_email` url is defined but it is not usable?

In `/rest_auth/registration/urls.py` we can find something like this:

```
url(r'^account-confirm-email/(?P<key>[-:\w]+)/$', TemplateView.as_view(),
    name='account_confirm_email'),
```

This url is used by `django-allauth`. Empty `TemplateView` is defined just to allow `reverse()` call inside app - when email with verification link is being sent.

You should override this view/url to handle it in your API client somehow and then, send post to `/verify-email/` endpoint with proper key. If you don't want to use API on that step, then just use `ConfirmEmailView` view from: `django-allauth` <https://github.com/pennersr/django-allauth/blob/master/allauth/account/views.py>

2. I get an error: Reverse for 'password\_reset\_confirm' not found.

You need to add `password_reset_confirm` url into your `urls.py` (at the top of any other included urls). Please check the `urls.py` module inside demo app example for more details.

3. How can I update `UserProfile` assigned to `User` model?

Assuming you already have `UserProfile` model defined like this

```
from django.db import models
from django.contrib.auth.models import User

class UserProfile(models.Model):
    user = models.OneToOneField(User)
    # custom fields for user
    company_name = models.CharField(max_length=100)
```

To allow update user details within one request send to `rest_auth.views.UserDetailsView` view, create serializer like this:

```
from rest_framework import serializers
from rest_auth.serializers import UserDetailsSerializer

class UserSerializer(UserDetailsSerializer):

    company_name = serializers.CharField(source="userprofile.company_name"
↪)

    class Meta(UserDetailsSerializer.Meta):
        fields = UserDetailsSerializer.Meta.fields + ('company_name',)
```

```

def update(self, instance, validated_data):
    profile_data = validated_data.pop('userprofile', {})
    company_name = profile_data.get('company_name')

    instance = super(UserSerializer, self).update(instance, validated_
↔data)

    # get and update user profile
    profile = instance.userprofile
    if profile_data and company_name:
        profile.company_name = company_name
        profile.save()
    return instance

```

And setup `USER_DETAILS_SERIALIZER` in django settings:

```

REST_AUTH_SERIALIZERS = {
    'USER_DETAILS_SERIALIZER': 'demo.serializers.UserSerializer'
}

```

## Changelog

### 0.9.2

- added permission classes configuration for registration
- added more info to JWT docs
- added Polish translations

### 0.9.1

- fixed import error when extending rest\_auth serializers
- added sensitive fields decorator
- added Spanish translations

### 0.9.0

- allowed using custom UserDetailsSerializer with JWTSerializer
- fixed error with logout on GET
- updated api endpoints and configuration docs
- bugfixes
- minor text fixes

### 0.8.2

- fixed allauth import error

- added swagger docs to demo project

### 0.8.1

- added support for django-allauth hmac email confirmation pattern

### 0.8.0

- added support for django-rest-framework-jwt
- bugfixes

### 0.7.0

- Wrapped API returned strings in `ugettext_lazy`
- Fixed not using `get_username` which caused issues when using custom user model without username field
- Django 1.9 support
- Added `TwitterLoginSerializer`

### 0.6.0

- dropped support for Python 2.6
- dropped support for Django 1.6
- fixed demo code
- added better validation support for serializers
- added optional logout after password change
- compatibility fixes
- bugfixes

### 0.5.0

- replaced `request.DATA` with `request.data` for compatibility with DRF 3.2
- authorization codes for social login
- view classes rename (appended “View” to all of them)
- bugfixes

### 0.4.0

- Django 1.8 compatibility fixes



### 0.3.4

- fixed bug in PasswordResetConfirmation serializer (token field wasn't validated)
- fixed bug in Register view

### 0.3.3

- support django-rest-framework v3.0

### 0.3.2

- fixed few minor bugs

### 0.3.1

- added old\_password field in PasswordChangeSerializer
- make all endpoints browsable
- removed LoggedInRESTAPIView, LoggedOutRESTAPIView
- fixed minor bugs

### 0.3.0

- replaced `django-registration` with `django-allauth`
- moved registration logic to separated django application (`rest_auth.registration`)
- added serializers customization in django settings
- added social media authentication view
- changed request method from GET to POST in logout endpoint
- changed request method from POST to PUT/PATCH for user details edition
- changed password reset confirm url - uid and token should be sent in POST
- increase test coverage
- made compatible with django 1.7
- removed user profile support