
Cartographer Documentation

Release 1.0.0

The Cartographer Authors

Aug 17, 2017

1	Configuration	1
1.1	cartographer.common.proto.CeresSolverOptions	1
1.2	cartographer.mapping.proto.MapBuilderOptions	1
1.3	cartographer.mapping.proto.SparsePoseGraphOptions	1
1.4	cartographer.mapping.proto.TrajectoryBuilderOptions	2
1.5	cartographer.mapping.sparse_pose_graph.proto.ConstraintBuilderOptions	2
1.6	cartographer.mapping.sparse_pose_graph.proto.OptimizationProblemOptions	3
1.7	cartographer.mapping_2d.proto.LocalTrajectoryBuilderOptions	3
1.8	cartographer.mapping_2d.proto.RangeDataInserterOptions	4
1.9	cartographer.mapping_2d.proto.SubmapsOptions	4
1.10	cartographer.mapping_2d.scan_matching.proto.CeresScanMatcherOptions	4
1.11	cartographer.mapping_2d.scan_matching.proto.FastCorrelativeScanMatcherOptions	4
1.12	cartographer.mapping_2d.scan_matching.proto.RealTimeCorrelativeScanMatcherOptions	4
1.13	cartographer.mapping_3d.proto.LocalTrajectoryBuilderOptions	5
1.14	cartographer.mapping_3d.proto.MotionFilterOptions	5
1.15	cartographer.mapping_3d.proto.RangeDataInserterOptions	5
1.16	cartographer.mapping_3d.proto.SubmapsOptions	6
1.17	cartographer.mapping_3d.scan_matching.proto.CeresScanMatcherOptions	6
1.18	cartographer.mapping_3d.scan_matching.proto.FastCorrelativeScanMatcherOptions	6
1.19	cartographer.sensor.proto.AdaptiveVoxelFilterOptions	6
2	Getting started	7
2.1	Getting started with ROS	7
2.2	Getting started without ROS	7
3	System Requirements	9
3.1	Known Issues	9
4	How to cite us	11

cartographer.common.proto.CeresSolverOptions

bool use_nonmonotonic_steps Configure the Ceres solver. See the Ceres documentation for more information: <https://code.google.com/p/ceres-solver/>

int32 max_num_iterations Not yet documented.

int32 num_threads Not yet documented.

cartographer.mapping.proto.MapBuilderOptions

bool use_trajectory_builder_2d Not yet documented.

bool use_trajectory_builder_3d Not yet documented.

int32 num_background_threads Number of threads to use for background computations.

cartographer.mapping.proto.SparsePoseGraphOptions sparse_pose_graph_options Not yet documented.

cartographer.mapping.proto.SparsePoseGraphOptions

int32 optimize_every_n_scans Online loop closure: If positive, will run the loop closure while the map is built.

cartographer.mapping.sparse_pose_graph.proto.ConstraintBuilderOptions constraint_builder_options
Options for the constraint builder.

double matcher_translation_weight Weight used in the optimization problem for the translational component of non-loop-closure scan matcher constraints.

double matcher_rotation_weight Weight used in the optimization problem for the rotational component of non-loop-closure scan matcher constraints.

cartographer.mapping.sparse_pose_graph.proto.OptimizationProblemOptions optimization_problem_options
Options for the optimization problem.

int32 max_num_final_iterations Number of iterations to use in ‘optimization_problem_options’ for the final optimization.

double global_sampling_ratio Rate at which we sample a single trajectory’s scans for global localization.

cartographer.mapping.proto.TrajectoryBuilderOptions

cartographer.mapping_2d.proto.LocalTrajectoryBuilderOptions trajectory_builder_2d_options Not yet documented.

cartographer.mapping_3d.proto.LocalTrajectoryBuilderOptions trajectory_builder_3d_options Not yet documented.

bool pure_localization Not yet documented.

cartographer.mapping.sparse_pose_graph.proto.ConstraintBuilderOptions

double sampling_ratio A constraint will be added if the proportion of added constraints to potential constraints drops below this number.

double max_constraint_distance Threshold for poses to be considered near a submap.

cartographer.sensor.proto.AdaptiveVoxelFilterOptions adaptive_voxel_filter_options Voxel filter used to compute a sparser point cloud for matching.

double min_score Threshold for the scan match score below which a match is not considered. Low scores indicate that the scan and map do not look similar.

double global_localization_min_score Threshold below which global localizations are not trusted.

double loop_closure_translation_weight Weight used in the optimization problem for the translational component of loop closure constraints.

double loop_closure_rotation_weight Weight used in the optimization problem for the rotational component of loop closure constraints.

bool log_matches If enabled, logs information of loop-closing constraints for debugging.

cartographer.mapping_2d.scan_matching.proto.FastCorrelativeScanMatcherOptions fast_correlative_scan_matcher_options
Options for the internally used scan matchers.

cartographer.mapping_2d.scan_matching.proto.CeresScanMatcherOptions ceres_scan_matcher_options Not yet documented.

cartographer.mapping_3d.scan_matching.proto.FastCorrelativeScanMatcherOptions fast_correlative_scan_matcher_options_3d
Not yet documented.

cartographer.sensor.proto.AdaptiveVoxelFilterOptions high_resolution_adaptive_voxel_filter_options Voxel filter used for high resolution, 3D loop closure refinement.

cartographer.sensor.proto.AdaptiveVoxelFilterOptions low_resolution_adaptive_voxel_filter_options Voxel filter used for low resolution, 3D loop closure refinement.

cartographer.mapping_3d.scan_matching.proto.CeresScanMatcherOptions ceres_scan_matcher_options_3d
Not yet documented.

cartographer.mapping.sparse_pose_graph.proto.OptimizationProblemOptions

double huber_scale Scaling parameter for Huber loss function.

double acceleration_weight Scaling parameter for the IMU acceleration term.

double rotation_weight Scaling parameter for the IMU rotation term.

double consecutive_scan_translation_penalty_factor Penalty factors for changes to the relative pose between consecutive scans.

double consecutive_scan_rotation_penalty_factor Not yet documented.

bool log_solver_summary If true, the Ceres solver summary will be logged for every optimization.

cartographer.common.proto.CeresSolverOptions ceres_solver_options Not yet documented.

cartographer.mapping_2d.proto.LocalTrajectoryBuilderOptions

float min_range Rangefinder points outside these ranges will be dropped.

float max_range Not yet documented.

float min_z Not yet documented.

float max_z Not yet documented.

float missing_data_ray_length Points beyond 'max_range' will be inserted with this length as empty space.

int32 scans_per_accumulation Number of scans to accumulate into one unwarped, combined scan to use for scan matching.

float voxel_filter_size Voxel filter that gets applied to the range data immediately after cropping.

cartographer.sensor.proto.AdaptiveVoxelFilterOptions adaptive_voxel_filter_options Voxel filter used to compute a sparser point cloud for matching.

bool use_online_correlative_scan_matching Whether to solve the online scan matching first using the correlative scan matcher to generate a good starting point for Ceres.

cartographer.mapping_2d.scan_matching.proto.RealTimeCorrelativeScanMatcherOptions real_time_correlative_scan_matcher_options Not yet documented.

cartographer.mapping_2d.scan_matching.proto.CeresScanMatcherOptions ceres_scan_matcher_options Not yet documented.

cartographer.mapping_3d.proto.MotionFilterOptions motion_filter_options Not yet documented.

double imu_gravity_time_constant Time constant in seconds for the orientation moving average based on observed gravity via the IMU. It should be chosen so that the error 1. from acceleration measurements not due to gravity (which gets worse when the constant is reduced) and 2. from integration of angular velocities (which gets worse when the constant is increased) is balanced.

cartographer.mapping_2d.proto.SubmapsOptions submaps_options Not yet documented.

bool use_imu_data True if IMU data should be expected and used.

cartographer.mapping_2d.proto.RangeDataInserterOptions

double hit_probability Probability change for a hit (this will be converted to odds and therefore must be greater than 0.5).

double miss_probability Probability change for a miss (this will be converted to odds and therefore must be less than 0.5).

bool insert_free_space If 'false', free space will not change the probabilities in the occupancy grid.

cartographer.mapping_2d.proto.SubmapsOptions

double resolution Resolution of the map in meters.

int32 num_range_data Number of scans before adding a new submap. Each submap will get twice the number of scans inserted: First for initialization without being matched against, then while being matched.

cartographer.mapping_2d.proto.RangeDataInserterOptions range_data_inserter_options Not yet documented.

cartographer.mapping_2d.scan_matching.proto.CeresScanMatcherOptions

double occupied_space_weight Scaling parameters for each cost functor.

double translation_weight Not yet documented.

double rotation_weight Not yet documented.

cartographer.common.proto.CeresSolverOptions ceres_solver_options Configure the Ceres solver. See the Ceres documentation for more information: <https://code.google.com/p/ceres-solver/>

cartographer.mapping_2d.scan_matching.proto.FastCorrelativeScanMatcherOptions

double linear_search_window Minimum linear search window in which the best possible scan alignment will be found.

double angular_search_window Minimum angular search window in which the best possible scan alignment will be found.

int32 branch_and_bound_depth Number of precomputed grids to use.

cartographer.mapping_2d.scan_matching.proto.RealTimeCorrelativeScanMatcherOptions

double linear_search_window Minimum linear search window in which the best possible scan alignment will be found.

double angular_search_window Minimum angular search window in which the best possible scan alignment will be found.

double translation_delta_cost_weight Weights applied to each part of the score.

double rotation_delta_cost_weight Not yet documented.

cartographer.mapping_3d.proto.LocalTrajectoryBuilderOptions

float min_range Rangefinder points outside these ranges will be dropped.

float max_range Not yet documented.

int32 scans_per_accumulation Number of scans to accumulate into one unwarped, combined scan to use for scan matching.

float voxel_filter_size Voxel filter that gets applied to the range data immediately after cropping.

cartographer.sensor.proto.AdaptiveVoxelFilterOptions high_resolution_adaptive_voxel_filter_options Voxel filter used to compute a sparser point cloud for matching.

cartographer.sensor.proto.AdaptiveVoxelFilterOptions low_resolution_adaptive_voxel_filter_options Not yet documented.

bool use_online_correlative_scan_matching Whether to solve the online scan matching first using the correlative scan matcher to generate a good starting point for Ceres.

cartographer.mapping_2d.scan_matching.proto.RealTimeCorrelativeScanMatcherOptions real_time_correlative_scan_matcher_options Not yet documented.

cartographer.mapping_3d.scan_matching.proto.CeresScanMatcherOptions ceres_scan_matcher_options Not yet documented.

cartographer.mapping_3d.proto.MotionFilterOptions motion_filter_options Not yet documented.

double imu_gravity_time_constant Time constant in seconds for the orientation moving average based on observed gravity via the IMU. It should be chosen so that the error 1. from acceleration measurements not due to gravity (which gets worse when the constant is reduced) and 2. from integration of angular velocities (which gets worse when the constant is increased) is balanced.

cartographer.mapping_3d.proto.SubmapsOptions submaps_options Not yet documented.

cartographer.mapping_3d.proto.MotionFilterOptions

double max_time_seconds Threshold above which a new scan is inserted based on time.

double max_distance_meters Threshold above which a new scan is inserted based on linear motion.

double max_angle_radians Threshold above which a new scan is inserted based on rotational motion.

cartographer.mapping_3d.proto.RangeDataInserterOptions

double hit_probability Probability change for a hit (this will be converted to odds and therefore must be greater than 0.5).

double miss_probability Probability change for a miss (this will be converted to odds and therefore must be less than 0.5).

int32 num_free_space_voxels Up to how many free space voxels are updated for scan matching. 0 disables free space.

cartographer.mapping_3d.proto.SubmapsOptions

double high_resolution Resolution of the ‘high_resolution’ map in meters used for local SLAM and loop closure.

double high_resolution_max_range Maximum range to filter the point cloud to before insertion into the ‘high_resolution’ map.

double low_resolution Resolution of the ‘low_resolution’ version of the map in meters used for local SLAM only.

int32 num_range_data Number of scans before adding a new submap. Each submap will get twice the number of scans inserted: First for initialization without being matched against, then while being matched.

cartographer.mapping_3d.proto.RangeDataInserterOptions range_data_inserter_options Not yet documented.

cartographer.mapping_3d.scan_matching.proto.CeresScanMatcherOptions

double translation_weight Scaling parameters for each cost functor.

double rotation_weight Not yet documented.

bool only_optimize_yaw Whether only to allow changes to yaw, keeping roll/pitch constant.

cartographer.common.proto.CeresSolverOptions ceres_solver_options Configure the Ceres solver. See the Ceres documentation for more information: <https://code.google.com/p/ceres-solver/>

cartographer.mapping_3d.scan_matching.proto.FastCorrelativeScanMatcherOptions

int32 branch_and_bound_depth Number of precomputed grids to use.

int32 full_resolution_depth Number of full resolution grids to use, additional grids will reduce the resolution by half each.

int32 rotational_histogram_size Number of histogram buckets for the rotational scan matcher.

double min_rotational_score Minimum score for the rotational scan matcher.

double linear_xy_search_window Linear search window in the plane orthogonal to gravity in which the best possible scan alignment will be found.

double linear_z_search_window Linear search window in the gravity direction in which the best possible scan alignment will be found.

double angular_search_window Minimum angular search window in which the best possible scan alignment will be found.

cartographer.sensor.proto.AdaptiveVoxelFilterOptions

float max_length ‘max_length’ of a voxel edge.

float min_num_points If there are more points and not at least ‘min_num_points’ remain, the voxel length is reduced trying to get this minimum number of points.

float max_range Points further away from the origin are removed.

Cartographer is a system that provides real-time simultaneous localization and mapping (SLAM) in 2D and 3D across multiple platforms and sensor configurations.

Cartographer is a standalone C++ library. To get started quickly, use our [ROS](#) integration.

Getting started with ROS

ROS integration is provided by the [Cartographer ROS repository](#). You will find complete documentation for using Cartographer with ROS at the [Cartographer ROS Read the Docs site](#).

Getting started without ROS

Please see our ROS integration as a starting point for integrating your system with the standalone library. Currently, it is the best available reference.

On Ubuntu 14.04 (Trusty):

```
1 # Install the required libraries that are available as debs.
2 sudo apt-get update
3 sudo apt-get install -y \
4     cmake \
5     g++ \
6     git \
7     google-mock \
8     libboost-all-dev \
9     libcairo2-dev \
10    libeigen3-dev \
11    libgflags-dev \
12    libgoogle-glog-dev \
13    liblua5.2-dev \
14    libprotobuf-dev \
15    libsuitesparse-dev \
16    ninja-build \
```

```
17  protobuf-compiler \  
18  python-sphinx
```

```
1  # Build and install Ceres.  
2  git clone https://ceres-solver.googlesource.com/ceres-solver  
3  cd ceres-solver  
4  mkdir build  
5  cd build  
6  cmake .. -G Ninja  
7  ninja  
8  ninja test  
9  sudo ninja install
```

```
1  # Build and install Cartographer.  
2  cd cartographer  
3  mkdir build  
4  cd build  
5  cmake .. -G Ninja  
6  ninja  
7  ninja test  
8  sudo ninja install
```

System Requirements

Although Cartographer may run on other systems, it is confirmed to be working on systems that meet the following requirements:

- 64-bit, modern CPU (e.g. 3rd generation i7)
- 16 GB RAM
- Ubuntu 14.04 (Trusty) and 16.04 (Xenial)
- gcc version 4.8.4 and 5.4.0

Known Issues

- 32-bit builds have libeigen alignment problems which cause crashes and/or memory corruptions.

CHAPTER 4

How to cite us

Background about the algorithms developed for Cartographer can be found in the following publication. If you use Cartographer for your research, we would appreciate it if you cite our paper.

W. Hess, D. Kohler, H. Rapp, and D. Andor, [Real-Time Loop Closure in 2D LIDAR SLAM](#), in *Robotics and Automation (ICRA), 2016 IEEE International Conference on*. IEEE, 2016. pp. 1271–1278.