
IPython Kernel Documentation

Release 4.7.0.dev

IPython Development Team

Sep 18, 2017

Contents

1	Changes in IPython kernel	3
1.1	4.7	3
1.2	4.6	3
1.3	4.5	4
1.4	4.4	5
1.5	4.3	5
1.6	4.2	6
1.7	4.1	6
1.8	4.0	7
2	Indices and tables	9

This contains minimal version-sensitive documentation for the IPython kernel package. Most IPython kernel documentation is in the [IPython documentation](#).

Contents:

Changes in IPython kernel

4.7

4.7.0

[4.7.0 on GitHub](#)

- Add event loop integration for `asyncio`.
- Use the new IPython completer API.
- Add support for displaying GIF images (`mimetype image/gif`).

4.6

4.6.1

[4.6.1 on GitHub](#)

- Fix eventloop-integration bug preventing Qt windows/widgets from displaying with ipykernel 4.6.0 and IPython 5.2.
- Avoid deprecation warnings about naive datetimes when working with `jupyter_client` 5.0.

4.6.0

[4.6.0 on GitHub](#)

- Add to `API DisplayPublisher.publish` two new fully backward-compatible keyword-args:
 - `update: bool`
 - `transient: dict`

- Support new `transient` key in `display_data` messages spec for `publish`. For a `display_data` message, `transient` contains data that shouldn't be persisted to files or documents. Add a `display_id` to this transient dict by `display(obj, display_id=...)`
- Add `ipykernel_launcher` module which removes the current working directory from `sys.path` before launching the kernel. This helps to reduce the cases where the kernel won't start because there's a `random.py` (or similar) module in the current working directory.
- Add busy/idle messages on IOPub during processing of aborted requests
- Add active event loop setting to GUI, which enables the correct response to IPython's `is_event_loop_running_XXX`
- Include IPython kernelspec in wheels to reduce reliance on “native kernel spec” in `jupyter_client`
- Modify `OutStream` to inherit from `TextIOBase` instead of object to improve API support and error reporting
- Fix IPython kernel death messages at start, such as “Kernel Restarting...” and “Kernel appears to have died”, when parent-poller handles PID 1
- Various bugfixes

4.5

4.5.2

[4.5.2 on GitHub](#)

- Fix bug when instantiating Comms outside of the IPython kernel (introduced in 4.5.1).

4.5.1

[4.5.1 on GitHub](#)

- Add missing `stream` parameter to overridden `getpass()`
- Remove locks from `iopub` thread, which could cause deadlocks during debugging
- Fix regression where `KeyboardInterrupt` was treated as an aborted request, rather than an error
- Allow instantiating Comms outside of the IPython kernel

4.5.0

[4.5 on GitHub](#)

- Use `figure.dpi` instead of `savefig.dpi` to set DPI for inline figures
- Support `ipympl` matplotlib backend (requires IPython update as well to fully work)
- Various bugfixes, including fixes for output coming from threads, and `input()` when called with non-string prompts, which `stdlib` allows.

4.4

4.4.1

[4.4.1 on GitHub](#)

- Fix circular import of matplotlib on Python 2 caused by the inline backend changes in 4.4.0.

4.4.0

[4.4.0 on GitHub](#)

- Use `MPLBACKEND` environment variable to tell matplotlib ≥ 1.5 use the inline backend by default. This is only done if `MPLBACKEND` is not already set and no backend has been explicitly loaded, so setting `MPLBACKEND=Qt4Agg` or calling `%matplotlib notebook` or `matplotlib.use('Agg')` will take precedence.
- Fixes for logging problems caused by 4.3, where logging could go to the terminal instead of the notebook.
- Add `--sys-prefix` and `--profile` arguments to **ipython kernel install**
- Allow Comm (Widget) messages to be sent from background threads.
- Select inline matplotlib backend by default if `%matplotlib magic` or `matplotlib.use()` are not called explicitly (for matplotlib ≥ 1.5).
- Fix some longstanding minor deviations from the message protocol (missing status: ok in a few replies, connect_reply format).
- Remove calls to `NoOpContext` from IPython, deprecated in 5.0.

4.3

4.3.2

- Use a nonempty dummy session key for inprocess kernels to avoid security warnings.

4.3.1

- Fix Windows Python 3.5 incompatibility caused by fault handler patch in 4.3

4.3.0

[4.3.0 on GitHub](#)

- Publish all IO in a thread, via `IOPubThread`. This solves the problem of requiring `sys.stdout.flush()` to be called in the notebook to produce output promptly during long-running cells.
- Remove references to outdated IPython `gui` in kernel banner.
- Patch fault handler to use `sys.__stderr__` instead of forwarded `sys.stderr`, which has no file no when forwarded.

- Deprecate some vestiges of the Big Split: - `ipykernel.find_connection_file()` is deprecated. Use `jupyter_client.find_connection_file()` instead. - Various pieces of code specific to IPython parallel are deprecated in `ipykernel` and moved to `ipyparallel`.

4.2

4.2.2

[4.2.2 on GitHub](#)

- Don't show interactive debugging info when kernel crashes
- Fix handling of numerical types in `json_clean`
- Testing fixes for output capturing

4.2.1

[4.2.1 on GitHub](#)

- Fix default display name back to “Python X” instead of “pythonX”

4.2.0

[4.2 on GitHub](#)

- Support sending a full message in initial opening of comms (metadata, buffers were not previously allowed)
- When using `ipython kernel install --name` to install the IPython kernelspec, default `display-name` to the same value as `--name`.

4.1

4.1.1

[4.1.1 on GitHub](#)

- Fix missing `ipykernel.__version__` on Python 2.
- Fix missing `target_name` when opening comms from the frontend.

4.1.0

[4.1 on GitHub](#)

- add `ipython kernel install` entrypoint for installing the IPython kernelspec
- provisional implementation of `comm_info` request/reply for msgspec v5.1

4.0

[4.0 on GitHub](#)

4.0 is the first release of ipykernel as a standalone package.

CHAPTER 2

Indices and tables

- `genindex`
- `modindex`
- `search`