

---

# Plone Jenkins/CI Team

*Release 1.0*

May 09, 2018



---

# Contents

---

<b>1</b>	<b>PLONE JENKINS/CI TEAM</b>	<b>1</b>
1.1	Who's on the team . . . . .	1
1.2	Who leads it . . . . .	1
1.3	What is the mission of the team . . . . .	2
1.4	What is the team doing, why the team exists . . . . .	2
1.5	How to contact the team . . . . .	2
1.6	How the activities are organized . . . . .	2
1.7	How to become part of the team . . . . .	2
<b>2</b>	<b>Servers</b>	<b>3</b>
2.1	Master . . . . .	3
2.2	Nodes . . . . .	3
<b>3</b>	<b>jenkins.plone.org Set Up Howto</b>	<b>7</b>
3.1	Prerequisites . . . . .	7
<b>4</b>	<b>Testing locally (vagrant)</b>	<b>11</b>
4.1	Set up . . . . .	11
<b>5</b>	<b>Run pull request jobs</b>	<b>13</b>
5.1	Test a pull request . . . . .	13
5.2	GitHub integration . . . . .	14
5.3	Mail integration . . . . .	14
<b>6</b>	<b>Run code analysis on a package</b>	<b>15</b>
<b>7</b>	<b>Run add-on jobs</b>	<b>17</b>
7.1	Test an add-on . . . . .	17
7.2	GitHub integration . . . . .	18
7.3	Mail integration . . . . .	18
<b>8</b>	<b>Indices and tables</b>	<b>19</b>



### 1.1 Who's on the team

- Ramiro B. da Luz
- Jonas Baumann
- William Deegan
- Thomas Desvain
- Gil Forcada
- Tom Gross
- Ed Manlove
- Ramon Navarro Bosch
- Ross Patterson
- Martin Peeters
- Asko Soukka
- Eric Steele
- Timo Stollenwerk
- Héctor Velarde

### 1.2 Who leads it

Timo Stollenwerk < tisto @ plone.org >

## 1.3 What is the mission of the team

- Running automated software tests and code analysis for Plone core, Plone core projects and selected Plone add-ons
- Notifying developers about regressions and code quality

## 1.4 What is the team doing, why the team exists

- What we are doing: running [jenkins.plone.org](https://jenkins.plone.org)
- Why do we exist: to ensure a high software quality for Plone

## 1.5 How to contact the team

- We currently use the plone-website mailinglist: [plone-website@lists.sourceforge.net](mailto:plone-website@lists.sourceforge.net)

## 1.6 How the activities are organized

- See <https://github.com/plone/jenkins.plone.org> and <https://github.com/plone/jenkins.plone.org/issues> for current activities
- We currently do not have regular meetings

## 1.7 How to become part of the team

- Send an email to [tisto @ plone.org](mailto:tisto@plone.org) or ping me on irc (tisto)

<http://jenkins.plone.org> runs on a number of different servers, see below.

### 2.1 Master

- hosted at hetzner.de
- IP: 78.47.49.108
- donor: Timo Stollenwerk
- contact: Timo Stollenwerk (tisto) and Gil Forcada (gforcada)

### 2.2 Nodes

#### 2.2.1 Nodes server

- hosted at hetzner.de
- IP: 88.99.26.113 / 2a01:4f8:10a:2ae::2
- donor: Plone Foundation
- contact: Paul Roeland (polyester) and Gil Forcada (gforcada)

#### Configuration

Base system: Ubuntu 16.04 LTS minimal

Install lxd:

```
apt-get install lxd
```

Initial configuration:

```
lxd init
(all default options)
```

Create nodes:

```
lxc launch ubuntu:16.04 node1
lxc launch ubuntu:16.04 node2
lxc launch ubuntu:16.04 node3
```

Add SSH keys:

```
lxc file push /root/.ssh/authorized_keys node1/root/.ssh/authorized_keys
lxc file push /root/.ssh/authorized_keys node2/root/.ssh/authorized_keys
lxc file push /root/.ssh/authorized_keys node3/root/.ssh/authorized_keys
```

Write down nodes IPs:

```
lxc list
```

Configure a jump host to connect to them:

```
Host jenkins-plone-org-nodes-host
  HostName 88.99.26.113
  User root
  ProxyCommand none

Host node1-jenkins-plone-org
  HostName XX.XX.XX.XX
  User root
  ProxyCommand ssh jenkins-plone-org-nodes-host nc %h %p 2> /dev/null

Host node2-jenkins-plone-org
  HostName XX.XX.XX.XX
  User root
  ProxyCommand ssh jenkins-plone-org-nodes-host nc %h %p 2> /dev/null

Host node3-jenkins-plone-org
  HostName XX.XX.XX.XX
  User root
  ProxyCommand ssh jenkins-plone-org-nodes-host nc %h %p 2> /dev/null
```

Connect to all nodes to accept their fingerprint:

```
ssh node1-jenkins-plone-org
ssh node2-jenkins-plone-org
ssh node3-jenkins-plone-org
```

Install python 2.7 (as ansible still needs it):

```
ssh node1-jenkins-plone-org "apt-get update && apt-get install -y python2.7"
ssh node2-jenkins-plone-org "apt-get update && apt-get install -y python2.7"
ssh node3-jenkins-plone-org "apt-get update && apt-get install -y python2.7"
```

Add iptables rules to let jenkins master connect to the nodes, these two lines are needed **for each** node:



```
iptables -t nat -A PREROUTING -p tcp --dport ${SPECIFIC_PORT} -j DNAT --to-destination ${NODE_IP}:22
iptables -t nat -A POSTROUTING -p tcp -d ${NODE_IP} --dport ${SPECIFIC_PORT} -j SNAT --to-source ${SERVER_IP}
```

---

**Note:** update SPECIFIC\_PORT to something like 808X (each node a different port), NODE\_IP to the IP of each node (node IP can be seen with `lxc list`) and SERVER\_IP to the server host (i.e. 88.99.26.113)

---

## TODO

- create ansible playbook for bootstrap the server so it does:
  - create containers with ansible
  - configure SSH
  - install python2.7 on containers
  - configure firewall



---

## jenkins.plone.org Set Up Howto

---

This document describes how to set up the entire Jenkins infrastructure for jenkins.plone.org. Those are the main steps:

- Set up Jenkins server (jenkins.plone.org, with Ansible)
- Set up Jenkins nodes (node[1-x].jenkins.plone.org, with Ansible)
- Set up the Jenkins jobs on the Jenkins server (with Jenkins Job Builder)

### 3.1 Prerequisites

Checkout this repository:

```
$ git clone git@github.com:plone/jenkins.plone.org.git
$ cd jenkins.plone.org
```

Create and activate a virtualenv:

```
$ virtualenv -p python2.7 .
$ source ./bin/activate
```

Install all the tools needed (ansible, ansible roles and jenkins-job-builder):

```
$ pip install -r requirements.txt
$ ansible-galaxy install -r ansible/roles.yml
$ git submodule update --init
```

---

**Note:** For the roles that are downloaded from checkouts, plone.jenkins\_server and plone.jenkins\_node, you will need to remove them and clone them manually if you want to make changes on them.

```
$ cd ansible/roles
$ rm -rf plone.jenkins_server
$ rm -rf plone.jenkins_node
$ git clone git@github.com:plone/plone.jenkins_server
$ git clone git@github.com:plone/plone.jenkins_node
```

Check `ansible/inventory.txt` and make sure that you can connect to the machines listed there.

Copy your public ssh key to all servers:

```
$ ssh-copy-id -i ~/.ssh/<SSH-KEY>.pub root@<SERVER_IP>
```

### 3.1.1 Set Up Jenkins Server

```
$ ./update_master.sh
```

### 3.1.2 Set Up Jenkins Nodes

```
$ ./update_nodes.sh
```

### 3.1.3 Set Up Jenkins Jobs

*Do the steps described above to clone, activate `virtualenv` and fetch submodules.*

Put `jenkins-job-builder` in development mode:

```
$ cd src/jenkins-job-builder
$ pip install -r requirements.txt
$ python setup.py develop
```

Test the jobs are properly setup:

```
$ jenkins-jobs --conf jobs/config.ini.in test jobs/jobs.yml -o output
```

---

**Note:** A folder named `output` should contain one file per each jenkins job configured on `jobs.yml`

---

Create your own `jobs/config.ini` by copying it from `jobs/config.ini.in`:

```
$ cp jobs/config.ini.in jobs/config.ini
```

Add your own credentials to `jobs/config.ini`. You can find them when you log into Jenkins and copy your API token (e.g. <http://jenkins.plone.org/user/tisto/configure>).

Create your own `ansible/secrets.yml` by copying it from `ansible/secrets.yml.in`:

```
$ cp ansible/secrets.yml.in ansible/secrets.yml
```

Add github API secrets that are needed for the github login functionality on `jenkins.plone.org`. You can find those settings on plone organization in github: <https://github.com/organizations/plone/settings/applications>

Look for the Plone Jenkins CI application name.

For the `github_api_key` you need a personal token (from <https://github.com/jenkins-plone-org> github user).

Now finally install the jobs on the server:

```
$ ./update_jobs.sh
```

### 3.1.4 Manual Configuration

There are currently a few steps that we need to carry out manually. We will automate them later.

1. Github post-commit hook for buildout.coredev:

- go to <https://github.com/plone/buildout.coredev/settings/hooks>
- create a new webhook with the following details:
  - Payload URL: <http://jenkins.plone.org/github-webhook/>
  - Content type: `application/x-www-form-urlencoded`
  - Secret: *nothing*
  - Which events would you like to trigger this webhook?: Send me everything
  - Active: yes

2. Manage Jenkins -> Configure System:

- E-mail Notification:
  - SMTP Server: `smtp.gmail.com`
  - Use SSL: `True`
  - SMTP Port: `465`
  - Reply-To Address: `jenkins@plone.org`
  - Use SMTP Authentication: `True`
    - \* User Name: `jenkins@plone.org`
    - \* Password: ...

3. Manage Jenkins -> Manage Credentials -> Add Credentials: SSH Username with private key:

- Scope: `System`
- Username: `jenkins`
- Description: `jenkins.plone.org private ssh key`
- Private Key: From a file on Jenkins master: File: `/var/lib/jenkins/jenkins.plone.org`

=> Upload `jenkins.plone.org` private ssh key manually to `/var/lib/jenkins` => `chown jenkins:jenkins jenkins.plone.org`



---

## Testing locally (vagrant)

---

As collaborative configuration of servers is really useful to spread knowledge, so it is also that one can step on each others toes, or not be sure if a server can be really be used for testing, or if others are *already* testing on it while you also want to test...

So to make it short and easy: having a local environment (i.e. virtual image) to test changes before sending a pull request is extremely helpful.

For this `vagrant` is a perfect fit.

### 4.1 Set up

- install `vagrant` and its dependencies and everything said on [jenkins.plone.org](http://jenkins.plone.org) *Set Up Howto*
- from within a clone of `jenkins.plone.org` repository checkout run:

```
vagrant up master
vagrant up node
```

`vagrant` will automatically run the ansible playbook for them.

If the playbook fails, run:

```
vagrant provision master
vagrant provision node
```

And that will re-run the ansible playbook once again, and hopefully fixing the previous problem.

You can enjoy your newly `jenkins.plone.org` master server locally at:

```
http://localhost:8080
```

---

**Note:** There seems to be some problems with `nginx`.

POST requests get the port (8080) removed on the response. Adding the port back on the wrong URL makes it work again.

---

Finally, to run `jenkins-job-builder` on it, run:

```
jenkins-jobs --conf jobs/config.ini.in update jobs/jobs.yml
```

*Enjoy!*



---

## Run pull request jobs

---

Before merging a pull request on GitHub (or manually via the command line), one needs to be sure that nothing breaks due to the changes made on the pull request.

For that we have some special jenkins job meant for that:

- If the pull request targets Plone 5.2: <http://jenkins.plone.org/job/pull-request-5.2>
- If the pull request targets Plone 5.1: <http://jenkins.plone.org/job/pull-request-5.1>
- If the pull request targets Plone 5.0: <http://jenkins.plone.org/job/pull-request-5.0>
- If the pull request targets Plone 4.3: <http://jenkins.plone.org/job/pull-request-4.3>

If the pull request targets **both** 5.2 *and* 5.1 you need to run a job on each of the jenkins jobs mentioned above.

### 5.1 Test a pull request

To test a pull request with this jenkins job, either:

- watch this video: [https://youtu.be/mXs\\_OcJhnU](https://youtu.be/mXs_OcJhnU)
- follow the detailed steps below

#### 5.1.1 Run a pull request job

- go to <http://jenkins.plone.org>
- log in with your github user
- click on the Pull Request 5.2 job or Pull Request 5.1 job or Pull Request 5.0 job or Pull Request 4.3 job if you are targeting that Plone version
- click on the huge button **Build with Parameters** Plone 5.2 or Plone 5.1 or Plone 5.0 or Plone 4.3
- paste the pull request URL on the text field (or multiple pull requests if they have to be combined, then one per line), like for example <https://github.com/plone/plone.outputfilters/pull/16>

- click on the `Build` button

## 5.2 GitHub integration

As soon as the job starts the pull request on GitHub will be notified, showing that the pull request is being tested by `jenkins.plone.org`.

When it finishes, GitHub will be notified again and either report that all tests passed, or that there has been some failures and thus it would not be wise to merge the pull request.

## 5.3 Mail integration

Reporting is not only done via GitHub, but also by email.

When the jenkins job is finished it will report by mail to the user that started the jenkins job.

On the mail, the status of the job and a link to the jenkins job itself and to the pull request(s) are provided for convenience.

---

## Run code analysis on a package

---

[jenkins.plone.org](http://jenkins.plone.org) is running code analysis (via [plone.recipe.codeanalysis](http://plone.recipe.codeanalysis)) on a number of packages, see the [up-to-date list](#).

Follow these steps to check how any arbitrary package adheres to our Plone official guidelines.

---

**Note:** See the [very same script](#) that Jenkins uses, below follows a more detailed step to step on how to run it and fix the errors.

---

Clone the repository and create a Python virtual environment:

```
git clone git@github.com:plone/plone.app.discussion.git
cd plone.app.discussion
virtualenv .
source bin/activate
```

Create a cleanup branch, although not mandatory it's always a good idea:

```
git checkout -b cleanup
```

Get the QA configuration and bootstrap:

```
wget https://raw.githubusercontent.com/plone/buildout.coredev/5.2/bootstrap.py -O bootstrap.py
↪ bootstrap.py
wget https://raw.githubusercontent.com/plone/buildout.coredev/5.2/experimental/qa.cfg -O qa.cfg
↪ -O qa.cfg
wget https://raw.githubusercontent.com/plone/plone.recipe.codeanalysis/master/.isort.cfg -O .isort.cfg
↪ cfg -O .isort.cfg

python bootstrap.py --setuptools-version 31.1.1 --buildout-version 2.8.0 -c qa.cfg
```

Adjust `qa.cfg` to the package:

- check that the `directory` option on `code-analysis` part matches the top-level folder of the distribution

- remove the `jenkins = True` line (so that `bin/code-analysis` shows its report on the terminal)

Finally run buildout and code analysis:

```
bin/buildout -c qa.cfg
bin/code-analysis
```

The first easy fixes can be easily solved with `autopep8` and `isort`:

```
pip install autopep8 isort

isort plone/app/discussion/*.py
autopep8 --in-place -r plone/app/discussion
```

By default `autopep8` does white space only changes which are basically guaranteed safe.

**Important** exception: undo any changes made by `autopep8` to Python **skin** scripts. For instance, it will change the double comment hashes at the top to single hashes, which completely break those Python scripts.

After committing the initial `autopep8` run, you can run `autopep8` in more aggressive mode, but you have to check these changes more carefully:

```
autopep8 --in-place --ignore W690,E711,E721 --aggressive
```

Keep running `bin/code-analysis` to see how much errors are still left to be fixed.

Once finished, add a comment on `CHANGES.rst` and commit all the changes in a single commit:

```
$EDITOR CHANGES.rst

git commit -am"Cleanup"
```

Push the branch:

```
git push -u
```

Create a pull request on github and start a jenkins job to verify that your changes did not break anything. For that, see the *docs about testing pull requests*.

Lastly file an issue on [jenkins.plone.org](https://jenkins.plone.org) issue tracker so that Jenkins start monitoring the package.

**Done! Thanks for cleaning one package!**

---

## Run add-on jobs

---

Before a final release of Plone core is done, add-ons might want to check if they need any porting effort to make the add-on compatible with it.

For that we have some special jenkins jobs:

- If the add-on targets Plone 5.1: <http://jenkins.plone.org/job/test-addon-5.1>
- If the add-on targets Plone 5.0: <http://jenkins.plone.org/job/test-addon-5.0>
- If the add-on targets Plone 4.3: <http://jenkins.plone.org/job/test-addon-4.3>

### 7.1 Test an add-on

- go to <http://jenkins.plone.org>
- log in with your github user
- click on the [Test add-on against Plone 5.2 job](#) or [Test add-on against Plone 5.1 job](#) or [Test add-on against Plone 5.0 job](#) or [Test add-on against Plone 4.3 job](#) if you are targeting that Plone version
- click on the huge button **Build with Parameters** [Plone 5.2](#) or [Plone 5.1](#) or [Plone 5.0](#) or [Plone 4.3](#)
- paste the add-on git URL for the add-on that you want to test on the `ADDON_URL` field, for example <https://github.com/collective/collective.cover.git>
- (*optionally*) type the branch you want to test the add-on against on the `ADDON_BRANCH` field, by default it will be the master branch
- click on the `Build` button

---

**Note:** For the jobs to work properly they need to get the add-on name out of the URL, for that, the last path of the URL will be used, i.e. <https://github.com/my-org/my-cool-repo.git> or <https://gitlab.com/another-org/project/something/else/my-cool-repo.git> If not the add-on name can not be guessed with a regular expression.

---

## 7.2 GitHub integration

A comment will be added on the latest commit on that branch once the job finishes.

## 7.3 Mail integration

When the jenkins job is finished it will report by mail to the user that started the jenkins job.

On the mail, the status of the job will be provided.

## CHAPTER 8

---

### Indices and tables

---

- `genindex`
- `modindex`
- `search`