
kafka-python Documentation

Release 1.4.3.dev

Dana Powers

May 23, 2018

Contents

1	KafkaConsumer	3
2	KafkaProducer	5
3	Thread safety	7
4	Compression	9
5	Protocol	11
6	Low-level	13
6.1	Usage	13
6.2	kafka-python API	15
6.3	Simple APIs (DEPRECATED)	38
6.4	Install	40
6.5	Tests	41
6.6	Compatibility	42
6.7	Support	43
6.8	License	43
6.9	Changelog	43

kafka-python is best used with newer brokers (0.9+), but is backwards-compatible with older versions (to 0.8.0). Some features will only be enabled on newer brokers. For example, fully coordinated consumer groups – i.e., dynamic partition assignment to multiple consumers in the same group – requires use of 0.9 kafka brokers. Supporting this feature for earlier broker releases would require writing and maintaining custom leadership election and membership / health check code (perhaps using zookeeper or consul). For older brokers, you can achieve something similar by manually assigning different partitions to each consumer instance with config management tools like chef, ansible, etc. This approach will work fine, though it does not support rebalancing on failures. See [Compatibility](#) for more details.

Please note that the master branch may contain unreleased features. For release documentation, please see [readthedocs](#) and/or python's inline help.

```
>>> pip install kafka-python
```

KafkaConsumer

`KafkaConsumer` is a high-level message consumer, intended to operate as similarly as possible to the official java client. Full support for coordinated consumer groups requires use of kafka brokers that support the Group APIs: kafka v0.9+.

See `KafkaConsumer` for API and configuration details.

The consumer iterator returns `ConsumerRecords`, which are simple namedtuples that expose basic message attributes: topic, partition, offset, key, and value:

```
>>> from kafka import KafkaConsumer
>>> consumer = KafkaConsumer('my_favorite_topic')
>>> for msg in consumer:
...     print (msg)
```

```
>>> # join a consumer group for dynamic partition assignment and offset commits
>>> from kafka import KafkaConsumer
>>> consumer = KafkaConsumer('my_favorite_topic', group_id='my_favorite_group')
>>> for msg in consumer:
...     print (msg)
```

```
>>> # manually assign the partition list for the consumer
>>> from kafka import TopicPartition
>>> consumer = KafkaConsumer(bootstrap_servers='localhost:1234')
>>> consumer.assign([TopicPartition('foobar', 2)])
>>> msg = next(consumer)
```

```
>>> # Deserialize msgpack-encoded values
>>> consumer = KafkaConsumer(value_deserializer=msgpack.loads)
>>> consumer.subscribe(['msgpackfoo'])
>>> for msg in consumer:
...     assert isinstance(msg.value, dict)
```


CHAPTER 2

KafkaProducer

KafkaProducer is a high-level, asynchronous message producer. The class is intended to operate as similarly as possible to the official java client. See [KafkaProducer](#) for more details.

```
>>> from kafka import KafkaProducer
>>> producer = KafkaProducer(bootstrap_servers='localhost:1234')
>>> for _ in range(100):
...     producer.send('foobar', b'some_message_bytes')
```

```
>>> # Block until a single message is sent (or timeout)
>>> future = producer.send('foobar', b'another_message')
>>> result = future.get(timeout=60)
```

```
>>> # Block until all pending messages are at least put on the network
>>> # NOTE: This does not guarantee delivery or success! It is really
>>> # only useful if you configure internal batching using linger_ms
>>> producer.flush()
```

```
>>> # Use a key for hashed-partitioning
>>> producer.send('foobar', key=b'foo', value=b'bar')
```

```
>>> # Serialize json messages
>>> import json
>>> producer = KafkaProducer(value_serializer=lambda v: json.dumps(v).encode('utf-8'))
>>> producer.send('fizzbuzz', {'foo': 'bar'})
```

```
>>> # Serialize string keys
>>> producer = KafkaProducer(key_serializer=str.encode)
>>> producer.send('flipflap', key='ping', value=b'1234')
```

```
>>> # Compress messages
>>> producer = KafkaProducer(compression_type='gzip')
```

(continues on next page)

(continued from previous page)

```
>>> for i in range(1000):  
...     producer.send('foobar', b'msg %d' % i)
```

CHAPTER 3

Thread safety

The `KafkaProducer` can be used across threads without issue, unlike the `KafkaConsumer` which cannot. While it is possible to use the `KafkaConsumer` in a thread-local manner, multiprocessing is recommended.

CHAPTER 4

Compression

kafka-python supports gzip compression/decompression natively. To produce or consume lz4 compressed messages, you should install python-lz4 (pip install lz4). To enable snappy, install python-snappy (also requires snappy library). See [Installation](#) for more information.

CHAPTER 5

Protocol

A secondary goal of kafka-python is to provide an easy-to-use protocol layer for interacting with kafka brokers via the python repl. This is useful for testing, probing, and general experimentation. The protocol support is leveraged to enable a `check_version()` method that probes a kafka broker and attempts to identify which version it is running (0.8.0 to 1.0).

Legacy support is maintained for low-level consumer and producer classes, SimpleConsumer and SimpleProducer.

6.1 Usage

6.1.1 KafkaConsumer

```
from kafka import KafkaConsumer

# To consume latest messages and auto-commit offsets
consumer = KafkaConsumer('my-topic',
                          group_id='my-group',
                          bootstrap_servers=['localhost:9092'])
for message in consumer:
    # message value and key are raw bytes -- decode if necessary!
    # e.g., for unicode: `message.value.decode('utf-8')`
    print ("%s:%d:%d: key=%s value=%s" % (message.topic, message.partition,
                                          message.offset, message.key,
                                          message.value))

# consume earliest available messages, don't commit offsets
KafkaConsumer(auto_offset_reset='earliest', enable_auto_commit=False)

# consume json messages
KafkaConsumer(value_deserializer=lambda m: json.loads(m.decode('ascii')))

# consume msgpack
KafkaConsumer(value_deserializer=msgpack.unpackb)

# StopIteration if no message after 1sec
KafkaConsumer(consumer_timeout_ms=1000)
```

(continues on next page)

(continued from previous page)

```

# Subscribe to a regex topic pattern
consumer = KafkaConsumer()
consumer.subscribe(pattern='^awesome.*')

# Use multiple consumers in parallel w/ 0.9 kafka brokers
# typically you would run each on a different server / process / CPU
consumer1 = KafkaConsumer('my-topic',
                           group_id='my-group',
                           bootstrap_servers='my.server.com')
consumer2 = KafkaConsumer('my-topic',
                           group_id='my-group',
                           bootstrap_servers='my.server.com')

```

There are many configuration options for the consumer class. See `KafkaConsumer` API documentation for more details.

6.1.2 KafkaProducer

```

from kafka import KafkaProducer
from kafka.errors import KafkaError

producer = KafkaProducer(bootstrap_servers=['broker1:1234'])

# Asynchronous by default
future = producer.send('my-topic', b'raw_bytes')

# Block for 'synchronous' sends
try:
    record_metadata = future.get(timeout=10)
except KafkaError:
    # Decide what to do if produce request failed...
    log.exception()
    pass

# Successful result returns assigned partition and offset
print (record_metadata.topic)
print (record_metadata.partition)
print (record_metadata.offset)

# produce keyed messages to enable hashed partitioning
producer.send('my-topic', key=b'foo', value=b'bar')

# encode objects via msgpack
producer = KafkaProducer(value_serializer=msgpack.dumps)
producer.send('msgpack-topic', {'key': 'value'})

# produce json messages
producer = KafkaProducer(value_serializer=lambda m: json.dumps(m).encode('ascii'))
producer.send('json-topic', {'key': 'value'})

# produce asynchronously
for _ in range(100):
    producer.send('my-topic', b'msg')

def on_send_success(record_metadata):

```

(continues on next page)

(continued from previous page)

```

print(record_metadata.topic)
print(record_metadata.partition)
print(record_metadata.offset)

def on_send_error(excp):
    log.error('I am an errback', exc_info=excp)
    # handle exception

# produce asynchronously with callbacks
producer.send('my-topic', b'raw_bytes').add_callback(on_send_success).add_errback(on_
→send_error)

# block until all async messages are sent
producer.flush()

# configure multiple retries
producer = KafkaProducer(retries=5)

```

6.2 kafka-python API

6.2.1 KafkaConsumer

class `kafka.KafkaConsumer` (**topics*, ***configs*)

Consume records from a Kafka cluster.

The consumer will transparently handle the failure of servers in the Kafka cluster, and adapt as topic-partitions are created or migrate between brokers. It also interacts with the assigned kafka Group Coordinator node to allow multiple consumers to load balance consumption of topics (requires kafka >= 0.9.0.0).

The consumer is not thread safe and should not be shared across threads.

Parameters **topics* (*str*) – optional list of topics to subscribe to. If not set, call `subscribe()` or `assign()` before consuming records.

Keyword Arguments

- **bootstrap_servers** – ‘host[:port]’ string (or list of ‘host[:port]’ strings) that the consumer should contact to bootstrap initial cluster metadata. This does not have to be the full node list. It just needs to have at least one broker that will respond to a Metadata API Request. Default port is 9092. If no servers are specified, will default to localhost:9092.
- **client_id** (*str*) – A name for this client. This string is passed in each request to servers and can be used to identify specific server-side log entries that correspond to this client. Also submitted to GroupCoordinator for logging with respect to consumer group administration. Default: ‘kafka-python-{version}’
- **group_id** (*str or None*) – The name of the consumer group to join for dynamic partition assignment (if enabled), and to use for fetching and committing offsets. If None, auto-partition assignment (via group coordinator) and offset commits are disabled. Default: None
- **key_deserializer** (*callable*) – Any callable that takes a raw message key and returns a deserialized key.
- **value_deserializer** (*callable*) – Any callable that takes a raw message value and returns a deserialized value.

- **fetch_min_bytes** (*int*) – Minimum amount of data the server should return for a fetch request, otherwise wait up to `fetch_max_wait_ms` for more data to accumulate. Default: 1.
- **fetch_max_wait_ms** (*int*) – The maximum amount of time in milliseconds the server will block before answering the fetch request if there isn't sufficient data to immediately satisfy the requirement given by `fetch_min_bytes`. Default: 500.
- **fetch_max_bytes** (*int*) – The maximum amount of data the server should return for a fetch request. This is not an absolute maximum, if the first message in the first non-empty partition of the fetch is larger than this value, the message will still be returned to ensure that the consumer can make progress. NOTE: consumer performs fetches to multiple brokers in parallel so memory usage will depend on the number of brokers containing partitions for the topic. Supported Kafka version $\geq 0.10.1.0$. Default: 52428800 (50 MB).
- **max_partition_fetch_bytes** (*int*) – The maximum amount of data per-partition the server will return. The maximum total memory used for a request = `#partitions * max_partition_fetch_bytes`. This size must be at least as large as the maximum message size the server allows or else it is possible for the producer to send messages larger than the consumer can fetch. If that happens, the consumer can get stuck trying to fetch a large message on a certain partition. Default: 1048576.
- **request_timeout_ms** (*int*) – Client request timeout in milliseconds. Default: 305000.
- **retry_backoff_ms** (*int*) – Milliseconds to backoff when retrying on errors. Default: 100.
- **reconnect_backoff_ms** (*int*) – The amount of time in milliseconds to wait before attempting to reconnect to a given host. Default: 50.
- **reconnect_backoff_max_ms** (*int*) – The maximum amount of time in milliseconds to wait when reconnecting to a broker that has repeatedly failed to connect. If provided, the backoff per host will increase exponentially for each consecutive connection failure, up to this maximum. To avoid connection storms, a randomization factor of 0.2 will be applied to the backoff resulting in a random range between 20% below and 20% above the computed value. Default: 1000.
- **max_in_flight_requests_per_connection** (*int*) – Requests are pipelined to kafka brokers up to this number of maximum requests per broker connection. Default: 5.
- **auto_offset_reset** (*str*) – A policy for resetting offsets on `OffsetOutOfRange` errors: 'earliest' will move to the oldest available message, 'latest' will move to the most recent. Any other value will raise the exception. Default: 'latest'.
- **enable_auto_commit** (*bool*) – If True, the consumer's offset will be periodically committed in the background. Default: True.
- **auto_commit_interval_ms** (*int*) – Number of milliseconds between automatic offset commits, if `enable_auto_commit` is True. Default: 5000.
- **default_offset_commit_callback** (*callable*) – Called as `callback(offsets, response)` response will be either an `Exception` or an `OffsetCommitResponse` struct. This callback can be used to trigger custom actions when a commit request completes.
- **check_crcs** (*bool*) – Automatically check the CRC32 of the records consumed. This ensures no on-the-wire or on-disk corruption to the messages occurred. This check adds some overhead, so it may be disabled in cases seeking extreme performance. Default: True
- **metadata_max_age_ms** (*int*) – The period of time in milliseconds after which we force a refresh of metadata, even if we haven't seen any partition leadership changes to proactively discover any new brokers or partitions. Default: 300000

- **partition_assignment_strategy** (*list*) – List of objects to use to distribute partition ownership amongst consumer instances when group management is used. Default: [RangePartitionAssignor, RoundRobinPartitionAssignor]
- **max_poll_records** (*int*) – The maximum number of records returned in a single call to `poll()`. Default: 500
- **max_poll_interval_ms** (*int*) – The maximum delay between invocations of `poll()` when using consumer group management. This places an upper bound on the amount of time that the consumer can be idle before fetching more records. If `poll()` is not called before expiration of this timeout, then the consumer is considered failed and the group will rebalance in order to reassign the partitions to another member. Default 300000
- **session_timeout_ms** (*int*) – The timeout used to detect failures when using Kafka's group management facilities. The consumer sends periodic heartbeats to indicate its liveness to the broker. If no heartbeats are received by the broker before the expiration of this session timeout, then the broker will remove this consumer from the group and initiate a rebalance. Note that the value must be in the allowable range as configured in the broker configuration by `group.min.session.timeout.ms` and `group.max.session.timeout.ms`. Default: 10000
- **heartbeat_interval_ms** (*int*) – The expected time in milliseconds between heartbeats to the consumer coordinator when using Kafka's group management facilities. Heartbeats are used to ensure that the consumer's session stays active and to facilitate rebalancing when new consumers join or leave the group. The value must be set lower than `session_timeout_ms`, but typically should be set no higher than 1/3 of that value. It can be adjusted even lower to control the expected time for normal rebalances. Default: 3000
- **receive_buffer_bytes** (*int*) – The size of the TCP receive buffer (`SO_RCVBUF`) to use when reading data. Default: None (relies on system defaults). The java client defaults to 32768.
- **send_buffer_bytes** (*int*) – The size of the TCP send buffer (`SO_SNDBUF`) to use when sending data. Default: None (relies on system defaults). The java client defaults to 131072.
- **socket_options** (*list*) – List of tuple-arguments to `socket.setsockopt` to apply to broker connection sockets. Default: [(`socket.IPPROTO_TCP`, `socket.TCP_NODELAY`, 1)]
- **consumer_timeout_ms** (*int*) – number of milliseconds to block during message iteration before raising `StopIteration` (i.e., ending the iterator). Default block forever [float('inf')].
- **skip_double_compressed_messages** (*bool*) – A bug in `KafkaProducer` <= 1.2.4 caused some messages to be corrupted via double-compression. By default, the fetcher will return these messages as a compressed blob of bytes with a single offset, i.e. how the message was actually published to the cluster. If you prefer to have the fetcher automatically detect corrupt messages and skip them, set this option to `True`. Default: `False`.
- **security_protocol** (*str*) – Protocol used to communicate with brokers. Valid values are: `PLAINTEXT`, `SSL`. Default: `PLAINTEXT`.
- **ssl_context** (*ssl.SSLContext*) – Pre-configured `SSLContext` for wrapping socket connections. If provided, all other `ssl_*` configurations will be ignored. Default: `None`.
- **ssl_check_hostname** (*bool*) – Flag to configure whether `ssl` handshake should verify that the certificate matches the brokers hostname. Default: `True`.
- **ssl_cafile** (*str*) – Optional filename of `ca` file to use in certificate verification. Default: `None`.

- **ssl_certfile** (*str*) – Optional filename of file in pem format containing the client certificate, as well as any ca certificates needed to establish the certificate’s authenticity. Default: None.
- **ssl_keyfile** (*str*) – Optional filename containing the client private key. Default: None.
- **ssl_password** (*str*) – Optional password to be used when loading the certificate chain. Default: None.
- **ssl_crlfile** (*str*) – Optional filename containing the CRL to check for certificate expiration. By default, no CRL check is done. When providing a file, only the leaf certificate will be checked against this CRL. The CRL can only be checked with Python 3.4+ or 2.7.9+. Default: None.
- **api_version** (*tuple*) – Specify which Kafka API version to use. If set to None, the client will attempt to infer the broker version by probing various APIs. Different versions enable different functionality.

Examples

(0, 9) enables full group coordination features with automatic partition assignment and rebalancing,

(0, 8, 2) enables kafka-storage offset commits with manual partition assignment only,

(0, 8, 1) enables zookeeper-storage offset commits with manual partition assignment only,

(0, 8, 0) enables basic functionality but requires manual partition assignment and offset management.

Default: None

- **api_version_auto_timeout_ms** (*int*) – number of milliseconds to throw a timeout exception from the constructor when checking the broker api version. Only applies if `api_version` set to ‘auto’
- **metric_reporters** (*list*) – A list of classes to use as metrics reporters. Implementing the `AbstractMetricsReporter` interface allows plugging in classes that will be notified of new metric creation. Default: []
- **metrics_num_samples** (*int*) – The number of samples maintained to compute metrics. Default: 2
- **metrics_sample_window_ms** (*int*) – The maximum age in milliseconds of samples used to compute metrics. Default: 30000
- **selector** (*selectors.BaseSelector*) – Provide a specific selector implementation to use for I/O multiplexing. Default: `selectors.DefaultSelector`
- **exclude_internal_topics** (*bool*) – Whether records from internal topics (such as offsets) should be exposed to the consumer. If set to True the only way to receive records from an internal topic is subscribing to it. Requires 0.10+ Default: True
- **sasl_mechanism** (*str*) – String picking sasl mechanism when `security_protocol` is `SASL_PLAINTEXT` or `SASL_SSL`. Currently only `PLAIN` is supported. Default: None
- **sasl_plain_username** (*str*) – Username for sasl `PLAIN` authentication. Default: None

- **sasl_plain_password** (*str*) – Password for sasl PLAIN authentication. Default: None
- **sasl_kerberos_service_name** (*str*) – Service name to include in GSSAPI sasl mechanism handshake. Default: 'kafka'

Note: Configuration parameters are described in more detail at <https://kafka.apache.org/documentation/#newconsumerconfigs>

assign (*partitions*)

Manually assign a list of TopicPartitions to this consumer.

Parameters **partitions** (*list of TopicPartition*) – Assignment for this instance.

Raises

- `IllegalStateException` – If consumer has already called
- `subscribe()`.

Warning: It is not possible to use both manual partition assignment with `assign()` and group assignment with `subscribe()`.

Note: This interface does not support incremental assignment and will replace the previous assignment (if there was one).

Note: Manual topic assignment through this method does not use the consumer's group management functionality. As such, there will be no rebalance operation triggered when group membership or cluster and topic metadata change.

assignment ()

Get the TopicPartitions currently assigned to this consumer.

If partitions were directly assigned using `assign()`, then this will simply return the same partitions that were previously assigned. If topics were subscribed using `subscribe()`, then this will give the set of topic partitions currently assigned to the consumer (which may be None if the assignment hasn't happened yet, or if the partitions are in the process of being reassigned).

Returns {TopicPartition, ... }

Return type set

beginning_offsets (*partitions*)

Get the first offset for the given partitions.

This method does not change the current consumer position of the partitions.

Note: This method may block indefinitely if the partition does not exist.

Parameters **partitions** (*list*) – List of TopicPartition instances to fetch offsets for.

Returns int{}: The earliest available offsets for the given partitions.

Return type “{TopicPartition

Raises

- `UnsupportedVersionError` – If the broker does not support looking up the offsets by timestamp.
- `KafkaTimeoutError` – If fetch failed in `request_timeout_ms`.

close (*autocommit=True*)

Close the consumer, waiting indefinitely for any needed cleanup.

Keyword Arguments **autocommit** (*bool*) – If auto-commit is configured for this consumer, this optional flag causes the consumer to attempt to commit any pending consumed offsets prior to close. Default: True

commit (*offsets=None*)

Commit offsets to kafka, blocking until success or error.

This commits offsets only to Kafka. The offsets committed using this API will be used on the first fetch after every rebalance and also on startup. As such, if you need to store offsets in anything other than Kafka, this API should not be used. To avoid re-processing the last message read if a consumer is restarted, the committed offset should be the next message your application should consume, i.e.: `last_offset + 1`.

Blocks until either the commit succeeds or an unrecoverable error is encountered (in which case it is thrown to the caller).

Currently only supports kafka-topic offset storage (not zookeeper).

Parameters **offsets** (*dict, optional*) – {TopicPartition: OffsetAndMetadata} dict to commit with the configured `group_id`. Defaults to currently consumed offsets for all subscribed partitions.

commit_async (*offsets=None, callback=None*)

Commit offsets to kafka asynchronously, optionally firing callback.

This commits offsets only to Kafka. The offsets committed using this API will be used on the first fetch after every rebalance and also on startup. As such, if you need to store offsets in anything other than Kafka, this API should not be used. To avoid re-processing the last message read if a consumer is restarted, the committed offset should be the next message your application should consume, i.e.: `last_offset + 1`.

This is an asynchronous call and will not block. Any errors encountered are either passed to the callback (if provided) or discarded.

Parameters

- **offsets** (*dict, optional*) – {TopicPartition: OffsetAndMetadata} dict to commit with the configured `group_id`. Defaults to currently consumed offsets for all subscribed partitions.
- **callback** (*callable, optional*) – Called as `callback(offsets, response)` with response as either an `Exception` or an `OffsetCommitResponse` struct. This callback can be used to trigger custom actions when a commit request completes.

Returns `kafka.future.Future`

committed (*partition*)

Get the last committed offset for the given partition.

This offset will be used as the position for the consumer in the event of a failure.

This call may block to do a remote call if the partition in question isn't assigned to this consumer or if the consumer hasn't yet initialized its cache of committed offsets.

Parameters `partition` (*TopicPartition*) – The partition to check.

Returns The last committed offset, or None if there was no prior commit.

end_offsets (*partitions*)

Get the last offset for the given partitions. The last offset of a partition is the offset of the upcoming message, i.e. the offset of the last available message + 1.

This method does not change the current consumer position of the partitions.

Note: This method may block indefinitely if the partition does not exist.

Parameters `partitions` (*list*) – List of TopicPartition instances to fetch offsets for.

Returns int}: The end offsets for the given partitions.

Return type “{TopicPartition

Raises

- `UnsupportedVersionError` – If the broker does not support looking up the offsets by timestamp.
- `KafkaTimeoutError` – If fetch failed in `request_timeout_ms`

highwater (*partition*)

Last known highwater offset for a partition.

A highwater offset is the offset that will be assigned to the next message that is produced. It may be useful for calculating lag, by comparing with the reported position. Note that both position and highwater refer to the *next* offset – i.e., highwater offset is one greater than the newest available message.

Highwater offsets are returned in FetchResponse messages, so will not be available if no FetchRequests have been sent for this partition yet.

Parameters `partition` (*TopicPartition*) – Partition to check

Returns Offset if available

Return type int or None

metrics (*raw=False*)

Get metrics on consumer performance.

This is ported from the Java Consumer, for details see: https://kafka.apache.org/documentation/#new_consumer_monitoring

Warning: This is an unstable interface. It may change in future releases without warning.

offsets_for_times (*timestamps*)

Look up the offsets for the given partitions by timestamp. The returned offset for each partition is the earliest offset whose timestamp is greater than or equal to the given timestamp in the corresponding partition.

This is a blocking call. The consumer does not have to be assigned the partitions.

If the message format version in a partition is before 0.10.0, i.e. the messages do not have timestamps, None will be returned for that partition. None will also be returned for the partition if there are no messages in it.

Note: This method may block indefinitely if the partition does not exist.

Parameters `timestamps` (*dict*) – {TopicPartition: int} mapping from partition to the timestamp to look up. Unit should be milliseconds since beginning of the epoch (midnight Jan 1, 1970 (UTC))

Returns OffsetAndTimestamp{}: mapping from partition to the timestamp and offset of the first message with timestamp greater than or equal to the target timestamp.

Return type “{TopicPartition

Raises

- `ValueError` – If the target timestamp is negative
- `UnsupportedVersionError` – If the broker does not support looking up the offsets by timestamp.
- `KafkaTimeoutError` – If fetch failed in `request_timeout_ms`

partitions_for_topic (*topic*)

Get metadata about the partitions for a given topic.

Parameters `topic` (*str*) – Topic to check.

Returns Partition ids

Return type set

pause (**partitions*)

Suspend fetching from the requested partitions.

Future calls to `poll()` will not return any records from these partitions until they have been resumed using `resume()`.

Note: This method does not affect partition subscription. In particular, it does not cause a group rebalance when automatic assignment is used.

Parameters `*partitions` (*TopicPartition*) – Partitions to pause.

paused ()

Get the partitions that were previously paused using `pause()`.

Returns {partition (*TopicPartition*), ... }

Return type set

poll (*timeout_ms=0, max_records=None*)

Fetch data from assigned topics / partitions.

Records are fetched and returned in batches by topic-partition. On each poll, consumer will try to use the last consumed offset as the starting offset and fetch sequentially. The last consumed offset can be manually set through `seek()` or automatically set as the last committed offset for the subscribed list of partitions.

Incompatible with iterator interface – use one or the other, not both.

Parameters

- `timeout_ms` (*int, optional*) – Milliseconds spent waiting in poll if data is not available in the buffer. If 0, returns immediately with any records that are available currently in the buffer, else returns empty. Must not be negative. Default: 0

- **max_records** (*int, optional*) – The maximum number of records returned in a single call to `poll()`. Default: Inherit value from `max_poll_records`.

Returns

Topic to list of records since the last fetch for the subscribed list of topics and partitions.

Return type dict

position (*partition*)

Get the offset of the next record that will be fetched

Parameters **partition** (*TopicPartition*) – Partition to check

Returns Offset

Return type int

resume (**partitions*)

Resume fetching from the specified (paused) partitions.

Parameters ***partitions** (*TopicPartition*) – Partitions to resume.

seek (*partition, offset*)

Manually specify the fetch offset for a `TopicPartition`.

Overrides the fetch offsets that the consumer will use on the next `poll()`. If this API is invoked for the same partition more than once, the latest offset will be used on the next `poll()`.

Note: You may lose data if this API is arbitrarily used in the middle of consumption to reset the fetch offsets.

Parameters

- **partition** (*TopicPartition*) – Partition for seek operation
- **offset** (*int*) – Message offset in partition

Raises `AssertionError` – If offset is not an int ≥ 0 ; or if partition is not currently assigned.

seek_to_beginning (**partitions*)

Seek to the oldest available offset for partitions.

Parameters ***partitions** – Optionally provide specific `TopicPartitions`, otherwise default to all assigned partitions.

Raises `AssertionError` – If any partition is not currently assigned, or if no partitions are assigned.

seek_to_end (**partitions*)

Seek to the most recent available offset for partitions.

Parameters ***partitions** – Optionally provide specific `TopicPartitions`, otherwise default to all assigned partitions.

Raises `AssertionError` – If any partition is not currently assigned, or if no partitions are assigned.

subscribe (*topics=(), pattern=None, listener=None*)

Subscribe to a list of topics, or a topic regex pattern.

Partitions will be dynamically assigned via a group coordinator. Topic subscriptions are not incremental: this list will replace the current assignment (if there is one).

This method is incompatible with `assign()`.

Parameters

- **topics** (*list*) – List of topics for subscription.
- **pattern** (*str*) – Pattern to match available topics. You must provide either topics or pattern, but not both.
- **listener** (*ConsumerRebalanceListener*) – Optionally include listener callback, which will be called before and after each rebalance operation.

As part of group management, the consumer will keep track of the list of consumers that belong to a particular group and will trigger a rebalance operation if one of the following events trigger:

- Number of partitions change for any of the subscribed topics
- Topic is created or deleted
- An existing member of the consumer group dies
- A new member is added to the consumer group

When any of these events are triggered, the provided listener will be invoked first to indicate that the consumer’s assignment has been revoked, and then again when the new assignment has been received. Note that this listener will immediately override any listener set in a previous call to subscribe. It is guaranteed, however, that the partitions revoked/assigned through this interface are from topics subscribed in this call.

Raises

- `IllegalStateException` – If called after previously calling `assign()`.
- `AssertionError` – If neither topics or pattern is provided.
- `TypeError` – If listener is not a `ConsumerRebalanceListener`.

`subscription()`

Get the current topic subscription.

Returns {topic, ...}

Return type set

`topics()`

Get all topics the user is authorized to view.

Returns topics

Return type set

`unsubscribe()`

Unsubscribe from all topics and clear all assigned partitions.

6.2.2 KafkaProducer

class `kafka.KafkaProducer` (***configs*)

A Kafka client that publishes records to the Kafka cluster.

The producer is thread safe and sharing a single producer instance across threads will generally be faster than having multiple instances.

The producer consists of a pool of buffer space that holds records that haven’t yet been transmitted to the server as well as a background I/O thread that is responsible for turning these records into requests and transmitting them to the cluster.

`send()` is asynchronous. When called it adds the record to a buffer of pending record sends and immediately returns. This allows the producer to batch together individual records for efficiency.

The ‘acks’ config controls the criteria under which requests are considered complete. The “all” setting will result in blocking on the full commit of the record, the slowest but most durable setting.

If the request fails, the producer can automatically retry, unless ‘retries’ is configured to 0. Enabling retries also opens up the possibility of duplicates (see the documentation on message delivery semantics for details: <http://kafka.apache.org/documentation.html#semantics>).

The producer maintains buffers of unsent records for each partition. These buffers are of a size specified by the ‘batch_size’ config. Making this larger can result in more batching, but requires more memory (since we will generally have one of these buffers for each active partition).

By default a buffer is available to send immediately even if there is additional unused space in the buffer. However if you want to reduce the number of requests you can set ‘linger_ms’ to something greater than 0. This will instruct the producer to wait up to that number of milliseconds before sending a request in hope that more records will arrive to fill up the same batch. This is analogous to Nagle’s algorithm in TCP. Note that records that arrive close together in time will generally batch together even with `linger_ms=0` so under heavy load batching will occur regardless of the linger configuration; however setting this to something larger than 0 can lead to fewer, more efficient requests when not under maximal load at the cost of a small amount of latency.

The `buffer_memory` controls the total amount of memory available to the producer for buffering. If records are sent faster than they can be transmitted to the server then this buffer space will be exhausted. When the buffer space is exhausted additional `send` calls will block.

The `key_serializer` and `value_serializer` instruct how to turn the key and value objects the user provides into bytes.

Keyword Arguments

- **bootstrap_servers** – ‘host[:port]’ string (or list of ‘host[:port]’ strings) that the producer should contact to bootstrap initial cluster metadata. This does not have to be the full node list. It just needs to have at least one broker that will respond to a Metadata API Request. Default port is 9092. If no servers are specified, will default to localhost:9092.
- **client_id** (*str*) – a name for this client. This string is passed in each request to servers and can be used to identify specific server-side log entries that correspond to this client. Default: ‘kafka-python-producer-#’ (appended with a unique number per instance)
- **key_serializer** (*callable*) – used to convert user-supplied keys to bytes. If not `None`, called as `f(key)`, should return bytes. Default: `None`.
- **value_serializer** (*callable*) – used to convert user-supplied message values to bytes. If not `None`, called as `f(value)`, should return bytes. Default: `None`.
- **acks** (*0, 1, 'all'*) – The number of acknowledgments the producer requires the leader to have received before considering a request complete. This controls the durability of records that are sent. The following settings are common:
 - 0: Producer will not wait for any acknowledgment from the server.** The message will immediately be added to the socket buffer and considered sent. No guarantee can be made that the server has received the record in this case, and the retries configuration will not take effect (as the client won’t generally know of any failures). The offset given back for each record will always be set to -1.
 - 1: Wait for leader to write the record to its local log only.** Broker will respond without awaiting full acknowledgement from all followers. In this case should the leader fail immediately after acknowledging the record but before the followers have replicated it then the record will be lost.

all: Wait for the full set of in-sync replicas to write the record. This guarantees that the record will not be lost as long as at least one in-sync replica remains alive. This is the strongest available guarantee.

If unset, defaults to `acks=1`.

- **`compression_type`** (*str*) – The compression type for all data generated by the producer. Valid values are ‘gzip’, ‘snappy’, ‘lz4’, or None. Compression is of full batches of data, so the efficacy of batching will also impact the compression ratio (more batching means better compression). Default: None.
- **`retries`** (*int*) – Setting a value greater than zero will cause the client to resend any record whose send fails with a potentially transient error. Note that this retry is no different than if the client resent the record upon receiving the error. Allowing retries without setting `max_in_flight_requests_per_connection` to 1 will potentially change the ordering of records because if two batches are sent to a single partition, and the first fails and is retried but the second succeeds, then the records in the second batch may appear first. Default: 0.
- **`batch_size`** (*int*) – Requests sent to brokers will contain multiple batches, one for each partition with data available to be sent. A small batch size will make batching less common and may reduce throughput (a batch size of zero will disable batching entirely). Default: 16384
- **`linger_ms`** (*int*) – The producer groups together any records that arrive in between request transmissions into a single batched request. Normally this occurs only under load when records arrive faster than they can be sent out. However in some circumstances the client may want to reduce the number of requests even under moderate load. This setting accomplishes this by adding a small amount of artificial delay; that is, rather than immediately sending out a record the producer will wait for up to the given delay to allow other records to be sent so that the sends can be batched together. This can be thought of as analogous to Nagle’s algorithm in TCP. This setting gives the upper bound on the delay for batching: once we get `batch_size` worth of records for a partition it will be sent immediately regardless of this setting, however if we have fewer than this many bytes accumulated for this partition we will ‘linger’ for the specified time waiting for more records to show up. This setting defaults to 0 (i.e. no delay). Setting `linger_ms=5` would have the effect of reducing the number of requests sent but would add up to 5ms of latency to records sent in the absence of load. Default: 0.
- **`partitioner`** (*callable*) – Callable used to determine which partition each message is assigned to. Called (after key serialization): `partitioner(key_bytes, all_partitions, available_partitions)`. The default partitioner implementation hashes each non-None key using the same murmur2 algorithm as the java client so that messages with the same key are assigned to the same partition. When a key is None, the message is delivered to a random partition (filtered to partitions with available leaders only, if possible).
- **`buffer_memory`** (*int*) – The total bytes of memory the producer should use to buffer records waiting to be sent to the server. If records are sent faster than they can be delivered to the server the producer will block up to `max_block_ms`, raising an exception on timeout. In the current implementation, this setting is an approximation. Default: 33554432 (32MB)
- **`max_block_ms`** (*int*) – Number of milliseconds to block during `send()` and `partitions_for()`. These methods can be blocked either because the buffer is full or metadata unavailable. Blocking in the user-supplied serializers or partitioner will not be counted against this timeout. Default: 60000.
- **`max_request_size`** (*int*) – The maximum size of a request. This is also effectively a cap on the maximum record size. Note that the server has its own cap on record size which may be different from this. This setting will limit the number of record batches the producer

will send in a single request to avoid sending huge requests. Default: 1048576.

- **metadata_max_age_ms** (*int*) – The period of time in milliseconds after which we force a refresh of metadata even if we haven't seen any partition leadership changes to proactively discover any new brokers or partitions. Default: 300000
- **retry_backoff_ms** (*int*) – Milliseconds to backoff when retrying on errors. Default: 100.
- **request_timeout_ms** (*int*) – Client request timeout in milliseconds. Default: 30000.
- **receive_buffer_bytes** (*int*) – The size of the TCP receive buffer (SO_RCVBUF) to use when reading data. Default: None (relies on system defaults). Java client defaults to 32768.
- **send_buffer_bytes** (*int*) – The size of the TCP send buffer (SO_SNDBUF) to use when sending data. Default: None (relies on system defaults). Java client defaults to 131072.
- **socket_options** (*list*) – List of tuple-arguments to socket.setsockopt to apply to broker connection sockets. Default: [(socket.IPPROTO_TCP, socket.TCP_NODELAY, 1)]
- **reconnect_backoff_ms** (*int*) – The amount of time in milliseconds to wait before attempting to reconnect to a given host. Default: 50.
- **reconnect_backoff_max_ms** (*int*) – The maximum amount of time in milliseconds to wait when reconnecting to a broker that has repeatedly failed to connect. If provided, the backoff per host will increase exponentially for each consecutive connection failure, up to this maximum. To avoid connection storms, a randomization factor of 0.2 will be applied to the backoff resulting in a random range between 20% below and 20% above the computed value. Default: 1000.
- **max_in_flight_requests_per_connection** (*int*) – Requests are pipelined to kafka brokers up to this number of maximum requests per broker connection. Note that if this setting is set to be greater than 1 and there are failed sends, there is a risk of message re-ordering due to retries (i.e., if retries are enabled). Default: 5.
- **security_protocol** (*str*) – Protocol used to communicate with brokers. Valid values are: PLAINTEXT, SSL, SASL_PLAINTEXT, SASL_SSL. Default: PLAINTEXT.
- **ssl_context** (*ssl.SSLContext*) – pre-configured SSLContext for wrapping socket connections. If provided, all other ssl_* configurations will be ignored. Default: None.
- **ssl_check_hostname** (*bool*) – flag to configure whether ssl handshake should verify that the certificate matches the brokers hostname. default: true.
- **ssl_cafile** (*str*) – optional filename of ca file to use in certificate verification. default: none.
- **ssl_certfile** (*str*) – optional filename of file in pem format containing the client certificate, as well as any ca certificates needed to establish the certificate's authenticity. default: none.
- **ssl_keyfile** (*str*) – optional filename containing the client private key. default: none.
- **ssl_password** (*str*) – optional password to be used when loading the certificate chain. default: none.
- **ssl_crlfile** (*str*) – optional filename containing the CRL to check for certificate expiration. By default, no CRL check is done. When providing a file, only the leaf certificate will be checked against this CRL. The CRL can only be checked with Python 3.4+ or 2.7.9+. default: none.

- **api_version** (*tuple*) – Specify which Kafka API version to use. If set to None, the client will attempt to infer the broker version by probing various APIs. Example: (0, 10, 2). Default: None
- **api_version_auto_timeout_ms** (*int*) – number of milliseconds to throw a timeout exception from the constructor when checking the broker api version. Only applies if api_version set to 'auto'
- **metric_reporters** (*list*) – A list of classes to use as metrics reporters. Implementing the AbstractMetricsReporter interface allows plugging in classes that will be notified of new metric creation. Default: []
- **metrics_num_samples** (*int*) – The number of samples maintained to compute metrics. Default: 2
- **metrics_sample_window_ms** (*int*) – The maximum age in milliseconds of samples used to compute metrics. Default: 30000
- **selector** (*selectors.BaseSelector*) – Provide a specific selector implementation to use for I/O multiplexing. Default: selectors.DefaultSelector
- **sasl_mechanism** (*str*) – string picking sasl mechanism when security_protocol is SASL_PLAINTEXT or SASL_SSL. Currently only PLAIN is supported. Default: None
- **sasl_plain_username** (*str*) – username for sasl PLAIN authentication. Default: None
- **sasl_plain_password** (*str*) – password for sasl PLAIN authentication. Default: None
- **sasl_kerberos_service_name** (*str*) – Service name to include in GSSAPI sasl mechanism handshake. Default: 'kafka'

Note: Configuration parameters are described in more detail at <https://kafka.apache.org/0100/configuration.html#producerconfigs>

close (*timeout=None*)
Close this producer.

Parameters *timeout* (*float, optional*) – timeout in seconds to wait for completion.

flush (*timeout=None*)

Invoking this method makes all buffered records immediately available to send (even if *linger_ms* is greater than 0) and blocks on the completion of the requests associated with these records. The post-condition of `flush()` is that any previously sent record will have completed (e.g. `Future.is_done() == True`). A request is considered completed when either it is successfully acknowledged according to the 'acks' configuration for the producer, or it results in an error.

Other threads can continue sending messages while one thread is blocked waiting for a flush call to complete; however, no guarantee is made about the completion of messages sent after the flush call begins.

Parameters *timeout* (*float, optional*) – timeout in seconds to wait for completion.

Raises `KafkaTimeoutError` – failure to flush buffered records within the provided timeout

metrics (*raw=False*)

Get metrics on producer performance.

This is ported from the Java Producer, for details see: https://kafka.apache.org/documentation/#producer_monitoring

Warning: This is an unstable interface. It may change in future releases without warning.

partitions_for (*topic*)

Returns set of all known partitions for the topic.

send (*topic, value=None, key=None, partition=None, timestamp_ms=None*)

Publish a message to a topic.

Parameters

- **topic** (*str*) – topic where the message will be published
- **value** (*optional*) – message value. Must be type bytes, or be serializable to bytes via configured `value_serializer`. If value is None, key is required and message acts as a ‘delete’. See kafka compaction documentation for more details: <http://kafka.apache.org/documentation.html#compaction> (compaction requires kafka >= 0.8.1)
- **partition** (*int, optional*) – optionally specify a partition. If not set, the partition will be selected using the configured ‘partitioner’.
- **key** (*optional*) – a key to associate with the message. Can be used to determine which partition to send the message to. If partition is None (and producer’s partitioner config is left as default), then messages with the same key will be delivered to the same partition (but if key is None, partition is chosen randomly). Must be type bytes, or be serializable to bytes via configured `key_serializer`.
- **timestamp_ms** (*int, optional*) – epoch milliseconds (from Jan 1 1970 UTC) to use as the message timestamp. Defaults to current time.

Returns resolves to RecordMetadata

Return type FutureRecordMetadata

Raises `KafkaTimeoutError` – if unable to fetch topic metadata, or unable to obtain memory buffer prior to configured `max_block_ms`

6.2.3 KafkaClient

class `kafka.client.KafkaClient` (***configs*)

A network client for asynchronous request/response network I/O.

This is an internal class used to implement the user-facing producer and consumer clients.

This class is not thread-safe!

cluster

ClusterMetadata – Local cache of cluster metadata, retrieved via MetadataRequests during `poll()`.

Keyword Arguments

- **bootstrap_servers** – ‘host[:port]’ string (or list of ‘host[:port]’ strings) that the consumer should contact to bootstrap initial cluster metadata. This does not have to be the full node list. It just needs to have at least one broker that will respond to a Metadata API Request. Default port is 9092. If no servers are specified, will default to localhost:9092.
- **client_id** (*str*) – a name for this client. This string is passed in each request to servers and can be used to identify specific server-side log entries that correspond to this client. Also submitted to GroupCoordinator for logging with respect to consumer group administration. Default: ‘kafka-python-{version}’

- **reconnect_backoff_ms** (*int*) – The amount of time in milliseconds to wait before attempting to reconnect to a given host. Default: 50.
- **reconnect_backoff_max_ms** (*int*) – The maximum amount of time in milliseconds to wait when reconnecting to a broker that has repeatedly failed to connect. If provided, the backoff per host will increase exponentially for each consecutive connection failure, up to this maximum. To avoid connection storms, a randomization factor of 0.2 will be applied to the backoff resulting in a random range between 20% below and 20% above the computed value. Default: 1000.
- **request_timeout_ms** (*int*) – Client request timeout in milliseconds. Default: 30000.
- **retry_backoff_ms** (*int*) – Milliseconds to backoff when retrying on errors. Default: 100.
- **max_in_flight_requests_per_connection** (*int*) – Requests are pipelined to kafka brokers up to this number of maximum requests per broker connection. Default: 5.
- **receive_buffer_bytes** (*int*) – The size of the TCP receive buffer (SO_RCVBUF) to use when reading data. Default: None (relies on system defaults). Java client defaults to 32768.
- **send_buffer_bytes** (*int*) – The size of the TCP send buffer (SO_SNDBUF) to use when sending data. Default: None (relies on system defaults). Java client defaults to 131072.
- **socket_options** (*list*) – List of tuple-arguments to socket.setsockopt to apply to broker connection sockets. Default: [(socket.IPPROTO_TCP, socket.TCP_NODELAY, 1)]
- **metadata_max_age_ms** (*int*) – The period of time in milliseconds after which we force a refresh of metadata even if we haven't seen any partition leadership changes to proactively discover any new brokers or partitions. Default: 300000
- **security_protocol** (*str*) – Protocol used to communicate with brokers. Valid values are: PLAINTEXT, SSL. Default: PLAINTEXT.
- **ssl_context** (*ssl.SSLContext*) – Pre-configured SSLContext for wrapping socket connections. If provided, all other ssl_* configurations will be ignored. Default: None.
- **ssl_check_hostname** (*bool*) – Flag to configure whether SSL handshake should verify that the certificate matches the broker's hostname. Default: True.
- **ssl_cafile** (*str*) – Optional filename of CA file to use in certificate verification. Default: None.
- **ssl_certfile** (*str*) – Optional filename of file in PEM format containing the client certificate, as well as any CA certificates needed to establish the certificate's authenticity. Default: None.
- **ssl_keyfile** (*str*) – Optional filename containing the client private key. Default: None.
- **ssl_password** (*str*) – Optional password to be used when loading the certificate chain. Default: None.
- **ssl_crlfile** (*str*) – Optional filename containing the CRL to check for certificate expiration. By default, no CRL check is done. When providing a file, only the leaf certificate will be checked against this CRL. The CRL can only be checked with Python 3.4+ or 2.7.9+. Default: None.

- **api_version** (*tuple*) – Specify which Kafka API version to use. If set to None, Kafka-Client will attempt to infer the broker version by probing various APIs. Example: (0, 10, 2). Default: None
- **api_version_auto_timeout_ms** (*int*) – number of milliseconds to throw a timeout exception from the constructor when checking the broker api version. Only applies if api_version is None
- **selector** (*selectors.BaseSelector*) – Provide a specific selector implementation to use for I/O multiplexing. Default: selectors.DefaultSelector
- **metrics** (*kafka.metrics.Metrics*) – Optionally provide a metrics instance for capturing network IO stats. Default: None.
- **metric_group_prefix** (*str*) – Prefix for metric names. Default: ‘’
- **sasl_mechanism** (*str*) – string picking sasl mechanism when security_protocol is SASL_PLAINTEXT or SASL_SSL. Currently only PLAIN is supported. Default: None
- **sasl_plain_username** (*str*) – username for sasl PLAIN authentication. Default: None
- **sasl_plain_password** (*str*) – password for sasl PLAIN authentication. Default: None
- **sasl_kerberos_service_name** (*str*) – Service name to include in GSSAPI sasl mechanism handshake. Default: ‘kafka’

add_topic (*topic*)

Add a topic to the list of topics tracked via metadata.

Parameters **topic** (*str*) – topic to track

Returns resolves after metadata request/response

Return type Future

check_version (*node_id=None, timeout=2, strict=False*)

Attempt to guess the version of a Kafka broker.

Note: It is possible that this method blocks longer than the specified timeout. This can happen if the entire cluster is down and the client enters a bootstrap backoff sleep. This is only possible if node_id is None.

Returns: version tuple, i.e. (0, 10), (0, 9), (0, 8, 2), ...

Raises

- NodeNotReadyError (if node_id is provided)
- NoBrokersAvailable (if node_id is None)
- UnrecognizedBrokerVersion – please file bug if seen!
- AssertionError (if strict=True) – please file bug if seen!

close (*node_id=None*)

Close one or all broker connections.

Parameters **node_id** (*int, optional*) – the id of the node to close

connected (*node_id*)

Return True iff the node_id is connected.

connection_delay (*node_id*)

Return the number of milliseconds to wait, based on the connection state, before attempting to send data. When disconnected, this respects the reconnect backoff time. When connecting, returns 0 to allow non-blocking connect to finish. When connected, returns a very large number to handle slow/stalled connections.

Parameters `node_id` (*int*) – The id of the node to check

Returns The number of milliseconds to wait.

Return type `int`

in_flight_request_count (*node_id=None*)

Get the number of in-flight requests for a node or all nodes.

Parameters `node_id` (*int, optional*) – a specific node to check. If unspecified, return the total for all nodes

Returns pending in-flight requests for the node, or all nodes if None

Return type `int`

is_disconnected (*node_id*)

Check whether the node connection has been disconnected or failed.

A disconnected node has either been closed or has failed. Connection failures are usually transient and can be resumed in the next `ready()` call, but there are cases where transient failures need to be caught and re-acted upon.

Parameters `node_id` (*int*) – the id of the node to check

Returns True iff the node exists and is disconnected

Return type `bool`

is_ready (*node_id, metadata_priority=True*)

Check whether a node is ready to send more requests.

In addition to connection-level checks, this method also is used to block additional requests from being sent during a metadata refresh.

Parameters

- `node_id` (*int*) – id of the node to check
- `metadata_priority` (*bool*) – Mark node as not-ready if a metadata refresh is required. Default: True

Returns True if the node is ready and metadata is not refreshing

Return type `bool`

least_loaded_node ()

Choose the node with fewest outstanding requests, with fallbacks.

This method will prefer a node with an existing connection and no in-flight-requests. If no such node is found, a node will be chosen randomly from disconnected nodes that are not “blacked out” (i.e., are not subject to a reconnect backoff).

Returns `node_id` or None if no suitable node was found

poll (*timeout_ms=None, future=None*)

Try to read and write to sockets.

This method will also attempt to complete node connections, refresh stale metadata, and run previously-scheduled tasks.

Parameters

- **timeout_ms** (*int, optional*) – maximum amount of time to wait (in ms) for at least one response. Must be non-negative. The actual timeout will be the minimum of timeout, request timeout and metadata timeout. Default: request_timeout_ms
- **future** (*Future, optional*) – if provided, blocks until future.is_done

Returns responses received (can be empty)

Return type list

ready (*node_id, metadata_priority=True*)

Check whether a node is connected and ok to send more requests.

Parameters

- **node_id** (*int*) – the id of the node to check
- **metadata_priority** (*bool*) – Mark node as not-ready if a metadata refresh is required. Default: True

Returns True if we are ready to send to the given node

Return type bool

send (*node_id, request*)

Send a request to a specific node.

Parameters

- **node_id** (*int*) – destination node
- **request** (*Struct*) – request object (not-encoded)

Raises `AssertionError` – if node_id is not in current cluster metadata

Returns resolves to Response struct or Error

Return type Future

set_topics (*topics*)

Set specific topics to track for metadata.

Parameters **topics** (*list of str*) – topics to check for metadata

Returns resolves after metadata request/response

Return type Future

6.2.4 BrokerConnection

class `kafka.BrokerConnection` (*host, port, afd, **configs*)

Initialize a Kafka broker connection

Keyword Arguments

- **client_id** (*str*) – a name for this client. This string is passed in each request to servers and can be used to identify specific server-side log entries that correspond to this client. Also submitted to GroupCoordinator for logging with respect to consumer group administration. Default: 'kafka-python-{version}'
- **reconnect_backoff_ms** (*int*) – The amount of time in milliseconds to wait before attempting to reconnect to a given host. Default: 50.

- **reconnect_backoff_max_ms** (*int*) – The maximum amount of time in milliseconds to wait when reconnecting to a broker that has repeatedly failed to connect. If provided, the backoff per host will increase exponentially for each consecutive connection failure, up to this maximum. To avoid connection storms, a randomization factor of 0.2 will be applied to the backoff resulting in a random range between 20% below and 20% above the computed value. Default: 1000.
- **request_timeout_ms** (*int*) – Client request timeout in milliseconds. Default: 30000.
- **max_in_flight_requests_per_connection** (*int*) – Requests are pipelined to kafka brokers up to this number of maximum requests per broker connection. Default: 5.
- **receive_buffer_bytes** (*int*) – The size of the TCP receive buffer (SO_RCVBUF) to use when reading data. Default: None (relies on system defaults). Java client defaults to 32768.
- **send_buffer_bytes** (*int*) – The size of the TCP send buffer (SO_SNDBUF) to use when sending data. Default: None (relies on system defaults). Java client defaults to 131072.
- **socket_options** (*list*) – List of tuple-arguments to socket.setsockopt to apply to broker connection sockets. Default: [(socket.IPPROTO_TCP, socket.TCP_NODELAY, 1)]
- **security_protocol** (*str*) – Protocol used to communicate with brokers. Valid values are: PLAINTEXT, SSL, SASL_PLAINTEXT, SASL_SSL. Default: PLAINTEXT.
- **ssl_context** (*ssl.SSLContext*) – pre-configured SSLContext for wrapping socket connections. If provided, all other ssl_* configurations will be ignored. Default: None.
- **ssl_check_hostname** (*bool*) – flag to configure whether ssl handshake should verify that the certificate matches the brokers hostname. default: True.
- **ssl_cafile** (*str*) – optional filename of ca file to use in certificate verification. default: None.
- **ssl_certfile** (*str*) – optional filename of file in pem format containing the client certificate, as well as any ca certificates needed to establish the certificate’s authenticity. default: None.
- **ssl_keyfile** (*str*) – optional filename containing the client private key. default: None.
- **ssl_password** (*callable, str, bytes, bytearray*) – optional password or callable function that returns a password, for decrypting the client private key. Default: None.
- **ssl_crlfile** (*str*) – optional filename containing the CRL to check for certificate expiration. By default, no CRL check is done. When providing a file, only the leaf certificate will be checked against this CRL. The CRL can only be checked with Python 3.4+ or 2.7.9+. default: None.
- **api_version** (*tuple*) – Specify which Kafka API version to use. Accepted values are: (0, 8, 0), (0, 8, 1), (0, 8, 2), (0, 9), (0, 10). Default: (0, 8, 2)
- **api_version_auto_timeout_ms** (*int*) – number of milliseconds to throw a timeout exception from the constructor when checking the broker api version. Only applies if api_version is None
- **selector** (*selectors.BaseSelector*) – Provide a specific selector implementation to use for I/O multiplexing. Default: selectors.DefaultSelector
- **state_change_callback** (*callable*) – function to be called when the connection state changes from CONNECTING to CONNECTED etc.

- **metrics** (*kafka.metrics.Metrics*) – Optionally provide a metrics instance for capturing network IO stats. Default: None.
- **metric_group_prefix** (*str*) – Prefix for metric names. Default: ‘’
- **sasl_mechanism** (*str*) – Authentication mechanism when security_protocol is configured for SASL_PLAINTEXT or SASL_SSL. Valid values are: PLAIN, GSSAPI. Default: PLAIN
- **sasl_plain_username** (*str*) – username for sasl PLAIN authentication. Default: None
- **sasl_plain_password** (*str*) – password for sasl PLAIN authentication. Default: None
- **sasl_kerberos_service_name** (*str*) – Service name to include in GSSAPI sasl mechanism handshake. Default: ‘kafka’

blacked_out ()

Return true if we are disconnected from the given node and can’t re-establish a connection yet

can_send_more ()

Return True unless there are max_in_flight_requests_per_connection.

check_version (*timeout=2, strict=False*)

Attempt to guess the broker version.

Note: This is a blocking call.

Returns: version tuple, i.e. (0, 10), (0, 9), (0, 8, 2), ...

close (*error=None*)

Close socket and fail all in-flight-requests.

Parameters *error* (*Exception, optional*) – pending in-flight-requests will be failed with this exception. Default: kafka.errors.KafkaConnectionError.

connect ()

Attempt to connect and return ConnectionState

connected ()

Return True iff socket is connected.

connecting ()

Returns True if still connecting (this may encompass several different states, such as SSL handshake, authorization, etc).

connection_delay ()

Return the number of milliseconds to wait, based on the connection state, before attempting to send data. When disconnected, this respects the reconnect backoff time. When connecting, returns 0 to allow non-blocking connect to finish. When connected, returns a very large number to handle slow/stalled connections.

disconnected ()

Return True iff socket is closed

recv ()

Non-blocking network receive.

Return list of (response, future) tuples

send (*request*)

send request, return Future()

Can block on network if request is larger than `send_buffer_bytes`

6.2.5 ClusterMetadata

class `kafka.cluster.ClusterMetadata` (***configs*)

A class to manage kafka cluster metadata.

This class does not perform any IO. It simply updates internal state given API responses (`MetadataResponse`, `GroupCoordinatorResponse`).

Keyword Arguments

- **retry_backoff_ms** (*int*) – Milliseconds to backoff when retrying on errors. Default: 100.
- **metadata_max_age_ms** (*int*) – The period of time in milliseconds after which we force a refresh of metadata even if we haven't seen any partition leadership changes to proactively discover any new brokers or partitions. Default: 300000

add_group_coordinator (*group*, *response*)

Update with metadata for a group coordinator

Parameters

- **group** (*str*) – name of group from `GroupCoordinatorRequest`
- **response** (`GroupCoordinatorResponse`) – broker response

Returns True if metadata is updated, False on error

Return type bool

add_listener (*listener*)

Add a callback function to be called on each metadata update

available_partitions_for_topic (*topic*)

Return set of partitions with known leaders

Parameters **topic** (*str*) – topic to check for partitions

Returns {partition (*int*), ... }

Return type set

broker_metadata (*broker_id*)

Get `BrokerMetadata`

Parameters **broker_id** (*int*) – *node_id* for a broker to check

Returns `BrokerMetadata` or `None` if not found

brokers ()

Get all `BrokerMetadata`

Returns {`BrokerMetadata`, ... }

Return type set

coordinator_for_group (*group*)

Return *node_id* of group coordinator.

Parameters **group** (*str*) – name of consumer group

Returns *node_id* for group coordinator

Return type int

failed_update (*exception*)

Update cluster state given a failed MetadataRequest.

leader_for_partition (*partition*)

Return node_id of leader, -1 unavailable, None if unknown.

partitions_for_broker (*broker_id*)

Return TopicPartitions for which the broker is a leader.

Parameters **broker_id** (*int*) – node id for a broker

Returns {TopicPartition, ... }

Return type set

partitions_for_topic (*topic*)

Return set of all partitions for topic (whether available or not)

Parameters **topic** (*str*) – topic to check for partitions

Returns {partition (int), ... }

Return type set

refresh_backoff ()

Return milliseconds to wait before attempting to retry after failure

remove_listener (*listener*)

Remove a previously added listener callback

request_update ()

Flags metadata for update, return Future()

Actual update must be handled separately. This method will only change the reported ttl()

Returns kafka.future.Future (value will be the cluster object after update)

topics (*exclude_internal_topics=True*)

Get set of known topics.

Parameters **exclude_internal_topics** (*bool*) – Whether records from internal topics (such as offsets) should be exposed to the consumer. If set to True the only way to receive records from an internal topic is subscribing to it. Default True

Returns {topic (str), ... }

Return type set

ttl ()

Milliseconds until metadata should be refreshed

update_metadata (*metadata*)

Update cluster state given a MetadataResponse.

Parameters **metadata** (*MetadataResponse*) – broker response to a metadata request

Returns: None

with_partitions (*partitions_to_add*)

Returns a copy of cluster metadata with partitions added

6.3 Simple APIs (DEPRECATED)

6.3.1 SimpleConsumer (DEPRECATED)

```

from kafka import SimpleProducer, SimpleClient

# To consume messages
client = SimpleClient('localhost:9092')
consumer = SimpleConsumer(client, "my-group", "my-topic")
for message in consumer:
    # message is raw byte string -- decode if necessary!
    # e.g., for unicode: `message.decode('utf-8')`
    print(message)

# Use multiprocessing for parallel consumers
from kafka import MultiProcessConsumer

# This will split the number of partitions among two processes
consumer = MultiProcessConsumer(client, "my-group", "my-topic", num_procs=2)

# This will spawn processes such that each handles 2 partitions max
consumer = MultiProcessConsumer(client, "my-group", "my-topic",
                                partitions_per_proc=2)

for message in consumer:
    print(message)

for message in consumer.get_messages(count=5, block=True, timeout=4):
    print(message)

client.close()

```

6.3.2 SimpleProducer (DEPRECATED)

Asynchronous Mode

```

from kafka import SimpleProducer, SimpleClient

# To send messages asynchronously
client = SimpleClient('localhost:9092')
producer = SimpleProducer(client, async_send=True)
producer.send_messages('my-topic', b'async message')

# To send messages in batch. You can use any of the available
# producers for doing this. The following producer will collect
# messages in batch and send them to Kafka after 20 messages are
# collected or every 60 seconds
# Notes:
# * If the producer dies before the messages are sent, there will be losses
# * Call producer.stop() to send the messages and cleanup
producer = SimpleProducer(client,
                          async_send=True,

```

(continues on next page)

(continued from previous page)

```
batch_send_every_n=20,
batch_send_every_t=60)
```

Synchronous Mode

```
from kafka import SimpleProducer, SimpleClient

# To send messages synchronously
client = SimpleClient('localhost:9092')
producer = SimpleProducer(client, async_send=False)

# Note that the application is responsible for encoding messages to type bytes
producer.send_messages('my-topic', b'some message')
producer.send_messages('my-topic', b'this method', b'is variadic')

# Send unicode message
producer.send_messages('my-topic', u'?.encode('utf-8'))

# To wait for acknowledgements
# ACK_AFTER_LOCAL_WRITE : server will wait till the data is written to
#                          a local log before sending response
# ACK_AFTER_CLUSTER_COMMIT : server will block until the message is committed
#                          by all in sync replicas before sending a response
producer = SimpleProducer(client,
                          async_send=False,
                          req_acks=SimpleProducer.ACK_AFTER_LOCAL_WRITE,
                          ack_timeout=2000,
                          sync_fail_on_error=False)

responses = producer.send_messages('my-topic', b'another message')
for r in responses:
    logging.info(r.offset)
```

6.3.3 KeyedProducer (DEPRECATED)

```
from kafka import (
    SimpleClient, KeyedProducer,
    Murmur2Partitioner, RoundRobinPartitioner)

kafka = SimpleClient('localhost:9092')

# HashedPartitioner is default (currently uses python hash())
producer = KeyedProducer(kafka)
producer.send_messages(b'my-topic', b'key1', b'some message')
producer.send_messages(b'my-topic', b'key2', b'this method')

# Murmur2Partitioner attempts to mirror the java client hashing
producer = KeyedProducer(kafka, partitioner=Murmur2Partitioner)

# Or just produce round-robin (or just use SimpleProducer)
producer = KeyedProducer(kafka, partitioner=RoundRobinPartitioner)
```

6.3.4 SimpleClient (DEPRECATED)

```

import time
from kafka import SimpleClient
from kafka.errors import LeaderNotAvailableError, NotLeaderForPartitionError
from kafka.protocol import create_message
from kafka.structs import ProduceRequestPayload

kafka = SimpleClient('localhost:9092')
payload = ProduceRequestPayload(topic='my-topic', partition=0,
                                messages=[create_message("some message")])

retries = 5
resps = []
while retries and not resps:
    retries -= 1
    try:
        resps = kafka.send_produce_request(
            payloads=[payload], fail_on_error=True)
    except LeaderNotAvailableError, NotLeaderForPartitionError:
        kafka.load_metadata_for_topics()
        time.sleep(1)

    # Other exceptions you might consider handling:
    # UnknownTopicOrPartitionError, TopicAuthorizationFailedError,
    # RequestTimedOutError, MessageSizeTooLargeError, InvalidTopicError,
    # RecordListTooLargeError, InvalidRequiredAcksError,
    # NotEnoughReplicasError, NotEnoughReplicasAfterAppendError

kafka.close()

resps[0].topic      # 'my-topic'
resps[0].partition  # 0
resps[0].error      # 0
resps[0].offset     # offset of the first message sent in this request

```

6.4 Install

Install with your favorite package manager

6.4.1 Latest Release

Pip:

```
pip install kafka-python
```

Releases are also listed at <https://github.com/dpkp/kafka-python/releases>

6.4.2 Bleeding-Edge

```
git clone https://github.com/dpkp/kafka-python
pip install ./kafka-python
```

6.4.3 Optional LZ4 install

To enable LZ4 compression/decompression, install python-lz4:

```
>>> pip install lz4
```

6.4.4 Optional Snappy install

Install Development Libraries

Download and build Snappy from <http://code.google.com/p/snappy/downloads/list>

Ubuntu:

```
apt-get install libsnappy-dev
```

OSX:

```
brew install snappy
```

From Source:

```
wget http://snappy.googlecode.com/files/snappy-1.0.5.tar.gz
tar xzvf snappy-1.0.5.tar.gz
cd snappy-1.0.5
./configure
make
sudo make install
```

Install Python Module

Install the *python-snappy* module

```
pip install python-snappy
```

6.4.5 Optional crc32c install

Highly recommended if you are using Kafka 11+ brokers. For those *kafka-python* uses a new message protocol version, that requires calculation of *crc32c*, which differs from *zlib.crc32* hash implementation. By default *kafka-python* calculates it in pure python, which is quite slow. To speed it up we optionally support <https://pypi.python.org/pypi/crc32c> package if it's installed.

```
pip install crc32c
```

6.5 Tests

Test environments are managed via tox. The test suite is run via pytest. Individual tests are written using unittest, pytest, and in some cases, doctest.

Linting is run via pylint, but is generally skipped on pypy due to pylint compatibility / performance issues.

For test coverage details, see <https://coveralls.io/github/dpkp/kafka-python>

The test suite includes unit tests that mock network interfaces, as well as integration tests that setup and teardown kafka broker (and zookeeper) fixtures for client / consumer / producer testing.

6.5.1 Unit tests

To run the tests locally, install tox – *pip install tox* See <https://tox.readthedocs.io/en/latest/install.html>

Then simply run tox, optionally setting the python environment. If unset, tox will loop through all environments.

```
tox -e py27
tox -e py35

# run protocol tests only
tox -- -v test.test_protocol

# re-run the last failing test, dropping into pdb
tox -e py27 -- --lf --pdb

# see available (pytest) options
tox -e py27 -- --help
```

6.5.2 Integration tests

```
KAFKA_VERSION=0.10.1.1 tox -e py27
KAFKA_VERSION=0.8.2.2 tox -e py35
```

Integration tests start Kafka and Zookeeper fixtures. This requires downloading kafka server binaries:

```
./build_integration.sh
```

By default, this will install 0.8.2.2, 0.9.0.1, 0.10.1.1, and 0.10.2.1 brokers into the servers/ directory. To install a specific version,

e.g., set *KAFKA_VERSION=0.10.2.1*:

```
KAFKA_VERSION=0.10.2.1 ./build_integration.sh
```

Then run the tests against supported Kafka versions, simply set the *KAFKA_VERSION* env variable to the server build you want to use for testing:

```
KAFKA_VERSION=0.10.2.1 tox -e py27
```

To test against the kafka source tree, set *KAFKA_VERSION=trunk* [optionally set *SCALA_VERSION* (defaults to 2.10)]

```
SCALA_VERSION=2.11 KAFKA_VERSION=trunk ./build_integration.sh
KAFKA_VERSION=trunk tox -e py35
```

6.6 Compatibility

kafka-python is compatible with (and tested against) broker versions 1.0 through 0.8.0 . kafka-python is not compatible with the 0.8.2-beta release.

kafka-python is tested on python 2.7, 3.4, 3.5, 3.6 and pypy.

Builds and tests via Travis-CI. See <https://travis-ci.org/dpkp/kafka-python>

6.7 Support

For support, see github issues at <https://github.com/dpkp/kafka-python>

Limited IRC chat at #kafka-python on freenode (general chat is #apache-kafka).

For information about Apache Kafka generally, see <https://kafka.apache.org/>

For general discussion of kafka-client design and implementation (not python specific), see <https://groups.google.com/forum/m/#!forum/kafka-clients>

6.8 License

Copyright 2016, Dana Powers, David Arthur, and Contributors (See [AUTHORS](#)).

6.9 Changelog

6.9.1 1.4.2 (Mar 10, 2018)

Bugfixes

- Close leaked selector in version check (dpkp #1425)
- Fix *BrokerConnection.connection_delay()* to return milliseconds (dpkp #1414)
- Use local copies in *Fetcher._fetchable_partitions* to avoid mutation errors (dpkp #1400)
- Fix error var name in *_unpack* (j2gg0s #1403)
- Fix KafkaConsumer compacted offset handling (dpkp #1397)
- Fix byte size estimation with kafka producer (blakeembrey #1393)
- Fix coordinator timeout in consumer poll interface (braedon #1384)

Client

- Add *BrokerConnection.connect_blocking()* to improve bootstrap to multi-address hostnames (dpkp #1411)
- Short-circuit *BrokerConnection.close()* if already disconnected (dpkp #1424)
- Only increase reconnect backoff if all addrinfos have been tried (dpkp #1423)
- Make *BrokerConnection* *.host / .port / .afi* immutable to avoid incorrect 'metadata changed' checks (dpkp #1422)
- Connect with sockaddrs to support non-zero ipv6 scope ids (dpkp #1433)
- Check timeout type in *KafkaClient* constructor (asdaraujo #1293)
- Update string representation of *SimpleClient* (asdaraujo #1293)
- Do not validate *api_version* against known versions (dpkp #1434)

Consumer

- Avoid tight poll loop in consumer when brokers are down (dppk #1415)
- Validate `max_records` in `KafkaConsumer.poll` (dppk #1398)
- KAFKA-5512: Awake heartbeat thread when it is time to poll (dppk #1439)

Producer

- Validate that serializers generate bytes-like (or None) data (dppk #1420)

Core / Protocol

- Support alternative lz4 package: `lz4framed` (everpcpc #1395)
- Use hardware accelerated CRC32C function if available (tvoinarovskiy #1389)
- Add Admin CreatePartitions API call (alexef #1386)

Test Infrastructure

- Close `KafkaConsumer` instances during tests (dppk #1410)
- Introduce new fixtures to prepare for migration to `pytest` (asdaraujo #1293)
- Removed `pytest-catchlog` dependency (asdaraujo #1380)
- Fixes racing condition when message is sent to broker before topic logs are created (asdaraujo #1293)
- Add kafka 1.0.1 release to test fixtures (dppk #1437)

Logging / Error Messages

- Re-enable logging during broker version check (dppk #1430)
- Connection logging cleanups (dppk #1432)
- Remove old `CommitFailed` error message from coordinator (dppk #1436)

6.9.2 1.4.1 (Feb 9, 2018)

Bugfixes

- Fix consumer poll stuck error when no available partition (ckyoog #1375)
- Increase some integration test timeouts (dppk #1374)
- Use `raw` in case string overridden (jeffwidman #1373)
- Fix pending completion `IndexError` bug caused by multiple threads (dppk #1372)

6.9.3 1.4.0 (Feb 6, 2018)

This is a substantial release. Although there are no known ‘showstopper’ bugs as of release, we do recommend you test any planned upgrade to your application prior to running in production.

Some of the major changes include:

- We have officially dropped python 2.6 support
- The `KafkaConsumer` now includes a background thread to handle coordinator heartbeats
- API protocol handling has been separated from networking code into a new class, `KafkaProtocol`
- Added support for kafka message format v2
- Refactored DNS lookups during kafka broker connections
- SASL authentication is working (we think)
- Removed several circular references to improve gc on close()

Thanks to all contributors – the state of the kafka-python community is strong!

Detailed changelog are listed below:

Client

- Fixes for SASL support
 - Refactor SASL/gssapi support (dppk #1248 #1249 #1257 #1262 #1280)
 - Add security layer negotiation to the GSSAPI authentication (asdaraujo #1283)
 - Fix overriding `sasl_kerberos_service_name` in `KafkaConsumer` / `KafkaProducer` (natedogs911 #1264)
 - Fix typo in `_try_authenticate_plain` (everpcpc #1333)
 - Fix for Python 3 byte string handling in SASL auth (christophelec #1353)
- Move callback processing from `BrokerConnection` to `KafkaClient` (dppk #1258)
- Use socket timeout of `request_timeout_ms` to prevent blocking forever on send (dppk #1281)
- Refactor dns lookup in `BrokerConnection` (dppk #1312)
- Read all available socket bytes (dppk #1332)
- Honor `reconnect_backoff` in `conn.connect()` (dppk #1342)

Consumer

- KAFKA-3977: Defer fetch parsing for space efficiency, and to raise exceptions to user (dppk #1245)
- KAFKA-4034: Avoid unnecessary consumer coordinator lookup (dppk #1254)
- Handle `lookup_coordinator` send failures (dppk #1279)
- KAFKA-3888 Use background thread to process consumer heartbeats (dppk #1266)
- Improve `KafkaConsumer` cleanup (dppk #1339)
- Fix coordinator `join_future` race condition (dppk #1338)
- Avoid `KeyError` when filtering fetchable partitions (dppk #1344)
- Name heartbeat thread with `group_id`; use backoff when polling (dppk #1345)

- KAFKA-3949: Avoid race condition when subscription changes during rebalance (dppk #1364)
- Fix #1239 regression to avoid consuming duplicate compressed messages from mid-batch (dppk #1367)

Producer

- Fix timestamp not passed to RecordMetadata (tvoinarovskiy #1273)
- Raise non-API exceptions (jeffwidman #1316)
- Fix reconnect_backoff_max_ms default config bug in KafkaProducer (YaoC #1352)

Core / Protocol

- Add kafka.protocol.parser.KafkaProtocol w/ receive and send (dppk #1230)
- Refactor MessageSet and Message into LegacyRecordBatch to later support v2 message format (tvoinarovskiy #1252)
- Add DefaultRecordBatch implementation aka V2 message format parser/builder. (tvoinarovskiy #1185)
- optimize util.crc32 (ofek #1304)
- Raise better struct pack/unpack errors (jeffwidman #1320)
- Add Request/Response structs for kafka broker 1.0.0 (dppk #1368)

Bugfixes

- use python standard max value (lukekingbru #1303)
- changed for to use enumerate() (TheAtomicOption #1301)
- Explicitly check for None rather than falsey (jeffwidman #1269)
- Minor Exception cleanup (jeffwidman #1317)
- Use non-deprecated exception handling (jeffwidman a699f6a)
- Remove assertion with side effect in client.wakeup() (bgedik #1348)
- use absolute imports everywhere (kevinkjt2000 #1362)

Test Infrastructure

- Use 0.11.0.2 kafka broker for integration testing (dppk #1357 #1244)
- Add a Makefile to help build the project, generate docs, and run tests (tvoinarovskiy #1247)
- Add fixture support for 1.0.0 broker (dppk #1275)
- Add kafka 1.0.0 to travis integration tests (dppk #1365)
- Change fixture default host to localhost (asdaraujo #1305)
- Minor test cleanups (dppk #1343)
- Use latest pytest 3.4.0, but drop pytest-sugar due to incompatibility (dppk #1361)

Documentation

- Expand metrics docs (jeffwidman #1243)
- Fix docstring (jeffwidman #1261)
- Added controlled thread shutdown to example.py (TheAtomicOption #1268)
- Add license to wheel (jeffwidman #1286)
- Use correct casing for MB (jeffwidman #1298)

Logging / Error Messages

- Fix two bugs in printing bytes instance (jeffwidman #1296)

6.9.4 1.3.5 (Oct 7, 2017)

Bugfixes

- Fix partition assignment race condition (jeffwidman #1240)
- Fix consumer bug when seeking / resetting to the middle of a compressed messageset (dphp #1239)
- Fix traceback sent to stderr not logging (dbgasaway #1221)
- Stop using mutable types for default arg values (jeffwidman #1213)
- Remove a few unused imports (jameslamb #1188)

Client

- Refactor BrokerConnection to use asynchronous receive_bytes pipe (dphp #1032)

Consumer

- Drop unused sleep kwarg to poll (dphp #1177)
- Enable KafkaConsumer beginning_offsets() and end_offsets() with older broker versions (buptlly #1200)
- Validate consumer subscription topic strings (nikeee #1238)

Documentation

- Small fixes to SASL documentation and logging; validate security_protocol (dphp #1231)
- Various typo and grammar fixes (jeffwidman)

6.9.5 1.3.4 (Aug 13, 2017)

Bugfixes

- Avoid multiple connection attempts when refreshing metadata (dphp #1067)
- Catch socket.errors when sending / recving bytes on wake socketpair (dphp #1069)

- Deal with brokers that reappear with different IP address (originsmike #1085)
- Fix join-time-max and sync-time-max metrics to use Max() measure function (billyevans #1146)
- Raise AssertionError when decompression unsupported (bts-webber #1159)
- Catch ssl.EOFErrors on Python3.3 so we close the failing conn (Ormod #1162)
- Select on sockets to avoid busy polling during bootstrap (dphp #1175)
- Initialize metadata_snapshot in group coordinator to avoid unnecessary rebalance (dphp #1174)

Client

- Timeout idle connections via connections_max_idle_ms (dphp #1068)
- Warn, dont raise, on DNS lookup failures (dphp #1091)
- Support exponential backoff for broker reconnections – KIP-144 (dphp #1124)
- Add gssapi support (Kerberos) for SASL (Harald-Berghoff #1152)
- Add private map of api key -> min/max versions to BrokerConnection (dphp #1169)

Consumer

- Backoff on unavailable group coordinator retry (dphp #1125)
- Only change_subscription on pattern subscription when topics change (Artimi #1132)
- Add offsets_for_times, beginning_offsets and end_offsets APIs (tvoinarovskyi #1161)

Producer

- Raise KafkaTimeoutError when flush times out (infecto)
- Set producer atexit timeout to 0 to match del (Ormod #1126)

Core / Protocol

- 0.11.0.0 protocol updates (only - no client support yet) (dphp #1127)
- Make UnknownTopicOrPartitionError retrievable error (tvoinarovskyi)

Test Infrastructure

- pylint 1.7.0+ supports python 3.6 and merge py36 into common testenv (jianbin-wei #1095)
- Add kafka 0.10.2.1 into integration testing version (jianbin-wei #1096)
- Disable automated tests for python 2.6 and kafka 0.8.0 and 0.8.1.1 (jianbin-wei #1096)
- Support manual py26 testing; dont advertise 3.3 support (dphp)
- Add 0.11.0.0 server resources, fix tests for 0.11 brokers (dphp)
- Use fixture hostname, dont assume localhost (dphp)
- Add 0.11.0.0 to travis test matrix, remove 0.10.1.1; use scala 2.11 artifacts (dphp #1176)

Logging / Error Messages

- Improve error message when expiring batches in KafkaProducer (dppk #1077)
- Update producer.send docstring – raises KafkaTimeoutError (infecto)
- Use logging’s built-in string interpolation (jeffwidman)
- Fix produce timeout message (melor #1151)
- Fix producer batch expiry messages to use seconds (dnwe)

Documentation

- Fix typo in KafkaClient docstring (jeffwidman #1054)
- Update README: Prefer python-lz4 over lz4tools (kiri11 #1057)
- Fix poll() hyperlink in KafkaClient (jeffwidman)
- Update RTD links with https / .io (jeffwidman #1074)
- Describe consumer thread-safety (ecksun)
- Fix typo in consumer integration test (jeffwidman)
- Note `max_in_flight_requests_per_connection > 1` may change order of messages (tvoinarovskiy #1149)

6.9.6 1.3.3 (Mar 14, 2017)

Core / Protocol

- Derive all api classes from Request / Response base classes (dppk 1030)
- Prefer python-lz4 if available (dppk 1024)
- Fix kwarg handing in `kafka.protocol.struct.Struct` (dppk 1025)
- Fixed couple of “leaks” when gc is disabled (Mephius 979)
- Added `max_bytes` option and `FetchRequest_v3` usage. (Drizzt1991 962)
- `CreateTopicsRequest / Response v1` (dppk 1012)
- Add `MetadataRequest_v2` and `MetadataResponse_v2` structures for KIP-78 (Drizzt1991 974)
- KIP-88 / KAFKA-3853: `OffsetFetch v2` structs (jeffwidman 971)
- DRY-up the `MetadataRequest_v1` struct (jeffwidman 966)
- Add `JoinGroup v1` structs (jeffwidman 965)
- DRY-up the `OffsetCommitResponse` Structs (jeffwidman 970)
- DRY-up the `OffsetFetch` structs (jeffwidman 964)
- `time` → `timestamp` to match Java API (jeffwidman 969)
- Add support for `offsetRequestV1` messages (jlafaye 951)
- Add `FetchRequest/Response_v3` structs (jeffwidman 943)
- Add `CreateTopics / DeleteTopics` Structs (jeffwidman 944)

Test Infrastructure

- Add python3.6 to travis test suite, drop python3.3 (exponea 992)
- Update to 0.10.1.1 for integration testing (dppk 953)
- Update vendored berkerpeksag/selectors34 to ff61b82 (Mephius 979)
- Remove dead code (jeffwidman 967)
- Update pytest fixtures to new yield syntax (jeffwidman 919)

Consumer

- Avoid re-encoding message for crc check (dppk 1027)
- Optionally skip auto-commit during consumer.close (dppk 1031)
- Return copy of consumer subscription set (dppk 1029)
- Short-circuit group coordinator requests when NodeNotReady (dppk 995)
- Avoid unknown coordinator after client poll (dppk 1023)
- No longer configure a default consumer group (dppk 1016)
- Dont refresh metadata on failed group coordinator request unless needed (dppk 1006)
- Fail-fast on timeout constraint violations during KafkaConsumer creation (harelba 986)
- Default max_poll_records to Java default of 500 (jeffwidman 947)
- For 0.8.2, only attempt connection to coordinator if least_loaded_node succeeds (dppk)

Producer

- change default timeout of KafkaProducer.close() to threading.TIMEOUT_MAX on py3 (mmyjona 991)

Client

- Add optional kwarg to ready/is_ready to disable metadata-priority logic (dppk 1017)
- When closing a broker connection without error, fail in-flight-requests with Cancelled (dppk 1010)
- Catch socket errors during ssl handshake (dppk 1007)
- Drop old brokers when rebuilding broker metadata (dppk 1005)
- Drop bad disconnect test – just use the mocked-socket test (dppk 982)
- Add support for Python built without ssl (minagawa-sho 954)
- Do not re-close a disconnected connection (dppk)
- Drop unused last_failure time from BrokerConnection (dppk)
- Use connection state functions where possible (dppk)
- Pass error to BrokerConnection.close() (dppk)

Bugfixes

- Free lz4 decompression context to avoid leak (dphp 1024)
- Fix sasl reconnect bug: auth future must be reset on close (dphp 1003)
- Fix raise exception from SubscriptionState.assign_from_subscribed (qntln 960)
- Fix blackout calculation: mark last_attempt time during connection close (dphp 1008)
- Fix buffer pool reallocation after raising timeout (dphp 999)

Logging / Error Messages

- Add client info logging re bootstrap; log connection attempts to balance with close (dphp)
- Minor additional logging for consumer coordinator (dphp)
- Add more debug-level connection logging (dphp)
- Do not need str(self) when formatting to %s (dphp)
- Add new broker response errors (dphp)
- Small style fixes in kafka.errors (dphp)
- Include the node id in BrokerConnection logging (dphp 1009)
- Replace %s with %r in producer debug log message (chekunkov 973)

Documentation

- Sphinx documentation updates (jeffwidman 1019)
- Add sphinx formatting to hyperlink methods (jeffwidman 898)
- Fix BrokerConnection api_version docs default (jeffwidman 909)
- PEP-8: Spacing & removed unused imports (jeffwidman 899)
- Move BrokerConnection docstring to class (jeffwidman 968)
- Move docstring so it shows up in Sphinx/RTD (jeffwidman 952)
- Remove non-pip install instructions (jeffwidman 940)
- Spelling and grammar changes (melissacrawford396 923)
- Fix typo: coorelation -> correlation (jeffwidman 929)
- Make SSL warning list the correct Python versions (jeffwidman 924)
- Fixup comment reference to _maybe_connect (dphp)
- Add ClusterMetadata sphinx documentation (dphp)

Legacy Client

- Add send_list_offset_request for searching offset by timestamp (charyam 1001)
- Use select to poll sockets for read to reduce CPU usage (jianbin-wei 958)
- Use select.select without instance bounding (adamwen829 949)

6.9.7 1.3.2 (Dec 28, 2016)

Core

- Add kafka.serializer interfaces (dpkp 912)
- from kafka import ConsumerRebalanceListener, OffsetAndMetadata
- Use 0.10.0.1 for integration tests (dpkp 803)

Consumer

- KAFKA-3007: KafkaConsumer max_poll_records (dpkp 831)
- Raise exception if given a non-str topic (ssaamm 824)
- Immediately update metadata for pattern subscription (laz2 915)

Producer

- Update Partitioners for use with KafkaProducer (barrotsteinde 827)
- Sort partitions before calling partitioner (ms7s 905)
- Added ssl_password config option to KafkaProducer class (kierkegaard13 830)

Client

- Always check for request timeouts (dpkp 887)
- When hostname lookup is necessary, do every connect (benauthor 812)

Bugfixes

- Fix errorcode check when socket.connect_ex raises an exception (guojh 907)
- Fix fetcher bug when processing offset out of range (sibiryakov 860)
- Fix possible request draining in ensure_active_group (dpkp 896)
- Fix metadata refresh handling with 0.10+ brokers when topic list is empty (sibiryakov 867)
- KafkaProducer should set timestamp in Message if provided (Drizzt1991 875)
- Fix murmur2 bug handling python2 bytes that do not ascii encode (dpkp 815)
- Monkeypatch max_in_flight_requests_per_connection when checking broker version (dpkp 834)
- Fix message timestamp_type (qix 828)

Logging / Error Messages

- Always include an error for logging when the coordinator is marked dead (dpkp 890)
- Only string-ify BrokerResponseError args if provided (dpkp 889)
- Update warning re advertised.listeners / advertised.host.name (jeffwidman 878)
- Fix unrecognized sasl_mechanism error message (sharego 883)

Documentation

- Add docstring for `max_records` (jeffwidman 897)
- Fixup doc references to `max_in_flight_requests_per_connection`
- Fix typo: `passowrd` -> `password` (jeffwidman 901)
- Fix documentation typo 'Default' -> 'Default'. (rolando 895)
- Added doc for `max_poll_records` option (Drizzt1991 881)
- Remove old design notes from Kafka 8 era (jeffwidman 876)
- Fix documentation typos (jeffwidman 874)
- Fix quota violation exception message (dphp 809)
- Add comment for round robin partitioner with different subscriptions
- Improve `KafkaProducer` docstring for retries configuration

6.9.8 1.3.1 (Aug 8, 2016)

Bugfixes

- Fix `AttributeError` in `BrokerConnectionMetrics` after reconnecting

6.9.9 1.3.0 (Aug 4, 2016)

Incompatible Changes

- Delete `KafkaConnection` class (dphp 769)
- Rename `partition_assignment` -> `assignment` in `MemberMetadata` for consistency
- Move `selectors34` and `socketpair` to `kafka.vendor` (dphp 785)
- Change `api_version` config to tuple; deprecate str with warning (dphp 761)
- Rename `_DEFAULT_CONFIG` -> `DEFAULT_CONFIG` in `KafkaProducer` (dphp 788)

Improvements

- Vendor six 1.10.0 to eliminate runtime dependency (dphp 785)
- Add `KafkaProducer` and `KafkaConsumer.metrics()` with instrumentation similar to java client (dphp 754 / 772 / 794)
- Support Sasl PLAIN authentication (larsjsol PR 779)
- Add checksum and size to `RecordMetadata` and `ConsumerRecord` (KAFKA-3196 / 770 / 594)
- Use `MetadataRequest v1` for 0.10+ `api_version` (dphp 762)
- Fix `KafkaConsumer` autocommit for 0.8 brokers (dphp 756 / 706)
- Improve error logging (dphp 760 / 759)
- Adapt benchmark scripts from <https://github.com/mrafayaleem/kafka-jython> (dphp 754)
- Add `api_version` config to `KafkaClient` (dphp 761)

- New Metadata method with_partitions() (dppk 787)
- Use socket_options configuration to setsockopt(). Default TCP_NODELAY (dppk 783)
- Expose selector type as config option (dppk 764)
- Drain pending requests to the coordinator before initiating group rejoin (dppk 798)
- Send combined size and payload bytes to socket to avoid potentially split packets with TCP_NODELAY (dppk 797)

Bugfixes

- Ignore socket.error when checking for protocol out of sync prior to socket close (dppk 792)
- Fix offset fetch when partitions are manually assigned (KAFKA-3960 / 786)
- Change pickle_method to use python3 special attributes (jpaulodit 777)
- Fix ProduceResponse v2 throttle_time_ms
- Always encode size with MessageSet (#771)
- Avoid buffer overread when compressing messageset in KafkaProducer
- Explicit format string argument indices for python 2.6 compatibility
- Simplify RecordMetadata; short circuit callbacks (#768)
- Fix autocommit when partitions assigned manually (KAFKA-3486 / #767 / #626)
- Handle metadata updates during consumer rebalance (KAFKA-3117 / #766 / #701)
- Add a consumer config option to exclude internal topics (KAFKA-2832 / #765)
- Protect writes to wakeup socket with threading lock (#763 / #709)
- Fetcher spending unnecessary time during metrics recording (KAFKA-3785)
- Always use absolute_import (dppk)

Test / Fixtures

- Catch select errors while capturing test fixture logs
- Fix consumer group test race condition (dppk 795)
- Retry fixture failures on a different port (dppk 796)
- Dump fixture logs on failure

Documentation

- Fix misspelling of password (ssaamm 793)
- Document the ssl_password config option (ssaamm 780)
- Fix typo in KafkaConsumer documentation (ssaamm 775)
- Expand consumer.fetcher inline comments
- Update kafka configuration links -> 0.10.0.0 docs
- Fixup metrics_sample_window_ms docstring in consumer

6.9.10 1.2.5 (July 15, 2016)

Bugfixes

- Fix bug causing KafkaProducer to double-compress message batches on retry
- Check for double-compressed messages in KafkaConsumer, log warning and optionally skip
- Drop recursion in `_unpack_message_set`; only decompress once

6.9.11 1.2.4 (July 8, 2016)

Bugfixes

- Update `consumer_timeout_ms` docstring - KafkaConsumer raises StopIteration, no longer ConsumerTimeout
- Use explicit subscription state flag to handle `seek()` during message iteration
- Fix consumer iteration on compacted topics (dphp PR 752)
- Support `ssl_password` config when loading cert chains (amckemie PR 750)

6.9.12 1.2.3 (July 2, 2016)

Patch Improvements

- Fix gc error log: avoid AttributeError in `_unregister_cleanup` (dphp PR 747)
- Wakeup socket optimizations (dphp PR 740)
- Assert will be disabled by “python -O” (tyronecai PR 736)
- Randomize order of topics/partitions processed by fetcher to improve balance (dphp PR 732)
- Allow `client.check_version` timeout to be set in Producer and Consumer constructors (eastlondoner PR 647)

6.9.13 1.2.2 (June 21, 2016)

Bugfixes

- Clarify timeout unit in KafkaProducer `close` and `flush` (ms7s PR 734)
- Avoid busy poll during metadata refresh failure with `retry_backoff_ms` (dphp PR 733)
- `check_version` should scan nodes until version found or timeout (dphp PR 731)
- Fix bug which could cause `least_loaded_node` to always return the same unavailable node (dphp PR 730)
- Fix producer garbage collection with weakref in `atexit` handler (dphp PR 728)
- Close client selector to fix fd leak (msmith PR 729)
- Tweak spelling mistake in error const (steve8918 PR 719)
- Rearrange connection tests to separate legacy KafkaConnection

6.9.14 1.2.1 (June 1, 2016)

Bugfixes

- Fix regression in MessageSet decoding wrt PartialMessages (#716)
- Catch response decode errors and log details (#715)
- Fix Legacy support url (#712 - JonasGroeger)
- Update sphinx docs re 0.10 broker support

6.9.15 1.2.0 (May 24, 2016)

Support Kafka 0.10 Features

- Add protocol support for ApiVersionRequest (dppk PR 678)
- KAFKA-3025: Message v1 – add timestamp and relative offsets (dppk PR 693)
- Use Fetch/Produce API v2 for brokers \geq 0.10 (uses message format v1) (dppk PR 694)
- Use standard LZ4 framing for v1 messages / kafka 0.10 (dppk PR 695)

Consumers

- Update SimpleConsumer / legacy protocol to handle compressed messages (paulcavallaro PR 684)

Producers

- KAFKA-3388: Fix expiration of batches sitting in the accumulator (dppk PR 699)
- KAFKA-3197: when `max.in.flight.request.per.connection = 1`, attempt to guarantee ordering (dppk PR 698)
- Don't use soon-to-be-reserved keyword `await` as function name (FutureProduceResult) (dppk PR 697)

Clients

- Fix socket leaks in KafkaClient (dppk PR 696)

Documentation

<none>

Internals

- Support SSL CRL [requires python 2.7.9+ / 3.4+] (vincentbernat PR 683)
- Use original hostname for SSL checks (vincentbernat PR 682)
- Always pass encoded message bytes to MessageSet.encode()
- Raise ValueError on protocol encode/decode errors
- Supplement socket.gaierror exception in BrokerConnection.connect() (erikbeebe PR 687)

- BrokerConnection check_version: expect 0.9 to fail with CorrelationIdError
- Fix small bug in Sensor (zackdever PR 679)

6.9.16 1.1.1 (Apr 26, 2016)

Bugfixes

- Fix throttle_time_ms sensor handling (zackdever PR 667)
- Improve handling of disconnected sockets (EasyPost PR 666 / dpkp)
- Disable standard metadata refresh triggers during bootstrap (dpkp)
- More predictable Future callback/errback exceptions (zackdever PR 670)
- Avoid some exceptions in Coordinator.__del__ (dpkp PR 668)

6.9.17 1.1.0 (Apr 25, 2016)

Consumers

- Avoid resending FetchRequests that are pending on internal queue
- Log debug messages when skipping fetched messages due to offset checks
- KAFKA-3013: Include topic-partition in exception for expired batches
- KAFKA-3318: clean up consumer logging and error messages
- Improve unknown coordinator error handling
- Improve auto-commit error handling when group_id is None
- Add paused() API (zackdever PR 602)
- Add default_offset_commit_callback to KafkaConsumer DEFAULT_CONFIGS

Producers

<none>

Clients

- Support SSL connections
- Use selectors module for non-blocking IO
- Refactor KafkaClient connection management
- Fix AttributeError in __del__
- SimpleClient: catch errors thrown by _get_leader_for_partition (zackdever PR 606)

Documentation

- Fix serializer/deserializer examples in README
- Update max.block.ms docstring
- Remove errant next(consumer) from consumer documentation
- Add producer.flush() to usage docs

Internals

- Add initial metrics implementation (zackdever PR 637)
- KAFKA-2136: support Fetch and Produce v1 (throttle_time_ms)
- Use version-indexed lists for request/response protocol structs (dphp PR 630)
- Split kafka.common into kafka.structs and kafka.errors
- Handle partial socket send() (dphp PR 611)
- Fix windows support (dphp PR 603)
- IPv6 support (TimEvens PR 615; Roguelazer PR 642)

6.9.18 1.0.2 (Mar 14, 2016)

Consumers

- Improve KafkaConsumer Heartbeat handling (dphp PR 583)
- Fix KafkaConsumer.position bug (stefanth PR 578)
- Raise TypeError when partition is not a TopicPartition (dphp PR 587)
- KafkaConsumer.poll should sleep to prevent tight-loops (dphp PR 597)

Producers

- Fix producer threading bug that can crash sender (dphp PR 590)
- Fix bug in producer buffer pool reallocation (dphp PR 585)
- Remove spurious warnings when closing sync SimpleProducer (twm PR 567)
- Fix FutureProduceResult.await() on python2.6 (dphp)
- Add optional timeout parameter to KafkaProducer.flush() (dphp)
- KafkaProducer optimizations (zackdever PR 598)

Clients

- Improve error handling in SimpleClient.load_metadata_for_topics (dphp)
- Improve handling of KafkaClient.least_loaded_node failure (dphp PR 588)

Documentation

- Fix KafkaError import error in docs (shichao-an PR 564)
- Fix serializer / deserializer examples (scribu PR 573)

Internals

- Update to Kafka 0.9.0.1 for integration testing
- Fix `ifr.future.failure` in `conn.py` (mortenlj PR 566)
- Improve Zookeeper / Kafka Fixture management (dphp)

6.9.19 1.0.1 (Feb 19, 2016)

Consumers

- Add `RangePartitionAssignor` (and use as default); add assignor tests (dphp PR 550)
- Make sure all consumers are in same generation before stopping group test
- Verify node ready before sending offset fetch request from coordinator
- Improve warning when offset fetch request returns unknown topic / partition

Producers

- Warn if pending batches failed during flush
- Fix concurrency bug in `RecordAccumulator.ready()`
- Fix bug in `SimpleBufferPool` memory condition waiting / timeout
- Support `batch_size = 0` in producer buffers (dphp PR 558)
- Catch duplicate `batch.done()` calls [e.g., `maybe_expire` then a response errback]

Clients

Documentation

- Improve `kafka.cluster` docstrings
- Migrate `load_example.py` to `KafkaProducer` / `KafkaConsumer`

Internals

- Don't override system `rcvbuf` or `sndbuf` unless configured explicitly (dphp PR 557)
- Some attributes may not exist in `__del__` if we failed assertions
- Break up some circular references and close client wake pipes on `__del__` (aisch PR 554)

6.9.20 1.0.0 (Feb 15, 2016)

This release includes significant code changes. Users of older kafka-python versions are encouraged to test upgrades before deploying to production as some interfaces and configuration options have changed.

Users of SimpleConsumer / SimpleProducer / SimpleClient (formerly KafkaClient) from prior releases should migrate to KafkaConsumer / KafkaProducer. Low-level APIs (Simple*) are no longer being actively maintained and will be removed in a future release.

For comprehensive API documentation, please see `python help()` / `docstrings`, `kafka-python.readthedocs.org`, or run `'tox -e docs'` from source to build documentation locally.

Consumers

- KafkaConsumer re-written to emulate the new 0.9 kafka consumer (java client) and support coordinated consumer groups (feature requires $\geq 0.9.0.0$ brokers)
 - Methods no longer available:
 - * `configure` [initialize a new consumer instead]
 - * `set_topic_partitions` [use `subscribe()` or `assign()`]
 - * `fetch_messages` [use `poll()` or iterator interface]
 - * `get_partition_offsets`
 - * `offsets` [use `committed(partition)`]
 - * `task_done` [handled internally by auto-commit; or commit offsets manually]
 - Configuration changes (consistent with updated java client):
 - * lots of new configuration parameters – see docs for details
 - * `auto_offset_reset`: previously values were ‘smallest’ or ‘largest’, now values are ‘earliest’ or ‘latest’
 - * `fetch_wait_max_ms` is now `fetch_max_wait_ms`
 - * `max_partition_fetch_bytes` is now `max_partition_fetch_bytes`
 - * `deserializer_class` is now `value_deserializer` and `key_deserializer`
 - * `auto_commit_enable` is now `enable_auto_commit`
 - * `auto_commit_interval_messages` was removed
 - * `socket_timeout_ms` was removed
 - * `refresh_leader_backoff_ms` was removed
- SimpleConsumer and MultiProcessConsumer are now deprecated and will be removed in a future release. Users are encouraged to migrate to KafkaConsumer.

Producers

- new producer class: `KafkaProducer`. Exposes the same interface as official java client. Async by default; returned `future.get()` can be called for synchronous blocking
- SimpleProducer is now deprecated and will be removed in a future release. Users are encouraged to migrate to `KafkaProducer`.

Clients

- synchronous `KafkaClient` renamed to `SimpleClient`. For backwards compatibility, you will get a `SimpleClient` via `'from kafka import KafkaClient'`. This will change in a future release.
- All client calls use non-blocking IO under the hood.
- Add probe method `check_version()` to infer broker versions.

Documentation

- Updated README and sphinx documentation to address new classes.
- Docstring improvements to make python `help()` easier to use.

Internals

- Old protocol stack is deprecated. It has been moved to `kafka.protocol.legacy` and may be removed in a future release.
- Protocol layer re-written using Type classes, Schemas and Structs (modeled on the java client).
- Add support for LZ4 compression (including broken framing header checksum).

6.9.21 0.9.5 (Dec 6, 2015)

Consumers

- Initial support for consumer coordinator: offsets only (toddpalino PR 420)
- Allow blocking until some messages are received in `SimpleConsumer` (saaros PR 457)
- Support subclass config changes in `KafkaConsumer` (zackdever PR 446)
- Support retry semantics in `MultiProcessConsumer` (barricadeio PR 456)
- Support `partition_info` in `MultiProcessConsumer` (scrapinghub PR 418)
- Enable `seek()` to an absolute offset in `SimpleConsumer` (haosdent PR 412)
- Add `KafkaConsumer.close()` (ucarion PR 426)

Producers

- Catch `client.reinit()` exceptions in async producer (dphp)
- `Producer.stop()` now blocks until async thread completes (dphp PR 485)
- Catch errors during `load_metadata_for_topics` in async producer (bschopman PR 467)
- Add compression-level support for codecs that support it (trbs PR 454)
- Fix translation of Java murmur2 code, fix byte encoding for Python 3 (chrischamberlin PR 439)
- Only call `stop()` on not-stopped producer objects (docker-hub PR 435)
- Allow null payload for deletion feature (scrapinghub PR 409)

Clients

- Use non-blocking io for broker aware requests (ecanzonieri PR 473)
- Use debug logging level for metadata request (ecanzonieri PR 415)
- Catch KafkaUnavailableError in `_send_broker_aware_request` (mutability PR 436)
- Lower logging level on replica not available and commit (ecanzonieri PR 415)

Documentation

- Update docs and links wrt maintainer change (mumrah -> dpkp)

Internals

- Add py35 to tox testing
- Update travis config to use container infrastructure
- Add 0.8.2.2 and 0.9.0.0 resources for integration tests; update default official releases
- new pylint disables for pylint 1.5.1 (zackdever PR 481)
- Fix python3 / python2 comments re `queue/Queue` (dpkp)
- Add `Murmur2Partitioner` to kafka `__all__` imports (dpkp Issue 471)
- Include LICENSE in PyPI sdist (koobs PR 441)

6.9.22 0.9.4 (June 11, 2015)

Consumers

- Refactor `SimpleConsumer` internal fetch handling (dpkp PR 399)
- Handle exceptions in `SimpleConsumer` `commit()` and `reset_partition_offset()` (dpkp PR 404)
- Improve `FailedPayloadsError` handling in `KafkaConsumer` (dpkp PR 398)
- `KafkaConsumer`: avoid raising `KeyError` in `task_done` (dpkp PR 389)
- `MultiProcessConsumer` – support configured partitions list (dpkp PR 380)
- Fix `SimpleConsumer` leadership change handling (dpkp PR 393)
- Fix `SimpleConsumer` connection error handling (reAsOn2010 PR 392)
- Improve Consumer handling of ‘falsy’ partition values (wting PR 342)
- Fix `_offsets` call error in `KafkaConsumer` (hellais PR 376)
- Fix str/bytes bug in `KafkaConsumer` (dpkp PR 365)
- Register atexit handlers for consumer and producer thread/multiprocess cleanup (dpkp PR 360)
- Always fetch commit offsets in base consumer unless group is None (dpkp PR 356)
- Stop consumer threads on delete (dpkp PR 357)
- Deprecate `metadata_broker_list` in favor of `bootstrap_servers` in `KafkaConsumer` (dpkp PR 340)
- Support pass-through parameters in multiprocess consumer (scrapinghub PR 336)

- Enable offset commit on SimpleConsumer.seek (ecanzonieri PR 350)
- Improve multiprocessing consumer partition distribution (scrapinghub PR 335)
- Ignore messages with offset less than requested (wkiser PR 328)
- Handle OffsetOutOfRange in SimpleConsumer (ecanzonieri PR 296)

Producers

- Add Murmur2Partitioner (dphp PR 378)
- Log error types in SimpleProducer and SimpleConsumer (dphp PR 405)
- SimpleProducer support configuration of fail_on_error (dphp PR 396)
- Deprecate KeyedProducer.send() (dphp PR 379)
- Further improvements to async producer code (dphp PR 388)
- Add more configuration parameters for async producer (dphp)
- Deprecate SimpleProducer batch_send=True in favor of async (dphp)
- Improve async producer error handling and retry logic (vshlapakov PR 331)
- Support message keys in async producer (vshlapakov PR 329)
- Use threading instead of multiprocessing for Async Producer (vshlapakov PR 330)
- Stop threads on __del__ (chmduquesne PR 324)
- Fix leadership failover handling in KeyedProducer (dphp PR 314)

KafkaClient

- Add .topics property for list of known topics (dphp)
- Fix request / response order guarantee bug in KafkaClient (dphp PR 403)
- Improve KafkaClient handling of connection failures in _get_conn (dphp)
- Client clears local metadata cache before updating from server (dphp PR 367)
- KafkaClient should return a response or error for each request - enable better retry handling (dphp PR 366)
- Improve str/bytes conversion in KafkaClient and KafkaConsumer (dphp PR 332)
- Always return sorted partition ids in client.get_partition_ids_for_topic() (dphp PR 315)

Documentation

- Cleanup Usage Documentation
- Improve KafkaConsumer documentation (dphp PR 341)
- Update consumer documentation (sontek PR 317)
- Add doc configuration for tox (sontek PR 316)
- Switch to .rst doc format (sontek PR 321)
- Fixup google groups link in README (sontek PR 320)
- Automate documentation at kafka-python.readthedocs.org

Internals

- Switch integration testing from 0.8.2.0 to 0.8.2.1 (dppk PR 402)
- Fix most flaky tests, improve debug logging, improve fixture handling (dppk)
- General style cleanups (dppk PR 394)
- Raise error on duplicate topic-partition payloads in protocol grouping (dppk)
- Use module-level loggers instead of simply 'kafka' (dppk)
- Remove pkg_resources check for __version__ at runtime (dppk PR 387)
- Make external API consistently support python3 strings for topic (kecaps PR 361)
- Fix correlation id overflow (dppk PR 355)
- Cleanup kafka/common structs (dppk PR 338)
- Use context managers in gzip_encode / gzip_decode (dppk PR 337)
- Save failed request as FailedPayloadsError attribute (jobevers PR 302)
- Remove unused kafka.queue (mumrah)

6.9.23 0.9.3 (Feb 3, 2015)

- Add coveralls.io support (sontek PR 307)
- Fix python2.6 threading.Event bug in ReentrantTimer (dppk PR 312)
- Add kafka 0.8.2.0 to travis integration tests (dppk PR 310)
- Auto-convert topics to utf-8 bytes in Producer (sontek PR 306)
- Fix reference cycle between SimpleConsumer and ReentrantTimer (zhaopengzp PR 309)
- Add Sphinx API docs (wedaly PR 282)
- Handle additional error cases exposed by 0.8.2.0 kafka server (dppk PR 295)
- Refactor error class management (alexcb PR 289)
- Expose KafkaConsumer in __all__ for easy imports (Dinoshauer PR 286)
- SimpleProducer starts on random partition by default (alexcb PR 288)
- Add keys to compressed messages (meandthewallaby PR 281)
- Add new high-level KafkaConsumer class based on java client api (dppk PR 234)
- Add KeyedProducer.send_messages api (pubnub PR 277)
- Fix consumer pending() method (jettify PR 276)
- Update low-level demo in README (sunisdown PR 274)
- Include key in KeyedProducer messages (se7entyse7en PR 268)
- Fix SimpleConsumer timeout behavior in get_messages (dppk PR 238)
- Fix error in consumer.py test against max_buffer_size (rthille/wizzat PR 225/242)
- Improve string concat performance on pypy / py3 (dppk PR 233)
- Reorg directory layout for consumer/producer/partitioners (dppk/wizzat PR 232/243)

- Add OffsetCommitContext (locationlabs PR 217)
- Metadata Refactor (dpkp PR 223)
- Add Python 3 support (brutasse/wizzat - PR 227)
- Minor cleanups - imports / README / PyPI classifiers (dpkp - PR 221)
- Fix socket test (dpkp - PR 222)
- Fix exception catching bug in test_failover_integration (zever - PR 216)

6.9.24 0.9.2 (Aug 26, 2014)

- Warn users that async producer does not reliably handle failures (dpkp - PR 213)
- Fix spurious ConsumerFetchSizeTooSmall error in consumer (DataDog - PR 136)
- Use PyLint for static error checking (dpkp - PR 208)
- Strictly enforce str message type in producer.send_messages (dpkp - PR 211)
- Add test timers via nose-timer plugin; list 10 slowest timings by default (dpkp)
- Move fetching last known offset logic to a stand alone function (zever - PR 177)
- Improve KafkaConnection and add more tests (dpkp - PR 196)
- Raise TypeError if necessary when encoding strings (mdaniel - PR 204)
- Use Travis-CI to publish tagged releases to pypi (tkuhlman / mumrah)
- Use official binary tarballs for integration tests and parallelize travis tests (dpkp - PR 193)
- Improve new-topic creation handling (wizzat - PR 174)

6.9.25 0.9.1 (Aug 10, 2014)

- Add codec parameter to Producers to enable compression (patricklucas - PR 166)
- Support IPv6 hosts and network (snaury - PR 169)
- Remove dependency on distribute (patricklucas - PR 163)
- Fix connection error timeout and improve tests (wizzat - PR 158)
- SimpleProducer randomization of initial round robin ordering (alexcb - PR 139)
- Fix connection timeout in KafkaClient and KafkaConnection (maciejkula - PR 161)
- Fix seek + commit behavior (wizzat - PR 148)

6.9.26 0.9.0 (Mar 21, 2014)

- Connection refactor and test fixes (wizzat - PR 134)
- Fix when partition has no leader (mrtheb - PR 109)
- Change Producer API to take topic as send argument, not as instance variable (rdiomar - PR 111)
- Substantial refactor and Test Fixing (rdiomar - PR 88)
- Fix Multiprocess Consumer on windows (mahendra - PR 62)

- Improve fault tolerance; add integration tests (jimjh)
- PEP8 / Flakes / Style cleanups (Vetoshkin Nikita; mrtheb - PR 59)
- Setup Travis CI (jimjh - PR 53/54)
- Fix import of BufferUnderflowError (jimjh - PR 49)
- Fix code examples in README (StevenLeRoux - PR 47/48)

6.9.27 0.8.0

- Changing auto_commit to False in [SimpleConsumer](kafka/consumer.py), until 0.8.1 is release offset commits are unsupported
- Adding fetch_size_bytes to SimpleConsumer constructor to allow for user-configurable fetch sizes
- Allow SimpleConsumer to automatically increase the fetch size if a partial message is read and no other messages were read during that fetch request. The increase factor is 1.5
- Exception classes moved to kafka.common

A

`add_group_coordinator()` (kafka.cluster.ClusterMetadata method), 36
`add_listener()` (kafka.cluster.ClusterMetadata method), 36
`add_topic()` (kafka.client.KafkaClient method), 31
`assign()` (kafka.KafkaConsumer method), 19
`assignment()` (kafka.KafkaConsumer method), 19
`available_partitions_for_topic()` (kafka.cluster.ClusterMetadata method), 36

B

`beginning_offsets()` (kafka.KafkaConsumer method), 19
`blacked_out()` (kafka.BrokerConnection method), 35
`broker_metadata()` (kafka.cluster.ClusterMetadata method), 36
`BrokerConnection` (class in kafka), 33
`brokers()` (kafka.cluster.ClusterMetadata method), 36

C

`can_send_more()` (kafka.BrokerConnection method), 35
`check_version()` (kafka.BrokerConnection method), 35
`check_version()` (kafka.client.KafkaClient method), 31
`close()` (kafka.BrokerConnection method), 35
`close()` (kafka.client.KafkaClient method), 31
`close()` (kafka.KafkaConsumer method), 20
`close()` (kafka.KafkaProducer method), 28
`cluster` (kafka.client.KafkaClient attribute), 29
`ClusterMetadata` (class in kafka.cluster), 36
`commit()` (kafka.KafkaConsumer method), 20
`commit_async()` (kafka.KafkaConsumer method), 20
`committed()` (kafka.KafkaConsumer method), 20
`connect()` (kafka.BrokerConnection method), 35
`connected()` (kafka.BrokerConnection method), 35
`connected()` (kafka.client.KafkaClient method), 31
`connecting()` (kafka.BrokerConnection method), 35
`connection_delay()` (kafka.BrokerConnection method), 35

`connection_delay()` (kafka.client.KafkaClient method), 31
`coordinator_for_group()` (kafka.cluster.ClusterMetadata method), 36

D

`disconnected()` (kafka.BrokerConnection method), 35

E

`end_offsets()` (kafka.KafkaConsumer method), 21

F

`failed_update()` (kafka.cluster.ClusterMetadata method), 37
`flush()` (kafka.KafkaProducer method), 28

H

`highwater()` (kafka.KafkaConsumer method), 21

I

`in_flight_request_count()` (kafka.client.KafkaClient method), 32
`is_disconnected()` (kafka.client.KafkaClient method), 32
`is_ready()` (kafka.client.KafkaClient method), 32

K

`KafkaClient` (class in kafka.client), 29
`KafkaConsumer` (class in kafka), 15
`KafkaProducer` (class in kafka), 24

L

`leader_for_partition()` (kafka.cluster.ClusterMetadata method), 37
`least_loaded_node()` (kafka.client.KafkaClient method), 32

M

`metrics()` (kafka.KafkaConsumer method), 21
`metrics()` (kafka.KafkaProducer method), 28

O

offsets_for_times() (kafka.KafkaConsumer method), 21

P

partitions_for() (kafka.KafkaProducer method), 29
partitions_for_broker() (kafka.cluster.ClusterMetadata method), 37
partitions_for_topic() (kafka.cluster.ClusterMetadata method), 37
partitions_for_topic() (kafka.KafkaConsumer method), 22
pause() (kafka.KafkaConsumer method), 22
paused() (kafka.KafkaConsumer method), 22
poll() (kafka.client.KafkaClient method), 32
poll() (kafka.KafkaConsumer method), 22
position() (kafka.KafkaConsumer method), 23

R

ready() (kafka.client.KafkaClient method), 33
recv() (kafka.BrokerConnection method), 35
refresh_backoff() (kafka.cluster.ClusterMetadata method), 37
remove_listener() (kafka.cluster.ClusterMetadata method), 37
request_update() (kafka.cluster.ClusterMetadata method), 37
resume() (kafka.KafkaConsumer method), 23

S

seek() (kafka.KafkaConsumer method), 23
seek_to_beginning() (kafka.KafkaConsumer method), 23
seek_to_end() (kafka.KafkaConsumer method), 23
send() (kafka.BrokerConnection method), 35
send() (kafka.client.KafkaClient method), 33
send() (kafka.KafkaProducer method), 29
set_topics() (kafka.client.KafkaClient method), 33
subscribe() (kafka.KafkaConsumer method), 23
subscription() (kafka.KafkaConsumer method), 24

T

topics() (kafka.cluster.ClusterMetadata method), 37
topics() (kafka.KafkaConsumer method), 24
ttl() (kafka.cluster.ClusterMetadata method), 37

U

unsubscribe() (kafka.KafkaConsumer method), 24
update_metadata() (kafka.cluster.ClusterMetadata method), 37

W

with_partitions() (kafka.cluster.ClusterMetadata method), 37