

---

# **MyGene.info Documentation**

***Release 3.0***

**Chunlei Wu**

September 12, 2016



<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>What's new in v3 API</b>	<b>3</b>
<b>3</b>	<b>Quick start</b>	<b>5</b>
3.1	Gene query service . . . . .	5
3.1.1	URL . . . . .	5
3.1.2	Examples . . . . .	5
3.1.3	To learn more . . . . .	5
3.2	Gene annotation service . . . . .	6
3.2.1	URL . . . . .	6
3.2.2	Examples . . . . .	6
3.2.3	To learn more . . . . .	6
<b>4</b>	<b>Documentation</b>	<b>7</b>
4.1	Migration from v2 API . . . . .	7
4.1.1	URL change . . . . .	7
4.1.2	Returned Objects . . . . .	7
4.2	Gene annotation data . . . . .	11
4.2.1	Data sources . . . . .	11
4.2.2	Gene object . . . . .	12
4.2.3	Species . . . . .	12
4.2.4	Genome assemblies . . . . .	13
4.2.5	Available fields . . . . .	13
4.3	Gene query service . . . . .	13
4.3.1	Service endpoint . . . . .	13
4.3.2	GET request . . . . .	14
4.3.3	Batch queries via POST . . . . .	20
4.4	Gene annotation service . . . . .	23
4.4.1	Service endpoint . . . . .	23
4.4.2	GET request . . . . .	23
4.4.3	Batch queries via POST . . . . .	74
4.5	Usage and Demo . . . . .	76
4.5.1	Call from web applications . . . . .	76
4.5.2	Demo Applications . . . . .	77
4.5.3	Autocomplete widget for gene query . . . . .	78
4.6	Third-party packages . . . . .	79
4.6.1	MyGene python module . . . . .	79

4.6.2	MyGene autocomplete widget . . . . .	80
4.6.3	Another MyGene Python wrapper . . . . .	80
4.7	Terms of Use . . . . .	81
<b>5</b>	<b>How to cite</b>	<b>83</b>
<b>6</b>	<b>FAQ</b>	<b>85</b>
<b>7</b>	<b>Related links</b>	<b>87</b>
<b>8</b>	<b>Contact us</b>	<b>89</b>

---

# Introduction

---



MyGene.info provides simple-to-use REST web services to query/retrieve gene annotation data. It's designed with **simplicity** and **performance** emphasized. A typical use case is to use it to power a web application which requires querying genes and obtaining common gene annotations. For example, MyGene.info services are used to power BioGPS.



---

## What's new in v3 API

---

- Refseq accession number now contains version
- “ensembl”, “refseq” and “accession” contains associations between RNA and protein
- Better mapping between Ensembl and Entrez gene IDs
- JSON structure slightly changed
- and more bugfixes

You can read more details about this version on our **blog <http://mygene.info/mygene-info-v3-is-out>**

Migration guide from v2 to v3 API

Still want to stick with v2 API for a while? It's still there: [v2 API](#), but annotation data there won't be updated any more.





---

## Quick start

---

MyGene.info provides two simple web services: one for gene queries and the other for gene annotation retrieval. Both return results in [JSON](#) format.

### 3.1 Gene query service

#### 3.1.1 URL

```
http://mygene.info/v3/query
```

#### 3.1.2 Examples

```
http://mygene.info/v3/query?q=cdk2
http://mygene.info/v3/query?q=cdk2&species=human
http://mygene.info/v3/query?q=cdk?
http://mygene.info/v3/query?q=IL*
http://mygene.info/v3/query?q=entrezgene:1017
http://mygene.info/v3/query?q=ensemblgene:ENSG00000123374
http://mygene.info/v3/query?q=cdk2&fields=symbol,refseq
```

---

**Hint:** View nicely formatted JSON result in your browser with this handy add-on: [JSON formater](#) for Chrome or [JSONView](#) for Firefox.

---

#### 3.1.3 To learn more

- You can read the full description of our query syntax [here](#).
- Try it live on [interactive API page](#).
- Play with our demo applications.
- Batch queries? Yes, you can. do it with a POST request.

## 3.2 Gene annotation service

### 3.2.1 URL

```
http://mygene.info/v3/gene/<geneid>
```

### 3.2.2 Examples

```
http://mygene.info/v3/gene/1017  
http://mygene.info/v3/gene/ENSG00000123374  
http://mygene.info/v3/gene/1017?fields=name,symbol,summary
```

“<geneid>” can be any of valid Entrez or Ensembl Gene ids. A retired Entrez Gene id works too if it is replaced by a new one.

### 3.2.3 To learn more

- You can read the full description of our query syntax [here](#).
- Try it live on [interactive API page](#).
- Play with our demo applications.
- Yes, batch queries via POST request as well.

## 4.1 Migration from v2 API

Migrating from v2 API to v3 API is easy. Here's a summary of the changes. You may also want to read our [blog](#) for complementary information.

### 4.1.1 URL change

You will need to access v3 API using “/v3” prefix for service urls:

#### Gene query service endpoint

**v2** <http://mygene.info/v2/query>

**v3** <http://mygene.info/v3/query>

#### Gene annotation service endpoint

**v2** <http://mygene.info/v2/gene>

**v3** <http://mygene.info/v3/gene>

### 4.1.2 Returned Objects

There are several small changes in the returned data structure, as summarized here:

#### Accession number with version

“**refseq**” and “**accession**” fields now contain accession number including version. Data can be search with and without version. Version is available for “*genomic*”, “*rna*” and “*protein*” accession number keys.

---

**Note:** “*genomic*” field is returned but is not searchable

---

**v2:** [http://mygene.info/v2/query?q=NM\\_052827&fields=refseq.rna](http://mygene.info/v2/query?q=NM_052827&fields=refseq.rna)

```

1 {
2   "hits": [
3     {
4       "_id": "1017",
5       "refseq": {
6         "rna": [
7           "NM_001290230",
8           "NM_001798",
9           "NM_052827",
10          "XM_011537732"
11        ]
12      }
13    }
14  ],
15  "max_score": 0.51962745,
16  "took": 3,
17  "total": 1
18 }
19

```

v3: [http://mygene.info/v3/query?q=NM\\_052827&fields=refseq.rna](http://mygene.info/v3/query?q=NM_052827&fields=refseq.rna)

```

1 {
2   "hits": [
3     {
4       "_id": "1017",
5       "_score": 10.052136,
6       "refseq": {
7         "rna": [
8           "NM_001290230.1",
9           "NM_001798.4",
10          "NM_052827.3",
11          "XM_011537732.1"
12        ]
13      }
14    }
15  ],
16  "total": 1,
17  "took": 14,
18  "max_score": 10.052136
19 }

```

### “translation” field for RNA-protein mapping

For “ensembl”, “refseq” and “accession” fields, a new sub-field name “*translation*” is now available. It gives the association between RNA and its protein product. v2 does not have this information in returned objects.

v3: [http://mygene.info/v3/query?q=NM\\_052827&fields=refseq.translation,refseq.rna,refseq.protein](http://mygene.info/v3/query?q=NM_052827&fields=refseq.translation,refseq.rna,refseq.protein)

```

1 {
2   "max_score": 10.052136,
3   "total": 1,
4   "hits": [
5     {
6       "_id": "1017",
7       "_score": 10.052136,
8       "refseq": {
9         "protein": [

```

```

10     "NP_001277159.1",
11     "NP_001789.2",
12     "NP_439892.2",
13     "XP_011536034.1"
14 ],
15   "rna": [
16     "NM_001290230.1",
17     "NM_001798.4",
18     "NM_052827.3",
19     "XM_011537732.1"
20 ],
21   "translation": [
22     {
23       "protein": "XP_011536034.1",
24       "rna": "XM_011537732.1"
25     },
26     {
27       "protein": "NP_001789.2",
28       "rna": "NM_001798.4"
29     },
30     {
31       "protein": "NP_439892.2",
32       "rna": "NM_052827.3"
33     },
34     {
35       "protein": "NP_001277159.1",
36       "rna": "NM_001290230.1"
37     }
38   ]
39 }
40 }
41 ],
42 "took": 4
43 }

```

### “exons” data structure modification

**Warning:** Backward-incompatible, data structure changed

“exons” field has two major modifications. It now contains a list of dictionary instead of a dictionary indexed by the accession number. This accession number is found within the dictionary under the key “*transcript*”. Finally, inner “exons” key has been rename to “*position*”.

v2: <http://mygene.info/v2/gene/1698?fields=exons>

```

1 {
2   "_id": "259236",
3   "exons": {
4     "NM_147196": {
5       "cdsstart": 46701487,
6       "cdsend": 46709688,
7       "txstart": 46701332,
8       "txend": 46710923,
9       "chr": "3",
10      "exons": [
11        [

```

```

12     46701332,
13     46701580
14   ],
15   [
16     46705789,
17     46705907
18   ],
19   [
20     46709125,
21     46709275
22   ],
23   [
24     46709578,
25     46710923
26   ]
27 ],
28 "strand": 1
29 }
30 }
31
32
33 }

```

v3: <http://mygene.info/v3/gene/1698?fields=exons>

```

1 {
2   "_id": "259236",
3   "_score": 21.732534,
4   "exons": [
5     {
6       "cdsend": 46709688,
7       "cdsstart": 46701487,
8       "chr": "3",
9       "position": [
10        [
11          46701332,
12          46701580
13        ],
14        [
15          46705789,
16          46705907
17        ],
18        [
19          46709125,
20          46709275
21        ],
22        [
23          46709578,
24          46710923
25        ]
26      ],
27      "strand": 1,
28      "transcript": "NM_147196",
29      "txend": 46710923,
30      "txstart": 46701332
31    }
32  ]
33 }

```

## “dotfield” notation default changed

**Warning:** May be backward-incompatible, default data structure changed (but can be restored with “dotfield” paramater setting)

By default, “dotfield” notation is now disabled for gene annotation endpoint in v3 (/gene). It’s enabled by default in v2. You will need to explicitly pass “dotfield=1” to your queries to have the same behavior as v2.

**Note:** “dotfield” notation is disabled by default for gene query endpoint (/gene) in both v2 and v2

**v2:** <http://mygene.info/v2/gene/1017?fields=refseq.rna>

```

1 {
2
3   "_id": "1017",
4   "refseq.rna": [
5     "NM_001290230",
6     "NM_001798",
7     "NM_052827",
8     "XM_011537732"
9   ]
10
11
12 }
```

**v3:** <http://mygene.info/v3/gene/1017?fields=refseq.rna>

```

1 {
2   "_id": "1017",
3   "_score": 21.731894,
4   "refseq": {
5     "rna": [
6       "NM_001290230.1",
7       "NM_001798.4",
8       "NM_052827.3",
9       "XM_011537732.1"
10    ]
11  }
12 }
```

## Querying “reporter” data source

“reporter” data now has to be queried explicitly, prefixing the query term by “reporter:”

**v3:** <http://mygene.info/v3/query?q=reporter:2845421&fields=reporter>

## 4.2 Gene annotation data

### 4.2.1 Data sources

We currently obtain the gene annotation data from several public data resources and keep them up-to-date, so that you don’t have to do it:

Source	Update frequency	Notes
NCBI Entrez	weekly snapshot	
Ensembl	whenever a new release is available	Ensembl Pre! and EnsemblGenomes are not included at the moment
Uniprot	whenever a new release is available	
NetAffy	whenever a new release is available	
PharmGKB	whenever a new release is available	
UCSC	whenever a new release is available	For “exons” field
CPDB	whenever a new release is available	For “pathway” field

The most updated data information can be accessed [here](#).

## 4.2.2 Gene object

Gene annotation data are both stored and returned as a gene object, which is essentially a collection of fields (attributes) and their values:

```
{
  "_id": "1017"
  "taxid": 9606,
  "symbol": "CDK2",
  "entrezgene": 1017,
  "name": "cyclin-dependent kinase 2",
  "genomic_pos": {
    "start": 56360553,
    "chr": "12",
    "end": 56366568,
    "strand": 1
  }
}
```

The example above omits most of available fields. For a full example, you can just check out a few gene examples: [CDK2](#), [ADA](#). Or, did you try our [interactive API page](#) yet?

## 4.2.3 Species

We support **ALL** species annotated by NCBI and Ensembl. All of our services allow you to pass a “**species**” parameter to limit the query results. “species” parameter accepts taxonomy ids as the input. You can look for the taxonomy ids for your favorite species from [NCBI Taxonomy](#).

For convenience, we allow you to pass these *common names* for commonly used species (e.g. “species=human,mouse,rat”):



Common name	Genus name	Taxonomy id
human	Homo sapiens	9606
mouse	Mus musculus	10090
rat	Rattus norvegicus	10116
fruitfly	Drosophila melanogaster	7227
nematode	Caenorhabditis elegans	6239
zebrafish	Danio rerio	7955
thale-cress	Arabidopsis thaliana	3702
frog	Xenopus tropicalis	8364
pig	Sus scrofa	9823

If needed, you can pass “species=all” to query against all available species, although, we recommend you to pass specific species you need for faster response.

#### 4.2.4 Genome assemblies

Our gene query service supports genome interval queries. We import genomic location data from Ensembl, so all species available there are supported. You can find the their reference genome assemblies information [here](#).

This table lists the genome assemblies for commonly-used species:

Common name	Genus name	Genome assembly
human	Homo sapiens	GRCh38 (hg38), also support hg19
mouse	Mus musculus	GRCm38 (mm10), also support mm9
rat	Rattus norvegicus	Rnor_5.0 (rn4)
fruitfly	Drosophila melanogaster	BDGP5 (dm3)
nematode	Caenorhabditis elegans	WBcel235 (ce10)
zebrafish	Danio rerio	Zv9 (danRer6)
frog	Xenopus tropicalis	JGI_4.2 (xenTro2)
pig	Sus scrofa	Sscrofa10.2 (susScr2)

#### 4.2.5 Available fields

The table below lists of all of the possible fields that could be in a gene object.

### 4.3 Gene query service

This page describes the reference for MyGene.info gene query web service. It’s also recommended to try it live on our [interactive API page](#).

#### 4.3.1 Service endpoint

```
http://mygene.info/v3/query
```

## 4.3.2 GET request

### Query parameters

#### q

Required, passing user query. The detailed query syntax for parameter “q” we explained *below*.

#### fields

Optional, can be a comma-separated fields to limit the fields returned from the matching gene hits. The supported field names can be found from any gene object (e.g. [gene 1017](#)). Note that it supports dot notation as well, e.g., you can pass “refseq.rna”. If “fields=all”, all available fields will be returned. Default: “symbol,name,taxid,entrezgene”.

#### species

Optional, can be used to limit the gene hits from given species. You can use “common names” for nine common species (human, mouse, rat, fruitfly, nematode, zebrafish, thale-cress, frog and pig). All other species, you can provide their taxonomy ids. See more details here. Multiple species can be passed using comma as a separator. Passing “all” will query against all available species. Default: human,mouse,rat.

#### size

Optional, the maximum number of matching gene hits to return (with a cap of 1000 at the moment). Default: 10.

#### from

Optional, the number of matching gene hits to skip, starting from 0. Default: 0

---

**Hint:** The combination of “size” and “from” parameters can be used to get paging for large query:

---

q=cdk*&size=50	first 50 hits
q=cdk*&size=50&from=50	the next 50 hits

#### sort

Optional, the comma-separated fields to sort on. Prefix with “-” for descending order, otherwise in ascending order. Default: sort by matching scores in descending order.

#### facets

Optional, a single field or comma-separated fields to return facets, for example, “facets=taxid”, “facets=taxid,type\_of\_gene”. See *examples of faceted queries here*.

### species\_facet\_filter

Optional, relevant when faceting on species (i.e., “facets=taxid” are passed). It’s used to pass species filter without changing the scope of faceting, so that the returned facet counts won’t change. Either species name or taxonomy id can be used, just like “*species*” parameter above. See *examples of faceted queries here*.

### entrezonly

Optional, when passed as “true” or “1”, the query returns only the hits with valid Entrez gene ids. Default: false.

### ensemblonly

Optional, when passed as “true” or “1”, the query returns only the hits with valid Ensembl gene ids. Default: false.

### callback

Optional, you can pass a “**callback**” parameter to make a [JSONP](#) call.

### dotfield

Optional, can be used to control the format of the returned fields when passed “fields” parameter contains dot notation, e.g. “fields=refseq.rna”. If “dotfield” is true, the returned data object contains a single “refseq.rna” field, otherwise, a single “refseq” field with a sub-field of “rna”. Default: false.

### filter

Alias for “fields” parameter.

### limit

Alias for “size” parameter.

### skip

Alias for “from” parameter.

### email

Optional, if you are regular users of our services, we encourage you to provide us an email, so that we can better track the usage or follow up with you.

## Query syntax

Examples of query parameter “q”:

### Simple queries

search for everything:

q=cdk2	search for any fields
q=tumor suppressor	default as "AND" for all query terms
q="cyclin-dependent kinase"	search for the phrase

### Fielded queries

q=entrezgene:1017
q=symbol:cdk2
q=refseq:NM_001798

Field	Description	Examples
<b>entrezgene</b>	Entrez gene id	q=entrezgene:1017
<b>ensemblgene</b>	Ensembl gene id	q=ensemblgene:ENSG00000123374
<b>symbol</b>	official gene symbol	q=symbol:cdk2
<b>name</b>	gene name	q=name:cyclin-dependent
<b>alias</b>	gene alias	q=alias:p33
<b>summary</b>	gene summary text	q=summary:insulin
<b>refseq</b>	NCBI RefSeq id (both rna and proteins)	q=refseq:NM_001798 q=refseq:NP_439892
<b>unigene</b>	NCBI UniGene id	q=unigene:Hs.19192
<b>homologene</b>	NCBI HomoloGene id	q=homologene:74409
<b>accession</b>	NCBI GeneBank Accession number	q=accession:AA810989
<b>ensembltranscript</b>	Ensembl transcript id	q=ensembltranscript:ENST00000266970
<b>ensemblprotein</b>	Ensembl protein id	q=ensemblprotein:ENSP00000243067
<b>uniprot</b>	UniProt id	q=uniprot:P24941
<b>ipi</b> (deprecated!)	IPI id	q=ipi:IPI00031681
<b>pdb</b>	PDB id	q=pdb:1AQ1
<b>prosite</b>	Prosite id	q=prosite:PS50011
<b>pfam</b>	PFam id	q=pfam:PF00069
<b>interpro</b>	InterPro id	q=interpro:IPR008351
<b>mim</b>	OMIM id	q=mim:116953
<b>pharmgkb</b>	PharmGKB id	q=pharmgkb:PA101
<b>reporter</b>	Affymetrix probeset id	q=reporter:204252_at
<b>reagent</b>	GNF reagent id	q=reagent:GNF282834
<b>go</b>	Gene Ontology id	q=go:0000307
<b>hgnc</b>	HUGO Gene Nomenclature Committee	q=hgnc:1771
<b>hprd</b>	Human Protein Reference Database	q=hprd:00310
<b>mgc</b>	Mouse Genome Informatics	q=mgc:MGIV:88339
<b>rgd</b>	Rat Genome Database	q=rgd:620620

Continued on next page

Table 4.1 – continued from previous page

Field	Description	Examples
<b>flybase</b>	A Database of Drosophila Genes & Genomes	<code>q=flybase:FBgn0004107&amp;species=fruitfly</code>
<b>wormbase</b>	C elegans and related nematodes database	<code>q=wormbase:WBGene00057218&amp;species=31234</code>
<b>zfin</b>	Zebrafish Information Network	<code>q=zfin:ZDB-GENE-980526-104&amp;species=zebrafish</code>
<b>tair</b>	Arabidopsis Information Resource	<code>q=tair:AT3G48750&amp;species=thale-cress</code>
<b>xenbase</b>	Xenopus laevis and Xenopus tropicalis biology and genomics resource	<code>q=xenbase:XB-GENE-1001990&amp;species=frog</code>
<b>mirbase</b>	database of published miRNA sequences and annotation	<code>q=mirbase:MI0017267</code>
<b>retired</b>	Retired Entrez gene id, including those with replaced gene ids.	<code>q=retired:84999</code>

### Available fields

#### Genome interval query

When we detect your query (“q” parameter) contains a genome interval pattern like this one:

```
chrX:151,073,054-151,383,976
```

we will do the genome interval query for you. Besides above interval string, you also need to specify “species” parameter (with the default as human). These are all accepted queries:

```
q=chrX:151073054-151383976&species:9606
q=chrX:151,073,054-151,383,976&species:human
```

---

**Hint:** As you can see above, the genomic locations can include commas in it.

---

#### See also:

Genome assembly information

#### Wildcard queries

Wildcard character “\*” or “?” is supported in either simple queries or fielded queries:

<code>q=CDK?</code>	single character wildcard
<code>q=symbol:CDK?</code>	single character wildcard within "symbol" field
<code>q=IL*R</code>	multiple character wildcard

**Note:** Wildcard character can not be the first character. It will be ignored.

---

### Boolean operators and grouping

You can use **AND/OR/NOT** boolean operators and grouping to form complicated queries:

q=tumor AND suppressor	AND operator
q=CDK2 OR BTK	OR operator
q="tumor suppressor" NOT receptor	NOT operator
q=(interleukin OR insulin) AND receptor	the use of parentheses

### Returned object

A GET request like this:

```
http://mygene.info/v3/query?q=symbol:cdk2
```

should return hits as:

```
{
  "hits": [
    {
      "name": "cyclin-dependent kinase 2",
      "_score": 87.76775,
      "symbol": "CDK2",
      "taxid": 9606,
      "entrezgene": 1017,
      "_id": "1017"
    },
    {
      "name": "cyclin-dependent kinase 2",
      "_score": 79.480484,
      "symbol": "Cdk2",
      "taxid": 10090,
      "entrezgene": 12566,
      "_id": "12566"
    },
    {
      "name": "cyclin dependent kinase 2",
      "_score": 62.286797,
      "symbol": "Cdk2",
      "taxid": 10116,
      "entrezgene": 362817,
      "_id": "362817"
    }
  ],
  "total": 3,
  "max_score": 87.76775,
  "took": 4
}
```

## Faceted queries

If you need to perform a faceted query, you can pass an optional “*facets*” parameter. For example, if you want to get the facets on species, you can pass “*facets=taxid*”:

A GET request like this:

```
http://mygene.info/v3/query?q=cdk2&size=1&facets=taxid
```

should return hits as:

```
{
  "hits": [
    {
      "entrezgene": 1017,
      "name": "cyclin-dependent kinase 2",
      "_score": 400.43347,
      "symbol": "CDK2",
      "_id": "1017",
      "taxid": 9606
    }
  ],
  "total": 26,
  "max_score": 400.43347,
  "took": 7,
  "facets": {
    "taxid": {
      "_type": "terms",
      "total": 26,
      "terms": [
        {
          "count": 14,
          "term": 9606
        },
        {
          "count": 7,
          "term": 10116
        },
        {
          "count": 5,
          "term": 10090
        }
      ]
    },
    "other": 0,
    "missing": 0
  }
}
```

Another useful field to get facets on is “*type\_of\_gene*”:

```
http://mygene.info/v3/query?q=cdk2&size=1&facets=type_of_gene
```

It should return hits as:

```
{
  "hits": [
    {
      "entrezgene": 1017,
      "name": "cyclin-dependent kinase 2",
```

```

    "_score":400.43347,
    "symbol":"CDK2",
    "_id":"1017",
    "taxid":9606
  }
],
"total":26,
"max_score":400.43347,
"took":97,
"facets":{
  "type_of_gene":{
    "_type":"terms",
    "total":26,
    "terms":[
      {
        "count":20,
        "term":"protein-coding"
      },
      {
        "count":6,
        "term":"pseudo"
      }
    ]
  },
  "other":0,
  "missing":0
}
}

```

If you need to, you can also pass multiple fields as comma-separated list:

```
http://mygene.info/v3/query?q=cdk2&size=1&facets=taxid,type_of_gene
```

Particularly relevant to species facets (i.e., “facets=taxid”), you can pass a “*species\_facet\_filter*” parameter to filter the returned hits on a given species, without changing the scope of the facets (i.e. facet counts will not change). This is useful when you need to get the subset of the hits for a given species after the initial faceted query on species.

You can see the different “hits” are returned in the following queries, while “facets” keeps the same:

```
http://mygene.info/v3/query?q=cdk?&size=1&facets=taxid&species_facet_filter=human
```

v.s.

```
http://mygene.info/v3/query?q=cdk?&size=1&facets=taxid&species_facet_filter=mouse
```

### 4.3.3 Batch queries via POST

Although making simple GET requests above to our gene query service is sufficient in most of use cases, there are some cases you might find it’s more efficient to make queries in a batch (e.g., retrieving gene annotation for multiple genes). Fortunately, you can also make batch queries via POST requests when you need:

```

URL: http://mygene.info/v3/query
HTTP method: POST

```



## Query parameters

### q

Required, multiple query terms separated by comma (also support “+” or white space), but no wildcard, e.g., ‘q=1017,1018’ or ‘q=CDK2+BTK’

### scopes

Optional, specify one or more fields (separated by comma) as the search “scopes”, e.g., “scopes=entrezgene”, “scopes=entrezgene,ensemblgene”. The available “fields” can be passed to “scopes” parameter are *listed above*. Default: “scopes=entrezgene,ensemblgene,retired” (either Entrez or Ensembl gene ids).

### species

Optional, can be used to limit the gene hits from given species. You can use “common names” for nine common species (human, mouse, rat, fruitfly, nematode, zebrafish, thale-cress, frog and pig). All other species, you can provide their taxonomy ids. See more details here. Multiple species can be passed using comma as a separator. Default: human,mouse,rat.

### fields

Optional, can be a comma-separated fields to limit the fields returned from the matching gene hits. The supported field names can be found from any gene object (e.g. [gene 1017](#)). Note that it supports dot notation as well, e.g., you can pass “refseq.rna”. If “fields=all”, all available fields will be returned. Default: “symbol,name,taxid,entrezgene”.

### dotfield

Optional, can be used to control the format of the returned fields when passed “fields” parameter contains dot notation, e.g. “fields=refseq.rna”. If “dotfield” is true, the returned data object contains a single “refseq.rna” field, otherwise, a single “refseq” field with a sub-field of “rna”. Default: false.

### email

Optional, if you are regular users of our services, we encourage you to provide us an email, so that we can better track the usage or follow up with you.

## Example code

Unlike GET requests, you can easily test them from browser, make a POST request is often done via a piece of code. Here is a sample python snippet:

```
import requests
headers = {'content-type': 'application/x-www-form-urlencoded'}
params = 'q=1017,1018&scopes=entrezgene&fields=name,symbol,taxid,entrezgene'
res = requests.post('http://mygene.info/v3/query', data=params, headers=headers)
```

## Returned object

Returned result (the value of “res.text” variable above) from above example code should look like this:

```
[
  {
    '_id': '1017',
    '_score': 22.757837,
    'entrezgene': 1017,
    'name': 'cyclin dependent kinase 2',
    'query': '1017',
    'symbol': 'CDK2',
    'taxid': 9606
  },
  {
    '_id': '1018',
    '_score': 22.757782,
    'entrezgene': 1018,
    'name': 'cyclin dependent kinase 3',
    'query': '1018',
    'symbol': 'CDK3',
    'taxid': 9606
  }
]
```

---

**Tip:** “query” field in returned object indicates the matching query term.

---

---

**Note:** if no “fields” parameter is specified, all available fields will be returned

---

If a query term has no match, it will return with “**notfound**” field as “**true**”:

```
params = 'q=1017,dummy&scopes=entrezgene&fields=name,symbol,taxid,entrezgene'
res = requests.post('http://mygene.info/v3/query', data=params, headers=headers)
```

```
[
  {
    "name": "cyclin-dependent kinase 2",
    "symbol": "CDK2",
    "taxid": 9606,
    "entrezgene": 1017,
    "query": "1017",
    "_id": "1017"
  },
  {
    "query": "dummy",
    "notfound": true
  }
]
```

If a query term has multiple matches, they will be included with the same “query” field:

```
params = 'q=tp53,1017&scopes=symbol,entrezgene&fields=name,symbol,taxid,entrezgene'
res = requests.post('http://mygene.info/v3/query', data=params, headers=headers)
```

```
[
  {
    "name": "tumor protein p53",
    "symbol": "TP53",
    "taxid": 9606,
    "entrezgene": 7157,
    "query": "tp53",
    "_id": "7157"
  },
  {
    "name": "tumor protein p53",
    "symbol": "Tp53",
    "taxid": 10116,
    "entrezgene": 24842,
    "query": "tp53",
    "_id": "24842"
  },
  {
    "name": "cyclin-dependent kinase 2",
    "symbol": "CDK2",
    "taxid": 9606,
    "entrezgene": 1017,
    "query": "1017",
    "_id": "1017"
  }
]
```

## 4.4 Gene annotation service

This page describes the reference for MyGene.info gene annotation web service. It's also recommended to try it live on our [interactive API page](#).

### 4.4.1 Service endpoint

```
http://mygene.info/v3/gene
```

### 4.4.2 GET request

To obtain the gene annotation via our web service is as simple as calling this URL:

```
http://mygene.info/v3/gene/<geneid>
```

**geneid** above can be either Entrez gene id ("1017") or Ensembl gene id ("ENSG00000123374"). By default, this will return the complete gene annotation object in JSON format. See [here](#) for an example and [here](#) for more details. If the input **geneid** is not valid, 404 (NOT FOUND) will be returned.

---

**Hint:** A retired Entrez gene id works too if it is replaced by a new one, e.g., [245794](#). But a "*discontinued*" gene id will not return any hit, e.g., [138](#).

---

Optionally, you can pass a "**fields**" parameter to return only the annotation you want (by filtering returned object fields):

```
http://mygene.info/v3/gene/1017?fields=name,symbol
```

“**fields**” accepts any attributes (a.k.a fields) available from the gene object. Multiple attributes should be separated by commas. If an attribute is not available for a specific gene object, it will be ignored. Note that the attribute names are case-sensitive.

Just like gene query service, you can also pass a “**callback**” parameter to make a **JSONP** call.

### Query parameters

#### fields

Optional, can be a comma-separated fields to limit the fields returned from the gene object. If “fields=all”, all available fields will be returned. Note that it supports dot notation as well, e.g., you can pass “refseq.rna”. Default: “fields=all”.

#### callback

Optional, you can pass a “**callback**” parameter to make a **JSONP** *<http://ajaxian.com/archives/jsonp-with-padding>* call.

#### filter

Alias for “fields” parameter.

#### dotfield

Optional, can be used to control the format of the returned fields when passed “fields” parameter contains dot notation, e.g. “fields=refseq.rna”. If “dotfield” is true, the returned data object contains a single “refseq.rna” field, otherwise, a single “refseq” field with a sub-field of “rna”. Default: false.

#### email

Optional, if you are regular users of our services, we encourage you to provide us an email, so that we can better track the usage or follow up with you.

### Returned object

A GET request like this:

```
http://mygene.info/v3/gene/1017
```

should return a gene object below:

```
{
  "HGNC": "1771",
  "HPRD": "00310",
  "MIM": "116953",
  "Vega": "OTTHUMG00000170575",
  "_id": "1017",
```

```
"_score": 21.731894,
"accession": {
  "genomic": [
    "AC025162.48",
    "AC034102.32",
    "AF512553.1",
    "AJ223951.1",
    "AMYH02026556.1",
    "AMYH02026557.1",
    "CH471054.1",
    "KT584459.1",
    "NC_000012.12",
    "NC_018923.2",
    "NG_034014.1",
    "U50730.2"
  ],
  "protein": [
    "AAA35667.1",
    "AAH03065.1",
    "AAM34794.1",
    "AAP35467.1",
    "ABM84693.1",
    "ABM92215.1",
    "BAA32794.1",
    "BAF84630.1",
    "BAG56780.1",
    "CAA43807.1",
    "CAA43985.1",
    "CAL38014.1",
    "EAW96856.1",
    "EAW96857.1",
    "EAW96858.1",
    "EAW96859.1",
    "EAW96860.1",
    "NP_001277159.1",
    "NP_001789.2",
    "NP_439892.2",
    "P24941.2",
    "XP_011536034.1"
  ],
  "rna": [
    "AA789250.1",
    "AA810989.1",
    "AB012305.1",
    "AK291941.1",
    "AK293246.1",
    "AM393136.1",
    "BC003065.2",
    "BJ991087.1",
    "BT006821.1",
    "DA814453.1",
    "DQ890598.2",
    "DQ893767.2",
    "M68520.1",
    "NM_001290230.1",
    "NM_001798.4",
    "NM_052827.3",
    "X61622.1",
```

```
"X62071.1",
"XM_011537732.1"
],
"translation": [
  {
    "protein": "BAA32794.1",
    "rna": "AB012305.1"
  },
  {
    "protein": "XP_011536034.1",
    "rna": "XM_011537732.1"
  },
  {
    "protein": "ABM92215.1",
    "rna": "DQ890598.2"
  },
  {
    "protein": "NP_439892.2",
    "rna": "NM_052827.3"
  },
  {
    "protein": "AAA35667.1",
    "rna": "M68520.1"
  },
  {
    "protein": "BAG56780.1",
    "rna": "AK293246.1"
  },
  {
    "protein": "BAF84630.1",
    "rna": "AK291941.1"
  },
  {
    "protein": "AAP35467.1",
    "rna": "BT006821.1"
  },
  {
    "protein": "CAA43807.1",
    "rna": "X61622.1"
  },
  {
    "protein": "CAL38014.1",
    "rna": "AM393136.1"
  },
  {
    "protein": "CAA43985.1",
    "rna": "X62071.1"
  },
  {
    "protein": "AAH03065.1",
    "rna": "BC003065.2"
  },
  {
    "protein": "NP_001789.2",
    "rna": "NM_001798.4"
  },
  {
    "protein": "NP_001277159.1",
```

```

    "rna": "NM_001290230.1"
  },
  {
    "protein": "ABM84693.1",
    "rna": "DQ893767.2"
  }
]
},
"alias": [
  "CDKN2",
  "p33 (CDK2)"
],
"ec": "2.7.11.22",
"ensembl": {
  "gene": "ENSG00000123374",
  "protein": [
    "ENSP00000243067",
    "ENSP00000266970",
    "ENSP00000393605",
    "ENSP00000450983",
    "ENSP00000452138",
    "ENSP00000452514"
  ],
  "transcript": [
    "ENST00000266970",
    "ENST00000354056",
    "ENST00000440311",
    "ENST00000553376",
    "ENST00000554545",
    "ENST00000554619",
    "ENST00000555357",
    "ENST00000555408",
    "ENST00000556146",
    "ENST00000556276",
    "ENST00000556464",
    "ENST00000556656"
  ],
  "translation": [
    {
      "protein": "ENSP00000266970",
      "rna": "ENST00000266970"
    },
    {
      "protein": "ENSP00000450983",
      "rna": "ENST00000555408"
    },
    {
      "protein": "ENSP00000452514",
      "rna": "ENST00000553376"
    },
    {
      "protein": "ENSP00000393605",
      "rna": "ENST00000440311"
    },
    {
      "protein": "ENSP00000452138",
      "rna": "ENST00000555357"
    }
  ],

```

```
{
  "protein": "ENSP00000243067",
  "rna": "ENST00000354056"
}
],
"entrezgene": 1017,
"exons": [
  {
    "cdsend": 55971625,
    "cdsstart": 55967008,
    "chr": "12",
    "position": [
      [
        55966768,
        55967124
      ],
      [
        55968048,
        55968169
      ],
      [
        55968777,
        55968948
      ],
      [
        55971043,
        55971247
      ],
      [
        55971520,
        55972789
      ]
    ],
    "strand": 1,
    "transcript": "NM_001290230",
    "txend": 55972789,
    "txstart": 55966768
  },
  {
    "cdsend": 55971625,
    "cdsstart": 55967008,
    "chr": "12",
    "position": [
      [
        55966768,
        55967124
      ],
      [
        55967856,
        55967934
      ],
      [
        55968048,
        55968169
      ],
      [
        55968777,
```



```

    55968948
  ],
  [
    55969474,
    55969576
  ],
  [
    55971043,
    55971247
  ],
  [
    55971520,
    55972789
  ]
],
"strand": 1,
"transcript": "NM_001798",
"txend": 55972789,
"txstart": 55966768
},
{
  "cdsend": 55971625,
  "cdsstart": 55967008,
  "chr": "12",
  "position": [
    [
      55966768,
      55967124
    ],
    [
      55967856,
      55967934
    ],
    [
      55968048,
      55968169
    ],
    [
      55968777,
      55968948
    ],
    [
      55971043,
      55971247
    ],
    [
      55971520,
      55972789
    ]
  ],
  "strand": 1,
  "transcript": "NM_052827",
  "txend": 55972789,
  "txstart": 55966768
}
],
"exons_hg19": [
  {

```

```
"cdsend": 56365409,
"cdsstart": 56360792,
"chr": "12",
"position": [
  [
    56360552,
    56360908
  ],
  [
    56361832,
    56361953
  ],
  [
    56362561,
    56362732
  ],
  [
    56364827,
    56365031
  ],
  [
    56365304,
    56366573
  ]
],
"strand": 1,
"transcript": "NM_001290230",
"txend": 56366573,
"txstart": 56360552
},
{
  "cdsend": 56365409,
  "cdsstart": 56360792,
  "chr": "12",
  "position": [
    [
      56360552,
      56360908
    ],
    [
      56361640,
      56361718
    ],
    [
      56361832,
      56361953
    ],
    [
      56362561,
      56362732
    ],
    [
      56363258,
      56363360
    ],
    [
      56364827,
      56365031
    ]
  ]
}
```

```

    ],
    [
      56365304,
      56366573
    ]
  ],
  "strand": 1,
  "transcript": "NM_001798",
  "txend": 56366573,
  "txstart": 56360552
},
{
  "cdsend": 56365409,
  "cdsstart": 56360792,
  "chr": "12",
  "position": [
    [
      56360552,
      56360908
    ],
    [
      56361640,
      56361718
    ],
    [
      56361832,
      56361953
    ],
    [
      56362561,
      56362732
    ],
    [
      56364827,
      56365031
    ],
    [
      56365304,
      56366573
    ]
  ],
  "strand": 1,
  "transcript": "NM_052827",
  "txend": 56366573,
  "txstart": 56360552
}
],
"generif": [
  {
    "pubmed": 11907280,
    "text": "Cyclin A/Cdk2 and cyclin E/cdk2 continuously shuttle between the nucleus and the cytoplasm"
  },
  {
    "pubmed": 12049628,
    "text": "results argue that TTK-associated CDK2 may function to maintain target-specific phosphorylation"
  },
  {
    "pubmed": 12081504,

```

```

    "text": "Activation mechanism role of cyclin binding versus phosphorylation"
  },
  {
    "pubmed": 12114499,
    "text": "CDK2/cyclin E is required for Tat-dependent transcription in vitro."
  },
  {
    "pubmed": 12149264,
    "text": "CDK2 binding to cyclin E is required to drive cells from G(1) into S phase"
  },
  {
    "pubmed": 12531694,
    "text": "Interferon gamma reduces the activity of Cdk4 and Cdk2, inhibiting he G1 cell cycle in"
  },
  {
    "pubmed": 12676582,
    "text": "CDK2 is not required for sustained cell division."
  },
  {
    "pubmed": 12729791,
    "text": "Data suggest that the interaction between PKCeta and cyclin E is carefully regulated,"
  },
  {
    "pubmed": 12732645,
    "text": "IRF1 represses CDK2 gene expression by interfering with SP1-dependent transcriptional"
  },
  {
    "pubmed": 12801928,
    "text": "role in regulating Cdc25A half life"
  },
  {
    "pubmed": 12810668,
    "text": "TGF-beta 1 inhibition requires early G(1) induction and stabilization of p21 protein,"
  },
  {
    "pubmed": 12857729,
    "text": "Cdk2 has a role in phosphorylation of the NF-Y transcription factor"
  },
  {
    "pubmed": 12912980,
    "text": "CDK2 has a role in the G2 DNA damage checkpoint"
  },
  {
    "pubmed": 12915577,
    "text": "Kaposi's sarcoma-associated herpesvirus K-bZIP physically associates with cyclin-CDK2"
  },
  {
    "pubmed": 12947099,
    "text": "it is evident that B-Myb protein may promote cell proliferation by a non-transcription"
  },
  {
    "pubmed": 12954644,
    "text": "Inhibition of Cdk2 by 1,25-(OH)2D3 may thus involve two mechanisms: 1) reduced nuclear"
  },
  {
    "pubmed": 14506259,
    "text": "kinetic insight into the basis for selecting suboptimal specificity determinants for t"
  },
  },

```

```

{
  "pubmed": 14536078,
  "text": "multisite phosphorylation by Cdk2 and GSK3 controls cyclin E degradation"
},
{
  "pubmed": 14550307,
  "text": "CDK2 binds to SU9516 at Leu83 and Glu81"
},
{
  "pubmed": 14551212,
  "text": "CDK2 activation process through phosphorylation is examined using 2D PAGE"
},
{
  "pubmed": 14562046,
  "text": "Epstein-Barr virus can inhibit genotoxin-induced G1 arrest downstream of p53 by preven
},
{
  "pubmed": 14612403,
  "text": "p220 is an essential downstream component of the cyclin E/Cdk2 signaling pathway and
},
{
  "pubmed": 14645251,
  "text": "CDK2-cyclin E, without prior CDK4-cyclin D activity, can phosphorylate and inactivate
},
{
  "pubmed": 14646596,
  "text": "significant difference in their biochemical properties between CDK4/cyclin D1 and CDK2
},
{
  "pubmed": 14694185,
  "text": "cyclin-dependent kinase (CDK)2, -4, and -6 were down-regulated from the myelocytes/met
},
{
  "pubmed": 14701826,
  "text": "CDK2 complexes have roles in G(1)/S deregulation and tumor progression"
},
{
  "pubmed": 14985333,
  "text": "CDK2 regulates beta-catenin phosphorylation/ degradation"
},
{
  "pubmed": 15004027,
  "text": "Cdk2 and Cdk4 phosphorylate human Cdt1 and induce its degradation"
},
{
  "pubmed": 15024385,
  "text": "Binding to Cdk2-cyclin A is accompanied by p27 folding, and kinetic data suggest a se
},
{
  "pubmed": 15063782,
  "text": "We also found that cyclin A/CDK2 phosphorylates Axin, thereby enhancing its associati
},
{
  "pubmed": 15159402,
  "text": "study provides evidence that the cyclin A1-cyclin dependent kinase 2 complex plays a
},
{
  "pubmed": 15178429,

```

```

"text": "interacts with dephosphorylated NIRF"
},
{
  "pubmed": 15199159,
  "text": "cyclin A-cdk2 plays an ancillary noncatalytic role in the ubiquitination of p27 (KIP1)
},
{
  "pubmed": 15226429,
  "text": "Results identify an important role for CDK2 in the maintenance of genomic stability, a
},
{
  "pubmed": 15309028,
  "text": "after CDK4/6 inactivation, the fate of pancreatic tumor cells depends on the ability t
},
{
  "pubmed": 15355984,
  "text": "Data suggest that cyclin D1-Cdk2 complexes mediate some of the transforming effects of
},
{
  "pubmed": 15456866,
  "text": "These findings establish a novel function for cyclin A1 and CDK2 in DNA double strand
},
{
  "pubmed": 15572662,
  "text": "Phosphorylation of progesterone receptor serine 400 mediates ligand-independent trans
},
{
  "pubmed": 15601848,
  "text": "cyclin A/Cdk2 has a role as a progesterone receptor coactivator"
},
{
  "pubmed": 15607961,
  "text": "CDK2 depletion suppressed growth and cell cycle progression in melanoma and may be a s
},
{
  "pubmed": 15611077,
  "text": "Inhibition of CDK2 kinase by indole-3-carbinol is accompanied by selective alterations
},
{
  "pubmed": 15632290,
  "text": "molecular dynamics study on the complex CDK2 with the peptide substrate HHASPRK"
},
{
  "pubmed": 15649889,
  "text": "Results demonstrate that a peptide derived from the alpha5 helix of cyclin A signific
},
{
  "pubmed": 15660127,
  "text": "crystal structure of phospho-CDK2 in complex with a truncated cyclin E1 (residues 81-3
},
{
  "pubmed": 15665273,
  "text": "CDK2-BRCA1-Nucleophosmin pathway coordinately functions in cell growth and tumor progr
},
{
  "pubmed": 15671017,
  "text": "HTm4 binding to KAP.Cdk2.cyclin A complex enhances the phosphatase activity of KAP, d
},

```

```

{
  "pubmed": 15695825,
  "text": "Results present a comprehensive description of the dynamic behavior of cyclin-dependent
},
{
  "pubmed": 15707957,
  "text": "Puralpha has been shown to colocalize with cyclin A/Cdk2 and to coimmunoprecipitate w
},
{
  "pubmed": 15890360,
  "text": "Rapid binding of p27 domain 1 to cyclin A tethers the inhibitor to the binary Cdk2/cy
},
{
  "pubmed": 15922732,
  "text": "CDK2 translational down-regulation may be a key regulatory event in replicative senesc
},
{
  "pubmed": 15944161,
  "text": "Origin recognition complex 2 has an unexpected role in CDK2 activation, a linkage that
},
{
  "pubmed": 15964852,
  "text": "Cdk2 destabilizes p21 via the cy2 cyclin-binding motif and p21 phosphorylation"
},
{
  "pubmed": 16036217,
  "text": "Our results demonstrate that differential regulation of Cdc2 and Cdk2 activity by dif
},
{
  "pubmed": 16082200,
  "text": "CINP is part of the Cdc7-dependent mechanism of origin firing and a functional and phy
},
{
  "pubmed": 16082227,
  "text": "CDK2 inhibition modifies the dynamics of chromatin-bound minichromosome maintenance co
},
{
  "pubmed": 16085226,
  "text": "results indicate that CDK2 participates in Tat-mediated HIV-1 transcription and may se
},
{
  "pubmed": 16150942,
  "text": "Cdk2 inhibition decreases the efficiency of chemical induction of KSHV lytic transcrip
},
{
  "pubmed": 16258277,
  "text": "A new concept indicates in this review that both Cdk2 and/or Cdc2 can drive cells thro
},
{
  "pubmed": 16262700,
  "text": "Cdk2 dependent phosphorylation(s) cannot be a critical trigger of replicon initiation
},
{
  "pubmed": 16343435,
  "text": "We propose that during TNFalpha-induced apoptosis, PKCdelta-mediated phosphorylation o
},
{
  "pubmed": 16407256,

```

```

    "text": "molecular analysis of the CDK5/p25 and CDK2/cyclin A systems"
  },
  {
    "pubmed": 16504183,
    "text": "Cyclin-dependent kinases regulate the transcriptional activity of FOXM1; a combinati
  },
  {
    "pubmed": 16540140,
    "text": "Here, we show that human papillomavirus type 16 16E1--E4 is also able to associate wit
  },
  {
    "pubmed": 16575928,
    "text": "The interaction between roscovitine and cyclin-dependent kinase 2 (cdk2) was investig
  },
  {
    "pubmed": 16707497,
    "text": "the phospho-CDK2/cyclin A recruitment site has a role in substrate recognition"
  },
  {
    "pubmed": 16762841,
    "text": "Phosphorylation of the linker histone H1 by CDK regulates its binding to HP1alpha"
  },
  {
    "pubmed": 16765349,
    "text": "suggest a novel retinoic acid (RA)-signaling, by which RA-induced p21 induction and co
  },
  {
    "pubmed": 16824683,
    "text": "Membrane depolarization may stimulate cellular proliferation by augmenting the express
  },
  {
    "pubmed": 16912045,
    "text": "the Chk1-mediated S-phase checkpoint targets initiation factor Cdc45 via a Cdc25A/Cdk2
  },
  {
    "pubmed": 16912201,
    "text": "Breast cancer cells lacking cancer predisposition genes BRCA1 are more sensitive to CD
  },
  {
    "pubmed": 17001081,
    "text": "analysis of the NBI1-binding site on cyclin A which inhibits the catalytic activity of
  },
  {
    "pubmed": 17013093,
    "text": "progression of melanoma is associated with changes in CDK-2 expression level"
  },
  {
    "pubmed": 17038621,
    "text": "functional interaction between CDK2 and FOXO1 provides a mechanism that regulates apop
  },
  {
    "pubmed": 17095507,
    "text": "Kinetic and crystallographic analyses of CDK2-cyclin A complexes reveal that this inh
  },
  {
    "pubmed": 17207508,
    "text": "Review highlights an alternative role for CDK2 in the regulation of progesterone recep
  },

```



```

{
  "pubmed": 17293600,
  "text": "TopBP1 necessary for the G(1)/S transition: one for activating cyclin E/CDK2 kinase and
},
{
  "pubmed": 17361108,
  "text": "Our results demonstrate that CDK2 is capable of autophosphorylation at Thr160."
},
{
  "pubmed": 17371838,
  "text": "results argue that Mdm2 is needed for full inhibition of Cdk2 activity by p21, thereby
},
{
  "pubmed": 17386261,
  "text": "Both Cdk1 and -2 require cyclin binding and T loop phosphorylation for full activity."
},
{
  "pubmed": 17409409,
  "text": "Observational study of gene-disease association. (HuGE Navigator)"
},
{
  "pubmed": 17495531,
  "text": "The structure of phospho-CDK2/cyclin B is reported. pCDK2/cyclin B is less discriminat
},
{
  "pubmed": 17638878,
  "text": "ATRIP is a CDK2 substrate, and CDK2-dependent phosphorylation of S224 regulates the ab
},
{
  "pubmed": 17713927,
  "text": "Phosphorylation on a conserved Thr14 can inhibit activities of both the kinases, but p
},
{
  "pubmed": 18042686,
  "text": "The conserved rigid regions are important for nucleotide binding, catalysis, and subst
},
{
  "pubmed": 18156799,
  "text": "cdk2 activity is necessary for the survival of human DLBCL."
},
{
  "pubmed": 18174243,
  "text": "Observational study of gene-disease association. (HuGE Navigator)"
},
{
  "pubmed": 18199752,
  "text": "major Cdk2-dependent multiple gene regulatory events are present in pemphigus vulgar"
},
{
  "pubmed": 18202766,
  "text": "serum starvation induces G1 arrest through suppression of Skp2-dependent CDK2 activity
},
{
  "pubmed": 18208561,
  "text": "growth arrest by SmE directly correlates with the reduction of cyclin E, CDK2, CDC25C
},
{
  "pubmed": 18236071,

```

```

    "text": "Findings strongly demonstrate that retinoblastoma (RB) and cyclin-dependent kinase 2
  },
  {
    "pubmed": 18276582,
    "text": "Cyclin E and SV40 small T antigen cooperate to bypass quiescence and contribute to tra
  },
  {
    "pubmed": 18281541,
    "text": "Observational study of gene-disease association. (HuGE Navigator)"
  },
  {
    "pubmed": 18345036,
    "text": "Bim-mediated apoptosis following actin damage due to deregulation of Cdk2 and the cell
  },
  {
    "pubmed": 18372919,
    "text": "G2 phase cyclin A/cdk2 controls the timing of entry into mitosis by controlling the su
  },
  {
    "pubmed": 18400748,
    "text": "disruption of the spindle-assembly checkpoint does not directly influence p53 activat
  },
  {
    "pubmed": 18408738,
    "text": "Results suggest that GSK-3 regulates nuclear p27 Kip1 expression through downregulatio
  },
  {
    "pubmed": 18470542,
    "text": "The structures of fully active cyclin-dependent kinase-2 (CDK2) complexed with ATP and
  },
  {
    "pubmed": 18507837,
    "text": "Observational study of gene-disease association. (HuGE Navigator)"
  },
  {
    "pubmed": 18617527,
    "text": "Cdk2-associated complexes, by targeting SHP-1 for proteolysis, counteract the ability
  },
  {
    "pubmed": 18635963,
    "text": "Cyclin A-CDK activity during G(1) would result in an inhibition of progression into th
  },
  {
    "pubmed": 18667424,
    "text": "the cyclin A-CDK2 complex may be a potential effector of NFATs, specifically NFATc1,
  },
  {
    "pubmed": 18784074,
    "text": "Cdk2 negatively regulates the activity of hPXR, and suggest an important role for Cdk2
  },
  {
    "pubmed": 18806832,
    "text": "This suggests an important role for CDK2 in cell cycle regulation in hESCs that are 1
  },
  {
    "pubmed": 18941885,
    "text": "Observational study of gene-disease association. (HuGE Navigator)"
  },
  },

```

```

{
  "pubmed": 19061641,
  "text": "Cyclin A assembles with Cdk1 only after complex formation with Cdk2 reaches a plateau
},
{
  "pubmed": 19066288,
  "text": "These findings establish phosphorylation events by CDKs 1 and 2 as key regulators of D
},
{
  "pubmed": 19091404,
  "text": "Notch-1 may be mediated through regulating the expression of cell cycle regulatory pro
},
{
  "pubmed": 19101503,
  "text": "These results demonstrate that double phosphorylation of CDK2 peptides increases the s
},
{
  "pubmed": 19103742,
  "text": "the pathway of apoptin-induced apoptosis and show that it essentially depends on abnor
},
{
  "pubmed": 19124506,
  "text": "Observational study of gene-disease association. (HuGE Navigator)"
},
{
  "pubmed": 19166026,
  "text": "Overexpression of CDK2 was strongly correlated with abnormal proliferation in larynge
},
{
  "pubmed": 19197163,
  "text": "Results show that human Cdk2 is a functional homolog for most of Ime2 functions."
},
{
  "pubmed": 19201832,
  "text": "disruption of Smad2 function by CDK2 phosphorylation acts as a mechanism for TGF-beta
},
{
  "pubmed": 19258477,
  "text": "Observational study of gene-disease association. (HuGE Navigator)"
},
{
  "pubmed": 19258477,
  "text": "Strengthened signals in imputation-based analysis at CDK2 SNPs rs2069391, rs2069414 an
},
{
  "pubmed": 19321444,
  "text": "The combination of st and deregulated cyclin E result in cooperative and coordinated a
},
{
  "pubmed": 19440053,
  "text": "Co-depletion of Cdc6 and p53 in normal cells restored Cdk2 activation and Rb phosphory
},
{
  "pubmed": 19594747,
  "text": "Observational study of gene-disease association. (HuGE Navigator)"
},
{
  "pubmed": 19596857,

```

```
"text": "resistance of oral squamous carcinoma to IFNgamma is not due to deficiency in STAT1-de
},
{
  "pubmed": 19609547,
  "text": "Four genes previously not examined in that respect in laryngeal carcinoma, occurred to
},
{
  "pubmed": 19631451,
  "text": "Data demonstrate that the novel anticancer mechanism of hinokitiol involves accumulati
},
{
  "pubmed": 19703905,
  "text": "cyclin A/cdk2-dependent phosphorylation of APC affects astral microtubule attachment t
},
{
  "pubmed": 19706521,
  "text": "Results suggest that simple but robust rules encoded in the CDK2 structure play a dom
},
{
  "pubmed": 19723060,
  "text": "Studies indicate that roscovitine arrests the cell cycle is direct inhibition of CDK1,
},
{
  "pubmed": 19724860,
  "text": "Overexpression of Notch1 in laryngeal carcinoma cell line was coupled with the downreg
},
{
  "pubmed": 19738611,
  "text": "Observational study of gene-disease association. (HuGE Navigator)"
},
{
  "pubmed": 19797611,
  "text": "results show that the expression of UGT1A1 and CYP2B6 is negatively regulated through
},
{
  "pubmed": 19822658,
  "text": "Results underscore the crucial role of cyclin A2-CDK2 in regulating the PLK1-SCF(beta
},
{
  "pubmed": 19829063,
  "text": "Since CAC1 interacts with CDK2 and promotes the kinase activity of CDK2 protein, we pr
},
{
  "pubmed": 19838212,
  "text": "Chk1 signalling causes centrosome amplification after ionizing radiation by upregulat
},
{
  "pubmed": 19838216,
  "text": "Data show that SHP-1 knockdown increases p27stability, decreases the CDK6 levels, indu
},
{
  "pubmed": 19854217,
  "text": "expression upregulation is critical for TLR9-stimulated proliferation of lung cancer c
},
{
  "pubmed": 19858290,
  "text": "Export was also reduced by Cdk inhibition or cyclin A RNA interference, suggesting tha
```

```

{
  "pubmed": 19885547,
  "text": "aberrant regulation of S100P in HCC might activate cyclin D1 and CDK expression and c
},
{
  "pubmed": 19960406,
  "text": "Cellular production of IGFBP-3 leads to G1 cell cycle arrest with inhibition of CDK2 a
},
{
  "pubmed": 19966300,
  "text": "Data show that Myc repressed Ras-induced senescence, and that Cdk2 interacted with Myc
},
{
  "pubmed": 20017906,
  "text": "FUS-DDIT3 and the normal DDIT3 bind CDK2."
},
{
  "pubmed": 20062077,
  "text": "Results directly show that the inhibition of Cdk1 activity and the persistence of Cdk2
},
{
  "pubmed": 20068231,
  "text": "Results show that most of the up-regulated sites phosphorylated by cyclin-dependent CD
},
{
  "pubmed": 20079829,
  "text": "the nitric oxide-mediated biphasic effect was dependent on Cdk2 nitrosylation/activat
},
{
  "pubmed": 20147522,
  "text": "central roles for CDK2 nuclear-cytoplasmic trafficking and cyclin E in the mechanism o
},
{
  "pubmed": 20195506,
  "text": "These findings demonstrate that Cdk2 maintains a balance of S-phase regulatory protein
},
{
  "pubmed": 20399812,
  "text": "Data describe the properties of a mutant form of Cdk2 identified during large-scale se
},
{
  "pubmed": 20422243,
  "text": "Triticum aestivum-5B2 (( Ta ) 5B2) is suggested to be a wheat analogue of human CDK2 e
},
{
  "pubmed": 20444741,
  "text": "Conclude that cisplatin likely activates both caspase-dependent and -independent cell
},
{
  "pubmed": 20465575,
  "text": "In addition to having a pivotal role in the up-regulation of IL-2 and IL-2RA gene exp
},
{
  "pubmed": 20508983,
  "text": "Observational study of gene-disease association. (HuGE Navigator)"
},
{
  "pubmed": 20512928,

```

```
"text": "Hr and VDR interact via multiple protein-protein interfaces, catalyzing histone demethylase activity",
},
{
  "pubmed": 20694007,
  "text": "protein phosphatase 1 competition with Cdk-cyclins for retinoblastoma protein(Rb) binding",
},
{
  "pubmed": 20711190,
  "text": "cyclin-dependent kinases (Cdks), especially Cdk1 and Cdk2, promote interphase nuclear envelope breakdown",
},
{
  "pubmed": 20844047,
  "text": "Nuclear export of HPV31 E1 is inhibited by Cdk2 phosphorylation at two serines residues",
},
{
  "pubmed": 20935635,
  "text": "The results demonstrate that CDK2-mediated phosphorylation is a key mechanism governing cell cycle progression",
},
{
  "pubmed": 21048031,
  "text": "Observational study of gene-disease association and gene-environment interaction. (Human Genome Epidemiology)",
},
{
  "pubmed": 21062975,
  "text": "Data show that miR-302 simultaneously suppressed both the cyclin E-CDK2 and cyclin D-CDK4 complexes",
},
{
  "pubmed": 21099355,
  "text": "Overexpression of human Cdk2 resulted in a defect in the G1 to S transition and a reduction in cell growth",
},
{
  "pubmed": 21233845,
  "text": "MicroRNA miR-885-5p targets CDK2 and MCM5, activates p53 and inhibits proliferation and cell cycle progression",
},
{
  "pubmed": 21262353,
  "text": "Cdk2 functions via a Cdk2/SHP-1/beta-catenin/CEACAM1 axis, and show that Cdk2 has the ability to phosphorylate CEACAM1",
},
{
  "pubmed": 21264535,
  "text": "XPD may play an important role in cell apoptosis of hepatoma by inducing an over-expression of p21",
},
{
  "pubmed": 21319273,
  "text": "CDK2 downregulation causes high apoptosis at the early time points"
},
{
  "pubmed": 21325496,
  "text": "Conclude that in cisplatin induced-kidney injury phosphorylation of p21 by Cdk2 limits its transcriptional activity",
},
{
  "pubmed": 21454540,
  "text": "the ability of Emil to inhibit APC/C is negatively regulated by CDKs"
},
{
  "pubmed": 21515670,
  "text": "cyclin E and CDK2 genes are key physiological effectors of the c-ETS1 proto-oncogene."
},
},
```

```

{
  "pubmed": 21565702,
  "text": "Transient binding of a second catalytic magnesium activates the structure and dynamics
},
{
  "pubmed": 21596315,
  "text": "The deubiquitinase USP37 binds CDH1 and removes degradative polyubiquitin from cyclin
},
{
  "pubmed": 21646351,
  "text": "anti-oncogenic role of miR-372 may be through control of cell growth and cell cycle pr
},
{
  "pubmed": 21658603,
  "text": "Cdk2 is required for cell proliferation."
},
{
  "pubmed": 21769424,
  "text": "RT-PCR and Western blotting results revealed that both mRNA and protein levels of CDK2
},
{
  "pubmed": 21871181,
  "text": "NF-Y binds to CCAAT sequences in the Cyclin A promoter, as well as to those in the pro
},
{
  "pubmed": 21918011,
  "text": "Epstein-Barr virus Rta-mediated transactivation of p21 and 14-3-3sigma arrests cells a
},
{
  "pubmed": 21941773,
  "text": "The expression level of CDK2 protein did not change significantly in silica-induced hu
},
{
  "pubmed": 21965652,
  "text": "excess of MCM3 up-regulates the phosphorylation of CHK1 Ser-345 and CDK2 Thr-14."
},
{
  "pubmed": 22084169,
  "text": "The S-phase-specific cyclin-dependent kinase 2 was required for robust activation of A
},
{
  "pubmed": 22231403,
  "text": "The authors show that, in human and mouse, Mre11 controls these events through a direc
},
{
  "pubmed": 22467868,
  "text": "Lin-28 homologue A (LIN28A) promotes cell cycle progression via regulation of cyclin-c
},
{
  "pubmed": 22474407,
  "text": "CDK2 inhibition drastically diminishes anchorage-independent growth of human cancer ce
},
{
  "pubmed": 22479189,
  "text": "low molecular weight cyclin E (LMW-E) requires CDK2-associated kinase activity to indu
},
{
  "pubmed": 22673765,

```

```
    "text": "The activation of p21(Waf1/Cip1) was significantly up-regulated over time, but there v
  },
  {
    "pubmed": 22718829,
    "text": "Human cytomegalovirus IE1/2 expression was downregulated by cyclin A2, CDK1 and CDK2."
  },
  {
    "pubmed": 22819841,
    "text": "exposure of cancer cells (such as HeLa and MCF7 cells) to H2O2 increased CDK2 activity
  },
  {
    "pubmed": 22927831,
    "text": "By a chemical-genetic approach study identified Nbs1 as a target of Cdk2, and mapped t
  },
  {
    "pubmed": 22951823,
    "text": "cellular CDK2 phosphorylates the functionally critical S/T-P sites of the hepadnavirus
  },
  {
    "pubmed": 23028682,
    "text": "cyclin A-Cdk2 regulates apoptosis through a mechanism that involves Rad9phosphorylati
  },
  {
    "pubmed": 23065011,
    "text": "human papillomavirus E4 proteins can interact with cyclin A and cdk2, which may contr
  },
  {
    "pubmed": 23082202,
    "text": "Cdk2 also binds the N-terminal domain of Fbw7-gamma as well as SLP-1."
  },
  {
    "pubmed": 23140174,
    "text": "CDK2 phosphorylates CDK9 on Ser 90 and thereby contributes to HIV-1 transcription."
  },
  {
    "pubmed": 23184662,
    "text": "EEF2 phosphorylation by cyclin A-cyclin-dependent kinase 2 (CDK2) on a novel site, ser
  },
  {
    "pubmed": 23185313,
    "text": "This study aimed to explore the effects of single nucleotide polymorphisms in CDK2 and
  },
  {
    "pubmed": 23230143,
    "text": "Findings revealed a novel function of simultaneous p27 and CDK2 cytoplasmic mislocaliz
  },
  {
    "pubmed": 23300027,
    "text": "possible relationship between the CDK2 deleterious variants and the drug-binding abil
  },
  {
    "pubmed": 23321641,
    "text": "Constitutive Cdk2 activity promotes aneuploidy while altering the spindle assembly and
  },
  {
    "pubmed": 23390492,
    "text": "Constitutive CCND1/CDK2 expression contributes to neoplastic mammary epithelial cell t
```



```

{
  "pubmed": 23390529,
  "text": "The prolyl isomerase Pin1 acts synergistically with CDK2 to regulate the basal activiti
},
{
  "pubmed": 23446853,
  "text": "Aurora-A kinase-induced centrosome amplification was mediated by Cdk2 kinase."
},
{
  "pubmed": 23479742,
  "text": "the up-regulation of CDK2 by CUL4B is achieved via the repression of miR-372 and miR-3
},
{
  "pubmed": 23532886,
  "text": "Data indicate that TG02 blocked signaling by CDKs 1, 2, 7, and 9 and ERK5, leading to
},
{
  "pubmed": 23643165,
  "text": "The expression of CDK2 mRNA significantly decreased in P(CDK2-siRNA)."
},
{
  "pubmed": 23671119,
  "text": "A specific and essential roles for Cdk2 inhibitory phosphorylation in the successful e
},
{
  "pubmed": 23720738,
  "text": "MCM7 is a substrate of cyclin E/Cdk2 and can be phosphorylated on Ser-121."
},
{
  "pubmed": 23727278,
  "text": "Data indicate that different binding sites of cyclin-dependent kinase (CDK2) contribut
},
{
  "pubmed": 23737759,
  "text": "CDK7 involved in phosphorylation/activation of CDK4 and CDK6; existence of CDK4-activa
},
{
  "pubmed": 23776131,
  "text": "FBXO28 activity and stability are regulated during the cell cycle by CDK1/2-mediated p
},
{
  "pubmed": 23781148,
  "text": "antitumor effects of DOC-1R may be mediated by negatively regulating G1 phase progress
},
{
  "pubmed": 23787073,
  "text": "This study indicates that genetic polymorphisms of AURKA, BRCA1 and CCNE1 may affect c
},
{
  "pubmed": 24075009,
  "text": "Cells decide at the end of mitosis to either start the next cell cycle by immediately
},
{
  "pubmed": 24204256,
  "text": "PKC activation then triggered activation of cdk-2, which became further activated by c
},
{
  "pubmed": 24216307,

```

```

    "text": "Two nuclear export signals of Cdc6 work cooperatively and distinctly for the cytoplasmic export of
  },
  {
    "pubmed": 24240190,
    "text": "CDK2 knockdown alters the profile of Rb phosphorylation in coronary artery smooth muscle cells
  },
  {
    "pubmed": 24386425,
    "text": "Of the total, the deregulation of several genes (CDK1, CDK2, CDK4, MCM2, MCM3, MCM4, MCM5, MCM6,
  },
  {
    "pubmed": 24444383,
    "text": "MYC-dependent breast cancer cells possess high MYC expression and high level of MYC phosphorylation
  },
  {
    "pubmed": 24520316,
    "text": "CRIF1 may play a regulatory role in the BM microenvironment-induced leukemia cell cycle progression
  },
  {
    "pubmed": 24623419,
    "text": "Authors identified and validated two additional host proteins interacting with human SV40 large T
  },
  {
    "pubmed": 24671051,
    "text": "Expression of Notch1, -2, and -3, CDK2, and CCNE1 was significantly decreased by upregulation of
  },
  {
    "pubmed": 24700371,
    "text": "In the subsequent molecular experiments, western blot analysis and kinase activity detection
  },
  {
    "pubmed": 24820417,
    "text": "Results show that CDK2 phosphorylates Thr-156 in GATA3."
  },
  {
    "pubmed": 24911186,
    "text": "Report structure-based discovery of allosteric inhibitors of CDK2."
  },
  {
    "pubmed": 24922574,
    "text": "CDK2 Supports HIV-1 Reverse Transcription in CD4+ T Cells.HIV-1 reverse transcriptase activity
  },
  {
    "pubmed": 24935000,
    "text": "It is concluded that non-response to everolimus is characterized by increased cdk2/cyclin D1
  },
  {
    "pubmed": 24947816,
    "text": "More effective packing and interactions between CDK2 and LMW cyclin E isoforms, however,
  },
  {
    "pubmed": 25015816,
    "text": "CDK2 was strongly linked to cell cycle progression and coordinated SAMHD1 phosphorylation
  },
  {
    "pubmed": 25071185,
    "text": "Cdk1 activity blocks lysosomal degradation of HIF-1alpha and increases HIF-1alpha protein
  },

```

```

{
  "pubmed": 25136960,
  "text": "A positive correlation between cdk2/cyclin A expression level and tumor growth. Amygdala",
},
{
  "pubmed": 25149358,
  "text": "for both oncogene- and DNA damage-induced cellular senescence, CDK2 transcript and protein",
},
{
  "pubmed": 25154617,
  "text": "Which is mutated at the CDK2 phosphorylation site."
},
{
  "pubmed": 25218592,
  "text": "The Cell Cycle Profiling - Risk Score (C2P-RS) based on CDK1 and CDK2 specific activities",
},
{
  "pubmed": 25218637,
  "text": "Data indicate that tumour suppressor RASSF1A triggers large tumor suppressor kinase 1",
},
{
  "pubmed": 25220500,
  "text": "Cyclin A2 and its associated kinase (CDK2) activity are required for optimal induction of",
},
{
  "pubmed": 25265349,
  "text": "High CDK2 expression is associated with nasopharyngeal carcinoma."
},
{
  "pubmed": 25271736,
  "text": "observations suggested that androgen suppresses the proliferation of CRPC cells partially",
},
{
  "pubmed": 25303791,
  "text": "TPPII, MYBBP1A and CDK2 form a protein-protein interaction network."
},
{
  "pubmed": 25410660,
  "text": "Inhibition of CDK2 phosphorylation blocked phosphorylation of hnRNP K, preventing its",
},
{
  "pubmed": 25443276,
  "text": "At a median follow-up of 36 months (1-109M), tumor with low CDK2SA-CDK1SA ratio showed",
},
{
  "pubmed": 25451924,
  "text": "miR-638 regulates proliferation and myeloid differentiation by targeting CDK2 and may",
},
{
  "pubmed": 25463638,
  "text": "No association of CDK2 polymorphisms with risk of endometrial carcinoma found in Chinese",
},
{
  "pubmed": 25501982,
  "text": "HOXA7 promotes cell proliferation, and these changes are mediated by cyclin E1/CDK2"
},
{
  "pubmed": 25541464,

```

```
"text": "Using the fact that deletion of the yeast CDC28 gene is functionally complemented by h
},
{
  "pubmed": 25728284,
  "text": "CDK2 up-regulates the protein level of KLF10 through reducing its association with SIA
},
{
  "pubmed": 25744732,
  "text": "Diclofenac and curcumin overcome these carcinogenic effects by downregulating telomera
},
{
  "pubmed": 25754137,
  "text": "The docking and molecular dynamics investigation performed here led to the identificat
},
{
  "pubmed": 25808870,
  "text": "CP110 plays a mechanistic role in response of lung cancer cells to CDK2 inhibition, es
},
{
  "pubmed": 25832654,
  "text": "NUAK2 silencing and inactivation of the PI3K pathway efficiently controlled CDK2 expr
},
{
  "pubmed": 25860957,
  "text": "Identified ING5 as a novel CDK2 substrate. ING5 is phosphorylated at a single site, th
},
{
  "pubmed": 25918937,
  "text": "analysis of the conformational characteristics and ligand binding mechanisms of CDK2
},
{
  "pubmed": 26026083,
  "text": "G1 arrest induced by SB265610 occurred at concentrations lacking CXCR2 selectivity and
},
{
  "pubmed": 26124340,
  "text": "We found no significant associations for CDKN2 p16 580 C>T and MDM2 SNP309 T>G variant
},
{
  "pubmed": 26139602,
  "text": "Sox2 phosphorylation by Cdk2 promotes the establishment but not the maintenance of the
},
{
  "pubmed": 26147897,
  "text": "fluspirilene is a potential CDK2 inhibitor and a candidate anti-cancer drug for the tr
},
{
  "pubmed": 26151768,
  "text": "In G28 cells, a dosedependent induction of CDK2, p21 and cyclin D was observed between
},
{
  "pubmed": 26204491,
  "text": "ovary tumors with elevated CCNE1 expression may be staged for Cdk2-targeted therapy"
},
{
  "pubmed": 26297806,
  "text": "Centriolar satellites build a centrosomal microcephaly protein complex critical for hu
},
```

```

{
  "pubmed": 26373553,
  "text": "PIWIL2 has a role in promoting progression of non-small cell lung cancer by inducing C
},
{
  "pubmed": 26555773,
  "text": "both cell lines feature a significant reduction of CDK2 expression verified at the RN
}
],
"genomic_pos": {
  "chr": "12",
  "end": 55972784,
  "start": 55966769,
  "strand": 1
},
"genomic_pos_hg19": {
  "chr": "12",
  "end": 56366568,
  "start": 56360553,
  "strand": 1
},
"go": {
  "BP": [
    {
      "evidence": "TAS",
      "id": "GO:0000082",
      "term": "G1/S transition of mitotic cell cycle"
    },
    {
      "evidence": "NAS",
      "id": "GO:0000086",
      "pubmed": 1653904,
      "term": "G2/M transition of mitotic cell cycle"
    },
    {
      "evidence": "TAS",
      "id": "GO:0000086",
      "term": "G2/M transition of mitotic cell cycle"
    },
    {
      "evidence": "IEA",
      "id": "GO:0002088",
      "term": "lens development in camera-type eye"
    },
    {
      "evidence": "TAS",
      "id": "GO:0006260",
      "pubmed": 19238148,
      "term": "DNA replication"
    },
    {
      "evidence": "IEA",
      "id": "GO:0006281",
      "term": "DNA repair"
    },
    {
      "evidence": "IEA",
      "id": "GO:0006813",

```

```

    "term": "potassium ion transport"
  },
  {
    "evidence": "TAS",
    "id": "GO:0006977",
    "term": "DNA damage response, signal transduction by p53 class mediator resulting in cell cycle arrest"
  },
  {
    "evidence": "IEA",
    "id": "GO:0007067",
    "term": "mitotic nuclear division"
  },
  {
    "evidence": "IMP",
    "id": "GO:0007099",
    "pubmed": 26297806,
    "term": "centriole replication"
  },
  {
    "evidence": "TAS",
    "id": "GO:0007126",
    "pubmed": 19238148,
    "term": "meiotic nuclear division"
  },
  {
    "evidence": "IEP",
    "id": "GO:0007265",
    "pubmed": 9054499,
    "term": "Ras protein signal transduction"
  },
  {
    "evidence": "IDA",
    "id": "GO:0008284",
    "pubmed": 10767298,
    "term": "positive regulation of cell proliferation"
  },
  {
    "evidence": "IEA",
    "id": "GO:0009636",
    "term": "response to toxic substance"
  },
  {
    "evidence": "IEA",
    "id": "GO:0016572",
    "term": "histone phosphorylation"
  },
  {
    "evidence": "IDA",
    "id": "GO:0018105",
    "pubmed": 23184662,
    "term": "peptidyl-serine phosphorylation"
  },
  {
    "evidence": "IEA",
    "id": "GO:0031100",
    "term": "organ regeneration"
  },
  {

```

```

    "evidence": "TAS",
    "id": "GO:0031571",
    "pubmed": 21319273,
    "term": "mitotic G1 DNA damage checkpoint"
  },
  {
    "evidence": "IEA",
    "id": "GO:0032298",
    "term": "positive regulation of DNA-dependent DNA replication initiation"
  },
  {
    "evidence": "IEA",
    "id": "GO:0032355",
    "term": "response to estradiol"
  },
  {
    "evidence": "IEA",
    "id": "GO:0032869",
    "term": "cellular response to insulin stimulus"
  },
  {
    "evidence": "IEA",
    "id": "GO:0042493",
    "term": "response to drug"
  },
  {
    "evidence": "IEA",
    "id": "GO:0045471",
    "term": "response to ethanol"
  },
  {
    "evidence": "IEA",
    "id": "GO:0045893",
    "term": "positive regulation of transcription, DNA-templated"
  },
  {
    "evidence": "IEA",
    "id": "GO:0046686",
    "term": "response to cadmium ion"
  },
  {
    "evidence": "TAS",
    "id": "GO:0051298",
    "pubmed": 19238148,
    "term": "centrosome duplication"
  },
  {
    "evidence": "IEA",
    "id": "GO:0051301",
    "term": "cell division"
  },
  {
    "evidence": "TAS",
    "id": "GO:0051436",
    "term": "negative regulation of ubiquitin-protein ligase activity involved in mitotic cell cy
  },
  {
    "evidence": "TAS",

```

```

    "id": "GO:0051439",
    "term": "regulation of ubiquitin-protein ligase activity involved in mitotic cell cycle"
  },
  {
    "evidence": "IEA",
    "id": "GO:0051591",
    "term": "response to cAMP"
  },
  {
    "evidence": "IEA",
    "id": "GO:0051602",
    "term": "response to electrical stimulus"
  },
  {
    "evidence": "IDA",
    "id": "GO:0060968",
    "pubmed": 20935635,
    "term": "regulation of gene silencing"
  },
  {
    "evidence": "TAS",
    "id": "GO:0071732",
    "pubmed": 20079829,
    "term": "cellular response to nitric oxide"
  },
  {
    "evidence": "TAS",
    "id": "GO:1901796",
    "term": "regulation of signal transduction by p53 class mediator"
  }
],
"CC": [
  {
    "evidence": "IDA",
    "id": "GO:0000307",
    "pubmed": 8692841,
    "term": "cyclin-dependent protein kinase holoenzyme complex"
  },
  {
    "evidence": "IEA",
    "id": "GO:0000781",
    "term": "chromosome, telomeric region"
  },
  {
    "evidence": "IEA",
    "id": "GO:0000793",
    "term": "condensed chromosome"
  },
  {
    "evidence": "IEA",
    "id": "GO:0000805",
    "term": "X chromosome"
  },
  {
    "evidence": "IEA",
    "id": "GO:0000806",
    "term": "Y chromosome"
  }
],

```



```

{
  "evidence": "IDA",
  "id": "GO:0005634",
  "pubmed": 10767298,
  "term": "nucleus"
},
{
  "evidence": "TAS",
  "id": "GO:0005654",
  "term": "nucleoplasm"
},
{
  "evidence": "IEA",
  "id": "GO:0005667",
  "term": "transcription factor complex"
},
{
  "evidence": "IDA",
  "id": "GO:0005737",
  "pubmed": 10767298,
  "term": "cytoplasm"
},
{
  "evidence": "IDA",
  "id": "GO:0005768",
  "pubmed": 21262353,
  "term": "endosome"
},
{
  "evidence": "TAS",
  "id": "GO:0005813",
  "pubmed": 19238148,
  "term": "centrosome"
},
{
  "evidence": "TAS",
  "id": "GO:0005829",
  "term": "cytosol"
},
{
  "evidence": "IDA",
  "id": "GO:0015030",
  "pubmed": 10995387,
  "term": "Cajal body"
}
],
"MF": [
  {
    "evidence": "TAS",
    "id": "GO:0004674",
    "term": "protein serine/threonine kinase activity"
  },
  {
    "evidence": "IDA",
    "id": "GO:0004693",
    "pubmed": 21596315,
    "term": "cyclin-dependent protein serine/threonine kinase activity"
  }
],

```

```
{
  "evidence": "TAS",
  "id": "GO:0004693",
  "term": "cyclin-dependent protein serine/threonine kinase activity"
},
{
  "evidence": "IPI",
  "id": "GO:0005515",
  "pubmed": [
    8242750,
    8521818,
    8684460,
    8756328,
    8756624,
    9840943,
    10330164,
    11463386,
    11980914,
    12244298,
    12361598,
    12839962,
    12941338,
    15107404,
    15178429,
    15189033,
    15232106,
    15239650,
    15611625,
    15890360,
    16209941,
    16326706,
    16458891,
    16765349,
    16962592,
    17053782,
    17254966,
    17254967,
    17418410,
    19150984,
    19829063,
    20098747,
    20871633,
    21092281,
    21596315,
    21952639,
    23082202,
    23455922,
    23602568,
    23853094,
    24218572,
    25241761,
    25416956,
    25852190,
    26496610
  ],
  "term": "protein binding"
},
{
```

```

    "evidence": "IEA",
    "id": "GO:0005524",
    "term": "ATP binding"
  },
  {
    "evidence": "TAS",
    "id": "GO:0016301",
    "term": "kinase activity"
  },
  {
    "evidence": "IDA",
    "id": "GO:0030332",
    "pubmed": 1653904,
    "term": "cyclin binding"
  },
  {
    "evidence": "IEA",
    "id": "GO:0032403",
    "term": "protein complex binding"
  },
  {
    "evidence": "IDA",
    "id": "GO:0035173",
    "pubmed": 8692841,
    "qualifier": "contributes_to",
    "term": "histone kinase activity"
  },
  {
    "evidence": "IEA",
    "id": "GO:0046872",
    "term": "metal ion binding"
  }
]
},
"homologene": {
  "genes": [
    [
      9606,
      1017
    ],
    [
      10090,
      12566
    ],
    [
      10116,
      362817
    ],
    [
      7227,
      42453
    ],
    [
      7955,
      406715
    ],
    [
      3702,

```

```
824036
],
[
  8364,
  493498
],
[
  4530,
  4328135
],
[
  4530,
  4331415
],
[
  4896,
  2539869
],
[
  4932,
  852457
],
[
  5141,
  3876264
],
[
  7165,
  3291042
],
[
  9031,
  100529062
],
[
  9544,
  711002
],
[
  9598,
  467032
],
[
  9615,
  100855704
],
[
  9913,
  519217
],
[
  28985,
  2896999
],
[
  33169,
  4620303
],
],
```

```

    [
      318829,
      2679140
    ]
  ],
  "id": 74409
},
"interpro": [
  {
    "desc": "Protein kinase-like domain",
    "id": "IPR011009",
    "short_desc": "Kinase-like_dom"
  },
  {
    "desc": "Serine/threonine-protein kinase, active site",
    "id": "IPR008271",
    "short_desc": "Ser/Thr_kinase_AS"
  },
  {
    "desc": "Serine/threonine/dual specificity protein kinase, catalytic domain",
    "id": "IPR002290",
    "short_desc": "Ser/Thr_dual-sp_kinase"
  },
  {
    "desc": "Protein kinase domain",
    "id": "IPR000719",
    "short_desc": "Prot_kinase_dom"
  },
  {
    "desc": "Protein kinase, ATP binding site",
    "id": "IPR017441",
    "short_desc": "Protein_kinase_ATP_BS"
  }
],
"ipi": [
  "IPI00031681",
  "IPI00910650"
],
"map_location": "12q13",
"name": "cyclin dependent kinase 2",
"pathway": {
  "biocarta": [
    {
      "id": "cellcyclepathway",
      "name": "cyclins and cell cycle regulation"
    },
    {
      "id": "efppathway",
      "name": "estrogen responsive protein efp controls cell cycle and breast tumors growth"
    },
    {
      "id": "fbw7pathway",
      "name": "cyclin e destruction pathway"
    },
    {
      "id": "g1pathway",
      "name": "cell cycle: g1/s check point"
    }
  ],

```

```
{
  "id": "mcmpathway",
  "name": "cdk regulation of dna replication"
},
{
  "id": "p27pathway",
  "name": "regulation of p27 phosphorylation during cell cycle progression"
},
{
  "id": "p53pathway",
  "name": "p53 signaling pathway"
},
{
  "id": "raccycdpathway",
  "name": "influence of ras and rho proteins on g1 to s transition"
},
{
  "id": "rbpathway",
  "name": "rb tumor suppressor/checkpoint signaling in response to dna damage"
},
{
  "id": "skp2e2fpathway",
  "name": "e2f1 destruction pathway"
}
],
"kegg": [
  {
    "id": "hsa04068",
    "name": "FoxO signaling pathway - Homo sapiens (human)"
  },
  {
    "id": "hsa04110",
    "name": "Cell cycle - Homo sapiens (human)"
  },
  {
    "id": "hsa04114",
    "name": "Oocyte meiosis - Homo sapiens (human)"
  },
  {
    "id": "hsa04115",
    "name": "p53 signaling pathway - Homo sapiens (human)"
  },
  {
    "id": "hsa04151",
    "name": "PI3K-Akt signaling pathway - Homo sapiens (human)"
  },
  {
    "id": "hsa04914",
    "name": "Progesterone-mediated oocyte maturation - Homo sapiens (human)"
  },
  {
    "id": "hsa05161",
    "name": "Hepatitis B - Homo sapiens (human)"
  },
  {
    "id": "hsa05162",
    "name": "Measles - Homo sapiens (human)"
  }
],
```

```

{
  "id": "hsa05168",
  "name": "Herpes simplex infection - Homo sapiens (human)"
},
{
  "id": "hsa05169",
  "name": "Epstein-Barr virus infection - Homo sapiens (human)"
},
{
  "id": "hsa05200",
  "name": "Pathways in cancer - Homo sapiens (human)"
},
{
  "id": "hsa05203",
  "name": "Viral carcinogenesis - Homo sapiens (human)"
},
{
  "id": "hsa05215",
  "name": "Prostate cancer - Homo sapiens (human)"
},
{
  "id": "hsa05222",
  "name": "Small cell lung cancer - Homo sapiens (human)"
}
],
"netpath": [
  {
    "id": "Pathway_BCR",
    "name": "BCR"
  },
  {
    "id": "Pathway_EGFR1",
    "name": "EGFR1"
  },
  {
    "id": "Pathway_ID",
    "name": "ID"
  },
  {
    "id": "Pathway_IL2",
    "name": "IL2"
  },
  {
    "id": "Pathway_KitReceptor",
    "name": "KitReceptor"
  },
  {
    "id": "Pathway_RAGE",
    "name": "RAGE"
  },
  {
    "id": "Pathway_TGF_beta_Receptor",
    "name": "TGF_beta_Receptor"
  }
],
"pid": [
  {
    "id": "atr_pathway",

```

```

    "name": "ATR signaling pathway"
  },
  {
    "id": "bard1pathway",
    "name": "BARD1 signaling events"
  },
  {
    "id": "e2f_pathway",
    "name": "E2F transcription factor network"
  },
  {
    "id": "foxmlpathway",
    "name": "FOXO1 transcription factor network"
  },
  {
    "id": "foxopathway",
    "name": "FoxO family signaling"
  },
  {
    "id": "il2_1pathway",
    "name": "IL2-mediated signaling events"
  },
  {
    "id": "mtor_4pathway",
    "name": "mTOR signaling pathway"
  },
  {
    "id": "p53regulationpathway",
    "name": "p53 pathway"
  },
  {
    "id": "p73pathway",
    "name": "p73 transcription factor network"
  },
  {
    "id": "prlsignalingeventspathway",
    "name": "Signaling events mediated by PRL"
  },
  {
    "id": "rb_1pathway",
    "name": "Regulation of retinoblastoma protein"
  },
  {
    "id": "smad2_3nuclearpathway",
    "name": "Regulation of nuclear SMAD2/3 signaling"
  }
],
"reactome": [
  {
    "id": "R-HSA-109582",
    "name": "Hemostasis"
  },
  {
    "id": "R-HSA-1538133",
    "name": "G0 and Early G1"
  },
  {
    "id": "R-HSA-1640170",

```



```

    "name": "Cell Cycle"
  },
  {
    "id": "R-HSA-174143",
    "name": "APC/C-mediated degradation of cell cycle proteins"
  },
  {
    "id": "R-HSA-176187",
    "name": "Activation of ATR in response to replication stress"
  },
  {
    "id": "R-HSA-176408",
    "name": "Regulation of APC/C activators between G1/S and early anaphase"
  },
  {
    "id": "R-HSA-187577",
    "name": "SCF(Skp2)-mediated degradation of p27/p21"
  },
  {
    "id": "R-HSA-2262752",
    "name": "Cellular responses to stress"
  },
  {
    "id": "R-HSA-2559582",
    "name": "Senescence-Associated Secretory Phenotype (SASP)"
  },
  {
    "id": "R-HSA-2559583",
    "name": "Cellular Senescence"
  },
  {
    "id": "R-HSA-2559586",
    "name": "DNA Damage/Telomere Stress Induced Senescence"
  },
  {
    "id": "R-HSA-453274",
    "name": "Mitotic G2-G2/M phases"
  },
  {
    "id": "R-HSA-453276",
    "name": "Regulation of mitotic cell cycle"
  },
  {
    "id": "R-HSA-453279",
    "name": "Mitotic G1-G1/S phases"
  },
  {
    "id": "R-HSA-68874",
    "name": "M/G1 Transition"
  },
  {
    "id": "R-HSA-68911",
    "name": "G2 Phase"
  },
  {
    "id": "R-HSA-68949",
    "name": "Orcl removal from chromatin"
  },
},

```

```
{
  "id": "R-HSA-68962",
  "name": "Activation of the pre-replicative complex"
},
{
  "id": "R-HSA-69002",
  "name": "DNA Replication Pre-Initiation"
},
{
  "id": "R-HSA-69017",
  "name": "CDK-mediated phosphorylation and removal of Cdc6"
},
{
  "id": "R-HSA-69052",
  "name": "Switching of origins to a post-replicative state"
},
{
  "id": "R-HSA-69200",
  "name": "Phosphorylation of proteins involved in G1/S transition by active Cyclin E:Cdk2 comp
},
{
  "id": "R-HSA-69202",
  "name": "Cyclin E associated events during G1/S transition "
},
{
  "id": "R-HSA-69206",
  "name": "G1/S Transition"
},
{
  "id": "R-HSA-69239",
  "name": "Synthesis of DNA"
},
{
  "id": "R-HSA-69242",
  "name": "S Phase"
},
{
  "id": "R-HSA-69273",
  "name": "Cyclin A/B1 associated events during G2/M transition"
},
{
  "id": "R-HSA-69275",
  "name": "G2/M Transition"
},
{
  "id": "R-HSA-69278",
  "name": "Cell Cycle, Mitotic"
},
{
  "id": "R-HSA-69300",
  "name": "Removal of licensing factors from origins"
},
{
  "id": "R-HSA-69304",
  "name": "Regulation of DNA replication"
},
{
  "id": "R-HSA-69306",
```

```

    "name": "DNA Replication"
  },
  {
    "id": "R-HSA-69481",
    "name": "G2/M Checkpoints"
  },
  {
    "id": "R-HSA-69563",
    "name": "p53-Dependent G1 DNA Damage Response"
  },
  {
    "id": "R-HSA-69580",
    "name": "p53-Dependent G1/S DNA damage checkpoint"
  },
  {
    "id": "R-HSA-69615",
    "name": "G1/S DNA Damage Checkpoints"
  },
  {
    "id": "R-HSA-69620",
    "name": "Cell Cycle Checkpoints"
  },
  {
    "id": "R-HSA-69656",
    "name": "Cyclin A:Cdk2-associated events at S phase entry"
  },
  {
    "id": "R-HSA-983231",
    "name": "Factors involved in megakaryocyte development and platelet production"
  }
],
"wikipathways": [
  {
    "id": "WP1530",
    "name": "miRNA Regulation of DNA Damage Response"
  },
  {
    "id": "WP179",
    "name": "Cell Cycle"
  },
  {
    "id": "WP2032",
    "name": "TSH signaling pathway"
  },
  {
    "id": "WP2261",
    "name": "Signaling Pathways in Glioblastoma"
  },
  {
    "id": "WP2374",
    "name": "Oncostatin M Signaling Pathway"
  },
  {
    "id": "WP2377",
    "name": "Integrated Pancreatic Cancer Pathway"
  },
  {
    "id": "WP2431",

```

```
    "name": "Spinal Cord Injury"
  },
  {
    "id": "WP2446",
    "name": "Retinoblastoma (RB) in Cancer"
  },
  {
    "id": "WP2586",
    "name": "Aryl Hydrocarbon Receptor"
  },
  {
    "id": "WP2877",
    "name": "Vitamin D Receptor Pathway"
  },
  {
    "id": "WP45",
    "name": "G1 to S cell cycle control"
  },
  {
    "id": "WP466",
    "name": "DNA Replication"
  },
  {
    "id": "WP53",
    "name": "ID signaling pathway"
  },
  {
    "id": "WP707",
    "name": "DNA Damage Response"
  }
]
},
"pdb": [
  "1AQ1",
  "1B38",
  "1B39",
  "1BUH",
  "1CKP",
  "1DI8",
  "1DM2",
  "1E1V",
  "1E1X",
  "1E9H",
  "1F5Q",
  "1FIN",
  "1FQ1",
  "1FVT",
  "1FVV",
  "1G5S",
  "1GIH",
  "1GII",
  "1GIJ",
  "1GY3",
  "1GZ8",
  "1H00",
  "1H01",
  "1H07",
  "1H08",
```

```
"1H0V",  
"1H0W",  
"1H1P",  
"1H1Q",  
"1H1R",  
"1H1S",  
"1H24",  
"1H25",  
"1H26",  
"1H27",  
"1H28",  
"1HCK",  
"1HCL",  
"1JST",  
"1JSU",  
"1JSV",  
"1JVP",  
"1KE5",  
"1KE6",  
"1KE7",  
"1KE8",  
"1KE9",  
"1OGU",  
"1OI9",  
"1OIQ",  
"1OIR",  
"1OIT",  
"1OIU",  
"1OIY",  
"1OKV",  
"1OKW",  
"1OL1",  
"1OL2",  
"1P2A",  
"1P5E",  
"1PF8",  
"1PKD",  
"1PW2",  
"1PXI",  
"1PXJ",  
"1P XK",  
"1PXL",  
"1PXM",  
"1PXN",  
"1PXO",  
"1PXP",  
"1PYE",  
"1QMZ",  
"1R78",  
"1URC",  
"1URW",  
"1V1K",  
"1VYW",  
"1VYZ",  
"1W0X",  
"1W8C",  
"1W98",  
"1WCC",
```

```
"1Y8Y",  
"1Y91",  
"1YKR",  
"2A0C",  
"2A4L",  
"2B52",  
"2B53",  
"2B54",  
"2B55",  
"2BHE",  
"2BHH",  
"2BKZ",  
"2BPM",  
"2BTR",  
"2BTS",  
"2C4G",  
"2C5N",  
"2C5O",  
"2C5V",  
"2C5X",  
"2C5Y",  
"2C68",  
"2C69",  
"2C6I",  
"2C6K",  
"2C6L",  
"2C6M",  
"2C6O",  
"2C6T",  
"2CCH",  
"2CCI",  
"2CJM",  
"2CLX",  
"2DS1",  
"2DUV",  
"2EXM",  
"2FVD",  
"2G9X",  
"2HIC",  
"2I40",  
"2IW6",  
"2IW8",  
"2IW9",  
"2J9M",  
"2JGZ",  
"2R3F",  
"2R3G",  
"2R3H",  
"2R3I",  
"2R3J",  
"2R3K",  
"2R3L",  
"2R3M",  
"2R3N",  
"2R3O",  
"2R3P",  
"2R3Q",  
"2R3R",
```

```
"2R64",  
"2UUE",  
"2UZB",  
"2UZD",  
"2UZE",  
"2UZL",  
"2UZN",  
"2UZO",  
"2V0D",  
"2V22",  
"2VTA",  
"2VTH",  
"2VTI",  
"2VTJ",  
"2VTL",  
"2VTM",  
"2VTN",  
"2VTO",  
"2VTP",  
"2VTQ",  
"2VTR",  
"2VTS",  
"2VTT",  
"2VU3",  
"2VV9",  
"2W05",  
"2W06",  
"2W17",  
"2W1H",  
"2WEV",  
"2WFY",  
"2WHB",  
"2WIH",  
"2WIP",  
"2WMA",  
"2WMB",  
"2WPA",  
"2WXV",  
"2X1N",  
"2XMY",  
"2XNB",  
"3BHT",  
"3BHU",  
"3BHV",  
"3DDP",  
"3DDQ",  
"3DOG",  
"3EID",  
"3EJ1",  
"3EOC",  
"3EZR",  
"3EZV",  
"3F5X",  
"3FZ1",  
"3IG7",  
"3IGG",  
"3LE6",  
"3LFN",
```

```
"3LFQ",  
"3LFS",  
"3MY5",  
"3NS9",  
"3PJ8",  
"3PXF",  
"3PXQ",  
"3PXR",  
"3PXY",  
"3PXZ",  
"3PY0",  
"3PY1",  
"3QHR",  
"3QHW",  
"3QL8",  
"3QQF",  
"3QQG",  
"3QQH",  
"3QQJ",  
"3QQK",  
"3QQL",  
"3QRT",  
"3QRU",  
"3QTQ",  
"3QTR",  
"3QTS",  
"3QTU",  
"3QTW",  
"3QTX",  
"3QTZ",  
"3QU0",  
"3QWJ",  
"3QWK",  
"3QX2",  
"3QX4",  
"3QXO",  
"3QXP",  
"3QZF",  
"3QZG",  
"3QZH",  
"3QZI",  
"3R1Q",  
"3R1S",  
"3R1Y",  
"3R28",  
"3R6X",  
"3R71",  
"3R73",  
"3R7E",  
"3R7I",  
"3R7U",  
"3R7V",  
"3R7Y",  
"3R83",  
"3R8L",  
"3R8M",  
"3R8P",  
"3R8U",
```



```
"3R8V",  
"3R8Z",  
"3R9D",  
"3R9H",  
"3R9N",  
"3R9O",  
"3RAH",  
"3RAI",  
"3RAK",  
"3RAL",  
"3RJC",  
"3RK5",  
"3RK7",  
"3RK9",  
"3RKB",  
"3RM6",  
"3RM7",  
"3RMF",  
"3RNI",  
"3ROY",  
"3RPO",  
"3RPR",  
"3RPV",  
"3RPY",  
"3RZB",  
"3S00",  
"3S00",  
"3S1H",  
"3S2P",  
"3SQQ",  
"3SW4",  
"3SW7",  
"3TI1",  
"3TIY",  
"3TIZ",  
"3TNW",  
"3ULI",  
"3UNJ",  
"3UNK",  
"3WBL",  
"4ACM",  
"4BCK",  
"4BCM",  
"4BCN",  
"4BCO",  
"4BCP",  
"4BCQ",  
"4BGH",  
"4BZD",  
"4CFM",  
"4CFN",  
"4CFU",  
"4CFV",  
"4CFW",  
"4CFX",  
"4D1X",  
"4D1Z",  
"4EK3",
```

```
"4EK4",
"4EK5",
"4EK6",
"4EK8",
"4EOI",
"4EOJ",
"4EOK",
"4EOL",
"4EOM",
"4EON",
"4EOO",
"4EOP",
"4EOQ",
"4EOR",
"4EOS",
"4ERW",
"4EZ3",
"4EZ7",
"4FKG",
"4FKI",
"4FKJ",
"4FKL",
"4FKO",
"4FKP",
"4FKQ",
"4FKR",
"4FKS",
"4FKT",
"4FKU",
"4FKV",
"4FKW",
"4FX3",
"4GCJ",
"4I3Z",
"4II5",
"4KD1",
"4LYN",
"4NJ3",
"4RJ3",
"5A14",
"5AND",
"5ANE",
"5ANG",
"5ANI",
"5ANJ",
"5ANK",
"5ANO",
"5CYI",
"5D1J",
"5FP5",
"5FP6",
"5IEV",
"5IEX",
"5IEY",
"5IF1"
],
"pfam": "PF00069",
"pharmgkb": "PA101",
```

```

"pir": "A41227",
"prosite": "PS50011",
"reagent": {
  "GNF_Qia_hs-genome_v1_siRNA": [
    {
      "id": "GNF247215",
      "relationship": "is"
    },
    {
      "id": "GNF247216",
      "relationship": "is"
    },
    {
      "id": "GNF247217",
      "relationship": "is"
    },
    {
      "id": "GNF247218",
      "relationship": "is"
    }
  ],
  "GNF_hs-ORFeome1_1_reads": {
    "id": "GNF161504",
    "relationship": "is"
  },
  "GNF_hs-Origene": [
    {
      "id": "GNF035860",
      "relationship": "similar to"
    },
    {
      "id": "GNF037258",
      "relationship": "is"
    },
    {
      "id": "GNF048982",
      "relationship": "is"
    }
  ],
  "GNF_hs-druggable_lenti-shRNA": [
    {
      "id": "GNF081385",
      "relationship": "is"
    },
    {
      "id": "GNF081386",
      "relationship": "is"
    },
    {
      "id": "GNF081387",
      "relationship": "is"
    }
  ],
  "GNF_hs-druggable_plasmid-shRNA": [
    {
      "id": "GNF051995",
      "relationship": "is"
    }
  ],

```

```
{
  "id": "GNF056761",
  "relationship": "is"
},
{
  "id": "GNF061563",
  "relationship": "is"
},
{
  "id": "GNF078683",
  "relationship": "is"
}
],
"GNF_hs-druggable_siRNA": [
  {
    "id": "GNF066537",
    "relationship": "is"
  },
  {
    "id": "GNF066538",
    "relationship": "is"
  }
],
"GNF_hs-pkinase_IDT-siRNA": [
  {
    "id": "GNF166768",
    "relationship": "is"
  },
  {
    "id": "GNF166769",
    "relationship": "is"
  },
  {
    "id": "GNF166770",
    "relationship": "is"
  },
  {
    "id": "GNF166771",
    "relationship": "is"
  }
],
"GNF_hs_LentiORF-HA-MYC": {
  "id": "GNF282834",
  "relationship": "is"
},
"GNF_hs_LentiORF-Jred": {
  "id": "GNF283761",
  "relationship": "is"
},
"GNF_mm+hs-MGC": {
  "id": "GNF002384",
  "relationship": "is"
},
"Invitrogen_IVTHSSIPk2": [
  {
    "id": "GNF324610",
    "relationship": "is"
  }
],
```

```

    {
      "id": "GNF324611",
      "relationship": "is"
    }
  ],
  "NIBRI_hs-Secretome_pDEST": {
    "id": "GNF337962",
    "relationship": "is"
  },
  "NOVART_hs-genome_siRNA": [
    {
      "id": "GNF093028",
      "relationship": "is"
    },
    {
      "id": "GNF132726",
      "relationship": "is"
    }
  ]
},
"refseq": {
  "genomic": [
    "NC_000012.12",
    "NC_018923.2",
    "NG_034014.1"
  ],
  "protein": [
    "NP_001277159.1",
    "NP_001789.2",
    "NP_439892.2",
    "XP_011536034.1"
  ],
  "rna": [
    "NM_001290230.1",
    "NM_001798.4",
    "NM_052827.3",
    "XM_011537732.1"
  ],
  "translation": [
    {
      "protein": "XP_011536034.1",
      "rna": "XM_011537732.1"
    },
    {
      "protein": "NP_001789.2",
      "rna": "NM_001798.4"
    },
    {
      "protein": "NP_439892.2",
      "rna": "NM_052827.3"
    },
    {
      "protein": "NP_001277159.1",
      "rna": "NM_001290230.1"
    }
  ]
},
"reporter": {

```

```

"HG-U133_Plus_2": [
  "204252_at",
  "211803_at",
  "211804_s_at"
],
"HG-U95Av2": [
  "1792_g_at",
  "1833_at"
],
"HTA-2_0": "TC12000496.hg.1",
"HuEx-1_0": "3417146",
"HuGene-1_1": "7956076",
"HuGene-2_1": "16752305"
},
"summary": "This gene encodes a member of a family of serine/threonine protein kinases that partic
"symbol": "CDK2",
"taxid": 9606,
"type_of_gene": "protein-coding",
"unigene": [
  "Hs.19192",
  "Hs.689624"
],
"uniprot": {
  "Swiss-Prot": "P24941",
  "TrEMBL": [
    "A0A024RB10",
    "A0A024RB77",
    "B4DDL9",
    "E7ESI2",
    "G3V317",
    "G3V5T9"
  ]
},
"wikipedia": {
  "url_stub": "Cyclin-dependent kinase 2"
}
}

```

#### 4.4.3 Batch queries via POST

Although making simple GET requests above to our gene query service is sufficient in most of use cases, there are some cases you might find it's more efficient to make queries in a batch (e.g., retrieving gene annotation for multiple genes). Fortunately, you can also make batch queries via POST requests when you need:

```

URL: http://mygene.info/v3/gene
HTTP method: POST

```

#### Query parameters

##### ids

Required. Accept multiple geneids (either Entrez or Ensembl gene ids) seperated by comma, e.g., 'ids=1017,1018' or 'ids=695,ENSG00000123374'. Note that currently we only take the input ids up to **1000** maximum, the rest will be omitted.

**fields**

Optional, can be a comma-separated fields to limit the fields returned from the matching hits. If “fields=all”, all available fields will be returned. Note that it supports dot notation as well, e.g., you can pass “refseq.rna”. Default: “symbol,name,taxid,entrezgene”.

**species**

Optional, can be used to limit the gene hits from given species. You can use “common names” for nine common species (human, mouse, rat, fruitfly, nematode, zebrafish, thale-cress, frog and pig). All other species, you can provide their taxonomy ids. See more details here. Multiple species can be passed using comma as a separator. Passing “all” will query against all available species. Default: all.

**dotfield**

Optional, can be used to control the format of the returned fields when passed “fields” parameter contains dot notation, e.g. “fields=refseq.rna”. If “dotfield” is true, the returned data object contains a single “refseq.rna” field, otherwise, a single “refseq” field with a sub-field of “rna”. Default: false.

**email**

Optional, if you are regular users of our services, we encourage you to provide us an email, so that we can better track the usage or follow up with you.

**Example code**

Unlike GET requests, you can easily test them from browser, make a POST request is often done via a piece of code, still trivial of course. Here is a sample python snippet:

```
import requests
headers = {'content-type': 'application/x-www-form-urlencoded'}
params = 'ids=1017,695&fields=name,symbol,refseq.rna'
res = requests.post('http://mygene.info/v3/gene', data=params, headers=headers)
```

**Returned object**

Returned result (the value of “res.text” variable above) from above example code should look like this:

```
[
  {
    '_id': '1017',
    '_score': 21.731894,
    'name': 'cyclin dependent kinase 2',
    'query': '1017',
    'refseq': {
      'rna': [
        'NM_001290230.1',
        'NM_001798.4',
        'NM_052827.3',
        'XM_011537732.1'
      ]
    }
  }
]
```

```
    },
    'symbol': 'CDK2'
  },
  {
    '_id': '695',
    '_score': 21.730501,
    'name': 'Bruton tyrosine kinase',
    'query': '695',
    'refseq': {
      'rna': [
        'NM_000061.2',
        'NM_001287344.1',
        'NM_001287345.1'
      ]
    }
  },
  'symbol': 'BTK'
}
]
```

## 4.5 Usage and Demo

This page provides some usage examples and demo applications.

### 4.5.1 Call from web applications

You can call MyGene.info services from either server-side or client-side (via AJAX). The sample code can be found at “*demo*” section.

#### Calling services from server-side

All common programming languages provide functions for making http requests and JSON parsing. For Python, you can use build-in `httplib` and `json` modules (v2.6 up), or third-party `httplib2` and `simplejson` modules. For Perl, `LWP::Simple` and `JSON` modules should work nicely.

#### Making AJAX calls from client-side

When making an AJAX call from a web application, it is restricted by “same-origin” security policy, but there are several standard ways to get it around.

#### Making your own server-side proxy

To overcome “same-origin” restriction, you can create proxy at your server-side to our services. And then call your proxied services from your web application.

Setup proxy in popular server-side applications, like `Apache`, `Nginx` and `PHP`, are straightforward.



## Making JSONP call

Because our core services are just called as simple GET http requests (though we support POST requests for batch queries too), you can bypass “same-origin” restriction by making JSONP call as well. To read more about JSONP, see [1](#), [2](#), or just Google about it. All our services accept an optional “**callback**” parameter, so that you can pass your callback function to make a JSONP call.

All popular javascript libraries have the support for making JSONP calls, like in [jQuery](#), [ExtJS](#), [MooTools](#)

## Cross-origin http request through CORS

Cross-Origin Resource Sharing (CORS) specification is a [W3C draft specification](#) defining client-side cross-origin requests. It’s actually supported by all major browsers by now (Internet Explorer 8+, Firefox 3.5+, Safari 4+, and Chrome. See more on [browser support](#)), but not many people are aware of it. Unlike JSONP, which is limited to GET requests only, you can make cross-domain POST requests as well. Our services supports CORS requests on both GET and POST requests. You can find more information and use case [here](#) and [here](#).

jQuery’s native ajax call supports CORS since v1.5.

## 4.5.2 Demo Applications

In this demo, we want to create a web site to display expression charts from a microarray dataset (Affymetrix MOE430v2 chip). The expression data are indexed by porobeset ids, but we need to allow users to query for any mouse genes using any commonly-used identifiers, and then display expression charts for any selected gene.

We implemented this demo in four ways:

### Example 1: using CGI

- [Download sample code here](#).
- It’s a simple python CGI script. To run it, you just need to drop it to your favorite web server’s cgi-bin folder (make sure your python, v2.6 up, is in the path).
- [See it in action here](#)

### Example 2: using tornado

- [Download sample code here](#).
- This single python script can be used to run a standalone website. Just run:  
`python mygene_info_demo_tornado.py`. You then have your website up at `http://localhost:8000`.

Besides python (v2.6 up), you also need [tornado](#) to run this code. You can either install it by your own (`pip install tornado`), or download [this zip file](#), which includes tornado in it.

- [See it in action here](#)

### Example 3: using JSONP

- [Download sample code here.](#)
- The zip file contains one html file and one javascript file. There is no server-side code at all. To run it, just unzip it and open the html file in any browser. All remote service calls are done at client side (via browsers). Put the files into any web server serving static files will allow you to publish to the world.
- [See it in action here](#)

### Example 4: using CORS

- [Download sample code here.](#)
- The zip file contains one html file and one javascript file. There is no server-side code at all. To run it, just unzip it and open the html file in any browser. All remote service calls are done at client side (via browsers). Put the files into any web server serving static files will allow you to publish to the world.
- This demo is almost the same as the one using JSONP, except that the actual AJAX call to MyGene.info server is made via CORS.
- [See it in action here](#)

## 4.5.3 Autocomplete widget for gene query

When you build a web application to have users to query for their favorite genes, the autocomplete widget is very useful, as it provides suggestions while users start to type into the field.

---

**Note:** The autocomplete widget below is a simple demo application. You may also want to have a look at this more sophisticated autocomplete widget, which comes with a lot more customization options.

---

### Try it live first

### About this widget

This autocomplete widget for gene query provides suggestions while you type a gene symbol or name into the field. Here the gene suggestions are displayed as “<Symbol>:<Name>”, automatically triggered when at least two characters are entered into the field.

At the backend, this widget is powered by the gene query web service from [MyGene.info](#). By default, the gene suggestions display human genes only.

### Use it in your website

To use this widget in your own website is very easy, just following these three steps:

1. Copy/paste this line into your html file:

```
<script src="http://mygene.info/widget/autocomplete/js/mygene_query_min.js" type="text/javascript">
```

---

**Hint:** if you prefer an un-minified javascript file, using “mygene\_query.js” instead.

---

2. Add “**mygene\_query\_target**” class to your target input element:

```
<input id="gene_query" style="width:250px" class="mygene_query_target">
```

so that we know which input field to enable autocomplete.

3. Define your own callback function, which is triggered after user selects a gene. For example:

```
<script type="text/javascript">
  mygene_query_select_callback = function(event, ui){
    alert( ui.item ?
      "Selected: " + ui.item.label + '('+ui.item.entrezgene+')':
      "Nothing selected, input was " + this.value);
  };
</script>
```

As shown in above example, you can access the gene object as **ui.item**:

ui.item._id	gene id
ui.item.value	gene symbol
ui.item.label	the label displayed in autocomplete dropdown list

**Note:** if you don’t define your own callback function (like the minimal HTML page below), the default behavior is to display an alert msg with the gene selected. To change this default behavior, you must overwrite with your own callback function (keep the same name as “**mygene\_query\_select\_callback**”).

A minimal HTML page with autocomplete enabled looks just like this ([See it in action here](#)):

```
<html>
<body>
  <label for="gene_query">Enter a gene here: </label>
  <input style="width:250px" class="mygene_query_target">
  <script src="http://mygene.info/widget/autocomplete/js/mygene_query_min.js" type="text/javascript">
</body>
</html>
```

Have fun! And send us feedback at [help@mygene.info](mailto:help@mygene.info).

## 4.6 Third-party packages

This page lists third-party packages/modules built upon [MyGene.info](#) services.

### 4.6.1 MyGene python module

“mygene” is an easy-to-use Python wrapper to access [MyGene.info](#) services.

You can install it easily using either [pip](#) or [easy\\_install](#):

```
pip install mygene #this is preferred
```

or:

```
easy_install mygene
```

This is a brief example:

```
In [1]: import mygene

In [2]: mg = mygene.MyGeneInfo()

In [3]: mg.getgene(1017)
Out[3]:
{'_id': '1017',
 'entrezgene': 1017,
 'name': 'cyclin-dependent kinase 2',
 'symbol': 'CDK2',
 'taxid': 9606}

In [4]: mg.query('cdk2', size=2)
Out[4]:
{'hits': [{'_id': '1017',
            '_score': 373.24667,
            'entrezgene': 1017,
            'name': 'cyclin-dependent kinase 2',
            'symbol': 'CDK2',
            'taxid': 9606},
          {'_id': '12566',
            '_score': 353.90176,
            'entrezgene': 12566,
            'name': 'cyclin-dependent kinase 2',
            'symbol': 'Cdk2',
            'taxid': 10090}],
 'max_score': 373.24667,
 'took': 10,
 'total': 28}
```

See <https://pypi.python.org/pypi/mygene> for more details.

## 4.6.2 MyGene autocomplete widget

This autocomplete widget for gene query (built upon JQueryUI's autocomplete widget) provides suggestions while you type a gene symbol or name into the field. You can easily embed it into your web application. It also provides many customization options for your different use-cases.

See <https://bitbucket.org/sulab/mygene.autocomplete/overview> for more details.

You can also play with this jsFiddle example:

## 4.6.3 Another MyGene Python wrapper

This is yet another Python wrapper of MyGene.info services created by Brian Schrader. It's hosted at <https://github.com/Sonictherocketman/mygene-api>.

It's available from PyPI as well:

```
pip install mygene-api
```

Some basic examples:

- Find a given gene with the id: CDK2.

```
""" Use the query API to find a gene with
the given symbol.
```

```

"""
from mygene.gene import Gene

results = Gene.find_by(q='CDK2')
for r in result:
    print r._id, r.name

>>> 1017 cyclin-dependent kinase 2
12566 cyclin-dependent kinase 2
362817 cyclin dependent kinase 2
52004 CDK2-associated protein 2
...

```

- Given an known gene, get it's begin and end coordinates.

```

""" Use the annotation API to find the full
details of a given gene.
"""
from mygene.gene import gene

gene = Gene.get('1017')
print gene._id, gene.genomic_pos_hg19['start'], gene.genomic_pos_hg19['end']

>>> 1017 56360553 56366568

```

- This library also supports the metadata API.

```

from mygene.metadata import Metadata

metadata = Metadata.get_metadata()
print metadata.stats['total_genes']

>>> 12611464

```

## 4.7 Terms of Use

The MyGene.info website (“MyGene.info”) has been designed to provide you with access to gene-centric annotation data that are maintained by The Scripps Research Institute (“TSRI”). TSRI authorizes you to access and use MyGene.info and the data and information contained on this MyGene.info website and database under the conditions set forth below.

You also agree that you will ensure that any copies of documents you generate by using MyGene.info shall retain and display all copyright and other proprietary notices contained therein. TSRI has attempted to provide accurate and current information on MyGene.info. However, TSRI makes no representations or warranties that the information contained or published on MyGene.info will be suitable for your specific purposes or for any other purposes. You agree to indemnify, defend, and hold TSRI harmless from all claims, damages, liabilities and expenses, including without limitation reasonable attorney’s fees and costs, whether or not a lawsuit or other proceeding is filed, that in any way arise out of or relate to your use of MyGene.info and/or use of the other third party websites referenced herein.

ALL INFORMATION AND DATA PROVIDED ON MYGENE.INFO IS PROVIDED “AS-IS” WITHOUT WARRANTY OF ANY KIND. TSRI MAKES NO REPRESENTATIONS OR WARRANTIES CONCERNING MYGENE.INFO OR ANY OTHER MATTER WHATSOEVER, INCLUDING WITHOUT LIMITATION ANY EXPRESS, IMPLIED OR STATUTORY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT OF THIRD PARTY RIGHTS, TITLE, ACCURACY, COMPLETENESS OR ARISING OUT OF COURSE OF CONDUCT OR TRADE CUSTOM OR USAGE, AND DISCLAIMS ALL SUCH

EXPRESS, IMPLIED OR STATUTORY WARRANTIES. TSRI MAKES NO WARRANTY OR REPRESENTATION THAT YOUR USE OF MYGENE.INFO WILL NOT INFRINGE UPON THE INTELLECTUAL PROPERTY OR OTHER RIGHTS OF ANY THIRD PARTY. FURTHER, TSRI SHALL NOT BE LIABLE IN ANY MANNER WHATSOEVER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES ARISING OUT OF OR IN ANY WAY RELATED TO MYGENE.INFO, THE USE OF, OR INABILITY TO USE, ANY OF THE INFORMATION OR DATA CONTAINED OR REFERENCED IN THIS WEBSITE OR ANY INFORMATION OR DATA THAT IS PROVIDED THROUGH LINKED WEBSITES, OR ANY OTHER MATTER. THE FOREGOING EXCLUSIONS AND LIMITATIONS SHALL APPLY TO ALL CLAIMS AND ACTIONS OF ANY KIND AND ON ANY THEORY OF LIABILITY, WHETHER BASED ON CONTRACT, TORT OR ANY OTHER GROUNDS, AND REGARDLESS OF WHETHER A PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, AND NOTWITHSTANDING ANY FAILURE OF ESSENTIAL PURPOSE OF ANY LIMITED REMEDY. BY USING THIS WEBSITE, YOU FURTHER AGREE THAT EACH WARRANTY DISCLAIMER, EXCLUSION OF DAMAGES OR OTHER LIMITATION OF LIABILITY HEREIN IS INTENDED TO BE SEVERABLE AND INDEPENDENT OF THE OTHER CLAUSES OR SENTENCES BECAUSE THEY EACH REPRESENT SEPARATE ELEMENTS OF RISK ALLOCATION BETWEEN THE PARTIES.

MyGene.info may contain information from third party websites, which may or may not be marked with the name of the source. Such information does not necessarily represent the views or opinions of TSRI, and TSRI shall have no responsibility whatsoever for such information. All information from third party websites are the sole responsibility of the person or entity that provides and/or maintains such website. As a MyGene.info user, you are solely responsible for any information that you display, generate, transmit or transfer while using MyGene.info, and for the consequences of such actions.

Should any MyGene.info user provide general, scientific or other feedback information, whether in the form of questions, comments, or suggestions to TSRI, regarding the content of TSRI's website or otherwise, such information shall not be deemed to be confidential or proprietary to you or to any other party. TSRI shall have no obligation of any kind with respect to such information and TSRI shall have the right, without limitation, to reproduce, use, disclose, merge, display, make derivatives of and distribute such information to others. TSRI shall also have the right, without limitation, to use and exploit such information, including ideas, concepts, know-how, inventions, techniques or other materials contained in such information for any purpose whatsoever, including but not limited to, making changes or improvements to MyGene.info and/or developing, manufacturing, marketing, selling or distributing products and technologies incorporating such information. However, you agree that TSRI has no obligation whatsoever to respond to your comments or to change or correct any information on MyGene.info based on your comments.

TSRI reserves the right to alter the content of MyGene.info in any way, at any time and for any reason, with or without prior notice to you, and TSRI will not be liable in any way for possible consequences of such changes or for inaccuracies, typographical errors or omissions in the contents hereof. Nothing contained herein shall be construed as conferring by implication, estoppel or otherwise any license or right under any patent, trademark or other intellectual property of TSRI or any third party. Except as expressly provided above, nothing contained herein shall be construed as conferring any right or license under any TSRI copyrights.

TSRI also reserves the right to modify these Terms of Use at any time and for any reason, with or without prior notice to you. You should always review the most current Terms of Use herein before using this website. By using this website, you agree to the current Terms of Use posted on this site. You also agree that these Terms of Use constitute the entire agreement between you and TSRI regarding the subject matter hereof and supersede all prior and contemporaneous understandings, oral or written, regarding such subject matter. In addition, if any provision of these Terms of Use is found by a court of competent jurisdiction to be invalid, void or unenforceable, the remaining provisions shall remain in full force and effect, and the affected provision shall be revised so as to reflect the original intent of the parties hereunder to the maximum extent permitted by applicable law.

BY USING THIS WEBSITE, YOU ACKNOWLEDGE AND AGREE THAT YOU HAVE READ, UNDERSTOOD AND AGREE TO ALL OF THESE TERMS OF USE.

---

**How to cite**

---

See citation page here: <http://mygene.info/citation/>





---

**FAQ**

---

See FAQ page here: <http://mygene.info/faq/>



---

**Related links**

---

- [mygene.info on Github](#)



---

**Contact us**

---

- [help@mygene.info](mailto:help@mygene.info)
- [@mygeneinfo](#)