
MySQLdb Documentation

Release 1.2.4b4

Andy Dustman

Jul 19, 2017

1	MySQLdb User's Guide	3
1.1	Introduction	3
1.2	Installation	4
1.3	_mysql	4
1.3.1	MySQL C API translation	4
1.3.2	MySQL C API function mapping	4
1.3.3	Some _mysql examples	5
1.4	MySQLdb	7
1.4.1	Functions and attributes	7
1.4.2	Connection Objects	9
1.4.3	Cursor Objects	9
1.4.4	Some examples	10
1.5	Using and extending	11
1.6	Embedded Server	12
2	MySQLdb Package	13
2.1	MySQLdb Package	13
2.2	connections Module	15
2.3	converters Module	17
2.4	cursors Module	18
2.5	times Module	18
2.6	Subpackages	19
2.6.1	constants Package	19
3	MySQLdb Frequently Asked Questions	21
3.1	Build Errors	21
3.2	ImportError	22
3.3	My data disappeared! (or won't go away!)	22
3.4	Other Errors	23
3.5	Other Resources	23
4	Indices and tables	25
	Python Module Index	27

Contents:

Contents

- *MySQLdb User's Guide*
 - *Introduction*
 - *Installation*
 - *_mysql*
 - * *MySQL C API translation*
 - * *MySQL C API function mapping*
 - * *Some _mysql examples*
 - *MySQLdb*
 - * *Functions and attributes*
 - * *Connection Objects*
 - * *Cursor Objects*
 - * *Some examples*
 - *Using and extending*
 - *Embedded Server*

Introduction

MySQLdb is an thread-compatible interface to the popular MySQL database server that provides the Python database API.

Installation

The README file has complete installation instructions.

`_mysql`

If you want to write applications which are portable across databases, use *MySQLdb*, and avoid using this module directly. `_mysql` provides an interface which mostly implements the MySQL C API. For more information, see the [MySQL documentation](#). The documentation for this module is intentionally weak because you probably should use the higher-level MySQLdb module. If you really need it, use the standard MySQL docs and transliterate as necessary.

MySQL C API translation

The MySQL C API has been wrapped in an object-oriented way. The only MySQL data structures which are implemented are the `MYSQL` (database connection handle) and `MYSQL_RES` (result handle) types. In general, any function which takes `MYSQL *mysql` as an argument is now a method of the connection object, and any function which takes `MYSQL_RES *result` as an argument is a method of the result object. Functions requiring none of the MySQL data structures are implemented as functions in the module. Functions requiring one of the other MySQL data structures are generally not implemented. Deprecated functions are not implemented. In all cases, the `mysql_` prefix is dropped from the name. Most of the `conn` methods listed are also available as MySQLdb Connection object methods. Their use is non-portable.

MySQL C API function mapping

C API	<code>_mysql</code>
<code>mysql_affected_rows()</code>	<code>conn.affected_rows()</code>
<code>mysql_autocommit()</code>	<code>conn.autocommit()</code>
<code>mysql_character_set_name()</code>	<code>conn.character_set_name()</code>
<code>mysql_close()</code>	<code>conn.close()</code>
<code>mysql_commit()</code>	<code>conn.commit()</code>
<code>mysql_connect()</code>	<code>_mysql.connect()</code>
<code>mysql_data_seek()</code>	<code>result.data_seek()</code>
<code>mysql_debug()</code>	<code>_mysql.debug()</code>
<code>mysql_dump_debug_info</code>	<code>conn.dump_debug_info()</code>
<code>mysql_escape_string()</code>	<code>_mysql.escape_string()</code>
<code>mysql_fetch_row()</code>	<code>result.fetch_row()</code>
<code>mysql_get_character_set_info()</code>	<code>conn.get_character_set_info()</code>
<code>mysql_get_client_info()</code>	<code>_mysql.get_client_info()</code>
<code>mysql_get_host_info()</code>	<code>conn.get_host_info()</code>
<code>mysql_get_proto_info()</code>	<code>conn.get_proto_info()</code>
<code>mysql_get_server_info()</code>	<code>conn.get_server_info()</code>
<code>mysql_info()</code>	<code>conn.info()</code>
<code>mysql_insert_id()</code>	<code>conn.insert_id()</code>
<code>mysql_num_fields()</code>	<code>result.num_fields()</code>
<code>mysql_num_rows()</code>	<code>result.num_rows()</code>
<code>mysql_options()</code>	various options to <code>_mysql.connect()</code>
<code>mysql_ping()</code>	<code>conn.ping()</code>

Continued on next page

Table 1.1 – continued from previous page

C API	<code>_mysql</code>
<code>mysql_query()</code>	<code>conn.query()</code>
<code>mysql_real_connect()</code>	<code>_mysql.connect()</code>
<code>mysql_real_query()</code>	<code>conn.query()</code>
<code>mysql_real_escape_string()</code>	<code>conn.escape_string()</code>
<code>mysql_rollback()</code>	<code>conn.rollback()</code>
<code>mysql_row_seek()</code>	<code>result.row_seek()</code>
<code>mysql_row_tell()</code>	<code>result.row_tell()</code>
<code>mysql_select_db()</code>	<code>conn.select_db()</code>
<code>mysql_set_character_set()</code>	<code>conn.set_character_set()</code>
<code>mysql_ssl_set()</code>	ssl option to <code>_mysql.connect()</code>
<code>mysql_stat()</code>	<code>conn.stat()</code>
<code>mysql_store_result()</code>	<code>conn.store_result()</code>
<code>mysql_thread_id()</code>	<code>conn.thread_id()</code>
<code>mysql_thread_safe_client()</code>	<code>conn.thread_safe_client()</code>
<code>mysql_use_result()</code>	<code>conn.use_result()</code>
<code>mysql_warning_count()</code>	<code>conn.warning_count()</code>
<code>CLIENT_*</code>	<code>MySQLdb.constants.CLIENT.*</code>
<code>CR_*</code>	<code>MySQLdb.constants.CR.*</code>
<code>ER_*</code>	<code>MySQLdb.constants.ER.*</code>
<code>FIELD_TYPE_*</code>	<code>MySQLdb.constants.FIELD_TYPE.*</code>
<code>FLAG_*</code>	<code>MySQLdb.constants.FLAG.*</code>

Some `_mysql` examples

Okay, so you want to use `_mysql` anyway. Here are some examples.

The simplest possible database connection is:

```
import _mysql
db=_mysql.connect()
```

This creates a connection to the MySQL server running on the local machine using the standard UNIX socket (or named pipe on Windows), your login name (from the `USER` environment variable), no password, and does not `USE` a database. Chances are you need to supply more information.:

```
db=_mysql.connect("localhost", "joebob", "moonpie", "thangs")
```

This creates a connection to the MySQL server running on the local machine via a UNIX socket (or named pipe), the user name “joebob”, the password “moonpie”, and selects the initial database “thangs”.

We haven’t even begun to touch upon all the parameters `connect()` can take. For this reason, I prefer to use keyword parameters:

```
db=_mysql.connect(host="localhost", user="joebob",
                  passwd="moonpie", db="thangs")
```

This does exactly what the last example did, but is arguably easier to read. But since the default host is “localhost”, and if your login name really was “joebob”, you could shorten it to this:

```
db=_mysql.connect(passwd="moonpie", db="thangs")
```

UNIX sockets and named pipes don’t work over a network, so if you specify a host other than `localhost`, TCP will be used, and you can specify an odd port if you need to (the default port is 3306):

```
db=_mysql.connect(host="outhouse",port=3307,passwd="moonpie",db="thangs")
```

If you really had to, you could connect to the local host with TCP by specifying the full host name, or 127.0.0.1.

Generally speaking, putting passwords in your code is not such a good idea:

```
db=_mysql.connect(host="outhouse",db="thangs",read_default_file=~/.my.cnf)
```

This does what the previous example does, but gets the username and password and other parameters from `~/.my.cnf` (UNIX-like systems). Read about [option files](#) for more details.

So now you have an open connection as `db` and want to do a query. Well, there are no cursors in MySQL, and no parameter substitution, so you have to pass a complete query string to `db.query()`:

```
db.query("""SELECT spam, eggs, sausage FROM breakfast
        WHERE price < 5""")
```

There's no return value from this, but exceptions can be raised. The exceptions are defined in a separate module, `_mysql_exceptions`, but `_mysql` exports them. Read DB API specification [PEP-249](#) to find out what they are, or you can use the catch-all `MySQLError`.

At this point your query has been executed and you need to get the results. You have two options:

```
r=db.store_result()
# ...or...
r=db.use_result()
```

Both methods return a result object. What's the difference? `store_result()` returns the entire result set to the client immediately. If your result set is really large, this could be a problem. One way around this is to add a `LIMIT` clause to your query, to limit the number of rows returned. The other is to use `use_result()`, which keeps the result set in the server and sends it row-by-row when you fetch. This does, however, tie up server resources, and it ties up the connection: You cannot do any more queries until you have fetched **all** the rows. Generally I recommend using `store_result()` unless your result set is really huge and you can't use `LIMIT` for some reason.

Now, for actually getting real results:

```
>>> r.fetch_row()
(('3', '2', '0'),)
```

This might look a little odd. The first thing you should know is, `fetch_row()` takes some additional parameters. The first one is, how many rows (`maxrows`) should be returned. By default, it returns one row. It may return fewer rows than you asked for, but never more. If you set `maxrows=0`, it returns all rows of the result set. If you ever get an empty tuple back, you ran out of rows.

The second parameter (`how`) tells it how the row should be represented. By default, it is zero which means, return as a tuple. `how=1` means, return it as a dictionary, where the keys are the column names, or `table.column` if there are two columns with the same name (say, from a join). `how=2` means the same as `how=1` except that the keys are *always* `table.column`; this is for compatibility with the old `MySQLdb` module.

OK, so why did we get a 1-tuple with a tuple inside? Because we implicitly asked for one row, since we didn't specify `maxrows`.

The other oddity is: Assuming these are numeric columns, why are they returned as strings? Because MySQL returns all data as strings and expects you to convert it yourself. This would be a real pain in the ass, but in fact, `_mysql` can do this for you. (And `MySQLdb` does do this for you.) To have automatic type conversion done, you need to create a type converter dictionary, and pass this to `connect()` as the `conv` keyword parameter.

The keys of `conv` should be MySQL column types, which in the C API are `FIELD_TYPE_*`. You can get these values like this:

```
from MySQLdb.constants import FIELD_TYPE
```

By default, any column type that can't be found in `conv` is returned as a string, which works for a lot of stuff. For our purposes, we probably want this:

```
my_conv = { FIELD_TYPE.LONG: int }
```

This means, if it's a `FIELD_TYPE_LONG`, call the builtin `int()` function on it. Note that `FIELD_TYPE_LONG` is an `INTEGER` column, which corresponds to a C `long`, which is also the type used for a normal Python integer. But beware: If it's really an `UNSIGNED INTEGER` column, this could cause overflows. For this reason, `MySQLdb` actually uses `long()` to do the conversion. But we'll ignore this potential problem for now.

Then if you use `db=_mysql.connect(conv=my_conv...)`, the results will come back `((3, 2, 0),)`, which is what you would expect.

MySQLdb

`MySQLdb` is a thin Python wrapper around `_mysql` which makes it compatible with the Python DB API interface (version 2). In reality, a fair amount of the code which implements the API is in `_mysql` for the sake of efficiency.

The DB API specification [PEP-249](#) should be your primary guide for using this module. Only deviations from the spec and other database-dependent things will be documented here.

Functions and attributes

Only a few top-level functions and attributes are defined within `MySQLdb`.

connect(parameters...) Constructor for creating a connection to the database. Returns a `Connection Object`. Parameters are the same as for the MySQL C API. In addition, there are a few additional keywords that correspond to what you would pass `mysql_options()` before connecting. Note that some parameters must be specified as keyword arguments! The default value for each parameter is `NULL` or zero, as appropriate. Consult the MySQL documentation for more details. The important parameters are:

host name of host to connect to. Default: use the local host via a UNIX socket (where applicable)

user user to authenticate as. Default: current effective user.

passwd password to authenticate with. Default: no password.

db database to use. Default: no default database.

port TCP port of MySQL server. Default: standard port (3306).

unix_socket location of UNIX socket. Default: use default location or TCP for remote hosts.

conv type conversion dictionary. Default: a copy of `MySQLdb.converters.conversions`

compress Enable protocol compression. Default: no compression.

connect_timeout Abort if connect is not completed within given number of seconds. Default: no timeout (?)

named_pipe Use a named pipe (Windows). Default: don't.

init_command Initial command to issue to server upon connection. Default: Nothing.

read_default_file MySQL configuration file to read; see the MySQL documentation for `mysql_options()`.

read_default_group Default group to read; see the MySQL documentation for `mysql_options()`.

cursorclass cursor class that `cursor()` uses, unless overridden. Default: `MySQLdb.cursors.Cursor`.
This must be a keyword parameter.

use_unicode If True, CHAR and VARCHAR and TEXT columns are returned as Unicode strings, using the configured character set. It is best to set the default encoding in the server configuration, or client configuration (read with `read_default_file`). If you change the character set after connecting (MySQL-4.1 and later), you'll need to put the correct character set name in `connection.charset`.

If False, text-like columns are returned as normal strings, but you can always write Unicode strings.

This must be a keyword parameter.

charset If present, the connection character set will be changed to this character set, if they are not equal. Support for changing the character set requires MySQL-4.1 and later server; if the server is too old, `UnsupportedError` will be raised. This option implies `use_unicode=True`, but you can override this with `use_unicode=False`, though you probably shouldn't.

If not present, the default character set is used.

This must be a keyword parameter.

sql_mode If present, the session SQL mode will be set to the given string. For more information on `sql_mode`, see the MySQL documentation. Only available for 4.1 and newer servers.

If not present, the session SQL mode will be unchanged.

This must be a keyword parameter.

ssl This parameter takes a dictionary or mapping, where the keys are parameter names used by the `mysql_ssl_set` MySQL C API call. If this is set, it initiates an SSL connection to the server; if there is no SSL support in the client, an exception is raised. *This must be a keyword parameter.*

apilevel String constant stating the supported DB API level. '2.0'

threadsafety Integer constant stating the level of thread safety the interface supports. This is set to 1, which means: Threads may share the module.

The MySQL protocol can not handle multiple threads using the same connection at once. Some earlier versions of MySQLdb utilized locking to achieve a `threadsafety` of 2. While this is not terribly hard to accomplish using the standard `Cursor` class (which uses `mysql_store_result()`), it is complicated by `SSCursor` (which uses `mysql_use_result()`); with the latter you must ensure all the rows have been read before another query can be executed. It is further complicated by the addition of transactions, since transactions start when a cursor execute a query, but end when `COMMIT` or `ROLLBACK` is executed by the `Connection` object. Two threads simply cannot share a connection while a transaction is in progress, in addition to not being able to share it during query execution. This excessively complicated the code to the point where it just isn't worth it.

The general upshot of this is: Don't share connections between threads. It's really not worth your effort or mine, and in the end, will probably hurt performance, since the MySQL server runs a separate thread for each connection. You can certainly do things like cache connections in a pool, and give those connections to one thread at a time. If you let two threads use a connection simultaneously, the MySQL client library will probably upchuck and die. You have been warned.

charset The character set used by the connection. In MySQL-4.1 and newer, it is possible (but not recommended) to change the connection's character set with an SQL statement. If you do this, you'll also need to change this attribute. Otherwise, you'll get encoding errors.

paramstyle String constant stating the type of parameter marker formatting expected by the interface. Set to 'format' = ANSI C printf format codes, e.g. '...WHERE name=%s'. If a mapping object is used for `conn.execute()`, then the interface actually uses 'pyformat' = Python extended format codes, e.g. '...WHERE name=%(name)s'. However, the API does not presently allow the specification of more than one style in `paramstyle`.

Note that any literal percent signs in the query string passed to `execute()` must be escaped, i.e. `%%`.

Parameter placeholders can **only** be used to insert column values. They can **not** be used for other parts of SQL, such as table names, statements, etc.

conv A dictionary or mapping which controls how types are converted from MySQL to Python and vice versa.

If the key is a MySQL type (from `FIELD_TYPE.*`), then the value can be either:

- a callable object which takes a string argument (the MySQL value), returning a Python value
- a sequence of 2-tuples, where the first value is a combination of flags from `MySQLdb.constants.FLAG`, and the second value is a function as above. The sequence is tested until the flags on the field match those of the first value. If both values are None, then the default conversion is done. Presently this is only used to distinguish TEXT and BLOB columns.

If the key is a Python type or class, then the value is a callable Python object (usually a function) taking two arguments (value to convert, and the conversion dictionary) which converts values of this type to a SQL literal string value.

This is initialized with reasonable defaults for most types. When creating a Connection object, you can pass your own type converter dictionary as a keyword parameter. Otherwise, it uses a copy of `MySQLdb.converters.conversions`. Several non-standard types are returned as strings, which is how MySQL returns all columns. For more details, see the built-in module documentation.

Connection Objects

Connection objects are returned by the `connect()` function.

commit() If the database and the tables support transactions, this commits the current transaction; otherwise this method successfully does nothing.

rollback() If the database and tables support transactions, this rolls back (cancels) the current transaction; otherwise a `NotSupportedError` is raised.

cursor([cursorclass]) MySQL does not support cursors; however, cursors are easily emulated. You can supply an alternative cursor class as an optional parameter. If this is not present, it defaults to the value given when creating the connection object, or the standard `Cursor` class. Also see the additional supplied cursor classes in the usage section.

There are many more methods defined on the connection object which are MySQL-specific. For more information on them, consult the internal documentation using `pydoc`.

Cursor Objects

callproc(procname, args) Calls stored procedure `procname` with the sequence of arguments in `args`. Returns the original arguments. Stored procedure support only works with MySQL-5.0 and newer.

Compatibility note: [PEP-249](#) specifies that if there are OUT or INOUT parameters, the modified values are to be returned. This is not consistently possible with MySQL. Stored procedure arguments must be passed as server variables, and can only be returned with a SELECT statement. Since a stored procedure may return zero or more result sets, it is impossible for MySQLdb to determine if there are result sets to fetch before the modified parameters are accessible.

The parameters are stored in the server as `@_*procname*_*n*`, where `n` is the position of the parameter. I.e., if you `cursor.callproc('foo', (a, b, c))`, the parameters will be accessible by a SELECT statement as `@_foo_0`, `@_foo_1`, and `@_foo_2`.

Compatibility note: It appears that the mere act of executing the CALL statement produces an empty result set, which appears after any result sets which might be generated by the stored procedure. Thus, you will always need to use `nextset()` to advance result sets.

close() Closes the cursor. Future operations raise `ProgrammingError`. If you are using server-side cursors, it is very important to close the cursor when you are done with it and before creating a new one.

info() Returns some information about the last query. Normally you don't need to check this. If there are any MySQL warnings, it will cause a `Warning` to be issued through the Python warning module. By default, `Warning` causes a message to appear on the console. However, it is possible to filter these out or cause `Warning` to be raised as exception. See the MySQL docs for `mysql_info()`, and the Python warning module. (Non-standard)

setinputsizes() Does nothing, successfully.

setoutputsizes() Does nothing, successfully.

nextset() Advances the cursor to the next result set, discarding the remaining rows in the current result set. If there are no additional result sets, it returns `None`; otherwise it returns a true value.

Note that MySQL doesn't support multiple result sets until 4.1.

Some examples

The `connect()` method works nearly the same as with `_mysql`:

```
import MySQLdb
db=MySQLdb.connect (passwd="moonpie", db="thangs")
```

To perform a query, you first need a cursor, and then you can execute queries on it:

```
c=db.cursor()
max_price=5
c.execute("""SELECT spam, eggs, sausage FROM breakfast
          WHERE price < %s""", (max_price,))
```

In this example, `max_price=5` Why, then, use `%s` in the string? Because `MySQLdb` will convert it to a SQL literal value, which is the string `'5'`. When it's finished, the query will actually say, "...WHERE price < 5".

Why the tuple? Because the DB API requires you to pass in any parameters as a sequence. Due to the design of the parser, `(max_price)` is interpreted as using algebraic grouping and simply as `max_price` and not a tuple. Adding a comma, i.e. `(max_price,)` forces it to make a tuple.

And now, the results:

```
>>> c.fetchone()
(3L, 2L, 0L)
```

Quite unlike the `_mysql` example, this returns a single tuple, which is the row, and the values are properly converted by default... except... What's with the L's?

As mentioned earlier, while MySQL's `INTEGER` column translates perfectly into a Python integer, `UNSIGNED INTEGER` could overflow, so these values are converted to Python long integers instead.

If you wanted more rows, you could use `c.fetchmany(n)` or `c.fetchall()`. These do exactly what you think they do. On `c.fetchmany(n)`, the `n` is optional and defaults to `c.arraysize`, which is normally 1. Both of these methods return a sequence of rows, or an empty sequence if there are no more rows. If you use a weird cursor class, the rows themselves might not be tuples.

Note that in contrast to the above, `c.fetchone()` returns `None` when there are no more rows to fetch.

The only other method you are very likely to use is when you have to do a multi-row insert:

```
c.executemany(
    """INSERT INTO breakfast (name, spam, eggs, sausage, price)
    VALUES (%s, %s, %s, %s, %s)""",
    [
        ("Spam and Sausage Lover's Plate", 5, 1, 8, 7.95 ),
        ("Not So Much Spam Plate", 3, 2, 0, 3.95 ),
        ("Don't Wany ANY SPAM! Plate", 0, 4, 3, 5.95 )
    ] )
```

Here we are inserting three rows of five values. Notice that there is a mix of types (strings, ints, floats) though we still only use %s. And also note that we only included format strings for one row. MySQLdb picks those out and duplicates them for each row.

Using and extending

In general, it is probably wise to not directly interact with the DB API except for small applications. Databases, even SQL databases, vary widely in capabilities and may have non-standard features. The DB API does a good job of providing a reasonably portable interface but some methods are non-portable. Specifically, the parameters accepted by `connect()` are completely implementation-dependent.

If you believe your application may need to run on several different databases, the author recommends the following approach, based on personal experience: Write a simplified API for your application which implements the specific queries and operations your application needs to perform. Implement this API as a base class which should have few database dependencies, and then derive a subclass from this which implements the necessary dependencies. In this way, porting your application to a new database should be a relatively simple matter of creating a new subclass, assuming the new database is reasonably standard.

Because MySQLdb's Connection and Cursor objects are written in Python, you can easily derive your own subclasses. There are several Cursor classes in `MySQLdb.cursors`:

BaseCursor The base class for Cursor objects. This does not raise Warnings.

CursorStoreResultMixin Causes the Cursor to use the `mysql_store_result()` function to get the query result. The entire result set is stored on the client side.

CursorUseResultMixin Causes the cursor to use the `mysql_use_result()` function to get the query result. The result set is stored on the server side and is transferred row by row using fetch operations.

CursorTupleRowsMixin Causes the cursor to return rows as a tuple of the column values.

CursorDictRowsMixin

Causes the cursor to return rows as a dictionary, where the keys are column names and the values are column values. Note that if the column names are not unique, i.e., you are selecting from two tables that share column names, some of them will be rewritten as `table.column`. This can be avoided by using the SQL AS keyword. (This is yet-another reason not to use * in SQL queries, particularly where JOIN is involved.)

Cursor The default cursor class. This class is composed of `CursorWarningMixin`, `CursorStoreResultMixin`, `CursorTupleRowsMixin`, and `BaseCursor`, i.e. it raises `Warning`, uses `mysql_store_result()`, and returns rows as tuples.

DictCursor Like `Cursor` except it returns rows as dictionaries.

SSCursor A "server-side" cursor. Like `Cursor` but uses `CursorUseResultMixin`. Use only if you are dealing with potentially large result sets.

SSDictCursor Like `SSCursor` except it returns rows as dictionaries.

Embedded Server

Instead of connecting to a stand-alone server over the network, the embedded server support lets you run a full server right in your Python code or application server.

If you have built MySQLdb with embedded server support, there are two additional functions you will need to make use of:

server_init(args, groups) Initialize embedded server. If this client is not linked against the embedded server library, this function does nothing.

args sequence of command-line arguments

groups sequence of groups to use in defaults files

server_end() Shut down embedded server. If not using an embedded server, this does nothing.

See the MySQL documentation for more information on the embedded server.

Title MySQLdb: a Python interface for MySQL

Author Andy Dustman

Version \$Revision\$

MySQLdb Package

MySQLdb - A DB API v2.0 compatible interface to MySQL.

This package is a wrapper around `_mysql`, which mostly implements the MySQL C API.

`connect()` – connects to server

See the C API specification and the MySQL documentation for more info on other items.

For information on how MySQLdb handles type conversion, see the `MySQLdb.converters` module.

`MySQLdb.Binary` (*x*)

`MySQLdb.Connect` (**args, **kwargs*)
Factory function for connections.`Connection`.

`MySQLdb.Connection` (**args, **kwargs*)
Factory function for connections.`Connection`.

`MySQLdb.Date`
alias of `date`

`MySQLdb.Time`
alias of `time`

`MySQLdb.Timestamp`
alias of `datetime`

`MySQLdb.DateFromTicks` (*ticks*)
Convert UNIX ticks into a date instance.

`MySQLdb.TimeFromTicks` (*ticks*)
Convert UNIX ticks into a time instance.

`MySQLdb.TimestampFromTicks` (*ticks*)
Convert UNIX ticks into a datetime instance.

exception MySQLdb.DataError

Bases: `_mysql_exceptions.DatabaseError`

Exception raised for errors that are due to problems with the processed data like division by zero, numeric value out of range, etc.

exception MySQLdb.DatabaseError

Bases: `_mysql_exceptions.Error`

Exception raised for errors that are related to the database.

exception MySQLdb.Error

Bases: `_mysql_exceptions.MySQLError`

Exception that is the base class of all other error exceptions (not Warning).

exception MySQLdb.IntegrityError

Bases: `_mysql_exceptions.DatabaseError`

Exception raised when the relational integrity of the database is affected, e.g. a foreign key check fails, duplicate key, etc.

exception MySQLdb.InterfaceError

Bases: `_mysql_exceptions.Error`

Exception raised for errors that are related to the database interface rather than the database itself.

exception MySQLdb.InternalError

Bases: `_mysql_exceptions.DatabaseError`

Exception raised when the database encounters an internal error, e.g. the cursor is not valid anymore, the transaction is out of sync, etc.

exception MySQLdb.MySQLError

Bases: `Exception`

Exception related to operation with MySQL.

exception MySQLdb.NotSupportedError

Bases: `_mysql_exceptions.DatabaseError`

Exception raised in case a method or database API was used which is not supported by the database, e.g. requesting a `.rollback()` on a connection that does not support transaction or has transactions turned off.

class MySQLdb.DBAPISet

Bases: `frozenset`

A special type of set for which `A == x` is true if A is a DBAPISet and x is a member of that set.

exception MySQLdb.OperationalError

Bases: `_mysql_exceptions.DatabaseError`

Exception raised for errors that are related to the database's operation and not necessarily under the control of the programmer, e.g. an unexpected disconnect occurs, the data source name is not found, a transaction could not be processed, a memory allocation error occurred during processing, etc.

exception MySQLdb.ProgrammingError

Bases: `_mysql_exceptions.DatabaseError`

Exception raised for programming errors, e.g. table not found or already exists, syntax error in the SQL statement, wrong number of parameters specified, etc.

exception MySQLdb.Warning

Bases: `Warning`, `_mysql_exceptions.MySQLError`

Exception raised for important warnings like data truncations while inserting, etc.

`MySQLdb.connect(*args, **kwargs)`

Factory function for connections.`Connection`.

`MySQLdb.debug()`

Does a `DEBUG_PUSH` with the given string. `mysql_debug()` uses the Fred Fish debug library. To use this function, you must compile the client library to support debugging.

`MySQLdb.escape()`

`escape(obj, dict)` – escape any special characters in object `obj` using mapping `dict` to provide quoting functions for each type. Returns a SQL literal string.

`MySQLdb.escape_dict()`

`escape_sequence(d, dict)` – escape any special characters in dictionary `d` using mapping `dict` to provide quoting functions for each type. Returns a dictionary of escaped items.

`MySQLdb.escape_sequence()`

`escape_sequence(seq, dict)` – escape any special characters in sequence `seq` using mapping `dict` to provide quoting functions for each type. Returns a tuple of escaped items.

`MySQLdb.escape_string()`

`escape_string(s)` – quote any SQL-interpreted characters in string `s`.

Use `connection.escape_string(s)`, if you use it at all. `_mysql.escape_string(s)` cannot handle character sets. You are probably better off using `connection.escape(o)` instead, since it will escape entire sequences as well as strings.

`MySQLdb.get_client_info()`

`get_client_info()` – Returns a string that represents the client library version.

`MySQLdb.string_literal()`

`string_literal(obj)` – converts object `obj` into a SQL string literal. This means, any special SQL characters are escaped, and it is enclosed within single quotes. In other words, it performs:

```
““%s”” % escape_string(str(obj))
```

Use `connection.string_literal(obj)`, if you use it at all. `_mysql.string_literal(obj)` cannot handle character sets.

connections Module

This module implements connections for MySQLdb. Presently there is only one class: `Connection`. Others are unlikely. However, you might want to make your own subclasses. In most cases, you will probably override `Connection.default_cursor` with a non-standard `Cursor` class.

class `MySQLdb.connections.Connection(*args, **kwargs)`

Bases: `_mysql.connection`

MySQL Database Connection Object

exception `DataError`

Bases: `_mysql_exceptions.DatabaseError`

Exception raised for errors that are due to problems with the processed data like division by zero, numeric value out of range, etc.

exception `Connection.DatabaseError`

Bases: `_mysql_exceptions.Error`

Exception raised for errors that are related to the database.

exception `Connection.Error`

Bases: `_mysql_exceptions.MySQLError`

Exception that is the base class of all other error exceptions (not Warning).

exception `Connection.IntegrityError`

Bases: `_mysql_exceptions.DatabaseError`

Exception raised when the relational integrity of the database is affected, e.g. a foreign key check fails, duplicate key, etc.

exception `Connection.InterfaceError`

Bases: `_mysql_exceptions.Error`

Exception raised for errors that are related to the database interface rather than the database itself.

exception `Connection.InternalError`

Bases: `_mysql_exceptions.DatabaseError`

Exception raised when the database encounters an internal error, e.g. the cursor is not valid anymore, the transaction is out of sync, etc.

exception `Connection.NotSupportedError`

Bases: `_mysql_exceptions.DatabaseError`

Exception raised in case a method or database API was used which is not supported by the database, e.g. requesting a `.rollback()` on a connection that does not support transaction or has transactions turned off.

exception `Connection.OperationalError`

Bases: `_mysql_exceptions.DatabaseError`

Exception raised for errors that are related to the database's operation and not necessarily under the control of the programmer, e.g. an unexpected disconnect occurs, the data source name is not found, a transaction could not be processed, a memory allocation error occurred during processing, etc.

exception `Connection.ProgrammingError`

Bases: `_mysql_exceptions.DatabaseError`

Exception raised for programming errors, e.g. table not found or already exists, syntax error in the SQL statement, wrong number of parameters specified, etc.

exception `Connection.Warning`

Bases: `Warning, _mysql_exceptions.MySQLError`

Exception raised for important warnings like data truncations while inserting, etc.

`Connection.autocommit` (*on*)

`Connection.begin()`

Explicitly begin a connection. Non-standard. DEPRECATED: Will be removed in 1.3. Use an SQL BEGIN statement instead.

`Connection.cursor` (*cursorclass=None*)

Create a cursor on which queries may be performed. The optional `cursorclass` parameter is used to create the Cursor. By default, `self.cursorclass=cursors.Cursor` is used.

`Connection.default_cursor`

alias of `Cursor`

`Connection.errorhandler` (*connection, cursor, errorclass, errorvalue*)

If `cursor` is not `None`, (`errorclass, errorvalue`) is appended to `cursor.messages`; otherwise it is appended to `connection.messages`. Then `errorclass` is raised with `errorvalue` as the value.

You can override this with your own error handler by assigning it to the instance.

`Connection.literal(o)`

If `o` is a single object, returns an SQL literal as a string. If `o` is a non-string sequence, the items of the sequence are converted and returned as a sequence.

Non-standard. For internal use; do not use this in your applications.

`Connection.query(query)`

`Connection.set_character_set(charset)`

Set the connection character set to `charset`. The character set can only be changed in MySQL-4.1 and newer. If you try to change the character set from the current value in an older version, `NotSupportedError` will be raised.

`Connection.set_sql_mode(sql_mode)`

Set the connection `sql_mode`. See MySQL documentation for legal values.

`Connection.show_warnings()`

Return detailed information about warnings as a sequence of tuples of (Level, Code, Message). This is only supported in MySQL-4.1 and up. If your server is an earlier version, an empty sequence is returned.

`Connection.waiter = None`

converters Module

MySQLdb type conversion module

This module handles all the type conversions for MySQL. If the default type conversions aren't what you need, you can make your own. The dictionary conversions maps some kind of type to a conversion function which returns the corresponding value:

Key: `FIELD_TYPE.*` (from `MySQLdb.constants`)

Conversion function:

Arguments: string

Returns: Python object

Key: Python type object (from types) or class

Conversion function:

Arguments: Python object of indicated type or class AND conversion dictionary

Returns: SQL literal value

Notes: Most conversion functions can ignore the dictionary, but it is a required parameter. It is necessary for converting things like sequences and instances.

Don't modify conversions if you can avoid it. Instead, make copies (with the `copy()` method), modify the copies, and then pass them to `MySQL.connect()`.

`MySQLdb.converters.Bool2Str(s, d)`

`MySQLdb.converters.Float2Str(o, d)`

`MySQLdb.converters.None2NULL(o, d)`

Convert None to NULL.

`MySQLdb.converters.Set2Str(s, d)`

`MySQLdb.converters.Str2Set(s)`

MySQLdb.converters.**Thing2Literal** (*o*, *d*)

Convert something into a SQL string literal. If using MySQL-3.23 or newer, `string_literal()` is a method of the `_mysql.MYSQL` object, and this function will be overridden with that method when the connection is created.

MySQLdb.converters.**Thing2Str** (*s*, *d*)

Convert something into a string via `str()`.

MySQLdb.converters.**Unicode2Str** (*s*, *d*)

Convert a unicode object to a string using the default encoding. This is only used as a placeholder for the real function, which is connection-dependent.

MySQLdb.converters.**array2Str** (*o*, *d*)

MySQLdb.converters.**char_array** (*s*)

MySQLdb.converters.**quote_tuple** (*t*, *d*)

cursors Module

MySQLdb Cursors

This module implements Cursors of various types for MySQLdb. By default, MySQLdb uses the Cursor class.

class MySQLdb.cursors.**Cursor** (*connection*)

Bases: MySQLdb.cursors.CursorStoreResultMixin, MySQLdb.cursors.CursorTupleRowsMixin, MySQLdb.cursors.BaseCursor

This is the standard Cursor class that returns rows as tuples and stores the result set in the client.

times Module

times module

This module provides some Date and Time classes for dealing with MySQL data.

Use Python datetime module to handle date and time columns.

MySQLdb.times.**DateFromTicks** (*ticks*)

Convert UNIX ticks into a date instance.

MySQLdb.times.**DateTime2literal** (*d*, *c*)

Format a DateTime object as an ISO timestamp.

MySQLdb.times.**DateTimeDelta2literal** (*d*, *c*)

Format a DateTimeDelta object as a time.

MySQLdb.times.**DateTime_or_None** (*s*)

MySQLdb.times.**Date_or_None** (*s*)

MySQLdb.times.**TimeDelta_or_None** (*s*)

MySQLdb.times.**TimeFromTicks** (*ticks*)

Convert UNIX ticks into a time instance.

MySQLdb.times.**Time_or_None** (*s*)

MySQLdb.times.**TimestampFromTicks** (*ticks*)

Convert UNIX ticks into a datetime instance.

MySQLdb.times.**format_TIMEDELTA** (*v*)

MySQLdb.times.**format_TIMESTAMP** (*d*)

MySQLdb.times.**mysql_timestamp_converter** (*s*)
Convert a MySQL TIMESTAMP to a Timestamp object.

Subpackages

constants Package

constants Package

CLIENT Module

MySQL CLIENT constants

These constants are used when creating the connection. Use bitwise-OR (`|`) to combine options together, and pass them as the `client_flags` parameter to `MySQLdb.Connection`. For more information on these flags, see the MySQL C API documentation for `mysql_real_connect()`.

CR Module

MySQL Connection Errors

Nearly all of these raise `OperationalError`. `COMMANDS_OUT_OF_SYNC` raises `ProgrammingError`.

ER Module

MySQL ER Constants

These constants are error codes for the bulk of the error conditions that may occur.

FIELD_TYPE Module

MySQL FIELD_TYPE Constants

These constants represent the various column (field) types that are supported by MySQL.

FLAG Module

MySQL FLAG Constants

These flags are used along with the `FIELD_TYPE` to indicate various properties of columns in a result set.

REFRESH Module

MySQL REFRESH Constants

These constants seem to mostly deal with things internal to the MySQL server. Forget you saw this.

MySQLdb Frequently Asked Questions

Contents

- *MySQLdb Frequently Asked Questions*
 - *Build Errors*
 - *ImportError*
 - *My data disappeared! (or won't go away!)*
 - *Other Errors*
 - *Other Resources*

Build Errors

ld: fatal: library -lmysqlclient_r: not found

mysqlclient_r is the thread-safe library. It's not available on all platforms, or all installations, apparently. You'll need to reconfigure site.cfg (in MySQLdb-1.2.1 and newer) to have threadsafe = False.

mysql.h: No such file or directory

This almost always mean you don't have development packages installed. On some systems, C headers for various things (like MySQL) are distributed as a separate package. You'll need to figure out what that is and install it, but often the name ends with -devel.

Another possibility: Some older versions of mysql_config behave oddly and may throw quotes around some of the path names, which confused MySQLdb-1.2.0. 1.2.1 works around these problems. If you see things like -I'/usr/local/include/mysql' in your compile command, that's probably the issue, but it shouldn't happen any more.

ImportError

ImportError: No module named `_mysql`

If you see this, it's likely you did some wrong when installing MySQLdb; re-read (or read) README. `_mysql` is the low-level C module that interfaces with the MySQL client library.

Various versions of MySQLdb in the past have had build issues on “weird” platforms; “weird” in this case means “not Linux”, though generally there aren't problems on Unix/POSIX platforms, including BSDs and Mac OS X. Windows has been more problematic, in part because there is no `mysql_config` available in the Windows installation of MySQL. 1.2.1 solves most, if not all, of these problems, but you will still have to edit a configuration file so that the setup knows where to find MySQL and what libraries to include.

ImportError: libmysqlclient_r.so.14: cannot open shared object file: No such file or directory

The number after `.so` may vary, but this means you have a version of MySQLdb compiled against one version of MySQL, and are now trying to run it against a different version. The shared library version tends to change between major releases.

Solution: Rebuilt MySQLdb, or get the matching version of MySQL.

Another thing that can cause this: The MySQL libraries may not be on your system path.

Solutions:

- set the `LD_LIBRARY_PATH` environment variable so that it includes the path to the MySQL libraries.
- set `static=True` in `site.cfg` for static linking
- reconfigure your system so that the MySQL libraries are on the default loader path. In Linux, you edit `/etc/ld.so.conf` and run `ldconfig`. For Solaris, see [Linker and Libraries Guide](#).

ImportError: ld.so.1: python: fatal: libmtmalloc.so.1: DF_1_NOOPEN tagged object may not be dlopen()'ed

This is a weird one from Solaris. What does it mean? I have no idea. However, things like this can happen if there is some sort of a compiler or environment mismatch between Python and MySQL. For example, on some commercial systems, you might have some code compiled with their own compiler, and other things compiled with GCC. They don't always mesh together. One way to encounter this is by getting binary packages from different vendors.

Solution: Rebuild Python or MySQL (or maybe both) from source.

ImportError: dlopen(./_mysql.so, 2): Symbol not found: `_sprintf$LDLBLStub` Referenced from: `./_mysql.so` Expected in: dynamic lookup

This is one from Mac OS X. It seems to have been a compiler mismatch, but this time between two different versions of GCC. It seems nearly every major release of GCC changes the ABI in some way, so linking code compiled with GCC-3.3 and GCC-4.0, for example, can be problematic.

My data disappeared! (or won't go away!)

Starting with 1.2.0, MySQLdb disables autocommit by default, as required by the DB-API standard (PEP-249). If you are using InnoDB tables or some other type of transactional table type, you'll need to do `connection.commit()` before closing the connection, or else none of your changes will be written to the database.

Conversely, you can also use `connection.rollback()` to throw away any changes you've made since the last commit.

Important note: Some SQL statements – specifically DDL statements like `CREATE TABLE` – are non-transactional, so they can't be rolled back, and they cause pending transactions to commit.

Other Errors

OperationalError: (1251, 'Client does not support authentication protocol requested by server; consider upgrading MySQL client')

This means your server and client libraries are not the same version. More specifically, it probably means you have a 4.1 or newer server and 4.0 or older client. You can either upgrade the client side, or try some of the workarounds in [Password Hashing as of MySQL 4.1](#).

Other Resources

- [Help forum](#). Please search before posting.
- [Google](#)
- [READ README!](#)
- [Read the User's Guide](#)
- [Read PEP-249](#)

CHAPTER 4

Indices and tables

- `genindex`
- `modindex`
- `search`

m

MySQLdb, 13
MySQLdb.connections, 15
MySQLdb.constants, 19
MySQLdb.constants.CLIENT, 19
MySQLdb.constants.CR, 19
MySQLdb.constants.ER, 19
MySQLdb.constants.FIELD_TYPE, 19
MySQLdb.constants.FLAG, 19
MySQLdb.constants.REFRESH, 19
MySQLdb.converters, 17
MySQLdb.cursors, 18
MySQLdb.times, 18

A

array2Str() (in module MySQLdb.converters), 18
autocommit() (MySQLdb.connections.Connection method), 16

B

begin() (MySQLdb.connections.Connection method), 16
Binary() (in module MySQLdb), 13
Bool2Str() (in module MySQLdb.converters), 17

C

char_array() (in module MySQLdb.converters), 18
Connect() (in module MySQLdb), 13
connect() (in module MySQLdb), 15
Connection (class in MySQLdb.connections), 15
Connection() (in module MySQLdb), 13
Connection.DatabaseError, 15
Connection.DataError, 15
Connection.Error, 15
Connection.IntegrityError, 16
Connection.InterfaceError, 16
Connection.InternalError, 16
Connection.NotSupportedError, 16
Connection.OperationalError, 16
Connection.ProgrammingError, 16
Connection.Warning, 16
Cursor (class in MySQLdb.cursors), 18
cursor() (MySQLdb.connections.Connection method), 16

D

DatabaseError, 14
DataError, 13
Date (in module MySQLdb), 13
Date_or_None() (in module MySQLdb.times), 18
DateFromTicks() (in module MySQLdb), 13
DateFromTicks() (in module MySQLdb.times), 18
DateTime2literal() (in module MySQLdb.times), 18
Date_time_or_None() (in module MySQLdb.times), 18
DateTimeDelta2literal() (in module MySQLdb.times), 18

DBAPISet (class in MySQLdb), 14
debug() (in module MySQLdb), 15
default_cursor (MySQLdb.connections.Connection attribute), 16

E

Error, 14
errorhandler() (MySQLdb.connections.Connection method), 16
escape() (in module MySQLdb), 15
escape_dict() (in module MySQLdb), 15
escape_sequence() (in module MySQLdb), 15
escape_string() (in module MySQLdb), 15

F

Float2Str() (in module MySQLdb.converters), 17
format_TIMEDELTA() (in module MySQLdb.times), 18
format_TIMESTAMP() (in module MySQLdb.times), 19

G

get_client_info() (in module MySQLdb), 15

I

IntegrityError, 14
InterfaceError, 14
InternalError, 14

L

literal() (MySQLdb.connections.Connection method), 16

M

mysql_timestamp_converter() (in module MySQLdb.times), 19
MySQLdb (module), 13
MySQLdb.connections (module), 15
MySQLdb.constants (module), 19
MySQLdb.constants.CLIENT (module), 19
MySQLdb.constants.CR (module), 19
MySQLdb.constants.ER (module), 19

MySQLdb.constants.FIELD_TYPE (module), 19
MySQLdb.constants.FLAG (module), 19
MySQLdb.constants.REFRESH (module), 19
MySQLdb.converters (module), 17
MySQLdb.cursors (module), 18
MySQLdb.times (module), 18
MySQLError, 14

N

None2NULL() (in module MySQLdb.converters), 17
NotSupportedError, 14

O

OperationalError, 14

P

ProgrammingError, 14

Q

query() (MySQLdb.connections.Connection method), 17
quote_tuple() (in module MySQLdb.converters), 18

S

Set2Str() (in module MySQLdb.converters), 17
set_character_set() (MySQLdb.connections.Connection method), 17
set_sql_mode() (MySQLdb.connections.Connection method), 17
show_warnings() (MySQLdb.connections.Connection method), 17
Str2Set() (in module MySQLdb.converters), 17
string_literal() (in module MySQLdb), 15

T

Thing2Literal() (in module MySQLdb.converters), 17
Thing2Str() (in module MySQLdb.converters), 18
Time (in module MySQLdb), 13
Time_or_None() (in module MySQLdb.times), 18
TimeDelta_or_None() (in module MySQLdb.times), 18
TimeFromTicks() (in module MySQLdb), 13
TimeFromTicks() (in module MySQLdb.times), 18
Timestamp (in module MySQLdb), 13
TimestampFromTicks() (in module MySQLdb), 13
TimestampFromTicks() (in module MySQLdb.times), 18

U

Unicode2Str() (in module MySQLdb.converters), 18

W

waiter (MySQLdb.connections.Connection attribute), 17
Warning, 14