

---

# **OpenXC for Python Documentation**

*Release 0.13.0*

**Christopher Peplin**

**Jul 27, 2017**



---

## Contents

---

<b>1</b>	<b>Installation</b>	<b>3</b>
<b>2</b>	<b>Command Line Tools</b>	<b>5</b>
<b>3</b>	<b>Example Code</b>	<b>15</b>
<b>4</b>	<b>Vehicle Data API Reference</b>	<b>17</b>
<b>5</b>	<b>Contributing</b>	<b>31</b>
	<b>Python Module Index</b>	<b>33</b>





**Version** 0.13.0

**Web** <http://openxcplatform.com>

**Download** <http://pypi.python.org/pypi/openxc/>

**Documentation** <http://python.openxcplatform.com>

**Source** <http://github.com/openxc/openxc-python/>

The OpenXC Python library (for Python 2.7) provides an interface to vehicle data from the OpenXC Platform. The primary platform for OpenXC applications is Android, but for prototyping and testing, often it is preferable to use a low-overhead environment like Python when developing.

In addition to a port of the Android library API, the package also contains a number of command-line tools for connecting to the vehicle interface and manipulating previously recorded vehicle data.

This Python package works with Python 2.7. Unfortunately we had to drop support for Python 3 when we added the protobuf library as a dependency.

For general documentation on the OpenXC platform, visit the main [OpenXC site](#).



### Install Python and Pip

This library (obviously) requires a Python language runtime - the OpenXC library currently works with Python 2.7, but not Python 3.x.

- **Mac OS X and Linux**

Mac OS X and most Linux distributions already have a compatible Python installed. Run `python --version` from a terminal to check - you need a 2.7.x version, such as 2.7.8.

- **Windows**

1. Download and run the [Python 2.7.x MSI installer](#). Make sure to select the option to Add `python.exe` to Path.
2. Add the Python Scripts directory your PATH: `PATH=%PATH%;c:\Python27\Scripts`. If you aren't sure how to edit your PATH, see [this guide for all versions of Windows](#). Log out and back in for the change to take effect.
3. Install [pip](#), a Python package manager by saving the `get-pip.py` script to a file and running it from a terminal.

- **Cygwin**

From the `setup.exe` package list, select the `python` and `python-setuptools` packages. Then, inside Cygwin install `pip` using `easy_install`:

```
$ easy_install pip
```

### Install the openxc Package

You can install or upgrade the OpenXC library from the Python Package Index (PyPI) with `pip` at the command line:

```
$ [sudo] pip install -U openxc
```

## USB Backend

If you intend to use the library to connect to a vehicle interface via USB, you must also install a native USB backend - `libusb-1.0` is the recommended library.

- **Mac OS X**

First install [Homebrew](#), then run:

```
$ brew install libusb
```

- **Ubuntu**

`libusb` is available in the main repository:

```
$ sudo apt-get install libusb-1.0-0
```

- **Arch Linux**

Install `libusb` using `pacman`:

```
$ sudo pacman -S libusb
```

- **Windows**

Download and install the [OpenXC VI USB driver](#). You must install the driver manually through the Device Manager while the VI is plugged in and on - either running the emulator firmware so it never turns off, or plugged into a real car.

- **Cygwin**

Install the VI USB driver as in a regular Windows installation.

If you get the error `Skipping USB device: [Errno 88] Operation not supported or unimplemented on this platform` when you run any of the OpenXC Python tools, make sure you **do not** have the `libusb` Cygwin package installed - that is explicitly not compatible.

## Using the development version

You can clone the repository and install the development version like so:

```
$ git clone https://github.com/openxc/openxc-python
$ cd openxc-python
$ pip install -e .
```

Any time you update the clone of the Git repository, all of the Python tools will be updated too.



---

### Command Line Tools

---

With all tools, the library will attempt to autodetect the payload format being used by the VI. If it's not sending any messages this is not possible, so you may need to provide the current payload format explicitly with the `--format` flag. For example, here's a command to change the passthrough status of bus 1, but with the payload format for the request explicitly set the protocol buffers:

```
$ openxc-control set --bus 1 --passthrough --format protobuf
```

The following links describe the available `openxc-python` commands.

#### **openxc-generate-firmware-code - configure CAN messages, signals and buses**

The [OpenXC vehicle interface firmware](#) uses a JSON-formatted configuration file to set up CAN messages, signals and buses. The configuration options and many examples are included with the [VI firmware docs](#). The configuration file is used to generate C++ that is compiled with the open source firmware.

The OpenXC Python library contains a command line tool, `openxc-generate-firmware-code`, that can parse VI configuration files and generate a proper C++ implementation to compile the VI firmware.

Once you've created a VI configuration file, run the `openxc-generate-firmware-code` tool to create an implementation of the functions in the VI's `signals.h`. In this example, the configuration is in the file `mycar.json`.

```
$ openxc-generate-firmware-code --message-set mycar.json > signals.cpp
```

#### **openxc-control - write messages to the VI and change its settings**

`openxc-control` is a command-line tool that can send control messages to an attached vehicle interface.

### Basic use

#### version

Print the current firmware version and firmware description of the attached CAN translator:

```
$ openxc-control version
```

An example response is `v7.2.1 (default)`, where the `default` firmware description can be modified in the JSON file via the "name" entry. The first example in [Low-level CAN Features](#) would return a value of `passthrough`.

#### id

Print the unique ID of the VI, if it has one. This is often the MAC address of the Bluetooth module.

```
$ openxc-control id
```

#### platform

Print the hardware platform of the vehicle interface.

```
$ openxc-control platform
```

Supported platforms include `CHIPKIT`, `BLUEBOARD`, `FORDBOARD`, `CROSSCHASM_C5`, `CROSSCHASM_C5_BT`, `CROSSCHASM_C5_BLE`, and `CROSSCHASM_C5_CELLULAR`

#### set

Modify the run-time configuration of the VI. Currently, you can change the acceptance filter (AF) bypass status, passthrough CAN message output, and the payload format used from the OpenXC message format.

Enable and disable CAN AF bypass for a bus:

```
$ openxc-control set --bus 1 --af-bypass
$ openxc-control set --bus 1 --no-af-bypass
```

Enable and disable passthrough of CAN messages to the output interface (e.g. USB or Bluetooth):

```
$ openxc-control set --bus 1 --passthrough
$ openxc-control set --bus 1 --no-passthrough
```

Change the payload format to Protocol Buffers, then back to JSON:

```
$ openxc-control set --new-payload-format json
$ openxc-control set --new-payload-format protobuf
```

Change the time for the RTC unit on the C5 devices:

```
$ openxc-control set --time 1461545558
```

Set the host and port for the C5 Cellular device

```
$ openxc-control set --network-host www.server.com --port 80
```

This will return true when successful. If network-host is supplied, but not port, port will default to 80.

## write

Send a write request to the VI, either for a simple vehicle message write (to be translated by the VI to a CAN message), or a raw CAN message.

To write a simple vehicle message, the `--name` and `--value` parameters are required. The `--event` parameter is optional.

```
$ openxc-control write --name turn_signal_status --value left
```

To write a CAN messages, the `--bus`, `--id` and `--data` parameters are required. `data` should be a hex string.

```
$ openxc-control write --bus 1 --id 0x124 --data 0x0234567812345678
```

A CAN message with an ID greater than can be represented with 11 bits will automatically be sent using the extended frame format. If you want to send a message with a lower ID using the extended frame format, you can use the `--frame-format` flag:

```
$ openxc-control write --bus 1 --id 0x124 --data 0x0234567812345678 --frame-format_
↳extended
```

---

**Note:** The vehicle interface must be running firmware that supports CAN writes, and must allow writing the specific message that you request with `openxc-control`.

---

## sd\_mount\_status

This queries the device to see if the SD card is mounted correctly.

```
$ openxc-control sd_mount_status
```

This will return 'True' if the SD card is available for writing. Otherwise, it will return 'False'.

## Command-line options

An overview of all possible command line options can be found via `--help`.

## openxc-dashboard - an ncurses UI to view data received from a VI

**openxc-dashboard** is a command-line tool that displays the current values of all OpenXC messages simultaneously. The dashboard uses `curses` to draw a basic GUI to the terminal.

Only OpenXC messages in the official public set will be displayed. Unofficial messages may be received, but will not appear on the dashboard.

For each message type, the dashboard displays:

- Message name

- Last received value
- A simple graph of the current value and the range seen
- Total number received since the program started
- A rough calculation of the frequency the message is sent in Hz

If the terminal window is not wide enough, only a subset of this data will be displayed. The wider you make the window, the more you'll see. The same goes for the list of messages - if the window is not tall enough, the message list will be truncated.

The dashboard also displays some overall summary data:

- Total messages received of any type
- Total amount of data received over the source interface
- Average data rate since the program started

If the number of message types is large, you can scroll up and down the list with the arrow keys or Page Up / Page Down keys.

This is a screenshot of the dashboard showing all possible columns of data.

```
accelerator_pedal_position  --===== 29.50 % Messages: 2204 Freq. (Hz): 60
brake_pedal_status         ----- False Messages: 6 Freq. (Hz): 0
engine_speed               --===== 2405.25 rotations / m Messages: 151 Freq. (Hz): 4
fuel_consumed_since_restart ----- 4.54 L Messages: 376 Freq. (Hz): 10
fuel_level                 --===== 10.87 % Messages: 1790 Freq. (Hz): 49
odometer                   ----- 25112.27 m Messages: 376 Freq. (Hz): 10
steering_wheel_angle      ----- 85.30 deg Messages: 241 Freq. (Hz): 6
torque_at_transmission     ----- 333.00 Nm Messages: 2211 Freq. (Hz): 61
transmission_gear_position ----- second Messages: 4 Freq. (Hz): 0
vehicle_speed              ----- 18.89 km / h Messages: 150 Freq. (Hz): 4

Message count: 7509 (0 corrupted)
Total received: 542.8KB
Data Rate: 15.0KB
```

This screenshot shows the dashboard displaying raw CAN messages (the vehicle interface must have CAN passthrough enabled).

```
Bus ? : 0x10a 0x4000000000000000 Messages: 10 Freq. (Hz): 0
Bus ? : 0x200 0x2712280b280b0000 Messages: 596 Freq. (Hz): 56
Bus ? : 0x201 0x0a53000027100000 Messages: 530 Freq. (Hz): 49
Bus ? : 0x211 0xffffe0000004800000 Messages: 481 Freq. (Hz): 45
Bus ? : 0x215 0x2710271027102710 Messages: 1060 Freq. (Hz): 99
Bus ? : 0x217 0x000a000360006400 Messages: 168 Freq. (Hz): 15
Bus ? : 0x230 0xdd00000000000000 Messages: 1007 Freq. (Hz): 94
Bus ? : 0x250 0x7e9e394a00000228 Messages: 170 Freq. (Hz): 15
Bus ? : 0x255 0x2000805d7f9c0000 Messages: 134 Freq. (Hz): 12
Bus ? : 0x265 0x400000410b000000 Messages: 10 Freq. (Hz): 0
Bus ? : 0x340 0x0a18000000000000 Messages: 84 Freq. (Hz): 7
Bus ? : 0x350 0x0000000000000000 Messages: 86 Freq. (Hz): 8
Bus ? : 0x351 0x000006000c020000 Messages: 13 Freq. (Hz): 1
Bus ? : 0x352 0x000000323fff0000 Messages: 12 Freq. (Hz): 1
Bus ? : 0x41 0x0061000000000000 Messages: 939 Freq. (Hz): 88
Bus ? : 0x415 0x8800200000000071 Messages: 155 Freq. (Hz): 14
Bus ? : 0x417 0x0000000000000000 Messages: 402 Freq. (Hz): 37

Message count: 10830 (0 corrupted)
Total received: 779.0KB
Data Rate: 73.2KB
```

## Basic use

Open the dashboard:

```
$ openxc-dashboard
```

Use a custom USB device:

```
$ openxc-dashboard --usb-vendor 4424
```

Use a a vehicle interface connected via serial instead of USB:

```
$ openxc-dashboard --serial --serial-device /dev/ttyUSB1
```

The `serial-device` option is only required if the virtual COM port is different than the default `/dev/ttyUSB0`.

Play back a trace file in real-time:

```
$ openxc-dashboard --trace monday-trace.json
```

## Command-line options

An overview of all possible command line options can be found via `--help`.

## openxc-diag - Send and receive OBD-II diagnostic messages

**openxc-diag** is a command-line tool for adding new recurring or one-time diagnostic message requests through a vehicle interface.

### Perform a single diagnostic request

This example will add a new one-time diagnostic request - it will be sent once, and any responses will be printed to the terminal via stdout. The `--message` and `--mode` options are required. This particular request sends a functional broadcast request (ID `0x7df`) for the mode 3 service, to store a “freeze frame”. See the Unified Diagnostics Service and On-Board Diagnostics standards for more information on valid modes.

The `bus` option is not required; the VI will use its default configured CAN bus if one is not specified.

```
$ openxc-diag add --message 0x7df --mode 0x3
```

---

**Note:** The vehicle interface must be running firmware that supports diagnostic requests.

---

### Add a recurring diagnostic request

This example will register a new recurring diagnostic request with the vehicle interface. It will request the OBD-II engine speed parameter at 1Hz, so if you subsequently run the `openxc-dump` command you will be able to read the responses.

```
$ openxc-diag add --message 0x7df --mode 0x1 --pid 0xc --frequency 1
```

## Cancel an existing recurring diagnostic request

This example will cancel the recurring diagnostic request we added in the previous example. Deleting requests also uses the combination of bus, ID, mode and PID to identify a request.

```
$ openxc-diag cancel --message 0x7df --mode 0x1 --pid 0xc
```

## Cancelling a non-recurring diagnostic request

If you're wondering why there are no examples of canceling an existing request that is not recurring, it's because they either complete or timeout within 1 second, so there's no reason to try and modify them.

## Command-line options

A description overview of all possible command line options can be found via `--help`.

## openxc-dump - view the unfiltered stream of data from a VI

**openxc-dump** is a command-line tool to view the raw data stream from an attached vehicle interface or trace file. It attempts to read OpenXC messages from the interface specified at the command line (USB, Bluetooth (Linux), serial a trace file) and prints each message received to `stdout`.

### Basic use

View everything:

```
$ openxc-dump
```

View only a particular message:

```
$ openxc-dump | grep steering_wheel_angle
```

Use a custom USB device:

```
$ openxc-dump --usb-vendor 4424
```

Use a vehicle interface connected via serial instead of USB:

```
$ openxc-dump --serial --serial-device /dev/ttyUSB1
```

The `serial-device` option is only required if the virtual COM port is different than the default `/dev/ttyUSB0`.

Use a VI with a Bluetooth adapter (this is only supported when connecting from Linux at the moment):

```
$ openxc-dump --bluetooth
```

This will scan and discover for an OpenXC VI, connect and start streaming the data. If you know the MAC address, you can also provide that explicitly with the `--bluetooth-address` flag.

Play back a trace file in real-time:

```
$ openxc-dump --trace monday-trace.json
```

## Command-line options

An overview of all possible command line options can be found via `--help`.

## Traces

You can record a trace of JSON messages from the CAN reader with `openxc-dump`. Simply redirect the output to a file, and you've got your trace. This can be used directly by the `openxc-android` library, for example.

```
$ openxc-dump > vehicle-data.trace
```

## openxc-gps - convert a vehicle data stream to GPX format

**openxc-gps** is a command-line tool to convert a raw OpenXC data stream that includes GPS information (namely latitude and longitude) into one of a few popular formats for GPS traces. The output file is printed to `stdout`, so the output must be redirected to save it to a file.

The only format currently supported is `.gpx`, which can be imported by Google Earth, the Google Maps API and many other popular tools.

### Basic use

Convert a previously recorded OpenXC JSON trace file to GPX:

```
$ openxc-gps --trace trace.json > trace.gpx
```

Convert a real-time stream from a USB vehicle interface to GPX in real-time (using all defaults, and printing to `stdout`):

```
$ openxc-gps
```

## Command-line options

An overview of all possible command line options can be found via `--help`.

## openxc-obd2scanner - detect OBD-II PIDs supported by a vehicle

**openxc-obd2scanner** is a simple and quick tool to check what OBD-II PIDs a vehicle actually supports. It sequentially scans all valid PIDs and prints the responses to `stdout`.

### Basic use

```
$ openxc-obd2scanner
```

## Command-line options

A description overview of all possible command line options can be found via `--help`.

## **openxc-scanner - scanner for determining support diagnostic requests**

**openxc-scanner** is a rudimentary diagnostic scanner that can give you a high level view of the what message IDs are used by modules on a vehicle network and to which diagnostics services they (potentially) respond.

When you run `openxc-scanner`, it will send a Tester Present diagnostic request to all possible 11-bit CAN message IDs (or arbitration IDs). For each module that responds, it then sends a blank request for each possible diagnostic service to the module's arbitration ID. Finally, for each service that responded, it fuzzes the payload field to see if anything interesting can happen.

Make sure you do not run this tool while operating your car. The Tester Present message can put modules into diagnostic modes that aren't safe for driving, or other unexpected behaviors may occur (e.g. your powered driver's seat may reset the position, or the powered trunk may open up).

## Basic use

There's not much to it, just run it and view the results. It may take a number of minutes to complete the scan if there are many active modules.

```
$ openxc-scanner
```

## Scanning a specific message ID

If you wish to scan only a single message ID, you can skip right to it:

```
$ openxc-scanner --message 0x7e0
```

## Command-line options

A description overview of all possible command line options can be found via `--help`.

## **openxc-trace-split - split merged OpenXC trace files into separate trips**

**openxc-trace-split** is a command-line tool to re-split a collection of previously recorded OpenXC trace files by different units of time.

Often, trace files are recorded into arbitrarily sized chunks, e.g. a new trace file every hour. The trace files are often most useful if grouped into more logical chunks e.g. one "trip" in the vehicle.

This tool accepts a list of JSON trace files as arguments, reads them into memory and sorts by time, then re-splits the file into new output files based on the requested split unit. The unit is "trips" by default, which looks for gaps of 5 minutes or more in the trace files to demarcate the trips.



The output files are named based on the timestamp of the first record recorded in the segment.

## Basic use

Re-combine two trace files and re-split by trip (the default split unit) instead of the original day splits:

```
$ openxc-trace-split monday.json tuesday.json
```

Re-combine two trace files and re-split by hour instead of the original day splits:

```
$ openxc-trace-split --split hour monday.json tuesday.json
```

Re-split an entire directory of JSON files by trip

```
$ openxc-trace-split *.json
```

## Command-line options

A quick overview of all possible command line options can be found via `--help`.

**-s, --split** <unit>

Change the time unit used to split trace files - choices are `day`, `hour` and `trip`. The default unit is `trip`, which looks for large gaps of time in the trace files where no data was recorded.



## CHAPTER 3

---

### Example Code

---

Read an unfiltered stream of OpenXC messages from a USB vehicle interface:

```
from openxc.interface import UsbVehicleInterface

def receive(message, **kwargs):
    # this callback will receive each message received as a dict
    print(message['name'])

vi = UsbVehicleInterface(callback=receive)
vi.start()
# This will block until the connection dies or you exit the program
vi.join()
```

If you want to connect to a Bluetooth interface (currently only supported in Linux), just replace `UsbVehicleInterface` with `BluetoothVehicleInterface`.

The base `VehicleInterface` classes all implement the Controller API, which also supports writing CAN messages, creating diagnostic requests and sending configuration commands to the VI.

For example, to create a diagnostic request and wait for responses:

```
message_id = 42
mode = 1
bus = 1
pid = 3

responses = vi.create_diagnostic_request(message, mode,
                                         bus=bus, pid=pid, wait_for_first_response=True)
```

To write a low-level CAN message (the VI must be configured to allow this):

```
vi.write(bus=1, id=42, data="0x1234567812345678")
```

To put the CAN acceptance filter in bypass mode for bus 1:

```
vi.set_passthrough(1, true)
```

There are many more commands and options, and most have documented APIs in the code base. You are encouraged you to dig around as the library is fairly small and should be easy to grok. More examples and documentation would be a most welcome contribution!

## Controllers

Contains the abstract interface for sending commands back to a vehicle interface.

```
class openxc.controllers.base.CommandResponseReceiver (queue, request,
                                                    quit_after_first=True)
```

A receiver that matches the 'command' field in responses to the original request.

Construct a new ResponseReceiver.

*queue* - A multithreading queue that this receiver will pull potential responses from. *request* - The request we are trying to match up with a response.

```
class openxc.controllers.base.Controller
```

A Controller is a physical vehicle interface that accepts commands to be send back to the vehicle. This class is abstract, and implementations of the interface must define at least the `write_bytes` method.

```
complex_request (request, wait_for_first_response=True)
```

Send a compound command request to the interface over the normal data channel.

**request** - A dict storing the request to send to the VI. It will be serialized to the currently selected output format.

**wait\_for\_first\_response** - If true, this function will block waiting for a response from the VI and return it to the caller. Otherwise, it will send the command and return immediately and any response will be lost.

```
create_diagnostic_request (message_id, mode, bus=None, pid=None, frequency=None, payload=None, wait_for_ack=True, wait_for_first_response=False,
                            decoded_type=None)
```

Send a new diagnostic message request to the VI

Required:

*message\_id* - The message ID (arbitration ID) for the request. *mode* - the diagnostic mode (or service).

Optional:

**bus** - The address of the CAN bus controller to send the request, either 1 or 2 for current VI hardware.

**pid** - The parameter ID, or PID, for the request (e.g. for a mode 1 request).

**frequency** - The frequency in hertz to add this as a recurring diagnostic requests. Must be greater than 0, or None if it is a one-time request.

**payload** - A bytearray to send as the request's optional payload. Only single frame diagnostic requests are supported by the VI firmware in the current version, so the payload has a maximum length of 6.

**wait\_for\_ack** - If True, will wait for an ACK of the command message. **wait\_for\_first\_response** - If True, this function will block waiting for

a diagnostic response to be received for the request. It will return either after timing out or after 1 matching response is received - there may be more responses to functional broadcast requests that arrive after returning.

**Returns a tuple of**

([list of ACK responses to create request], [list of diagnostic responses received])

**delete\_diagnostic\_request** (*message\_id, mode, bus=None, pid=None*)

**device\_id** ()

Request the unique device ID of the attached VI.

**modem\_configuration** (*host, port*)

Set the host:port for the Cellular device to send data to.

Returns True if the command was successful.

**platform** ()

Request the VI platform.

**rtc\_configuration** (*unix\_time*)

Set the Unix time if RTC is supported on the device.

Returns True if the command was successful.

**sd\_mount\_status** ()

Request for SD Mount status if available.

**set\_acceptance\_filter\_bypass** (*bus, bypass*)

Control the status of CAN acceptance filter for a bus.

Returns True if the command was successful.

**set\_passthrough** (*bus, enabled*)

Control the status of CAN message passthrough for a bus.

Returns True if the command was successful.

**set\_payload\_format** (*payload\_format*)

Set the payload format for messages sent to and from the VI.

Returns True if the command was successful.

**set\_predefined\_obd2\_requests** (*enabled*)

Control if pre-defined OBD2 requests should be sent.

Returns True if the command was successful.

**stop** ()

**version ()**

Request a firmware version identifier from the VI.

**write (\*\*kwargs)**

Serialize a raw or translated write request and send it to the VI, following the OpenXC message format.

**write\_bytes (data)**

Write the bytes in *data* to the controller interface.

**write\_raw (message\_id, data, bus=None, frame\_format=None)**

Send a raw write request to the VI.

**write\_translated (name, value, event=None)**

Send a translated write request to the VI.

**exception** `openxc.controllers.base.ControllerError`

**class** `openxc.controllers.base.DiagnosticResponseReceiver (queue, request)`

A receiver that matches the bus, ID, mode and PID from a diagnostic request to an incoming response.

**class** `openxc.controllers.base.ResponseReceiver (queue, request, quit_after_first=True)`

All commands to a vehicle interface are asynchronous. This class is used to wait for the response for a particular request in a thread. Before making a request, a `ResponseReceiver` is created to wait for the response. All responses received from the VI (which may or may not be in response to this particular command) are passed to the `ResponseReceiver`, until it either times out waiting or finds a matching response.

The synchronization mechanism is a multiprocessing `Queue`. The `ResponseReceiver` blocks waiting on a new response to be added to the queue, and the vehicle interface class puts newly received responses in the queues of `ResponseReceivers` as they arrive.

Construct a new `ResponseReceiver`.

*queue* - A multithreading queue that this receiver will pull potential responses from. *request* - The request we are trying to match up with a response.

**COMMAND\_RESPONSE\_TIMEOUT\_S = 0.5**

**handle\_responses ()**

Block and wait for responses to this object's original request, or until a timeout (`self.COMMAND_RESPONSE_TIMEOUT_S`).

This function is handy to use as the target function for a thread.

The responses received (or `None` if none was received before the timeout) is stored in a list at `self.responses`.

**start ()**

**wait\_for\_responses ()**

Block the thread and wait for the response to the given request to arrive from the VI. If no matching response is received in `COMMAND_RESPONSE_TIMEOUT_S` seconds, returns anyway.

Controller implementation for a virtual serial device.

**class** `openxc.controllers.serial.SerialControllerMixin`

An implementation of a `Controller` type that connects to a virtual serial device.

This class acts as a mixin, and expects `self.device` to be an instance of `serial.Serial`.

TODO Bah, this is kind of weird. refactor the relationship between sources/controllers.

**WAITIED\_FOR\_CONNECTION = False**

**complex\_request (request, blocking=True)**

**write\_bytes (data)**

Controller implementation for an OpenXC USB device.

```
class openxc.controllers.usb.UsbControllerMixin
```

An implementation of a Controller type that connects to an OpenXC USB device.

This class acts as a mixin, and expects `self.device` to be an instance of `usb.Device`.

TODO bah, this is kind of weird. refactor the relationship between sources/controllers.

```
COMPLEX_CONTROL_COMMAND = 131
```

```
out_endpoint
```

Open a reference to the USB device's only OUT endpoint. This method assumes that the USB device configuration has already been set.

```
write_bytes (data)
```

## Data Formats

JSON formatting utilities.

```
class openxc.formats.json.JsonFormatter
```

```
    classmethod deserialize (message)
```

```
    classmethod serialize (data)
```

```
class openxc.formats.json.JsonStreamer
```

```
    SERIALIZED_COMMAND_TERMINATOR = '\x00'
```

```
    parse_next_message ()
```

```
    serialize_for_stream (message)
```

## Measurements

Vehicle data measurement types pre-defined in OpenXC.

```
class openxc.measurements.AcceleratorPedalPosition (value, **kwargs)
```

```
    name = 'accelerator_pedal_position'
```

```
class openxc.measurements.BooleanMeasurement (value, **kwargs)
```

```
    DATA_TYPE
```

alias of bool

```
class openxc.measurements.BrakePedalStatus (value, **kwargs)
```

```
    name = 'brake_pedal_status'
```

```
class openxc.measurements.ButtonEvent (value, **kwargs)
```

```
    name = 'button_event'
```



```
states = ['up', 'down', 'left', 'right', 'ok']
```

```
class openxc.measurements.CanMessage (name, value, event=None, override_unit=False,  
                                     **kwargs)
```

Construct a new Measurement with the given name and value.

**Args:** name (str): The Measurement's generic name in OpenXC. value (str, float, or bool): The Measurement's value.

**Kwargs:** event (str, bool): An optional event for compound Measurements. override\_unit (bool): The value will be coerced to the correct units

if it is a plain number.

**Raises:** UnrecognizedMeasurementError if the value is not the correct units, e.g. if it's a string and we're expecting a numerical value

```
name = 'can_message'
```

```
class openxc.measurements.DoorStatus (value, **kwargs)
```

```
name = 'door_status'
```

```
states = ['driver', 'rear_left', 'rear_right', 'passenger']
```

```
class openxc.measurements.EngineSpeed (value, **kwargs)
```

```
name = 'engine_speed'
```

```
unit = ComposedUnit([LeafUnit('rotations', False)], [LeafUnit('m', True)], 1)
```

```
valid_range = <openxc.utils.Range object>
```

```
class openxc.measurements.EventedMeasurement (value, **kwargs)
```

```
DATA_TYPE
```

```
alias of unicode
```

```
class openxc.measurements.FuelConsumed (value, **kwargs)
```

```
name = 'fuel_consumed_since_restart'
```

```
unit = NamedComposedUnit('L', ComposedUnit([LeafUnit('m', True), LeafUnit('m', True), LeafUnit('m', True)], [], 0.001))
```

```
valid_range = <openxc.utils.Range object>
```

```
class openxc.measurements.FuelLevel (value, **kwargs)
```

```
name = 'fuel_level'
```

```
class openxc.measurements.HeadlampStatus (value, **kwargs)
```

```
name = 'headlamp_status'
```

```
class openxc.measurements.HighBeamStatus (value, **kwargs)
```

```
name = 'high_beam_status'
```

```
class openxc.measurements.IgnitionStatus (value, **kwargs)
```

```
name = 'ignition_status'  
states = ['off', 'accessory', 'run', 'start']
```

```
class openxc.measurements.LateralAcceleration (value, **kwargs)
```

```
name = 'lateral_acceleration'  
unit = ComposedUnit([LeafUnit('m', True)], [LeafUnit('s', True), LeafUnit('s', True)], 1)  
valid_range = <openxc.utils.Range object>
```

```
class openxc.measurements.Latitude (value, **kwargs)
```

```
name = 'latitude'  
unit = LeafUnit('deg', False)  
valid_range = <openxc.utils.Range object>
```

```
class openxc.measurements.Longitude (value, **kwargs)
```

```
name = 'longitude'  
unit = LeafUnit('deg', False)  
valid_range = <openxc.utils.Range object>
```

```
class openxc.measurements.LongitudinalAcceleration (value, **kwargs)
```

```
name = 'longitudinal_acceleration'  
unit = ComposedUnit([LeafUnit('m', True)], [LeafUnit('s', True), LeafUnit('s', True)], 1)  
valid_range = <openxc.utils.Range object>
```

```
class openxc.measurements.Measurement (name, value, event=None, override_unit=False,  
                                       **kwargs)
```

The Measurement is the base type of all values read from an OpenXC vehicle interface. All values encapsulated in a Measurement have an associated scalar unit (e.g. meters, degrees, etc) to avoid crashing a rover into Mars.

Construct a new Measurement with the given name and value.

**Args:** name (str): The Measurement's generic name in OpenXC. value (str, float, or bool): The Measurement's value.

**Kwargs:** event (str, bool): An optional event for compound Measurements. override\_unit (bool): The value will be coerced to the correct units

if it is a plain number.

**Raises:** UnrecognizedMeasurementError if the value is not the correct units, e.g. if it's a string and we're expecting a numerical value

#### DATA\_TYPE

alias of Number

**classmethod from\_dict (data)**

Create a new Measurement subclass instance using the given dict.

If Measurement.name\_from\_class was previously called with this data's associated Measurement sub-class in Python, the returned object will be an instance of that sub-class. If the measurement name in data is unrecognized, the returned object will be of the generic Measurement type.

**Args:**

**data (dict):** the data for the new measurement, including at least a name and value.

**name = 'generic'**

**classmethod name\_from\_class** (*measurement\_class*)

For a given measurement class, return its generic name.

The given class is expected to have a name attribute, otherwise this function will raise an exception. The point of using this method instead of just trying to grab that attribute in the application is to cache measurement name to class mappings for future use.

**Returns:** the generic OpenXC name for a measurement class.

**Raise:**

**UnrecognizedMeasurementError:** if the class does not have a valid generic name

**unit = LeafUnit('undef', False)**

**value**

**class** `openxc.measurements.NamedMeasurement` (*value, \*\*kwargs*)

A NamedMeasurement has a class-level name variable and thus the name argument is not required in its constructor.

**class** `openxc.measurements.NumericMeasurement` (*value, \*\*kwargs*)

A NumericMeasurement must have a numeric value and thus a valid range of acceptable values.

**percentage\_within\_range** ()

**valid\_range = None**

**within\_range** ()

**class** `openxc.measurements.Odometer` (*value, \*\*kwargs*)

**name = 'odometer'**

**unit = NamedComposedUnit('km', ComposedUnit([LeafUnit('m', True)], [], 1000), False)**

**valid\_range = <openxc.utils.Range object>**

**class** `openxc.measurements.ParkingBrakeStatus` (*value, \*\*kwargs*)

**name = 'parking\_brake\_status'**

**class** `openxc.measurements.PercentageMeasurement` (*value, \*\*kwargs*)

**unit = LeafUnit('%', False)**

**valid\_range = <openxc.utils.Range object>**

**class** `openxc.measurements.StatefulMeasurement` (*value, \*\*kwargs*)

Must have a class-level states member that defines a set of valid string states for this measurement's value.

**DATA\_TYPE**

alias of unicode

**states = None**

**valid\_state** ()

Determine if the current state is valid, given the class' state member.

**Returns:** True if the value is a valid state.

```
class openxc.measurements.SteeringWheelAngle (value, **kwargs)
```

```
    name = 'steering_wheel_angle'
```

```
    unit = LeafUnit('deg', False)
```

```
    valid_range = <openxc.utils.Range object>
```

```
class openxc.measurements.TorqueAtTransmission (value, **kwargs)
```

```
    name = 'torque_at_transmission'
```

```
    unit = NamedComposedUnit('Nm', ComposedUnit([NamedComposedUnit('N', ComposedUnit([LeafUnit('m', True), Na
```

```
    valid_range = <openxc.utils.Range object>
```

```
class openxc.measurements.TransmissionGearPosition (value, **kwargs)
```

```
    name = 'transmission_gear_position'
```

```
    states = ['first', 'second', 'third', 'fourth', 'fifth', 'sixth', 'seventh', 'eighth', 'neutral', 'reverse', 'park']
```

```
class openxc.measurements.TurnSignalStatus (value, **kwargs)
```

```
    name = 'turn_signal_status'
```

```
exception openxc.measurements.UnrecognizedMeasurementError
```

```
class openxc.measurements.VehicleSpeed (value, **kwargs)
```

```
    name = 'vehicle_speed'
```

```
    unit = ComposedUnit([NamedComposedUnit('km', ComposedUnit([LeafUnit('m', True)], [], 1000), False)], [NamedCom
```

```
    valid_range = <openxc.utils.Range object>
```

```
class openxc.measurements.WindshieldWiperStatus (value, **kwargs)
```

```
    name = 'windshield_wiper_status'
```

```
openxc.measurements.all_measurements ()
```

## Data Sinks

Common operations for all vehicle data sinks.

```
class openxc.sinks.base.DataSink
```

A base interface for all data sinks. At the minimum, a data sink must have a `receive()` method.

```
    receive (message, **kwargs)
```

Handle an incoming vehicle data message.

**Args:** message (dict) - a new OpenXC vehicle data message

**Kwargs:**

**data\_remaining (bool)** - if the originating data source can peek ahead in the data stream, this argument will True if there is more data available.

A data sink implementation for the core listener notification service of `openxc.vehicle.Vehicle`.

**class** `openxc.sinks.notifier.MeasurementNotifierSink`  
 Notify previously registered callbacks whenever measurements of a certian type have been received.

This data sink is the core of the asynchronous interface of `openxc.vehicle.Vehicle`.

**class** `Notifier (queue, callback)`

**run ()**

`MeasurementNotifierSink.register (measurement_class, callback)`

Call the callback with any new values of `measurement_class` received.

`MeasurementNotifierSink.unregister (measurement_class, callback)`

Stop notifying callback of new values of `measurement_class`.

If the callback wasn't previously registered, this method will have no effect.

Common functionality for data sinks that work on a queue of incoming messages.

**class** `openxc.sinks.queued.QueuedSink`  
 Store every message received and any kwargs from the originating data source as a tuple in a queue.

The queue can be reference in subclasses via the `queue` attribute.

**receive** (`message, **kwargs`)

Add the `message` and `kwargs` to the queue.

Trace file recording operations.

**class** `openxc.sinks.recorder.FileRecorderSink`  
 A sink to record trace files based on the messages received from all data sources.

**FILENAME\_DATE\_FORMAT** = '%Y-%m-%d-%H'

**FILENAME\_FORMAT** = '%s.json'

**class** `Recorder (queue)`

**run ()**

**class** `openxc.sinks.uploader.UploaderSink (url)`  
 Uploads all incoming vehicle data to a remote web application via HTTP.

TODO document service side format

Args: `url (str)` - the URL to send an HTTP POST request with vehicle data

**HTTP\_TIMEOUT** = 5000

**UPLOAD\_BATCH\_SIZE** = 25

**class** `Uploader (queue, url)`

**run ()**

## Data Sources

Abstract base interface for vehicle data sources.

**class** `openxc.sources.base.BytestreamDataSource` (*\*\*kwargs*)

A source that receives data is a series of bytes, with discrete messages separated by a newline character.

Subclasses of this class need only to implement the `read` method.

**run** ()

Continuously read data from the source and attempt to parse a valid message from the buffer of bytes.

When a message is parsed, passes it off to the callback if one is set.

**class** `openxc.sources.base.DataSource` (*callback=None, log\_mode=None, payload\_format=None*)

Interface for all vehicle data sources. This inherits from `Thread` and when a source is added to a vehicle it attempts to call the `start` () method if it exists. If an implementer of `DataSource` needs some background process to read data, it's just a matter of defining a `run` () method.

A data source requires a callback method to be specified. Whenever new data is received, it will pass it to that callback.

Construct a new `DataSource`.

By default, `DataSource` threads are marked as `daemon` threads, so they will die as soon as all other non-`daemon` threads in the process have quit.

**Kwargs:** `callback` - function to call with any new data received

**bytes\_received**

**format**

**formatter**

**read** (*timeout=None*)

Read data from the source.

**Kwargs:**

**timeout (float)** - if the source implementation could potentially block, timeout after this number of seconds.

**read\_logs** (*timeout=None*)

Read log data from the source.

**Kwargs:**

**timeout (float)** - if the source implementation could potentially block, timeout after this number of seconds.

**start** ()

**stop** ()

**streamer**

**exception** `openxc.sources.base.DataSourceError`

**exception** `openxc.sources.base.MissingPayloadFormatError`

**class** `openxc.sources.base.SourceLogger` (*source, mode='off'*)

**FILENAME\_TEMPLATE** = '%d-%m-%Y,%H-%M-%S'

**record** (*message*)

**run ()**

Continuously read data from the source and attempt to parse a valid message from the buffer of bytes. When a message is parsed, passes it off to the callback if one is set.

**stop ()**

A virtual serial port data source.

**class** `openxc.sources.serial.SerialDataSource` (*port=None, baudrate=None, \*\*kwargs*)

A data source reading from a serial port, which could be implemented with a USB to Serial or Bluetooth adapter.

Initialize a connection to the serial device.

**Kwargs:** *port* - optionally override the default virtual COM port *baudrate* - optionally override the default baudrate

**Raises:** DataSourceError if the serial device cannot be opened.

**DEFAULT\_BAUDRATE = 230400**

**DEFAULT\_PORT = '/dev/ttyUSB0'**

**read ()**

A USB vehicle interface data source.

**class** `openxc.sources.usb.UsbDataSource` (*vendor\_id=None, product\_id=None, \*\*kwargs*)

A source to receive data from an OpenXC vehicle interface via USB.

Initialize a connection to the USB device's IN endpoint.

**Kwargs:**

**vendor\_id (str or int) - optionally override the USB device vendor** ID we will attempt to connect to, if not using the OpenXC hardware.

**product\_id (str or int) - optionally override the USB device product** ID we will attempt to connect to, if not using the OpenXC hardware.

**log\_mode - optionally record or print logs from the USB device, which** are on a separate channel.

**Raises:** DataSourceError if the USB device with the given vendor ID is not connected.

**DEFAULT\_INTERFACE\_NUMBER = 0**

**DEFAULT\_PRODUCT\_ID = 1**

**DEFAULT\_READ\_REQUEST\_SIZE = 512**

**DEFAULT\_READ\_TIMEOUT = 200**

**DEFAULT\_VENDOR\_ID = 7108**

**LOG\_IN\_ENDPOINT = 11**

**VEHICLE\_DATA\_IN\_ENDPOINT = 2**

**read (timeout=None)**

**read\_logs (timeout=None)**

**stop ()**

A data source for reading from pre-recorded OpenXC trace files.

**class** `openxc.sources.trace.TraceDataSource` (*filename=None, realtime=True, loop=True, \*\*kwargs*)

A class to replay a previously recorded OpenXC vehicle data trace file. For details on the trace file format, see <http://openxcplatform.com/android/testing.html>.

Construct the source and attempt to open the trace file.

filename - the full absolute path to the trace file

realtime - if `True`, the trace will be replayed at approximately the same cadence as it was recorded. Otherwise, the trace file will be replayed as fast as possible (likely much faster than any vehicle).

loop - if `True`, the trace file will be looped and will provide data until the process exist or the source is stopped.

**read()**

Read a line of data from the input source at a time.

A network socket data source.

**class** `openxc.sources.network.NetworkDataSource` (*host=None, port=None, \*\*kwargs*)

A data source reading from a network socket, as implemented in the `openxc-vehicle-simulator`.

Initialize a connection to the network socket.

**Kwargs:** `host` - optionally override the default network host (default is local machine) `port` - optionally override the default network port (default is 50001) `log_mode` - optionally record or print logs from the network source

**Raises:** `DataSourceError` if the socket connection cannot be opened.

**DEFAULT\_PORT = 50001**

## Units

Define the scalar units used by vehicle measurements.

`openxc.units.Percentage`

`openxc.units.Meter`

`openxc.units.Kilometer`

`openxc.units.Hour`

`openxc.units.KilometersPerHour`

`openxc.units.RotationsPerMinute`

`openxc.units.Litre`

`openxc.units.Degree`

`openxc.units.NewtonMeter`

`openxc.units.MetersPerSecondSquared`

`openxc.units.Undefined`

## Utils

Data containers and other utilities.

**class** `openxc.utils.AgingData`

Mixin to associate a class with a time of birth.



**age**

Return the age of the data in seconds.

**class** `openxc.utils.Range` (*minimum, maximum*)  
Encapsulates a ranged defined by a min and max numerical value.

**spread**

Returns the spread between this Range's min and max.

**within\_range** (*value*)

Returns True if the value is between this Range, inclusive.

`openxc.utils.fatal_error` (*message*)

`openxc.utils.find_file` (*filename, search\_paths*)

`openxc.utils.load_json_from_search_path` (*filename, search\_paths*)

`openxc.utils.merge` (*a, b*)

Merge two deep dicts non-destructively

Uses a stack to avoid maximum recursion depth exceptions

```
>>> a = {'a': 1, 'b': {1: 1, 2: 2}, 'd': 6}
>>> b = {'c': 3, 'b': {2: 7}, 'd': {'z': [1, 2, 3]}}
>>> c = merge(a, b)
>>> from pprint import pprint; pprint(c)
{'a': 1, 'b': {1: 1, 2: 7}, 'c': 3, 'd': {'z': [1, 2, 3]}}
```

`openxc.utils.quacks_like_dict` (*object*)

Check if object is dict-like

`openxc.utils.quacks_like_list` (*object*)

Check if object is list-like

## Vehicle functions

This module is contains the `Vehicle` class, which is the main entry point for using the Python library to access vehicle data programatically. Most users will want to interact with an instance of `Vehicle`, and won't need to deal with other parts of the library directly (besides measurement types).

**class** `openxc.vehicle.Vehicle` (*interface=None*)

The `Vehicle` class is the main entry point for the OpenXC Python library. A `Vehicle` represents a connection to at least one vehicle data source and zero or 1 vehicle controllers, which can accept commands to send back to the vehicle. A `Vehicle` instance can have more than one data source (e.g. if the computer using this library has a secondary GPS data source).

Most applications will either request synchronous vehicle data measurements using the `get` method or with a callback function passed to `listen`.

More advanced applications that want access to all raw vehicle data may want to register a `DataSink` with a `Vehicle`.

Construct a new `Vehicle` instance, optionally providing an vehicle interface from `openxc.interface` to user for I/O.

**add\_sink** (*sink*)

Add a vehicle data sink to the instance. `sink` should be a sub-class of `DataSink` or at least have a `receive(message, **kwargs)` method.

The sink will be started if it is startable. (i.e. it has a `start ()` method).

**add\_source** (*source*)

Add a vehicle data source to the instance.

The Vehicle instance will be set as the callback of the source, and the source will be started if it is startable. (i.e. it has a `start ()` method).

**get** (*measurement\_class*)

Return the latest measurement for the given class or None if nothing has been received from the vehicle.

**listen** (*measurement\_class, callback*)

Register the callback function to be called whenever a new measurement of the given class is received from the vehicle data sources.

If the callback is already registered for measurements of the given type, this method will have no effect.

**unlisten** (*measurement\_class, callback*)

Stop notifying the given callback of new values of the measurement type.

If the callback was not previously registered as a listener, this method will have no effect.

Development of `openxc-python` happens at [GitHub](#). Be sure to see our [contribution document](#) for details.

### Test Suite

The `openxc-python` repository contains a test suite that can be run with the `tox` tool, which attempts to run the test suite in Python 2.7. If you wish to just run the test suite in your primary Python version, run

```
$ python setup.py test
```

To run it with `tox`:

```
$ tox
```

### Mailing list

For discussions about the usage, development, and future of OpenXC, please join the [OpenXC mailing list](#).

### Bug tracker

If you have any suggestions, bug reports or annoyances please report them to our issue tracker at <http://github.com/openxc/openxc-python/issues/>

### Authors and Contributors

A [complete list](#) of all authors is stored in the repository - thanks to everyone for the great contributions.



### O

- `openxc.controllers.base`, 17
- `openxc.controllers.serial`, 19
- `openxc.controllers.usb`, 20
- `openxc.formats.json`, 20
- `openxc.measurements`, 20
- `openxc.sinks.base`, 24
- `openxc.sinks.notifier`, 25
- `openxc.sinks.queued`, 25
- `openxc.sinks.recorder`, 25
- `openxc.sinks.uploader`, 25
- `openxc.sources.base`, 26
- `openxc.sources.network`, 28
- `openxc.sources.serial`, 27
- `openxc.sources.trace`, 27
- `openxc.sources.usb`, 27
- `openxc.units`, 28
- `openxc.utils`, 28
- `openxc.vehicle`, 29



## Symbols

-s, --split <unit>

command line option, 13

## A

AcceleratorPedalPosition (class in openxc.measurements), 20

add\_sink() (openxc.vehicle.Vehicle method), 29

add\_source() (openxc.vehicle.Vehicle method), 28

age (openxc.utils.AgingData attribute), 28

AgingData (class in openxc.utils), 28

all\_measurements() (in module openxc.measurements), 24

## B

BooleanMeasurement (class in openxc.measurements), 20

BrakePedalStatus (class in openxc.measurements), 20

ButtonEvent (class in openxc.measurements), 20

bytes\_received (openxc.sources.base.DataSource attribute), 26

BytestreamDataSource (class in openxc.sources.base), 26

## C

CanMessage (class in openxc.measurements), 21

command line option

-s, --split <unit>, 13

COMMAND\_RESPONSE\_TIMEOUT\_S (openxc.controllers.base.ResponseReceiver attribute), 19

CommandResponseReceiver (class in openxc.controllers.base), 17

COMPLEX\_CONTROL\_COMMAND (openxc.controllers.usb.UsbControllerMixin attribute), 20

complex\_request() (openxc.controllers.base.Controller method), 17

complex\_request() (openxc.controllers.serial.SerialControllerMixin method), 19

Controller (class in openxc.controllers.base), 17

ControllerError, 19

create\_diagnostic\_request() (openxc.controllers.base.Controller method), 17

## D

DATA\_TYPE (openxc.measurements.BooleanMeasurement attribute), 20

DATA\_TYPE (openxc.measurements.EventedMeasurement attribute), 21

DATA\_TYPE (openxc.measurements.Measurement attribute), 22

DATA\_TYPE (openxc.measurements.StatefulMeasurement attribute), 23

DataSink (class in openxc.sinks.base), 24

DataSource (class in openxc.sources.base), 26

DataSourceError, 26

DEFAULT\_BAUDRATE (openxc.sources.serial.SerialDataSource attribute), 27

DEFAULT\_INTERFACE\_NUMBER (openxc.sources.usb.UsbDataSource attribute), 27

DEFAULT\_PORT (openxc.sources.network.NetworkDataSource attribute), 28

DEFAULT\_PORT (openxc.sources.serial.SerialDataSource attribute), 27

DEFAULT\_PRODUCT\_ID (openxc.sources.usb.UsbDataSource attribute), 27

DEFAULT\_READ\_REQUEST\_SIZE (openxc.sources.usb.UsbDataSource attribute), 27

DEFAULT\_READ\_TIMEOUT (openxc.sources.usb.UsbDataSource attribute), 27

DEFAULT\_VENDOR\_ID (openxc.sources.usb.UsbDataSource attribute), 27

Degree (in module openxc.units), 28  
 delete\_diagnostic\_request()  
     (openxc.controllers.base.Controller method),  
     18  
 deserialize() (openxc.formats.json.JsonFormatter class  
     method), 20  
 device\_id() (openxc.controllers.base.Controller method),  
     18  
 DiagnosticResponseReceiver (class in  
     openxc.controllers.base), 19  
 DoorStatus (class in openxc.measurements), 21

## E

EngineSpeed (class in openxc.measurements), 21  
 EventedMeasurement (class in openxc.measurements), 21

## F

fatal\_error() (in module openxc.utils), 29  
 FILENAME\_DATE\_FORMAT  
     (openxc.sinks.recorder.FileRecorderSink  
     attribute), 25  
 FILENAME\_FORMAT (openxc.sinks.recorder.FileRecorderSink  
     attribute), 25  
 FILENAME\_TEMPLATE  
     (openxc.sources.base.SourceLogger attribute),  
     26  
 FileRecorderSink (class in openxc.sinks.recorder), 25  
 FileRecorderSink.Recorder (class in  
     openxc.sinks.recorder), 25  
 find\_file() (in module openxc.utils), 29  
 format (openxc.sources.base.DataSource attribute), 26  
 formatter (openxc.sources.base.DataSource attribute), 26  
 from\_dict() (openxc.measurements.Measurement class  
     method), 22  
 FuelConsumed (class in openxc.measurements), 21  
 FuelLevel (class in openxc.measurements), 21

## G

get() (openxc.vehicle.Vehicle method), 30

## H

handle\_responses() (openxc.controllers.base.ResponseReceiver  
     method), 19  
 HeadlampStatus (class in openxc.measurements), 21  
 HighBeamStatus (class in openxc.measurements), 21  
 Hour (in module openxc.units), 28  
 HTTP\_TIMEOUT (openxc.sinks.uploader.UploaderSink  
     attribute), 25

## I

IgnitionStatus (class in openxc.measurements), 21

## J

JsonFormatter (class in openxc.formats.json), 20

JsonStreamer (class in openxc.formats.json), 20

## K

Kilometer (in module openxc.units), 28  
 KilometersPerHour (in module openxc.units), 28

## L

LateralAcceleration (class in openxc.measurements), 22  
 Latitude (class in openxc.measurements), 22  
 listen() (openxc.vehicle.Vehicle method), 30  
 Litre (in module openxc.units), 28  
 load\_json\_from\_search\_path() (in module openxc.utils),  
     29  
 LOG\_IN\_ENDPOINT (openxc.sources.usb.UsbDataSource  
     attribute), 27  
 Longitude (class in openxc.measurements), 22  
 LongitudinalAcceleration (class in  
     openxc.measurements), 22

## M

Measurement (class in openxc.measurements), 22  
 MeasurementNotifierSink (class in openxc.sinks.notifier),  
     25  
 MeasurementNotifierSink.Notifier (class in  
     openxc.sinks.notifier), 25  
 merge() (in module openxc.utils), 29  
 Meter (in module openxc.units), 28  
 MetersPerSecondSquared (in module openxc.units), 28  
 MissingPayloadFormatError, 26  
 modem\_configuration() (openxc.controllers.base.Controller  
     method), 18

## N

name (openxc.measurements.AcceleratorPedalPosition  
     attribute), 20  
 name (openxc.measurements.BrakePedalStatus attribute),  
     20  
 name (openxc.measurements.ButtonEvent attribute), 20  
 name (openxc.measurements.CanMessage attribute), 21  
 name (openxc.measurements.DoorStatus attribute), 21  
 name (openxc.measurements.EngineSpeed attribute), 21  
 name (openxc.measurements.FuelConsumed attribute),  
     21  
 name (openxc.measurements.FuelLevel attribute), 21  
 name (openxc.measurements.HeadlampStatus attribute),  
     21  
 name (openxc.measurements.HighBeamStatus attribute),  
     21  
 name (openxc.measurements.IgnitionStatus attribute), 21  
 name (openxc.measurements.LateralAcceleration attri-  
     bute), 22  
 name (openxc.measurements.Latitude attribute), 22  
 name (openxc.measurements.Longitude attribute), 22



- name (openxc.measurements.LongitudinalAcceleration attribute), 22
- name (openxc.measurements.Measurement attribute), 23
- name (openxc.measurements.Odometer attribute), 23
- name (openxc.measurements.ParkingBrakeStatus attribute), 23
- name (openxc.measurements.SteeringWheelAngle attribute), 24
- name (openxc.measurements.TorqueAtTransmission attribute), 24
- name (openxc.measurements.TransmissionGearPosition attribute), 24
- name (openxc.measurements.TurnSignalStatus attribute), 24
- name (openxc.measurements.VehicleSpeed attribute), 24
- name (openxc.measurements.WindshieldWiperStatus attribute), 24
- name\_from\_class() (openxc.measurements.Measurement class method), 23
- NamedMeasurement (class in openxc.measurements), 23
- NetworkDataSource (class in openxc.sources.network), 28
- NewtonMeter (in module openxc.units), 28
- NumericMeasurement (class in openxc.measurements), 23
- O**
- Odometer (class in openxc.measurements), 23
- openxc.controllers.base (module), 17
- openxc.controllers.serial (module), 19
- openxc.controllers.usb (module), 20
- openxc.formats.json (module), 20
- openxc.measurements (module), 20
- openxc.sinks.base (module), 24
- openxc.sinks.notifier (module), 25
- openxc.sinks.queued (module), 25
- openxc.sinks.recorder (module), 25
- openxc.sinks.uploader (module), 25
- openxc.sources.base (module), 26
- openxc.sources.network (module), 28
- openxc.sources.serial (module), 27
- openxc.sources.trace (module), 27
- openxc.sources.usb (module), 27
- openxc.units (module), 28
- openxc.utils (module), 28
- openxc.vehicle (module), 29
- out\_endpoint (openxc.controllers.usb.UsbControllerMixin attribute), 20
- P**
- ParkingBrakeStatus (class in openxc.measurements), 23
- parse\_next\_message() (openxc.formats.json.JsonStreamer method), 20
- Percentage (in module openxc.units), 28
- percentage\_within\_range() (openxc.measurements.NumericMeasurement method), 23
- PercentageMeasurement (class in openxc.measurements), 23
- platform() (openxc.controllers.base.Controller method), 18
- Q**
- quacks\_like\_dict() (in module openxc.utils), 29
- quacks\_like\_list() (in module openxc.utils), 29
- QueuedSink (class in openxc.sinks.queued), 25
- R**
- Range (class in openxc.utils), 29
- read() (openxc.sources.base.DataSource method), 26
- read() (openxc.sources.serial.SerialDataSource method), 27
- read() (openxc.sources.trace.TraceDataSource method), 28
- read() (openxc.sources.usb.UsbDataSource method), 27
- read\_logs() (openxc.sources.base.DataSource method), 26
- read\_logs() (openxc.sources.usb.UsbDataSource method), 27
- receive() (openxc.sinks.base.DataSink method), 24
- receive() (openxc.sinks.queued.queued.QueueSink method), 25
- record() (openxc.sources.base.SourceLogger method), 26
- register() (openxc.sinks.notifier.MeasurementNotifierSink method), 25
- ResponseReceiver (class in openxc.controllers.base), 19
- RotationsPerMinute (in module openxc.units), 28
- rtc\_configuration() (openxc.controllers.base.Controller method), 18
- run() (openxc.sinks.notifier.MeasurementNotifierSink.Notifier method), 25
- run() (openxc.sinks.recorder.FileRecorderSink.Recorder method), 25
- run() (openxc.sinks.uploader.UploaderSink.Uploader method), 25
- run() (openxc.sources.base.BytestreamDataSource method), 26
- run() (openxc.sources.base.SourceLogger method), 26
- S**
- sd\_mount\_status() (openxc.controllers.base.Controller method), 18
- SerialControllerMixin (class in openxc.controllers.serial), 19
- SerialDataSource (class in openxc.sources.serial), 27
- serialize() (openxc.formats.json.JsonFormatter class method), 20
- serialize\_for\_stream() (openxc.formats.json.JsonStreamer method), 20

- SERIALIZED\_COMMAND\_TERMINATOR (openxc.formats.json.JsonStreamer attribute), 20
  - set\_acceptance\_filter\_bypass() (openxc.controllers.base.Controller method), 18
  - set\_passthrough() (openxc.controllers.base.Controller method), 18
  - set\_payload\_format() (openxc.controllers.base.Controller method), 18
  - set\_predefined\_obd2\_requests() (openxc.controllers.base.Controller method), 18
  - SourceLogger (class in openxc.sources.base), 26
  - spread (openxc.utils.Range attribute), 29
  - start() (openxc.controllers.base.ResponseReceiver method), 19
  - start() (openxc.sources.base.DataSource method), 26
  - StatefulMeasurement (class in openxc.measurements), 23
  - states (openxc.measurements.ButtonEvent attribute), 20
  - states (openxc.measurements.DoorStatus attribute), 21
  - states (openxc.measurements.IgnitionStatus attribute), 22
  - states (openxc.measurements.StatefulMeasurement attribute), 23
  - states (openxc.measurements.TransmissionGearPosition attribute), 24
  - SteeringWheelAngle (class in openxc.measurements), 24
  - stop() (openxc.controllers.base.Controller method), 18
  - stop() (openxc.sources.base.DataSource method), 26
  - stop() (openxc.sources.base.SourceLogger method), 27
  - stop() (openxc.sources.usb.UsbDataSource method), 27
  - streamer (openxc.sources.base.DataSource attribute), 26
- T**
- TorqueAtTransmission (class in openxc.measurements), 24
  - TraceDataSource (class in openxc.sources.trace), 27
  - TransmissionGearPosition (class in openxc.measurements), 24
  - TurnSignalStatus (class in openxc.measurements), 24
- U**
- Undefined (in module openxc.units), 28
  - unit (openxc.measurements.EngineSpeed attribute), 21
  - unit (openxc.measurements.FuelConsumed attribute), 21
  - unit (openxc.measurements.LateralAcceleration attribute), 22
  - unit (openxc.measurements.Latitude attribute), 22
  - unit (openxc.measurements.Longitude attribute), 22
  - unit (openxc.measurements.LongitudinalAcceleration attribute), 22
  - unit (openxc.measurements.Measurement attribute), 23
  - unit (openxc.measurements.Odometer attribute), 23
  - unit (openxc.measurements.PercentageMeasurement attribute), 23
  - unit (openxc.measurements.SteeringWheelAngle attribute), 24
  - unit (openxc.measurements.TorqueAtTransmission attribute), 24
  - unit (openxc.measurements.VehicleSpeed attribute), 24
  - unlisten() (openxc.vehicle.Vehicle method), 30
  - UnrecognizedMeasurementError, 24
  - unregister() (openxc.sinks.notifier.MeasurementNotifierSink method), 25
  - UPLOAD\_BATCH\_SIZE (openxc.sinks.uploader.UploaderSink attribute), 25
  - UploaderSink (class in openxc.sinks.uploader), 25
  - UploaderSink.Uploader (class in openxc.sinks.uploader), 25
  - UsbControllerMixin (class in openxc.controllers.usb), 20
  - UsbDataSource (class in openxc.sources.usb), 27
- V**
- valid\_range (openxc.measurements.EngineSpeed attribute), 21
  - valid\_range (openxc.measurements.FuelConsumed attribute), 21
  - valid\_range (openxc.measurements.LateralAcceleration attribute), 22
  - valid\_range (openxc.measurements.Latitude attribute), 22
  - valid\_range (openxc.measurements.Longitude attribute), 22
  - valid\_range (openxc.measurements.LongitudinalAcceleration attribute), 22
  - valid\_range (openxc.measurements.NumericMeasurement attribute), 23
  - valid\_range (openxc.measurements.Odometer attribute), 23
  - valid\_range (openxc.measurements.PercentageMeasurement attribute), 23
  - valid\_range (openxc.measurements.SteeringWheelAngle attribute), 24
  - valid\_range (openxc.measurements.TorqueAtTransmission attribute), 24
  - valid\_range (openxc.measurements.VehicleSpeed attribute), 24
  - valid\_state() (openxc.measurements.StatefulMeasurement method), 23
  - value (openxc.measurements.Measurement attribute), 23
  - Vehicle (class in openxc.vehicle), 29
  - VEHICLE\_DATA\_IN\_ENDPOINT (openxc.sources.usb.UsbDataSource attribute), 27
  - VehicleSpeed (class in openxc.measurements), 24
  - version() (openxc.controllers.base.Controller method), 18

## W

- `wait_for_responses()` (`openxc.controllers.base.ResponseReceiver` method), 19
- `WAITIED_FOR_CONNECTION` (`openxc.controllers.serial.SerialControllerMixin` attribute), 19
- `WindshieldWiperStatus` (class in `openxc.measurements`), 24
- `within_range()` (`openxc.measurements.NumericMeasurement` method), 23
- `within_range()` (`openxc.utils.Range` method), 29
- `write()` (`openxc.controllers.base.Controller` method), 19
- `write_bytes()` (`openxc.controllers.base.Controller` method), 19
- `write_bytes()` (`openxc.controllers.serial.SerialControllerMixin` method), 19
- `write_bytes()` (`openxc.controllers.usb.UsbControllerMixin` method), 20
- `write_raw()` (`openxc.controllers.base.Controller` method), 19
- `write_translated()` (`openxc.controllers.base.Controller` method), 19