

---

# **phpMyAdmin Documentation**

*Release 4.5.0-dev*

**The phpMyAdmin devel team**

August 26, 2015



<b>1</b>	<b>Introduction</b>	<b>3</b>
1.1	Supported features . . . . .	3
1.2	A word about users . . . . .	4
<b>2</b>	<b>Requirements</b>	<b>5</b>
2.1	Web server . . . . .	5
2.2	PHP . . . . .	5
2.3	Database . . . . .	5
2.4	Web browser . . . . .	6
<b>3</b>	<b>Installation</b>	<b>7</b>
3.1	Linux distributions . . . . .	7
3.2	Installing on Windows . . . . .	8
3.3	Quick Install . . . . .	8
3.4	Verifying phpMyAdmin releases . . . . .	10
3.5	phpMyAdmin configuration storage . . . . .	11
3.6	Upgrading from an older version . . . . .	12
3.7	Using authentication modes . . . . .	13
3.8	Securing your phpMyAdmin installation . . . . .	14
<b>4</b>	<b>Configuration</b>	<b>17</b>
4.1	Basic settings . . . . .	17
4.2	Server connection settings . . . . .	19
4.3	Generic settings . . . . .	32
4.4	Cookie authentication options . . . . .	36
4.5	Navigation panel setup . . . . .	37
4.6	Main panel . . . . .	41
4.7	Database structure . . . . .	42
4.8	Browse mode . . . . .	43
4.9	Editing mode . . . . .	44
4.10	Export and import settings . . . . .	45
4.11	Tabs display settings . . . . .	46
4.12	PDF Options . . . . .	47
4.13	Languages . . . . .	47
4.14	Web server settings . . . . .	48
4.15	Theme settings . . . . .	50
4.16	Design customization . . . . .	52
4.17	Text fields . . . . .	53

4.18	SQL query box settings . . . . .	54
4.19	Web server upload/save/import directories . . . . .	55
4.20	Various display setting . . . . .	56
4.21	Page titles . . . . .	57
4.22	Theme manager settings . . . . .	58
4.23	Default queries . . . . .	58
4.24	MySQL settings . . . . .	59
4.25	Developer . . . . .	59
<b>5</b>	<b>User Guide</b>	<b>61</b>
5.1	Transformations . . . . .	61
5.2	User management . . . . .	62
5.3	Other sources of information . . . . .	63
5.4	Import and export . . . . .	63
<b>6</b>	<b>FAQ - Frequently Asked Questions</b>	<b>65</b>
6.1	Server . . . . .	65
6.2	Configuration . . . . .	73
6.3	Known limitations . . . . .	75
6.4	ISPs, multi-user installations . . . . .	78
6.5	Browsers or client OS . . . . .	80
6.6	Using phpMyAdmin . . . . .	82
6.7	phpMyAdmin project . . . . .	92
6.8	Security . . . . .	93
6.9	Synchronization . . . . .	93
<b>7</b>	<b>Developers Information</b>	<b>95</b>
<b>8</b>	<b>Distributing and packaging phpMyAdmin</b>	<b>97</b>
8.1	External libraries . . . . .	97
<b>9</b>	<b>Copyright</b>	<b>99</b>
9.1	Third party licenses . . . . .	99
<b>10</b>	<b>Credits</b>	<b>101</b>
10.1	Credits, in chronological order . . . . .	101
10.2	Translators . . . . .	107
10.3	Documentation translators . . . . .	109
10.4	Original Credits of Version 2.1.0 . . . . .	110
<b>11</b>	<b>Glossary</b>	<b>111</b>
<b>12</b>	<b>Indices and tables</b>	<b>119</b>

Contents:



---

## Introduction

---

phpMyAdmin can manage a whole MySQL server (needs a super-user) as well as a single database. To accomplish the latter you'll need a properly set up MySQL user who can read/write only the desired database. It's up to you to look up the appropriate part in the MySQL manual.

### 1.1 Supported features

Currently phpMyAdmin can:

- browse and drop databases, tables, views, columns and indexes
- display multiple results sets through stored procedures or queries
- create, copy, drop, rename and alter databases, tables, columns and indexes
- maintenance server, databases and tables, with proposals on server configuration
- execute, edit and bookmark any *SQL*-statement, even batch-queries
- load text files into tables
- create <sup>1</sup> and read dumps of tables
- export <sup>1</sup> data to various formats: *CSV*, *XML*, *PDF*, *ISO/IEC 26300 - OpenDocument* Text and Spreadsheet, Microsoft Word 2000, and LATEX formats
- import data and *MySQL* structures from *OpenDocument* spreadsheets, as well as *XML*, *CSV*, and *SQL* files
- administer multiple servers
- manage MySQL users and privileges
- check referential integrity in MyISAM tables
- using Query-by-example (QBE), create complex queries automatically connecting required tables
- create *PDF* graphics of your database layout
- search globally in a database or a subset of it
- transform stored data into any format using a set of predefined functions, like displaying BLOB-data as image or download-link
- track changes on databases, tables and views

---

<sup>1</sup> phpMyAdmin can compress (*Zip*, *GZip* or *RFC 1952* formats) dumps and *CSV* exports if you use PHP with *Zlib* support (`--with-zlib`). Proper support may also need changes in `php.ini`.

- support InnoDB tables and foreign keys
- support mysqli, the improved MySQL extension see *1.17 Which Database versions does phpMyAdmin support?*
- create, edit, call, export and drop stored procedures and functions
- create, edit, export and drop events and triggers
- communicate in *80 different languages*

## 1.2 A word about users

Many people have difficulty understanding the concept of user management with regards to phpMyAdmin. When a user logs in to phpMyAdmin, that username and password are passed directly to MySQL. phpMyAdmin does no account management on its own (other than allowing one to manipulate the MySQL user account information); all users must be valid MySQL users.



---

## Requirements

---

### 2.1 Web server

Since phpMyAdmin's interface is based entirely in your browser, you'll need a web server (such as Apache, nginx, *IIS*) to install phpMyAdmin's files into.

### 2.2 PHP

- You need PHP 5.5.0 or newer, with `session` support, the Standard PHP Library (SPL) extension, JSON support, and the `mbstring` extension.
- To support uploading of ZIP files, you need the PHP `zip` extension.
- You need GD2 support in PHP to display inline thumbnails of JPEGs (“image/jpeg: inline”) with their original aspect ratio.
- When using the cookie authentication (the default), the `mcrypt` extension is strongly suggested.
- To support upload progress bars, see [2.9 Seeing an upload progress bar](#).
- To support XML and Open Document Spreadsheet importing, you need the `libxml` extension.
- To support reCAPTCHA on the login page, you need the `openssl` extension.
- Performance suggestion: install the `ctype` extension.

**See also:**

*1.31 Does phpMyAdmin support PHP 5?, Using authentication modes*

### 2.3 Database

phpMyAdmin supports MySQL-compatible databases.

- MySQL 5.5 or newer
- MariaDB 5.5 or newer
- Drizzle

**See also:**

*1.17 Which Database versions does phpMyAdmin support?*

## 2.4 Web browser

To access phpMyAdmin you need a web browser with cookies and JavaScript enabled.

---

## Installation

---

phpMyAdmin does not apply any special security methods to the MySQL database server. It is still the system administrator's job to grant permissions on the MySQL databases properly. phpMyAdmin's *Users* page can be used for this.

**Warning:** *Mac* users should note that if you are on a version before *Mac OS X*, StuffIt unstuffs with *Mac* formats. So you'll have to resave as in BBEdit to Unix style ALL phpMyAdmin scripts before uploading them to your server, as PHP seems not to like *Mac*-style end of lines character (“\r”).

### 3.1 Linux distributions

phpMyAdmin is included in most Linux distributions. It is recommended to use distribution packages when possible - they usually provide integration to your distribution and you will automatically get security updates from your distribution.

#### 3.1.1 Debian

Debian's package repositories include a phpMyAdmin package, but be aware that the configuration file is maintained in `/etc/phpmyadmin` and may differ in some ways from the official phpMyAdmin documentation.

#### 3.1.2 OpenSUSE

OpenSUSE already comes with phpMyAdmin package, just install packages from the [openSUSE Build Service](#).

#### 3.1.3 Ubuntu

Ubuntu ships phpMyAdmin package, however if you want to use recent version, you can use packages from [PPA for Michal Čihař](#).

#### 3.1.4 Gentoo

Gentoo ships the phpMyAdmin package, both in a near stock configuration as well as in a `webapp-config` configuration. Use `emerge dev-db/phpmyadmin` to install.

### 3.1.5 Mandriva

Mandriva ships the phpMyAdmin package in their `contrib` branch and can be installed via the usual Control Center.

### 3.1.6 Fedora

Fedora ships the phpMyAdmin package, but be aware that the configuration file is maintained in `/etc/phpMyAdmin/` and may differ in some ways from the official phpMyAdmin documentation.

### 3.1.7 Red Hat Enterprise Linux

Red Hat Enterprise Linux itself and thus derivatives like CentOS don't ship phpMyAdmin, but the Fedora-driven repository [Extra Packages for Enterprise Linux \(EPEL\)](#) is doing so, if it's enabled. But be aware that the configuration file is maintained in `/etc/phpMyAdmin/` and may differ in some ways from the official phpMyAdmin documentation.

## 3.2 Installing on Windows

The easiest way to get phpMyAdmin on Windows is using third party products which include phpMyAdmin together with a database and web server such as [XAMPP](#).

You can find more of such options at [Wikipedia](#).

## 3.3 Quick Install

1. Choose an appropriate distribution kit from the [phpmyadmin.net Downloads](#) page. Some kits contain only the English messages, others contain all languages. We'll assume you chose a kit whose name looks like `phpMyAdmin-x.x.x-all-languages.tar.gz`.
2. Ensure you have downloaded a genuine archive, see [Verifying phpMyAdmin releases](#).
3. Untar or unzip the distribution (be sure to unzip the subdirectories): `tar -xzf phpMyAdmin_x.x.x-all-languages.tar.gz` in your webserver's document root. If you don't have direct access to your document root, put the files in a directory on your local machine, and, after step 4, transfer the directory on your web server using, for example, ftp.
4. Ensure that all the scripts have the appropriate owner (if PHP is running in safe mode, having some scripts with an owner different from the owner of other scripts will be a problem). See [4.2 What's the preferred way of making phpMyAdmin secure against evil access?](#) and [1.26 I just installed phpMyAdmin in my document root of IIS but I get the error "No input file specified" when trying to run phpMyAdmin](#). for suggestions.
5. Now you must configure your installation. There are two methods that can be used. Traditionally, users have hand-edited a copy of `config.inc.php`, but now a wizard-style setup script is provided for those who prefer a graphical installation. Creating a `config.inc.php` is still a quick way to get started and needed for some advanced features.

### 3.3.1 Manually creating the file

To manually create the file, simply use your text editor to create the file `config.inc.php` (you can copy `config.sample.inc.php` to get a minimal configuration file) in the main (top-level) phpMyAdmin directory

(the one that contains `index.php`). phpMyAdmin first loads `libraries/config.default.php` and then overrides those values with anything found in `config.inc.php`. If the default value is okay for a particular setting, there is no need to include it in `config.inc.php`. You'll probably need only a few directives to get going; a simple configuration may look like this:

```
<?php
$cfg['blowfish_secret'] = 'ba17c1ec07d65003'; // use here a value of your choice

$i=0;
$i++;
$cfg['Servers'][$i]['auth_type']      = 'cookie';
?>
```

Or, if you prefer to not be prompted every time you log in:

```
<?php
$i=0;
$i++;
$cfg['Servers'][$i]['user']          = 'root';
$cfg['Servers'][$i]['password']      = 'cbb74bc'; // use here your password
$cfg['Servers'][$i]['auth_type']    = 'config';
?>
```

For a full explanation of possible configuration values, see the *Configuration* of this document.

### 3.3.2 Using Setup script

Instead of manually editing `config.inc.php`, you can use phpMyAdmin's setup feature. First you must manually create a folder `config` in the phpMyAdmin directory. This is a security measure. On a Linux/Unix system you can use the following commands:

```
cd phpMyAdmin
mkdir config                # create directory for saving
chmod o+rw config          # give it world writable permissions
```

And to edit an existing configuration, copy it over first:

```
cp config.inc.php config/   # copy current configuration for editing
chmod o+w config/config.inc.php # give it world writable permissions
```

**Note:** Debian and Ubuntu have simplified this setup and all you need to do is to execute `/usr/sbin/pma-configure`.

On other platforms, simply create the folder and ensure that your web server has read and write access to it. *1.26 I just installed phpMyAdmin in my document root of IIS but I get the error "No input file specified" when trying to run phpMyAdmin.* can help with this.

Next, open your browser and visit the location where you installed phpMyAdmin, with the `/setup` suffix. If you have an existing configuration, use the Load button to bring its content inside the setup panel. Note that **changes are not saved to disk until you explicitly choose "Save"** from the *Configuration* area of the screen. Normally the script saves the new `config.inc.php` to the `config/` directory, but if the webserver does not have the proper permissions you may see the error "Cannot load or save configuration." Ensure that the `config/` directory exists and has the proper permissions - or use the Download link to save the config file locally and upload it (via FTP or some similar means) to the proper location.

Once the file has been saved, it must be moved out of the `config/` directory and the permissions must be reset, again as a security measure:

```
mv config/config.inc.php .           # move file to current directory
chmod o-rw config.inc.php           # remove world read and write permissions
rm -rf config                        # remove not needed directory
```

**Note:** Debian and Ubuntu have simplified this setup and all you need to do is to execute `/usr/sbin/pma-secure`.

---

Now the file is ready to be used. You can choose to review or edit the file with your favorite editor, if you prefer to set some advanced options which the setup script does not provide.

1. If you are using the `auth_type` “config”, it is suggested that you protect the phpMyAdmin installation directory because using config does not require a user to enter a password to access the phpMyAdmin installation. Use of an alternate authentication method is recommended, for example with HTTP-AUTH in a `.htaccess` file or switch to using `auth_type` cookie or http. See the *ISPs, multi-user installations* for additional information, especially *4.4 phpMyAdmin always gives “Access denied” when using HTTP authentication.*
2. Open the main phpMyAdmin directory in your browser. phpMyAdmin should now display a welcome screen and your databases, or a login dialog if using *HTTP* or cookie authentication mode.
3. You should deny access to the `./libraries` and `./setup/lib` subfolders in your webserver configuration. Such configuration prevents from possible path exposure and cross side scripting vulnerabilities that might happen to be found in that code. For the Apache webserver, this is often accomplished with a `.htaccess` file in those directories.
4. It is generally a good idea to protect a public phpMyAdmin installation against access by robots as they usually can not do anything good there. You can do this using `robots.txt` file in root of your webserver or limit access by web server configuration, see *1.42 How can I prevent robots from accessing phpMyAdmin?*.

### 3.4 Verifying phpMyAdmin releases

Since July 2015 all phpMyAdmin releases are cryptographically signed by the releasing developer, who is currently Marc Delisle. His key id is 0x81AF644A, his PGP fingerprint is:

```
436F F188 4B1A 0C3F DCBF 0D79 FEFC 65D1 81AF 644A
```

and you can get more identification information from <https://keybase.io/lem9>. You should verify that the signature matches the archive you have downloaded. This way you can be sure that you are using the same code that was released.

Each archive is accompanied with `.asc` files which contains the PGP signature for it. Once you have both of them in the same folder, you can verify the signature:

```
$ gpg --verify phpMyAdmin-4.4.9-all-languages.zip.asc
gpg: Signature made Fri Jun 12 13:09:58 2015 CEST using RSA key ID 81AF644A
gpg: Can't check signature: No public key
```

As you can see gpg complains that it does not know the public key. At this point you should do one of the following steps:

- Download the keyring from [our download server](#), then import it with:

```
$ gpg --import phpmyadmin.keyring
```

- Download and import the key from one of the key servers:

```
$ gpg --keyserver hkp://pgp.mit.edu --recv-keys 81AF644A
gpg: requesting key 81AF644A from hkp server pgp.mit.edu
gpg: key 81AF644A: public key "Marc Delisle <marc@infomarc.info>" imported
gpg: no ultimately trusted keys found
gpg: Total number processed: 1
gpg:          imported: 1 (RSA: 1)
```

This will improve the situation a bit - at this point you can verify that the signature from the given key is correct but you still can not trust the name used in the key:

```
$ gpg --verify phpMyAdmin-4.4.9-all-languages.zip.asc
gpg: Signature made Fri Jun 12 13:09:58 2015 CEST using RSA key ID 81AF644A
gpg: Good signature from "Marc Delisle <marc@infomarc.info>" [unknown]
gpg: WARNING: This key is not certified with a trusted signature!
gpg:          There is no indication that the signature belongs to the owner.
Primary key fingerprint: 436F F188 4B1A 0C3F DCBF 0D79 FEFC 65D1 81AF 644A
```

The problem here is that anybody could issue the key with this name. You need to ensure that the key is actually owned by the mentioned person. The GNU Privacy Handbook covers this topic in the chapter [Validating other keys on your public keyring](#). The most reliable method is to meet the developer in person and exchange key fingerprints, however you can also rely on the web of trust. This way you can trust the key transitively through signatures of others, who have met the developer in person. For example you can see how [Marc's key links to Linus's key](#).

Once the key is trusted, the warning will not occur:

```
$ gpg --verify phpMyAdmin-4.4.9-all-languages.zip.asc
gpg: Signature made Fri Jun 12 13:09:58 2015 CEST using RSA key ID 81AF644A
gpg: Good signature from "Marc Delisle <marc@infomarc.info>" [full]
```

Should the signature be invalid (the archive has been changed), you would get a clear error regardless of the fact that the key is trusted or not:

```
$ gpg --verify phpMyAdmin-4.4.9-all-languages.zip.asc
gpg: Signature made Fri Jun 12 13:09:58 2015 CEST using RSA key ID 81AF644A
gpg: BAD signature from "Marc Delisle <marc@infomarc.info>" [unknown]
```

## 3.5 phpMyAdmin configuration storage

For a whole set of additional features (bookmarks, comments, *SQL*-history, tracking mechanism, *PDF*-generation, column contents transformation, etc.) you need to create a set of special tables. Those tables can be located in your own database, or in a central database for a multi-user installation (this database would then be accessed by the controluser, so no other user should have rights to it).

### 3.5.1 Zero configuration

In many cases, this database structure can be automatically created and configured. This is called “Zero Configuration” mode and can be particularly useful in shared hosting situations. “Zeroconf” mode is on by default, to disable set `$cfg['ZeroConf']` to false.

The following three scenarios are covered by the Zero Configuration mode:

- When entering a database where the configuration storage tables are not present, phpMyAdmin offers to create them from the Operations tab.
- When entering a database where the tables do already exist, the software automatically detects this and begins using them. This is the most common situation; after the tables are initially created automatically they are

continually used without disturbing the user; this is also most useful on shared hosting where the user is not able to edit `config.inc.php` and usually the user only has access to one database.

- When having access to multiple databases, if the user first enters the database containing the configuration storage tables then switches to another database, phpMyAdmin continues to use the tables from the first database; the user is not prompted to create more tables in the new database.

### 3.5.2 Manual configuration

Please look at your `./sql/` directory, where you should find a file called `create_tables.sql`. (If you are using a Windows server, pay special attention to *1.23 I'm running MySQL on a Win32 machine. Each time I create a new table the table and column names are changed to lowercase!*).

If you already had this infrastructure and:

- upgraded to MySQL 4.1.2 or newer, please use `sql/upgrade_tables_mysql_4_1_2+.sql`.
- upgraded to phpMyAdmin 4.3.0 or newer from 2.5.0 or newer ( $\leq 4.2.x$ ), please use `sql/upgrade_column_info_4_3_0+.sql`.

and then create new tables by importing `sql/create_tables.sql`.

You can use your phpMyAdmin to create the tables for you. Please be aware that you may need special (administrator) privileges to create the database and tables, and that the script may need some tuning, depending on the database name.

After having imported the `sql/create_tables.sql` file, you should specify the table names in your `config.inc.php` file. The directives used for that can be found in the *Configuration*.

You will also need to have a controluser ( `$\$cfg['Servers'][$i]['controluser']$`  and  `$\$cfg['Servers'][$i]['controlpass']$`  settings) with the proper rights to those tables. For example you can create it using following statement:

```
GRANT SELECT, INSERT, UPDATE, DELETE ON <pma_db>.* TO 'pma'@'localhost' IDENTIFIED BY 'pmapass';
```

## 3.6 Upgrading from an older version

**Never** extract the new version over an existing installation of phpMyAdmin; we had evidence of problems caused by this.

Simply copy `config.inc.php` from your previous installation into the newly unpacked one. Configuration files from old versions may require some tweaking as some options have been changed or removed. For compatibility with PHP 5.3 and later, remove a `set_magic_quotes_runtime(0);` statement that you might find near the end of your configuration file.

You should **not** copy `libraries/config.default.php` over `config.inc.php` because the default configuration file is version- specific.

If you have upgraded your MySQL server from a version previous to 4.1.2 to version 5.x or newer and if you use the phpMyAdmin configuration storage, you should run the *SQL* script found in `sql/upgrade_tables_mysql_4_1_2+.sql`.

If you have upgraded your phpMyAdmin to 4.3.0 or newer from 2.5.0 or newer ( $\leq 4.2.x$ ) and if you use the phpMyAdmin configuration storage, you should run the *SQL* script found in `sql/upgrade_column_info_4_3_0+.sql`.

Do not forget to clear the browser cache and to empty the old session by logging out and logging in again.



## 3.7 Using authentication modes

*HTTP* and cookie authentication modes are recommended in a **multi-user environment** where you want to give users access to their own database and don't want them to play around with others. Nevertheless be aware that MS Internet Explorer seems to be really buggy about cookies, at least till version 6. Even in a **single-user environment**, you might prefer to use *HTTP* or cookie mode so that your user/password pair are not in clear in the configuration file.

*HTTP* and cookie authentication modes are more secure: the MySQL login information does not need to be set in the phpMyAdmin configuration file (except possibly for the `$cfg['Servers'][$i]['controluser']`). However, keep in mind that the password travels in plain text, unless you are using the HTTPS protocol. In cookie mode, the password is stored, encrypted with the AES algorithm, in a temporary cookie.

Then each of the *true* users should be granted a set of privileges on a set of particular databases. Normally you shouldn't give global privileges to an ordinary user, unless you understand the impact of those privileges (for example, you are creating a superuser). For example, to grant the user *real\_user* with all privileges on the database *user\_base*:

```
GRANT ALL PRIVILEGES ON user_base.* TO 'real_user'@localhost IDENTIFIED BY 'real_password';
```

What the user may now do is controlled entirely by the MySQL user management system. With *HTTP* or cookie authentication mode, you don't need to fill the user/password fields inside the `$cfg['Servers']`.

### 3.7.1 HTTP authentication mode

- Uses *HTTP* Basic authentication method and allows you to log in as any valid MySQL user.
- Is supported with most PHP configurations. For *IIS (ISAPI)* support using *CGI PHP* see [1.32 Can I use HTTP authentication with IIS?](#), for using with Apache *CGI* see [1.35 Can I use HTTP authentication with Apache CGI?](#).
- See also [4.4 phpMyAdmin always gives "Access denied" when using HTTP authentication.](#) about not using the *.htaccess* mechanism along with '*HTTP*' authentication mode.

### 3.7.2 Cookie authentication mode

- Username and password are stored in cookies during the session and password is deleted when it ends.
- With this mode, the user can truly log out of phpMyAdmin and log back in with the same username.
- If you want to allow users to enter any hostname to connect (rather than only servers that are configured in `config.inc.php`), see the `$cfg['AllowArbitraryServer']` directive.
- As mentioned in the *Requirements* section, having the `mcrypt` extension will speed up access considerably, but is not required.

### 3.7.3 Signon authentication mode

- This mode is a convenient way of using credentials from another application to authenticate to phpMyAdmin to implement single signon solution.
- The other application has to store login information into session data (see `$cfg['Servers'][$i]['SignonSession']`) or you need to implement script to return the credentials (see `$cfg['Servers'][$i]['SignonScript']`).
- When no credentials are available, the user is being redirected to `$cfg['Servers'][$i]['SignonURL']`, where you should handle the login process.

The very basic example of saving credentials in a session is available as `examples/signon.php`:

Alternatively you can also use this way to integrate with OpenID as shown in `examples/openid.php`:

If you intend to pass the credentials using some other means than, you have to implement wrapper in PHP to get that data and set it to `$cfg['Servers'][$i]['SignonScript']`. There is very minimal example in `examples/signon-script.php`:

**See also:**

```
$cfg['Servers'][$i]['auth_type'],           $cfg['Servers'][$i]['SignonSession'],
$cfg['Servers'][$i]['SignonScript'], $cfg['Servers'][$i]['SignonURL']
```

### 3.7.4 Config authentication mode

- This mode is sometimes the less secure one because it requires you to fill the `$cfg['Servers'][$i]['user']` and `$cfg['Servers'][$i]['password']` fields (and as a result, anyone who can read your `config.inc.php` can discover your username and password).
- In the *ISPs, multi-user installations* section, there is an entry explaining how to protect your configuration file.
- For additional security in this mode, you may wish to consider the Host authentication `$cfg['Servers'][$i]['AllowDeny']['order']` and `$cfg['Servers'][$i]['AllowDeny']['rules']` configuration directives.
- Unlike cookie and http, does not require a user to log in when first loading the phpMyAdmin site. This is by design but could allow any user to access your installation. Use of some restriction method is suggested, perhaps a `.htaccess` file with the HTTP-AUTH directive or disallowing incoming HTTP requests at one's router or firewall will suffice (both of which are beyond the scope of this manual but easily searchable with Google).

### 3.7.5 Swekey authentication mode

The Swekey is a low cost authentication USB key that can be used in web applications. When Swekey authentication is activated, phpMyAdmin requires the users's Swekey to be plugged before entering the login page (currently supported for cookie authentication mode only). Swekey Authentication is disabled by default. To enable it, add the following line to `config.inc.php`:

```
$cfg['Servers'][$i]['auth_swekey_config'] = '/etc/swekey.conf';
```

You then have to create the `swekey.conf` file that will associate each user with their Swekey Id. It is important to place this file outside of your web server's document root (in the example, it is located in `/etc`). Feel free to use it with your own users' information. If you want to purchase a Swekey please visit [https://www.phpmyadmin.net/auth\\_key/](https://www.phpmyadmin.net/auth_key/) since this link provides funding for phpMyAdmin.

A self documented sample file is provided in the file `examples/swekey.sample.conf`:

**See also:**

```
$cfg['Servers'][$i]['auth_swekey_config']
```

## 3.8 Securing your phpMyAdmin installation

The phpMyAdmin team tries hard to make the application secure, however there are always ways to make your installation more secure:

- Remove the `setup` directory from phpMyAdmin, you will probably not use it after the initial setup.

- Properly choose an authentication method - *Cookie authentication mode* is probably the best choice for shared hosting.
- In case you don't want all MySQL users to be able to access phpMyAdmin, you can use `$cfg['Servers'][$i]['AllowDeny']['rules']` to limit them.
- Consider hiding phpMyAdmin behind an authentication proxy, so that users need to authenticate prior to providing MySQL credentials to phpMyAdmin. You can achieve this by configuring your web server to request HTTP authentication. For example in Apache this can be done by:

```
AuthType Basic
AuthName "Restricted Access"
AuthUserFile /usr/share/phpmyadmin/passwd
Require valid-user
```

Once you have changed configuration, you need to create list of users which can authenticate. This can be done using **htpasswd** utility:

```
htpasswd -c /usr/share/phpmyadmin/passwd username
```

- If you are afraid of automated attacks, enabling Captcha by `$cfg['CaptchaLoginPublicKey']` and `$cfg['CaptchaLoginPrivateKey']` might be an option.



---

## Configuration

---

Almost all configurable data is placed in `config.inc.php`. If this file does not exist, please refer to the *Installation* section to create one. This file only needs to contain the parameters you want to change from their corresponding default value in `libraries/config.default.php`.

If a directive is missing from your file, you can just add another line with the file. This file is for over-writing the defaults; if you wish to use the default value there's no need to add a line here.

The parameters which relate to design (like colors) are placed in `themes/themename/layout.inc.php`. You might also want to create `config.footer.inc.php` and `config.header.inc.php` files to add your site specific code to be included on start and end of each page.

---

**Note:** Some distributions (eg. Debian or Ubuntu) store `config.inc.php` in `/etc/phpmyadmin` instead of within phpMyAdmin sources.

---

**Warning:** *Mac* users should note that if you are on a version before *Mac OS X*, PHP does not seem to like *Mac* end of lines character (`\r`). So ensure you choose the option that allows to use the \*nix end of line character (`\n`) in your text editor before saving a script you have modified.

### 4.1 Basic settings

`$cfg['PmaAbsoluteUri']`

**Type** string

**Default value** ''

Sets here the complete *URL* (with full path) to your phpMyAdmin installation's directory. E.g. `http://www.example.net/path_to_your_phpMyAdmin_directory/`. Note also that the *URL* on most of web servers are case-sensitive. Don't forget the trailing slash at the end.

Starting with version 2.3.0, it is advisable to try leaving this blank. In most cases phpMyAdmin automatically detects the proper setting. Users of port forwarding will need to set `$cfg['PmaAbsoluteUri']` (*more info*).

A good test is to browse a table, edit a row and save it. There should be an error message if phpMyAdmin is having trouble auto-detecting the correct value. If you get an error that this must be set or if the autodetect code fails to detect your path, please post a bug report on our bug tracker so we can improve the code.

**See also:**

*1.40 When accessing phpMyAdmin via an Apache reverse proxy, cookie login does not work.*

**`$cfg['PmaNoRelation_DisableWarning']`**

**Type** boolean

**Default value** false

Starting with version 2.3.0 phpMyAdmin offers a lot of features to work with master / foreign – tables (see `$cfg['Servers'][$i]['pmadb']`).

If you tried to set this up and it does not work for you, have a look on the *Structure* page of one database where you would like to use it. You will find a link that will analyze why those features have been disabled.

If you do not want to use those features set this variable to `true` to stop this message from appearing.

**`$cfg['SuhosinDisableWarning']`**

**Type** boolean

**Default value** false

A warning is displayed on the main page if Suhosin is detected.

You can set this parameter to `true` to stop this message from appearing.

**`$cfg['LoginCookieValidityDisableWarning']`**

**Type** boolean

**Default value** false

A warning is displayed on the main page if the PHP parameter `session.gc_maxlifetime` is lower than cookie validity configured in phpMyAdmin.

You can set this parameter to `true` to stop this message from appearing.

**`$cfg['ServerLibraryDifference_DisableWarning']`**

**Type** boolean

**Default value** false

A warning is displayed on the main page if there is a difference between the MySQL library and server version.

You can set this parameter to `true` to stop this message from appearing.

**`$cfg['ReservedWordDisableWarning']`**

**Type** boolean

**Default value** false

This warning is displayed on the Structure page of a table if one or more column names match with words which are MySQL reserved.

If you want to turn off this warning, you can set it to `true` and warning will no longer be displayed.

**`$cfg['TranslationWarningThreshold']`**

**Type** integer

**Default value** 80

Show warning about incomplete translations on certain threshold.

**`$cfg['SendErrorReports']`**

**Type** string

**Default value** 'ask'

Sets the default behavior for JavaScript error reporting.

Whenever an error is detected in the JavaScript execution, an error report may be sent to the phpMyAdmin team if the user agrees.

The default setting of `'ask'` will ask the user everytime there is a new error report. However you can set this parameter to `'always'` to send error reports without asking for confirmation or you can set it to `'never'` to never send error reports.

This directive is available both in the configuration file and in users preferences. If the person in charge of a multi-user installation prefers to disable this feature for all users, a value of `'never'` should be set, and the `$cfg['UserprefsDisallow']` directive should contain `'SendErrorReports'` in one of its array values.

#### `$cfg['ConsoleEnterExecutes']`

**Type** boolean

**Default value** false

Setting this to `true` allows the user to execute queries by pressing Enter instead of Ctrl+Enter. A new line can be inserted by pressing Shift + Enter.

The behaviour of the console can be temporarily changed using console's settings interface.

#### `$cfg['AllowThirdPartyFraming']`

**Type** boolean

**Default value** false

Setting this to `true` allows phpMyAdmin to be included inside a frame, and is a potential security hole allowing cross-frame scripting attacks or clickjacking.

## 4.2 Server connection settings

### `$cfg['Servers']`

**Type** array

**Default value** one server array with settings listed below

Since version 1.4.2, phpMyAdmin supports the administration of multiple MySQL servers. Therefore, a `$cfg['Servers']`-array has been added which contains the login information for the different servers. The first `$cfg['Servers'][$i]['host']` contains the hostname of the first server, the second `$cfg['Servers'][$i]['host']` the hostname of the second server, etc. In `libraries/config.default.php`, there is only one section for server definition, however you can put as many as you need in `config.inc.php`, copy that block or needed parts (you don't have to define all settings, just those you need to change).

---

**Note:** The `$cfg['Servers']` array starts with `$cfg['Servers'][1]`. Do not use `$cfg['Servers'][0]`. If you want more than one server, just copy following section (including `$i` incrementation) several times. There is no need to define full server array, just define values you need to change.

---

#### `$cfg['Servers'][$i]['host']`

**Type** string

**Default value** `'localhost'`

The hostname or *IP* address of your  $i$ -th MySQL-server. E.g. localhost.

Possible values are:

- hostname, e.g., 'localhost' or 'mydb.example.org'
- IP address, e.g., '127.0.0.1' or '192.168.10.1'
- dot - '.', i.e., use named pipes on windows systems
- empty - '', disables this server

---

**Note:**

**phpMyAdmin supports connecting to MySQL servers reachable via IPv6 only.** To connect to an IPv6 MySQL server, enter its IPv6 address in this field.

---

**\$cfg['Servers'][\$i]['port']**

**Type** string

**Default value** ''

The port-number of your  $i$ -th MySQL-server. Default is 3306 (leave blank).

---

**Note:** If you use localhost as the hostname, MySQL ignores this port number and connects with the socket, so if you want to connect to a port different from the default port, use 127.0.0.1 or the real hostname in `$cfg['Servers'][$i]['host']`.

---

**\$cfg['Servers'][\$i]['socket']**

**Type** string

**Default value** ''

The path to the socket to use. Leave blank for default. To determine the correct socket, check your MySQL configuration or, using the `mysql` command-line client, issue the `status` command. Among the resulting information displayed will be the socket used.

**\$cfg['Servers'][\$i]['ssl']**

**Type** boolean

**Default value** false

Whether to enable SSL for the connection between phpMyAdmin and the MySQL server.

When using the 'mysql' extension, none of the remaining 'ssl...' configuration options apply.

We strongly recommend the 'mysql\_i' extension when using this option.

**\$cfg['Servers'][\$i]['ssl\_key']**

**Type** string

**Default value** NULL

Path to the key file when using SSL for connecting to the MySQL server.

For example:

```
$cfg['Servers'][$i]['ssl_key'] = '/etc/mysql/server-key.pem';
```

**\$cfg['Servers'][\$i]['ssl\_cert']**

**Type** string



**Default value** NULL

Path to the cert file when using SSL for connecting to the MySQL server.

`$cfg['Servers'][$i]['ssl_ca']`

**Type** string

**Default value** NULL

Path to the CA file when using SSL for connecting to the MySQL server.

`$cfg['Servers'][$i]['ssl_ca_path']`

**Type** string

**Default value** NULL

Directory containing trusted SSL CA certificates in PEM format.

`$cfg['Servers'][$i]['ssl_ciphers']`

**Type** string

**Default value** NULL

List of allowable ciphers for SSL connections to the MySQL server.

`$cfg['Servers'][$i]['connect_type']`

**Type** string

**Default value** 'tcp'

What type connection to use with the MySQL server. Your options are 'socket' and 'tcp'. It defaults to tcp as that is nearly guaranteed to be available on all MySQL servers, while sockets are not supported on some platforms. To use the socket mode, your MySQL server must be on the same machine as the Web server.

`$cfg['Servers'][$i]['compress']`

**Type** boolean

**Default value** false

Whether to use a compressed protocol for the MySQL server connection or not (experimental).

`$cfg['Servers'][$i]['controlhost']`

**Type** string

**Default value** ''

Permits to use an alternate host to hold the configuration storage data.

`$cfg['Servers'][$i]['controlport']`

**Type** string

**Default value** ''

Permits to use an alternate port to connect to the host that holds the configuration storage.

`$cfg['Servers'][$i]['controluser']`

**Type** string

**Default value** ''

`$cfg['Servers'][$i]['controlpass']`

**Type** string

**Default value** ''

This special account is used for 2 distinct purposes: to make possible all relational features (see `$cfg['Servers'][$i]['pmadb']`).

Changed in version 2.2.5: those were called `stduser` and `stdpass`

**See also:**

*Installation, Using authentication modes, phpMyAdmin configuration storage*

**`$cfg['Servers'][$i]['auth_type']`**

**Type** string

**Default value** 'cookie'

Whether config or cookie or *HTTP* or signon authentication should be used for this server.

- 'config' authentication (`$auth_type = 'config'`) is the plain old way: username and password are stored in `config.inc.php`.
- 'cookie' authentication mode (`$auth_type = 'cookie'`) allows you to log in as any valid MySQL user with the help of cookies.
- 'http' authentication allows you to log in as any valid MySQL user via HTTP-Auth.
- 'signon' authentication mode (`$auth_type = 'signon'`) allows you to log in from prepared PHP session data or using supplied PHP script.

**See also:**

*Using authentication modes*

**`$cfg['Servers'][$i]['auth_http_realm']`**

**Type** string

**Default value** ''

When using `auth_type = http`, this field allows to define a custom *HTTP* Basic Auth Realm which will be displayed to the user. If not explicitly specified in your configuration, a string combined of "phpMyAdmin " and either `$cfg['Servers'][$i]['verbose']` or `$cfg['Servers'][$i]['host']` will be used.

**`$cfg['Servers'][$i]['auth_swekey_config']`**

**Type** string

**Default value** ''

The name of the file containing *Swekey authentication mode* ids and login names for hardware authentication. Leave empty to deactivate this feature.

**`$cfg['Servers'][$i]['user']`**

**Type** string

**Default value** 'root'

**`$cfg['Servers'][$i]['password']`**

**Type** string

**Default value** ''

When using `$cfg['Servers'][$i]['auth_type']` set to 'config', this is the user/password-pair which phpMyAdmin will use to connect to the MySQL server. This user/password pair is not needed when *HTTP* or cookie authentication is used and should be empty.

`$cfg['Servers'][$i]['nopassword']`

**Type** boolean

**Default value** false

Allow attempt to log in without password when a login with password fails. This can be used together with http authentication, when authentication is done some other way and phpMyAdmin gets user name from auth and uses empty password for connecting to MySQL. Password login is still tried first, but as fallback, no password method is tried.

`$cfg['Servers'][$i]['only_db']`

**Type** string or array

**Default value** ''

If set to a (an array of) database name(s), only this (these) database(s) will be shown to the user. Since phpMyAdmin 2.2.1, this/these database(s) name(s) may contain MySQL wildcards characters (“\_” and “%”): if you want to use literal instances of these characters, escape them (I.E. use 'my\\_db' and not 'my\_db').

This setting is an efficient way to lower the server load since the latter does not need to send MySQL requests to build the available database list. But **it does not replace the privileges rules of the MySQL database server**. If set, it just means only these databases will be displayed but **not that all other databases can't be used**.

An example of using more that one database:

```
$cfg['Servers'][$i]['only_db'] = array('db1', 'db2');
```

Changed in version 4.0.0: Previous versions permitted to specify the display order of the database names via this directive.

`$cfg['Servers'][$i]['hide_db']`

**Type** string

**Default value** ''

Regular expression for hiding some databases from unprivileged users. This only hides them from listing, but a user is still able to access them (using, for example, the SQL query area). To limit access, use the MySQL privilege system. For example, to hide all databases starting with the letter “a”, use

```
$cfg['Servers'][$i]['hide_db'] = '^a';
```

and to hide both “db1” and “db2” use

```
$cfg['Servers'][$i]['hide_db'] = '^(db1|db2)$';
```

More information on regular expressions can be found in the [PCRE pattern syntax](#) portion of the PHP reference manual.

`$cfg['Servers'][$i]['verbose']`

**Type** string

**Default value** ''

Only useful when using phpMyAdmin with multiple server entries. If set, this string will be displayed instead of the hostname in the pull-down menu on the main page. This can be useful if you want to show only certain databases on your system, for example. For HTTP auth, all non-US-ASCII characters will be stripped.

`$cfg['Servers'][$i]['pmadb']`

**Type** string

**Default value** ''

The name of the database containing the phpMyAdmin configuration storage.

See the *phpMyAdmin configuration storage* section in this document to see the benefits of this feature, and for a quick way of creating this database and the needed tables.

If you are the only user of this phpMyAdmin installation, you can use your current database to store those special tables; in this case, just put your current database name in `$cfg['Servers'][$i]['pmadb']`. For a multi-user installation, set this parameter to the name of your central database containing the phpMyAdmin configuration storage.

#### `$cfg['Servers'][$i]['bookmarktable']`

**Type** string

**Default value** ''

Since release 2.2.0 phpMyAdmin allows users to bookmark queries. This can be useful for queries you often run. To allow the usage of this functionality:

- set up `$cfg['Servers'][$i]['pmadb']` and the phpMyAdmin configuration storage
- enter the table name in `$cfg['Servers'][$i]['bookmarktable']`

#### `$cfg['Servers'][$i]['relation']`

**Type** string

**Default value** ''

Since release 2.2.4 you can describe, in a special 'relation' table, which column is a key in another table (a foreign key). phpMyAdmin currently uses this to:

- make clickable, when you browse the master table, the data values that point to the foreign table;
- display in an optional tool-tip the "display column" when browsing the master table, if you move the mouse to a column containing a foreign key (use also the 'table\_info' table); (see *6.7 How can I use the "display column" feature?*)
- in edit/insert mode, display a drop-down list of possible foreign keys (key value and "display column" are shown) (see *6.21 In edit/insert mode, how can I see a list of possible values for a column, based on some foreign table?*)
- display links on the table properties page, to check referential integrity (display missing foreign keys) for each described key;
- in query-by-example, create automatic joins (see *6.6 How can I use the relation table in Query-by-example?*)
- enable you to get a *PDF* schema of your database (also uses the table\_coords table).

The keys can be numeric or character.

To allow the usage of this functionality:

- set up `$cfg['Servers'][$i]['pmadb']` and the phpMyAdmin configuration storage
- put the relation table name in `$cfg['Servers'][$i]['relation']`
- now as normal user open phpMyAdmin and for each one of your tables where you want to use this feature, click *Structure/Relation view/* and choose foreign columns.

---

**Note:** In the current version, `master_db` must be the same as `foreign_db`. Those columns have been put in future development of the cross-db relations.

---

#### `$cfg['Servers'][$i]['table_info']`

**Type** string

**Default value** ''

Since release 2.3.0 you can describe, in a special 'table\_info' table, which column is to be displayed as a tool-tip when moving the cursor over the corresponding key. This configuration variable will hold the name of this special table. To allow the usage of this functionality:

- set up `$cfg['Servers'][$i]['pmadb']` and the phpMyAdmin configuration storage
- put the table name in `$cfg['Servers'][$i]['table_info']` (e.g. pma\_\_table\_info)
- then for each table where you want to use this feature, click “Structure/Relation view/Choose column to display” to choose the column.

**See also:**

*6.7 How can I use the “display column” feature?*

`$cfg['Servers'][$i]['table_coords']`

**Type** string

**Default value** ''

`$cfg['Servers'][$i]['pdf_pages']`

**Type** string

**Default value** ''

Since release 2.3.0 you can have phpMyAdmin create *PDF* pages showing the relations between your tables. Further, the designer interface permits visually managing the relations. To do this it needs two tables “pdf\_pages” (storing information about the available *PDF* pages) and “table\_coords” (storing coordinates where each table will be placed on a *PDF* schema output). You must be using the “relation” feature.

To allow the usage of this functionality:

- set up `$cfg['Servers'][$i]['pmadb']` and the phpMyAdmin configuration storage
- put the correct table names in `$cfg['Servers'][$i]['table_coords']` and `$cfg['Servers'][$i]['pdf_pages']`

**See also:**

*6.8 How can I produce a PDF schema of my database?.*

`$cfg['Servers'][$i]['column_info']`

**Type** string

**Default value** ''

This part requires a content update! Since release 2.3.0 you can store comments to describe each column for each table. These will then be shown on the “printview”.

Starting with release 2.5.0, comments are consequently used on the table property pages and table browse view, showing up as tool-tips above the column name (properties page) or embedded within the header of table in browse view. They can also be shown in a table dump. Please see the relevant configuration directives later on.

Also new in release 2.5.0 is a MIME- transformation system which is also based on the following table structure. See *Transformations* for further information. To use the MIME- transformation system, your column\_info table has to have the three new columns ‘mimetype’, ‘transformation’, ‘transformation\_options’.

Starting with release 4.3.0, a new input-oriented transformation system has been introduced. Also, backward compatibility code used in the old transformations system was removed. As a result, an update to column\_info table is necessary for previous transformations and the new input-oriented transformation system to

work. phpMyAdmin will upgrade it automatically for you by analyzing your current `column_info` table structure. However, if something goes wrong with the auto-upgrade then you can use the SQL script found in `./sql/upgrade_column_info_4_3_0+.sql` to upgrade it manually.

To allow the usage of this functionality:

- set up `$cfg['Servers'][$i]['pmadb']` and the phpMyAdmin configuration storage
- put the table name in `$cfg['Servers'][$i]['column_info']` (e.g. `pma__column_info`)
- to update your PRE-2.5.0 `Column_comments` table use this: and remember that the Variable in `config.inc.php` has been renamed from `$cfg['Servers'][$i]['column_comments']` to `$cfg['Servers'][$i]['column_info']`

```
ALTER TABLE `pma__column_comments`
ADD `mimetype` VARCHAR( 255 ) NOT NULL,
ADD `transformation` VARCHAR( 255 ) NOT NULL,
ADD `transformation_options` VARCHAR( 255 ) NOT NULL;
```

- to update your PRE-4.3.0 `Column_info` table manually use this `./sql/upgrade_column_info_4_3_0+.sql` SQL script.

---

**Note:** For auto-upgrade functionality to work, your `$cfg['Servers'][$i]['controluser']` must have ALTER privilege on `phpmyadmin` database. See the [MySQL documentation for GRANT](#) on how to GRANT privileges to a user.

---

#### `$cfg['Servers'][$i]['history']`

**Type** string

**Default value** ''

Since release 2.5.0 you can store your *SQL* history, which means all queries you entered manually into the phpMyAdmin interface. If you don't want to use a table-based history, you can use the JavaScript-based history.

Using that, all your history items are deleted when closing the window. Using `$cfg['QueryHistoryMax']` you can specify an amount of history items you want to have on hold. On every login, this list gets cut to the maximum amount.

The query history is only available if JavaScript is enabled in your browser.

To allow the usage of this functionality:

- set up `$cfg['Servers'][$i]['pmadb']` and the phpMyAdmin configuration storage
- put the table name in `$cfg['Servers'][$i]['history']` (e.g. `pma__history`)

#### `$cfg['Servers'][$i]['recent']`

**Type** string

**Default value** ''

Since release 3.5.0 you can show recently used tables in the navigation panel. It helps you to jump across table directly, without the need to select the database, and then select the table. Using `$cfg['NumRecentTables']` you can configure the maximum number of recent tables shown. When you select a table from the list, it will jump to the page specified in `$cfg['NavigationTreeDefaultTabTable']`.

Without configuring the storage, you can still access the recently used tables, but it will disappear after you logout.

To allow the usage of this functionality persistently:

- set up `$cfg['Servers'][$i]['pmadb']` and the phpMyAdmin configuration storage
- put the table name in `$cfg['Servers'][$i]['recent']` (e.g. `pma__recent`)

**`$cfg['Servers'][$i]['table_uiprefs']`****Type** string**Default value** ''

Since release 3.5.0 phpMyAdmin can be configured to remember several things (sorted column `$cfg['RememberSorting']`, column order, and column visibility from a database table) for browsing tables. Without configuring the storage, these features still can be used, but the values will disappear after you logout.

To allow the usage of these functionality persistently:

- set up `$cfg['Servers'][$i]['pmadb']` and the phpMyAdmin configuration storage
- put the table name in `$cfg['Servers'][$i]['table_uiprefs']` (e.g. `pma__table_uiprefs`)

**`$cfg['Servers'][$i]['users']`****Type** string**Default value** ''**`$cfg['Servers'][$i]['usergroups']`****Type** string**Default value** ''

Since release 4.1.0 you can create different user groups with menu items attached to them. Users can be assigned to these groups and the logged in user would only see menu items configured to the usergroup he is assigned to. To do this it needs two tables “usergroups” (storing allowed menu items for each user group) and “users” (storing users and their assignments to user groups).

To allow the usage of this functionality:

- set up `$cfg['Servers'][$i]['pmadb']` and the phpMyAdmin configuration storage
- put the correct table names in `$cfg['Servers'][$i]['users']` (e.g. `pma__users`) and `$cfg['Servers'][$i]['usergroups']` (e.g. `pma__usergroups`)

**`$cfg['Servers'][$i]['navigationhiding']`****Type** string**Default value** ''

Since release 4.1.0 you can hide/show items in the navigation tree.

To allow the usage of this functionality:

- set up `$cfg['Servers'][$i]['pmadb']` and the phpMyAdmin configuration storage
- put the table name in `$cfg['Servers'][$i]['navigationhiding']` (e.g. `pma__navigationhiding`)

**`$cfg['Servers'][$i]['central_columns']`****Type** string**Default value** ''

Since release 4.3.0 you can have a central list of columns per database. You can add/remove columns to the list as per your requirement. These columns in the central list will be available to use while you create a new column for a table or create a table itself. You can select a column from central list while creating a new column, it will save you from writing the same column definition over again or from writing different names for similar column.

To allow the usage of this functionality:

- set up `$cfg['Servers'][$i]['pmadb']` and the phpMyAdmin configuration storage
- put the table name in `$cfg['Servers'][$i]['central_columns']` (e.g. `pma__central_columns`)

#### `$cfg['Servers'][$i]['designer_settings']`

**Type** string

**Default value** ''

Since release 4.5.0 your designer settings can be remembered. Your choice regarding 'Angular/Direct Links', 'Snap to Grid', 'Toggle Relation Lines', 'Small/Big All', 'Move Menu' and 'Pin Text' can be remembered persistently.

To allow the usage of this functionality:

- set up `$cfg['Servers'][$i]['pmadb']` and the phpMyAdmin configuration storage
- put the table name in `$cfg['Servers'][$i]['designer_settings']` (e.g. `pma__designer_settings`)

#### `$cfg['Servers'][$i]['savedsearches']`

**Type** string

**Default value** ''

Since release 4.2.0 you can save and load query-by-example searches from the Database > Query panel.

To allow the usage of this functionality:

- set up `$cfg['Servers'][$i]['pmadb']` and the phpMyAdmin configuration storage
- put the table name in `$cfg['Servers'][$i]['savedsearches']` (e.g. `pma__savedsearches`)

#### `$cfg['Servers'][$i]['export_templates']`

**Type** string

**Default value** ''

Since release 4.5.0 you can save and load export templates.

To allow the usage of this functionality:

- set up `$cfg['Servers'][$i]['pmadb']` and the phpMyAdmin configuration storage
- put the table name in `$cfg['Servers'][$i]['export_templates']` (e.g. `pma__export_templates`)

#### `$cfg['Servers'][$i]['tracking']`

**Type** string

**Default value** ''



Since release 3.3.x a tracking mechanism is available. It helps you to track every *SQL* command which is executed by phpMyAdmin. The mechanism supports logging of data manipulation and data definition statements. After enabling it you can create versions of tables.

The creation of a version has two effects:

- phpMyAdmin saves a snapshot of the table, including structure and indexes.
- phpMyAdmin logs all commands which change the structure and/or data of the table and links these commands with the version number.

Of course you can view the tracked changes. On the *Tracking* page a complete report is available for every version. For the report you can use filters, for example you can get a list of statements within a date range. When you want to filter usernames you can enter \* for all names or you enter a list of names separated by ','. In addition you can export the (filtered) report to a file or to a temporary database.

To allow the usage of this functionality:

- set up `$cfg['Servers'][$i]['pmadb']` and the phpMyAdmin configuration storage
- put the table name in `$cfg['Servers'][$i]['tracking']` (e.g. pma\_\_tracking)

`$cfg['Servers'][$i]['tracking_version_auto_create']`

**Type** boolean

**Default value** false

Whether the tracking mechanism creates versions for tables and views automatically.

If this is set to true and you create a table or view with

- CREATE TABLE ...
- CREATE VIEW ...

and no version exists for it, the mechanism will create a version for you automatically.

`$cfg['Servers'][$i]['tracking_default_statements']`

**Type** string

**Default value** 'CREATE TABLE,ALTER TABLE,DROP TABLE,RENAME TABLE,CREATE INDEX,DROP INDEX,INSERT,UPDATE,DELETE,TRUNCATE,REPLACE,CREATE VIEW,ALTER VIEW,DROP VIEW,CREATE DATABASE,ALTER DATABASE,DROP DATABASE'

Defines the list of statements the auto-creation uses for new versions.

`$cfg['Servers'][$i]['tracking_add_drop_view']`

**Type** boolean

**Default value** true

Whether a DROP VIEW IF EXISTS statement will be added as first line to the log when creating a view.

`$cfg['Servers'][$i]['tracking_add_drop_table']`

**Type** boolean

**Default value** true

Whether a DROP TABLE IF EXISTS statement will be added as first line to the log when creating a table.

`$cfg['Servers'][$i]['tracking_add_drop_database']`

**Type** boolean

**Default value** true

Whether a DROP DATABASE IF EXISTS statement will be added as first line to the log when creating a database.

`$cfg['Servers'][$i]['userconfig']`

**Type** string

**Default value** ''

Since release 3.4.x phpMyAdmin allows users to set most preferences by themselves and store them in the database.

If you don't allow for storing preferences in `$cfg['Servers'][$i]['pmadb']`, users can still personalize phpMyAdmin, but settings will be saved in browser's local storage, or, if it is unavailable, until the end of session.

To allow the usage of this functionality:

- set up `$cfg['Servers'][$i]['pmadb']` and the phpMyAdmin configuration storage
- put the table name in `$cfg['Servers'][$i]['userconfig']`

`$cfg['Servers'][$i]['MaxTableUiprefs']`

**Type** integer

**Default value** 100

Maximum number of rows saved in `$cfg['Servers'][$i]['table_uiprefs']` table.

When tables are dropped or renamed, `$cfg['Servers'][$i]['table_uiprefs']` may contain invalid data (referring to tables which no longer exist). We only keep this number of newest rows in `$cfg['Servers'][$i]['table_uiprefs']` and automatically delete older rows.

`$cfg['Servers'][$i]['SessionTimeZone']`

**Type** string

**Default value** ''

Sets the time zone used by phpMyAdmin. Leave blank to use the time zone of your database server. Possible values are explained at <http://dev.mysql.com/doc/refman/5.7/en/time-zone-support.html>

This is useful when your database server uses a time zone which is different from the time zone you want to use in phpMyAdmin.

`$cfg['Servers'][$i]['AllowRoot']`

**Type** boolean

**Default value** true

Whether to allow root access. This is just a shortcut for the `$cfg['Servers'][$i]['AllowDeny']['rules']` below.

`$cfg['Servers'][$i]['AllowNoPassword']`

**Type** boolean

**Default value** false

Whether to allow logins without a password. The default value of `false` for this parameter prevents unintended access to a MySQL server with was left with an empty password for root or on which an anonymous (blank) user is defined.

`$cfg['Servers'][$i]['AllowDeny']['order']`

**Type** string

**Default value** ''

If your rule order is empty, then *IP* authorization is disabled.

If your rule order is set to 'deny,allow' then the system applies all deny rules followed by allow rules. Access is allowed by default. Any client which does not match a Deny command or does match an Allow command will be allowed access to the server.

If your rule order is set to 'allow,deny' then the system applies all allow rules followed by deny rules. Access is denied by default. Any client which does not match an Allow directive or does match a Deny directive will be denied access to the server.

If your rule order is set to 'explicit', authorization is performed in a similar fashion to rule order 'deny,allow', with the added restriction that your host/username combination **must** be listed in the *allow* rules, and not listed in the *deny* rules. This is the **most** secure means of using Allow/Deny rules, and was available in Apache by specifying allow and deny rules without setting any order.

Please also see `$cfg['TrustedProxies']` for detecting IP address behind proxies.

`$cfg['Servers'][$i]['AllowDeny']['rules']`

**Type** array of strings

**Default value** array()

The general format for the rules is as such:

```
<'allow' | 'deny'> <username> [from] <ipmask>
```

If you wish to match all users, it is possible to use a '%' as a wildcard in the *username* field.

There are a few shortcuts you can use in the *ipmask* field as well (please note that those containing `SERVER_ADDRESS` might not be available on all web servers):

```
'all' -> 0.0.0.0/0
'localhost' -> 127.0.0.1/8
'localnetA' -> SERVER_ADDRESS/8
'localnetB' -> SERVER_ADDRESS/16
'localnetC' -> SERVER_ADDRESS/24
```

Having an empty rule list is equivalent to either using 'allow % from all' if your rule order is set to 'deny,allow' or 'deny % from all' if your rule order is set to 'allow,deny' or 'explicit'.

For the *IP address* matching system, the following work:

- xxx.xxx.xxx.xxx (an exact *IP address*)
- xxx.xxx.xxx.[yyy-zzz] (an *IP address* range)
- xxx.xxx.xxx.xxx/nn (CIDR, Classless Inter-Domain Routing type *IP* addresses)

But the following does not work:

- xxx.xxx.xxx.xx[yyy-zzz] (partial *IP* address range)

For *IPv6* addresses, the following work:

- xxxx:xxxx:xxxx:xxxx:xxxx:xxxx:xxxx:xxxx (an exact *IPv6* address)
- xxxx:xxxx:xxxx:xxxx:xxxx:xxxx:xxxx:[yyyy-zzzz] (an *IPv6* address range)
- xxxx:xxxx:xxxx:xxxx/nn (CIDR, Classless Inter-Domain Routing type *IPv6* addresses)

But the following does not work:

•xxxx:xxxx:xxxx:xxxx:xxxx:xxxx:xxxx:xx[yy-zzz] (partial *IPv6* address range)

`$cfg['Servers'][$i]['DisableIS']`

**Type** boolean

**Default value** false

Disable using `INFORMATION_SCHEMA` to retrieve information (use `SHOW` commands instead), because of speed issues when many databases are present. Currently used in some parts of the code, more to come.

`$cfg['Servers'][$i]['SignonScript']`

**Type** string

**Default value** ''

Name of PHP script to be sourced and executed to obtain login credentials. This is alternative approach to session based single signon. The script has to provide a function called `get_login_credentials` which returns list of username and password, accepting single parameter of existing username (can be empty). See `examples/signon-script.php` for an example:

**See also:**

*Signon authentication mode*

`$cfg['Servers'][$i]['SignonSession']`

**Type** string

**Default value** ''

Name of session which will be used for signon authentication method. You should use something different than `phpMyAdmin`, because this is session which `phpMyAdmin` uses internally. Takes effect only if `$cfg['Servers'][$i]['SignonScript']` is not configured.

**See also:**

*Signon authentication mode*

`$cfg['Servers'][$i]['SignonURL']`

**Type** string

**Default value** ''

*URL* where user will be redirected to log in for signon authentication method. Should be absolute including protocol.

**See also:**

*Signon authentication mode*

`$cfg['Servers'][$i]['LogoutURL']`

**Type** string

**Default value** ''

*URL* where user will be redirected after logout (doesn't affect config authentication method). Should be absolute including protocol.

## 4.3 Generic settings

`$cfg['ServerDefault']`

**Type** integer

**Default value** 1

If you have more than one server configured, you can set `$cfg['ServerDefault']` to any one of them to autoconnect to that server when phpMyAdmin is started, or set it to 0 to be given a list of servers without logging in.

If you have only one server configured, `$cfg['ServerDefault']` MUST be set to that server.

#### `$cfg['VersionCheck']`

**Type** boolean

**Default value** true

Enables check for latest versions using JavaScript on the main phpMyAdmin page or by directly accessing `version_check.php`.

---

**Note:** This setting can be adjusted by your vendor.

---

#### `$cfg['ProxyUrl']`

**Type** string

**Default value**

“”

The url of the proxy to be used when phpmyadmin needs to access the outside internet such as when retrieving the latest version info or submitting error reports. You need this if the server where phpMyAdmin is installed does not have direct access to the internet. The format is: “hostname:portnumber”

#### `$cfg['ProxyUser']`

**Type** string

**Default value**

“”

The username for authenticating with the proxy. By default, no authentication is performed. If a username is supplied, Basic Authentication will be performed. No other types of authentication are currently supported.

#### `$cfg['ProxyPass']`

**Type** string

**Default value**

“”

The password for authenticating with the proxy.

#### `$cfg['MaxDbList']`

**Type** integer

**Default value** 100

The maximum number of database names to be displayed in the main panel’s database list.

#### `$cfg['MaxTableList']`

**Type** integer

**Default value** 250

The maximum number of table names to be displayed in the main panel's list (except on the Export page).

`$cfg['ShowHint']`

**Type** boolean

**Default value** true

Whether or not to show hints (for example, hints when hovering over table headers).

`$cfg['MaxCharactersInDisplayedSQL']`

**Type** integer

**Default value** 1000

The maximum number of characters when a *SQL* query is displayed. The default limit of 1000 should be correct to avoid the display of tons of hexadecimal codes that represent BLOBs, but some users have real *SQL* queries that are longer than 1000 characters. Also, if a query's length exceeds this limit, this query is not saved in the history.

`$cfg['PersistentConnections']`

**Type** boolean

**Default value** false

Whether *persistent connections* should be used or not. Works with following extensions:

- mysql (*mysql\_pconnect*),
- mysqli (requires PHP 5.3.0 or newer, [more information](#)).

`$cfg['ForceSSL']`

**Type** boolean

**Default value** false

Whether to force using https while accessing phpMyAdmin. In a reverse proxy setup, setting this to `true` is not supported.

---

**Note:** In some setups (like separate SSL proxy or load balancer) you might have to set `$cfg['PmaAbsoluteUri']` for correct redirection.

---

`$cfg['ExecTimeLimit']`

**Type** integer [number of seconds]

**Default value** 300

Set the number of seconds a script is allowed to run. If seconds is set to zero, no time limit is imposed. This setting is used while importing/exporting dump files but has no effect when PHP is running in safe mode.

`$cfg['SessionSavePath']`

**Type** string

**Default value** ''

Path for storing session data (*session\_save\_path* PHP parameter).

`$cfg['MemoryLimit']`

**Type** string [number of bytes]

**Default value** '-1'

Set the number of bytes a script is allowed to allocate. If set to `'-1'`, no limit is imposed.

This setting is used while importing/exporting dump files and at some other places in phpMyAdmin so you definitely don't want to put here a too low value. It has no effect when PHP is running in safe mode.

You can also use any string as in `php.ini`, eg. `'16M'`. Ensure you don't omit the suffix (16 means 16 bytes!)

#### `$cfg['SkipLockedTables']`

**Type** boolean

**Default value** false

Mark used tables and make it possible to show databases with locked tables (since MySQL 3.23.30).

#### `$cfg['ShowSQL']`

**Type** boolean

**Default value** true

Defines whether *SQL* queries generated by phpMyAdmin should be displayed or not.

#### `$cfg['RetainQueryBox']`

**Type** boolean

**Default value** false

Defines whether the *SQL* query box should be kept displayed after its submission.

#### `$cfg['CodemirrorEnable']`

**Type** boolean

**Default value** true

Defines whether to use a Javascript code editor for SQL query boxes. CodeMirror provides syntax highlighting and line numbers. However, middle-clicking for pasting the clipboard contents in some Linux distributions (such as Ubuntu) is not supported by all browsers.

#### `$cfg['DefaultForeignKeyChecks']`

**Type** string

**Default value** `'default'`

Default value of the checkbox for foreign key checks, to disable/enable foreign key checks for certain queries. The possible values are `'default'`, `'enable'` or `'disable'`. If set to `'default'`, the value of the MySQL variable `FOREIGN_KEY_CHECKS` is used.

#### `$cfg['AllowUserDropDatabase']`

**Type** boolean

**Default value** false

Defines whether normal users (non-administrator) are allowed to delete their own database or not. If set as false, the link *Drop Database* will not be shown, and even a `DROP DATABASE mydatabase` will be rejected. Quite practical for *ISP* 's with many customers.

---

**Note:** This limitation of *SQL* queries is not as strict as when using MySQL privileges. This is due to nature of *SQL* queries which might be quite complicated. So this choice should be viewed as help to avoid accidental dropping rather than strict privilege limitation.

---

#### `$cfg['Confirm']`

**Type** boolean

**Default value** true

Whether a warning (“Are your really sure...”) should be displayed when you’re about to lose data.

**\$cfg[‘UseDbSearch’]**

**Type** boolean

**Default value** true

Define whether the “search string inside database” is enabled or not.

**\$cfg[‘IgnoreMultiSubmitErrors’]**

**Type** boolean

**Default value** false

Define whether phpMyAdmin will continue executing a multi-query statement if one of the queries fails. Default is to abort execution.

## 4.4 Cookie authentication options

**\$cfg[‘blowfish\_secret’]**

**Type** string

**Default value** ‘ ‘

The “cookie” auth\_type uses AES algorithm to encrypt the password. If you are using the “cookie” auth\_type, enter here a random passphrase of your choice. It will be used internally by the AES algorithm: you won’t be prompted for this passphrase. There is no maximum length for this secret.

---

**Note:** The configuration is called blowfish\_secret for historical reasons as Blowfish algorithm was originally used to do the encryption.

---

Changed in version 3.1.0: Since version 3.1.0 phpMyAdmin can generate this on the fly, but it makes a bit weaker security as this generated secret is stored in session and furthermore it makes impossible to recall user name from cookie.

**\$cfg[‘LoginCookieRecall’]**

**Type** boolean

**Default value** true

Define whether the previous login should be recalled or not in cookie authentication mode.

This is automatically disabled if you do not have configured `$cfg[‘blowfish_secret’]`.

**\$cfg[‘LoginCookieValidity’]**

**Type** integer [number of seconds]

**Default value** 1440

Define how long a login cookie is valid. Please note that php configuration option `session.gc_maxlifetime` might limit session validity and if the session is lost, the login cookie is also invalidated. So it is a good idea to set `session.gc_maxlifetime` at least to the same value of `$cfg[‘LoginCookieValidity’]`.

**\$cfg[‘LoginCookieStore’]**



**Type** integer [number of seconds]

**Default value** 0

Define how long login cookie should be stored in browser. Default 0 means that it will be kept for existing session. This is recommended for not trusted environments.

`$cfg['LoginCookieDeleteAll']`

**Type** boolean

**Default value** true

If enabled (default), logout deletes cookies for all servers, otherwise only for current one. Setting this to false makes it easy to forget to log out from other server, when you are using more of them.

`$cfg['AllowArbitraryServer']`

**Type** boolean

**Default value** false

If enabled, allows you to log in to arbitrary servers using cookie authentication.

---

**Note:** Please use this carefully, as this may allow users access to MySQL servers behind the firewall where your *HTTP* server is placed. See also `$cfg['ArbitraryServerRegexp']`.

---

`$cfg['ArbitraryServerRegexp']`

**Type** string

**Default value** ''

Restricts the MySQL servers to which the user can log in when `$cfg['AllowArbitraryServer']` is enabled by matching the *IP* or the hostname of the MySQL server to the given regular expression. The regular expression must be enclosed with a delimiter character.

`$cfg['CaptchaLoginPublicKey']`

**Type** string

**Default value** ''

The public key for the reCaptcha service that can be obtained from <http://www.google.com/recaptcha>. reCaptcha will be then used in *Cookie authentication mode*.

`$cfg['CaptchaLoginPrivateKey']`

**Type** string

**Default value** ''

The private key for the reCaptcha service that can be obtain from <http://www.google.com/recaptcha>. reCaptcha will be then used in *Cookie authentication mode*.

## 4.5 Navigation panel setup

`$cfg['ShowDatabasesNavigationAsTree']`

**Type** boolean

**Default value** true

In the navigation panel, replaces the database tree with a selector

**\$cfg['FirstLevelNavigationItems']**

**Type** integer

**Default value** 100

The number of first level databases that can be displayed on each page of navigation tree.

**\$cfg['MaxNavigationItems']**

**Type** integer

**Default value** 50

The number of items (tables, columns, indexes) that can be displayed on each page of the navigation tree.

**\$cfg['NavigationTreeEnableGrouping']**

**Type** boolean

**Default value** true

Defines whether to group the databases based on a common prefix in their name *\$cfg['NavigationTreeDbSeparator']*.

**\$cfg['NavigationTreeDbSeparator']**

**Type** string or array

**Default value** '\_'

The string used to separate the parts of the database name when showing them in a tree. Alternatively you can specify more strings in an array and all of them will be used as a separator.

**\$cfg['NavigationTreeTableSeparator']**

**Type** string or array

**Default value** '\_\_\_'

Defines a string to be used to nest table spaces. This means if you have tables like *first\_\_second\_\_third* this will be shown as a three-level hierarchy like: *first > second > third*. If set to false or empty, the feature is disabled. NOTE: You should not use this separator at the beginning or end of a table name or multiple times after another without any other characters in between.

**\$cfg['NavigationTreeTableLevel']**

**Type** integer

**Default value** 1

Defines how many sublevels should be displayed when splitting up tables by the above separator.

**\$cfg['NumRecentTables']**

**Type** integer

**Default value** 10

The maximum number of recently used tables shown in the navigation panel. Set this to 0 (zero) to disable the listing of recent tables.

**\$cfg['ZeroConf']**

**Type** boolean

**Default value** true

Enables Zero Configuration mode in which the user will be offered a choice to create phpMyAdmin configuration storage in the current database or use the existing one, if already present.

This setting has no effect if the phpMyAdmin configuration storage database is properly created and the related configuration directives (such as `$cfg['Servers'][$i]['pmadb']` and so on) are configured.

#### `$cfg['NavigationLinkWithMainPanel']`

**Type** boolean

**Default value** true

Defines whether or not to link with main panel by highlighting the current database or table.

#### `$cfg['NavigationDisplayLogo']`

**Type** boolean

**Default value** true

Defines whether or not to display the phpMyAdmin logo at the top of the navigation panel.

#### `$cfg['NavigationLogoLink']`

**Type** string

**Default value** 'index.php'

Enter *URL* where logo in the navigation panel will point to. For use especially with self made theme which changes this. For external URLs, you should include URL scheme as well.

#### `$cfg['NavigationLogoLinkWindow']`

**Type** string

**Default value** 'main'

Whether to open the linked page in the main window (*main*) or in a new one (*new*). Note: use *new* if you are linking to `phpmyadmin.net`.

#### `$cfg['NavigationTreeDisplayItemFilterMinimum']`

**Type** integer

**Default value** 30

Defines the minimum number of items (tables, views, routines and events) to display a JavaScript filter box above the list of items in the navigation tree.

To disable the filter completely some high number can be used (e.g. 9999)

#### `$cfg['NavigationTreeDisplayDbFilterMinimum']`

**Type** integer

**Default value** 30

Defines the minimum number of databases to display a JavaScript filter box above the list of databases in the navigation tree.

To disable the filter completely some high number can be used (e.g. 9999)

#### `$cfg['NavigationDisplayServers']`

**Type** boolean

**Default value** true

Defines whether or not to display a server choice at the top of the navigation panel.

**\$cfg['DisplayServersList']**

**Type** boolean

**Default value** false

Defines whether to display this server choice as links instead of in a drop-down.

**\$cfg['NavigationTreeDefaultTabTable']**

**Type** string

**Default value** 'structure'

Defines the tab displayed by default when clicking the small icon next to each table name in the navigation panel. Possible values:

- structure
- sql
- search
- insert
- browse

**\$cfg['NavigationTreeDefaultTabTable2']**

**Type** string

**Default value** null

Defines the tab displayed by default when clicking the second small icon next to each table name in the navigation panel. Possible values:

- (empty)
- structure
- sql
- search
- insert
- browse

**\$cfg['NavigationTreeEnableExpansion']**

**Type** boolean

**Default value** false

Whether to offer the possibility of tree expansion in the navigation panel.

**\$cfg['NavigationTreeShowTables']**

**Type** boolean

**Default value** true

Whether to show tables under database in the navigation panel.

**\$cfg['NavigationTreeShowViews']**

**Type** boolean

**Default value** true

Whether to show views under database in the navigation panel.

`$cfg['NavigationTreeShowFunctions']`

**Type** boolean

**Default value** true

Whether to show functions under database in the navigation panel.

`$cfg['NavigationTreeShowProcedures']`

**Type** boolean

**Default value** true

Whether to show procedures under database in the navigation panel.

`$cfg['NavigationTreeShowEvents']`

**Type** boolean

**Default value** true

Whether to show events under database in the navigation panel.

## 4.6 Main panel

`$cfg['ShowStats']`

**Type** boolean

**Default value** true

Defines whether or not to display space usage and statistics about databases and tables. Note that statistics requires at least MySQL 3.23.3 and that, at this date, MySQL doesn't return such information for Berkeley DB tables.

`$cfg['ShowServerInfo']`

**Type** boolean

**Default value** true

Defines whether to display detailed server information on main page. You can additionally hide more information by using `$cfg['Servers'][$i]['verbose']`.

`$cfg['ShowPhpInfo']`

**Type** boolean

**Default value** false

`$cfg['ShowChgPassword']`

**Type** boolean

**Default value** true

`$cfg['ShowCreateDb']`

**Type** boolean

**Default value** true

Defines whether to display the *PHP information* and *Change password* links and form for creating database or not at the starting main (right) frame. This setting does not check MySQL commands entered directly.

Please note that to block the usage of `phpinfo()` in scripts, you have to put this in your `php.ini`:

```
disable_functions = phpinfo()
```

Also note that enabling the *Change password* link has no effect with config authentication mode: because of the hard coded password value in the configuration file, end users can't be allowed to change their passwords.

#### `$cfg['ShowGitRevision']`

**Type** boolean

**Default value** true

Defines whether to display informations about the current Git revision (if applicable) on the main panel.

#### `$cfg['MysqlMinVersion']`

**Type** array

Defines the minimum supported MySQL version. The default is chosen by the phpMyAdmin team; however this directive was asked by a developer of the Plesk control panel to ease integration with older MySQL servers (where most of the phpMyAdmin features work).

## 4.7 Database structure

#### `$cfg['ShowDbStructureCreation']`

**Type** boolean

**Default value** false

Defines whether the database structure page (tables list) has a “Creation” column that displays when each table was created.

#### `$cfg['ShowDbStructureLastUpdate']`

**Type** boolean

**Default value** false

Defines whether the database structure page (tables list) has a “Last update” column that displays when each table was last updated.

#### `$cfg['ShowDbStructureLastCheck']`

**Type** boolean

**Default value** false

Defines whether the database structure page (tables list) has a “Last check” column that displays when each table was last checked.

#### `$cfg['HideStructureActions']`

**Type** boolean

**Default value** true

Defines whether the table structure actions are hidden under a “More” drop-down.

## 4.8 Browse mode

### `$cfg['TableNavigationLinksMode']`

**Type** string

**Default value** 'icons'

Defines whether the table navigation links contain 'icons', 'text' or 'both'.

### `$cfg['ActionLinksMode']`

**Type** string

**Default value** 'both'

If set to `icons`, will display icons instead of text for db and table properties links (like *Browse*, *Select*, *Insert*, ...). Can be set to 'both' if you want icons AND text. When set to `text`, will only show text.

### `$cfg['RowActionType']`

**Type** string

**Default value** 'both'

Whether to display icons or text or both icons and text in table row action segment. Value can be either of 'icons', 'text' or 'both'.

### `$cfg['ShowAll']`

**Type** boolean

**Default value** false

Defines whether a user should be displayed a "Show all" button in browse mode or not in all cases. By default it is shown only on small tables (less than 500 rows) to avoid performance issues while getting too many rows.

### `$cfg['MaxRows']`

**Type** integer

**Default value** 25

Number of rows displayed when browsing a result set and no LIMIT clause is used. If the result set contains more rows, "Previous" and "Next" links will be shown. Possible values: 25,50,100,250,500.

### `$cfg['Order']`

**Type** string

**Default value** 'SMART'

Defines whether columns are displayed in ascending (ASC) order, in descending (DESC) order or in a "smart" (SMART) order - I.E. descending order for columns of type TIME, DATE, DATETIME and TIMESTAMP, ascending order else- by default.

### `$cfg['GridEditing']`

**Type** string

**Default value** 'double-click'

Defines which action (`double-click` or `click`) triggers grid editing. Can be deactivated with the `disabled` value.

### `$cfg['RelationalDisplay']`

**Type** string

**Default value** 'K'

Defines the initial behavior for Options > Relational. K, which is the default, displays the key while D shows the display column.

**\$cfg['SaveCellsAtOnce']**

**Type** boolean

**Default value** false

Defines whether or not to save all edited cells at once for grid editing.

## 4.9 Editing mode

**\$cfg['ProtectBinary']**

**Type** boolean or string

**Default value** 'blob'

Defines whether BLOB or BINARY columns are protected from editing when browsing a table's content. Valid values are:

- false to allow editing of all columns;
- 'blob' to allow editing of all columns except BLOBS;
- 'noblob' to disallow editing of all columns except BLOBS (the opposite of 'blob');
- 'all' to disallow editing of all BINARY or BLOB columns.

**\$cfg['ShowFunctionFields']**

**Type** boolean

**Default value** true

Defines whether or not MySQL functions fields should be initially displayed in edit/insert mode. Since version 2.10, the user can toggle this setting from the interface.

**\$cfg['ShowFieldTypesInDataEditView']**

**Type** boolean

**Default value** true

Defines whether or not type fields should be initially displayed in edit/insert mode. The user can toggle this setting from the interface.

**\$cfg['InsertRows']**

**Type** integer

**Default value** 2

Defines the maximum number of concurrent entries for the Insert page.

**\$cfg['ForeignKeyMaxLimit']**

**Type** integer

**Default value** 100

If there are fewer items than this in the set of foreign keys, then a drop-down box of foreign keys is presented, in the style described by the *\$cfg['ForeignKeyDropdownOrder']* setting.



`$cfg['ForeignKeyDropdownOrder']`

**Type** array

**Default value** array('content-id', 'id-content')

For the foreign key drop-down fields, there are several methods of display, offering both the key and value data. The contents of the array should be one or both of the following strings: `content-id`, `id-content`.

## 4.10 Export and import settings

`$cfg['ZipDump']`

**Type** boolean

**Default value** true

`$cfg['GZipDump']`

**Type** boolean

**Default value** true

`$cfg['BZipDump']`

**Type** boolean

**Default value** true

Defines whether to allow the use of zip/GZip/BZip2 compression when creating a dump file

`$cfg['CompressOnFly']`

**Type** boolean

**Default value** true

Defines whether to allow on the fly compression for GZip/BZip2 compressed exports. This doesn't affect smaller dumps and allows users to create larger dumps that won't otherwise fit in memory due to php memory limit. Produced files contain more GZip/BZip2 headers, but all normal programs handle this correctly.

`$cfg['Export']`

**Type** array

**Default value** array(...)

In this array are defined default parameters for export, names of items are similar to texts seen on export page, so you can easily identify what they mean.

`$cfg['Export']['method']`

**Type** string

**Default value** 'quick'

Defines how the export form is displayed when it loads. Valid values are:

- `quick` to display the minimum number of options to configure
- `custom` to display every available option to configure
- `custom-no-form` same as `custom` but does not display the option of using quick export

`$cfg['Import']`

**Type** array

**Default value** array(...)

In this array are defined default parameters for import, names of items are similar to texts seen on import page, so you can easily identify what they mean.

## 4.11 Tabs display settings

**\$cfg['TabsMode']**

**Type** string

**Default value** 'both'

Defines whether the menu tabs contain 'icons', 'text' or 'both'.

**\$cfg['PropertiesNumColumns']**

**Type** integer

**Default value** 1

How many columns will be utilized to display the tables on the database property view? When setting this to a value larger than 1, the type of the database will be omitted for more display space.

**\$cfg['DefaultTabServer']**

**Type** string

**Default value** 'welcome'

Defines the tab displayed by default on server view. Possible values:

- welcome (recommended for multi-user setups)
- databases,
- status
- variables
- privileges

**\$cfg['DefaultTabDatabase']**

**Type** string

**Default value** 'structure'

Defines the tab displayed by default on database view. Possible values:

- structure
- sql
- search
- operations

**\$cfg['DefaultTabTable']**

**Type** string

**Default value** 'browse'

Defines the tab displayed by default on table view. Possible values:

- structure

- sql
- search
- insert
- browse

## 4.12 PDF Options

`$cfg['PDFPageSizes']`

**Type** array

**Default value** `array('A3', 'A4', 'A5', 'letter', 'legal')`

Array of possible paper sizes for creating PDF pages.

You should never need to change this.

`$cfg['PDFDefaultPageSize']`

**Type** string

**Default value** `'A4'`

Default page size to use when creating PDF pages. Valid values are any listed in `$cfg['PDFPageSizes']`.

## 4.13 Languages

`$cfg['DefaultLang']`

**Type** string

**Default value** `'en'`

Defines the default language to use, if not browser-defined or user-defined. The corresponding language file needs to be in `locale/code/LC_MESSAGES/phpmyadmin.mo`.

`$cfg['DefaultConnectionCollation']`

**Type** string

**Default value** `'utf8_general_ci'`

Defines the default connection collation to use, if not user-defined. See the [MySQL documentation](#) for charsets for list of possible values. This setting is ignored when connected to Drizzle server.

`$cfg['Lang']`

**Type** string

**Default value** not set

Force language to use. The corresponding language file needs to be in `locale/code/LC_MESSAGES/phpmyadmin.mo`.

`$cfg['FilterLanguages']`

**Type** string

**Default value** `''`

Limit list of available languages to those matching the given regular expression. For example if you want only Czech and English, you should set filter to `'^(cs|en)'`.

#### `$cfg['RecodingEngine']`

**Type** string

**Default value** `'auto'`

You can select here which functions will be used for character set conversion. Possible values are:

- auto - automatically use available one (first is tested iconv, then recode)
- iconv - use iconv or libiconv functions
- recode - use recode\_string function
- mb - use mbstring extension
- none - disable encoding conversion

Enabled charset conversion activates a pull-down menu in the Export and Import pages, to choose the character set when exporting a file. The default value in this menu comes from `$cfg['Export']['charset']` and `$cfg['Import']['charset']`.

#### `$cfg['IconvExtraParams']`

**Type** string

**Default value** `'//TRANSLIT'`

Specify some parameters for iconv used in charset conversion. See [iconv documentation](#) for details. By default `//TRANSLIT` is used, so that invalid characters will be transliterated.

#### `$cfg['AvailableCharsets']`

**Type** array

**Default value** `array(...)`

Available character sets for MySQL conversion. You can add your own (any of supported by recode/iconv) or remove these which you don't use. Character sets will be shown in same order as here listed, so if you frequently use some of these move them to the top.

## 4.14 Web server settings

#### `$cfg['OBGzip']`

**Type** string/boolean

**Default value** `'auto'`

Defines whether to use GZip output buffering for increased speed in *HTTP* transfers. Set to true/false for enabling/disabling. When set to 'auto' (string), phpMyAdmin tries to enable output buffering and will automatically disable it if your browser has some problems with buffering. IE6 with a certain patch is known to cause data corruption when having enabled buffering.

#### `$cfg['TrustedProxies']`

**Type** array

**Default value** `array()`

Lists proxies and HTTP headers which are trusted for `$cfg['Servers'][$i]['AllowDeny']['order']`. This list is by default empty, you need to fill in some trusted proxy servers if you want to use rules for IP addresses behind proxy.

The following example specifies that phpMyAdmin should trust a HTTP\_X\_FORWARDED\_FOR (X-Forwarded-For) header coming from the proxy 1.2.3.4:

```
$cfg['TrustedProxies'] = array('1.2.3.4' => 'HTTP_X_FORWARDED_FOR');
```

The `$cfg['Servers'][$i]['AllowDeny']['rules']` directive uses the client's IP address as usual.

#### `$cfg['GD2Available']`

**Type** string

**Default value** 'auto'

Specifies whether GD >= 2 is available. If yes it can be used for MIME transformations. Possible values are:

- auto - automatically detect
- yes - GD 2 functions can be used
- no - GD 2 function cannot be used

#### `$cfg['CheckConfigurationPermissions']`

**Type** boolean

**Default value** true

We normally check the permissions on the configuration file to ensure it's not world writable. However, phpMyAdmin could be installed on a NTFS filesystem mounted on a non-Windows server, in which case the permissions seems wrong but in fact cannot be detected. In this case a sysadmin would set this parameter to false.

#### `$cfg['LinkLengthLimit']`

**Type** integer

**Default value** 1000

Limit for length of *URL* in links. When length would be above this limit, it is replaced by form with button. This is required as some web servers (*IIS*) have problems with long *URL*.

#### `$cfg['CSPAllow']`

**Type** string

**Default value** ''

Additional string to include in allowed script and image sources in Content Security Policy header.

This can be useful when you want to include some external JavaScript files in `config.footer.inc.php` or `config.header.inc.php`, which would be normally not allowed by Content Security Policy.

To allow some sites, just list them within the string:

```
$cfg['CSPAllow'] = 'example.com example.net';
```

New in version 4.0.4.

#### `$cfg['DisableMultiTableMaintenance']`

**Type** boolean

**Default value** false

In the database Structure page, it's possible to mark some tables then choose an operation like optimizing for many tables. This can slow down a server; therefore, setting this to `true` prevents this kind of multiple maintenance operation.

## 4.15 Theme settings

`$cfg['NaviWidth']`

**Type** integer

**Default value**

Navigation panel width in pixels. See `themes/themename/layout.inc.php`.

`$cfg['NaviBackground']`

**Type** string [CSS color for background]

**Default value**

`$cfg['MainBackground']`

**Type** string [CSS color for background]

**Default value**

The background styles used for both the frames. See `themes/themename/layout.inc.php`.

`$cfg['NaviPointerBackground']`

**Type** string [CSS color for background]

**Default value**

`$cfg['NaviPointerColor']`

**Type** string [CSS color]

**Default value**

The style used for the pointer in the navigation panel. See `themes/themename/layout.inc.php`.

`$cfg['Border']`

**Type** integer

**Default value**

The size of a table's border. See `themes/themename/layout.inc.php`.

`$cfg['ThBackground']`

**Type** string [CSS color for background]

**Default value**

`$cfg['ThColor']`

**Type** string [CSS color]

**Default value**

The style used for table headers. See `themes/themename/layout.inc.php`.

`$cfg['BgOne']`

**Type** string [CSS color]

**Default value**

The color (HTML) #1 for table rows. See `themes/themename/layout.inc.php`.

**`$cfg['BgTwo']`**

**Type** string [CSS color]

**Default value**

The color (HTML) #2 for table rows. See `themes/themename/layout.inc.php`.

**`$cfg['BrowsePointerBackground']`**

**Type** string [CSS color]

**Default value**

The background color used when hovering over a row in the Browse panel. See `themes/themename/layout.inc.php`.

**`$cfg['BrowsePointerColor']`**

**Type** string [CSS color]

**Default value**

The text color used when hovering over a row in the Browse panel. Used when `$cfg['BrowsePointerEnable']` is true. See `themes/themename/layout.inc.php`.

**`$cfg['BrowseMarkerBackground']`**

**Type** string [CSS color]

**Default value**

The background color used to highlight a row selected by checkbox in the Browse panel or when a column is selected. Used when `$cfg['BrowsePointerEnable']` is true. See `themes/themename/layout.inc.php`.

**`$cfg['BrowseMarkerColor']`**

**Type** string [CSS color]

**Default value**

The color used when you visually mark a row or column in the Browse panel. Rows can be marked by clicking the checkbox to the left of the row and columns can be marked by clicking the column's header (outside of the header text). See `themes/themename/layout.inc.php`.

**`$cfg['FontFamily']`**

**Type** string

**Default value**

You put here a valid CSS font family value, for example `arial, sans-serif`. See `themes/themename/layout.inc.php`.

**`$cfg['FontFamilyFixed']`**

**Type** string

**Default value**

You put here a valid CSS font family value, for example `monospace`. This one is used in textarea. See `themes/themename/layout.inc.php`.

## 4.16 Design customization

### `$cfg['NavigationTreePointerEnable']`

**Type** boolean

**Default value** true

When set to true, hovering over an item in the navigation panel causes that item to be marked (the background is highlighted).

### `$cfg['BrowsePointerEnable']`

**Type** boolean

**Default value** true

When set to true, hovering over a row in the Browse page causes that row to be marked (the background is highlighted).

### `$cfg['BrowseMarkerEnable']`

**Type** boolean

**Default value** true

When set to true, a data row is marked (the background is highlighted) when the row is selected with the checkbox.

### `$cfg['LimitChars']`

**Type** integer

**Default value** 50

Maximum number of characters shown in any non-numeric field on browse view. Can be turned off by a toggle button on the browse page.

### `$cfg['RowActionLinks']`

**Type** string

**Default value** 'left'

Defines the place where table row links (Edit, Copy, Delete) would be put when tables contents are displayed (you may have them displayed at the left side, right side, both sides or nowhere).

### `$cfg['RowActionLinksWithoutUnique']`

**Type** boolean

**Default value** false

Defines whether to show row links (Edit, Copy, Delete) and checkboxes for multiple row operations even when the selection does not have a unique key. Using row actions in the absence of a unique key may result in different/more rows being affected since there is no guaranteed way to select the exact row(s).

### `$cfg['RememberSorting']`

**Type** boolean

**Default value** true

If enabled, remember the sorting of each table when browsing them.

### `$cfg['TablePrimaryKeyOrder']`

**Type** string



**Default value** 'NONE'

This defines the default sort order for the tables, having a primary key, when there is no sort order defines externally. Acceptable values : ['NONE', 'ASC', 'DESC']

**\$cfg['ShowBrowseComments']**

**Type** boolean

**Default value** true

**\$cfg['ShowPropertyComments']**

**Type** boolean

**Default value** true

By setting the corresponding variable to `true` you can enable the display of column comments in Browse or Property display. In browse mode, the comments are shown inside the header. In property mode, comments are displayed using a CSS-formatted dashed-line below the name of the column. The comment is shown as a tool-tip for that column.

## 4.17 Text fields

**\$cfg['CharEditing']**

**Type** string

**Default value** 'input'

Defines which type of editing controls should be used for CHAR and VARCHAR columns. Applies to data editing and also to the default values in structure editing. Possible values are:

- input - this allows to limit size of text to size of columns in MySQL, but has problems with newlines in columns
- textarea - no problems with newlines in columns, but also no length limitations

**\$cfg['MinSizeForInputField']**

**Type** integer

**Default value** 4

Defines the minimum size for input fields generated for CHAR and VARCHAR columns.

**\$cfg['MaxSizeForInputField']**

**Type** integer

**Default value** 60

Defines the maximum size for input fields generated for CHAR and VARCHAR columns.

**\$cfg['TextareaCols']**

**Type** integer

**Default value** 40

**\$cfg['TextareaRows']**

**Type** integer

**Default value** 15

`$cfg['CharTextareaCols']`

**Type** integer

**Default value** 40

`$cfg['CharTextareaRows']`

**Type** integer

**Default value** 2

Number of columns and rows for the textareas. This value will be emphasized (\*2) for *SQL* query textareas and (\*1.25) for *SQL* textareas inside the query window.

The Char\* values are used for CHAR and VARCHAR editing (if configured via `$cfg['CharEditing']`).

`$cfg['LongtextDoubleTextarea']`

**Type** boolean

**Default value** true

Defines whether textarea for LONGTEXT columns should have double size.

`$cfg['TextareaAutoSelect']`

**Type** boolean

**Default value** false

Defines if the whole textarea of the query box will be selected on click.

`$cfg['EnableAutocompleteForTablesAndColumns']`

**Type** boolean

**Default value** true

Whether to enable autocomplete for table and column names in any SQL query box.

## 4.18 SQL query box settings

`$cfg['SQLQuery']['Edit']`

**Type** boolean

**Default value** true

Whether to display an edit link to change a query in any SQL Query box.

`$cfg['SQLQuery']['Explain']`

**Type** boolean

**Default value** true

Whether to display a link to explain a SELECT query in any SQL Query box.

`$cfg['SQLQuery']['ShowAsPHP']`

**Type** boolean

**Default value** true

Whether to display a link to wrap a query in PHP code in any SQL Query box.

`$cfg['SQLQuery']['Refresh']`

**Type** boolean

**Default value** true

Whether to display a link to refresh a query in any SQL Query box.

## 4.19 Web server upload/save/import directories

**\$cfg['UploadDir']**

**Type** string

**Default value** ''

The name of the directory where *SQL* files have been uploaded by other means than phpMyAdmin (for example, ftp). Those files are available under a drop-down box when you click the database or table name, then the Import tab.

If you want different directory for each user, %u will be replaced with username.

Please note that the file names must have the suffix ".sql" (or ".sql.bz2" or ".sql.gz" if support for compressed formats is enabled).

This feature is useful when your file is too big to be uploaded via *HTTP*, or when file uploads are disabled in PHP.

---

**Note:** If PHP is running in safe mode, this directory must be owned by the same user as the owner of the phpMyAdmin scripts. See also *1.16 I cannot upload big dump files (memory, HTTP or timeout problems)* for alternatives.

---

**\$cfg['SaveDir']**

**Type** string

**Default value** ''

The name of the directory where dumps can be saved.

If you want different directory for each user, %u will be replaced with username.

Please note that the directory must exist and has to be writable for the user running webserver.

---

**Note:** If PHP is running in safe mode, this directory must be owned by the same user as the owner of the phpMyAdmin scripts.

---

**\$cfg['TempDir']**

**Type** string

**Default value** ''

The name of the directory where temporary files can be stored.

This is needed for importing ESRI Shapefiles, see *6.30 Import: How can I import ESRI Shapefiles?* and to work around limitations of `open_basedir` for uploaded files, see *1.11 I get an 'open\_basedir restriction' while uploading a file from the query box..*

If the directory where phpMyAdmin is installed is subject to an `open_basedir` restriction, you need to create a temporary directory in some directory accessible by the web server. However for security reasons, this directory should be outside the tree published by webserver. If you cannot avoid having this directory published by webserver, place at least an empty `index.html` file there, so that directory listing is not possible.

This directory should have as strict permissions as possible as the only user required to access this directory is the one who runs the webserver. If you have root privileges, simply make this user owner of this directory and make it accessible only by it:

```
chown www-data:www-data tmp
chmod 700 tmp
```

If you cannot change owner of the directory, you can achieve a similar setup using *ACL*:

```
chmod 700 tmp
setfacl -m "g:www-data:rwx" tmp
setfacl -d -m "g:www-data:rwx" tmp
```

If neither of above works for you, you can still make the directory **chmod 777**, but it might impose risk of other users on system reading and writing data in this directory.

## 4.20 Various display setting

### `$cfg['RepeatCells']`

**Type** integer

**Default value** 100

Repeat the headers every X cells, or 0 to deactivate.

### `$cfg['QueryHistoryDB']`

**Type** boolean

**Default value** false

### `$cfg['QueryHistoryMax']`

**Type** integer

**Default value** 25

If `$cfg['QueryHistoryDB']` is set to `true`, all your Queries are logged to a table, which has to be created by you (see `$cfg['Servers'][$i]['history']`). If set to false, all your queries will be appended to the form, but only as long as your window is opened they remain saved.

When using the JavaScript based query window, it will always get updated when you click on a new table/db to browse and will focus if you click on *Edit SQL* after using a query. You can suppress updating the query window by checking the box *Do not overwrite this query from outside the window* below the query textarea. Then you can browse tables/databases in the background without losing the contents of the textarea, so this is especially useful when composing a query with tables you first have to look in. The checkbox will get automatically checked whenever you change the contents of the textarea. Please uncheck the button whenever you definitely want the query window to get updated even though you have made alterations.

If `$cfg['QueryHistoryDB']` is set to `true` you can specify the amount of saved history items using `$cfg['QueryHistoryMax']`.

### `$cfg['BrowseMIME']`

**Type** boolean

**Default value** true

Enable *Transformations*.

### `$cfg['MaxExactCount']`

**Type** integer

**Default value** 500000

For InnoDB tables, determines for how large tables phpMyAdmin should get the exact row count using SELECT COUNT. If the approximate row count as returned by SHOW TABLE STATUS is smaller than this value, SELECT COUNT will be used, otherwise the approximate count will be used.

**\$cfg['MaxExactCountViews']**

**Type** integer

**Default value** 0

For VIEWS, since obtaining the exact count could have an impact on performance, this value is the maximum to be displayed, using a SELECT COUNT ... LIMIT. Setting this to 0 bypasses any row counting.

**\$cfg['NaturalOrder']**

**Type** boolean

**Default value** true

Sorts database and table names according to natural order (for example, t1, t2, t10). Currently implemented in the navigation panel and in Database view, for the table list.

**\$cfg['InitialSlidersState']**

**Type** string

**Default value** 'closed'

If set to 'closed', the visual sliders are initially in a closed state. A value of 'open' does the reverse. To completely disable all visual sliders, use 'disabled'.

**\$cfg['UserprefsDisallow']**

**Type** array

**Default value** array()

Contains names of configuration options (keys in \$cfg array) that users can't set through user preferences. For possible values, refer to libraries/config/user\_preferences.forms.php.

**\$cfg['UserprefsDeveloperTab']**

**Type** boolean

**Default value** false

Activates in the user preferences a tab containing options for developers of phpMyAdmin.

## 4.21 Page titles

**\$cfg['TitleTable']**

**Type** string

**Default value** '@HTTP\_HOST@ / @VSERVER@ / @DATABASE@ / @TABLE@ | @PHPMYADMIN@'

**\$cfg['TitleDatabase']**

**Type** string

**Default value** '@HTTP\_HOST@ / @VSERVER@ / @DATABASE@ | @PHPMYADMIN@'

`$cfg['TitleServer']`

**Type** string

**Default value** '@HTTP\_HOST@ / @VSERVER@ | @PHPMYADMIN@'

`$cfg['TitleDefault']`

**Type** string

**Default value** '@HTTP\_HOST@ | @PHPMYADMIN@'

Allows you to specify window's title bar. You can use [6.27 What format strings can I use?](#).

## 4.22 Theme manager settings

`$cfg['ThemePath']`

**Type** string

**Default value** './themes'

If theme manager is active, use this as the path of the subdirectory containing all the themes.

`$cfg['ThemeManager']`

**Type** boolean

**Default value** true

Enables user-selectable themes. See [2.7 Using and creating themes](#).

`$cfg['ThemeDefault']`

**Type** string

**Default value** 'pmahomme'

The default theme (a subdirectory under `$cfg['ThemePath']`).

`$cfg['ThemePerServer']`

**Type** boolean

**Default value** false

Whether to allow different theme for each server.

## 4.23 Default queries

`$cfg['DefaultQueryTable']`

**Type** string

**Default value** 'SELECT \* FROM @TABLE@ WHERE 1'

`$cfg['DefaultQueryDatabase']`

**Type** string

**Default value** ''

Default queries that will be displayed in query boxes when user didn't specify any. You can use standard [6.27 What format strings can I use?](#).

## 4.24 MySQL settings

`$cfg['DefaultFunctions']`

**Type** array

**Default value** array(...)

Functions selected by default when inserting/changing row, Functions are defined for meta types as (FUNC\_NUMBER, FUNC\_DATE, FUNC\_CHAR, FUNC\_SPATIAL, FUNC\_UUID) and for `first_timestamp`, which is used for first timestamp column in table.

## 4.25 Developer

**Warning:** These settings might have huge effect on performance or security.

`$cfg['DBG']`

**Type** array

**Default value** array(...)

`$cfg['DBG']['sql']`

**Type** boolean

**Default value** false

Enable logging queries and execution times to be displayed in the console's Debug SQL tab.

`$cfg['DBG']['demo']`

**Type** boolean

**Default value** false

Enable to let server present itself as demo server. This is used for `<http://demo.phpmyadmin.net/>`.





## 5.1 Transformations

### 5.1.1 Introduction

To enable transformations, you have to setup the `column_info` table and the proper directives. Please see the *Configuration* on how to do so.

You can apply different transformations to the contents of each column. The transformation will take the content of each column and transform it with certain rules defined in the selected transformation.

Say you have a column 'filename' which contains a filename. Normally you would see in phpMyAdmin only this filename. Using transformations you can transform that filename into a HTML link, so you can click inside of the phpMyAdmin structure on the column's link and will see the file displayed in a new browser window. Using transformation options you can also specify strings to append/prepend to a string or the format you want the output stored in.

For a general overview of all available transformations and their options, you can consult your `<www.your-host.com>/<your-install-dir>/transformation_overview.php` installation.

For a tutorial on how to effectively use transformations, see our [Link section](#) on the official phpMyAdmin homepage.

### 5.1.2 Usage

Go to your `tbl_structure.php` page (i.e. reached through clicking on the 'Structure' link for a table). There click on "Change" (or change icon) and there you will see three new fields at the end of the line. They are called 'MIME-type', 'Browser transformation' and 'Transformation options'.

- The field 'MIME-type' is a drop-down field. Select the MIME-type that corresponds to the column's contents. Please note that transformations are inactive as long as no MIME-type is selected.
- The field 'Browser transformation' is a drop-down field. You can choose from a hopefully growing amount of pre-defined transformations. See below for information on how to build your own transformation. There are global transformations and mimetype-bound transformations. Global transformations can be used for any mimetype. They will take the mimetype, if necessary, into regard. Mimetype-bound transformations usually only operate on a certain mimetype. There are transformations which operate on the main mimetype (like 'image'), which will most likely take the subtype into regard, and those who only operate on a specific subtype (like 'image/jpeg'). You can use transformations on mimetypes for which the function was not defined for. There is no security check for you selected the right transformation, so take care of what the output will be like.
- The field 'Transformation options' is a free-type textfield. You have to enter transform-function specific options here. Usually the transforms can operate with default options, but it is generally a good idea to look up the

overview to see which options are necessary. Much like the ENUM/SET-Fields, you have to split up several options using the format 'a','b','c',...(NOTE THE MISSING BLANKS). This is because internally the options will be parsed as an array, leaving the first value the first element in the array, and so forth. If you want to specify a MIME character set you can define it in the transformation\_options. You have to put that outside of the pre-defined options of the specific mime-transform, as the last value of the set. Use the format “; charset=XXX”. If you use a transform, for which you can specify 2 options and you want to append a character set, enter “first parameter’,’second parameter’,’charset=us-ascii”. You can, however use the defaults for the parameters: “’,’,’; charset =us-ascii”.

### 5.1.3 File structure

All specific transformations for mimetypes are defined through class files in the directory 'libraries/plugins/transformations/'. Each of them extends a certain transformation abstract class declared in libraries/plugins/transformations/abstract.

They are stored in files to ease up customization and easy adding of new transformations.

Because the user cannot enter own mimetypes, it is kept sure that transformations always work. It makes no sense to apply a transformation to a mimetype the transform-function doesn't know to handle.

There is a file called '*transformations.lib.php*' that provides some basic functions which can be included by any other transform function.

The file name convention is [Mimetype]\_[Subtype]\_[Transformation Name].class.php, while the abstract class that it extends has the name [Transformation Name]TransformationsPlugin. All of the methods that have to be implemented by a transformations plug-in are:

1. getMIMETYPE() and getMIMESubtype() in the main class;
2. getName(), getInfo() and applyTransformation() in the abstract class it extends.

The getMIMETYPE(), getMIMESubtype() and getName() methods return the name of the MIME type, MIME Subtype and transformation accordingly. getInfo() returns the transformation's description and possible options it may receive and applyTransformation() is the method that does the actual work of the transformation plug-in.

Please see the libraries/plugins/transformations/TEMPLATE and libraries/plugins/transformations/TEMPLATE\_ABSTRACT files for adding your own transformation plug-in. You can also generate a new transformation plug-in (with or without the abstract transformation class), by using libraries/plugins/transformations/generator\_plugin.sh or libraries/plugins/transformations/generator\_main\_class.sh.

The applyTransformation() method always gets passed three variables:

1. **\$buffer** - Contains the text inside of the column. This is the text, you want to transform.
2. **\$options** - Contains any user-passed options to a transform function as an array.
3. **\$meta** - Contains an object with information about your column. The data is drawn from the output of the `mysql_fetch_field()` function. This means, all object properties described on the [manual page](#) are available in this variable and can be used to transform a column accordingly to unsigned/zerofill/not\_null/... properties. The `$meta->mimetype` variable contains the original MIME-type of the column (i.e. 'text/plain', 'image/jpeg' etc.)

## 5.2 User management

User management is the process of controlling which users are allowed to connect to the MySQL server and what permissions they have on each database. phpMyAdmin does not handle user management, rather it passes the username and password on to MySQL, which then determines whether a user is permitted to perform a particular action. Within

phpMyAdmin, administrators have full control over creating users, viewing and editing privileges for existing users, and removing users.

Within phpMyAdmin, user management is controlled via the *Users* link from the main page. Users can be created, edited, and removed.

### 5.2.1 Creating a new user

To create a new user, click the *Add a new user* link near the bottom of the *Users* page (you must be a “superuser”, e.g., user “root”). Use the textboxes and drop-downs to configure the user to your particular needs. You can then select whether to create a database for that user and grant specific global privileges. Once you’ve created the user (by clicking Go), you can define that user’s permissions on a specific database (don’t grant global privileges in that case). In general, users do not need any global privileges (other than USAGE), only permissions for their specific database.

### 5.2.2 Editing an existing user

To edit an existing user, simply click the pencil icon to the right of that user in the *Users* page. You can then edit their global- and database-specific privileges, change their password, or even copy those privileges to a new user.

### 5.2.3 Deleting a user

From the *Users* page, check the checkbox for the user you wish to remove, select whether or not to also remove any databases of the same name (if they exist), and click Go.

### 5.2.4 Assigning privileges to user for a specific database

Users are assigned to databases by editing the user record (from the *Users* link on the home page) not from within the *Users* link under the table. If you are creating a user specifically for a given table you will have to create the user first (with no global privileges) and then go back and edit that user to add the table and privileges for the individual table.

## 5.3 Other sources of information

### 5.3.1 Printed Book

The definitive guide to using phpMyAdmin is the book *Mastering phpMyAdmin for Effective MySQL Management* by Marc Delisle. You can get information on that book and other officially endorsed [books at the phpMyAdmin site](#).

### 5.3.2 Tutorials

Third party tutorials and articles are listed on our [wiki page](#).

## 5.4 Import and export

In addition to the standard Import and Export tab, you can also import an SQL file directly by dragging and dropping it from your local file manager to the phpMyAdmin interface in your web browser.

### 5.4.1 Open Document Spreadsheet

When importing an ODS spreadsheet, the spreadsheet must be named in a specific way in order to make the import as simple as possible.

#### Table name

During import, phpMyAdmin uses the sheet name as the table name; you should rename the sheet in your spreadsheet program in order to match your existing table name (or the table you wish to create, though this is less of a concern since you could quickly rename the new table from the Operations tab).

#### Column names

You should also make the first row of your spreadsheet a header with the names of the columns (this can be accomplished by inserting a new row at the top of your spreadsheet). When on the Import screen, select the checkbox for “The first line of the file contains the table column names;” this way your newly imported data will go to the proper columns.

---

## FAQ - Frequently Asked Questions

---

Please have a look at our [Link section](#) on the official phpMyAdmin homepage for in-depth coverage of phpMyAdmin's features and or interface.

### 6.1 Server

#### 6.1.1 1.1 My server is crashing each time a specific action is required or phpMyAdmin sends a blank page or a page full of cryptic characters to my browser, what can I do?

Try to set the `$cfg['OBGzip']` directive to `false` in your `config.inc.php` file and the `zlib.output_compression` directive to `Off` in your php configuration file.

#### 6.1.2 1.2 My Apache server crashes when using phpMyAdmin.

You should first try the latest versions of Apache (and possibly MySQL). If your server keeps crashing, please ask for help in the various Apache support groups.

**See also:**

*1.1 My server is crashing each time a specific action is required or phpMyAdmin sends a blank page or a page full of cryptic characters to my browser, what can I do?*

#### 6.1.3 1.3 (withdrawn).

#### 6.1.4 1.4 Using phpMyAdmin on IIS, I'm displayed the error message: "The specified CGI application misbehaved by not returning a complete set of HTTP headers ...".

You just forgot to read the `install.txt` file from the PHP distribution. Have a look at the last message in this [PHP bug report #12061](#) from the official PHP bug database.

### 6.1.5 1.5 Using phpMyAdmin on IIS, I'm facing crashes and/or many error messages with the HTTP.

This is a known problem with the PHP *ISAPI* filter: it's not so stable. Please use instead the cookie authentication mode.

### 6.1.6 1.6 I can't use phpMyAdmin on PWS: nothing is displayed!

This seems to be a PWS bug. Filippo Simoncini found a workaround (at this time there is no better fix): remove or comment the DOCTYPE declarations (2 lines) from the scripts `libraries/Header.class.php` and `index.php`.

### 6.1.7 1.7 How can I GZip a dump or a CSV export? It does not seem to work.

This feature is based on the `gzencode()` PHP function to be more independent of the platform (Unix/Windows, Safe Mode or not, and so on). So, you must have Zlib support (`--with-zlib`).

### 6.1.8 1.8 I cannot insert a text file in a table, and I get an error about safe mode being in effect.

Your uploaded file is saved by PHP in the "upload dir", as defined in `php.ini` by the variable `upload_tmp_dir` (usually the system default is `/tmp`). We recommend the following setup for Apache servers running in safe mode, to enable uploads of files while being reasonably secure:

- create a separate directory for uploads: `mkdir /tmp/php`
- give ownership to the Apache server's user.group: `chown apache.apache /tmp/php`
- give proper permission: `chmod 600 /tmp/php`
- put `upload_tmp_dir = /tmp/php` in `php.ini`
- restart Apache

### 6.1.9 1.9 (withdrawn).

### 6.1.10 1.10 I'm having troubles when uploading files with phpMyAdmin running on a secure server. My browser is Internet Explorer and I'm using the Apache server.

As suggested by "Rob M" in the phpWizard forum, add this line to your `httpd.conf`:

```
SetEnvIf User-Agent ".*MSIE.*" nokeepalive ssl-unclean-shutdown
```

It seems to clear up many problems between Internet Explorer and SSL.

### 6.1.11 1.11 I get an 'open\_basedir restriction' while uploading a file from the query box.

Since version 2.2.4, phpMyAdmin supports servers with `open_basedir` restrictions. However you need to create temporary directory and configure it as `$cfg['TempDir']`. The uploaded files will be moved there, and after execution of your *SQL* commands, removed.

### 6.1.12 1.12 I have lost my MySQL root password, what can I do?

The MySQL manual explains how to [reset the permissions](#).

### 6.1.13 1.13 (withdrawn).

### 6.1.14 1.14 (withdrawn).

### 6.1.15 1.15 I have problems with *mysql.user* column names.

In previous MySQL versions, the `User` and `Password` columns were named `user` and `password`. Please modify your column names to align with current standards.

### 6.1.16 1.16 I cannot upload big dump files (memory, HTTP or timeout problems).

Starting with version 2.7.0, the import engine has been re-written and these problems should not occur. If possible, upgrade your phpMyAdmin to the latest version to take advantage of the new import features.

The first things to check (or ask your host provider to check) are the values of `upload_max_filesize`, `memory_limit` and `post_max_size` in the `php.ini` configuration file. All of these three settings limit the maximum size of data that can be submitted and handled by PHP. One user also said that `post_max_size` and `memory_limit` need to be larger than `upload_max_filesize`. There exist several workarounds if your upload is too big or your hosting provider is unwilling to change the settings:

- Look at the `$cfg['UploadDir']` feature. This allows one to upload a file to the server via scp, ftp, or your favorite file transfer method. PhpMyAdmin is then able to import the files from the temporary directory. More information is available in the *Configuration* of this document.
- Using a utility (such as [BigDump](#)) to split the files before uploading. We cannot support this or any third party applications, but are aware of users having success with it.
- If you have shell (command line) access, use MySQL to import the files directly. You can do this by issuing the “source” command from within MySQL:

```
source filename.sql;
```

### 6.1.17 1.17 Which Database versions does phpMyAdmin support?

For [MySQL](#), versions 5.5 and newer are supported. For older MySQL versions, our [Downloads](#) page offers older phpMyAdmin versions (which may have become unsupported).

For [MariaDB](#), versions 5.5 and newer are supported.

For [Drizzle](#), versions 7.1 and newer are supported.

### 6.1.18 1.17a I cannot connect to the MySQL server. It always returns the error message, “Client does not support authentication protocol requested by server; consider upgrading MySQL client”

You tried to access MySQL with an old MySQL client library. The version of your MySQL client library can be checked in your `phpinfo()` output. In general, it should have at least the same minor version as your server - as mentioned in *1.17 Which Database versions does phpMyAdmin support?*. This problem is generally caused by using MySQL version 4.1 or newer. MySQL changed the authentication hash and your PHP is trying to use the old method.

The proper solution is to use the [mysqli extension](#) with the proper client library to match your MySQL installation. More information (and several workarounds) are located in the [MySQL Documentation](#).

### 6.1.19 1.18 (withdrawn).

### 6.1.20 1.19 I can't run the "display relations" feature because the script seems not to know the font face I'm using!

The *TCPDF* library we're using for this feature requires some special files to use font faces. Please refer to the [TCPDF manual](#) to build these files.

### 6.1.21 1.20 I receive an error about missing mysqli and mysql extensions.

To connect to a MySQL server, PHP needs a set of MySQL functions called "MySQL extension". This extension may be part of the PHP distribution (compiled-in), otherwise it needs to be loaded dynamically. Its name is probably *mysqli.so* or *php\_mysqli.dll*. phpMyAdmin tried to load the extension but failed. Usually, the problem is solved by installing a software package called "PHP-MySQL" or something similar.

There are currently two interfaces PHP provides as MySQL extensions - `mysql` and `mysqli`. The `mysqli` is tried first, because it's the best one.

### 6.1.22 1.21 I am running the CGI version of PHP under Unix, and I cannot log in using cookie auth.

In `php.ini`, set `mysql.max_links` higher than 1.

### 6.1.23 1.22 I don't see the "Location of text file" field, so I cannot upload.

This is most likely because in `php.ini`, your `file_uploads` parameter is not set to "on".

### 6.1.24 1.23 I'm running MySQL on a Win32 machine. Each time I create a new table the table and column names are changed to lowercase!

This happens because the MySQL directive `lower_case_table_names` defaults to 1 (ON) in the Win32 version of MySQL. You can change this behavior by simply changing the directive to 0 (OFF): Just edit your `my.ini` file that should be located in your Windows directory and add the following line to the group `[mysqld]`:

```
set-variable = lower_case_table_names=0
```

Next, save the file and restart the MySQL service. You can always check the value of this directive using the query

```
SHOW VARIABLES LIKE 'lower_case_table_names';
```

### 6.1.25 1.24 (withdrawn).

### 6.1.26 1.25 I am running Apache with mod\_gzip-1.3.26.1a on Windows XP, and I get problems, such as undefined variables when I run a SQL query.

A tip from Jose Fandos: put a comment on the following two lines in `httpd.conf`, like this:



```
# mod_gzip_item_include file \.php$
# mod_gzip_item_include mime "application/x-httpd-php.*"
```

as this version of mod\_gzip on Apache (Windows) has problems handling PHP scripts. Of course you have to restart Apache.

### 6.1.27 1.26 I just installed phpMyAdmin in my document root of IIS but I get the error “No input file specified” when trying to run phpMyAdmin.

This is a permission problem. Right-click on the phpmyadmin folder and choose properties. Under the tab Security, click on “Add” and select the user “IUSR\_machine” from the list. Now set his permissions and it should work.

### 6.1.28 1.27 I get empty page when I want to view huge page (eg. db\_structure.php with plenty of tables).

This was caused by a PHP bug that occur when GZIP output buffering is enabled. If you turn off it (by `$cfg['OBGzip']` in `config.inc.php`), it should work. This bug will has been fixed in PHP 5.0.0.

### 6.1.29 1.28 My MySQL server sometimes refuses queries and returns the message ‘Errorcode: 13’. What does this mean?

This can happen due to a MySQL bug when having database / table names with upper case characters although `lower_case_table_names` is set to 1. To fix this, turn off this directive, convert all database and table names to lower case and turn it on again. Alternatively, there’s a bug-fix available starting with MySQL 3.23.56 / 4.0.11-gamma.

### 6.1.30 1.29 When I create a table or modify a column, I get an error and the columns are duplicated.

It is possible to configure Apache in such a way that PHP has problems interpreting .php files.

The problems occur when two different (and conflicting) set of directives are used:

```
SetOutputFilter PHP
SetInputFilter PHP
```

and

```
AddType application/x-httpd-php .php
```

In the case we saw, one set of directives was in `/etc/httpd/conf/httpd.conf`, while the other set was in `/etc/httpd/conf/addon-modules/php.conf`. The recommended way is with `AddType`, so just comment out the first set of lines and restart Apache:

```
#SetOutputFilter PHP
#SetInputFilter PHP
```

### 6.1.31 1.30 I get the error “navigation.php: Missing hash”.

This problem is known to happen when the server is running Turck MMCache but upgrading MMCache to version 2.3.21 solves the problem.

### 6.1.32 1.31 Does phpMyAdmin support PHP 5?

Yes.

Since release 4.5, phpMyAdmin supports only PHP 5.5 and newer. Since release 4.1 phpMyAdmin supports only PHP 5.3 and newer. For PHP 5.2 you can use 4.0.x releases.

### 6.1.33 1.32 Can I use HTTP authentication with IIS?

Yes. This procedure was tested with phpMyAdmin 2.6.1, PHP 4.3.9 in *ISAPI* mode under *IIS* 5.1.

1. In your `php.ini` file, set `cgi.rfc2616_headers = 0`
2. In Web Site Properties -> File/Directory Security -> Anonymous Access dialog box, check the Anonymous access checkbox and uncheck any other checkboxes (i.e. uncheck Basic authentication, Integrated Windows authentication, and Digest if it's enabled.) Click OK.
3. In Custom Errors, select the range of 401;1 through 401;5 and click the Set to Default button.

See also:

[RFC 2616](#)

### 6.1.34 1.33 (withdrawn).

### 6.1.35 1.34 Can I access directly to database or table pages?

Yes. Out of the box, you can use *URL* like `http://server/phpMyAdmin/index.php?server=X&db=database&table=table&target=script`. For *server* you use the server number which refers to the order of the server paragraph in `config.inc.php`. Table and script parts are optional. If you want `http://server/phpMyAdmin/database[/table]/[script]` *URL*, you need to do some configuration. Following lines apply only for Apache web server. First make sure, that you have enabled some features within global configuration. You need `Options FollowSymLinks` and `AllowOverride FileInfo` enabled for directory where phpMyAdmin is installed and you need `mod_rewrite` to be enabled. Then you just need to create following `.htaccess` file in root folder of phpMyAdmin installation (don't forget to change directory name inside of it):

```
RewriteEngine On
RewriteBase /path_to_phpMyAdmin
RewriteRule ^([a-zA-Z0-9_]+)/([a-zA-Z0-9_]+)/([a-z_]+\.\php)$ index.php?db=$1&table=$2&target=$3 [R]
RewriteRule ^([a-zA-Z0-9_]+)/([a-z_]+\.\php)$ index.php?db=$1&target=$2 [R]
RewriteRule ^([a-zA-Z0-9_]+)/([a-zA-Z0-9_]+)$ index.php?db=$1&table=$2 [R]
RewriteRule ^([a-zA-Z0-9_]+)$ index.php?db=$1 [R]
```

### 6.1.36 1.35 Can I use HTTP authentication with Apache CGI?

Yes. However you need to pass authentication variable to *CGI* using following rewrite rule:

```
RewriteEngine On
RewriteRule .* - [E=REMOTE_USER:%{HTTP:Authorization},L]
```

### 6.1.37 1.36 I get an error “500 Internal Server Error”.

There can be many explanations to this and a look at your server's error log might give a clue.

### 6.1.38 1.37 I run phpMyAdmin on cluster of different machines and password encryption in cookie auth doesn't work.

If your cluster consist of different architectures, PHP code used for encryption/decryption won't work correct. This is caused by use of pack/unpack functions in code. Only solution is to use mcrypt extension which works fine in this case.

### 6.1.39 1.38 Can I use phpMyAdmin on a server on which Suhosin is enabled?

Yes but the default configuration values of Suhosin are known to cause problems with some operations, for example editing a table with many columns and no primary key or with textual primary key.

Suhosin configuration might lead to malfunction in some cases and it can not be fully avoided as phpMyAdmin is kind of application which needs to transfer big amounts of columns in single HTTP request, what is something what Suhosin tries to prevent. Generally all `suhosin.request.*`, `suhosin.post.*` and `suhosin.get.*` directives can have negative effect on phpMyAdmin usability. You can always find in your error logs which limit did cause dropping of variable, so you can diagnose the problem and adjust matching configuration variable.

The default values for most Suhosin configuration options will work in most scenarios, however you might want to adjust at least following parameters:

- `suhosin.request.max_vars` should be increased (eg. 2048)
- `suhosin.post.max_vars` should be increased (eg. 2048)
- `suhosin.request.max_array_index_length` should be increased (eg. 256)
- `suhosin.post.max_array_index_length` should be increased (eg. 256)
- `suhosin.request.max_totalname_length` should be increased (eg. 8192)
- `suhosin.post.max_totalname_length` should be increased (eg. 8192)
- `suhosin.get.max_value_length` should be increased (eg. 1024)
- `suhosin.sql.bailout_on_error` needs to be disabled (the default)
- `suhosin.log.*` should not include *SQL*, otherwise you get big slowdown

You can also disable the warning using the `$cfg['SuhosinDisableWarning']`.

### 6.1.40 1.39 When I try to connect via https, I can log in, but then my connection is redirected back to http. What can cause this behavior?

Be sure that you have enabled `SSLOptions` and `StdEnvVars` in your Apache configuration.

**See also:**

<[http://httpd.apache.org/docs/2.0/mod/mod\\_ssl.html#ssloptions](http://httpd.apache.org/docs/2.0/mod/mod_ssl.html#ssloptions)>

### 6.1.41 1.40 When accessing phpMyAdmin via an Apache reverse proxy, cookie login does not work.

To be able to use cookie auth Apache must know that it has to rewrite the set-cookie headers. Example from the Apache 2.2 documentation:

```
ProxyPass /mirror/foo/ http://backend.example.com/
ProxyPassReverse /mirror/foo/ http://backend.example.com/
ProxyPassReverseCookieDomain backend.example.com public.example.com
ProxyPassReverseCookiePath / /mirror/foo/
```

Note: if the backend url looks like `http://host/~user/phpmyadmin`, the tilde (~) must be url encoded as %7E in the `ProxyPassReverse*` lines. This is not specific to phpmyadmin, it's just the behavior of Apache.

```
ProxyPass /mirror/foo/ http://backend.example.com/~user/phpmyadmin
ProxyPassReverse /mirror/foo/ http://backend.example.com/%7Euser/phpmyadmin
ProxyPassReverseCookiePath /%7Euser/phpmyadmin /mirror/foo
```

**See also:**

[<http://httpd.apache.org/docs/2.2/mod/mod\\_proxy.html>](http://httpd.apache.org/docs/2.2/mod/mod_proxy.html)

### 6.1.42 1.41 When I view a database and ask to see its privileges, I get an error about an unknown column.

The MySQL server's privilege tables are not up to date, you need to run the `mysql_upgrade` command on the server.

### 6.1.43 1.42 How can I prevent robots from accessing phpMyAdmin?

You can add various rules to `.htaccess` to filter access based on user agent field. This is quite easy to circumvent, but could prevent at least some robots accessing your installation.

```
RewriteEngine on

# Allow only GET and POST verbs
RewriteCond %{REQUEST_METHOD} !^(GET|POST)$ [NC,OR]

# Ban Typical Vulnerability Scanners and others
# Kick out Script Kiddies
RewriteCond %{HTTP_USER_AGENT} ^(java|curl|wget).* [NC,OR]
RewriteCond %{HTTP_USER_AGENT} ^.*(libwww-perl|curl|wget|python|nikto|wkito|pikto|scan|acunetix).* [F]
RewriteCond %{HTTP_USER_AGENT} ^.*(winhttp|HTTrack|clshttp|archiver|loader|email|harvest|extract|grab

# Ban Search Engines, Crawlers to your administrative panel
# No reasons to access from bots
# Ultimately Better than the useless robots.txt
# Did google respect robots.txt?
# Try google: intitle:phpMyAdmin intext:"Welcome to phpMyAdmin *.*.*" intext:"Log in" -wiki -forum -
RewriteCond %{HTTP_USER_AGENT} ^.*(AdsBot-Google|ia_archiver|Scooter|Ask.Jeeves|Baiduspider|Exabot|F

RewriteRule .* - [F]
```

### 6.1.44 1.43 Why can't I display the structure of my table containing hundreds of columns?

Because your PHP's `memory_limit` is too low; adjust it in `php.ini`.

## 6.2 Configuration

### 6.2.1 2.1 The error message “Warning: Cannot add header information - headers already sent by ...” is displayed, what’s the problem?

Edit your `config.inc.php` file and ensure there is nothing (I.E. no blank lines, no spaces, no characters...) neither before the `<?php` tag at the beginning, neither after the `?>` tag at the end. We also got a report from a user under *IIS*, that used a zipped distribution kit: the file `libraries/Config.class.php` contained an end-of-line character (hex 0A) at the end; removing this character cleared his errors.

### 6.2.2 2.2 phpMyAdmin can’t connect to MySQL. What’s wrong?

Either there is an error with your PHP setup or your username/password is wrong. Try to make a small script which uses `mysql_connect` and see if it works. If it doesn’t, it may be you haven’t even compiled MySQL support into PHP.

### 6.2.3 2.3 The error message “Warning: MySQL Connection Failed: Can’t connect to local MySQL server through socket ‘/tmp/mysql.sock’ (111) ...” is displayed. What can I do?

For RedHat users, Harald Legner suggests this on the mailing list:

On my RedHat-Box the socket of MySQL is `/var/lib/mysql/mysql.sock`. In your `php.ini` you will find a line

```
mysql.default_socket = /tmp/mysql.sock
```

change it to

```
mysql.default_socket = /var/lib/mysql/mysql.sock
```

Then restart apache and it will work.

Here is a fix suggested by Brad Ummer:

- First, you need to determine what socket is being used by MySQL. To do this, telnet to your server and go to the MySQL bin directory. In this directory there should be a file named `mysqladmin`. Type `./mysqladmin variables`, and this should give you a bunch of info about your MySQL server, including the socket (`/tmp/mysql.sock`, for example).
- Then, you need to tell PHP to use this socket. To do this in phpMyAdmin, you need to complete the socket information in the `config.inc.php`. For example: `$cfg['Servers'][$i]['socket']` Please also make sure that the permissions of this file allow to be readable by your webserver (i.e. `'0755'`).

Have also a look at the [corresponding section of the MySQL documentation](#).

### 6.2.4 2.4 Nothing is displayed by my browser when I try to run phpMyAdmin, what can I do?

Try to set the `$cfg['OBGzip']` directive to `false` in the phpMyAdmin configuration file. It helps sometime. Also have a look at your PHP version number: if it contains “b” or “alpha” it means you’re running a testing version of PHP. That’s not a so good idea, please upgrade to a plain revision.

### 6.2.5 2.5 Each time I want to insert or change a row or drop a database or a table, an error 404 (page not found) is displayed or, with HTTP or cookie authentication, I'm asked to log in again. What's wrong?

Check the value you set for the `$cfg['PmaAbsoluteUri']` directive in the phpMyAdmin configuration file.

### 6.2.6 2.6 I get an “Access denied for user: ‘root@localhost’ (Using password: YES)”-error when trying to access a MySQL-Server on a host which is port-forwarded for my localhost.

When you are using a port on your localhost, which you redirect via port-forwarding to another host, MySQL is not resolving the localhost as expected. Erik Wasser explains: The solution is: if your host is “localhost” MySQL (the command line tool `mysql` as well) always tries to use the socket connection for speeding up things. And that doesn't work in this configuration with port forwarding. If you enter “127.0.0.1” as hostname, everything is right and MySQL uses the *TCP* connection.

### 6.2.7 2.7 Using and creating themes

Themes are configured with `$cfg['ThemePath']`, `$cfg['ThemeManager']` and `$cfg['ThemeDefault']`. Under `$cfg['ThemePath']`, you should not delete the directory `pmahomme` or its underlying structure, because this is the system theme used by phpMyAdmin. `pmahomme` contains all images and styles, for backwards compatibility and for all themes that would not include images or css-files. If `$cfg['ThemeManager']` is enabled, you can select your favorite theme on the main page. Your selected theme will be stored in a cookie.

To create a theme:

- make a new subdirectory (for example “your\_theme\_name”) under `$cfg['ThemePath']` (by default themes)
- copy the files and directories from `pmahomme` to “your\_theme\_name”
- edit the css-files in “your\_theme\_name/css”
- put your new images in “your\_theme\_name/img”
- edit `layout.inc.php` in “your\_theme\_name”
- edit `info.inc.php` in “your\_theme\_name” to contain your chosen theme name, that will be visible in user interface
- make a new screenshot of your theme and save it under “your\_theme\_name/screen.png”

In theme directory there is file `info.inc.php` which contains theme verbose name, theme generation and theme version. These versions and generations are enumerated from 1 and do not have any direct dependence on phpMyAdmin version. Themes within same generation should be backwards compatible - theme with version 2 should work in phpMyAdmin requiring version 1. Themes with different generation are incompatible.

If you do not want to use your own symbols and buttons, remove the directory “img” in “your\_theme\_name”. phpMyAdmin will use the default icons and buttons (from the system-theme `pmahomme`).

### 6.2.8 2.8 I get “Missing parameters” errors, what can I do?

Here are a few points to check:

- In `config.inc.php`, try to leave the `$cfg['PmaAbsoluteUri']` directive empty. See also *4.7 Authentication window is displayed more than once, why?*.
- Maybe you have a broken PHP installation or you need to upgrade your Zend Optimizer. See <http://bugs.php.net/bug.php?id=31134>.
- If you are using Hardened PHP with the ini directive `varfilter.max_request_variables` set to the default (200) or another low value, you could get this error if your table has a high number of columns. Adjust this setting accordingly. (Thanks to Klaus Dorninger for the hint).
- In the `php.ini` directive `arg_separator.input`, a value of `”;` will cause this error. Replace it with `“&”`.
- If you are using `Hardened-PHP`, you might want to increase `request limits`.
- The directory specified in the `php.ini` directive `session.save_path` does not exist or is read-only.

### 6.2.9 2.9 Seeing an upload progress bar

To be able to see a progress bar during your uploads, your server must have the `APC` extension, the `uploadprogress` one, or you must be running PHP 5.4.0 or higher. Moreover, the `JSON` extension has to be enabled in your PHP.

If using `APC`, you must set `apc.rfc1867` to `on` in your `php.ini`.

If using PHP 5.4.0 or higher, you must set `session.upload_progress.enabled` to `1` in your `php.ini`. However, starting from phpMyAdmin version 4.0.4, session-based upload progress has been temporarily deactivated due to its problematic behavior.

**See also:**

[RFC 1867](#)

## 6.3 Known limitations

### 6.3.1 3.1 When using HTTP authentication, a user who logged out can not log in again in with the same nick.

This is related to the authentication mechanism (protocol) used by phpMyAdmin. To bypass this problem: just close all the opened browser windows and then go back to phpMyAdmin. You should be able to log in again.

### 6.3.2 3.2 When dumping a large table in compressed mode, I get a memory limit error or a time limit error.

Compressed dumps are built in memory and because of this are limited to php's memory limit. For `GZip/BZip2` exports this can be overcome since 2.5.4 using `$cfg['CompressOnFly']` (enabled by default). `Zip` exports can not be handled this way, so if you need `Zip` files for larger dump, you have to use another way.

### 6.3.3 3.3 With InnoDB tables, I lose foreign key relationships when I rename a table or a column.

This is an InnoDB bug, see <http://bugs.mysql.com/bug.php?id=21704>.

### 6.3.4 3.4 I am unable to import dumps I created with the mysqldump tool bundled with the MySQL server distribution.

The problem is that older versions of `mysqldump` created invalid comments like this:

```
-- MySQL dump 8.22
--
-- Host: localhost Database: database
-----
-- Server version 3.23.54
```

The invalid part of the code is the horizontal line made of dashes that appears once in every dump created with `mysqldump`. If you want to run your dump you have to turn it into valid MySQL. This means, you have to add a whitespace after the first two dashes of the line or add a `#` before it: `-- -----` or `#-----`

### 6.3.5 3.5 When using nested folders, multiple hierarchies are displayed in a wrong manner.

Please note that you should not use the separating string multiple times without any characters between them, or at the beginning/end of your table name. If you have to, think about using another `TableSeparator` or disabling that feature.

See also:

```
$cfg['NavigationTreeTableSeparator']
```

### 6.3.6 3.6 (withdrawn).

### 6.3.7 3.7 I have table with many (100+) columns and when I try to browse table I get series of errors like “Warning: unable to parse url”. How can this be fixed?

Your table neither have a primary key nor an unique one, so we must use a long expression to identify this row. This causes problems to `parse_url` function. The workaround is to create a primary or unique key.

### 6.3.8 3.8 I cannot use (clickable) HTML-forms in columns where I put a MIME-Transformation onto!

Due to a surrounding form-container (for multi-row delete checkboxes), no nested forms can be put inside the table where phpMyAdmin displays the results. You can, however, use any form inside of a table if keep the parent form-container with the target to `tbl_row_delete.php` and just put your own input-elements inside. If you use a custom submit input field, the form will submit itself to the displaying page again, where you can validate the `$HTTP_POST_VARS` in a transformation. For a tutorial on how to effectively use transformations, see our [Link section](#) on the official phpMyAdmin-homepage.

### 6.3.9 3.9 I get error messages when using “--sql\_mode=ANSI” for the MySQL server.

When MySQL is running in ANSI-compatibility mode, there are some major differences in how *SQL* is structured (see <http://dev.mysql.com/doc/mysql/en/ansi-mode.html>). Most important of all, the quote-character (`"`) is interpreted as an identifier quote character and not as a string quote character, which makes many internal phpMyAdmin operations



into invalid *SQL* statements. There is no workaround to this behaviour. News to this item will be posted in [Bug report #1013](#).

**6.3.10 3.10 Homonyms and no primary key: When the results of a SELECT display more that one column with the same value (for example `SELECT lastname from employees where firstname like 'A%'` and two “Smith” values are displayed), if I click Edit I cannot be sure that I am editing the intended row.**

Please make sure that your table has a primary key, so that phpMyAdmin can use it for the Edit and Delete links.

**6.3.11 3.11 The number of rows for InnoDB tables is not correct.**

phpMyAdmin uses a quick method to get the row count, and this method only returns an approximate count in the case of InnoDB tables. See `$cfg['MaxExactCount']` for a way to modify those results, but this could have a serious impact on performance. However, one can easily replace the approximate row count with exact count by simply clicking on the approximate count. This can also be done for all tables at once by clicking on the rows sum displayed at the bottom.

**6.3.12 3.12 (withdrawn).**

**6.3.13 3.13 I get an error when entering USE followed by a db name containing an hyphen.**

The tests I have made with MySQL 5.1.49 shows that the API does not accept this syntax for the USE command.

**6.3.14 3.14 I am not able to browse a table when I don't have the right to SELECT one of the columns.**

This has been a known limitation of phpMyAdmin since the beginning and it's not likely to be solved in the future.

**6.3.15 3.15 (withdrawn).**

**6.3.16 3.16 (withdrawn).**

**6.3.17 3.17 (withdrawn).**

**6.3.18 3.18 When I import a CSV file that contains multiple tables, they are lumped together into a single table.**

There is no reliable way to differentiate tables in *CSV* format. For the time being, you will have to break apart *CSV* files containing multiple tables.

### 6.3.19 3.19 When I import a file and have phpMyAdmin determine the appropriate data structure it only uses int, decimal, and varchar types.

Currently, the import type-detection system can only assign these MySQL types to columns. In future, more will likely be added but for the time being you will have to edit the structure to your liking post-import. Also, you should note the fact that phpMyAdmin will use the size of the largest item in any given column as the column size for the appropriate type. If you know you will be adding larger items to that column then you should manually adjust the column sizes accordingly. This is done for the sake of efficiency.

### 6.3.20 3.20 After upgrading, some bookmarks are gone or their content cannot be shown.

At some point, the character set used to store bookmark content has changed. It's better to recreate your bookmark from the newer phpMyAdmin version.

## 6.4 ISPs, multi-user installations

### 6.4.1 4.1 I'm an ISP. Can I setup one central copy of phpMyAdmin or do I need to install it for each customer?

Since version 2.0.3, you can setup a central copy of phpMyAdmin for all your users. The development of this feature was kindly sponsored by NetCologne GmbH. This requires a properly setup MySQL user management and phpMyAdmin *HTTP* or cookie authentication.

**See also:**

*Using authentication modes*

### 6.4.2 4.2 What's the preferred way of making phpMyAdmin secure against evil access?

This depends on your system. If you're running a server which cannot be accessed by other people, it's sufficient to use the directory protection bundled with your webserver (with Apache you can use *.htaccess* files, for example). If other people have telnet access to your server, you should use phpMyAdmin's *HTTP* or cookie authentication features.

Suggestions:

- Your `config.inc.php` file should be `chmod 660`.
- All your phpMyAdmin files should be `chown -R phpmy.apache`, where `phpmy` is a user whose password is only known to you, and `apache` is the group under which Apache runs.
- Follow security recommendations for PHP and your webserver.

### 6.4.3 4.3 I get errors about not being able to include a file in */lang* or in */libraries*.

Check `php.ini`, or ask your sysadmin to check it. The `include_path` must contain `''` somewhere in it, and `open_basedir`, if used, must contain `''` and `"/lang"` to allow normal operation of phpMyAdmin.

### 6.4.4 4.4 phpMyAdmin always gives “Access denied” when using HTTP authentication.

This could happen for several reasons:

- `$cfg['Servers'][$i]['controluser']` and/or `$cfg['Servers'][$i]['controlpass']` are wrong.
- The username/password you specify in the login dialog are invalid.
- You have already setup a security mechanism for the phpMyAdmin- directory, eg. a `.htaccess` file. This would interfere with phpMyAdmin’s authentication, so remove it.

### 6.4.5 4.5 Is it possible to let users create their own databases?

Starting with 2.2.5, in the user management page, you can enter a wildcard database name for a user (for example “joe%”), and put the privileges you want. For example, adding `SELECT`, `INSERT`, `UPDATE`, `DELETE`, `CREATE`, `DROP`, `INDEX`, `ALTER` would let a user create/manage his/her database(s).

### 6.4.6 4.6 How can I use the Host-based authentication additions?

If you have existing rules from an old `.htaccess` file, you can take them and add a username between the ‘deny’/‘allow’ and ‘from’ strings. Using the username wildcard of ‘%’ would be a major benefit here if your installation is suited to using it. Then you can just add those updated lines into the `$cfg['Servers'][$i]['AllowDeny']['rules']` array.

If you want a pre-made sample, you can try this fragment. It stops the ‘root’ user from logging in from any networks other than the private network `IP` blocks.

```
//block root from logging in except from the private networks
$cfg['Servers'][$i]['AllowDeny']['order'] = 'deny,allow';
$cfg['Servers'][$i]['AllowDeny']['rules'] = array(
    'deny root from all',
    'allow root from localhost',
    'allow root from 10.0.0.0/8',
    'allow root from 192.168.0.0/16',
    'allow root from 172.16.0.0/12',
);
```

### 6.4.7 4.7 Authentication window is displayed more than once, why?

This happens if you are using a `URL` to start phpMyAdmin which is different than the one set in your `$cfg['PmaAbsoluteUri']`. For example, a missing “www”, or entering with an `IP` address while a domain name is defined in the config file.

### 6.4.8 4.8 Which parameters can I use in the URL that starts phpMyAdmin?

When starting phpMyAdmin, you can use the `db`, `pma_username`, `pma_password` and `server` parameters. This last one can contain either the numeric host index (from `$i` of the configuration file) or one of the host names present in the configuration file. Using `pma_username` and `pma_password` has been tested along with the usage of ‘cookie’ `auth_type`.

## 6.5 Browsers or client OS

### 6.5.1 5.1 I get an out of memory error, and my controls are non-functional, when trying to create a table with more than 14 columns.

We could reproduce this problem only under Win98/98SE. Testing under WinNT4 or Win2K, we could easily create more than 60 columns. A workaround is to create a smaller number of columns, then come back to your table properties and add the other columns.

### 6.5.2 5.2 With Xitami 2.5b4, phpMyAdmin won't process form fields.

This is not a phpMyAdmin problem but a Xitami known bug: you'll face it with each script/website that use forms. Upgrade or downgrade your Xitami server.

### 6.5.3 5.3 I have problems dumping tables with Konqueror (phpMyAdmin 2.2.2).

With Konqueror 2.1.1: plain dumps, zip and GZip dumps work ok, except that the proposed file name for the dump is always 'tbl\_dump.php'. Bzip2 dumps don't seem to work. With Konqueror 2.2.1: plain dumps work; zip dumps are placed into the user's temporary directory, so they must be moved before closing Konqueror, or else they disappear. GZip dumps give an error message. Testing needs to be done for Konqueror 2.2.2.

### 6.5.4 5.4 I can't use the cookie authentication mode because Internet Explorer never stores the cookies.

MS Internet Explorer seems to be really buggy about cookies, at least till version 6.

### 6.5.5 5.5 In Internet Explorer 5.0, I get JavaScript errors when browsing my rows.

Upgrade to at least Internet Explorer 5.5 SP2.

### 6.5.6 5.6 In Internet Explorer 5.0, 5.5 or 6.0, I get an error (like "Page not found") when trying to modify a row in a table with many columns, or with a text column.

Your table neither have a primary key nor an unique one, so we must use a long *URL* to identify this row. There is a limit on the length of the *URL* in those browsers, and this not happen in Netscape, for example. The workaround is to create a primary or unique key, or use another browser.

### 6.5.7 5.7 I refresh (reload) my browser, and come back to the welcome page.

Some browsers support right-clicking into the frame you want to refresh, just do this in the right frame.

### 6.5.8 5.8 With Mozilla 0.9.7 I have problems sending a query modified in the query box.

Looks like a Mozilla bug: 0.9.6 was OK. We will keep an eye on future Mozilla versions.

### **6.5.9 5.9 With Mozilla 0.9.? to 1.0 and Netscape 7.0-PR1 I can't type a whitespace in the SQL-Query edit area: the page scrolls down.**

This is a Mozilla bug (see bug #26882 at [BugZilla](#)).

### **6.5.10 5.10 With Netscape 4.75 I get empty rows between each row of data in a CSV exported file.**

This is a known Netscape 4.75 bug: it adds some line feeds when exporting data in octet-stream mode. Since we can't detect the specific Netscape version, we cannot workaroud this bug.

### **6.5.11 5.11 Extended-ASCII characters like German umlauts are displayed wrong.**

Please ensure that you have set your browser's character set to the one of the language file you have selected on phpMyAdmin's start page. Alternatively, you can try the auto detection mode that is supported by the recent versions of the most browsers.

### **6.5.12 5.12 Mac OS X Safari browser changes special characters to "?".**

This issue has been reported by a *Mac OS X* user, who adds that Chimera, Netscape and Mozilla do not have this problem.

### **6.5.13 5.13 With Internet Explorer 5.5 or 6, and HTTP authentication type, I cannot manage two servers: I log in to the first one, then the other one, but if I switch back to the first, I have to log in on each operation.**

This is a bug in Internet Explorer, other browsers do not behave this way.

### **6.5.14 5.14 Using Opera6, I can manage to get to the authentication, but nothing happens after that, only a blank screen.**

Please upgrade to Opera7 at least.

### **6.5.15 5.15 I have display problems with Safari.**

Please upgrade to at least version 1.2.3.

### **6.5.16 5.16 With Internet Explorer, I get "Access is denied" Javascript errors. Or I cannot make phpMyAdmin work under Windows.**

Please check the following points:

- Maybe you have defined your `$cfg['PmaAbsoluteUri']` setting in `config.inc.php` to an *IP* address and you are starting phpMyAdmin with a *URL* containing a domain name, or the reverse situation.
- Security settings in IE and/or Microsoft Security Center are too high, thus blocking scripts execution.
- The Windows Firewall is blocking Apache and MySQL. You must allow *HTTP* ports (80 or 443) and MySQL port (usually 3306) in the "in" and "out" directions.

### 6.5.17 5.17 With Firefox, I cannot delete rows of data or drop a database.

Many users have confirmed that the Tabbrowser Extensions plugin they installed in their Firefox is causing the problem.

### 6.5.18 5.18 With Konqueror 4.2.x an invalid `LIMIT` clause is generated when I browse a table.

This happens only when both of these conditions are met: using the `http` authentication mode and `register_globals` being set to `On` on the server. It seems to be a browser-specific problem; meanwhile use the `cookie` authentication mode.

### 6.5.19 5.19 I get JavaScript errors in my browser.

Issues have been reported with some combinations of browser extensions. To troubleshoot, disable all extensions then clear your browser cache to see if the problem goes away.

## 6.6 Using phpMyAdmin

### 6.6.1 6.1 I can't insert new rows into a table / I can't create a table - MySQL brings up a SQL error.

Examine the *SQL* error with care. Often the problem is caused by specifying a wrong column-type. Common errors include:

- Using `VARCHAR` without a size argument
- Using `TEXT` or `BLOB` with a size argument

Also, look at the syntax chapter in the MySQL manual to confirm that your syntax is correct.

### 6.6.2 6.2 When I create a table, I set an index for two columns and phpMyAdmin generates only one index with those two columns.

This is the way to create a multi-columns index. If you want two indexes, create the first one when creating the table, save, then display the table properties and click the Index link to create the other index.

### 6.6.3 6.3 How can I insert a null value into my table?

Since version 2.2.3, you have a checkbox for each column that can be null. Before 2.2.3, you had to enter "null", without the quotes, as the column's value. Since version 2.5.5, you have to use the checkbox to get a real `NULL` value, so if you enter "NULL" this means you want a literal `NULL` in the column, and not a `NULL` value (this works in PHP4).

## 6.6.4 6.4 How can I backup my database or table?

Click on a database or table name in the navigation panel, the properties will be displayed. Then on the menu, click “Export”, you can dump the structure, the data, or both. This will generate standard *SQL* statements that can be used to recreate your database/table. You will need to choose “Save as file”, so that phpMyAdmin can transmit the resulting dump to your station. Depending on your PHP configuration, you will see options to compress the dump. See also the `$cfg['ExecTimeLimit']` configuration variable. For additional help on this subject, look for the word “dump” in this document.

## 6.6.5 6.5 How can I restore (upload) my database or table using a dump? How can I run a “.sql” file?

Click on a database name in the navigation panel, the properties will be displayed. Select “Import” from the list of tabs in the right-hand frame (or “*SQL*” if your phpMyAdmin version is previous to 2.7.0). In the “Location of the text file” section, type in the path to your dump filename, or use the Browse button. Then click Go. With version 2.7.0, the import engine has been re-written, if possible it is suggested that you upgrade to take advantage of the new features. For additional help on this subject, look for the word “upload” in this document.

## 6.6.6 6.6 How can I use the relation table in Query-by-example?

Here is an example with the tables persons, towns and countries, all located in the database “mydb”. If you don’t have a `pma__relation` table, create it as explained in the configuration section. Then create the example tables:

```
CREATE TABLE REL_countries (
country_code char(1) NOT NULL default '',
description varchar(10) NOT NULL default '',
PRIMARY KEY (country_code)
) TYPE=MyISAM;

INSERT INTO REL_countries VALUES ('C', 'Canada');

CREATE TABLE REL_persons (
id tinyint(4) NOT NULL auto_increment,
person_name varchar(32) NOT NULL default '',
town_code varchar(5) default '0',
country_code char(1) NOT NULL default '',
PRIMARY KEY (id)
) TYPE=MyISAM;

INSERT INTO REL_persons VALUES (11, 'Marc', 'S', '');
INSERT INTO REL_persons VALUES (15, 'Paul', 'S', 'C');

CREATE TABLE REL_towns (
town_code varchar(5) NOT NULL default '0',
description varchar(30) NOT NULL default '',
PRIMARY KEY (town_code)
) TYPE=MyISAM;

INSERT INTO REL_towns VALUES ('S', 'Sherbrooke');
INSERT INTO REL_towns VALUES ('M', 'Montréal');
```

To setup appropriate links and display information:

- on table “REL\_persons” click Structure, then Relation view

- for “town\_code”, choose from dropdowns, “mydb”, “REL\_towns”, “code” for foreign database, table and column respectively
- for “country\_code”, choose from dropdowns, “mydb”, “REL\_countries”, “country\_code” for foreign database, table and column respectively
- on table “REL\_towns” click Structure, then Relation view
- in “Choose column to display”, choose “description”
- repeat the two previous steps for table “REL\_countries”

Then test like this:

- Click on your db name in the navigation panel
- Choose “Query”
- Use tables: persons, towns, countries
- Click “Update query”
- In the columns row, choose persons.person\_name and click the “Show” tickbox
- Do the same for towns.description and countries.descriptions in the other 2 columns
- Click “Update query” and you will see in the query box that the correct joins have been generated
- Click “Submit query”

### 6.6.7 6.7 How can I use the “display column” feature?

Starting from the previous example, create the `pma__table_info` as explained in the configuration section, then browse your persons table, and move the mouse over a town code or country code. See also [6.21 In edit/insert mode, how can I see a list of possible values for a column, based on some foreign table?](#) for an additional feature that “display column” enables: drop-down list of possible values.

### 6.6.8 6.8 How can I produce a PDF schema of my database?

First the configuration variables “relation”, “table\_coords” and “pdf\_pages” have to be filled in. Then you need to think about your schema layout. Which tables will go on which pages?

- Select your database in the navigation panel.
- Choose “Operations” in the navigation bar at the top.
- Choose “Edit *PDF* Pages” near the bottom of the page.
- Enter a name for the first *PDF* page and click Go. If you like, you can use the “automatic layout,” which will put all your linked tables onto the new page.
- Select the name of the new page (making sure the Edit radio button is selected) and click Go.
- Select a table from the list, enter its coordinates and click Save. Coordinates are relative; your diagram will be automatically scaled to fit the page. When initially placing tables on the page, just pick any coordinates – say, 50x50. After clicking Save, you can then use the [6.28 How can I easily edit relational schema for export?](#) to position the element correctly.
- When you’d like to look at your *PDF*, first be sure to click the Save button beneath the list of tables and coordinates, to save any changes you made there. Then scroll all the way down, select the *PDF* options you want, and click Go.



- Internet Explorer for Windows may suggest an incorrect filename when you try to save a generated *PDF*. When saving a generated *PDF*, be sure that the filename ends in “.pdf”, for example “schema.pdf”. Browsers on other operating systems, and other browsers on Windows, do not have this problem.

### 6.6.9 6.9 phpMyAdmin is changing the type of one of my columns!

No, it's MySQL that is doing [silent column type changing](#).

### 6.6.10 6.10 When creating a privilege, what happens with underscores in the database name?

If you do not put a backslash before the underscore, this is a wildcard grant, and the underscore means “any character”. So, if the database name is “john\_db”, the user would get rights to john1db, john2db ... If you put a backslash before the underscore, it means that the database name will have a real underscore.

### 6.6.11 6.11 What is the curious symbol ø in the statistics pages?

It means “average”.

### 6.6.12 6.12 I want to understand some Export options.

#### Structure:

- “Add DROP TABLE” will add a line telling MySQL to [drop the table](#), if it already exists during the import. It does NOT drop the table after your export, it only affects the import file.
- “If Not Exists” will only create the table if it doesn't exist. Otherwise, you may get an error if the table name exists but has a different structure.
- “Add AUTO\_INCREMENT value” ensures that AUTO\_INCREMENT value (if any) will be included in backup.
- “Enclose table and column names with backquotes” ensures that column and table names formed with special characters are protected.
- “Add into comments” includes column comments, relations, and MIME types set in the pmadb in the dump as *SQL* comments (*/\* xxx \*/*).

#### Data:

- “Complete inserts” adds the column names on every INSERT command, for better documentation (but resulting file is bigger).
- “Extended inserts” provides a shorter dump file by using only once the INSERT verb and the table name.
- “Delayed inserts” are best explained in the [MySQL manual - INSERT DELAYED Syntax](#).
- “Ignore inserts” treats errors as a warning instead. Again, more info is provided in the [MySQL manual - INSERT Syntax](#), but basically with this selected, invalid values are adjusted and inserted rather than causing the entire statement to fail.

### 6.6.13 6.13 I would like to create a database with a dot in its name.

This is a bad idea, because in MySQL the syntax “database.table” is the normal way to reference a database and table name. Worse, MySQL will usually let you create a database with a dot, but then you cannot work with it, nor delete it.

### 6.6.14 6.14 (withdrawn).

### 6.6.15 6.15 I want to add a BLOB column and put an index on it, but MySQL says “BLOB column ‘..’ used in key specification without a key length”.

The right way to do this, is to create the column without any indexes, then display the table structure and use the “Create an index” dialog. On this page, you will be able to choose your BLOB column, and set a size to the index, which is the condition to create an index on a BLOB column.

### 6.6.16 6.16 How can I simply move in page with plenty editing fields?

You can use `Ctrl+arrows` (`Option+Arrows` in Safari) for moving on most pages with many editing fields (table structure changes, row editing, etc.).

### 6.6.17 6.17 Transformations: I can’t enter my own mimetype! WTF is this feature then useful for?

Slow down :). Defining mimetypes is of no use, if you can’t put transformations on them. Otherwise you could just put a comment on the column. Because entering your own mimetype will cause serious syntax checking issues and validation, this introduces a high-risk false- user-input situation. Instead you have to initialize mimetypes using functions or empty mimetype definitions.

Plus, you have a whole overview of available mimetypes. Who knows all those mimetypes by heart so he/she can enter it at will?

### 6.6.18 6.18 Bookmarks: Where can I store bookmarks? Why can’t I see any bookmarks below the query box? What are these variables for?

Any query you have executed can be stored as a bookmark on the page where the results are displayed. You will find a button labeled ‘Bookmark this query’ just at the end of the page. As soon as you have stored a bookmark, it is related to the database you run the query on. You can now access a bookmark dropdown on each page, the query box appears on for that database.

You can also have, inside the query, placeholders for variables. This is done by inserting into the query SQL comments between `/*` and `*/`. Inside the comments, the special strings `[VARIABLE{variable-number}]` is used. Be aware that the whole query minus the SQL comments must be valid by itself, otherwise you won’t be able to store it as a bookmark.

When you execute the bookmark, everything typed into the *Variables* input boxes on the query box page will replace the strings `/* [VARIABLE{variable-number}] */` in your stored query.

Also remember, that everything else inside the `/* [VARIABLE{variable-number}] */` string for your query will remain the way it is, but will be stripped of the `/**/` chars. So you can use:

```
/*, [VARIABLE1] AS myname */
```

which will be expanded to

```
, VARIABLE1 as myname
```

in your query, where VARIABLE1 is the string you entered in the Variable 1 input box.

A more complex example. Say you have stored this query:

```
SELECT Name, Address FROM addresses WHERE 1 /* AND Name LIKE '%[VARIABLE1]%' */
```

Say, you now enter “phpMyAdmin” as the variable for the stored query, the full query will be:

```
SELECT Name, Address FROM addresses WHERE 1 AND Name LIKE '%phpMyAdmin%'
```

**NOTE THE ABSENCE OF SPACES** inside the `/**/` construct. Any spaces inserted there will be later also inserted as spaces in your query and may lead to unexpected results especially when using the variable expansion inside of a “LIKE” expression.

### 6.6.19 6.19 How can I create simple LATEX document to include exported table?

You can simply include table in your LATEX documents, minimal sample document should look like following one (assuming you have table exported in file `table.tex`):

```
\documentclass{article} % or any class you want
\usepackage{longtable} % for displaying table
\begin{document} % start of document
\include{table} % including exported table
\end{document} % end of document
```

### 6.6.20 6.20 I see a lot of databases which are not mine, and cannot access them.

You have one of these global privileges: CREATE TEMPORARY TABLES, SHOW DATABASES, LOCK TABLES. Those privileges also enable users to see all the database names. So if your users do not need those privileges, you can remove them and their databases list will shorten.

See also:

<<http://bugs.mysql.com/179>>

### 6.6.21 6.21 In edit/insert mode, how can I see a list of possible values for a column, based on some foreign table?

You have to setup appropriate links between the tables, and also setup the “display column” in the foreign table. See [6.6 How can I use the relation table in Query-by-example?](#) for an example. Then, if there are 100 values or less in the foreign table, a drop-down list of values will be available. You will see two lists of values, the first list containing the key and the display column, the second list containing the display column and the key. The reason for this is to be able to type the first letter of either the key or the display column. For 100 values or more, a distinct window will appear, to browse foreign key values and choose one. To change the default limit of 100, see `$cfg['ForeignKeyMaxLimit']`.

### 6.6.22 6.22 Bookmarks: Can I execute a default bookmark automatically when entering Browse mode for a table?

Yes. If a bookmark has the same label as a table name and it’s not a public bookmark, it will be executed.

### 6.6.23 6.23 Export: I heard phpMyAdmin can export Microsoft Excel files?

You can use *CSV* for Microsoft Excel, which works out of the box.

Changed in version 3.4.5: Since phpMyAdmin 3.4.5 support for direct export to Microsoft Excel version 97 and newer was dropped.

### 6.6.24 6.24 Now that phpMyAdmin supports native MySQL 4.1.x column comments, what happens to my column comments stored in pmadb?

Automatic migration of a table's pmadb-style column comments to the native ones is done whenever you enter Structure page for this table.

### 6.6.25 6.25 (withdrawn).

### 6.6.26 6.26 How can I select a range of rows?

Click the first row of the range, hold the shift key and click the last row of the range. This works everywhere you see rows, for example in Browse mode or on the Structure page.

### 6.6.27 6.27 What format strings can I use?

In all places where phpMyAdmin accepts format strings, you can use @VARIABLE@ expansion and `strftime` format strings. The expanded variables depend on a context (for example, if you haven't chosen a table, you can not get the table name), but the following variables can be used:

@HTTP\_HOST@ HTTP host that runs phpMyAdmin

@SERVER@ MySQL server name

@VERBOSE@ Verbose MySQL server name as defined in `$cfg['Servers'][$i]['verbose']`

@VSERVER@ Verbose MySQL server name if set, otherwise normal

@DATABASE@ Currently opened database

@TABLE@ Currently opened table

@COLUMNS@ Columns of the currently opened table

@PHPMYADMIN@ phpMyAdmin with version

### 6.6.28 6.28 How can I easily edit relational schema for export?

By clicking on the button 'toggle scratchboard' on the page where you edit x/y coordinates of those elements you can activate a scratchboard where all your elements are placed. By clicking on an element, you can move them around in the pre-defined area and the x/y coordinates will get updated dynamically. Likewise, when entering a new position directly into the input field, the new position in the scratchboard changes after your cursor leaves the input field.

You have to click on the 'OK'-button below the tables to save the new positions. If you want to place a new element, first add it to the table of elements and then you can drag the new element around.

By changing the paper size and the orientation you can change the size of the scratchboard as well. You can do so by just changing the dropdown field below, and the scratchboard will resize automatically, without interfering with the current placement of the elements.

If ever an element gets out of range you can either enlarge the paper size or click on the 'reset' button to place all elements below each other.

### 6.6.29 6.29 Why can't I get a chart from my query result table?

Not every table can be put to the chart. Only tables with one, two or three columns can be visualised as a chart. Moreover the table must be in a special format for chart script to understand it. Currently supported formats can be found in the [wiki](#).

### 6.6.30 6.30 Import: How can I import ESRI Shapefiles?

An ESRI Shapefile is actually a set of several files, where .shp file contains geometry data and .dbf file contains data related to those geometry data. To read data from .dbf file you need to have PHP compiled with the dBase extension (`--enable-dbase`). Otherwise only geometry data will be imported.

To upload these set of files you can use either of the following methods:

Configure upload directory with `$cfg['UploadDir']`, upload both .shp and .dbf files with the same filename and chose the .shp file from the import page.

Create a Zip archive with .shp and .dbf files and import it. For this to work, you need to set `$cfg['TempDir']` to a place where the web server user can write (for example `./tmp`).

To create the temporary directory on a UNIX-based system, you can do:

```
cd phpMyAdmin
mkdir tmp
chmod o+rx tmp
```

### 6.6.31 6.31 How do I create a relation in designer?

To select relation, click: The display column is shown in pink. To set/unset a column as the display column, click the “Choose column to display” icon, then click on the appropriate column name.

### 6.6.32 6.32 How can I use the zoom search feature?

The Zoom search feature is an alternative to table search feature. It allows you to explore a table by representing its data in a scatter plot. You can locate this feature by selecting a table and clicking the *Search* tab. One of the sub-tabs in the *Table Search* page is *Zoom Search*.

Consider the table REL\_persons in [6.6 How can I use the relation table in Query-by-example?](#) for an example. To use zoom search, two columns need to be selected, for example, id and town\_code. The id values will be represented on one axis and town\_code values on the other axis. Each row will be represented as a point in a scatter plot based on its id and town\_code. You can include two additional search criteria apart from the two fields to display.

You can choose which field should be displayed as label for each point. If a display column has been set for the table (see [6.7 How can I use the “display column” feature?](#)), it is taken as the label unless you specify otherwise. You can also select the maximum number of rows you want to be displayed in the plot by specifying it in the ‘Max rows to plot’ field. Once you have decided over your criteria, click ‘Go’ to display the plot.

After the plot is generated, you can use the mousewheel to zoom in and out of the plot. In addition, panning feature is enabled to navigate through the plot. You can zoom-in to a certain level of detail and use panning to locate your area of interest. Clicking on a point opens a dialogue box, displaying field values of the data row represented by the point. You can edit the values if required and click on submit to issue an update query. Basic instructions on how to use can be viewed by clicking the ‘How to use?’ link located just above the plot.

### 6.6.33 6.33 When browsing a table, how can I copy a column name?

Selecting the name of the column within the browse table header cell for copying is difficult, as the columns support reordering by dragging the header cells as well as sorting by clicking on the linked column name. To copy a column name, double-click on the empty area next to the column name, when the tooltip tells you to do so. This will show you an input box with the column name. You may right-click the column name within this input box to copy it to your clipboard.

### 6.6.34 6.34 How can I use the Favorite Tables feature?

Favorite Tables feature is very much similar to Recent Tables feature. It allows you to add a shortcut for the frequently used tables of any database in the navigation panel. You can easily navigate to any table in the list by simply choosing it from the list. These tables are stored in your browser's local storage if you have not configured your *phpMyAdmin Configuration Storage*. Otherwise these entries are stored in *phpMyAdmin Configuration Storage*.

**IMPORTANT:** In absence of *phpMyAdmin Configuration Storage*, your Favorite tables may be different in different browsers based on your different selections in them.

To add a table to Favorite list simply click on the *Gray* star in front of a table name in the list of tables of a Database and wait until it turns to *Yellow*. To remove a table from list, simply click on the *Yellow* star and wait until it turns *Gray* again.

Using `$cfg['NumFavoriteTables']` in your `config.inc.php` file, you can define the maximum number of favorite tables shown in the navigation panel. Its default value is *10*.

### 6.6.35 6.35 How can I use the Range search feature?

With the help of range search feature, one can specify a range of values for particular column(s) while performing search operation on a table from the *Search* tab.

To use this feature simply click on the *BETWEEN* or *NOT BETWEEN* operators from the operator select list in front of the column name. On choosing one of the above options, a dialog box will show up asking for the *Minimum* and *Maximum* value for that column. Only the specified range of values will be included in case of *BETWEEN* and excluded in case of *NOT BETWEEN* from the final results.

Note: The Range search feature will work only *Numeric* and *Date* data type columns.

### 6.6.36 6.36 What is Central columns and How can I use this feature?

As the name suggests, the Central columns feature enables to maintain a central list of columns per database to avoid similar name for the same data element and bring consistency of data type for the same data element. You can use the central list of columns to add an element to any table structure in that database which will save from writing similar column name and column definition.

To add a column to central list, go to table structure page, check the columns you want to include and then simply click on "Add to central columns". If you want to add all unique columns from more than one table from a database then go to database structure page, check the tables you want to include and then select "Add columns to central list".

To remove a column from central list, go to Table structure page, check the columns you want to remove and then simply click on "Remove from central columns". If you want to remove all columns from more than one tables from a database then go to database structure page, check the tables you want to include and then select "Remove columns from central list".

To view and manage the central list, select the database you want to manage central columns for then from the top menu click on “Central columns”. You will be taken to a page where you will have options to edit, delete or add new columns to central list.

### 6.6.37 6.37 How can I use Improve Table structure feature?

Improve table structure feature helps to bring the table structure upto Third Normal Form. A wizard is presented to user which asks questions about the elements during the various steps for normalization and a new structure is proposed accordingly to bring the table into the First/Second/Third Normal form. On startup of the wizard, user gets to select upto what normal form they want to normalize the table structure.

Here is an example table which you can use to test all of the three First, Second and Third Normal Form.

```
CREATE TABLE `VetOffice` (
  `petName` varchar(64) NOT NULL,
  `petBreed` varchar(64) NOT NULL,
  `petType` varchar(64) NOT NULL,
  `petDOB` date NOT NULL,
  `ownerLastName` varchar(64) NOT NULL,
  `ownerFirstName` varchar(64) NOT NULL,
  `ownerPhone1` int(12) NOT NULL,
  `ownerPhone2` int(12) NOT NULL,
  `ownerEmail` varchar(64) NOT NULL,
);
```

The above table is not in First normal Form as no primary key exists. Primary key is supposed to be (*petName*, *ownerLastName*, *ownerFirstName*). If the primary key is chosen as suggested the resultant table won't be in Second as well as Third Normal form as the following dependencies exists.

```
(OwnerLastName, OwnerFirstName) -> OwnerEmail
(OwnerLastName, OwnerFirstName) -> OwnerPhone
PetBreed -> PetType
```

Which says, OwnerEmail depends on OwnerLastName and OwnerFirstName. OwnerPhone depends on OwnerLastName and OwnerFirstName. PetType depends on PetBreed.

### 6.6.38 6.38 How can I reassign auto-incremented values?

Some users prefer their AUTO\_INCREMENT values to be consecutive; this is not always the case after row deletion.

Here are the steps to accomplish this. These are manual steps because they involve a manual verification at one point.

- Ensure that you have exclusive access to the table to rearrange
- On your primary key column (i.e. id), remove the AUTO\_INCREMENT setting
- Delete your primary key in Structure > indexes
- Create a new column future\_id as primary key, AUTO\_INCREMENT
- Browse your table and verify that the new increments correspond to what you're expecting
- Drop your old id column
- Rename the future\_id column to id
- Move the new id column via Structure > Move columns



### 6.6.39 6.39 What is the “Adjust privileges” option when renaming, copying, or moving a database, table, column, or procedure?

When renaming/copying/moving a database/table/column/procedure, MySQL does not adjust the original privileges relating to these objects on its own. By selecting this option, phpMyAdmin will adjust the privilege table so that users have the same privileges on the new items.

For example: A user ‘bob’@‘localhost’ has a ‘SELECT’ privilege on a column named ‘id’. Now, if this column is renamed to ‘id\_new’; MySQL, on its own, would **not** adjust the column privileges to the new column name. phpMyAdmin can make this adjustment for you automatically.

Notes:

- While adjusting privileges for a database, the privileges of all *table-related privileges*, all *column-related privileges* and all *procedure-related privileges* for the tables, columns and procedures inside that database are also adjusted to the database’s new name.
- Similarly, while adjusting privileges for a table, the privileges of all *column-related privileges* for the columns inside the table are also adjusted to the table’s new name.
- While adjusting privileges, the user performing the operation **must** have the following privileges:
  - SELECT, INSERT, UPDATE, DELETE privileges on following tables: *mysql*.‘db’, *mysql*.‘columns\_priv’, *mysql*.‘tables\_priv’, *mysql*.‘procs\_priv’
  - FLUSH privilege (GLOBAL)

Thus, if you want to replicate the database/table/column/procedure as it is while renaming/copying/moving these objects, make sure you have checked this option.

### 6.6.40 6.40 I see “Bind parameters” checkbox in the “SQL” page. How do I write parameterized SQL queries?

From version 4.5, phpMyAdmin allows users to execute parameterized queries in the “SQL” page. Parameters should be prefixed with a colon(:) and when the “Bind parameters” checkbox is checked these parameters will be identified and input fields for these parameters will be presented. Values entered in these field will be substituted in the query before being executed.

## 6.7 phpMyAdmin project

### 6.7.1 7.1 I have found a bug. How do I inform developers?

Our Bug Tracker is located at <<http://sf.net/projects/phpmyadmin/>> under the Bugs section. But please first discuss your bug with other users: <<https://www.phpmyadmin.net/support/>>

### 6.7.2 7.2 I want to translate the messages to a new language or upgrade an existing language, where do I start?

Translations are very welcome and all you need to have are the language skills. The easiest way is to use our online translation service. You can check out all the possibilities to translate in the [translate](#) section on our website.



### 6.7.3 7.3 I would like to help out with the development of phpMyAdmin. How should I proceed?

We welcome every contribution to the development of phpMyAdmin. You can check out all the possibilities to contribute in the [contribute](#) section on our website.

**See also:**

*Developers Information*

## 6.8 Security

### 6.8.1 8.1 Where can I get information about the security alerts issued for phpMyAdmin?

Please refer to [<https://www.phpmyadmin.net/security/>](https://www.phpmyadmin.net/security/).

### 6.8.2 8.2 How can I protect phpMyAdmin against brute force attacks?

If you use Apache web server, phpMyAdmin exports information about authentication to the Apache environment and it can be used in Apache logs. Currently there are two variables available:

**userID** User name of currently active user (he does not have to be logged in).

**userStatus** Status of currently active user, one of `ok` (user is logged in), `mysql-denied` (MySQL denied user login), `allow-denied` (user denied by allow/deny rules), `root-denied` (root is denied in configuration), `empty-denied` (empty password is denied).

LogFormat directive for Apache can look like following:

```
LogFormat "%h %l %u %t \"%r\" %>s %b \"%{Referer}i\" \"%{User-Agent}i\" %{userID}n %{userStatus}n"
```

You can then use any log analyzing tools to detect possible break-in attempts.

## 6.9 Synchronization

### 6.9.1 9.1 (withdrawn).

### 6.9.2 9.2 (withdrawn).



---

## Developers Information

---

phpMyAdmin is Open Source, so you're invited to contribute to it. Many great features have been written by other people and you too can help to make phpMyAdmin a useful tool.

You can check out all the possibilities to contribute in the [contribute](#) section on our website.



---

## Distributing and packaging phpMyAdmin

---

This document is intended to give advices to people who want to redistribute phpMyAdmin inside other software package such as Linux distribution or some all in one package including web server and MySQL server.

Generally you can customize some basic aspects (paths to some files and behavior) in `libraries/vendor_config.php`.

For example if you want setup script to generate config file in var, change `SETUP_CONFIG_FILE` to `/var/lib/phpmyadmin/config.inc.php` and you will also probably want to skip directory writable check, so set `SETUP_DIR_WRITABLE` to `false`.

### 8.1 External libraries

phpMyAdmin includes several external libraries, you might want to replace them with system ones if they are available, but please note that you should test whether version you provide is compatible with the one we ship.

Currently known list of external libraries:

**js/jquery** jQuery js framework and various jQuery based libraries.

**libraries/php-gettext** php-gettext library

**libraries/tcpdf** tcpdf library, stripped down of not needed files

**libraries/phpseclib** portions of phpseclib library



---

## Copyright

---

```
Copyright (C) 1998-2000 Tobias Ratschiller <tobias_at_ratschiller.com>
Copyright (C) 2001-2014 Marc Delisle <marc_at_infomarc.info>
Olivier Müller <om_at_omnis.ch>
Robin Johnson <robbat2_at_users.sourceforge.net>
Alexander M. Turek <me_at_derrabus.de>
Michal Čihař <michal_at_cihar.com>
Garvin Hicking <me_at_supergarv.de>
Michael Keck <mkkeck_at_users.sourceforge.net>
Sebastian Mendel <cybot_tm_at_users.sourceforge.net>
[check credits for more details]
```

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License version 2, as published by the Free Software Foundation.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

### 9.1 Third party licenses

phpMyAdmin includes several third party libraries which come under their respective licenses.

jQuery's license, which is where we got the files under `js/jquery/` is (MITIGPL), a copy of each license is available in this repository (GPL is available as `LICENSE`, MIT as `js/jquery/MIT-LICENSE.txt`).

TCPDF which is located under `libraries/tcpdf` is released under GPL version 3 and the license is available as `libraries/tcpdf/LICENSE.TXT`.

DejaVu fonts which are located under `libraries/tcpdf/fonts/` and their license is documented in `libraries/tcpdf/fonts/dejavu-fonts-ttf-2.33/LICENSE`.

PHP-gettext which is located under `libraries/php-gettext/` is released under GPL version 2 license which is available in the `LICENSE` file.





## 10.1 Credits, in chronological order

- Tobias Ratschiller <tobias\_at\_ratschiller.com>
  - creator of the phpmyadmin project
  - maintainer from 1998 to summer 2000
- Marc Delisle <marc\_at\_infomarc.info>
  - multi-language version in December 1998
  - various fixes and improvements
  - *SQL* analyser (most of it)
  - current project maintainer
  - maintains content on our website
- Olivier Müller <om\_at\_omnis.ch>
  - started SourceForge phpMyAdmin project in March 2001
  - sync'ed different existing CVS trees with new features and bugfixes
  - multi-language improvements, dynamic language selection
  - many bugfixes and improvements
- Loïc Chapeaux <lolo\_at\_phpheaven.net>
  - rewrote and optimized JavaScript, DHTML and DOM stuff
  - rewrote the scripts so they fit the *PEAR* coding standards and generate XHTML1.0 and CSS2 compliant codes
  - improved the language detection system
  - many bugfixes and improvements
- Robin Johnson <robbat2\_at\_users.sourceforge.net>
  - database maintenance controls
  - table type code
  - Host authentication *IP* Allow/Deny
  - DB-based configuration (Not completed)

- *SQL* parser and pretty-printer
  - *SQL* validator
  - many bugfixes and improvements
- Armel Fauveau <armel.fauveau\_at\_globalis-ms.com>
  - bookmarks feature
  - multiple dump feature
  - gzip dump feature
  - zip dump feature
- Geert Lund <glund\_at\_silversoft.dk>
  - various fixes
  - moderator of the phpMyAdmin former users forum at phpwizard.net
- Korakot Chaovavanich <korakot\_at\_iname.com>
  - “insert as new row” feature
- Pete Kelly <webmaster\_at\_trafficg.com>
  - rewrote and fix dump code
  - bugfixes
- Steve Alberty <alberty\_at\_neptunlabs.de>
  - rewrote dump code for PHP4
  - mySQL table statistics
  - bugfixes
- Benjamin Gandon <gandon\_at\_isia.cma.fr>
  - main author of the version 2.1.0.1
  - bugfixes
- Alexander M. Turek <me\_at\_derrabus.de>
  - MySQL 4.0 / 4.1 / 5.0 compatibility
  - abstract database interface (PMA\_DBI) with MySQLi support
  - privileges administration
  - *XML* exports
  - various features and fixes
  - German language file updates
- Mike Beck <mike.beck\_at\_web.de>
  - automatic joins in QBE
  - links column in printview
  - Relation view
- Michal Čihař <michal\_at\_cihar.com>
  - enhanced index creation/display feature

- feature to use a different charset for HTML than for MySQL
- improvements of export feature
- various features and fixes
- Czech language file updates
- created current website for phpMyAdmin
- Christophe Gesché from the “MySQL Form Generator for PHPMyAdmin” (<http://sf.net/projects/phpmysqlformgen/>)
  - suggested the patch for multiple table printviews
- Garvin Hicking <me\_at\_supergarv.de>
  - built the patch for vertical display of table rows
  - built the Javascript based Query window + *SQL* history
  - Improvement of column/db comments
  - (MIME)-Transformations for columns
  - Use custom alias names for Databases in left frame
  - hierarchical/nested table display
  - *PDF*-scratchboard for WYSIWYG- distribution of *PDF* relations
  - new icon sets
  - vertical display of column properties page
  - some bugfixes, features, support, German language additions
- Yukihiro Kawada <kawada\_at\_den.fujifilm.co.jp>
  - japanese kanji encoding conversion feature
- Piotr Roszatycki <d3xter\_at\_users.sourceforge.net> and Dan Wilson
  - the Cookie authentication mode
- Axel Sander <n8falke\_at\_users.sourceforge.net>
  - table relation-links feature
- Maxime Delorme <delorme.maxime\_at\_free.fr>
  - *PDF* schema output, thanks also to Olivier Plathey for the “FPDF” library (see <<http://www.fpdf.org/>>), Steven Wittens for the “UFPDF” library (see <<http://www.acko.net/node/56>>) and Nicola Asuni for the “TCPDF” library (see <<http://www.tcpdf.org/>>).
- Olof Edlund <olof.edlund\_at\_upright.se>
  - *SQL* validator server
- Ivan R. Lanin <ivanlanin\_at\_users.sourceforge.net>
  - phpMyAdmin logo (until June 2004)
- Mike Cochrane <mike\_at\_graftonhall.co.nz>
  - blowfish library from the Horde project (withdrawn in release 4.0)
- Marcel Tschopp <ne0x\_at\_users.sourceforge.net>
  - mysqli support

- many bugfixes and improvements
- Nicola Asuni (Tecnick.com)
  - TCPDF library (<http://www.tcpdf.org>)
- Michael Keck <mkkeck\_at\_users.sourceforge.net>
  - redesign for 2.6.0
  - phpMyAdmin sailboat logo (June 2004)
- Mathias Landhäußer
  - Representation at conferences
- Sebastian Mendel <cybot\_tm\_at\_users.sourceforge.net>
  - interface improvements
  - various bugfixes
- Ivan A Kirillov
  - new relations Designer
- Raj Kissu Rajandran (Google Summer of Code 2008)
  - BLOBstreaming support (withdrawn in release 4.0)
- Piotr Przybylski (Google Summer of Code 2008, 2010 and 2011)
  - improved setup script
  - user preferences
  - Drizzle support
- Derek Schaefer (Google Summer of Code 2009)
  - Improved the import system
- Alexander Rutkowski (Google Summer of Code 2009)
  - Tracking mechanism
- Zahra Naeem (Google Summer of Code 2009)
  - Synchronization feature (removed in release 4.0)
- Tomáš Srnka (Google Summer of Code 2009)
  - Replication support
- Muhammad Adnan (Google Summer of Code 2010)
  - Relation schema export to multiple formats
- Lori Lee (Google Summer of Code 2010)
  - User interface improvements
  - ENUM/SET editor
  - Simplified interface for export/import
- Ninad Pundalik (Google Summer of Code 2010)
  - AJAXifying the interface
- Martynas Mickevičius (Google Summer of Code 2010)

- Charts
- Barrie Leslie
  - BLOBstreaming support with PBMS PHP extension (withdrawn in release 4.0)
- Ankit Gupta (Google Summer of Code 2010)
  - Visual query builder
- Madhura Jayaratne (Google Summer of Code 2011)
  - OpenGIS support
- Ammar Yasir (Google Summer of Code 2011)
  - Zoom search
- Aris Feryanto (Google Summer of Code 2011)
  - Browse-mode improvements
- Thilanka Kaushalya (Google Summer of Code 2011)
  - AJAXification
- Tyron Madlener (Google Summer of Code 2011)
  - Query statistics and charts for the status page
- Zarubin Stas (Google Summer of Code 2011)
  - Automated testing
- Rouslan Placella (Google Summer of Code 2011 and 2012)
  - Improved support for Stored Routines, Triggers and Events
  - Italian translation updates
  - Removal of frames, new navigation
- Dieter Adriaenssens
  - Various bugfixes
  - Dutch translation updates
- Alex Marin (Google Summer of Code 2012)
  - New plugins and properties system
- Thilina Buddika Abeyrathna (Google Summer of Code 2012)
  - Refactoring
- Atul Pratap Singh (Google Summer of Code 2012)
  - Refactoring
- Chanaka Indrajith (Google Summer of Code 2012)
  - Refactoring
- Yasitha Pandithawatta (Google Summer of Code 2012)
  - Automated testing
- Jim Wigginton (phpseclib.sourceforge.net)
  - phpseclib

- Bin Zu (Google Summer of Code 2013)
  - Refactoring
- Supun Nakandala (Google Summer of Code 2013)
  - Refactoring
- Mohamed Ashraf (Google Summer of Code 2013)
  - AJAX error reporting
- Adam Kang (Google Summer of Code 2013)
  - Automated testing
- Ayush Chaudhary (Google Summer of Code 2013)
  - Automated testing
- Kasun Chathuranga (Google Summer of Code 2013)
  - Interface improvements
- Hugues Peccatte
  - Load/save query by example (database search bookmarks)
- Smita Kumari (Google Summer of Code 2014)
  - Central list of columns
  - Improve table structure (normalization)
- Ashutosh Dhundhara (Google Summer of Code 2014)
  - Interface improvements
- Dhananjay Nakrani (Google Summer of Code 2014)
  - PHP error reporting
- Edward Cheng (Google Summer of Code 2014)
  - SQL Query Console
- Kankanamge Bimal Yashodha (Google Summer of Code 2014)
  - Refactoring: Designer/schema integration
- Chirayu Chiripal (Google Summer of Code 2014)
  - Custom field handlers (Input based MIME transformations)
  - Export with table/column name changes
- Dan Ungureanu (Google Summer of Code 2015)
  - New parser and analyzer
- Nisarg Jhaveri (Google Summer of Code 2015)
  - Page-related settings
  - SQL debugging integration to the Console
  - Other UI improvements

And also to the following people who have contributed minor changes, enhancements, bugfixes or support for a new language since version 2.1.0:

Bora Alioglu, Ricardo ?, Sven-Erik Andersen, Alessandro Astarita, Péter Bakondy, Borges Botelho, Olivier Bussier, Neil Darlow, Mats Engstrom, Ian Davidson, Laurent Dhima, Kristof Hamann, Thomas Kläger, Lubos Klokner, Martin Marconcini, Girish Nair, David Nordenberg, Andreas Pauley, Bernard M. Piller, Laurent Haas, “Sakamoto”, Yuval Sarna, www.securereality.com.au, Alexis Soulard, Alvar Soome, Siu Sun, Peter Svec, Michael Tacosky, Rachim Tamsjadi, Kositer Uros, Luís V., Martijn W. van der Lee, Algis Vainauskas, Daniel Villanueva, Vinay, Ignacio Vazquez-Abrams, Chee Wai, Jakub Wilk, Thomas Michael Winningham, Vilius Zigmantas, “Manuzhai”.

## 10.2 Translators

Following people have contributed to translation of phpMyAdmin:

- Arabic
  - Abdullah Al-Saedi <abdullah.10\_at\_windowslive.com>
- Bulgarian
  - stoyanster <stoyanster\_at\_gmail.com>
- Catalan
  - Xavier Navarro <xvnavarro\_at\_gmail.com>
- Czech
  - Michal Čihář <michal\_at\_cihar.com>
- Danish
  - opensource <opensource\_at\_jth.net>
  - Jørgen Thomsen <opensource\_at\_jth.net>
- German
  - mrbendig <mrbendig\_at\_mrbendig.com>
  - torsten.funck <torsten.funck\_at\_googlemail.com>
  - Sven Strickroth <email\_at\_cs-ware.de>
  - typo3 <typo3\_at\_dirk-weise.de>
  - Jo Michael <me\_at\_mynetx.net>
- Greek
  - Panagiotis Papazoglou <papaz\_p\_at\_yahoo.com>
- English (United Kingdom)
  - Robert Readman <robert\_readman\_at\_hotmail.com>
- Spanish
  - Matías Bellone <matiasbellone\_at\_gmail.com>
- French
  - Marc Delisle <marc\_at\_infomarc.info>
- Hindi

- u4663530 <u4663530\_at\_anu.edu.au>
  - rsedwardian <rsedwardian\_at\_gmail.com>
- Hungarian
  - gergo314 <gergo314\_at\_gmail.com>
- Italian
  - Rouslan Placella <rouslan\_at\_placella.com>
- Japanese
  - Yuichiro <yuichiro\_at\_pop07.odn.ne.jp>
- Lithuanian
  - Kęstutis <forkik\_at\_gmail.com>
- Norwegian Bokmål
  - Sven-Erik Andersen <sven.erik.andersen\_at\_gmail.com>
- Dutch
  - Dieter Adriaenssens <ruleant\_at\_users.sourceforge.net>
  - Herman van Rink <rink\_at\_initfour.nl>
- Polish
  - Stanisław Krukowski <stankruk\_at\_neostrada.pl>
  - Marcin Koziół <lord\_dark\_at\_wp.pl>
- Portuguese
  - JoaoTMDias <contacto\_at\_joaodias.me>
- Portuguese (Brazil)
  - wiltave <wiltave\_at\_gmail.com>
  - emerson4br <emerson4br\_at\_gmail.com>
- Romanian
  - alexukf <alex.ukf\_at\_gmail.com>
- Russian
  - Victor Volkov <hanut\_at\_php-myadmin.ru>
- Sinhala
  - Madhura Jayaratne <madhura.cj\_at\_gmail.com>
- Slovak
  - Martin Lacina <martin\_at\_whistler.sk>
- Slovenian
  - Domen <dbc334\_at\_gmail.com>
- Swedish
  - stefan <stefan\_at\_inkopsforum.se>
- Tamil



- ysajeepan <ysajeepan\_at\_live.com>
- Telugu
  - veeven <veeven\_at\_gmail.com>
- Thai
  - kanichet <kanichet\_at\_hotmail.com>
- Turkish
  - Burak Yavuz <hitowerdigit\_at\_hotmail.com>
- Uighur
  - gheni <gheni\_at\_yahoo.cn>
- Ukrainian
  - typim <duke3d\_at\_ukr.net>
  - oleg-ilnytskyi <ukraine.oleg\_at\_gmail.com>
- Urdu
  - Mehboob Khan <mehboobbugti\_at\_gmail.com>
- Simplified Chinese
  - shanyan baishui <Siramizu\_at\_gmail.com>
- Traditional Chinese
  - star <star\_at\_origin.club.tw>

## 10.3 Documentation translators

Following people have contributed to translation of phpMyAdmin documentation:

- Czech
  - Michal Čihář <michal\_at\_cihar.com>
- Greek
  - Panagiotis Papazoglou <papaz\_p\_at\_yahoo.com>
- English (United Kingdom)
  - Robert Readman <robert\_readman\_at\_hotmail.com>
- French
  - Cédric Corazza <cedric.corazza\_at\_wanadoo.fr>
- Japanese
  - Yuichiro Takahashi <yuichiro\_at\_pop07.odn.ne.jp>
- Polish
  - Stanisław Krukowski <stankruk\_at\_neostrada.pl>
- Portuguese (Brazil)
  - mjaning <mjaning\_at\_gmail.com>

- Slovenian
  - Domenen <dbc334\_at\_gmail.com>

## 10.4 Original Credits of Version 2.1.0

This work is based on Peter Kuppelwieser's MySQL-Webadmin. It was his idea to create a web-based interface to MySQL using PHP3. Although I have not used any of his source-code, there are some concepts I've borrowed from him. phpMyAdmin was created because Peter told me he wasn't going to further develop his (great) tool.

Thanks go to

- Amalesh Kempf <ak-lsml\_at\_living-source.com> who contributed the code for the check when dropping a table or database. He also suggested that you should be able to specify the primary key on tbl\_create.php3. To version 1.1.1 he contributed the ldi\_\*.php3-set (Import text-files) as well as a bug-report. Plus many smaller improvements.
- Jan Legenhausen <jan\_at\_nrw.net>: He made many of the changes that were introduced in 1.3.0 (including quite significant ones like the authentication). For 1.4.1 he enhanced the table-dump feature. Plus bug-fixes and help.
- Marc Delisle <DelislMa\_at\_CollegeSherbrooke.qc.ca> made phpMyAdmin language-independent by outsourcing the strings to a separate file. He also contributed the French translation.
- Alexandr Bravo <abravo\_at\_hq.admiral.ru> who contributed tbl\_select.php3, a feature to display only some columns from a table.
- Chris Jackson <chrisj\_at\_ctel.net> added support for MySQL functions in tbl\_change.php3. He also added the "Query by Example" feature in 2.0.
- Dave Walton <walton\_at\_nordicdms.com> added support for multiple servers and is a regular contributor for bug-fixes.
- Gabriel Ash <ga244\_at\_is8.nyu.edu> contributed the random access features for 2.0.6.

The following people have contributed minor changes, enhancements, bugfixes or support for a new language:

Jim Kraai, Jordi Bruguera, Miquel Obrador, Geert Lund, Thomas Kleemann, Alexander Leidinger, Kiko Albiol, Daniel C. Chao, Pavel Piankov, Sascha Kettler, Joe Pruett, Renato Lins, Mark Kronsbein, Jannis Hermanns, G. Wieggers.

And thanks to everyone else who sent me email with suggestions, bug-reports and or just some feedback.

---

## Glossary

---

From Wikipedia, the free encyclopedia

**.htaccess** the default name of Apache's directory-level configuration file.

**See also:**

<<http://www.wikipedia.org/wiki/.htaccess>>

**ACL** Access Control List

**Blowfish** a keyed, symmetric block cipher, designed in 1993 by Bruce Schneier.

**See also:**

<[http://www.wikipedia.org/wiki/Blowfish\\_\(cipher\)](http://www.wikipedia.org/wiki/Blowfish_(cipher))>

**Browser** a software application that enables a user to display and interact with text, images, and other information typically located on a web page at a website on the World Wide Web.

**See also:**

<[http://en.wikipedia.org/wiki/Web\\_browser](http://en.wikipedia.org/wiki/Web_browser)>

**bzip2** a free software/open source data compression algorithm and program developed by Julian Seward.

**See also:**

<<http://www.wikipedia.org/wiki/Bzip2>>

**CGI** Common Gateway Interface is an important World Wide Web technology that enables a client web browser to request data from a program executed on the Web server.

**See also:**

<<http://www.wikipedia.org/wiki/CGI>>

**Changelog** a log or record of changes made to a project.

**See also:**

<<http://www.wikipedia.org/wiki/Changelog>>

**Client** a computer system that accesses a (remote) service on another computer by some kind of network.

**See also:**

<[http://www.wikipedia.org/wiki/Client\\_\(computing\)](http://www.wikipedia.org/wiki/Client_(computing))>

**column** a set of data values of a particular simple type, one for each row of the table.

**See also:**

<[http://www.wikipedia.org/wiki/Column\\_\(database\)](http://www.wikipedia.org/wiki/Column_(database))>

**Cookie** a packet of information sent by a server to a World Wide Web browser and then sent back by the browser each time it accesses that server.

**See also:**

<[http://www.wikipedia.org/wiki/HTTP\\_cookie](http://www.wikipedia.org/wiki/HTTP_cookie)>

**CSV** Comma- separated values

**See also:**

<[http://www.wikipedia.org/wiki/Comma-separated\\_values](http://www.wikipedia.org/wiki/Comma-separated_values)>

**DB** look at *database*

**database** an organized collection of data.

**See also:**

<<http://www.wikipedia.org/wiki/Database>>

**Engine** look at *storage engines*

**extension** a PHP module that extends PHP with additional functionality.

**See also:**

<<http://www.wikipedia.org/wiki/extension>>

**FAQ** Frequently Asked Questions is a list of commonly asked question and there answers.

**See also:**

<<http://www.wikipedia.org/wiki/FAQ>>

**Field** one part of divided data/columns.

**See also:**

<[http://www.wikipedia.org/wiki/Field\\_\(computer\\_science\)](http://www.wikipedia.org/wiki/Field_(computer_science))>

**foreign key** a column or group of columns in a database row that point to a key column or group of columns forming a key of another database row in some (usually different) table.

**See also:**

<[http://www.wikipedia.org/wiki/Foreign\\_key](http://www.wikipedia.org/wiki/Foreign_key)>

**FPDF** the free *PDF* library

**See also:**

<<http://www.fpdf.org/>>

**GD** Graphics Library by Thomas Boutell and others for dynamically manipulating images.

**See also:**

<[http://www.wikipedia.org/wiki/GD\\_Graphics\\_Library](http://www.wikipedia.org/wiki/GD_Graphics_Library)>

**GD2** look at *gd*

**gzip** gzip is short for GNU zip, a GNU free software file compression program.

**See also:**

<<http://www.wikipedia.org/wiki/Gzip>>

**host** any machine connected to a computer network, a node that has a hostname.

**See also:**

<<http://www.wikipedia.org/wiki/Host>>

**hostname** the unique name by which a network attached device is known on a network.

**See also:**

<<http://www.wikipedia.org/wiki/Hostname>>

**HTTP** HyperText Transfer Protocol is the primary method used to transfer or convey information on the World Wide Web.

**See also:**

<[http://www.wikipedia.org/wiki/HyperText\\_Transfer\\_Protocol](http://www.wikipedia.org/wiki/HyperText_Transfer_Protocol)>

**https** a *HTTP*-connection with additional security measures.

**See also:**

<[http://www.wikipedia.org/wiki/Https\\_URI\\_scheme](http://www.wikipedia.org/wiki/Https_URI_scheme)>

**IEC** International Electrotechnical Commission

**IIS** Internet Information Services is a set of Internet-based services for servers using Microsoft Windows.

**See also:**

<[http://www.wikipedia.org/wiki/Internet\\_Information\\_Services](http://www.wikipedia.org/wiki/Internet_Information_Services)>

**Index** a feature that allows quick access to the rows in a table.

**See also:**

<[http://www.wikipedia.org/wiki/Index\\_\(database\)](http://www.wikipedia.org/wiki/Index_(database))>

**IP** Internet Protocol is a data-oriented protocol used by source and destination hosts for communicating data across a packet-switched internetwork.

**See also:**

<[http://www.wikipedia.org/wiki/Internet\\_Protocol](http://www.wikipedia.org/wiki/Internet_Protocol)>

**IP Address** a unique number that devices use in order to identify and communicate with each other on a network utilizing the Internet Protocol standard.

**See also:**

<[http://www.wikipedia.org/wiki/IP\\_Address](http://www.wikipedia.org/wiki/IP_Address)>

**IPv6** IPv6 (Internet Protocol version 6) is the latest revision of the Internet Protocol (*IP*), designed to deal with the long-anticipated problem of its predecessor IPv4 running out of addresses.

**See also:**

<<http://www.wikipedia.org/wiki/IPv6>>

**ISAPI** Internet Server Application Programming Interface is the API of Internet Information Services (IIS).

**See also:**

<<http://www.wikipedia.org/wiki/ISAPI>>

**ISP** Internet service provider is a business or organization that offers users access to the Internet and related services.

**See also:**

<<http://www.wikipedia.org/wiki/ISP>>

**ISO** International Standards Organisation

**JPEG** a most commonly used standard method of lossy compression for photographic images.

**See also:**

<<http://www.wikipedia.org/wiki/JPEG>>

**JPG** look at *jpeg*

**Key** look at *index*

**LATEX** a document preparation system for the TEX typesetting program.

**See also:**

<<http://www.wikipedia.org/wiki/LaTeX>>

**Mac** Apple Macintosh is line of personal computers is designed, developed, manufactured, and marketed by Apple Computer.

. seealso:: <<http://www.wikipedia.org/wiki/Mac>>

**Mac OS X** the operating system which is included with all currently shipping Apple Macintosh computers in the consumer and professional markets.

**See also:**

<[http://www.wikipedia.org/wiki/Mac\\_OS\\_X](http://www.wikipedia.org/wiki/Mac_OS_X)>

**MCrypt** a cryptographic library.

**See also:**

<<http://www.wikipedia.org/wiki/MCrypt>>

**mccrypt** the MCrypt PHP extension.

**See also:**

<<http://php.net/mccrypt>>

**MIME** Multipurpose Internet Mail Extensions is an Internet Standard for the format of e-mail.

**See also:**

<<http://www.wikipedia.org/wiki/MIME>>

**module** some sort of extension for the Apache Webserver.

**See also:**

<<http://www.wikipedia.org/wiki/module>>

**MySQL** a multithreaded, multi-user, SQL (Structured Query Language) Database Management System (DBMS).

**See also:**

<<http://www.wikipedia.org/wiki/MySQL>>

**mysqli** the improved MySQL client PHP extension.

**See also:**

<<http://php.net/mysqli>>

**mysql** the MySQL client PHP extension.

**See also:**

<<http://php.net/mysql>>

**OpenDocument** open standard for office documents.

**See also:**

<<http://www.wikipedia.org/wiki/OpenDocument>>

**OS X** look at *Mac OS X*.

**See also:**

<[http://www.wikipedia.org/wiki/OS\\_X](http://www.wikipedia.org/wiki/OS_X)>

**PDF** Portable Document Format is a file format developed by Adobe Systems for representing two dimensional documents in a device independent and resolution independent format.

**See also:**

<[http://www.wikipedia.org/wiki/Portable\\_Document\\_Format](http://www.wikipedia.org/wiki/Portable_Document_Format)>

**PEAR** the PHP Extension and Application Repository.

**See also:**

<<http://pear.php.net/>>

**PCRE** Perl Compatible Regular Expressions is the perl-compatible regular expression functions for PHP

**See also:**

<<http://php.net/pcre>>

**PHP** short for “PHP: Hypertext Preprocessor”, is an open-source, reflective programming language used mainly for developing server-side applications and dynamic web content, and more recently, a broader range of software applications.

**See also:**

<<http://www.wikipedia.org/wiki/PHP>>

**port** a connection through which data is sent and received.

**See also:**

<[http://www.wikipedia.org/wiki/Port\\_\(computing\)](http://www.wikipedia.org/wiki/Port_(computing))>

**RFC** Request for Comments (RFC) documents are a series of memoranda encompassing new research, innovations, and methodologies applicable to Internet technologies.

**See also:**

<[http://www.wikipedia.org/wiki/Request\\_for\\_Comments](http://www.wikipedia.org/wiki/Request_for_Comments)>

**RFC 1952** GZIP file format specification version 4.3

**See also:**

**[RFC 1952](#)**

**Row (record, tuple)** represents a single, implicitly structured data item in a table.

**See also:**

<[http://www.wikipedia.org/wiki/Row\\_\(database\)](http://www.wikipedia.org/wiki/Row_(database))>

**Server** a computer system that provides services to other computing systems over a network.

**See also:**

<[http://www.wikipedia.org/wiki/Server\\_\(computing\)](http://www.wikipedia.org/wiki/Server_(computing))>

**Storage Engines** handlers for different table types

**See also:**

<<http://dev.mysql.com/doc/en/storage-engines.html>>

**socket** a form of inter-process communication.

**See also:**

<[http://www.wikipedia.org/wiki/Socket#Computer\\_sockets](http://www.wikipedia.org/wiki/Socket#Computer_sockets)>

**SSL** Secure Sockets Layer is a cryptographic protocol which provides secure communication on the Internet.

**See also:**

<[http://www.wikipedia.org/wiki/Secure\\_Sockets\\_Layer](http://www.wikipedia.org/wiki/Secure_Sockets_Layer)>

**Stored procedure** a subroutine available to applications accessing a relational database system

**See also:**

<[http://en.wikipedia.org/wiki/Stored\\_procedure](http://en.wikipedia.org/wiki/Stored_procedure)>

**SQL** Structured Query Language

**See also:**

<<http://www.wikipedia.org/wiki/SQL>>

**table** a set of data elements (cells) that is organized, defined and stored as horizontal rows and vertical columns where each item can be uniquely identified by a label or key or by its position in relation to other items.

**See also:**

<[http://www.wikipedia.org/wiki/Table\\_\(database\)](http://www.wikipedia.org/wiki/Table_(database))>

**tar** a type of archive file format: the Tape ARchive format.

**See also:**

<[http://www.wikipedia.org/wiki/Tar\\_\(file\\_format\)](http://www.wikipedia.org/wiki/Tar_(file_format))>

**TCP** Transmission Control Protocol is one of the core protocols of the Internet protocol suite.

**See also:**

<<http://www.wikipedia.org/wiki/TCP>>

**TCPDF** Rewrite of *UFPDF* with various improvements.

**See also:**

<<http://www.tcpdf.org/>>

**trigger** a procedural code that is automatically executed in response to certain events on a particular table or view in a database

**See also:**

<[http://en.wikipedia.org/wiki/Database\\_trigger](http://en.wikipedia.org/wiki/Database_trigger)>



**UFPDF** Unicode/UTF-8 extension for *FPDF*

**See also:**

<<http://www.acko.net/node/56>>

**URL** Uniform Resource Locator is a sequence of characters, conforming to a standardized format, that is used for referring to resources, such as documents and images on the Internet, by their location.

**See also:**

<<http://www.wikipedia.org/wiki/URL>>

**Webserver** A computer (program) that is responsible for accepting HTTP requests from clients and serving them Web pages.

**See also:**

<<http://www.wikipedia.org/wiki/Webserver>>

**XML** Extensible Markup Language is a W3C-recommended general- purpose markup language for creating special-purpose markup languages, capable of describing many different kinds of data.

**See also:**

<<http://www.wikipedia.org/wiki/XML>>

**ZIP** a popular data compression and archival format.

**See also:**

<[http://www.wikipedia.org/wiki/ZIP\\_\(file\\_format\)](http://www.wikipedia.org/wiki/ZIP_(file_format))>

**zlib** an open-source, cross- platform data compression library by Jean-loup Gailly and Mark Adler.

**See also:**

<<http://www.wikipedia.org/wiki/Zlib>>



---

**Indices and tables**

---

- genindex
- search
- *Glossary*



## Symbols

- .htaccess, **111**
- \$cfg['ActionLinksMode'], **43**
- \$cfg['AllowArbitraryServer'], **13, 37**
- \$cfg['AllowThirdPartyFraming'], **19**
- \$cfg['AllowUserDropDatabase'], **35**
- \$cfg['ArbitraryServerRegexp'], **37**
- \$cfg['AvailableCharsets'], **48**
- \$cfg['BZipDump'], **45**
- \$cfg['BgOne'], **50**
- \$cfg['BgTwo'], **51**
- \$cfg['Border'], **50**
- \$cfg['BrowseMIME'], **56**
- \$cfg['BrowseMarkerBackground'], **51**
- \$cfg['BrowseMarkerColor'], **51**
- \$cfg['BrowseMarkerEnable'], **52**
- \$cfg['BrowsePointerBackground'], **51**
- \$cfg['BrowsePointerColor'], **51**
- \$cfg['BrowsePointerEnable'], **51, 52**
- \$cfg['CSPAllow'], **49**
- \$cfg['CaptchaLoginPrivateKey'], **15, 37**
- \$cfg['CaptchaLoginPublicKey'], **15, 37**
- \$cfg['CharEditing'], **53, 54**
- \$cfg['CharTextareaCols'], **53**
- \$cfg['CharTextareaRows'], **54**
- \$cfg['CheckConfigurationPermissions'], **49**
- \$cfg['CodemirrorEnable'], **35**
- \$cfg['CompressOnFly'], **45, 75**
- \$cfg['Confirm'], **35**
- \$cfg['ConsoleEnterExecutes'], **19**
- \$cfg['DBG'], **59**
- \$cfg['DBG']['demo'], **59**
- \$cfg['DBG']['sql'], **59**
- \$cfg['DefaultConnectionCollation'], **47**
- \$cfg['DefaultForeignKeyChecks'], **35**
- \$cfg['DefaultFunctions'], **59**
- \$cfg['DefaultLang'], **47**
- \$cfg['DefaultQueryDatabase'], **58**
- \$cfg['DefaultQueryTable'], **58**
- \$cfg['DefaultTabDatabase'], **46**
- \$cfg['DefaultTabServer'], **46**
- \$cfg['DefaultTabTable'], **46**
- \$cfg['DisableMultiTableMaintenance'], **49**
- \$cfg['DisplayServersList'], **39**
- \$cfg['EnableAutocompleteForTablesAndColumns'], **54**
- \$cfg['ExecTimeLimit'], **34, 83**
- \$cfg['Export'], **45**
- \$cfg['Export']['charset'], **48**
- \$cfg['Export']['method'], **45**
- \$cfg['FilterLanguages'], **47**
- \$cfg['FirstLevelNavigationItems'], **38**
- \$cfg['FontFamily'], **51**
- \$cfg['FontFamilyFixed'], **51**
- \$cfg['ForceSSL'], **34**
- \$cfg['ForeignKeyDropdownOrder'], **44**
- \$cfg['ForeignKeyMaxLimit'], **44, 87**
- \$cfg['GD2Available'], **49**
- \$cfg['GZipDump'], **45**
- \$cfg['GridEditing'], **43**
- \$cfg['HideStructureActions'], **42**
- \$cfg['IconvExtraParams'], **48**
- \$cfg['IgnoreMultiSubmitErrors'], **36**
- \$cfg['Import'], **45**
- \$cfg['Import']['charset'], **48**
- \$cfg['InitialSlidersState'], **57**
- \$cfg['InsertRows'], **44**
- \$cfg['Lang'], **47**
- \$cfg['LimitChars'], **52**
- \$cfg['LinkLengthLimit'], **49**
- \$cfg['LoginCookieDeleteAll'], **37**
- \$cfg['LoginCookieRecall'], **36**
- \$cfg['LoginCookieStore'], **36**
- \$cfg['LoginCookieValidity'], **36**
- \$cfg['LoginCookieValidityDisableWarning'], **18**
- \$cfg['LongtextDoubleTextarea'], **54**
- \$cfg['MainBackground'], **50**
- \$cfg['MaxCharactersInDisplayedSQL'], **34**
- \$cfg['MaxDbList'], **33**
- \$cfg['MaxExactCount'], **56, 77**
- \$cfg['MaxExactCountViews'], **57**
- \$cfg['MaxNavigationItems'], **38**

- \$cfg[‘MaxRows’], 43
- \$cfg[‘MaxSizeForInputField’], 53
- \$cfg[‘MaxTableList’], 33
- \$cfg[‘MemoryLimit’], 34
- \$cfg[‘MinSizeForInputField’], 53
- \$cfg[‘MysqlMinVersion’], 42
- \$cfg[‘NaturalOrder’], 57
- \$cfg[‘NaviBackground’], 50
- \$cfg[‘NaviPointerBackground’], 50
- \$cfg[‘NaviPointerColor’], 50
- \$cfg[‘NaviWidth’], 50
- \$cfg[‘NavigationDisplayLogo’], 39
- \$cfg[‘NavigationDisplayServers’], 39
- \$cfg[‘NavigationLinkWithMainPanel’], 39
- \$cfg[‘NavigationLogoLink’], 39
- \$cfg[‘NavigationLogoLinkWindow’], 39
- \$cfg[‘NavigationTreeDbSeparator’], 38
- \$cfg[‘NavigationTreeDefaultTabTable’], 26, 40
- \$cfg[‘NavigationTreeDefaultTabTable2’], 40
- \$cfg[‘NavigationTreeDisplayDbFilterMinimum’], 39
- \$cfg[‘NavigationTreeDisplayItemFilterMinimum’], 39
- \$cfg[‘NavigationTreeEnableExpansion’], 40
- \$cfg[‘NavigationTreeEnableGrouping’], 38
- \$cfg[‘NavigationTreePointerEnable’], 52
- \$cfg[‘NavigationTreeShowEvents’], 41
- \$cfg[‘NavigationTreeShowFunctions’], 40
- \$cfg[‘NavigationTreeShowProcedures’], 41
- \$cfg[‘NavigationTreeShowTables’], 40
- \$cfg[‘NavigationTreeShowViews’], 40
- \$cfg[‘NavigationTreeTableLevel’], 38
- \$cfg[‘NavigationTreeTableSeparator’], 38, 76
- \$cfg[‘NumFavoriteTables’], 90
- \$cfg[‘NumRecentTables’], 26, 38
- \$cfg[‘OBGzip’], 48, 65, 69, 73
- \$cfg[‘Order’], 43
- \$cfg[‘PDFDefaultPageSize’], 47
- \$cfg[‘PDFPageSizes’], 47
- \$cfg[‘PersistentConnections’], 34
- \$cfg[‘PmaAbsoluteUri’], 17, 34, 74, 75, 79, 81
- \$cfg[‘PmaNoRelation\_DisableWarning’], 17
- \$cfg[‘PropertiesNumColumns’], 46
- \$cfg[‘ProtectBinary’], 44
- \$cfg[‘ProxyPass’], 33
- \$cfg[‘ProxyUrl’], 33
- \$cfg[‘ProxyUser’], 33
- \$cfg[‘QueryHistoryDB’], 56
- \$cfg[‘QueryHistoryMax’], 26, 56
- \$cfg[‘RecodingEngine’], 48
- \$cfg[‘RelationalDisplay’], 43
- \$cfg[‘RememberSorting’], 27, 52
- \$cfg[‘RepeatCells’], 56
- \$cfg[‘ReservedWordDisableWarning’], 18
- \$cfg[‘RetainQueryBox’], 35
- \$cfg[‘RowActionLinks’], 52
- \$cfg[‘RowActionLinksWithoutUnique’], 52
- \$cfg[‘RowActionType’], 43
- \$cfg[‘SQLQuery’][‘Edit’], 54
- \$cfg[‘SQLQuery’][‘Explain’], 54
- \$cfg[‘SQLQuery’][‘Refresh’], 54
- \$cfg[‘SQLQuery’][‘ShowAsPHP’], 54
- \$cfg[‘SaveCellsAtOnce’], 44
- \$cfg[‘SaveDir’], 55
- \$cfg[‘SendErrorReports’], 18
- \$cfg[‘ServerDefault’], 32, 33
- \$cfg[‘ServerLibraryDifference\_DisableWarning’], 18
- \$cfg[‘Servers’], 13, 19
- \$cfg[‘Servers’][‘\$i’][‘AllowDeny’][‘order’], 14, 30, 49
- \$cfg[‘Servers’][‘\$i’][‘AllowDeny’][‘rules’], 14, 15, 30, 31, 49, 79
- \$cfg[‘Servers’][‘\$i’][‘AllowNoPassword’], 30
- \$cfg[‘Servers’][‘\$i’][‘AllowRoot’], 30
- \$cfg[‘Servers’][‘\$i’][‘DisableIS’], 32
- \$cfg[‘Servers’][‘\$i’][‘LogoutURL’], 32
- \$cfg[‘Servers’][‘\$i’][‘MaxTableUiprefs’], 30
- \$cfg[‘Servers’][‘\$i’][‘SessionTimeZone’], 30
- \$cfg[‘Servers’][‘\$i’][‘SignonScript’], 13, 14, 32
- \$cfg[‘Servers’][‘\$i’][‘SignonSession’], 13, 14, 32
- \$cfg[‘Servers’][‘\$i’][‘SignonURL’], 13, 14, 32
- \$cfg[‘Servers’][‘\$i’][‘auth\_http\_realm’], 22
- \$cfg[‘Servers’][‘\$i’][‘auth\_swekey\_config’], 14, 22
- \$cfg[‘Servers’][‘\$i’][‘auth\_type’], 14, 22
- \$cfg[‘Servers’][‘\$i’][‘bookmarktable’], 24
- \$cfg[‘Servers’][‘\$i’][‘central\_columns’], 27, 28
- \$cfg[‘Servers’][‘\$i’][‘column\_comments’], 26
- \$cfg[‘Servers’][‘\$i’][‘column\_info’], 25, 26
- \$cfg[‘Servers’][‘\$i’][‘compress’], 21
- \$cfg[‘Servers’][‘\$i’][‘connect\_type’], 21
- \$cfg[‘Servers’][‘\$i’][‘controlhost’], 21
- \$cfg[‘Servers’][‘\$i’][‘controlpass’], 12, 21, 79
- \$cfg[‘Servers’][‘\$i’][‘controlport’], 21
- \$cfg[‘Servers’][‘\$i’][‘controluser’], 12, 13, 21, 79
- \$cfg[‘Servers’][‘\$i’][‘designer\_settings’], 28
- \$cfg[‘Servers’][‘\$i’][‘export\_templates’], 28
- \$cfg[‘Servers’][‘\$i’][‘hide\_db’], 23
- \$cfg[‘Servers’][‘\$i’][‘history’], 26, 56
- \$cfg[‘Servers’][‘\$i’][‘host’], 19, 20, 22
- \$cfg[‘Servers’][‘\$i’][‘navigationhiding’], 27
- \$cfg[‘Servers’][‘\$i’][‘nopassword’], 22
- \$cfg[‘Servers’][‘\$i’][‘only\_db’], 23
- \$cfg[‘Servers’][‘\$i’][‘password’], 14, 22
- \$cfg[‘Servers’][‘\$i’][‘pdf\_pages’], 25
- \$cfg[‘Servers’][‘\$i’][‘pmadb’], 18, 22–30, 39
- \$cfg[‘Servers’][‘\$i’][‘port’], 20
- \$cfg[‘Servers’][‘\$i’][‘recent’], 26, 27
- \$cfg[‘Servers’][‘\$i’][‘relation’], 24
- \$cfg[‘Servers’][‘\$i’][‘savedsearches’], 28
- \$cfg[‘Servers’][‘\$i’][‘socket’], 20, 73
- \$cfg[‘Servers’][‘\$i’][‘ssl’], 20

\$cfg[‘Servers’][‘ssl\_ca’], 21  
 \$cfg[‘Servers’][‘ssl\_ca\_path’], 21  
 \$cfg[‘Servers’][‘ssl\_cert’], 20  
 \$cfg[‘Servers’][‘ssl\_ciphers’], 21  
 \$cfg[‘Servers’][‘ssl\_key’], 20  
 \$cfg[‘Servers’][‘table\_coords’], 25  
 \$cfg[‘Servers’][‘table\_info’], 24, 25  
 \$cfg[‘Servers’][‘table\_uiprefs’], 27, 30  
 \$cfg[‘Servers’][‘tracking’], 28, 29  
 \$cfg[‘Servers’][‘tracking\_add\_drop\_database’], 29  
 \$cfg[‘Servers’][‘tracking\_add\_drop\_table’], 29  
 \$cfg[‘Servers’][‘tracking\_add\_drop\_view’], 29  
 \$cfg[‘Servers’][‘tracking\_default\_statements’], 29  
 \$cfg[‘Servers’][‘tracking\_version\_auto\_create’], 29  
 \$cfg[‘Servers’][‘user’], 14, 22  
 \$cfg[‘Servers’][‘userconfig’], 30  
 \$cfg[‘Servers’][‘usergroups’], 27  
 \$cfg[‘Servers’][‘users’], 27  
 \$cfg[‘Servers’][‘verbose’], 22, 23, 41, 88  
 \$cfg[‘SessionSavePath’], 34  
 \$cfg[‘ShowAll’], 43  
 \$cfg[‘ShowBrowseComments’], 53  
 \$cfg[‘ShowChgPassword’], 41  
 \$cfg[‘ShowCreateDb’], 41  
 \$cfg[‘ShowDatabasesNavigationAsTree’], 37  
 \$cfg[‘ShowDbStructureCreation’], 42  
 \$cfg[‘ShowDbStructureLastCheck’], 42  
 \$cfg[‘ShowDbStructureLastUpdate’], 42  
 \$cfg[‘ShowFieldTypesInDataEditView’], 44  
 \$cfg[‘ShowFunctionFields’], 44  
 \$cfg[‘ShowGitRevision’], 42  
 \$cfg[‘ShowHint’], 34  
 \$cfg[‘ShowPhpInfo’], 41  
 \$cfg[‘ShowPropertyComments’], 53  
 \$cfg[‘ShowSQL’], 35  
 \$cfg[‘ShowServerInfo’], 41  
 \$cfg[‘ShowStats’], 41  
 \$cfg[‘SkipLockedTables’], 35  
 \$cfg[‘SuhosinDisableWarning’], 18, 71  
 \$cfg[‘TableNavigationLinksMode’], 43  
 \$cfg[‘TablePrimaryKeyOrder’], 52  
 \$cfg[‘TabsMode’], 46  
 \$cfg[‘TempDir’], 55, 66, 89  
 \$cfg[‘TextareaAutoSelect’], 54  
 \$cfg[‘TextareaCols’], 53  
 \$cfg[‘TextareaRows’], 53  
 \$cfg[‘ThBackground’], 50  
 \$cfg[‘ThColor’], 50  
 \$cfg[‘ThemeDefault’], 58, 74  
 \$cfg[‘ThemeManager’], 58, 74  
 \$cfg[‘ThemePath’], 58, 74  
 \$cfg[‘ThemePerServer’], 58  
 \$cfg[‘TitleDatabase’], 57  
 \$cfg[‘TitleDefault’], 58

\$cfg[‘TitleServer’], 57  
 \$cfg[‘TitleTable’], 57  
 \$cfg[‘TranslationWarningThreshold’], 18  
 \$cfg[‘TrustedProxies’], 31, 48  
 \$cfg[‘UploadDir’], 55, 67, 89  
 \$cfg[‘UseDbSearch’], 36  
 \$cfg[‘UserprefsDeveloperTab’], 57  
 \$cfg[‘UserprefsDisallow’], 19, 57  
 \$cfg[‘VersionCheck’], 33  
 \$cfg[‘ZeroConf’], 11, 38  
 \$cfg[‘ZipDump’], 45  
 \$cfg[‘blowfish\_secret’], 36

## A

ACL, 111  
 ActionLinksMode, 43  
 AllowArbitraryServer, 37  
 AllowDeny, order, 30  
 AllowDeny, rules, 31  
 AllowNoPassword, 30  
 AllowRoot, 30  
 AllowThirdPartyFraming, 19  
 AllowUserDropDatabase, 35  
 ArbitraryServerRegex, 37  
 auth\_http\_realm, 22  
 auth\_swekey\_config, 22  
 auth\_type, 22  
 Authentication mode, 12
 

- Config, 14
- Cookie, 13
- HTTP, 13
- Signon, 13
- Swekey, 14

 AvailableCharsets, 48

## B

BgOne, 50  
 BgTwo, 51  
 Blowfish, 111  
 blowfish\_secret, 36  
 bookmarktable, 24  
 Border, 50  
 BrowseMarkerBackground, 51  
 BrowseMarkerColor, 51  
 BrowseMarkerEnable, 52  
 BrowseMIME, 56  
 BrowsePointerBackground, 51  
 BrowsePointerColor, 51  
 BrowsePointerEnable, 52  
 Browser, 111  
 bzip2, 111  
 BZipDump, 45

## C

CaptchaLoginPrivateKey, [37](#)

CaptchaLoginPublicKey, [37](#)

central\_columns, [27](#)

CGI, [111](#)

Changelog, [111](#)

CharEditing, [53](#)

CharTextareaCols, [53](#)

CharTextareaRows, [54](#)

CheckConfigurationPermissions, [49](#)

Client, [111](#)

CodemirrorEnable, [35](#)

column, [111](#)

column\_info, [25](#)

compress, [21](#)

CompressOnFly, [45](#)

Config

Authentication mode, [14](#)

config.inc.php, [15](#)

configuration option

- \$cfg[‘ActionLinksMode’], [43](#)
- \$cfg[‘AllowArbitraryServer’], [13](#), [37](#)
- \$cfg[‘AllowThirdPartyFraming’], [19](#)
- \$cfg[‘AllowUserDropDatabase’], [35](#)
- \$cfg[‘ArbitraryServerRegex’], [37](#)
- \$cfg[‘AvailableCharsets’], [48](#)
- \$cfg[‘BZipDump’], [45](#)
- \$cfg[‘BgOne’], [50](#)
- \$cfg[‘BgTwo’], [51](#)
- \$cfg[‘Border’], [50](#)
- \$cfg[‘BrowseMIME’], [56](#)
- \$cfg[‘BrowseMarkerBackground’], [51](#)
- \$cfg[‘BrowseMarkerColor’], [51](#)
- \$cfg[‘BrowseMarkerEnable’], [52](#)
- \$cfg[‘BrowsePointerBackground’], [51](#)
- \$cfg[‘BrowsePointerColor’], [51](#)
- \$cfg[‘BrowsePointerEnable’], [51](#), [52](#)
- \$cfg[‘CSPAllow’], [49](#)
- \$cfg[‘CaptchaLoginPrivateKey’], [15](#), [37](#)
- \$cfg[‘CaptchaLoginPublicKey’], [15](#), [37](#)
- \$cfg[‘CharEditing’], [53](#), [54](#)
- \$cfg[‘CharTextareaCols’], [53](#)
- \$cfg[‘CharTextareaRows’], [54](#)
- \$cfg[‘CheckConfigurationPermissions’], [49](#)
- \$cfg[‘CodemirrorEnable’], [35](#)
- \$cfg[‘CompressOnFly’], [45](#), [75](#)
- \$cfg[‘Confirm’], [35](#)
- \$cfg[‘ConsoleEnterExecutes’], [19](#)
- \$cfg[‘DBG’], [59](#)
- \$cfg[‘DBG’][‘demo’], [59](#)
- \$cfg[‘DBG’][‘sql’], [59](#)
- \$cfg[‘DefaultConnectionCollation’], [47](#)
- \$cfg[‘DefaultForeignKeyChecks’], [35](#)
- \$cfg[‘DefaultFunctions’], [59](#)

- \$cfg[‘DefaultLang’], [47](#)
- \$cfg[‘DefaultQueryDatabase’], [58](#)
- \$cfg[‘DefaultQueryTable’], [58](#)
- \$cfg[‘DefaultTabDatabase’], [46](#)
- \$cfg[‘DefaultTabServer’], [46](#)
- \$cfg[‘DefaultTabTable’], [46](#)
- \$cfg[‘DisableMultiTableMaintenance’], [49](#)
- \$cfg[‘DisplayServersList’], [39](#)
- \$cfg[‘EnableAutocompleteForTablesAndColumns’], [54](#)
- \$cfg[‘ExecTimeLimit’], [34](#), [83](#)
- \$cfg[‘Export’], [45](#)
- \$cfg[‘Export’][‘charset’], [48](#)
- \$cfg[‘Export’][‘method’], [45](#)
- \$cfg[‘FilterLanguages’], [47](#)
- \$cfg[‘FirstLevelNavigationItems’], [38](#)
- \$cfg[‘FontFamily’], [51](#)
- \$cfg[‘FontFamilyFixed’], [51](#)
- \$cfg[‘ForceSSL’], [34](#)
- \$cfg[‘ForeignKeyDropdownOrder’], [44](#)
- \$cfg[‘ForeignKeyMaxLimit’], [44](#), [87](#)
- \$cfg[‘GD2Available’], [49](#)
- \$cfg[‘GZipDump’], [45](#)
- \$cfg[‘GridEditing’], [43](#)
- \$cfg[‘HideStructureActions’], [42](#)
- \$cfg[‘IconvExtraParams’], [48](#)
- \$cfg[‘IgnoreMultiSubmitErrors’], [36](#)
- \$cfg[‘Import’], [45](#)
- \$cfg[‘Import’][‘charset’], [48](#)
- \$cfg[‘InitialSlidersState’], [57](#)
- \$cfg[‘InsertRows’], [44](#)
- \$cfg[‘Lang’], [47](#)
- \$cfg[‘LimitChars’], [52](#)
- \$cfg[‘LinkLengthLimit’], [49](#)
- \$cfg[‘LoginCookieDeleteAll’], [37](#)
- \$cfg[‘LoginCookieRecall’], [36](#)
- \$cfg[‘LoginCookieStore’], [36](#)
- \$cfg[‘LoginCookieValidity’], [36](#)
- \$cfg[‘LoginCookieValidityDisableWarning’], [18](#)
- \$cfg[‘LongtextDoubleTextarea’], [54](#)
- \$cfg[‘MainBackground’], [50](#)
- \$cfg[‘MaxCharactersInDisplayedSQL’], [34](#)
- \$cfg[‘MaxDbList’], [33](#)
- \$cfg[‘MaxExactCount’], [56](#), [77](#)
- \$cfg[‘MaxExactCountViews’], [57](#)
- \$cfg[‘MaxNavigationItems’], [38](#)
- \$cfg[‘MaxRows’], [43](#)
- \$cfg[‘MaxSizeForInputField’], [53](#)
- \$cfg[‘MaxTableList’], [33](#)
- \$cfg[‘MemoryLimit’], [34](#)
- \$cfg[‘MinSizeForInputField’], [53](#)
- \$cfg[‘MysqlMinVersion’], [42](#)
- \$cfg[‘NaturalOrder’], [57](#)
- \$cfg[‘NaviBackground’], [50](#)



- \$cfg['NaviPointerBackground'], 50
- \$cfg['NaviPointerColor'], 50
- \$cfg['NaviWidth'], 50
- \$cfg['NavigationDisplayLogo'], 39
- \$cfg['NavigationDisplayServers'], 39
- \$cfg['NavigationLinkWithMainPanel'], 39
- \$cfg['NavigationLogoLink'], 39
- \$cfg['NavigationLogoLinkWindow'], 39
- \$cfg['NavigationTreeDbSeparator'], 38
- \$cfg['NavigationTreeDefaultTabTable'], 26, 40
- \$cfg['NavigationTreeDefaultTabTable2'], 40
- \$cfg['NavigationTreeDisplayDbFilterMinimum'], 39
- \$cfg['NavigationTreeDisplayItemFilterMinimum'], 39
- \$cfg['NavigationTreeEnableExpansion'], 40
- \$cfg['NavigationTreeEnableGrouping'], 38
- \$cfg['NavigationTreePointerEnable'], 52
- \$cfg['NavigationTreeShowEvents'], 41
- \$cfg['NavigationTreeShowFunctions'], 40
- \$cfg['NavigationTreeShowProcedures'], 41
- \$cfg['NavigationTreeShowTables'], 40
- \$cfg['NavigationTreeShowViews'], 40
- \$cfg['NavigationTreeTableLevel'], 38
- \$cfg['NavigationTreeTableSeparator'], 38, 76
- \$cfg['NumFavoriteTables'], 90
- \$cfg['NumRecentTables'], 26, 38
- \$cfg['OBGzip'], 48, 65, 69, 73
- \$cfg['Order'], 43
- \$cfg['PDFDefaultPageSize'], 47
- \$cfg['PDFPageSizes'], 47
- \$cfg['PersistentConnections'], 34
- \$cfg['PmaAbsoluteUri'], 17, 34, 74, 75, 79, 81
- \$cfg['PmaNoRelation\_DisableWarning'], 17
- \$cfg['PropertiesNumColumns'], 46
- \$cfg['ProtectBinary'], 44
- \$cfg['ProxyPass'], 33
- \$cfg['ProxyUrl'], 33
- \$cfg['ProxyUser'], 33
- \$cfg['QueryHistoryDB'], 56
- \$cfg['QueryHistoryMax'], 26, 56
- \$cfg['RecodingEngine'], 48
- \$cfg['RelationalDisplay'], 43
- \$cfg['RememberSorting'], 27, 52
- \$cfg['RepeatCells'], 56
- \$cfg['ReservedWordDisableWarning'], 18
- \$cfg['RetainQueryBox'], 35
- \$cfg['RowActionLinks'], 52
- \$cfg['RowActionLinksWithoutUnique'], 52
- \$cfg['RowActionType'], 43
- \$cfg['SQLQuery']['Edit'], 54
- \$cfg['SQLQuery']['Explain'], 54
- \$cfg['SQLQuery']['Refresh'], 54
- \$cfg['SQLQuery']['ShowAsPHP'], 54
- \$cfg['SaveCellsAtOnce'], 44
- \$cfg['SaveDir'], 55
- \$cfg['SendErrorReports'], 18
- \$cfg['ServerDefault'], 32, 33
- \$cfg['ServerLibraryDifference\_DisableWarning'], 18
- \$cfg['Servers'], 13, 19
- \$cfg['Servers'][\$i]['AllowDeny']['order'], 14, 30, 49
- \$cfg['Servers'][\$i]['AllowDeny']['rules'], 14, 15, 30, 31, 49, 79
- \$cfg['Servers'][\$i]['AllowNoPassword'], 30
- \$cfg['Servers'][\$i]['AllowRoot'], 30
- \$cfg['Servers'][\$i]['DisableIS'], 32
- \$cfg['Servers'][\$i]['LogoutURL'], 32
- \$cfg['Servers'][\$i]['MaxTableUiprefs'], 30
- \$cfg['Servers'][\$i]['SessionTimeZone'], 30
- \$cfg['Servers'][\$i]['SignonScript'], 13, 14, 32
- \$cfg['Servers'][\$i]['SignonSession'], 13, 14, 32
- \$cfg['Servers'][\$i]['SignonURL'], 13, 14, 32
- \$cfg['Servers'][\$i]['auth\_http\_realm'], 22
- \$cfg['Servers'][\$i]['auth\_swekey\_config'], 14, 22
- \$cfg['Servers'][\$i]['auth\_type'], 14, 22
- \$cfg['Servers'][\$i]['bookmarktable'], 24
- \$cfg['Servers'][\$i]['central\_columns'], 27, 28
- \$cfg['Servers'][\$i]['column\_comments'], 26
- \$cfg['Servers'][\$i]['column\_info'], 25, 26
- \$cfg['Servers'][\$i]['compress'], 21
- \$cfg['Servers'][\$i]['connect\_type'], 21
- \$cfg['Servers'][\$i]['controlhost'], 21
- \$cfg['Servers'][\$i]['controlpass'], 12, 21, 79
- \$cfg['Servers'][\$i]['controlport'], 21
- \$cfg['Servers'][\$i]['controluser'], 12, 13, 21, 79
- \$cfg['Servers'][\$i]['designer\_settings'], 28
- \$cfg['Servers'][\$i]['export\_templates'], 28
- \$cfg['Servers'][\$i]['hide\_db'], 23
- \$cfg['Servers'][\$i]['history'], 26, 56
- \$cfg['Servers'][\$i]['host'], 19, 20, 22
- \$cfg['Servers'][\$i]['navigationhiding'], 27
- \$cfg['Servers'][\$i]['nopassword'], 22
- \$cfg['Servers'][\$i]['only\_db'], 23
- \$cfg['Servers'][\$i]['password'], 14, 22
- \$cfg['Servers'][\$i]['pdf\_pages'], 25
- \$cfg['Servers'][\$i]['pmadb'], 18, 22–30, 39
- \$cfg['Servers'][\$i]['port'], 20
- \$cfg['Servers'][\$i]['recent'], 26, 27
- \$cfg['Servers'][\$i]['relation'], 24
- \$cfg['Servers'][\$i]['savedsearches'], 28
- \$cfg['Servers'][\$i]['socket'], 20, 73
- \$cfg['Servers'][\$i]['ssl'], 20
- \$cfg['Servers'][\$i]['ssl\_ca'], 21
- \$cfg['Servers'][\$i]['ssl\_ca\_path'], 21
- \$cfg['Servers'][\$i]['ssl\_cert'], 20
- \$cfg['Servers'][\$i]['ssl\_ciphers'], 21

- \$cfg['Servers'][\$i]['ssl\_key'], [20](#)
  - \$cfg['Servers'][\$i]['table\_coords'], [25](#)
  - \$cfg['Servers'][\$i]['table\_info'], [24, 25](#)
  - \$cfg['Servers'][\$i]['table\_uiprefs'], [27, 30](#)
  - \$cfg['Servers'][\$i]['tracking'], [28, 29](#)
  - \$cfg['Servers'][\$i]['tracking\_add\_drop\_database'], [29](#)
  - \$cfg['Servers'][\$i]['tracking\_add\_drop\_table'], [29](#)
  - \$cfg['Servers'][\$i]['tracking\_add\_drop\_view'], [29](#)
  - \$cfg['Servers'][\$i]['tracking\_default\_statements'], [29](#)
  - \$cfg['Servers'][\$i]['tracking\_version\_auto\_create'], [29](#)
  - \$cfg['Servers'][\$i]['user'], [14, 22](#)
  - \$cfg['Servers'][\$i]['userconfig'], [30](#)
  - \$cfg['Servers'][\$i]['usergroups'], [27](#)
  - \$cfg['Servers'][\$i]['users'], [27](#)
  - \$cfg['Servers'][\$i]['verbose'], [22, 23, 41, 88](#)
  - \$cfg['SessionSavePath'], [34](#)
  - \$cfg['ShowAll'], [43](#)
  - \$cfg['ShowBrowseComments'], [53](#)
  - \$cfg['ShowChgPassword'], [41](#)
  - \$cfg['ShowCreateDb'], [41](#)
  - \$cfg['ShowDatabasesNavigationAsTree'], [37](#)
  - \$cfg['ShowDbStructureCreation'], [42](#)
  - \$cfg['ShowDbStructureLastCheck'], [42](#)
  - \$cfg['ShowDbStructureLastUpdate'], [42](#)
  - \$cfg['ShowFieldTypesInDataEditView'], [44](#)
  - \$cfg['ShowFunctionFields'], [44](#)
  - \$cfg['ShowGitRevision'], [42](#)
  - \$cfg['ShowHint'], [34](#)
  - \$cfg['ShowPhpInfo'], [41](#)
  - \$cfg['ShowPropertyComments'], [53](#)
  - \$cfg['ShowSQL'], [35](#)
  - \$cfg['ShowServerInfo'], [41](#)
  - \$cfg['ShowStats'], [41](#)
  - \$cfg['SkipLockedTables'], [35](#)
  - \$cfg['SuhosinDisableWarning'], [18, 71](#)
  - \$cfg['TableNavigationLinksMode'], [43](#)
  - \$cfg['TablePrimaryKeyOrder'], [52](#)
  - \$cfg['TabsMode'], [46](#)
  - \$cfg['TempDir'], [55, 66, 89](#)
  - \$cfg['TextareaAutoSelect'], [54](#)
  - \$cfg['TextareaCols'], [53](#)
  - \$cfg['TextareaRows'], [53](#)
  - \$cfg['ThBackground'], [50](#)
  - \$cfg['ThColor'], [50](#)
  - \$cfg['ThemeDefault'], [58, 74](#)
  - \$cfg['ThemeManager'], [58, 74](#)
  - \$cfg['ThemePath'], [58, 74](#)
  - \$cfg['ThemePerServer'], [58](#)
  - \$cfg['TitleDatabase'], [57](#)
  - \$cfg['TitleDefault'], [58](#)
  - \$cfg['TitleServer'], [57](#)
  - \$cfg['TitleTable'], [57](#)
  - \$cfg['TranslationWarningThreshold'], [18](#)
  - \$cfg['TrustedProxies'], [31, 48](#)
  - \$cfg['UploadDir'], [55, 67, 89](#)
  - \$cfg['UseDbSearch'], [36](#)
  - \$cfg['UserprefsDeveloperTab'], [57](#)
  - \$cfg['UserprefsDisallow'], [19, 57](#)
  - \$cfg['VersionCheck'], [33](#)
  - \$cfg['ZeroConf'], [11, 38](#)
  - \$cfg['ZipDump'], [45](#)
  - \$cfg['blowfish\_secret'], [36](#)
- Configuration storage, [11](#)
- Confirm, [35](#)
- connect\_type, [21](#)
- ConsoleEnterExecutes, [19](#)
- controlhost, [21](#)
- controlpass, [21](#)
- controlport, [21](#)
- controluser, [21](#)
- Cookie, [112](#)
- Authentication mode, [13](#)
- CSPAllow, [49](#)
- CSV, [112](#)
- ## D
- database, [112](#)
  - DB, [112](#)
  - DBG, [59](#)
  - DBG, demo, [59](#)
  - DBG, sql, [59](#)
  - DefaultConnectionCollation, [47](#)
  - DefaultForeignKeyChecks, [35](#)
  - DefaultFunctions, [59](#)
  - DefaultLang, [47](#)
  - DefaultQueryDatabase, [58](#)
  - DefaultQueryTable, [58](#)
  - DefaultTabDatabase, [46](#)
  - DefaultTabServer, [46](#)
  - DefaultTabTable, [46](#)
  - designer\_settings, [28](#)
  - DisableIS, [32](#)
  - DisableMultiTableMaintenance, [49](#)
  - DisplayServersList, [39](#)
- ## E
- EnableAutocompleteForTablesAndColumns, [54](#)
  - Engine, [112](#)
  - ExecTimeLimit, [34](#)
  - Export, [45](#)
  - Export, method, [45](#)
  - export\_templates, [28](#)
  - extension, [112](#)

## F

FAQ, [112](#)  
 Field, [112](#)  
 FilterLanguages, [47](#)  
 FirstLevelNavigationItems, [38](#)  
 FontFamily, [51](#)  
 FontFamilyFixed, [51](#)  
 ForceSSL, [34](#)  
 foreign key, [112](#)  
 ForeignKeyDropdownOrder, [44](#)  
 ForeignKeyMaxLimit, [44](#)  
 FPDF, [112](#)

## G

GD, [112](#)  
 GD2, [112](#)  
 GD2Available, [49](#)  
 GridEditing, [43](#)  
 gzip, [112](#)  
 GZipDump, [45](#)

## H

hide\_db, [23](#)  
 HideStructureActions, [42](#)  
 history, [26](#)  
 host, [19](#), [113](#)  
 hostname, [113](#)  
 HTTP, [113](#)  
   Authentication mode, [13](#)  
 https, [113](#)

## I

IconvExtraParams, [48](#)  
 IEC, [113](#)  
 IgnoreMultiSubmitErrors, [36](#)  
 IIS, [113](#)  
 Import, [45](#)  
 Index, [113](#)  
 InitialSlidersState, [57](#)  
 InsertRows, [44](#)  
 IP, [113](#)  
 IP Address, [113](#)  
 IPv6, [113](#)  
 ISAPI, [113](#)  
 ISO, [114](#)  
 ISP, [113](#)

## J

JPEG, [114](#)  
 JPG, [114](#)

## K

Key, [114](#)

## L

Lang, [47](#)  
 LATEX, [114](#)  
 LimitChars, [52](#)  
 LinkLengthLimit, [49](#)  
 LoginCookieDeleteAll, [37](#)  
 LoginCookieRecall, [36](#)  
 LoginCookieStore, [36](#)  
 LoginCookieValidity, [36](#)  
 LoginCookieValidityDisableWarning, [18](#)  
 LogoutURL, [32](#)  
 LongtextDoubleTextarea, [54](#)

## M

Mac, [114](#)  
 Mac OS X, [114](#)  
 MainBackground, [50](#)  
 MaxCharactersInDisplayedSQL, [34](#)  
 MaxDbList, [33](#)  
 MaxExactCount, [56](#)  
 MaxExactCountViews, [57](#)  
 MaxNavigationItems, [38](#)  
 MaxRows, [43](#)  
 MaxSizeForInputField, [53](#)  
 MaxTableList, [33](#)  
 MaxTableUiprefs, [30](#)  
 MCrypt, [114](#)  
 mcrypt, [114](#)  
 MemoryLimit, [34](#)  
 MIME, [114](#)  
 MinSizeForInputField, [53](#)  
 module, [114](#)  
 MySQL, [114](#)  
 mysql, [115](#)  
 mysqli, [114](#)  
 MysqlMinVersion, [42](#)

## N

NaturalOrder, [57](#)  
 NaviBackground, [50](#)  
 NavigationDisplayLogo, [39](#)  
 NavigationDisplayServers, [39](#)  
 navigationhiding, [27](#)  
 NavigationLinkWithMainPanel, [39](#)  
 NavigationLogoLink, [39](#)  
 NavigationLogoLinkWindow, [39](#)  
 NavigationTreeDbSeparator, [38](#)  
 NavigationTreeDefaultTabTable, [40](#)  
 NavigationTreeDefaultTabTable2, [40](#)  
 NavigationTreeDisplayDbFilterMinimum, [39](#)  
 NavigationTreeDisplayItemFilterMinimum, [39](#)  
 NavigationTreeEnableExpansion, [40](#)  
 NavigationTreeEnableGrouping, [38](#)

- NavigationTreePointerEnable, [52](#)
- NavigationTreeShowEvents, [41](#)
- NavigationTreeShowFunctions, [40](#)
- NavigationTreeShowProcedures, [41](#)
- NavigationTreeShowTables, [40](#)
- NavigationTreeShowViews, [40](#)
- NavigationTreeTableLevel, [38](#)
- NavigationTreeTableSeparator, [38](#)
- NaviPointerBackground, [50](#)
- NaviPointerColor, [50](#)
- NaviWidth, [50](#)
- nopassword, [22](#)
- NumRecentTables, [38](#)

## O

- OBGzip, [48](#)
- only\_db, [23](#)
- OpenDocument, [115](#)
- Order, [43](#)
- OS X, [115](#)

## P

- password, [22](#)
- PCRE, [115](#)
- PDF, [115](#)
- pdf\_pages, [25](#)
- PDFDefaultPageSize, [47](#)
- PDFPageSizes, [47](#)
- PEAR, [115](#)
- PersistentConnections, [34](#)
- PHP, [115](#)
- phpMyAdmin configuration storage, [11](#)
- PmaAbsoluteUri, [17](#)
- pmadb, [11](#), [23](#)
- PmaNoRelation\_DisableWarning, [17](#)
- port, [20](#), [115](#)
- PropertiesNumColumns, [46](#)
- ProtectBinary, [44](#)
- ProxyPass, [33](#)
- ProxyUrl, [33](#)
- ProxyUser, [33](#)

## Q

- QueryHistoryDB, [56](#)
- QueryHistoryMax, [56](#)

## R

- recent, [26](#)
- RecodingEngine, [48](#)
- relation, [24](#)
- RelationalDisplay, [43](#)
- RememberSorting, [52](#)
- RepeatCells, [56](#)
- ReservedWordDisableWarning, [18](#)

- RetainQueryBox, [35](#)
- RFC, [115](#)
  - RFC 1867, [75](#)
  - RFC 1952, [115](#)
  - RFC 2616, [70](#)
- RFC 1952, [115](#)
- Row (record, tuple), [115](#)
- RowActionLinks, [52](#)
- RowActionLinksWithoutUnique, [52](#)
- RowActionType, [43](#)

## S

- SaveCellsAtOnce, [44](#)
- SaveDir, [55](#)
- savedsearches, [28](#)
- SendErrorReports, [18](#)
- Server, [116](#)
- server configuration
  - AllowDeny, order, [30](#)
  - AllowDeny, rules, [31](#)
  - AllowNoPassword, [30](#)
  - AllowRoot, [30](#)
  - auth\_http\_realm, [22](#)
  - auth\_swekey\_config, [22](#)
  - auth\_type, [22](#)
  - bookmarktable, [24](#)
  - central\_columns, [27](#)
  - column\_info, [25](#)
  - compress, [21](#)
  - connect\_type, [21](#)
  - controlhost, [21](#)
  - controlpass, [21](#)
  - controlport, [21](#)
  - controluser, [21](#)
  - designer\_settings, [28](#)
  - DisableIS, [32](#)
  - export\_templates, [28](#)
  - hide\_db, [23](#)
  - history, [26](#)
  - host, [19](#)
  - LogoutURL, [32](#)
  - MaxTableUiprefs, [30](#)
  - navigationhiding, [27](#)
  - nopassword, [22](#)
  - only\_db, [23](#)
  - password, [22](#)
  - pdf\_pages, [25](#)
  - pmadb, [23](#)
  - port, [20](#)
  - recent, [26](#)
  - relation, [24](#)
  - savedsearches, [28](#)
  - SessionTimeZone, [30](#)
  - SignonScript, [32](#)

- SignonSession, [32](#)
- SignonURL, [32](#)
- socket, [20](#)
- ssl, [20](#)
- ssl\_ca, [21](#)
- ssl\_ca\_path, [21](#)
- ssl\_cert, [20](#)
- ssl\_ciphers, [21](#)
- ssl\_key, [20](#)
- table\_coords, [25](#)
- table\_info, [24](#)
- table\_uiprefs, [27](#)
- tracking, [28](#)
- tracking\_add\_drop\_database, [29](#)
- tracking\_add\_drop\_table, [29](#)
- tracking\_add\_drop\_view, [29](#)
- tracking\_default\_statements, [29](#)
- tracking\_version\_auto\_create, [29](#)
- user, [22](#)
- userconfig, [30](#)
- usergroups, [27](#)
- users, [27](#)
- verbose, [23](#)
- ServerDefault, [32](#)
- ServerLibraryDifference\_DisableWarning, [18](#)
- Servers, [19](#)
- SessionSavePath, [34](#)
- SessionTimeZone, [30](#)
- Setup script, [9](#)
- ShowAll, [43](#)
- ShowBrowseComments, [53](#)
- ShowChgPassword, [41](#)
- ShowCreateDb, [41](#)
- ShowDatabasesNavigationAsTree, [37](#)
- ShowDbStructureCreation, [42](#)
- ShowDbStructureLastCheck, [42](#)
- ShowDbStructureLastUpdate, [42](#)
- ShowFieldTypesInDataEditView, [44](#)
- ShowFunctionFields, [44](#)
- ShowGitRevision, [42](#)
- ShowHint, [34](#)
- ShowPhpInfo, [41](#)
- ShowPropertyComments, [53](#)
- ShowServerInfo, [41](#)
- ShowSQL, [35](#)
- ShowStats, [41](#)
- Signon
  - Authentication mode, [13](#)
- SignonScript, [32](#)
- SignonSession, [32](#)
- SignonURL, [32](#)
- SkipLockedTables, [35](#)
- socket, [20](#), [116](#)
- SQL, [116](#)

- SQLQuery, Edit, [54](#)
- SQLQuery, Explain, [54](#)
- SQLQuery, Refresh, [54](#)
- SQLQuery, ShowAsPHP, [54](#)
- SSL, [116](#)
- ssl, [20](#)
- ssl\_ca, [21](#)
- ssl\_ca\_path, [21](#)
- ssl\_cert, [20](#)
- ssl\_ciphers, [21](#)
- ssl\_key, [20](#)
- Storage Engines, [116](#)
- Stored procedure, [116](#)
- SuhosinDisableWarning, [18](#)
- Swekey
  - Authentication mode, [14](#)

## T

- table, [116](#)
- table\_coords, [25](#)
- table\_info, [24](#)
- table\_uiprefs, [27](#)
- TableNavigationLinksMode, [43](#)
- TablePrimaryKeyOrder, [52](#)
- TabsMode, [46](#)
- tar, [116](#)
- TCP, [116](#)
- TCPDF, [116](#)
- TempDir, [55](#)
- TextareaAutoSelect, [54](#)
- TextareaCols, [53](#)
- TextareaRows, [53](#)
- ThBackground, [50](#)
- ThColor, [50](#)
- ThemeDefault, [58](#)
- ThemeManager, [58](#)
- ThemePath, [58](#)
- ThemePerServer, [58](#)
- TitleDatabase, [57](#)
- TitleDefault, [58](#)
- TitleServer, [57](#)
- TitleTable, [57](#)
- tracking, [28](#)
- tracking\_add\_drop\_database, [29](#)
- tracking\_add\_drop\_table, [29](#)
- tracking\_add\_drop\_view, [29](#)
- tracking\_default\_statements, [29](#)
- tracking\_version\_auto\_create, [29](#)
- TranslationWarningThreshold, [18](#)
- trigger, [116](#)
- TrustedProxies, [48](#)

## U

- UFPDF, [117](#)

UploadDir, [55](#)  
URL, [117](#)  
UseDbSearch, [36](#)  
user, [22](#)  
userconfig, [30](#)  
usergroups, [27](#)  
UserprefsDeveloperTab, [57](#)  
UserprefsDisallow, [57](#)  
users, [27](#)

## V

verbose, [23](#)  
VersionCheck, [33](#)

## W

Websserver, [117](#)

## X

XML, [117](#)

## Z

ZeroConf, [38](#)  
ZIP, [117](#)  
ZipDump, [45](#)  
zlib, [117](#)