

---

# **Pulp Smash Documentation**

*Release 2018.04.12*

**Jeremy Audet**

**Apr 23, 2018**



---

# Contents

---

<b>1</b>	<b>Introductory Video</b>	<b>3</b>
<b>2</b>	<b>Installation</b>	<b>5</b>
<b>3</b>	<b>Usage</b>	<b>7</b>
3.1	Configuring Pulp Smash . . . . .	7
3.2	Running the tests . . . . .	9
<b>4</b>	<b>About</b>	<b>11</b>
4.1	Why Pulp Smash? . . . . .	11
4.2	Scope and Limitations . . . . .	12
4.3	Contributing . . . . .	12
<b>5</b>	<b>Introductory Module</b>	<b>15</b>
<b>6</b>	<b>API Documentation</b>	<b>19</b>
6.1	<i>pulp_smash</i> . . . . .	19
6.2	<i>pulp_smash.api</i> . . . . .	19
6.3	<i>pulp_smash.cli</i> . . . . .	23
6.4	<i>pulp_smash.config</i> . . . . .	27
6.5	<i>pulp_smash.constants</i> . . . . .	31
6.6	<i>pulp_smash.exceptions</i> . . . . .	37
6.7	<i>pulp_smash.pulp_smash_cli</i> . . . . .	38
6.8	<i>pulp_smash.selectors</i> . . . . .	38
6.9	<i>pulp_smash.tests</i> . . . . .	39
6.10	<i>pulp_smash.tests.pulp2</i> . . . . .	41
6.11	<i>pulp_smash.tests.pulp2.constants</i> . . . . .	41
6.12	<i>pulp_smash.tests.pulp2.docker</i> . . . . .	42
6.13	<i>pulp_smash.tests.pulp2.docker.api_v2</i> . . . . .	42
6.14	<i>pulp_smash.tests.pulp2.docker.api_v2.test_copy</i> . . . . .	42
6.15	<i>pulp_smash.tests.pulp2.docker.api_v2.test_crud</i> . . . . .	43
6.16	<i>pulp_smash.tests.pulp2.docker.api_v2.test_duplicate_uploads</i> . . . . .	44
6.17	<i>pulp_smash.tests.pulp2.docker.api_v2.test_sync</i> . . . . .	44
6.18	<i>pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish</i> . . . . .	45
6.19	<i>pulp_smash.tests.pulp2.docker.api_v2.test_tags</i> . . . . .	48
6.20	<i>pulp_smash.tests.pulp2.docker.api_v2.test_upload</i> . . . . .	49
6.21	<i>pulp_smash.tests.pulp2.docker.api_v2.utils</i> . . . . .	50

6.22	<i>pulp_smash.tests.pulp2.docker.cli</i>	51
6.23	<i>pulp_smash.tests.pulp2.docker.cli.test_crud</i>	51
6.24	<i>pulp_smash.tests.pulp2.docker.cli.test_sync_publish</i>	53
6.25	<i>pulp_smash.tests.pulp2.docker.cli.utils</i>	53
6.26	<i>pulp_smash.tests.pulp2.docker.utils</i>	54
6.27	<i>pulp_smash.tests.pulp2.ostree</i>	54
6.28	<i>pulp_smash.tests.pulp2.ostree.api_v2</i>	54
6.29	<i>pulp_smash.tests.pulp2.ostree.api_v2.test_copy</i>	54
6.30	<i>pulp_smash.tests.pulp2.ostree.api_v2.test_crud</i>	55
6.31	<i>pulp_smash.tests.pulp2.ostree.api_v2.test_publish</i>	57
6.32	<i>pulp_smash.tests.pulp2.ostree.api_v2.test_sync</i>	57
6.33	<i>pulp_smash.tests.pulp2.ostree.utils</i>	58
6.34	<i>pulp_smash.tests.pulp2.platform</i>	58
6.35	<i>pulp_smash.tests.pulp2.platform.api_v2</i>	58
6.36	<i>pulp_smash.tests.pulp2.platform.api_v2.test_consumer</i>	59
6.37	<i>pulp_smash.tests.pulp2.platform.api_v2.test_content_applicability</i>	59
6.38	<i>pulp_smash.tests.pulp2.platform.api_v2.test_login</i>	60
6.39	<i>pulp_smash.tests.pulp2.platform.api_v2.test_repository</i>	60
6.40	<i>pulp_smash.tests.pulp2.platform.api_v2.test_search</i>	62
6.41	<i>pulp_smash.tests.pulp2.platform.api_v2.test_user</i>	64
6.42	<i>pulp_smash.tests.pulp2.platform.cli</i>	66
6.43	<i>pulp_smash.tests.pulp2.platform.cli.test_pulp_manage_db</i>	66
6.44	<i>pulp_smash.tests.pulp2.platform.cli.test_selinux</i>	67
6.45	<i>pulp_smash.tests.pulp2.platform.utils</i>	68
6.46	<i>pulp_smash.tests.pulp2.puppet</i>	68
6.47	<i>pulp_smash.tests.pulp2.puppet.api_v2</i>	68
6.48	<i>pulp_smash.tests.pulp2.puppet.api_v2.test_crud</i>	69
6.49	<i>pulp_smash.tests.pulp2.puppet.api_v2.test_duplicate_uploads</i>	69
6.50	<i>pulp_smash.tests.pulp2.puppet.api_v2.test_install_distributor</i>	69
6.51	<i>pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish</i>	70
6.52	<i>pulp_smash.tests.pulp2.puppet.api_v2.utils</i>	72
6.53	<i>pulp_smash.tests.pulp2.puppet.cli</i>	72
6.54	<i>pulp_smash.tests.pulp2.puppet.cli.test_sync</i>	73
6.55	<i>pulp_smash.tests.pulp2.puppet.utils</i>	74
6.56	<i>pulp_smash.tests.pulp2.python</i>	74
6.57	<i>pulp_smash.tests.pulp2.python.api_v2</i>	74
6.58	<i>pulp_smash.tests.pulp2.python.api_v2.test_crud</i>	74
6.59	<i>pulp_smash.tests.pulp2.python.api_v2.test_duplicate_uploads</i>	74
6.60	<i>pulp_smash.tests.pulp2.python.api_v2.test_sync_publish</i>	75
6.61	<i>pulp_smash.tests.pulp2.python.api_v2.utils</i>	76
6.62	<i>pulp_smash.tests.pulp2.python.utils</i>	76
6.63	<i>pulp_smash.tests.pulp2.rpm</i>	76
6.64	<i>pulp_smash.tests.pulp2.rpm.api_v2</i>	77
6.65	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_broker</i>	77
6.66	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_character_encoding</i>	78
6.67	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_comps_xml</i>	78
6.68	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_content_applicability</i>	81
6.69	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_content_sources</i>	82
6.70	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_copy</i>	83
6.71	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_crud</i>	84
6.72	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_download_policies</i>	85
6.73	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_duplicate_uploads</i>	88
6.74	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_errata</i>	89
6.75	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_export</i>	90

6.76	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_force_full</i>	92
6.77	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_iso_crud</i>	93
6.78	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_iso_sync_publish</i>	95
6.79	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist</i>	96
6.80	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_no_op_publish</i>	98
6.81	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_orphan_remove</i>	99
6.82	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_package_paths</i>	100
6.83	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_remove_unit</i>	101
6.84	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_repomd</i>	103
6.85	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_repository_layout</i>	104
6.86	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_repoview</i>	105
6.87	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_republish</i>	105
6.88	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_retain_old_count</i>	106
6.89	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_rsync_distributor</i>	107
6.90	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_publish</i>	111
6.91	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_sync</i>	112
6.92	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_search</i>	114
6.93	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_service_resiliency</i>	115
6.94	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_copies</i>	116
6.95	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_syncs</i>	118
6.96	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_uploads</i>	121
6.97	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_saved_for_packages</i>	124
6.98	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish</i>	125
6.99	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_tasks</i>	128
6.100	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_unassociate</i>	128
6.101	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_unavailable_checksum</i>	130
6.102	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_updateinfo</i>	131
6.103	<i>pulp_smash.tests.pulp2.rpm.api_v2.test_upload_publish</i>	135
6.104	<i>pulp_smash.tests.pulp2.rpm.api_v2.utils</i>	138
6.105	<i>pulp_smash.tests.pulp2.rpm.cli</i>	141
6.106	<i>pulp_smash.tests.pulp2.rpm.cli.test_character_encoding</i>	142
6.107	<i>pulp_smash.tests.pulp2.rpm.cli.test_copy_units</i>	142
6.108	<i>pulp_smash.tests.pulp2.rpm.cli.test_environments</i>	144
6.109	<i>pulp_smash.tests.pulp2.rpm.cli.test_langpacks</i>	144
6.110	<i>pulp_smash.tests.pulp2.rpm.cli.test_process_recycling</i>	145
6.111	<i>pulp_smash.tests.pulp2.rpm.cli.test_retain_old_count</i>	145
6.112	<i>pulp_smash.tests.pulp2.rpm.cli.test_search</i>	146
6.113	<i>pulp_smash.tests.pulp2.rpm.cli.test_sync</i>	147
6.114	<i>pulp_smash.tests.pulp2.rpm.cli.test_upload</i>	148
6.115	<i>pulp_smash.tests.pulp2.rpm.cli.utils</i>	148
6.116	<i>pulp_smash.tests.pulp2.rpm.utils</i>	149
6.117	<i>pulp_smash.tests.pulp2.utils</i>	150
6.118	<i>pulp_smash.tests.pulp3</i>	150
6.119	<i>pulp_smash.tests.pulp3.constants</i>	150
6.120	<i>pulp_smash.tests.pulp3.file</i>	151
6.121	<i>pulp_smash.tests.pulp3.file.api_v3</i>	151
6.122	<i>pulp_smash.tests.pulp3.file.api_v3.test_crd_publications</i>	151
6.123	<i>pulp_smash.tests.pulp3.file.api_v3.test_crud_content_unit</i>	151
6.124	<i>pulp_smash.tests.pulp3.file.api_v3.test_crud_publishers</i>	152
6.125	<i>pulp_smash.tests.pulp3.file.api_v3.test_crud_remotes</i>	153
6.126	<i>pulp_smash.tests.pulp3.file.api_v3.test_download_content</i>	154
6.127	<i>pulp_smash.tests.pulp3.file.api_v3.test_orphans</i>	154
6.128	<i>pulp_smash.tests.pulp3.file.api_v3.test_publish</i>	155
6.129	<i>pulp_smash.tests.pulp3.file.api_v3.test_repo_version</i>	155

6.130	<i>pulp_smash.tests.pulp3.file.api_v3.test_sync</i>	157
6.131	<i>pulp_smash.tests.pulp3.file.api_v3.test_unlinking_repo</i>	158
6.132	<i>pulp_smash.tests.pulp3.file.api_v3.utils</i>	159
6.133	<i>pulp_smash.tests.pulp3.file.utils</i>	159
6.134	<i>pulp_smash.tests.pulp3.pulpcore</i>	159
6.135	<i>pulp_smash.tests.pulp3.pulpcore.api_v3</i>	159
6.136	<i>pulp_smash.tests.pulp3.pulpcore.api_v3.test_api_docs</i>	159
6.137	<i>pulp_smash.tests.pulp3.pulpcore.api_v3.test_auth</i>	160
6.138	<i>pulp_smash.tests.pulp3.pulpcore.api_v3.test_crd_artifacts</i>	161
6.139	<i>pulp_smash.tests.pulp3.pulpcore.api_v3.test_crud_distributions</i>	162
6.140	<i>pulp_smash.tests.pulp3.pulpcore.api_v3.test_crud_repos</i>	162
6.141	<i>pulp_smash.tests.pulp3.pulpcore.api_v3.test_crud_users</i>	163
6.142	<i>pulp_smash.tests.pulp3.pulpcore.api_v3.test_status</i>	164
6.143	<i>pulp_smash.tests.pulp3.pulpcore.api_v3.test_workers</i>	164
6.144	<i>pulp_smash.tests.pulp3.pulpcore.utils</i>	165
6.145	<i>pulp_smash.tests.pulp3.utils</i>	165
6.146	<i>pulp_smash.utils</i>	168
6.147	<i>tests</i>	173
6.148	<i>tests.test_api</i>	173
6.149	<i>tests.test_cli</i>	174
6.150	<i>tests.test_config</i>	175
6.151	<i>tests.test_pulp_smash_cli</i>	177
6.152	<i>tests.test_selectors</i>	178
6.153	<i>tests.test_utils</i>	179

**Python Module Index**

**183**

Pulp Smash is a test suite for [Pulp](#). It lets you execute a workflow like this:

```
pip install pulp-smash
pulp-smash settings create # generate a settings file
python3 -m unittest discover pulp_smash.tests # run the tests
```

Pulp Smash is a GPL-licensed Python library, but no knowledge of Python is required to execute the tests. Just install the application, run it, and follow the prompts.

Pulp Smash has a presence on the following websites:

- [Documentation](#) is available on ReadTheDocs.
- A [Python package](#) is available on PyPi.
- [Source code](#) and the issue tracker are available on GitHub.

Documentation contents:





# CHAPTER 1

---

## Introductory Video

---

Location: *Pulp Smash* → *Introductory Video*

This video demonstrates how to install Pulp, demonstrates how to install, configure and run Pulp Smash, shows where to find more information, and covers some additional information. It covers much of the same information as the text-based documentation.

This video is designed to be viewed full-screen.

For more videos on Pulp and Pulp Smash, see the [Pulp Vimeo group](#).



## CHAPTER 2

---

### Installation

---

Location: *Pulp Smash* → *Installation*

Installing Pulp Smash into a virtual environment<sup>1</sup> is recommended. To create and activate a virtual environment:

```
python3 -m venv env
source env/bin/activate # run `deactivate` to exit environment
```

Pulp Smash can be installed from PyPI or from source. To install from PyPI:

```
pip install pulp-smash # prepend `python -m` on Python 3.3
```

To install Pulp Smash from source (GitHub):

```
git clone https://github.com/PulpQE/pulp-smash.git
cd pulp-smash
pip install .
```

Pulp Smash can also be installed from source in “develop mode,” where changes to source code are reflected in the working environment. The `--editable` flag does this. Also, development dependencies can be installed by requiring the extra “dev” group.

```
git clone https://github.com/PulpQE/pulp-smash.git
cd pulp-smash
pip install --editable .[dev]
```

For an explanation of key concepts and more installation strategies, see [Installing Python Modules](#).

---

<sup>1</sup> See [Virtual Environments and Packages](#) for an explanation of virtual environments. `python3 -m venv` and `virtualenv` are similar, but the former ships with Python as of Python 3.3, whereas the latter is a third party tool.



Location: *Pulp Smash* → *Usage*

## 3.1 Configuring Pulp Smash

Pulp Smash needs a configuration file to be present in order to know how to access the Pulp system under test. To do that you can use the following command:

```
pulp-smash settings create
```

Provide the information like the authentication credentials for a Pulp admin user, Pulp version, the system hostname, if the system is published under HTTPS or not, etc.

The `pulp-smash settings create` command will generate a settings file for a Pulp deployment. For more information about how to install Pulp check its [installation docs](#). The generated settings file will assume that both Pulp's Admin Client and Alternate Download Policies are installed and configured.

If you are planning to test a clustered Pulp deployment, then you are going to need to manually edit the settings file. Before getting into the details of the settings file, let's see how Pulp Smash finds the settings file.

Pulp Smash abides by the XDG Base Directory Specification. The configuration file may be placed in any XDG-compliant location. The first configuration file found is used. Settings are not cascaded.

---

**Note:** The default settings filename is `settings.json` and it must be under a directory called `pulp_smash`. The `pulp_smash` directory may be placed in any XDG-compliant location.

---

A non-default configuration file can be selected with an environment variable like so: `PULP_SMASH_CONFIG_FILE=alternate-settings.json python3 -m unittest discover pulp_smash.tests`. This variable should be a file name, not a path.

**Note:** Setting `PULP_SMASH_CONFIG_FILE` will make Pulp Smash look for an alternate filename but the file must continue be placed under the `pulp_smash` directory on any XDG-compliant location.

---

Now that how Pulp Smash finds the settings file is known, let's know how the configuration file format is. Consider the example below:

```
{
  "pulp": {
    "auth": ["username", "password"],
    "version": "2.12.2"
  },
  "systems": [
    {
      "hostname": "pulp.example.com",
      "roles": {
        "amqp broker": {"service": "qpidd"},
        "api": {
          "scheme": "https",
          "verify": true
        },
        "mongod": {},
        "pulp cli": {},
        "pulp celerybeat": {},
        "pulp resource manager": {},
        "pulp workers": {},
        "shell": {"transport": "local"},
        "squid": {}
      }
    }
  ]
}
```

Pulp Smash's configuration file format allows configuring either a Pulp deployment (as seen in the example above) or a clustered Pulp deployment where each service can be installed on its own machine. The “pulp” section lets you declare the version of and authentication credentials for the Pulp deployment under test. The “systems” section provides information about each system that composes the deployment. A system must have its hostname and the roles that system has.

**Note:** The only required role for a system is the `shell` role. Pulp Smash will not be able to test a Pulp deployment if any of the required roles are missing, see `pulp_smash.config.REQUIRED_ROLES` for the list of required roles.

---

Not all roles requires additional information. Currently, only the `amqp broker`, `api` and `shell` roles do. The `amqp broker` expects the service to be defined and it can be either `qpidd` or `rabbitmq`. The `api` role means that `httpd` will be running on the system. The `api`'s `scheme` allows specifying if the API should be accessed using HTTP or HTTPS, `verify` allows specifying if the request SSL certificate should be verified (true or false or a path to a custom certificate file, the path must be local to the system where Pulp Smash is being run). The `shell` role configures how the system will be accessed by using a `local` or `ssh` transport, only set `local` if Pulp Smash is running on that same system.

**Note:** Pulp Smash can access a system via SSH only if the SSH connection can be made without typing a password. Make sure to configure SSH so just running `ssh $hostname` will access the system. See `sshd_config(5)`.

---

The example below shows a configuration file that enables Pulp Smash to access a clustered Pulp deployment:

```

{
  "pulp": {
    "auth": ["username", "password"],
    "version": "2.12.1"
  },
  "systems": [
    {
      "hostname": "first.example.com",
      "roles": {
        "amqp broker": {"service": "qpidd"},
        "api": {"scheme": "https", "verify": true},
        "mongod": {},
        "pulp cli": {},
        "pulp celerybeat": {},
        "pulp resource manager": {},
        "pulp workers": {},
        "shell": {"transport": "ssh"},
        "squid": {}
      }
    },
    {
      "hostname": "second.example.com",
      "roles": {
        "api": {"scheme": "https", "verify": false},
        "pulp celerybeat": {},
        "pulp resource manager": {},
        "pulp workers": {},
        "shell": {"transport": "ssh"},
        "squid": {}
      }
    }
  ]
}

```

Note that the roles `mongod` and `amqp broker` is only available on the first system and that the Pulp related roles plus the `squid` are available on both. The example shows how to have a clustered deployment where second system will connect to the first system's `mongod` and `amqp broker`, all the other services will work as a failover redundancy. Like, if first system's `pulp resource manager` goes down than Pulp failover feature will activate and start using the second system's `pulp resource manager`.

Pulp Smash also has two other commands to help with configuration file management: `pulp-smash settings show` and `pulp-smash settings validate` to show the current settings file and validate the settings file format schema respectively. Those commands will take into consideration the environment variables to select an alternate settings file.

## 3.2 Running the tests

All tests can be run by running the command below:

```
python3 -m unittest discover pulp_smash.tests
```

Any subset of tests may also be selected. For example, you may also run `python3 -m unittest pulp_smash.tests.pulp2.platform.api_v2.test_login`. Consult the unittest documentation for test selection syntax, and consult the *API Documentation* to see which test modules are available, check the tests under the `pulp_smash.tests.* namespace`.





Location: *Pulp Smash* → *About*

Why does Pulp Smash exist? What are its goals, and what does it *not* do?

- *Why Pulp Smash?*
- *Scope and Limitations*
  - *Portability*
  - *Provisioning*
  - *Destructiveness*
- *Contributing*
  - *Learning Pulp Smash*
  - *Code Standards*
  - *Review Process*
  - *Labels*

## 4.1 Why Pulp Smash?

Pulp Smash exists to make testing Pulp easy.

## 4.2 Scope and Limitations

### 4.2.1 Portability

Pulp Smash should be usable in any environment that supports:

- one of the Python versions listed in `.travis.yml`,
- the dependencies listed in `setup.py`,
- a \*nix-like shell,
- the XDG Base Directory Specification,
- and OpenSSH or a compatible clone.

In addition, we recommend that GNU Make or a compatible clone be available.

This level of portability<sup>1</sup> allows Pulp Smash to be accessible<sup>2</sup>.

### 4.2.2 Provisioning

Pulp Smash is not concerned with provisioning systems. Users must bring their own systems.

### 4.2.3 Destructiveness

*Pulp Smash is highly destructive!* You should not use Pulp Smash for testing if you care about the state of the target system. Pulp Smash will do the following to a system under test, and possibly more:

- It will drop databases.
- It will forcefully delete files from the filesystem.
- It will stop and start system services.

Pulp Smash treats the system(s) under test as cattle, not pets.<sup>3</sup>

## 4.3 Contributing

Contributions are encouraged. The easiest way to contribute is to submit a pull request on GitHub, but patches are welcome no matter how they arrive.

### 4.3.1 Learning Pulp Smash

Not sure where to start? Consider reading an existing test module, creating a development environment, and tackling an open issue.

The *Introductory Module* is a great candidate for study.

---

<sup>1</sup> Portable software cannot make assumptions about its environment. It cannot reference `/etc/pki/tls/certs/ca-bundle.crt` or call `yum`. Instead, it must use standardized mechanisms for interacting with its environment. This separation of concerns should lead to an application with fewer responsibilities. Fewer responsibilities means fewer bugs and more focused developers.

<sup>2</sup> An inaccessible project is a dead project. Labeling a project “open source” and licensing it under a suitable terms does not change that fact. People have better things to do than bang their head against a wall.

<sup>3</sup> The “pets vs cattle” analogy is widely attributed to Bill Baker of Microsoft.

*Installation* provides a recipe for creating a virtualenv-based development environment. To verify the sanity of your development environment, `cd` into the Pulp Smash source code directory and execute `make all`.

The [Pulp Smash issues](#) list includes test cases that should be automated and added to the test suite.

### 4.3.2 Code Standards

Please adhere to the following guidelines:

- Pull requests must pass the [Travis CI](#) continuous integration tests. These tests are automatically run whenever a pull request is submitted. If you want to locally verify your changes before submitting a pull request, execute `make all`.
- Test failures must not be introduced. Consider running all new and modified tests and copy-pasting the output from the test run as a comment in the GitHub pull request. The simplest way to run the test suite is with `python3 -m unittest pulp_smash.tests`. See the unittest [Command-Line Interface](#) and `python3 -m pulp_smash` for more information.
- Each commit in a pull request must be atomic and address a single issue. Try asking yourself: “can I revert this commit?” Knowing how to [rewrite history](#) may help. In addition, please take the time to write a [good commit message](#). While not *strictly* necessary, consider: commits are (nearly) immutable, and getting commit messages right makes for a more pleasant review process, better release notes, and easier use of tools like `git log`, `git blame` or `git bisect`.
- The pull request must not raise any other outstanding concerns. For example, do not author a commit that adds a 10MB binary blob without exceedingly good reason. As another example, do not add a test that makes dozens of concurrent requests to a public service such as docker hub.

These next guidelines **are not** mandatory, but will match the formatting adopted in the existing code base.

- Docstrings should not end with a blank line.
- Lines should be hard wrapped at 79 characters.
- Comments should typically be preceded by a blank line.

### 4.3.3 Review Process

Changes that meet the *code standards* will be reviewed by a Pulp Smash developer and are likely to be merged.

Though commits are accepted as-is, they are frequently accompanied by a follow-up commit in which the reviewer makes a variety of changes, ranging from simple typo corrections and formatting adjustments to whole-sale restructuring of tests. This can take quite a bit of effort and time. If you’d like to make the review process faster and have more assurance your changes are being accepted with little to no modifications, take the time to really make your changes shine: ensure your code is DRY, matches existing formatting conventions, is organized into easy-to-read blocks, has isolated unit test assertions, and so on.

Join the [#pulp](#) IRC channel on [freenode](#) if you have further questions.

### 4.3.4 Labels

Issues are categorized with [labels](#). Pull requests are categorized with GitHub’s [pull request reviews](#) feature.

The specific meaning of (issue) labels is as follows.

**Issue Type: Bug** This label denotes an issue that describes a specific counter-productive behaviour. For example, an issue entitled “test X contains an incorrect assertion” is a great candidate for this label.

**Issue Type: Discussion** This label denotes an issue that broadly discusses some topic. Feature requests should be given this label. If a discussion results in a specific and concrete plan of action, a new issue should be opened, where that issue outlines a specific solution and has a label of “Issue Type: Plan”.

**Issue Type: Plan** This label denotes an issue that outlines a specific, concrete plan of action for improving Pulp Smash. This may include plans for new utilities or refactors of existing tests or other tools. Open-ended discussions (including feature requests) should go into issues labeled “Issue Type:Discussion.”

**Issue Type: Test Case** This label indicates that an issue is asking for a test case to be automated. (Issues with this label are a special type of plan.)

**Pulp Version: 3** This label serves to differentiate issues, that otherwise should belong to one of the above issue types, as being related to creation of automated tests or utilities for for Pulp 3. This label is meant to aid pulp-smash developers in filtering issues by major version, as Pulp 3 introduces many breaking changes.

---

## Introductory Module

---

Location: *Pulp Smash* → *Introductory Module*

`pulp_smash.tests.pulp2.platform.api_v2.test_login` is one of the shortest, simplest and most heavily commented modules in Pulp Smash. Reading through this module will give you a mental framework for understanding other modules and making your own changes. It is included here for convenience.

```
# coding=utf-8
"""Test the API's `authentication`_ functionality.

.. _authentication:
    https://docs.pulpproject.org/en/latest/dev-guide/integration/rest-api/
    ↪ authentication.html
"""
# Why The Comments?
# =====
#
# This module serves as an introduction to Pulp Smash. This module was picked
# because it's one of the simplest in the test suite. A "how to understand Pulp
# Smash tests" section in the documentation should link to this module.
#
# Encoding
# -----
#
# The encoding declaration at the beginning of this file tells Python which
# encoding scheme was used when creating this document, and therefore how to
# decode the bytes in this document. If omitted, Python might use an UTF-8
# decoder, or a utf-8 decoder, or something else, and that can be problematic.
# Try running this script with Python in a variety of environments:
#
#     #!/usr/bin/env python3
#     # ...
#     import sys
#     print(sys.getdefaultencoding())
#
```

(continues on next page)

(continued from previous page)

```
# Shebang
# -----
#
# There is no shebang at the top of this file. That's because this file is not
# meant to be executed directly. Instead, a "test runner" program will import
# this module, and it will decide if and how to execute the code herein.
# Several test runners can run Pulp Smash tests, but with varying degrees of
# compatibility. The "unittest" test runner is best supported. [1]
#
# Docstrings
# -----
#
# The docstrings throughout this module comply with reStructuredText syntax.
# [2] However, a tool like `rst2html` cannot extract and compile the docstrings
# from this file. Instead, the Sphinx documentation generator must be used. [3]
# It knows how to extract docstrings, and it knows how to treat directives like
# the `:meth:` directive. See the README file in the root of this repository
# for more information.
#
# Package Structure
# -----
#
# Why is this module placed where it is?
#
# First, a path such as `pulp_smash.tests.pulp2.platform.api_v2.test_login` is
# human-readable. This module of Pulp Smash tests relies on the base platform's
# API version 2 interface, and it tests logging in.
#
# Second, Pulp has a plug-in architecture, where the base platform is always
# present, and everything else is optional. Pulp Smash's packages are
# structured to reflect that plug-in architecture. This makes it easy for a
# test case to know which plug-ins it may reference. For example, test cases in
# `pulp_smash.tests.pulp2.rpm` may reference the RPM plug-in, but must not
# reference the Puppet plugin. This also makes it easier to automatically skip
# tests. For example, if the RPM plug-in is not installed on the Pulp system
# under test, all test cases in `pulp_smash.tests.pulp2.rpm` are skipped.
#
# No per-plugin test skipping logic is present in this module. Elsewhere, be on
# the look-out for `setUpModule` functions and mentions of the `load_tests`
# protocol. [4]
#
# Imports
# -----
#
# The imports are listed in the order recommended by PEP 8: double-underscore,
# standard library, third party and local. [5][6] In addition, blocks of
# imports are sorted alphabetically, and "import x" statements are placed
# before "from x import y" statements.
#
# [1] https://docs.python.org/3.5/library/unittest.html
# [2] http://docutils.sourceforge.net/docs/user/rst/quickstart.html
# [3] http://www.sphinx-doc.org/en/stable/
# [4] https://docs.python.org/3/library/unittest.html#load-tests-protocol
# [5] https://www.python.org/dev/peps/pep-0008/#imports
# [6] https://docs.python.org/3/library/\_\_future\_\_.html
import unittest
```

(continues on next page)

(continued from previous page)

```

from pulp_smash import api, config, selectors
from pulp_smash.tests.pulp2.constants import (
    ERROR_KEYS,
    LOGIN_KEYS,
    LOGIN_PATH,
)
from pulp_smash.tests.pulp2.platform.utils import set_up_module as setUpModule #_
↳pylint:disable=unused-import

class LoginTestCase(unittest.TestCase):
    """Tests for logging in."""

    # The `TestCase` class provides a lot of functionality, and it's a Good
    # Idea to read the unittest documentation. [1] Right now, you just need to
    # know that, when a test runner executes a `TestCase` class:
    #
    # * The `test*` methods run in alphabetic order.
    # * A failure in one `test*` method doesn't affect any other `test*`
    #   method.
    #
    # [1] https://docs.python.org/3/library/unittest.html

    def test_success(self):
        """Successfully log in to the server.

        Assert that:

        * The response has an HTTP 200 status code.
        * The response body is valid JSON and has correct keys.
        """
        # The object returned by `config.get_config()` tells the new `Client`
        # object where the Pulp server is, what the authentication credentials
        # are, and so on.
        #
        # There are several assertions that can be made about the login API
        # call. Rather than logging in logging in once for every test, we log
        # in just once, and make multiple assertions about that log in.
        response = api.Client(config.get_config()).post(LOGIN_PATH)
        with self.subTest(comment='check response status code'):
            self.assertEqual(response.status_code, 200)
        with self.subTest(comment='check response body'):
            self.assertEqual(frozenset(response.json().keys()), LOGIN_KEYS)

    def test_failure(self):
        """Unsuccessfully log in to the server.

        Assert that:

        * The response has an HTTP 401 status code.
        * The response body is valid JSON and has correct keys.
        """
        # By default, `Client` objects munge every response they receive. They
        # act cautiously, and do things like raise an exception if the response
        # has an HTTP 4XX or 5XX status code. We don't want that to happen in
        # this test case. So, we pass the `Client` object a non-default
        # function with which to munge responses. In addition, we override the

```

(continues on next page)

(continued from previous page)

```
# default authentication handling for just this one API call.
#
# The API and CLI clients are interesting and capable classes. Read
# about them.
cfg = config.get_config()
response = (
    api.Client(cfg, api.echo_handler).post(LOGIN_PATH, auth=(' ', ' '))
)
with self.subTest(comment='check response status code'):
    self.assertEqual(response.status_code, 401)
# The `version` attribute should correspond to the version of the Pulp
# server under test. This block of code says "if bug 1412 is not fixed
# in Pulp version X, then skip this test."
if selectors.bug_is_testable(1412, cfg.pulp_version):
    with self.subTest(comment='check response body'):
        self.assertEqual(frozenset(response.json().keys()), ERROR_KEYS)
```



Location: *Pulp Smash* → *API Documentation*

This is the Pulp Smash API documentation. It is mostly auto generated from the source code. Beware that Pulp Smash is very new. Its API is **not stable**. This section of the documentation should be treated as a handy reference for developers, not a gospel.

## 6.1 *pulp\_smash*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash*

The root of Pulp Smash's namespace.

## 6.2 *pulp\_smash.api*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.api*

A client for working with Pulp's API.

Working with an API can require repetitive calls to perform actions like check HTTP status codes. In addition, Pulp's API has specific quirks surrounding its handling of href paths and HTTP 202 status codes. This module provides a customizable client that makes it easier to work with the API in a safe and concise manner.

```
class pulp_smash.api.Client (server_config, response_handler=None, request_kwargs=None,  
                             pulp_system=None)
```

A convenience object for working with an API.

This class is a wrapper around the `requests.api` module provided by [Requests](#). Each of the functions from that module are exposed as methods here, and each of the arguments accepted by Requests' functions are also accepted by these methods. The difference between this class and the [Requests](#) functions lies in its configurable request and response handling mechanisms.

This class is flexible enough that it should be usable with any API, but certain defaults have been set to work well with [Pulp](#).

As an example of basic usage, let's say that you'd like to create a user, then read that user's information back from the server. This is one way to do it:

```
>>> from pulp_smash.api import Client
>>> from pulp_smash.config import get_config
>>> client = Client(get_config())
>>> response = client.post('/pulp/api/v2/users/', {'login': 'Alice'})
>>> response = client.get(response.json()[ '_href' ])
>>> print(response.json())
```

Notice how we never call `response.raise_for_status()`? We don't need to because, by default, `Client` instances do this. Handy!

How does this work? Each `Client` object has a callback function, `response_handler`, that is given a chance to munge each server response. How else might this callback be useful? Well, notice how we call `json()` on each server response? That's kludgy. Let's write our own callback that takes care of this for us:

```
>>> from pulp_smash.api import Client
>>> from pulp_smash.config import get_config
>>> def response_handler(server_config, response):
...     response.raise_for_status()
...     return response.json()
>>> client = Client(get_config(), response_handler=response_handler)
>>> response = client.post('/pulp/api/v2/users/', {'login': 'Alice'})
>>> response = client.get(response[ '_href' ])
>>> print(response)
```

Pulp Smash ships with several response handlers. See:

- `pulp_smash.api.code_handler()`
- `pulp_smash.api.echo_handler()`
- `pulp_smash.api.json_handler()`
- `pulp_smash.api.safe_handler()`

As mentioned, this class has configurable request and response handling mechanisms. We've covered response handling mechanisms — let's move on to request handling mechanisms.

When a client is instantiated, a `pulp_smash.config.PulpSmashConfig` must be passed to the constructor, and configuration options are copied from the `PulpSmashConfig` to the client. These options can be overridden on a per-object or per-request basis. Here's an example:

```
>>> from pulp_smash.api import Client
>>> from pulp_smash.config import PulpSmashConfig
>>> cfg = config.PulpSmashConfig(
...     pulp_auth=('username', 'password'),
...     systems=[
...         config.PulpSystem(
...             hostname='example.com',
...             roles={'api': {
...                 'scheme': 'https',
...                 'verify': '~/Documents/my.crt',
...             }}
...         )
...     ]
... )
>>> client = api.Client(cfg)
>>> client.request_kwargs['url'] == 'https://example.com'
```

(continues on next page)

(continued from previous page)

```

True
>>> client.request_kwargs['verify'] == '~/Documents/my.crt'
True
>>> response = client.get('/index.html') # Use my.crt for SSL verification
>>> response = client.get('/index.html', verify=False) # Disable SSL
>>> response = client.get('/index.html') # Use my.crt for SSL verification
>>> client.request_kwargs['verify'] = None
>>> response = client.get('/index.html') # Do default SSL verification

```

Anything accepted by the `Requests` functions may be placed in `request_kwargs` or passed in to a specific call. You can set `verify` for example.

The `url` argument is slightly special. When making a call, it is possible to pass in a relative URL, as shown in the examples above. (e.g. `/index.html`.) The default URL and passed-in URL are joined like so:

```
>>> urljoin(request_kwargs['url'], passed_in_url)
```

This allows one to easily use the hrefs returned by Pulp in constructing new requests.

The remainder of this docstring contains design notes. They are useful to advanced users and developers.

`Requests`' `requests.api.post` method has the following signature:

```
def post(url, data=None, json=None, **kwargs)
```

Pulp supports only JSON for most of its API endpoints, so it makes sense for us to demote `data` to being a regular kwarg and list `json` as the one and only positional argument.

We make `json` a positional argument for `post()`, `put()` and `patch()`, but not the other methods. Why? Because HTTP OPTIONS, GET, HEAD and DELETE **must not** have bodies. This is stated by the HTTP/1.1 specification, and network intermediaries such as caches are at liberty to drop such bodies.

Why the sentinel? Imagine the following scenario: a user provides a default JSON payload in `self.request_kwargs`, but they want to skip sending that payload for just one request. How can they do that? With `client.post(url, None)`.

**delete** (*url*, *\*\*kwargs*)  
Send an HTTP DELETE request.

**get** (*url*, *\*\*kwargs*)  
Send an HTTP GET request.

**head** (*url*, *\*\*kwargs*)  
Send an HTTP HEAD request.

**options** (*url*, *\*\*kwargs*)  
Send an HTTP OPTIONS request.

**patch** (*url*, *json=<object object>*, *\*\*kwargs*)  
Send an HTTP PATCH request.

**post** (*url*, *json=<object object>*, *\*\*kwargs*)  
Send an HTTP POST request.

**put** (*url*, *json=<object object>*, *\*\*kwargs*)  
Send an HTTP PUT request.

**request** (*method*, *url*, *\*\*kwargs*)  
Send an HTTP request.

Arguments passed directly in to this method override (but do not overwrite!) arguments specified in `self.request_kwargs`.

`pulp_smash.api.code_handler(server_config, response)`

Check the response status code, and return the response.

Unlike `safe_handler()`, this method doesn't wait for asynchronous tasks to complete if `response` has an HTTP 202 status code.

**Raises** `requests.exceptions.HTTPError` if the response status code is in the 4XX or 5XX range.

`pulp_smash.api.echo_handler(server_config, response)`

Immediately return `response`.

`pulp_smash.api.json_handler(server_config, response)`

Like `safe_handler`, but also return a JSON-decoded response body.

Do what `pulp_smash.api.safe_handler()` does. In addition, decode the response body as JSON and return the result.

`pulp_smash.api.poll_spawned_tasks(server_config, call_report, pulp_system=None)`

Recursively wait for spawned tasks to complete. Yield response bodies.

Recursively wait for each of the spawned tasks listed in the given `call report` to complete. For each task that completes, yield a response body representing that task's final state.

#### Parameters

- **server\_config** – A `pulp_smash.config.PulpSmashConfig` object.
- **call\_report** – A dict-like object with a `call report` structure.
- **pulp\_system** – The system from where to pool the task. If `None` is provided then the first system found with `api` role will be used.

**Returns** A generator yielding task bodies.

**Raises** Same as `poll_task()`.

`pulp_smash.api.poll_task(server_config, href, pulp_system=None)`

Wait for a task and its children to complete. Yield response bodies.

Poll the task at `href`, waiting for the task to complete. When a response is received indicating that the task is complete, yield that response body and recursively poll each child task.

#### Parameters

- **server\_config** – A `pulp_smash.config.PulpSmashConfig` object.
- **href** – The path to a task you'd like to monitor recursively.
- **pulp\_system** – The system from where to pool the task. If `None` is provided then the first system found with `api` role will be used.

**Returns** An generator yielding response bodies.

**Raises** `pulp_smash.exceptions.TaskTimedOutError` – If a task takes too long to complete.

`pulp_smash.api.safe_handler(server_config, response)`

Check status code, wait for tasks to complete, and check tasks.

Inspect the response's HTTP status code. If the response has an HTTP Accepted status code, inspect the returned `call report`, wait for each task to complete, and inspect each completed task.

**Raises** `requests.exceptions.HTTPError` if the response status code is in the 4XX or 5XX range.

**Raises**

- `pulp_smash.exceptions.CallReportError` – If the call report contains an error.
- `pulp_smash.exceptions.TaskReportError` – If the task report contains an error.

## 6.3 `pulp_smash.cli`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.cli*

A client for working with Pulp hosts via their CLI.

**class** `pulp_smash.cli.BaseServiceManager`

A base service manager.

Each subclass must implement the abstract methods to provide the service management on a single or multiple hosts.

Subclasses should take advantage of the helper methods offered by this class in order to manage services and check the proper service manager software available on a host.

This base class also offers a context manager to temporarily disable SELinux. It is useful when managing services on hosts running RHEL 6 and earlier, which has SELinux issues when running on Jenkins.

Make sure to call this class `__init__` method on the subclass `__init__` method to ensure the helper methods functionality.

**restart** (*services*)

Restart the given services.

**Parameters** `services` – A list or tuple of services to be restarted.

**start** (*services*)

Start the given services.

**Parameters** `services` – A list or tuple of services to be started.

**stop** (*services*)

Stop the given services.

**Parameters** `services` – A list or tuple of services to be stopped.

**class** `pulp_smash.cli.Client` (*server\_config*, *response\_handler=None*, *pulp\_system=None*)

A convenience object for working with a CLI.

This class provides the ability to execute shell commands on either the local host or a remote host. Here is a pedagogic usage example:

```
>>> from pulp_smash import cli, config
>>> system = (
...     config.PulpSystem('localhost', {'shell': {'transport': 'local'}})
... )
>>> cfg = config.PulpSmashConfig(systems=[system])
>>> client = cli.Client(cfg, pulp_system=system)
>>> response = client.run(('echo', '-n', 'foo'))
>>> response.returncode == 0
True
```

(continues on next page)

(continued from previous page)

```
>>> response.stdout == 'foo'
True
>>> response.stderr == ''
True
```

The above example shows how various classes fit together. It's also verbose: smartly chosen defaults mean that most real code is much more concise.

You can customize how `Client` objects execute commands and handle responses by fiddling with the two public instance attributes:

**machine** A `Plumbum` machine. `run()` delegates all command execution responsibilities to this object.

**response\_handler** A callback function. Each time `machine` executes a command, the result is handed to this callback, and the callback's return value is handed to the user.

If `pulp_system.roles['shell']['transport']` is `'local'` or `'ssh'`, `machine` will be set so that commands run locally or over SSH, respectively. If `pulp_system.roles['shell']['transport']` is `None`, the constructor will guess how to set `machine` by comparing the hostname embedded in `pulp_system.hostname` against the current host's hostname. If they match, `machine` is set to execute commands locally; and vice versa.

#### Parameters

- **server\_config** (`pulp_smash.config.PulpSmashConfig`) – Information about the host on which commands will be executed.
- **response\_handler** – A callback function. Defaults to `pulp_smash.cli.code_handler()`.
- **pulp\_system** (`pulp_smash.config.PulpSystem`) – A specific host to target, instead of the first host with the `pulp cli` role.

**run** (*args*, *\*\*kwargs*)

Run a command and return `self.response_handler(result)`.

This method is a thin wrapper around `Plumbum`'s `BaseCommand.run` method, which is itself a thin wrapper around the standard library's `subprocess.Popen` class. See their documentation for detailed usage instructions. See `pulp_smash.cli.Client` for a usage example.

**class** `pulp_smash.cli.CompletedProcess` (*args*, *returncode*, *stdout*, *stderr*)

A process that has finished running.

This class is similar to the `subprocess.CompletedProcess` class available in Python 3.5 and above. Significant differences include the following:

- All constructor arguments are required.
- `check_returncode()` returns a custom exception, not `subprocess.CalledProcessError`.

All constructor arguments are stored as instance attributes.

#### Parameters

- **args** – A string or a sequence. The arguments passed to `pulp_smash.cli.Client.run()`.
- **returncode** – The integer exit code of the executed process. Negative for signals.
- **stdout** – The standard output of the executed process.
- **stderr** – The standard error of the executed process.

**check\_returncode()**

Raise an exception if returncode is non-zero.

Raise `pulp_smash.exceptions.CalledProcessError` if returncode is non-zero.

Why not raise `subprocess.CalledProcessError`? Because `stdout` and `stderr` are not included when `str()` is called on a `CalledProcessError` object. A typical message is:

```
"Command ('ls', 'foo') returned non-zero exit status 2"
```

This information is valuable. One could still make `subprocess.CalledProcessError` work by overloading `args`:

```
>>> if isinstance(args, (str, bytes)):
...     custom_args = (args, stdout, stderr)
... else:
...     custom_args = tuple(args) + (stdout, stderr)
>>> subprocess.CalledProcessError(args, returncode)
```

But this seems like a hack.

In addition, it's generally good for an application to raise expected exceptions from its own namespace, so as to better abstract away dependencies.

**class pulp\_smash.cli.GlobalServiceManager** (*cfg*)

A service manager that manages services on all Pulp hosts.

Each instance of this class manages a single service. When a method like `start()` is executed, it will start a service on all hosts that are declared as running that service. For example, imagine that the following is executed:

```
>>> from pulp_smash import cli, config
>>> cfg = config.get_config()
>>> svc_mgr = cli.GlobalServiceManager(cfg)
>>> svc_mgr.start(['httpd'])
```

In this case, the service manager will iterate over all hosts in `cfg`. For each host that is declared as fulfilling the `api` role, Apache (`httpd`) will be restarted.

When asked to perform an action, this object may talk to each target host and determines whether it is running as root. If not root, all commands are prefixed with “sudo”. Please ensure that Pulp Smash can either execute commands as root or can successfully execute `sudo`. You may need to edit your `~/.ssh/config` file.

For conceptual information on why both a `pulp_smash.cli.ServiceManager` and a `pulp_smash.cli.GlobalServiceManager` are necessary, see `pulp_smash.config.PulpSmashConfig`.

**Parameters** `cfg` (`pulp_smash.config.PulpSmashConfig`) – Information about the Pulp deployment.

**Raises** `pulp_smash.exceptions.NoKnownServiceManagerError` – If unable to find any service manager on one of the target hosts.

**restart** (*services*)

Restart the services on every host that has the services.

**Parameters** `services` – An iterable of service names.

**Returns** A dict mapping the affected hosts' hostnames with a list of `pulp_smash.cli.CompletedProcess` objects.

**start** (*services*)

Start the services on every host that has the services.

**Parameters** `services` – An iterable of service names.

**Returns** A dict mapping the affected hosts' hostnames with a list of `pulp_smash.cli.CompletedProcess` objects.

**stop** (`services`)

Stop the services on every host that has the services.

**Parameters** `services` – An iterable of service names.

**Returns** A dict mapping the affected hosts' hostnames with a list of `pulp_smash.cli.CompletedProcess` objects.

**class** `pulp_smash.cli.PackageManager` (`cfg`)

A package manager on a host.

Each instance of this class represents the package manager on a host. An example may help to clarify this idea:

```
>>> from pulp_smash import cli, config
>>> pkg_mgr = cli.PackageManager(config.get_config())
>>> completed_process = pkg_mgr.install('vim')
>>> completed_process = pkg_mgr.uninstall('vim')
```

In the example above, the `pkg_mgr` object represents the package manager on the host referenced by `pulp_smash.config.get_config()`.

Upon instantiation, a `PackageManager` object talks to its target host and uses simple heuristics to determine which package manager is used. As a result, it's possible to manage packages on heterogeneous host with homogeneous commands.

Upon instantiation, this object talks to the target host and determines whether it is running as root. If not root, all commands are prefixed with “sudo”. Please ensure that Pulp Smash can either execute commands as root or can successfully execute `sudo`. You may need to edit your `~/.ssh/config` file.

**Parameters** `cfg` (`pulp_smash.config.PulpSmashConfig`) – Information about the target host.

**Raises** `pulp_smash.exceptions.NoKnownPackageManagerError` – If unable to find any package manager on the target host.

**install** (`*args`)

Install the named packages.

**Return type** `pulp_smash.cli.CompletedProcess`

**uninstall** (`*args`)

Uninstall the named packages.

**Return type** `pulp_smash.cli.CompletedProcess`

**upgrade** (`*args`)

Upgrade the named packages.

**Return type** `pulp_smash.cli.CompletedProcess`

**class** `pulp_smash.cli.ServiceManager` (`cfg`, `pulp_system`)

A service manager on a host.

Each instance of this class represents the service manager on a host. An example may help to clarify this idea:

```
>>> from pulp_smash import cli, config
>>> cfg = config.get_config()
>>> pulp_system = cfg.get_services_for_roles(('api',))[0]
```

(continues on next page)



(continued from previous page)

```

>>> svc_mgr = cli.ServiceManager(cfg, pulp_system)
>>> completed_process_list = svc_mgr.stop(['httpd'])
>>> completed_process_list = svc_mgr.start(['httpd'])

```

In the example above, `svc_mgr` represents the service manager (such as SysV or systemd) on a host. Upon instantiation, a `ServiceManager` object talks to its target host and uses simple heuristics to determine which service manager is available. As a result, it's possible to manage services on heterogeneous hosts with homogeneous commands.

Upon instantiation, this object talks to the target host and determines whether it is running as root. If not root, all commands are prefixed with “sudo”. Please ensure that Pulp Smash can either execute commands as root or can successfully execute sudo. You may need to edit your `~/.ssh/config` file.

For conceptual information on why both a `pulp_smash.cli.ServiceManager` and a `pulp_smash.cli.GlobalServiceManager` are necessary, see `pulp_smash.config.PulpSmashConfig`.

### Parameters

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about a Pulp application.
- **pulp\_system** (`pulp_smash.config.PulpSystem`) – The host to target.

**Raises** `pulp_smash.exceptions.NoKnownServiceManagerError` – If unable to find any service manager on the target host.

### restart (services)

Restart the given services.

**Parameters** **services** – An iterable of service names.

**Returns** An iterable of `pulp_smash.cli.CompletedProcess` objects.

### start (services)

Start the given services.

**Parameters** **services** – An iterable of service names.

**Returns** An iterable of `pulp_smash.cli.CompletedProcess` objects.

### stop (services)

Stop the given services.

**Parameters** **services** – An iterable of service names.

**Returns** An iterable of `pulp_smash.cli.CompletedProcess` objects.

### pulp\_smash.cli.code\_handler (completed\_proc)

Check the process for a non-zero return code. Return the process.

Check the return code by calling `completed_proc.check_returncode()`. See: `pulp_smash.cli.CompletedProcess.check_returncode()`.

### pulp\_smash.cli.echo\_handler (completed\_proc)

Immediately return `completed_proc`.

## 6.4 pulp\_smash.config

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.config*

Tools for managing information about hosts under test.

Pulp Smash needs to know about the Pulp application under test and the hosts that comprise that application. For example, it might need to know which username and password to use when communicating with a Pulp application, or it might need to know which host is hosting the squid service, if any. This module eases the task of managing that information.

```
pulp_smash.config.AMQP_SERVICES = {'qpidd', 'rabbitmq'}
```

The set of services that can fulfill the amqp broker role.

```
pulp_smash.config.CONFIG_JSON_SCHEMA = {'additionalProperties': False, 'definitions': {'s
```

The schema for Pulp Smash's configuration file.

```
pulp_smash.config.OPTIONAL_ROLES = {'squid', 'pulp cli'}
```

Additional roles that can be present in a Pulp application.

```
class pulp_smash.config.PulpSmashConfig(pulp_auth=None, pulp_version=None, sys-
                                     tems=None)
```

Information about a Pulp application.

This object stores information about Pulp application and its constituent hosts. A single Pulp application may have its services spread across several hosts. For example, one host might run Qpid, another might run MongoDB, and so on. Here's how to model a multi-host deployment where Apache runs on one host, and the remaining components run on another host:

```
>>> import requests
>>> from pulp_smash.config import PulpSmashConfig
>>> cfg = PulpSmashConfig(
...     pulp_auth=('username', 'password'),
...     pulp_version='2.12.2',
...     systems=[ # A misnomer. Think "hosts," not "systems."
...         PulpSystem(
...             hostname='pulp1.example.com',
...             roles={'api': {'scheme': 'https'}},
...         ),
...         PulpSystem(
...             hostname='pulp.example.com',
...             roles={
...                 'amqp broker': {'service': 'qpidd'},
...                 'mongod': {},
...                 'pulp celerybeat': {},
...                 'pulp resource manager': {},
...                 'pulp workers': {},
...                 'shell': {'transport': 'ssh'},
...             },
...         ),
...     ]
... )
```

In the simplest case, all of the services that comprise a Pulp application run on a single host. Here's an example of how this object might model a single-host deployment:

```
>>> import requests
>>> from pulp_smash.config import PulpSmashConfig
>>> cfg = PulpSmashConfig(
...     pulp_auth=('username', 'password'),
...     pulp_version='2.12.2',
...     systems=[ # A misnomer. Think "hosts," not "systems."
...         PulpSystem(
...             hostname='pulp.example.com',
...             roles={
```

(continues on next page)

(continued from previous page)

```

...         'amqp broker': {'service': 'qpidd'},
...         'api': {'scheme': 'https'},
...         'mongod': {},
...         'pulp cli': {},
...         'pulp celerybeat': {},
...         'pulp resource manager': {},
...         'pulp workers': {},
...         'shell': {'transport': 'ssh'},
...     },
... )
... ]
... )

```

In the simplest case, Pulp Smash’s configuration file resides at `~/.config/pulp_smash/settings.json`. However, there are several ways to alter this path. Pulp Smash obeys the [XDG Base Directory Specification](#). In addition, Pulp Smash responds to the `PULP_SMASH_CONFIG_FILE` environment variable. This variable is a relative path, and it defaults to `settings.json`.

Configuration files contain JSON data structured in a way that resembles what is accepted by this class’s constructor. For exact details on the structure of configuration files, see [pulp\\_smash.config.CONFIG\\_JSON\\_SCHEMA](#).

### Parameters

- **pulp\_auth** – A two-tuple. Credentials to use when communicating with the server. For example: `('username', 'password')`.
- **pulp\_version** – A string, such as `'1.2'` or `'0.8.rc3'`. Defaults to `'1!0'` (epoch 1, version 0). Must be compatible with the `packaging` library’s `packaging.version.Version` class.
- **systems** (`pulp_smash.config.PulpSystem`) – A list of the hosts comprising a Pulp application.

### default\_config\_file\_path

Build the default config file path.

### get\_base\_url (pulp\_system=None)

Generate the base URL for a given `pulp_system`.

**Parameters** `pulp_system` (`pulp_smash.config.PulpSystem`) – One of the hosts that comprises a Pulp application. Defaults to the first host with the `api` role.

### get\_config\_file\_path (xdg\_config\_file=None, xdg\_config\_dir=None)

Search for a config file and return the first found.

Search each of the standard XDG configuration directories for a configuration file. Return as soon as a configuration file is found. Beware of race conditions. By the time client code attempts to open the file, it may be gone or otherwise inaccessible.

### Parameters

- **xdg\_config\_file** – A string. The name of the configuration file that is being searched for.
- **xdg\_config\_dir** – A string. The name of the directory that is suffixed to the end of each of the `XDG_CONFIG_DIRS` paths.

**Returns** A string. A path to a configuration file.

Raises `pulp_smash.exceptions.ConfigFileNotFoundError` – If no configuration file can be found.

**get\_requests\_kwargs** (*pulp\_system=None*)

Get kwargs for use by the Requests functions.

This method returns a dict of attributes that can be unpacked and used as kwargs via the `**` operator. For example:

```
>>> cfg = PulpSmashConfig().read()
>>> requests.get(cfg.get_base_url() + '...', **cfg.get_requests_kwargs())
```

This method is useful because client code may not know which attributes should be passed from a `PulpSmashConfig` object to Requests. Consider that the example above could also be written like this:

```
>>> cfg = PulpSmashConfig().get()
>>> requests.get(
...     cfg.get_base_url() + '...',
...     auth=tuple(cfg.pulp_auth),
...     verify=cfg.get_systems('api')[0].roles['api']['verify'],
... )
```

But this latter approach is more fragile. The user must remember to get a host with `api` role to check for the `verify` config, then convert `pulp_auth` config to a tuple, and it will require maintenance if `cfg` gains or loses attributes.

**get\_systems** (*role*)

Return a list of hosts fulfilling the given role.

**Parameters** *role* – The role to filter the available hosts, see `pulp_smash.config.ROLES` for more information.

**read** (*xdg\_config\_file=None, xdg\_config\_dir=None*)

Read a configuration file.

**Parameters**

- **xdg\_config\_file** – A string. The name of the file to manipulate.
- **xdg\_config\_dir** – A string. The XDG configuration directory in which the configuration file resides.

**Returns** A new `pulp_smash.config.PulpSmashConfig` object. The current object is not modified by this method.

**Return type** `PulpSmashConfig`

**Raises** `warnings.DeprecationWarning` if the configuration file uses the old format instead of the new role-based format.

**static services\_for\_roles** (*roles*)

Return the services based on the roles.

**class** `pulp_smash.config.PulpSystem` (*hostname, roles*)

**hostname**

Alias for field number 0

**roles**

Alias for field number 1

`pulp_smash.config.REQUIRED_ROLES = {'mongod', 'pulp resource manager', 'api', 'pulp worker'}`  
 The set of roles that must be present in a functional Pulp application.

`pulp_smash.config.ROLES = {'pulp celerybeat', 'squid', 'pulp resource manager', 'shell', 'a'}`  
 The set of all roles that may be present in a Pulp application.

`pulp_smash.config.convert_old_config(config_dict)`  
 Convert the old configuration dict representation to the new format.

`pulp_smash.config.get_config()`  
 Return a copy of the global `PulpSmashConfig` object.

This method makes use of a cache. If the cache is empty, the configuration file is parsed and the cache is populated. Otherwise, a copy of the cached configuration object is returned.

**Returns** A copy of the global server configuration object.

**Return type** `pulp_smash.config.PulpSmashConfig`

`pulp_smash.config.validate_config(config_dict)`  
 Validate an in-memory configuration file.

Given an in-memory configuration file, verify its sanity by validating it against a schema and performing several semantic checks.

**Parameters** `config_dict` – A dictionary returned by `json.load` or `json.loads` after reading the config file.

**Raises** `pulp_smash.exceptions.ConfigValidationError` – If the any validation error is found.

## 6.5 `pulp_smash.constants`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.constants*

Values usable by multiple test modules.

`pulp_smash.constants.DOCKER_IMAGE_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures'`  
 The URL to a Docker image as created by `docker save`.

`pulp_smash.constants.DOCKER_UPSTREAM_NAME = 'dimage/manifest-list-test'`  
 The name of a Docker repository.

This repository has several desirable properties:

- It is available via both `DOCKER_V1_FEED_URL` and `DOCKER_V2_FEED_URL`.
- It has a manifest list, where one entry has an architecture of `amd64` and an `os` of `linux`. (The “latest” tag offers this.)
- It is relatively small.

This repository also has several shortcomings:

- This repository isn’t an official repository. It’s less trustworthy, and may be more likely to change with little or no notice.
- It doesn’t have a manifest list where no list entries have an architecture of `amd64` and an `os` of `linux`. (The “arm32v7” tag provides schema v1 content.)

One can get a high-level view of the content in this repository by executing:

```
curl --location --silent https://registry.hub.docker.com/v2/repositories/  
↪$this_constant/tags | python -m json.tool
```

`pulp_smash.constants.DOCKER_UPSTREAM_NAME_NOLIST = 'library/busybox'`

The name of a Docker repository without a manifest list.

`DOCKER_UPSTREAM_NAME` should be used when possible. However, this constant is useful for backward compatibility. If Pulp is asked to sync a repository, and:

- Pulp older than 2.14 is under test.
- The repository is configured to sync schema v2 content.
- The upstream repository has a manifest list.

... then Pulp will break when syncing. See [Pulp #2384](#).

`pulp_smash.constants.DOCKER_V1_FEED_URL = 'https://index.docker.io'`

The URL to a V1 Docker registry.

This URL can be used as the “feed” property of a Pulp Docker registry.

`pulp_smash.constants.DOCKER_V2_FEED_URL = 'https://registry-1.docker.io'`

The URL to a V2 Docker registry.

This URL can be used as the “feed” property of a Pulp Docker registry.

`pulp_smash.constants.DRPM = 'drpms/test-alpha-1.1-1_1.1-2.noarch.drpm'`

The path to a DRPM file in one of the DRPM repositories.

This path may be joined with `DRPM_SIGNED_FEED_URL` or `DRPM_UNSIGNED_FEED_URL`.

`pulp_smash.constants.DRPM_SIGNED_FEED_COUNT = 4`

The number of packages available at `DRPM_SIGNED_FEED_URL`.

`pulp_smash.constants.DRPM_SIGNED_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/fixt'`

The URL to a signed DRPM repository.

`pulp_smash.constants.DRPM_SIGNED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/fixt'`

The URL to a DRPM file.

Built from `DRPM_SIGNED_FEED_URL` and `DRPM`.

`pulp_smash.constants.DRPM_UNSIGNED_FEED_COUNT = 4`

The number of packages available at `DRPM_UNSIGNED_FEED_URL`.

`pulp_smash.constants.DRPM_UNSIGNED_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixt'`

The URL to an unsigned DRPM repository.

`pulp_smash.constants.DRPM_UNSIGNED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures'`

The URL to a unsigned DRPM file.

Built from `DRPM_UNSIGNED_FEED_URL` and `DRPM`.

`pulp_smash.constants.FILE2_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/fi'`

The URL to a file repository.

`pulp_smash.constants.FILE2_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/file2/'`

The URL to an ISO file at `FILE2_FEED_URL`.

`pulp_smash.constants.FILE_FEED_COUNT = 3`

The number of packages available at `FILE_FEED_URL`.

`pulp_smash.constants.FILE_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/fi'`

The URL to a file repository.

```
pulp_smash.constants.FILE_LARGE_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures'
```

The URL to a file repository containing a large number of files.

```
pulp_smash.constants.FILE_MIXED_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures'
```

The URL to a file repository containing invalid and valid entries.

```
pulp_smash.constants.FILE_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/file/1..'
```

The URL to an ISO file at [FILE\\_FEED\\_URL](#).

```
pulp_smash.constants.OPENSUSE_FEED_URL = 'https://download.opensuse.org/update/openSUSE-sta'
```

The URL to an openSUSE repository.

The repository contains at least one erratum.

**Warning:** This repository is large, and is served by a third party. Do not sync from this repository with the “immediate” or “background” download policies. Know that metadata parsing will be time-consuming.

```
pulp_smash.constants.OSTREE_BRANCHES = ['rawhide', 'stable']
```

A branch in [OSTREE\\_FEED](#). See [OSTree Importer Configuration](#).

```
pulp_smash.constants.OSTREE_FEED = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/ostree'
```

The URL to a URL of OSTree branches. See [OSTree Importer Configuration](#).

```
pulp_smash.constants.PULP_FIXTURES_BASE_URL = 'https://repos.fedorapeople.org/pulp/pulp/fi'
```

A URL at which generated [pulp fixtures](#) are hosted.

```
pulp_smash.constants.PULP_FIXTURES_KEY_ID = '269d9d98'
```

The 32-bit ID of the public key used to sign various fixture files.

To calculate a new key ID, find the public key used by Pulp Fixtures (it should be in the Pulp Fixtures source code repository) and use GnuPG to examine it:

```
$ gpg "$public_key_file"
pub  rsa2048 2016-08-05 [SC]
    6EDF301256480B9B801EBA3D05A5E6DA269D9D98
uid           Pulp QE
sub  rsa2048 2016-08-05 [E]
```

The last 32 bits (8 characters) of the key ID are what Pulp wants — in this example, 269D9D98.

```
pulp_smash.constants.PUPPET_FEED_2 = 'http://forge.puppetlabs.com'
```

The URL to a repository of Puppet modules.

```
pulp_smash.constants.PUPPET_MODULE_1 = {'author': 'pulpqe', 'name': 'dummyspuppet', 'vers.'
```

Information about a Puppet module available via Pulp Fixtures.

```
pulp_smash.constants.PUPPET_MODULE_2 = {'author': 'pulp', 'name': 'pulp', 'version': '1'
```

Information about a Puppet module available at [PUPPET\\_FEED\\_2](#).

```
pulp_smash.constants.PUPPET_MODULE_URL_1 = 'https://repos.fedorapeople.org/pulp/pulp/fi'
```

The URL to a Puppet module module available via Pulp Fixtures.

Test cases that require a single module should use this URL, and test cases that require a feed should use [PUPPET\\_MODULE\\_URL\\_2](#). Doing so shifts load away from the Puppet Forge.

Why do both URLs exist? Because simulating the Puppet Forge’s behaviour is unreasonably hard.

Pulp Fixtures is designed to create data that can be hosted by a simple HTTP server, such as `python3 -m http.server`. A dynamic API, such as the [Puppet Forge API](#), cannot be simulated. We could create a static tree of files, where that tree of files is the same as what the Puppet Forge would provide in response to a certain HTTP GET request. However:

- The [Puppet Forge API](#) will inevitably change over time as bugs are fixed and features are added. This will make a static facsimile of the Puppet Forge API outdated. This is more than a mere inconvenience: outdated information is also confusing!
- Without an in-depth understanding of each and every file the Puppet Forge yields, it is probable that static fixtures will be wrong from the get-go.

`pulp_smash.constants.PUPPET_MODULE_URL_2 = 'http://forge.puppetlabs.com/v3/files/pulp-pulp-1.0.0'`  
The URL to a Puppet module available at `PUPPET_FEED_2`.

`pulp_smash.constants.PUPPET_QUERY_2 = 'pulp-pulp-1.0.0'`  
A query that can be used to search for Puppet modules.

Built from `PUPPET_MODULE_2`.

Though the [Puppet Forge API](#) supports a variety of search types, Pulp only supports the ability to search for modules. As a result, it is impossible to create a Puppet repository and sync only an exact module or set of modules. This query intentionally returns a small number of Puppet modules. A query which selected a large number of modules would produce tests that took a long time and abused the free Puppet Forge service.

Beware that the Pulp API takes given Puppet queries and uses them to construct URL queries verbatim. Thus, if the user gives a query of “foo bar”, the following URL is constructed:

```
https://forge.puppet.com/modules.json?q=foo bar
```

In an attempt to avoid this error, this query is encoded before being submitted to Pulp.

`pulp_smash.constants.PYTHON_EGG_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/python-eggs'`  
The URL to a Python egg at `PYTHON_PYPI_FEED_URL`.

`pulp_smash.constants.PYTHON_PYPI_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/python-pypi'`  
The URL to the PyPI Python repository.

`pulp_smash.constants.PYTHON_WHEEL_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/python-wheels'`  
The URL to a Python egg at `PYTHON_PYPI_FEED_URL`.

`pulp_smash.constants.RPM = 'bear-4.1-1.noarch.rpm'`  
The name of an RPM file. See `pulp_smash.constants.RPM_SIGNED_URL`.

`pulp_smash.constants.RPM2 = 'camel-0.1-1.noarch.rpm'`  
The name of an RPM. See `pulp_smash.constants.RPM2_UNSIGNED_URL`.

`pulp_smash.constants.RPM2_UNSIGNED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/python-pypi'`  
The URL to an unsigned RPM file.

Built from `RPM_UNSIGNED_FEED_URL` and `RPM2`.

`pulp_smash.constants.RPM_ALT_LAYOUT_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/python-pypi'`  
The URL to a signed RPM repository. See `RPM_SIGNED_URL`.

`pulp_smash.constants.RPM_DATA = mappingproxy({'name': 'bear', 'epoch': '0', 'metadata': 'erratum'})`  
Metadata for an RPM with an associated erratum.

The metadata tags that may be present in an RPM may be printed with:

```
rpm --querytags
```

Metadata for an RPM can be printed with a command like the following:

```
for tag in name epoch version release arch vendor; do
    echo "$(rpm -qp bear-4.1-1.noarch.rpm --qf "%{tag}")"
done
```

There are three ways to measure the size of an RPM:



**installed size** The size of all the regular files in the payload.

**archive size** The uncompressed size of the payload, including necessary CPIO headers.

**package size** The actual size of an RPM file, as returned by `stat --format='%s' ...`

For more information, see the Fedora documentation on [RPM headers](#).

`pulp_smash.constants.RPM_ERRATUM_COUNT = 4`

The number of errata in `RPM_UNSIGNED_FEED_URL`.

`pulp_smash.constants.RPM_ERRATUM_ID = 'RHEA-2012:0058'`

The ID of an erratum.

The package contained on this erratum is defined by `pulp_smash.constants.RPM_ERRATUM_RPM_NAME` and the erratum is present on repository which feed is `pulp_smash.constants.RPM_SIGNED_FEED_URL`.

`pulp_smash.constants.RPM_ERRATUM_RPM_NAME = 'gorilla'`

The name of the RPM named by `pulp_smash.constants.RPM_ERRATUM_ID`.

`pulp_smash.constants.RPM_INCOMPLETE_FILELISTS_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/incomplete_filelists.xml'`

The URL to a repository with an incomplete `filelists.xml` file.

`pulp_smash.constants.RPM_INCOMPLETE_OTHER_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/incomplete_other.xml'`

The URL to a repository with an incomplete `other.xml` file.

`pulp_smash.constants.RPM_INVALID_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/invalid_feed.xml'`

The URL to an invalid RPM repository.

`pulp_smash.constants.RPM_INVALID_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/invalid_rpm.xml'`

The URL to an invalid RPM package.

`pulp_smash.constants.RPM_LARGE_UPDATEINFO = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/large_updateinfo.xml'`

The URL to RPM with a large `updateinfo.xml`.

`pulp_smash.constants.RPM_MIRRORLIST_BAD = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/mirrorlist_bad.xml'`

The URL to a mirrorlist file containing only invalid entries.

`pulp_smash.constants.RPM_MIRRORLIST_GOOD = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/mirrorlist_good.xml'`

The URL to a mirrorlist file containing only valid entries.

`pulp_smash.constants.RPM_MIRRORLIST_LARGE = 'https://mirrors.fedoraproject.org/metalink?repo=fedora7'`

A mirrorlist referencing a large RPM repository.

`pulp_smash.constants.RPM_MIRRORLIST_MIXED = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/mirrorlist_mixed.xml'`

The URL to a mirrorlist file containing invalid and valid entries.

`pulp_smash.constants.RPM_MISSING_FILELISTS_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/missing_filelists.xml'`

A repository that's missing its `filelists.xml` file.

`pulp_smash.constants.RPM_MISSING_OTHER_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/missing_other.xml'`

A repository that's missing its `other.xml` file.

`pulp_smash.constants.RPM_MISSING_PRIMARY_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/missing_primary.xml'`

A repository that's missing its `primary.xml` file.

`pulp_smash.constants.RPM_NAMESPACES = {'metadata/common': 'http://linux.duke.edu/metadata/common'}`

Namespaces used by XML-based RPM metadata.

Many of the XML files generated by the `createrepo` utility make use of these namespaces. Some of the files that use these namespaces are listed below:

**metadata/common** Used by `repopdata/primary.xml`.

**metadata/filelists** Used by `repodata/filelists.xml`.

**metadata/other** Used by `repodata/other.xml`.

**metadata/repo** Used by `repodata/repomd.xml`.

**metadata/rpm** Used by `repodata/repomd.xml`.

`pulp_smash.constants.RPM_PKGLISTS_UPDATEINFO_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/rpm/updateinfo'`  
A repository whose updateinfo file has multiple `<pkglist>` sections.

`pulp_smash.constants.RPM_SIGNED_FEED_COUNT = 32`  
The number of packages available at `RPM_SIGNED_FEED_URL`.

`pulp_smash.constants.RPM_SIGNED_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/rpm/signed'`  
The URL to a signed RPM repository. See `RPM_SIGNED_URL`.

`pulp_smash.constants.RPM_SIGNED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/rpm/signed/rpm'`  
The URL to an RPM file.  
Built from `RPM_SIGNED_FEED_URL` and `RPM`.

`pulp_smash.constants.RPM_UNSIGNED_FEED_COUNT = 32`  
The number of packages available at `RPM_UNSIGNED_FEED_URL`.

`pulp_smash.constants.RPM_UNSIGNED_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/rpm/unsigned'`  
The URL to an unsigned RPM repository. See `RPM_SIGNED_URL`.

`pulp_smash.constants.RPM_UNSIGNED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/rpm/unsigned/rpm'`  
The URL to an unsigned RPM file.  
Built from `RPM_UNSIGNED_FEED_URL` and `RPM`.

`pulp_smash.constants.RPM_UPDATED_INFO_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/rpm/updateinfo'`  
A repository whose updateinfo file has an errata section.

`pulp_smash.constants.RPM_WITH_NON_ASCII_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/rpm/non-ascii'`  
The URL to an RPM with non-ascii metadata in its header.

`pulp_smash.constants.RPM_WITH_NON_UTF_8_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/rpm/non-utf-8'`  
The URL to an RPM with non-UTF-8 metadata in its header.

`pulp_smash.constants.RPM_WITH_PULP_DISTRIBUTION_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/rpm/pulp-distribution'`  
The URL to a RPM repository with a `PULP_DISTRIBUTION.xml` file.

`pulp_smash.constants.RPM_WITH_VENDOR = 'rpm-with-vendor-1-1.fc25.noarch.rpm'`  
The name of an RPM. See `pulp_smash.constants.RPM_WITH_VENDOR_URL`.

`pulp_smash.constants.RPM_WITH_VENDOR_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/rpm/vendor'`  
A repository whose `primary.xml` file has an vendor section.

`pulp_smash.constants.RPM_WITH_VENDOR_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/rpm/vendor/rpm'`  
The URL of an RPM with a specified vendor in its header.

`pulp_smash.constants.SRPM = 'test-srpm02-1.0-1.src.rpm'`  
An SRPM file at `pulp_smash.constants.SRPM_SIGNED_FEED_URL`.

`pulp_smash.constants.SRPM_SIGNED_FEED_COUNT = 3`  
The number of packages available at `SRPM_SIGNED_FEED_URL`.

`pulp_smash.constants.SRPM_SIGNED_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/srpm/signed'`  
The URL to a signed SRPM repository.

`pulp_smash.constants.SRPM_SIGNED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures/srpm/signed/srpm'`  
The URL to an SRPM file.

Built from `SRPM_SIGNED_FEED_URL` and `SRPM`.

`pulp_smash.constants.SRPM_UNSIGNED_FEED_COUNT = 3`

The number of packages available at `SRPM_UNSIGNED_FEED_COUNT`.

`pulp_smash.constants.SRPM_UNSIGNED_FEED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixi`

The URL to an unsigned SRPM repository.

`pulp_smash.constants.SRPM_UNSIGNED_URL = 'https://repos.fedorapeople.org/pulp/pulp/fixtures`

The URL to an unsigned SRPM file.

Built from `SRPM_UNSIGNED_FEED_URL` and `SRPM`.

## 6.6 *pulp\_smash.exceptions*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.exceptions*

Custom exceptions defined by Pulp Smash.

**exception** `pulp_smash.exceptions.BugStatusUnknownError`

We have encountered a bug whose status is unknown to us.

See `pulp_smash.selectors` for more information on how bug statuses are used.

**exception** `pulp_smash.exceptions.BugTPRMissingError`

We have encountered a bug with no “Target Platform Release” field.

See `pulp_smash.selectors` for more information.

**exception** `pulp_smash.exceptions.CallReportError`

A call report contains an error.

For more information about pulp’s task handling, see [Synchronous and Asynchronous Calls and Task Management](#).

**exception** `pulp_smash.exceptions.CalledProcessError`

Indicates a CLI process has a non-zero return code.

See `pulp_smash.cli.CompletedProcess()` for more information.

**exception** `pulp_smash.exceptions.ConfigFileNotFoundError`

We cannot find the requested Pulp Smash configuration file.

See `pulp_smash.config` for more information on how configuration files are handled.

**exception** `pulp_smash.exceptions.ConfigFileSectionNotFoundError`

We cannot read the requested Pulp Smash configuration file section.

See `pulp_smash.config` for more information on how configuration files are handled.

**exception** `pulp_smash.exceptions.ConfigValidationError` (*error\_messages*, *\*args*, *\*\*kwargs*)

The configuration file has validation errors.

See `pulp_smash.config.validate_config()` for more information on how configuration validation is handled.

**exception** `pulp_smash.exceptions.NoKnownBrokerError`

We cannot determine the AMQP broker used by a system.

An “AMQP broker” is a tool such as RabbitMQ or Apache Qpid.

**exception** `pulp_smash.exceptions.NoKnownPackageManagerError`

We cannot determine the package manager used by a system.

A “package manager” is a tool such as yum or dnf.

**exception** `pulp_smash.exceptions.NoKnownServiceManagerError`

We cannot determine the service manager used by a system.

A “service manager” is a tool such as systemctl or service.

**exception** `pulp_smash.exceptions.TaskReportError` (*msg, task, \*args, \*\*kwargs*)

A task contains an error.

For more information about pulp’s task handling, see [Synchronous and Asynchronous Calls and Task Management](#).

**exception** `pulp_smash.exceptions.TaskTimedOutError`

We timed out while polling a task and waiting for it to complete.

See `pulp_smash.api.poll_spawned_tasks()` and `pulp_smash.api.poll_task()` for more information on how task polling is handled.

## 6.7 `pulp_smash.pulp_smash_cli`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.pulp\_smash\_cli*

The entry point for Pulp Smash’s command line interface.

## 6.8 `pulp_smash.selectors`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.selectors*

Tools for selecting and deselecting tests.

`pulp_smash.selectors.bug_is_testable` (*bug\_id, pulp\_version*)

Tell the caller whether bug `bug_id` should be tested.

### Parameters

- **bug\_id** – An integer bug ID, taken from <https://pulp.plan.io>.
- **pulp\_version** – A `packaging.version.Version` object telling the version of the Pulp server we are testing.

**Returns** True if the bug is testable, or False otherwise.

**Raises** `TypeError` if `bug_id` is not an integer.

**Raises** `pulp_smash.exceptions.BugStatusUnknownError` – If the bug has a status Pulp Smash does not recognize.

`pulp_smash.selectors.bug_is_untestable` (*bug\_id, pulp\_version*)

Return the inverse of `bug_is_testable()`.

`pulp_smash.selectors.require` (*version\_string*)

Optionally skip a test method, based on a version string.

This decorator concisely encapsulates a common pattern for skipping tests. It can be used like so:

```

>>> from pulp_smash.config import get_config
>>> from pulp_smash.utils import require
>>> from unittest import TestCase
>>> class MyTestCase(TestCase):
...
...     @classmethod
...     def setUpClass(cls):
...         cls.cfg = get_config()
...
...     @require('2.7') # References `self.cfg`
...     def test_foo(self):
...         pass # Add a test for Pulp 2.7+ here.

```

Notice that `cls.cfg` is assigned to. This is a **requirement**.

**Parameters** `version_string` – A PEP 440 compatible version string.

`pulp_smash.selectors.skip_if` (*func, var\_name, result*)

Optionally skip a test method, based on a condition.

This decorator checks to see if `func(getattr(self, var_name))` equals `result`. If so, a `unittest.SkipTest` exception is raised. Otherwise, nothing happens, and the decorated test method continues as normal. Here's an example:

```

>>> import unittest
>>> from pulp_smash.selectors import skip_if
>>> class MyTestCase(unittest.TestCase):
...
...     @classmethod
...     def setUpClass(cls):
...         cls.my_var = False
...
...     @skip_if(bool, 'my_var', False)
...     def test_01_skips(self):
...         pass
...
...     def test_02_runs(self):
...         type(self).my_var = True
...
...     @skip_if(bool, 'my_var', False)
...     def test_03_runs(self):
...         pass

```

**Parameters** `var_name` – A valid variable name.

## 6.9 `pulp_smash.tests`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests*

Tests for Pulp.

This package contain functional tests for Pulp. These tests should be run against live Pulp systems. These tests may target all of the different interfaces exposed by Pulp, including its API and CLI. These tests are entirely different from the unit tests in `tests`, which test Pulp Smash itself.

The tests are organized into a hierarchy in the following form: `major_pulp_version.plugin.interface`.

For example, Pulp 2 tests for the RPM plugin's API interface are in `pulp_smash.tests.pulp2.ostree.api_v2`.

There are several factors that determine whether or not a given test should run. These factors include:

- Which version of Pulp is under test? For example, version 2.13.2, 2.14.1, 3, and so on.
- Given that a certain version of Pulp is under test, which bugs affect that Pulp installation? For example, does <https://pulp.plan.io/issues/2144> affect the Pulp installation under test?
- Which plugins are installed? For example, docker, ostree, puppet, and so on.

These are all common reasons that a given test might be skipped. From a user's perspective, this is all automatic. They need only install Pulp Smash, configure it, and point a test runner at `pulp_smash.tests`.

From a Pulp Smash developer's perspective, some work needs to be done to make this happen. There are two especially common ways to make this happen. First, bug-specific skipping logic can be implemented with the methods in `pulp_smash.selectors`, especially `pulp_smash.selectors.bug_is_testable()` and its sibling. Second, a `setUpModule` function must be present in **every** `test*` module. In the simplest case, this can be done with pre-defined functions. For example, `pulp_smash.tests.pulp2.rpm.api_v2.test_broker` might do the following:

```
from pulp_smash.tests.pulp2.rpm.utils import set_up_module as setUpModule
```

By default, Requests refuses to make insecure HTTPS connections. You can override this behaviour by passing `verify=False`. For example:

```
requests.get('https://insecure.example.com', verify=False)
```

If you do this, Requests will make the connection. However, an `InsecureRequestWarning` will be raised. This is problematic. If a user has explicitly stated that they want insecure HTTPS connections and they are pestered about that fact, the user is effectively trained to ignore warnings.

This module attempts to solve that problem. When this module is imported, a filter is prepended to the warning module's list of filters. The filter states that `InsecureRequestWarning` warnings should be ignored. Note that this has no effect on whether SSL verification is performed. Insecure HTTPS connections are still blocked by default. The filter only has an effect on whether `InsecureRequestWarning` messages are displayed.

This filtering has a drawback: the warning module's filtering system is process-wide. Imagine an application which uses both Pulp Smash and some other library, and imagine that the other library generates `InsecureRequestWarning` warnings. The filter created here will suppress the warnings raised by that application. The `warnings.catch_warnings` context manager is not a good solution to this problem, as it is thread-unsafe.

This filtering is also limited: any Python code which executes after this module is imported can also manipulate the warning module's list of filters, and can therefore override the effects of this module. Unfortunately, the `unittest` test runner from the standard library does just that. As of this writing (with Python 3.5.3), the following filter (among others) is prepended to the warning module's filter list whenever a test case is executed:

```
>>> from warnings import filters
>>> filters[1]
('default', None, <class 'Warning'>, None, 0)
```

This filter matches all warnings — including `InsecureRequestWarning` — and causes them to be emitted. In theory, this does not occur if `-W 'ignore::requests.packages.urllib3.exceptions.InsecureRequestWarning'` is passed when calling `python -m unittest`. A more efficacious solution is to use a different test runner.

## 6.10 *pulp\_smash.tests.pulp2*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2*

Tests for Pulp 2.

## 6.11 *pulp\_smash.tests.pulp2.constants*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.constants*

Constants for Pulp 2 tests.

`pulp_smash.tests.pulp2.constants.CALL_REPORT_KEYS = frozenset({'error', 'result', 'spawned'})`  
 See: [Call Report](#).

`pulp_smash.tests.pulp2.constants.CONSUMERS_ACTIONS_CONTENT_REGENERATE_APPLICABILITY_PATH = ...`  
 See: [Content Applicability](#).

`pulp_smash.tests.pulp2.constants.CONSUMERS_CONTENT_APPLICABILITY_PATH = '/pulp/api/v2/consumers/'`  
 See: [Content Applicability](#).

`pulp_smash.tests.pulp2.constants.CONSUMERS_PATH = '/pulp/api/v2/consumers/'`  
 See: [Consumer APIs](#).

`pulp_smash.tests.pulp2.constants.CONTENT_SOURCES_PATH = '/etc/pulp/content/sources/conf.d'`  
 See: [Content Sources](#).

`pulp_smash.tests.pulp2.constants.CONTENT_UNITS_PATH = '/pulp/api/v2/content/units/'`  
 See: [Search for Units](#).

`pulp_smash.tests.pulp2.constants.CONTENT_UPLOAD_PATH = '/pulp/api/v2/content/uploads/'`  
 See: [Creating an Upload Request](#).

`pulp_smash.tests.pulp2.constants.ERROR_KEYS = frozenset({'error_message', 'exception', '_href'})`  
 See: [Exception Handling](#).

No href field should be present. See [Issue #1310](#).

`pulp_smash.tests.pulp2.constants.GROUP_CALL_REPORT_KEYS = frozenset({'group_id', '_href'})`  
 See: [Group Call Report](#).

`pulp_smash.tests.pulp2.constants.LOGIN_KEYS = frozenset({'key', 'certificate'})`  
 See: [User Certificates](#).

`pulp_smash.tests.pulp2.constants.LOGIN_PATH = '/pulp/api/v2/actions/login/'`  
 See: [Authentication](#).

`pulp_smash.tests.pulp2.constants.ORPHANS_PATH = 'pulp/api/v2/content/orphans/'`  
 See: [Orphaned Content](#).

`pulp_smash.tests.pulp2.constants.PLUGIN_TYPES_PATH = '/pulp/api/v2/plugins/types/'`  
 See: [Retrieve All Content Unit Types](#).

`pulp_smash.tests.pulp2.constants.PULP_SERVICES = {'pulp_workers', 'httpd', 'pulp_resource'}.`  
 Core Pulp services.

There are services beyond just these that Pulp depends on in order to function correctly. For example, an AMQP broker such as RabbitMQ or Qpid is integral to Pulp's functioning. However, if resetting Pulp (such as in `pulp_smash.utils.reset_pulp()`), this is the set of services that should be restarted.

`pulp_smash.tests.pulp2.constants.REPOSITORY_EXPORT_DISTRIBUTOR = 'export_distributor'`  
A `distributor_type_id` to export a repository.

See: [Export Distributors](#).

`pulp_smash.tests.pulp2.constants.REPOSITORY_GROUP_EXPORT_DISTRIBUTOR = 'group_export_distr:`  
A `distributor_type_id` to export a repository group.

See: [Export Distributors](#).

`pulp_smash.tests.pulp2.constants.REPOSITORY_GROUP_PATH = '/pulp/api/v2/repo_groups/'`  
See: [Repository Group APIs](#)

`pulp_smash.tests.pulp2.constants.REPOSITORY_PATH = '/pulp/api/v2/repositories/'`  
See: [Repository APIs](#).

`pulp_smash.tests.pulp2.constants.TASKS_PATH = '/pulp/api/v2/tasks/'`  
See: [Tasks APIs](#).

`pulp_smash.tests.pulp2.constants.USER_PATH = '/pulp/api/v2/users/'`  
See: [User APIs](#).

## 6.12 `pulp_smash.tests.pulp2.docker`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.docker*

This package contains tests for the Docker plugin.

## 6.13 `pulp_smash.tests.pulp2.docker.api_v2`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.docker.api\_v2*

This package contains tests for the Docker plugin with the Pulp v2 API.

## 6.14 `pulp_smash.tests.pulp2.docker.api_v2.test_copy`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.docker.api\_v2.test\_copy*

Tests for copying docker units between repositories.

**class** `pulp_smash.tests.pulp2.docker.api_v2.test_copy.CopyV1ContentTestCase` (*methodName='runTest*  
Copy data between Docker repositories with schema v1 content.

**classmethod** `setUpClass()`  
Create class-wide variables.

**classmethod** `tearDownClass()`  
Clean up resources.

**test\_01\_set\_up()**  
Create a repository and populate with with schema v1 content.

**test\_02\_copy\_images()**  
Copy tags from one repository to another.

Assert the same number of images are present in both repositories.



```

class pulp_smash.tests.pulp2.docker.api_v2.test_copy.CopyV2ContentTestCase (methodName='runTest')
    Copy data between Docker repositories with schema v2 content.

    classmethod setUpClass ()
        Create class-wide variables.

    classmethod tearDownClass ()
        Clean up resources.

    test_01_set_up ()
        Create a repository and populate with with schema v2 content.

    test_02_copy_manifest_lists ()
        Copy manifest lists from one repository to another.

        Assert the same number of manifest lists are present in both repositories. This test targets:
        

- Pulp #2384
- Pulp #2385

test_02_copy_manifests ()
        Copy manifests from one repository to another.

        Assert the same number of manifests are present in both repositories.

    test_02_copy_tags ()
        Copy tags from one repository to another.

        Assert the same number of tags are present in both repositories.

```

## 6.15 *pulp\_smash.tests.pulp2.docker.api\_v2.test\_crud*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.docker.api\_v2.test\_crud*

Test CRUD for Docker repositories.

This module contains tests for creating Docker repositories. It is intended to also contain read, update, and delete tests.

```

class pulp_smash.tests.pulp2.docker.api_v2.test_crud.CrudTestCase (methodName='runTest')
    CRUD a minimal Docker repository.

    static create_body ()
        Return a dict for creating a repository.

    static update_body ()
        Return a dict for creating a repository.

class pulp_smash.tests.pulp2.docker.api_v2.test_crud.CrudWithFeedTestCase (methodName='runTest')
    CRUD a Docker repository with a feed.

    static create_body ()
        Return a dict, with a feed, for creating a repository.

class pulp_smash.tests.pulp2.docker.api_v2.test_crud.UpdateTestCase (methodName='runTest')
    Show it is possible to update a distributor for a docker repository.

    classmethod setUpClass ()
        Create a docker repo with a distributor, and update the distributor.

        Do the following:

```

1. Create a docker repository and add a distributor.
2. Update the distributor. Use the distributor's href in the request.
3. Update the distributor. Use the repository's href in the request, and ensure the distributor is updated by packing certain data in the request body.

**test\_status\_codes** ()

Verify each of the server's responses has a correct status code.

**test\_update\_accepted** ()

Verify the information sent to the server can be read back.

`pulp_smash.tests.pulp2.docker.api_v2.test_crud.setUpModule()`

Skip tests on Pulp versions lower than 2.8.

## 6.16 *pulp\_smash.tests.pulp2.docker.api\_v2.test\_duplicate\_uploads*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.docker.api\_v2.test\_duplicate\_uploads*

Tests for how well Pulp can deal with duplicate uploads.

This module targets [Pulp #1406](#) and [Pulp Smash #81](#). The test procedure is as follows:

1. Create a new feed-less repository.
2. Upload content and import it into the repository. Assert the upload and import was successful.
3. Upload identical content and import it into the repository.

The second upload should silently fail for all Pulp releases in the 2.x series.

**class** `pulp_smash.tests.pulp2.docker.api_v2.test_duplicate_uploads.DuplicateUploadsTestCase`

Test how well Pulp can deal with duplicate content unit uploads.

**classmethod** `setUpClass` ()

Create a Docker repository.

## 6.17 *pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync*

Tests that sync docker repositories.

**class** `pulp_smash.tests.pulp2.docker.api_v2.test_sync.UpstreamNameTestsMixin`

Provides tests that sync a repository and override `upstream_name`.

Any class inheriting from this mixin must also inherit from `pulp_smash.utils.BaseAPITestCase`.

**test\_invalid\_upstream\_name** ()

Sync the repository and pass an invalid `upstream_name`.

Verify the sync request is rejected with an HTTP 400 status code.

**test\_valid\_upstream\_name** ()

Sync the repository and pass a valid `upstream_name`.

Verify the sync succeeds.

**class** `pulp_smash.tests.pulp2.docker.api_v2.test_sync.UpstreamNameV1TestCase` (*methodName='runTest'*)  
 Sync a v1 docker repository with various `upstream_name` options.

This test targets [Pulp #2230](#).

**classmethod** `setUpClass()`

Create a docker repository with an importer.

The importer has no `upstream_name` set. it must be passed via `override_config` when a sync is requested.

**class** `pulp_smash.tests.pulp2.docker.api_v2.test_sync.UpstreamNameV2TestCase` (*methodName='runTest'*)  
 Sync a v2 docker repository with various `upstream_name` options.

This test targets [Pulp #2230](#).

**classmethod** `setUpClass()`

Create a docker repository with an importer.

The importer has no `upstream_name` set. it must be passed via `override_config` when a sync is requested.

`pulp_smash.tests.pulp2.docker.api_v2.test_sync.setUpModule()`  
 Skip tests on Pulp versions lower than 2.8.

## 6.18 `pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync\_publish*

Tests for syncing and publishing docker repositories.

`pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.MANIFEST_LIST_V2` = {'\$schema': 'http://...'}  
 A schema for docker manifest lists.

`pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.MANIFEST_V1` = {'\$schema': 'http://...'}  
 A schema for docker v2 image manifests, schema 1.

`pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.MANIFEST_V2` = {'\$schema': 'http://...'}  
 A schema for docker v2 image manifests, schema 2.

**class** `pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmd64LinuxTestCase` (*methodName='runTest'*)  
 Sync a Docker image with no amd64/linux build.

A manifest list lets a single Docker repository contain multiple images. This is useful in the case where an image contains platform-specific code, and an image must be built for each supported architecture, OS, etc.

When a modern Docker client fetches an image, it does the following:

1. Get a manifest list.
2. Look through the list of available images.
3. Pick out an image that functions on the current host's platform.
4. Get a manifest for that image.
5. Use the information in the manifest to get the image layers.

Older Docker clients aren't aware of manifest lists, and when they go to fetch an image, they just ask for any old manifest from a repository. When a Docker registry receives such a request, it does the following:

1. Look through the list of available images.

2. If an image with an `architecture` of `amd64` and an `os` of `linux` is available, return its manifest. Otherwise, return an HTTP 404.

This test case verifies Pulp's behaviour in the case where an upstream Docker repository has content described by a manifest list.

This test case doesn't verify Pulp's behaviour in the case where an upstream Docker repository has content described by a v2 manifest or v1 manifest. In these cases, the correct behaviour of a Docker registry is not well defined. See the [backward compatibility](#) documentation.

**classmethod** `setUpClass()`

Create class-wide variables.

**classmethod** `tearDownClass()`

Clean up resources.

**test\_01\_set\_up()**

Create, sync and publish a Docker repository.

Specifically, do the following:

1. Create, sync and publish a Docker repository. Let the repository's upstream name reference a repository that has an image with a manifest list and no `amd64/linux` build.
2. Make Crane immediately re-read the metadata files published by Pulp. (Restart Apache.)

**test\_02\_get\_manifest\_list()**

Get a manifest list.

Assert that:

- The response headers include a `content-type` of `accept:application/vnd.docker.distribution.manifest.list.v2+json`. (See `test_02_get_manifest_list()`.)
- The response body matches `MANIFEST_LIST_V2`.
- The returned manifest list doesn't include any entry where `architecture` of `amd64` and `os` is `linux`.

**test\_02\_get\_manifest\_v1()**

Get a v1 manifest. Assert that an HTTP 404 is returned.

**test\_02\_get\_manifest\_v2()**

Get a v2 manifest. Assert that an HTTP 404 is returned.

**class** `pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NonNamespacedImageTestCase` (*metaclass=unittest.TestCase*)

Work with an image whose name has no namespace.

**test\_all()**

Work with an image whose name has no namespace.

Create, sync and publish a Docker repository whose `UPSTREAM_NAME` doesn't include a namespace. A typical Docker image has a name like "library/busybox." When a non-namespaced image name like "busybox" is given, a prefix of "library" is assumed.

**class** `pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.RepoRegistryIdTestCase` (*methodNames=('setUp', 'tearDown')*)

Show Pulp can publish repos with varying `repo_registry_id` values.

**do\_test** (*cfg, repo\_registry\_id*)

Execute the test with the given `repo_registry_id`.

**test\_all()**

Show Pulp can publish repos with varying `repo_registry_id` values.

The `repo_registry_id` setting defines a Docker repository's name as seen by clients such as the Docker CLI. It's traditionally a two-part name such as `docker/busybox`, but according to [Pulp #2368](#), it can contain an arbitrary number of slashes. This test case verifies that the `repo_registry_id` can be set to values containing one, two and three slashes.

Also see: [Pulp #2723](#).

**class** `pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.V1RegistryTestCase` (*methodName=*  
Create, sync, publish and interact with a v1 Docker registry.

**setUp** ()

Create a docker repository.

**classmethod setUpClass** ()

Create class-wide variables.

**test\_get\_crane\_repositories** ()

Issue an HTTP GET request to `/crane/repositories`.

Assert that the response is as described by [Crane Admin](#).

**test\_get\_crane\_repositories\_v1** ()

Issue an HTTP GET request to `/crane/repositories/v1`.

Assert that the response is as described by [Crane Admin](#).

**verify\_v1\_repo** (*repo*)

Implement the assertions for the `test*` methods.

**class** `pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.V2RegistryTestCase` (*methodName=*  
Create, sync, publish and interact with a v2 Docker registry.

**setUp** ()

Create docker repository.

**classmethod setUpClass** ()

Create class-wide variables.

**test\_get\_crane\_repositories\_v2** ()

Issue an HTTP GET request to `/crane/repositories/v2`.

Assert that the response is as described by [Crane Admin](#).

**test\_get\_manifest\_list** ()

Issue an HTTP GET request to `/v2/{repo_id}/manifests/latest`.

Pass a header of `accept:application/vnd.docker.distribution.manifest.list.v2+json` Assert that:

- The response body matches `MANIFEST_LIST_V2`.
- The response has a content-type equal to what was requested. (According to Docker's *backward compatibility* specification, if a registry is asked for a manifest list but doesn't have a manifest list, it may return a manifest instead. But this test targets manifest lists, and it will fail if that happens.)

**test\_get\_manifest\_v1** ()

Issue an HTTP GET request to `/v2/{repo_id}/manifests/latest`.

Pass each of the following headers in turn:

- (none)
- `accept:application/json`
- `accept:application/vnd.docker.distribution.manifest.v1+json`

Assert the response matches *MANIFEST\_V1*.

This test targets [Pulp #2336](#).

**test\_get\_manifest\_v2()**

Issue an HTTP GET request to `/v2/{repo_id}/manifests/latest`.

Pass a header of `accept:application/vnd.docker.distribution.manifest.v2+json`.

Assert that the response body matches *MANIFEST\_V2*.

This test targets [Pulp #2336](#).

## 6.19 *pulp\_smash.tests.pulp2.docker.api\_v2.test\_tags*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.docker.api\_v2.test\_tags*

Tests that work with tags on docker repositories.

**class** `pulp_smash.tests.pulp2.docker.api_v2.test_tags.DockerTagTestCase` (*methodName='runTest'*)

Tests for docker repository tagging feature.

**get\_latest\_tags()**

Return all tags in this test's repo with a name of "latest".

Starting with Pulp 2.13, docker schema v2 is supported. As a result, a tag or manifest may be included in search results twice, with a differing schema\_version. For convenience, if the Pulp system under test is version 2.13 or newer, only schema v1 is targeted. (The choice of schema version 1 is arbitrary.) See [Pulp #2099](#).

**Returns** A list of docker tags.

**get\_manifests()**

Return all manifests in this test's repo.

If the Pulp system under test is version 2.13 or newer, only return schema v1 manifests. See [get\\_latest\\_tags\(\)](#).

**setUp()**

Create and sync a docker repository.

**test\_create\_tag()**

Check if a tag can be created.

**test\_update\_tag()**

Check if a tag can be updated to a new manifest.

Do the following:

1. Find the tag in this test's docker repository whose name is "latest." Make note of the manifest it references.
2. Pick some other manifest. Update the repository so that the "latest" tag references the chosen manifest.
3. Find the tag in this test's docker repository whose name is "latest." Assert it references the chosen manifest.

**test\_update\_tag\_another\_repo()**

Check if tagging fail for a manifest from another repo.

**test\_update\_tag\_invalid\_manifest()**

Check if tagging fail for a invalid manifest.

`pulp_smash.tests.pulp2.docker.api_v2.test_tags.create_docker_repo` (*cfg*, *upstream\_name*, *use\_v1=False*)

Create a docker repository.

#### Parameters

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about a Pulp host.
- **upstream\_name** – The Docker container upstream name.
- **use\_v1** – If `True` use Docker V1 feed URL else use Docker V2 feed URL.

**Returns** Detailed information about the created repository.

`pulp_smash.tests.pulp2.docker.api_v2.test_tags.import_upload` (*cfg*, *repo*, *params*)

Create or update a docker repository.

#### Parameters

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about a Pulp host.
- **repo** – A dict of information about the targeted repository.
- **params** – A dict of information to pass as `import_upload` body.

**Returns** A dict of information about the creation/update report.

`pulp_smash.tests.pulp2.docker.api_v2.test_tags.setUpModule` ()

Skip tests on Pulp versions lower than 2.12.

## 6.20 `pulp_smash.tests.pulp2.docker.api_v2.test_upload`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.docker.api\_v2.test\_upload*

Tests for uploading content to docker repositories.

**class** `pulp_smash.tests.pulp2.docker.api_v2.test_upload.UploadManifestListV2TestCase` (*methodNames*)

Test upload of manifest list V2 without perform a sync.

**classmethod** `setUpClass` ()

Create class-wide variables.

**test\_all** ()

Upload a V2 manifest list.

Do the following:

1. Create, sync and publish a repository. Read the repository and the repository's manifest list.
2. Upload a modified version of the manifest list to the repository. Re-read the repository and the repository's manifest list.
3. Assert that:
  - The repository's manifest list hasn't been changed. (After all, the repository hasn't been published since the new manifest list was uploaded.)
  - The repository's `docker_manifest_list` attribute has increased by the appropriate number.

This test targets the following issues:

- Pulp #2993
- Pulp Smash #829

```
pulp_smash.tests.pulp2.docker.api_v2.test_upload.setUpModule()  
    Execute pulp-admin login.
```

## 6.21 *pulp\_smash.tests.pulp2.docker.api\_v2.utils*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.docker.api\_v2.utils*

Utility functions for Docker API tests.

**class** `pulp_smash.tests.pulp2.docker.api_v2.utils.SyncPublishMixin`

Tools for test cases that sync and publish Docker repositories.

This class must be mixed in to a class that inherits from `unittest.TestCase`.

**static** `adjust_url(url)`

Return a URL that can be used for talking with Crane.

The URL returned is the same as `url`, except that the scheme is set to HTTP, and the port is set to (or replaced by) 5000.

**Parameters** `url` – A string, such as `https://pulp.example.com/foo`.

**Returns** A string, such as `http://pulp.example.com:5000/foo`.

**create\_sync\_publish\_repo** (`cfg`, `importer_config`, `distributors=None`)

Create, sync and publish a repository.

Specifically do the following:

1. Create a repository and schedule it for deletion.
2. Sync and publish the repository.
3. Make Crane immediately re-read the metadata files published by Pulp. (Restart Apache)

### Parameters

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about a Pulp deployment.
- **importer\_config** – An importer configuration to pass when creating the repository. For example: `{'feed': '...'}`.
- **distributors** – Distributor configurations to pass when creating the repository. If no value is passed, one will be generated.

**Returns** A detailed dict of information about the repository.

**static** `make_crane_client(cfg)`

Make an API client for talking with Crane.

Create an API client for talking to Crane. The client returned by this method is similar to the following client:

```
>>> client = api.Client(cfg, api.json_handler)
```

However:

- The client's base URL is adjusted as described by `adjust_url()`.
- The client will send an `accept:application/json` header with each request.



**Parameters** `cfg` (`pulp_smash.config.PulpSmashConfig`) – Information about a Pulp deployment.

**Returns** An API client for talking with Crane.

**Return type** `pulp_smash.api.Client`

`pulp_smash.tests.pulp2.docker.api_v2.utils.gen_distributor()`  
Return a semi-random dict for use in creating a Docker distributor.

`pulp_smash.tests.pulp2.docker.api_v2.utils.gen_repo()`  
Return a semi-random dict that used for creating a Docker repo.

## 6.22 `pulp_smash.tests.pulp2.docker.cli`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.docker.cli*

Tests that communicate with the server via the pulp-admin CLI client.

## 6.23 `pulp_smash.tests.pulp2.docker.cli.test_crud`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.docker.cli.test\_crud*

CRUD tests for docker repositories.

These tests can also be accomplished via the API. However, there is value in showing that the pulp-admin CLI client correctly interfaces with the API.

**class** `pulp_smash.tests.pulp2.docker.cli.test_crud.CreateTestCase` (*methodName='runTest'*)  
Create docker repositories, both successfully and unsuccessfully.

**setUp** ()  
Provide a server config and a repository ID.

**tearDown** ()  
Delete created resources.

**test\_basic** ()  
Create a docker repository. Only provide a repository ID.  
Assert the return code is 0.

**test\_duplicate\_ids** ()  
Create two docker repositories with identical IDs.  
Assert only the first repository is created.

**test\_with\_feed\_upstream\_name** ()  
Create a docker repository. Provide a feed and upstream name.  
Assert the return code is 0.

**class** `pulp_smash.tests.pulp2.docker.cli.test_crud.DeleteV2TestCase` (*methodName='runTest'*)  
Delete a populated v2 repository.

There was a bug in the Docker server plugin that caused a traceback when repos were deleted. This test ensures that that operation works correctly.

<https://pulp.plan.io/issues/1296>

**classmethod setUpClass ()**  
Provide a server config and a repository ID.

**test\_data\_gone ()**  
Assert that the published data was cleaned up.

**test\_repo\_gone ()**  
Assert that the repo is not in the pulp-admin output anymore.

**test\_success ()**  
Assert that the CLI reported success.

**class pulp\_smash.tests.pulp2.docker.cli.test\_crud.UpdateDistributorTestCase** (*methodName='runTest'*)  
Update a docker repository and use the `--repo-registry-id` flag.

This test case targets [Pulp issue 1710](#). According to this bug, updating and using the `--repo-registry-id` flag would trigger a traceback.

**classmethod setUpClass ()**  
Provide a server config and a repository ID.

**classmethod tearDownClass ()**  
Delete created resources.

**test\_repo\_registry\_id\_flag ()**  
Verify the information sent to the server can be read back.

**test\_stdout ()**  
Inspect the stdout emitted by `pulp-admin` when updating.

**class pulp\_smash.tests.pulp2.docker.cli.test\_crud.UpdateEnableV1TestCase** (*methodName='runTest'*)  
Update a docker repository's `-enable-v1` flag.

There was a bug in `pulp-admin` wherein the `-enable-v1` flag could be set during repository creation, but not while updating repositories. This test ensures that behavior functions correctly.

**classmethod setUpClass ()**  
Provide a server config and a repository ID.

**classmethod tearDownClass ()**  
Delete created resources.

**test\_change\_enable\_v1\_flag ()**  
Test that the the `-enable-v1` flag was successful.

**test\_success ()**  
Assert that the CLI reported success.

**class pulp\_smash.tests.pulp2.docker.cli.test\_crud.UpdateEnableV2TestCase** (*methodName='runTest'*)  
Update a docker repository's `-enable-v2` flag.

There was a bug in `pulp-admin` wherein the `-enable-v2` flag could be set during repository creation, but not while updating repositories. This test ensures that behavior functions correctly.

**classmethod setUpClass ()**  
Provide a server config and a repository ID.

**classmethod tearDownClass ()**  
Delete created resources.

**test\_change\_enable\_v2\_flag ()**  
Test that the the `-enable-v2` flag was successful.

```
test_success ()
    Assert that the CLI reported success.
```

## 6.24 *pulp\_smash.tests.pulp2.docker.cli.test\_sync\_publish*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.docker.cli.test\_sync\_publish*

Tests for syncing and publishing docker repositories.

```
class pulp_smash.tests.pulp2.docker.cli.test_sync_publish.InvalidFeedTestCase (methodName='run')
    Show Pulp behaves correctly when syncing a repo with an invalid feed.
```

```
test_all ()
    Create a docker repo with an invalid feed and sync it.
```

```
pulp_smash.tests.pulp2.docker.cli.test_sync_publish.setUpModule ()
    Execute pulp-admin login.
```

## 6.25 *pulp\_smash.tests.pulp2.docker.cli.utils*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.docker.cli.utils*

Utility functions for docker CLI tests.

All of the functions in this module share a common structure. The first argument is a *pulp\_smash.config.PulpSmashConfig*, and all other arguments correspond to command-line options. Most arguments are named after a flag. For example, an argument *to\_repo\_id* corresponds to the flag `--to-repo-id`.

For the meaning of each argument, see pulp-admin.

```
pulp_smash.tests.pulp2.docker.cli.utils.repo_copy (server_config, unit_type,
                                                    from_repo_id=None,
                                                    to_repo_id=None)
```

Execute pulp-admin docker repo copy {unit\_type}.

```
pulp_smash.tests.pulp2.docker.cli.utils.repo_create (server_config, enable_v1=None,
                                                    enable_v2=None,
                                                    feed=None, repo_id=None,
                                                    repo_registry_id=None, up-
                                                    stream_name=None)
```

Execute pulp-admin docker repo create.

```
pulp_smash.tests.pulp2.docker.cli.utils.repo_delete (server_config, repo_id)
```

Execute pulp-admin docker repo delete.

```
pulp_smash.tests.pulp2.docker.cli.utils.repo_list (server_config, repo_id=None, de-
                                                    tails=False)
```

Execute pulp-admin docker repo list.

```
pulp_smash.tests.pulp2.docker.cli.utils.repo_publish (server_config, repo_id,
                                                    bg=None, force_full=None)
```

Execute pulp-admin docker repo publish run.

```
pulp_smash.tests.pulp2.docker.cli.utils.repo_search (server_config, unit_type,
                                                    fields=None, repo_id=None)
```

Execute pulp-admin docker repo search {unit\_type}.

```
pulp_smash.tests.pulp2.docker.cli.utils.repo_sync (server_config, repo_id)
```

Execute pulp-admin docker repo sync run.

`pulp_smash.tests.pulp2.docker.cli.utils.repo_update` (*server\_config*, *enable\_v1=None*,  
*enable\_v2=None*, *feed=None*,  
*repo\_id=None*, *up-*  
*stream\_name=None*,  
*repo\_registry\_id=None*)

Execute `pulp-admin docker repo update`.

## 6.26 `pulp_smash.tests.pulp2.docker.utils`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.docker.utils*

Utilities for Docker tests.

`pulp_smash.tests.pulp2.docker.utils.get_upstream_name` (*cfg*)  
Return a Docker upstream name.

Return `pulp_smash.constants.DOCKER_UPSTREAM_NAME_NOLIST` if Pulp is older than version 2.14. Otherwise, return `pulp_smash.constants.DOCKER_UPSTREAM_NAME`. See the documentation for those constants for more information.

`pulp_smash.tests.pulp2.docker.utils.set_up_module` ()  
Skip tests if Pulp 2 isn't under test or if Docker isn't installed.

`pulp_smash.tests.pulp2.docker.utils.write_manifest_list` (*cfg*, *manifest\_list*)  
Write out a content source to JSON file.

### Parameters

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – The Pulp deployment on which to create a repository.
- **manifest\_list** – A detailed dict of information about the manifest list.

**Returns** The path to created file, and the path to dir that stores the file.

## 6.27 `pulp_smash.tests.pulp2.ostree`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.ostree*

Functional tests for Pulp's ostree plugin.

## 6.28 `pulp_smash.tests.pulp2.ostree.api_v2`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.ostree.api\_v2*

Tests that communicate with the server via the v2 API.

## 6.29 `pulp_smash.tests.pulp2.ostree.api_v2.test_copy`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.ostree.api\_v2.test\_copy*

Tests that copy content between OSTree repositories.

**class** `pulp_smash.tests.pulp2.ostree.api_v2.test_copy.FilterTestCase` (*methodName='runTest'*)  
Copy content between OSTree repositories with a filter.

**test\_all** ()

Copy content between OSTree repositories with a filter.

Do the following:

1. Create a pair of repositories, and populate the first.
2. Randomly select a unit from the first repository, and copy it to the second repository.
3. Verify that the selected unit is the only one in the second repository.

## 6.30 `pulp_smash.tests.pulp2.ostree.api_v2.test_crud`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.ostree.api\_v2.test\_crud*

Test the CRUD API endpoints OSTree repositories.

**class** `pulp_smash.tests.pulp2.ostree.api_v2.test_crud.CreateDistributorsTestCase` (*methodName='runTest'*)  
Show Pulp can create OSTree distributors and prevent path conflicts.

This test case targets:

- [Pulp #1106](#)
- [Pulp #2769](#)

**classmethod** `setUpClass` ()

Create a pair of repositories.

Ensure the first repo has a distributor with a relative path. Succeeding tests will give the second repository distributors with relative paths, where those paths may or may not conflict with the first repository's distributor's relative path. This test splits the distributors across two repositories to ensure that Pulp correctly checks new relative paths against the existing relative paths in all repositories.

**test\_invalid\_v1** ()

Create a distributor whose relative path is invalid.

Re-use the same relative path. For example, if an existing relative path is `foo/bar`, then this relative path would be `foo/bar`.

**test\_invalid\_v2** ()

Create a distributor whose relative path is invalid.

Extend an existing relative path. For example, if an existing relative path is `foo/bar`, then this relative path would be `foo/bar/biz`.

**test\_invalid\_v3** ()

Create a distributor whose relative path is invalid.

Prepend a slash onto an existing relative path. For example, if an existing relative path is `foo/bar`, then this relative path would be `/foo/bar`.

**test\_valid\_v1** ()

Create a distributor whose relative path is valid.

Create a unique relative path. For example, if an existing relative path is `foo/bar`, then this relative path might be `biz/baz`.

**test\_valid\_v2()**

Create a distributor whose relative path is valid.

Create a relative path that contains three segments. Most other tests in this module have relative paths with two segments.

**class** `pulp_smash.tests.pulp2.ostree.api_v2.test_crud.CrudTestCase` (*methodName='runTest'*)  
CRUD a minimal OSTree repository.

**static create\_body()**

Return a dict for creating a repository.

**static update\_body()**

Return a dict for creating a repository.

**class** `pulp_smash.tests.pulp2.ostree.api_v2.test_crud.CrudWithFeedTestCase` (*methodName='runTest'*)  
CRUD an OSTree repository with a feed.

**static create\_body()**

Return a dict, with a feed, for creating a repository.

**class** `pulp_smash.tests.pulp2.ostree.api_v2.test_crud.UpdateDistributorsTestCase` (*methodName='runTest'*)  
Test the update of ostree distributors.

This test case targets:

- [Pulp #1106](#)
- [Pulp #2769](#)

**classmethod setUpClass()**

Create a pair of repositories.

Ensure each repo has a distributor with a relative path. Succeeding tests will update the second repository's distributor with varying relative paths, where those paths may or may not conflict with the first repository's distributor's relative path. This test splits the distributors across two repositories to ensure that Pulp correctly checks new relative paths against the existing relative paths in all repositories.

**test\_invalid\_v1()**

Update a distributor's relative path with an invalid value.

Re-use an existing relative path. For example, if an existing relative path is `foo/bar`, then this relative path would be `foo/bar`.

**test\_invalid\_v2()**

Update a distributor's relative path with an invalid value.

Extend an existing relative path. For example, if an existing relative path is `foo/bar`, then this relative path would be `foo/bar/biz`.

**test\_invalid\_v3()**

Update a distributor's relative path with an invalid value.

Prepend a slash to an existing relative path. For example, if an existing relative path is `foo/bar`, then this relative path would be `/foo/bar`.

**test\_valid\_v1()**

Update a distributor's relative path with a valid value.

Use a unique value for the new relative path. For example, if an existing relative path is `foo/bar`, then the new relative path might be `biz/baz`.

**test\_valid\_v2()**

Update a distributor's relative path with a valid value.

Use a three-segment value for the new relative path. Most other tests in this module have relative paths with two segments.

**class** `pulp_smash.tests.pulp2.ostree.api_v2.test_crud.UpdateImportersTestCase` (*methodName='runTest'*)  
Test the update of ostree importers.

This test targets the following issues:

- [Pulp Smash #839](#)
- [Pulp #3210](#)

**test\_all** ()  
Test the update of ostree importers.

Do the following:

1. Create a repository.
2. Update the `importer` associated with the repository.
3. Perform assertions about the just updated `importer`.

## 6.31 `pulp_smash.tests.pulp2.ostree.api_v2.test_publish`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.ostree.api\_v2.test\_publish*

Tests that publish OSTree repositories.

**class** `pulp_smash.tests.pulp2.ostree.api_v2.test_publish.PublishTestCase` (*methodName='runTest'*)  
Create, sync and publish an OSTree repository.

**test\_all** ()  
Create, sync and publish an OSTree repository.

Verify that:

- The distributor's `last_publish` attribute is `None` after the sync. This demonstrates that `auto_publish` correctly defaults to `False`.
- The distributor's `last_publish` attribute is not `None` after the publish.

## 6.32 `pulp_smash.tests.pulp2.ostree.api_v2.test_sync`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.ostree.api\_v2.test\_sync*

Tests that sync OSTree repositories.

**class** `pulp_smash.tests.pulp2.ostree.api_v2.test_sync.SyncInvalidBranchesTestCase` (*methodName='runTest'*)  
Create an OSTree repository with invalid branches and sync it.

**classmethod** `setUpClass` ()  
Create and sync an OSTree repository.

**class** `pulp_smash.tests.pulp2.ostree.api_v2.test_sync.SyncInvalidFeedTestCase` (*methodName='runTest'*)  
Create an OSTree repository with an invalid feed and sync it.

**classmethod** `setUpClass` ()  
Set `cls.body`.

**class** `pulp_smash.tests.pulp2.ostree.api_v2.test_sync.SyncMissingAttrsTestCase` (*methodName='runTest'*)  
Create an OSTree repository with no feed or branches and sync it.

**classmethod** `setUpClass` ()  
Create and sync an OSTree repository.

**class** `pulp_smash.tests.pulp2.ostree.api_v2.test_sync.SyncTestCase` (*methodName='runTest'*)  
Create an OSTree repository with a valid feed and branch, and sync it.

The sync should complete with no errors reported.

**classmethod** `setUpClass` ()  
Create an OSTree repository with a valid feed and branch.

**test\_task\_progress\_report** ()  
Assert no task's progress report contains error details.

### 6.33 `pulp_smash.tests.pulp2.ostree.utils`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.ostree.utils*

Utilities for interacting with OS tree.

`pulp_smash.tests.pulp2.ostree.utils.gen_distributor` ()  
Return a semi-random dict for use in creating an OSTree distributor.

For more information, see the generic repository [CRUD](#) documentation and the OSTree distributor configuration documentation.

`pulp_smash.tests.pulp2.ostree.utils.gen_repo` ()  
Return a semi-random dict for use in creating an OSTree repository.

`pulp_smash.tests.pulp2.ostree.utils.set_up_module` ()  
Skip tests if Pulp 2 isn't under test or if OSTree isn't installed.

### 6.34 `pulp_smash.tests.pulp2.platform`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.platform*

Functional tests for the Pulp platform.

According to the documentation:

Pulp can be viewed as consisting of two parts, the platform (which includes both the server and client applications) and plugins (which provide support for a particular set of content types).

This package contains tests for the Pulp platform. These tests target plugin-agnostic functionality. These tests should not rely on any plugin-specific functionality, such as the ability to work with RPMs or ISOs.

### 6.35 `pulp_smash.tests.pulp2.platform.api_v2`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.platform.api\_v2*

Tests that communicate with the server via the v2 API.



## 6.36 `pulp_smash.tests.pulp2.platform.api_v2.test_consumer`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.platform.api_v2.test_consumer`

Test the `consumer` API endpoints.

**class** `pulp_smash.tests.pulp2.platform.api_v2.test_consumer.BindConsumerTestCase` (*methodName=*  
Show that one can bind a consumer to a repository.

**test\_all** ()

Bind a consumer to a distributor.

Do the following:

1. Create a repository with a distributor.
2. Create a consumer.
3. Bind the consumer to the distributor.

Assert that:

- The response has an HTTP 200 status code.
- The response body contains the correct values.

## 6.37 `pulp_smash.tests.pulp2.platform.api_v2.test_content_applicability`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.platform.api_v2.test_content_applicability`

Test the API's *content applicability* functionality.

When a user asks Pulp to regenerate content applicability, Pulp responds with a call report and starts executing tasks in series. Starting with Pulp 2.8, it is possible for a user to explicitly request that Pulp execute tasks in parallel instead. This functionality is only available for certain API calls, and when this is done, Pulp returns a group call report instead of a regular call report. (See `pulp_smash.tests.pulp2.constants.CALL_REPORT_KEYS` and `pulp_smash.tests.pulp2.constants.GROUP_CALL_REPORT_KEYS`.) *SeriesTestCase* and *ParallelTestCase* test these two use cases, respectively.

**class** `pulp_smash.tests.pulp2.platform.api_v2.test_content_applicability.FailureTestCase` (*met*  
Fail to generate content applicability for consumers and repos.

**classmethod** `setUpClass` ()

Make calls to the server and save the responses.

**test\_body** ()

Assert each response is JSON and doesn't look like a call report.

**test\_status\_code** ()

Assert each response has an HTTP 400 status code.

**class** `pulp_smash.tests.pulp2.platform.api_v2.test_content_applicability.ParallelTestCase` (*m*  
Ask Pulp to regenerate content applicability for consumers and repos.

Do so in parallel. See `pulp_smash.tests.pulp2.platform.api_v2.test_content_applicability`.

**setUp** ()

Ensure this test only runs on Pulp 2.8 and later.

**classmethod** `setUpClass` ()

Make calls to the server and save the responses.

**test\_body()**

Assert each response is JSON and has a correct structure.

**class** `pulp_smash.tests.pulp2.platform.api_v2.test_content_applicability.SeriesTestCase` (*meth*)

Ask Pulp to regenerate content applicability for consumers and repos.

Do so in series. See `pulp_smash.tests.pulp2.platform.api_v2.test_content_applicability`.

**classmethod** `setUpClass()`

Make calls to the server and save the responses.

**test\_body()**

Assert each response is JSON and has a correct structure.

## 6.38 `pulp_smash.tests.pulp2.platform.api_v2.test_login`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.platform.api_v2.test_login`

Test the API's authentication functionality.

**class** `pulp_smash.tests.pulp2.platform.api_v2.test_login.LoginTestCase` (*methodName='runTest'*)

Tests for logging in.

**test\_failure()**

Unsuccessfully log in to the server.

Assert that:

- The response has an HTTP 401 status code.
- The response body is valid JSON and has correct keys.

**test\_success()**

Successfully log in to the server.

Assert that:

- The response has an HTTP 200 status code.
- The response body is valid JSON and has correct keys.

## 6.39 `pulp_smash.tests.pulp2.platform.api_v2.test_repository`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.platform.api_v2.test_repository`

Test the `repository` API endpoints.

The assumptions explored in this module have the following dependencies:

```
It is possible to create an untyped repository.
├── It is impossible to create a repository with a duplicate ID
│   or other invalid attributes.
├── It is possible to read a repository, including its importers and
│   distributors.
├── It is possible to update a repository.
└── It is possible to delete a repository.
```

**class** `pulp_smash.tests.pulp2.platform.api_v2.test_repository.CreateFailureTestCase` (*methodName*)  
Establish that repositories are not created in documented scenarios.

**classmethod** `setUpClass()`

Create several repositories.

Each repository is created to test a different failure scenario. The first repository is created in order to test duplicate ids.

**test\_body\_status\_code()**

Assert that each response body has the expected HTTP status code.

**test\_exception\_keys\_json()**

Assert the JSON body returned contains the correct keys.

**test\_location\_header()**

Assert that the Location header is correctly set in the response.

**test\_status\_code()**

Assert that each response has the expected HTTP status code.

**class** `pulp_smash.tests.pulp2.platform.api_v2.test_repository.CreateSuccessTestCase` (*methodName*)  
Establish we can create repositories.

**classmethod** `setUpClass()`

Create several repositories.

Create one repository with the minimum required attributes, and a second with all available attributes except importers and distributors.

**test\_attributes()**

Assert that each repository has the requested attributes.

**test\_location\_header()**

Assert the Location header is correctly set in each response.

According to RFC 7231, the [HTTP Location](#) header may be either an absolute or relative URL. Thus, given this request:

```
GET /index.html HTTP/1.1
Host: www.example.com
```

These two responses are equivalent:

```
HTTP/1.1 302 FOUND
Location: http://www.example.com/index.php
```

```
HTTP/1.1 302 FOUND
Location: /index.php
```

This test abides by the RFC and allows Pulp to return either absolute or relative URLs.

**test\_status\_code()**

Assert each response has an HTTP 201 status code.

**class** `pulp_smash.tests.pulp2.platform.api_v2.test_repository.ReadUpdateDeleteTestCase` (*methodName*)  
Establish we can read, update and delete repositories.

This test case assumes the assertions in `CreateSuccessTestCase` hold true.

**classmethod** `setUpClass()`

Create three repositories and read, update and delete them.

- test\_read()**  
Assert the “read” response body contains the correct attributes.
- test\_read\_details()**  
Assert the read with details has the correct attributes.
- test\_read\_imp\_distrib()**  
Assert reading with importers/distributors returns correct attrs.
- test\_status\_code()**  
Assert each response has a correct HTTP status code.
- test\_update\_attributes\_result()**  
Assert the “update” response body has the correct attributes.
- test\_update\_spawned\_tasks()**  
Assert the “update” response body mentions no spawned tasks.

## 6.40 *pulp\_smash.tests.pulp2.platform.api\_v2.test\_search*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.platform.api\_v2.test\_search*

Test Pulp’s Searching facilities.

The tests in this module make use of the [User APIs](#). However, few user-specific references are made. These tests could be rewritten to use repositories or something else with only minimal changes. Thus, the name of this module.

Each test case executes one or more pairs of semantically identical POST and GET requests. Each pair of search results should match exactly.

Most test cases assume that the assertions in some other test case hold true. The assumptions explored in this module have the following dependencies:

```

It is possible to ask for all resources of a kind.
├─ It is possible to sort search results.
├─ It is possible to ask for a single field in search results.
├─ It is possible to ask for several fields in search results.
├─ It is possible to ask for a resource with a specific ID.
   └─ It is possible to ask for a resource with one of several IDs.
      └─ It is possible to skip some search results.
         └─ It is possible to limit how many search results are returned.
    
```

**class** `pulp_smash.tests.pulp2.platform.api_v2.test_search.FieldTestCase` (*methodName='runTest'*)  
Ask for a single field in search results.

GET	{'field': 'name'} (urlencoded)
POST	{'criteria': {'fields': 'name'}}

**classmethod** `setUpClass()`  
Create one user. Execute searches.

**test\_field()**  
Only the requested key should be in each response.

**class** `pulp_smash.tests.pulp2.platform.api_v2.test_search.FieldsTestCase` (*methodName='runTest'*)  
Ask for several fields in search results.

GET	field=login&field=roles
POST	{'criteria': {'fields': ['login', 'roles']}}

**classmethod setUpClass()**

Create one user. Execute searches.

**test\_fields()**

Only the requested keys should be in each response.

**class** pulp\_smash.tests.pulp2.platform.api\_v2.test\_search.**FiltersIdTestCase** (*methodName='runTest*)  
Ask for a resource with a specific ID.

There is no specification for executing these searches with GET.

GET	{'filters': {'id': '...'}} (urlencoded)
POST	{'criteria': {'filters': {'id': '...'}}}

**classmethod setUpClass()**

Search for exactly one user.

**test\_result\_ids()**

Assert the search results contain the correct IDs.

**class** pulp\_smash.tests.pulp2.platform.api\_v2.test\_search.**FiltersIdsTestCase** (*methodName='runTest*)  
Ask for resources with one of several IDs.

There is no specification for executing these searches with GET.

GET	{'filters': {'id': {'\$in': ['...', '...']}}}
POST	{'criteria': {'filters': {'id': {'\$in': ['...', '...']}}}}

**classmethod setUpClass()**

Search for exactly two users.

**test\_result\_ids()**

Assert the search results contain the correct IDs.

**class** pulp\_smash.tests.pulp2.platform.api\_v2.test\_search.**LimitSkipTestCase** (*methodName='runTest*)  
Ask for search results to be limited or skipped.

There is no specification for executing these searches with GET.

GET	{'filters': {'id': {'\$in': [id1, id2]}}, 'limit': 1}
GET	{'filters': {'id': {'\$in': [id1, id2]}}, 'skip': 1}
POST	{'criteria': {'filters': {'id': {'\$in': [id1, id2]}}, 'limit': 1}}
POST	{'criteria': {'filters': {'id': {'\$in': [id1, id2]}}, 'skip': 1}}

**classmethod setUpClass()**

Create two users. Execute searches.

**test\_results()**

Check that one of the two created users has been found.

**class** `pulp_smash.tests.pulp2.platform.api_v2.test_search.MinimalTestCase` (*methodName='runTest'*)  
 Ask for all resources of a certain kind.

GET	no query parameters
POST	{'criteria': {}}

**classmethod** `setUpClass()`  
 Create one user. Execute searches.

**test\_user\_found()**  
 Assert each search result should include a user we created.

**class** `pulp_smash.tests.pulp2.platform.api_v2.test_search.SortTestCase` (*methodName='runTest'*)  
 Ask for sorted search results.

There is no specification for executing these searches with GET.

POST	{'criteria': {'sort': [['id', 'ascending']]}}
POST	{'criteria': {'sort': [['id', 'descending']]}}

**classmethod** `setUpClass()`  
 Create two users. Execute searches.

**test\_ascending()**  
 Assert ascending results are ordered from low to high.

**test\_descending()**  
 Assert descending results are ordered from high to low.

`pulp_smash.tests.pulp2.platform.api_v2.test_search.setUpModule()`  
 Create several users, each with a randomized login name.

Test cases may search for these users or otherwise perform non-destructive actions on them. Test cases should **not** change these users.

`pulp_smash.tests.pulp2.platform.api_v2.test_search.tearDownModule()`  
 Delete the users created by `setUpModule()`.

## 6.41 `pulp_smash.tests.pulp2.platform.api_v2.test_user`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.platform.api_v2.test_user`

Test the `user` API endpoints.

The assumptions explored in this module have the following dependencies:

<pre> It is possible to create a user. ├─ It is impossible to create a duplicate user. ├─ It is possible to read a user. ├─ It is possible to update a user. │   └─ It is possible to search for a (updated) user. └─ It is possible to delete a user.                 </pre>
---

**class** `pulp_smash.tests.pulp2.platform.api_v2.test_user.CreateTestCase` (*methodName='runTest'*)  
 Establish that we can create users. No prior assumptions are made.

**classmethod setUpClass ()**

Create several users.

Create one user with the minimum required attributes, and another with all available attributes.

**test\_attrs ()**

Assert that each user has the requested attributes.

**test\_password ()**

Assert that responses do not contain passwords.

**test\_status\_code ()**

Assert that each response has an HTTP 201 status code.

**class pulp\_smash.tests.pulp2.platform.api\_v2.test\_user.ReadUpdateDeleteTestCase (methodName=)**  
Establish that we can read, update and delete users.

This test case assumes that the assertions in *CreateTestCase* are valid.

**classmethod setUpClass ()**

Create three users and read, update and delete them respectively.

**test\_create\_duplicate\_user ()**

Verify one cannot create a user with a duplicate login.

**test\_password\_not\_in\_response ()**

Ensure read and update responses do not contain a password.

Target [https://bugzilla.redhat.com/show\\_bug.cgi?id=1020300](https://bugzilla.redhat.com/show_bug.cgi?id=1020300).

**test\_status\_code ()**

Ensure read, update and delete responses have 200 status codes.

**test\_updated\_user ()**

Assert the updated user has the assigned attributes.

**test\_updated\_user\_password ()**

Assert one can log in with a user with an updated password.

**test\_use\_deleted\_user ()**

Assert one cannot read, update or delete a deleted user.

**class pulp\_smash.tests.pulp2.platform.api\_v2.test\_user.SearchTestCase (methodName='runTest')**  
Establish we can search for users.

This test case assumes the assertions in *ReadUpdateDeleteTestCase* are valid.

**classmethod setUpClass ()**

Create a user and add it to the 'super-users' role.

Search for:

- Nothing at all:
- All users having only the super-users role.
- All users having no roles.
- A user by their login.
- A non-existent user by their login.

**test\_global\_search ()**

Assert the global search includes our user.

**test\_login\_filter\_exclusion()**  
Search for a non-existent user via the “login” filter.

**test\_login\_filter\_inclusion()**  
Search for a user via the “login” filter.

**test\_roles\_filter\_exclusion()**  
Assert that the “roles” filter can be used for exclusion.

**test\_roles\_filter\_inclusion()**  
Assert that the “roles” filter can be used for inclusion.

**test\_status\_codes()**  
Assert each response has an HTTP 200 status code.

## 6.42 *pulp\_smash.tests.pulp2.platform.cli*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.platform.cli*

Tests that communicate with the server via the CLI.

## 6.43 *pulp\_smash.tests.pulp2.platform.cli.test\_pulp\_manage\_db*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.platform.cli.test\_pulp\_manage\_db*

Tests for the `pulp-manage-db` executable.

`pulp-manage-db` should only run when `REQUIRED_SERVICES` are running and when `CONFLICTING_SERVICES` are stopped. See:

- Pulp #2186
- Pulp Smash #487

**class** `pulp_smash.tests.pulp2.platform.cli.test_pulp_manage_db.BaseTestCase` (*methodName='runTest*  
An abstract base class for the test cases in this module.

**classmethod** `setUpClass()`  
Maybe skip this test case.

**tearDown()**  
Start all of Pulp’s services.

`pulp_smash.tests.pulp2.platform.cli.test_pulp_manage_db.CONFLICTING_SERVICES = frozenset({`  
If any of these services are running, `pulp-manage-db` will abort.

**class** `pulp_smash.tests.pulp2.platform.cli.test_pulp_manage_db.NegativeTestCase` (*methodName='runTest*  
Assert `pulp-manage-db` doesn’t run when inappropriate.

**test\_celerybeat\_running()**  
Test with `pulp_celerybeat` running.

**test\_conflicting\_running()**  
Test with `CONFLICTING_SERVICES` running.

**test\_required\_stopped()**  
Test with `REQUIRED_SERVICES` stopped.



```
test_resource_manager_running()
    Test with pulp_resource_manager running.
```

This test targets [Pulp #2684](#).

```
test_workers_running()
    Test with pulp_workers running.
```

This test targets [Pulp #2684](#).

```
class pulp_smash.tests.pulp2.platform.cli.test_pulp_manage_db.PositiveTestCase (methodName='runTest')
    Assert pulp-manage-db runs when appropriate.
```

```
test_conflicting_stopped()
    Test with CONFLICTING_SERVICES stopped.
```

```
test_dry_run()
    Make sure pulp-manage-db runs if -dry-run is passed.
```

```
pulp_smash.tests.pulp2.platform.cli.test_pulp_manage_db.REQUIRED_SERVICES = frozenset({'monitordb', 'pulp'})
    If any of these services are stopped, pulp-manage-db will abort.
```

```
pulp_smash.tests.pulp2.platform.cli.test_pulp_manage_db.setUpModule()
    Log in.
```

```
pulp_smash.tests.pulp2.platform.cli.test_pulp_manage_db.tearDownModule()
    Reset Pulp, in case one of the test cases breaks Pulp.
```

## 6.44 `pulp_smash.tests.pulp2.platform.cli.test_selinux`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.platform.cli.test_selinux`

Tests to verify that Pulp has proper SELinux permissions.

```
pulp_smash.tests.pulp2.platform.cli.test_selinux.CELERY_LABEL = ':system_r:celery_t:s0'
    A label commonly applied to celery processes.
```

The “user” segment of the label is intentionally omitted, as it is known to vary. See [Pulp Smash #444](#) (comment).

```
class pulp_smash.tests.pulp2.platform.cli.test_selinux.FileLabelsTestCase (methodName='runTest')
    Test that files have correct SELinux labels.
```

This test case targets [Pulp Smash #442](#).

```
classmethod setUpClass()
    Create a CLI client.
```

```
test_pulp_celery_fc()
    Test files listed in pulp-celery.fc.
```

```
test_pulp_server_fc()
    Test files listed in pulp-server.fc.
```

```
test_pulp_streamer_fc()
    Test files listed in pulp-streamer.fc.
```

```
pulp_smash.tests.pulp2.platform.cli.test_selinux.HTTPD_LABEL = ':system_r:httpd_t:s0'
    A label commonly applied to httpd processes.
```

The “user” segment of the label is intentionally omitted, as it is known to vary. See [Pulp Smash #444](#) (comment).

```
pulp_smash.tests.pulp2.platform.cli.test_selinux.PS_FIELDS = ('label', 'args')
    The fields that ps should display. See man ps for details.
```

**class** `pulp_smash.tests.pulp2.platform.cli.test_selinux.Process` (*label, args*)  
A single line of output from `ps`.

**args**  
Alias for field number 1

**label**  
Alias for field number 0

**class** `pulp_smash.tests.pulp2.platform.cli.test_selinux.ProcessLabelsTestCase` (*methodName='runTest'*)  
Test that Pulp processes have correct SELinux labels.

This test case targets [Pulp Smash #444](#).

**classmethod** `setUpClass` ()  
Get all of the processes running on the target Pulp system.

**test\_celerybeat** ()  
Verify the label of the Pulp celerybeat process.  
It should have a label of `CELERY_LABEL`.

**test\_httpd** ()  
Verify the labels of the `wsgi:pulp*` processes.  
They should have a label of `HTTPD_LABEL`.

**test\_reserved\_resource\_worker\_0** ()  
Verify the labels of the `reserved_resource_worker-0` processes.  
They should have a label of `CELERY_LABEL`.

**test\_resource\_manager** ()  
Verify the labels of the `resource_manager` processes.  
They should have a label of `CELERY_LABEL`.

## 6.45 `pulp_smash.tests.pulp2.platform.utils`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.platform.utils*

Utilities for platform tests.

`pulp_smash.tests.pulp2.platform.utils.set_up_module` ()  
Skip tests if Pulp 2 isn't under test.

## 6.46 `pulp_smash.tests.pulp2.puppet`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.puppet*

Functional tests for Pulp's Puppet plugin.

## 6.47 `pulp_smash.tests.pulp2.puppet.api_v2`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.puppet.api\_v2*

Tests that communicate with the server via the v2 API.

## 6.48 *pulp\_smash.tests.pulp2.puppet.api\_v2.test\_crud*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.puppet.api\_v2.test\_crud*

Tests that CRUD Puppet repositories.

```
class pulp_smash.tests.pulp2.puppet.api_v2.test_crud.CRUDTestCase (methodName='runTest')
    Test that one can create, update, read and delete a test case.

    static create_body ()
        Return a dict for creating a repository.

    static update_body ()
        Return a dict for creating a repository.
```

## 6.49 *pulp\_smash.tests.pulp2.puppet.api\_v2.test\_duplicate\_uploads*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.puppet.api\_v2.test\_duplicate\_uploads*

Tests for how well Pulp can deal with duplicate uploads.

This module targets [Pulp #1406](#) and [Pulp Smash #81](#). The test procedure is as follows:

1. Create a new feed-less repository.
2. Upload content and import it into the repository. Assert the upload and import was successful.
3. Upload identical content and import it into the repository.

The second upload should silently fail for all Pulp releases in the 2.x series.

```
class pulp_smash.tests.pulp2.puppet.api_v2.test_duplicate_uploads.DuplicateUploadsTestCase
    Test how well Pulp can deal with duplicate content unit uploads.

    classmethod setUpClass ()
        Create a Puppet repository.
```

## 6.50 *pulp\_smash.tests.pulp2.puppet.api\_v2.test\_install\_distributor*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.puppet.api\_v2.test\_install\_distributor*

Tests for `puppet_install_distributor`.

For more information check [puppet\\_install\\_distributor](#)

```
class pulp_smash.tests.pulp2.puppet.api_v2.test_install_distributor.InstallDistributorTest
    Test Puppet install distributor.

    test_all ()
        Test puppet_install_distributor.

        Do the following:
        

1. Create a puppet repository with a puppet_install_distributor
2. Upload a puppet module
3. Publish the repository
4. Check if the puppet_install_distributor config was properly used

```

**class** `pulp_smash.tests.pulp2.puppet.api_v2.test_install_distributor.InstallDistributorThro`  
Test Puppet install distributor.

**test\_all** ()

Creating a repo with an invalid distributor should throw an error.

This test targets [Pulp #1237](#). Do the following:

1. Create a puppet repo
2. **Make an API call to create a distributor WITHOUT non-optional** `install_path`
3. Assert that an error is thrown
4. Assert that no repo is created

## 6.51 `pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish`

Test the API endpoints for puppet repositories.

**class** `pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish.CreateTestCase` (*methodName='runTe*  
Create two puppet repos, with and without feed URLs respectively.

**classmethod** `setUpClass` ()

Create two puppet repositories, with and without feed URLs.

**test\_id\_notes** ()

Validate the `id` and `notes` attributes for each repo.

**test\_importer\_config** ()

Validate the `config` attribute of each importer.

**test\_importer\_type\_id** ()

Validate the `importer_type_id` attribute of each importer.

**test\_number\_importers** ()

Each repository should have only one importer.

**class** `pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish.PublishTestCase` (*methodName='runT*  
Test repository syncing, publishing and data integrity.

Test uploading custom puppet module to repository, copying content between repositories, querying puppet modules from pulp server and integrity of downloaded modules. Three query formats are tested as are provided by different puppet versions:

- puppet version  $\leq 3.3$
- $3.3 < \text{puppet version} < 3.6$
- puppet version  $> 3.6$

**classmethod** `setUpClass` ()

Upload puppet module to a repo, copy it to another, publish and download.

Create two puppet repositories, both without feeds. Upload an module to the first repository. Copy its content to the second repository. Add distributors to the repositories, publish repositories and download modules back from them.

**test\_call\_report\_errors** ()

Verify each call report is error-free.

```

test_call_report_keys ()
    Verify each call report has a sane structure.
    

- Import into a Repository
- Copying Units Between Repositories

test_free ()
    Verify the response body for ending an upload.
    Delete an Upload Request
test_malloc ()
    Verify the response body for creating an upload request.
test_publish_errors ()
    Verify publishing a call report doesn't generate any errors.
test_publish_keys ()
    Verify publishing a repository generates a call report.
test_repo_units_consistency ()
    Verify the two puppet repositories have the same content units.
test_status_code ()
    Verify the HTTP status code of each server response.
test_unit_integrity ()
    Verify the integrity of the puppet modules downloaded from Pulp.
test_upload ()
    Verify the response body for uploading bits.
class pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish.SyncInvalidFeedTestCase (method)
    If an invalid feed is given a sync should complete with errors.
    classmethod setUpClass ()
        Create a puppet repository with an invalid feed and sync it.
    test_error_details ()
        Assert each task's progress report contains error details.
    test_number_tasks ()
        Assert only one task was spawned.
    test_status_code ()
        Assert the call to sync a repository returns an HTTP 202.
    test_task_error_traceback ()
        Assert the task's "error" and "traceback" fields are non-null.
class pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish.SyncNoFeedTestCase (methodName='')
    Create and sync a puppet repository with no feed.
    At least one of the sync tasks should fail. The task should fail in a graceful manner, without e.g. an internal
    tracebacks. This test targets Pulp #2628.
    test_all ()
        Create and sync a puppet repository with no feed.
class pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish.SyncValidFeedTestCase (methodName='')
    Create and sync puppet repositories with valid feeds.
    sync_repo (repo)
        Sync a repository, and verify no tasks contain an error message.

```

**test\_matching\_query()**

Sync a repository with a query that matches units.

Assert that:

- None of the sync tasks has an error message.
- Searching for module `pulp_smash.constants.PUPPET_MODULE_2` yields one result.
- The synced-in module can be downloaded.

**test\_non\_matching\_query()**

Sync a repository with a query that doesn't match any units.

Assert that:

- None of the sync tasks has an error message.
- Searching for module `pulp_smash.constants.PUPPET_MODULE_2` yields no results.

**class** `pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish.SyncValidManifestFeedTestCase`  
A valid Puppet manifest should sync correctly.

**classmethod** `setUpClass()`

Create repository with the feed pointing to a valid manifest.

**test\_number\_tasks()**

Assert only one task was spawned.

**test\_status\_code()**

Assert the call to sync a repository returns an HTTP 202.

**test\_task\_progress\_report()**

Assert each task's progress report shows no errors.

## 6.52 `pulp_smash.tests.pulp2.puppet.api_v2.utils`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.puppet.api_v2.utils`

Utility functions for Puppet API tests.

`pulp_smash.tests.pulp2.puppet.api_v2.utils.gen_distributor()`

Return a semi-random dict for use in creating a Puppet distributor.

`pulp_smash.tests.pulp2.puppet.api_v2.utils.gen_install_distributor()`

Return a semi-random dict used for creating a Puppet install distributor.

The caller must fill the `install_path` distributor\_config option otherwise Pulp will throw an error when creating the distributor.

`pulp_smash.tests.pulp2.puppet.api_v2.utils.gen_repo()`

Return a semi-random dict that used for creating a puppet repo.

## 6.53 `pulp_smash.tests.pulp2.puppet.cli`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.puppet.cli`

Tests that communicate with the server via the CLI.

## 6.54 `pulp_smash.tests.pulp2.puppet.cli.test_sync`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.puppet.cli.test\_sync*

Tests that sync Puppet repositories.

**class** `pulp_smash.tests.pulp2.puppet.cli.test_sync.SyncDownloadedContentTestCase` (*methodName=*  
 Test whether Pulp can associate already-downloaded content with a repo.

Consider the following scenario:

1. Create a repository with a feed and sync it.
2. Create a second repository with the same feed and sync it.

When the second repository is synced, Pulp should recognize that the needed content units are already present, and it should associate them with the second repository. However, according to [Pulp #1937](#), Pulp fails to do this, and the second repository will not be populated.

This test case tests [Pulp #1937](#) and the corresponding Pulp Smash issue, [Pulp Smash #269](#).

**test\_sync\_downloaded\_content** ()

Create two repositories with the same feed, and sync them serially.

More specifically, this test creates two puppet repositories with identical feeds, syncs them serially, and verifies that both have equal non-zero content unit counts.

**class** `pulp_smash.tests.pulp2.puppet.cli.test_sync.SyncFromPuppetForgeTestCase` (*methodName='run*  
 Test whether one can sync modules from the Puppet Forge.

According to [Pulp #1846](#), Pulp sometimes fails to sync modules available on the Puppet forge. There is no consistency regarding which modules fail to sync: according to one comment, Pulp only detects 40 modules (of ~1,800), and according to another comment, Pulp syncs 4,089 of 4,128 modules.

How do we test this? The ideal test case is to repeatedly sync the entire Puppet Forge and check for sync failures, until the probability of another random failure is low. This is problematic: we're abusing the Puppet Forge and extending the test time. A more realistic test is to sync a small number of modules and ensure that no errors occur. This provides much less assurance, but it does at least show that a sync from the Puppet Forge can complete.

`pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish` already syncs from the Puppet Forge, but [Pulp #1846](#) specifically uses the CLI.

The end result is a test case that syncs an unknown number of Puppet modules and which provides only minimal assurance that syncs from the Puppet Forge work. Unfortunately, we cannot do better.

**test\_sync\_puppet\_forge** ()

Create a Puppet repository and trigger a sync.

`pulp_smash.tests.pulp2.puppet.cli.test_sync.get_num_units_in_repo` (*server\_config*,  
*repo\_id*)

Tell how many puppet modules are in a repository.

### Parameters

- **server\_config** (`pulp_smash.config.PulpSmashConfig`) – Information about the Pulp server being targeted.
- **repo\_id** – A Puppet repository ID.

**Returns** The number of puppet modules in a repository, as an `int`.

`pulp_smash.tests.pulp2.puppet.cli.test_sync.setUpModule()`  
Skip this module of tests if appropriate.  
See Pulp #2574.

## 6.55 `pulp_smash.tests.pulp2.puppet.utils`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.puppet.utils*  
Utilities for Puppet tests.

`pulp_smash.tests.pulp2.puppet.utils.setUpModule()`  
Skip tests if Pulp 2 isn't under test or if Puppet isn't installed.

## 6.56 `pulp_smash.tests.pulp2.python`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.python*  
Functional tests for Pulp's Python plugin.

## 6.57 `pulp_smash.tests.pulp2.python.api_v2`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.python.api\_v2*  
Tests that communicate with the server via the v2 API.

## 6.58 `pulp_smash.tests.pulp2.python.api_v2.test_crud`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.python.api\_v2.test\_crud*  
Tests that CRUD Python repositories.

**class** `pulp_smash.tests.pulp2.python.api_v2.test_crud.CRUDTestCase` (*methodName='runTest'*)  
Test that one can create, update, read and delete a test case.

**static** `create_body()`  
Return a dict for creating a repository.

**static** `update_body()`  
Return a dict for creating a repository.

## 6.59 `pulp_smash.tests.pulp2.python.api_v2.test_duplicate_uploads`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.python.api\_v2.test\_duplicate\_uploads*  
Tests for how well Pulp can deal with duplicate uploads.

This module targets Pulp #1406 and Pulp Smash #81. The test procedure is as follows:

1. Create a new feed-less repository.
2. Upload content and import it into the repository. Assert the upload and import was successful.



3. Upload identical content and import it into the repository.

The second upload should silently fail for all Pulp releases in the 2.x series.

**class** `pulp_smash.tests.pulp2.python.api_v2.test_duplicate_uploads.DuplicateUploadsTestCase`  
 Test how well Pulp can deal with duplicate content unit uploads.

**classmethod** `setUpClass()`  
 Create a Python repo. Upload a Python package into it twice.

## 6.60 `pulp_smash.tests.pulp2.python.api_v2.test_sync_publish`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.python.api_v2.test_sync_publish`

Test the sync and publish API endpoints for Python repositories.

**class** `pulp_smash.tests.pulp2.python.api_v2.test_sync_publish.BaseTestCase` (*methodName='runTest'*)  
 A base class for the test cases in this module.

Test cases derived from this class (should) do the following:

1. Create and populate a Python repository. The procedure for populating the repository varies in each child class.
2. Create a second Python repository, and sync it from the first.

In each step, the `verify_*` methods are used if appropriate.

**classmethod** `setUpClass()`  
 Create class-wide variables.

**classmethod** `tearDownClass()`  
 Delete fixtures and orphans.

**test\_01\_first\_repo()**  
 Create, populate and publish a Python repository.  
 Subclasses must override this method.

**test\_02\_second\_repo()**  
 Create a second Python repository, and sync it from the first.

See:

- [Pulp #140](#)
- [Pulp Smash #493](#)

Note that, for [Pulp #140](#) to be fully tested, an additional test case should be created wherein one Pulp application syncs from another completely independent Pulp application.

**verify\_package\_types** (*cfg, repo*)  
 Assert `sdist` and `bdist_wheel` shelf-reader packages were synced.

This test targets [Pulp #1883](#).

**verify\_sync** (*cfg, call\_report*)  
 Verify the call to sync a Python repository succeeded.

Assert that:

- The call report has an HTTP 202 status code.
- None of the tasks spawned by the “sync” request contain errors.

**class** `pulp_smash.tests.pulp2.python.api_v2.test_sync_publish.SyncTestCase` (*methodName='runTest'*)  
Test whether content can be synced into a Python repository.

**test\_01\_first\_repo** ()

Create, sync content into and publish a Python repository.

See:

- [Pulp #135](#)
- [Pulp Smash #494](#)

**class** `pulp_smash.tests.pulp2.python.api_v2.test_sync_publish.UploadTestCase` (*methodName='runTest'*)  
Test whether content can be uploaded to a Python repository.

**test\_01\_first\_repo** ()

Create, upload content into and publish a Python repository.

See:

- [Pulp #136](#)
- [Pulp #2334](#)
- [Pulp Smash #492](#)

`pulp_smash.tests.pulp2.python.api_v2.test_sync_publish.get_details` (*cfg, repo*)  
Return detailed information about a Python repository.

`pulp_smash.tests.pulp2.python.api_v2.test_sync_publish.get_repo_path` (*cfg, repo*)  
Return the root path to a published Python repository.

## 6.61 `pulp_smash.tests.pulp2.python.api_v2.utils`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.python.api\_v2.utils*

Utility functions for Python API tests.

`pulp_smash.tests.pulp2.python.api_v2.utils.gen_distributor` ()  
Return a semi-random dict for use in creating a Python distributor.

`pulp_smash.tests.pulp2.python.api_v2.utils.gen_repo` ()  
Return a semi-random dict for use in creating a Python repository.

## 6.62 `pulp_smash.tests.pulp2.python.utils`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.python.utils*

Utilities for Python tests.

`pulp_smash.tests.pulp2.python.utils.set_up_module` ()  
Skip tests if Pulp 2 isn't under test or if Python isn't installed.

## 6.63 `pulp_smash.tests.pulp2.rpm`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm*

Functional tests for Pulp's RPM plugin.

## 6.64 *pulp\_smash.tests.pulp2.rpm.api\_v2*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2*

Tests that communicate with the server via the v2 API.

## 6.65 *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_broker*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_broker*

Tests for Pulp's "broker reconnect" feature.

Tests for #55:

Pulp offers a collection of behaviors known as "reconnect support" for the Pulp Broker. Here are the expected behaviors:

- If you start a Pulp service that connects to the broker and the broker is not running or is not network accessible for some reason, the Pulp services will wait-and-retry. It has a backoff behavior, but the important part is that Pulp services don't exit if they can't connect due to availability, and when the availability problem is resolved, the Pulp services reconnect.
- If you have a Pulp service connected to the broker and the broker shuts down, the Pulp services need the wait-and-retry as described above. Once the broker becomes available again the Pulp services should reconnect.

There are two scenarios to test here:

- support for initially connecting to a broker, and
- support for reconnecting to a broker that goes missing.

Both scenarios are executed by *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_broker.BrokerTestCase*.

**class** *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_broker.BrokerTestCase* (*methodName='runTest'*)  
Test Pulp's support for broker connections and reconnections.

**health\_check** ()  
Execute step three of the test plan.

**setUp** ()  
Provide a server config and Pulp services to stop and start.

**tearDown** ()  
Ensure Pulp services and AMQP broker are running.  
  
Stop all relevant services, then start them again. This approach is slow, but see [when broker reconnect test fails, all following tests fail](#).

**test\_broker\_connect** ()  
Test Pulp's support for initially connecting to a broker.

Do the following:

1. Stop both the broker and several other services.
2. Start the several other resources, wait, and start the broker.

3. Test Pulp's health. Create an RPM repository, sync it, add a distributor, publish it, and download an RPM.

**test\_broker\_reconnect** ()

Test Pulp's support for reconnecting to a broker that goes missing.

Do the following:

1. Start both the broker and several other services.
2. Stop the broker, wait, and start it again.
3. Test Pulp's health. Create an RPM repository, sync it, add a distributor, publish it, and download an RPM.

This test targets:

- Pulp #1635
- Pulp #2613

## 6.66 *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_character\_encoding*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_character\_encoding*

Tests for Pulp's character encoding handling.

RPM files have metadata embedded in their headers. This metadata should be encoded as utf-8, and Pulp should gracefully handle cases where invalid byte sequences are encountered.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_character_encoding.UploadNonAsciiTestCase` (*method*)  
Test whether one can upload an RPM with non-ascii metadata.

Specifically, do the following:

1. Create an RPM repository.
2. Upload and import `pulp_smash.constants.RPM_WITH_NON_ASCII_URL` into the repository.

**test\_all** ()

Test whether one can upload an RPM with non-ascii metadata.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_character_encoding.UploadNonUtf8TestCase` (*method*)  
Test whether one can upload an RPM with non-utf-8 metadata.

Specifically, do the following:

1. Create an RPM repository.
2. Upload and import `pulp_smash.constants.RPM_WITH_NON_UTF_8_URL` into the repository.

This test case targets Pulp #1903.

**test\_all** ()

Test whether one can upload an RPM with non-ascii metadata.

## 6.67 *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_comps\_xml*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_comps\_xml*

Verify an RPM repository's `comps.xml` file.

Each RPM repository has a `repodata` directory, in which various XML files containing metadata are present. This module houses test cases which verify the `comps.xml` file. For a sample `comps.xml` file, search through `pulp_smash.constants.RPM_SIGNED_FEED_URL`.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_comps_xml.SyncRepoTestCase` (*methodName='runTest'*)  
Sync in content from another RPM repository and publish it.

More specifically, this test case does the following:

1. Create a repository with a feed and a distributor.
2. Sync and publish the repository.
3. Verify the `comps.xml` file available in the published repository.

**classmethod** `setUpClass` ()

Create, sync and publish a repository. Fetch its `comps.xml`.

**test\_first\_level\_element** ()

Verify the top-level element is named “comps”.

**test\_langpacks\_element** ()

Verify a `langpacks` element is in `comps.xml`.

Support for package `langpacks` has been added in Pulp 2.9. Consequently, this test is skipped on earlier versions of Pulp.

**test\_second\_level\_elements** ()

Verify the correct second-level elements are present.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_comps_xml.UploadPackageGroupsTestCase` (*methodName='runTest'*)  
Upload custom package groups to an RPM repository and publish it.

More specifically, this test case does the following:

1. Create a repository without a feed.
2. Add yum distributor to the repository.
3. Generate several custom package groups. Upload each of them to Pulp, and import them into the repository.
4. Publish the repository.
5. Verify the `comps.xml` file available in the published repository.

**classmethod** `setUpClass` ()

Create an RPM repository, upload package groups, and publish.

**test\_conditional\_requires** ()

Assert `requires` attributes are correct on conditional packages.

This test assumes `test_packagelist_values` () has passed.

**test\_count** ()

Assert there is one “group” element per imported group unit.

**test\_default\_default** ()

Assert that the default value of `default` tag is ‘false’.

**test\_default\_uservisible** ()

Assert that the default value of `uservisible` tag is ‘false’.

**test\_display\_order\_occurences** ()

Assert `display_order` occurs once if omitted from the unit.

**test\_display\_order\_value ()**

Assert `display_order` is “1024” if omitted from the unit.

This test may be skipped if [Pulp #1787](#) is open.

**test\_has\_groups ()**

Assert that each imported group unit appears in the XML.

**test\_ids\_alone ()**

Assert each “group” element has one “id” child element.

**test\_ids\_unique ()**

Assert each group ID is unique.

**test\_one\_task\_per\_import ()**

Assert only one task is spawned per package group upload.

**test\_packagelist\_values ()**

Assert `packagelist` contains `packagereq` elements with correct text.

This test verifies that, for each of the 4 possible types of package in a group, the `packagelist` in the group XML contains exactly the package names in the uploaded unit.

**test\_root ()**

Assert the root element of the tree has a tag of “comps”.

**test\_single\_elements ()**

Assert that certain tags appear under groups exactly once.

**test\_tasks\_result ()**

Assert each task’s result success flag (if present) is true.

This test assumes `test_one_task_per_import ()` passes.

**test\_tasks\_state ()**

Assert each task’s state is “finished”.

This test assumes `test_one_task_per_import ()` passes.

**test\_translated\_string\_count ()**

Assert that the XML has correct number of translated strings.

Some fields (name, description) are translatable. The tags for these fields are expected to appear once per translation, plus once for the untranslated string. This test verifies that this is the case.

**test\_translated\_string\_values ()**

Assert that the XML has correct values for translated strings.

Some fields (name, description) are translatable. The tags for these fields are expected to appear once per translation, plus once for the untranslated string. This test verifies that each translated string matches exactly the string provided when the group unit was imported.

**test\_verbatim\_boolean\_fields ()**

Assert boolean fields on a unit appear correctly in generated XML.

This test is similar to `test_verbatim_string_fields ()`, but additionally verifies that boolean values are serialized as expected in the XML (i.e. as text ‘true’ or ‘false’).

**test\_verbatim\_string\_fields ()**

Assert string fields on a unit appear unmodified in generated XML.

This test covers fields from a group unit which are expected to be serialized as-is into top-level tags under a `<group>`. For example, this test asserts that the ‘name’ attribute on a group unit will appear in the generated XML as:

```
<group>
  <name>some-value</name>
  ...
</group>
```

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_comps_xml.UploadTwiceTestCase` (*methodName='runTest'*)  
Upload a package group twice.

The first upload should create a new package group, and the second should update the existing package group.  
See: [Pulp #2514](#).

**test\_all** ()  
Upload a package group to a repository twice.

`pulp_smash.tests.pulp2.rpm.api_v2.test_comps_xml.setUpModule` ()  
Possibly skip the tests in this module.

Skip tests if [Pulp #2277](#) affects us.

## 6.68 `pulp_smash.tests.pulp2.rpm.api_v2.test_content_applicability`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_content\_applicability*

Tests for Pulp's `content applicability` feature.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_content_applicability.BasicTestCase` (*methodName='runTest'*)  
Perform simple applicability generation tasks.

**classmethod** `setUpClass` ()  
Create and sync a repository.

The regular test methods that run after this can create consumers that bind to this repository.

**classmethod** `tearDownClass` ()  
Delete the repository created by `setUpClass` ().

**test\_negative** ()  
Verify content isn't made available when appropriate.

Do the same as `test_positive` (), except that both packages' versions are equal to what's offered by the repository.

**test\_positive** ()  
Verify content is made available when appropriate.

Specifically, do the following:

1. Create a consumer.
2. Bind the consumer to the repository created in `setUpClass` ().
3. Create a consumer profile where:
  - two packages are installed,
  - both packages' versions are lower than what's offered by the repository,
  - one of the corresponding packages in the repository has an applicable erratum, and
  - the other corresponding package in the repository doesn't have an applicable erratum.
4. Regenerate applicability for the consumer.

5. Fetch applicability for the consumer. Verify that both packages are listed as eligible for an upgrade.

`pulp_smash.tests.pulp2.rpm.api_v2.test_content_applicability.CONTENT_APPLICABILITY_REPORT_SCHEMA`  
A schema for a content applicability report for a consumer.

`pulp_smash.tests.pulp2.rpm.api_v2.test_content_applicability.RPM_WITHOUT_ERRATUM_METADATA_SCHEMA`  
Metadata for an RPM without an associated erratum.

`pulp_smash.tests.pulp2.rpm.api_v2.test_content_applicability.RPM_WITH_ERRATUM_METADATA_SCHEMA`  
Metadata for an RPM with an associated erratum.

## 6.69 `pulp_smash.tests.pulp2.rpm.api_v2.test_content_sources`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_content\_sources*

Tests for Pulp's content sources feature.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_content_sources.InvalidHeadersTestCase` (*methodName*)  
Define a content source with invalid headers.

See:

- [Pulp #1282](#)
- [Pulp Smash #643](#)

**classmethod** `setUpClass` ()  
Create a content source with invalid headers.

**classmethod** `tearDownClass` ()  
Destroy the created content source.

**test\_content\_sources** ()  
List Pulp's content sources.

Assert that the list doesn't include an entry corresponding to the newly defined content source configuration file.

**test\_refresh\_content\_sources** ()  
Refresh Pulp's content sources.

Assert that the refresh completes successfully. It should complete successfully because the broken content source is completely skipped.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_content_sources.ValidHeadersTestCase` (*methodName*)  
Define a content source with valid headers.

See:

- [Pulp #1282](#)
- [Pulp Smash #643](#)

**classmethod** `setUpClass` ()  
Create a content source with valid headers.

**classmethod** `tearDownClass` ()  
Destroy the created content source.

**test\_list\_content\_sources** ()  
List Pulp's content sources.

Assert that:



1. The list includes an entry corresponding to the newly defined content source configuration file.
2. This list entry includes the headers defined in the configuration file.

**test\_refresh\_content\_sources** ()

Refresh Pulp's content sources.

Assert that the refresh completes successfully.

## 6.70 *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_copy*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_copy*

Test cases that copy content units.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_copy.CopyErrataRecursiveTestCase` (*methodName='runTest'*)  
Test that recursive copy of erratas copies RPM packages.

**test\_all** ()

Test that recursive copy of erratas copies RPM packages.

This test targets the following issues:

- [Pulp Smash #769](#)
- [Pulp #3004](#)

Do the following:

1. Create and sync a repository with errata, and RPM packages.
2. Create second repository.
3. Copy units from from first repository to second repository using `recursive` as `true`, and filter `type_id` as `erratum`.
4. Assert that RPM packages were copied.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_copy.MtimeTestCase` (*methodName='runTest'*)  
Test whether copied files retain their original mtime.

**test\_all** ()

Test whether copied files retain their original mtime.

This test targets the following issues:

- [Pulp #2783](#)
- [Pulp Smash #720](#)

Do the following:

1. Create, sync and publish a repository, with `generate_sqlite` set to `true`.
2. Get the `mtime` of the sqlite files.
3. Upload an RPM package into the repository, and sync the repository.
4. Get the `mtime` of the sqlite files again. Verify that the mtimes are the same.

## 6.71 *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_crud*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_crud*

Tests that CRUD RPM repositories.

For information on repository CRUD operations, see [Creation, Deletion and Configuration](#).

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_crud.CrudTestCase` (*methodName='runTest'*)  
CRUD a minimal RPM repository.

**static** `create_body()`  
Return a dict for creating a repository.

**static** `update_body()`  
Return a dict for updating a repository.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_crud.CrudWithFeedTestCase` (*methodName='runTest'*)  
CRUD an RPM repository with a feed URL.

**static** `create_body()`  
Return a dict for creating a repository.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_crud.FeedURLUnquoteTestCase` (*methodName='runTest'*)  
Check that feed URLs are unquoted.

See <https://pulp.plan.io/issues/2520>.

**test\_all()**  
Ensure Pulp unquote feed URLs.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_crud.LastUnitAddedTestCase` (*methodName='runTest'*)  
Tests for ensuring proper `last_unit_added` behavior.

**setUp()**  
Perform common set-up tasks.

**test\_update\_on\_copy()**  
Check if copying units into a repo updates `last_unit_added`.

Do the following:

1. Create a repository with a feed and sync it.
2. Create a second repository. Assert the second repository's `last_unit_added` attribute is null.
3. Copy a content unit from first repository to the second. Assert the second repository's `last_unit_added` attribute is non-null.
4. Publish the second repository. Assert its `last_unit_added` attribute is non-null.

**test\_update\_on\_sync()**  
Check if syncing a repo updates `last_unit_added`.

Do the following:

1. Create a repository with a feed.
2. Assert the repository's `last_unit_added` attribute is null.
3. Sync the repository.
4. Assert the repository's `last_unit_added` attribute is non-null.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_crud.NonExistentRepoTestCase` (*methodName='runTest'*)  
Perform actions on non-existent repositories.

This test targets [Pulp Smash #157](#).

**setUp** ()  
Set variables used by each test case.

**test\_delete** ()  
Delete a non-existent repository.

**test\_update** ()  
Update a non-existent repository.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_crud.PulpDistributionTestCase` (*methodName='runTest'*)  
Check if a feed with PULP\_DISTRIBUTION.xml syncs properly.

See <https://pulp.plan.io/issues/1086>

**test\_all** ()  
Check for content synced from a feed with PULP\_DISTRIBUTION.xml.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_crud.RPMDistributorTestCase` (*methodName='runTest'*)  
RPM distributor tests.

**test\_update\_checksum\_type** ()  
Check if RPM distributor can receive null checksum\_type.

See: <https://pulp.plan.io/issues/2134>.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_crud.RepositoryGroupCrudTestCase` (*methodName='runTest'*)  
CRUD a minimal RPM repositories' groups.

For information on repositories' groups CRUD operations, see *Creation, Delete, and Update*  
<<http://docs.pulpproject.org/en/latest/dev-guide/integration/rest-api/repo/groups/cud.html>>

**classmethod setUpClass** ()  
Create, update, read and delete a repository group.

**test\_create** ()  
Assert the created repository group has all requested attributes.

Walk through each of the attributes present on the create body and verify the attribute is present in the repository group.

**test\_read** ()  
Assert the repo group update response has the requested changes.

**test\_status\_codes** ()  
Assert each response has a correct status code.

**test\_update** ()  
Assert the repo group update response has the requested changes.

## 6.72 `pulp_smash.tests.pulp2.rpm.api_v2.test_download_policies`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_download_policies`

Tests for Pulp's download policies, such as "background" and "on demand".

Beware that the test cases for the "on demand" download policy will fail if Pulp's Squid server is not configured to return an appropriate hostname or IP when performing redirection.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_download_policies.BackgroundTestCase` (*methodName*)  
Ensure the “background” download policy works.

**classmethod** `setUpClass` ()

Create an RPM repository with a valid feed and sync it.

Do the following:

1. Reset Pulp, including the Squid cache.
2. Create a repository with the “background” download policy.
3. Sync and publish the repository.
4. Download an RPM from the repository.

**test\_repo\_local\_units** ()

Assert that all content is downloaded for the repository.

**test\_request\_history** ()

Assert that the request was serviced directly by Pulp.

If Pulp did not have the content available locally, it would redirect the client to the streamer and the rpm request would contain a history entry for that redirect.

**test\_rpm\_checksum** ()

Assert the checksum of the downloaded RPM matches the metadata.

**test\_spawned\_download\_task** ()

Assert that a download task was spawned as a result of the sync.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_download_policies.FixFileCorruptionTestCase` (*m*)  
Ensure the “on demand” download policy can fix file corruption.

**classmethod** `get_rpm_abs_path` ()

Return the absolute path to `pulp_smash.constants.RPM`.

**classmethod** `setUpClass` ()

Create an RPM repository and issue a task to download the repo.

Do the following:

1. Reset Pulp.
2. Create a repository with the “on demand” download policy.
3. Sync and publish the repository.
4. Trigger a repository download.
5. Corrupt a file in the repository.
6. Trigger a repository download, without unit verification.
7. Trigger a repository download, with unit verification.

**test\_corruption\_occurred** ()

Assert corrupting a unit changes its checksum.

This is to ensure we actually corrupted the RPM and validates further testing.

**test\_start\_end\_checksums** ()

Verify Pulp’s behaviour when `verify_all_units` is true.

Assert that the pre-corruption checksum of the unit is the same as the post-redownload checksum of the unit.

**test\_units\_after\_download()**

Assert all units are downloaded after download\_repo finishes.

**test\_units\_before\_download()**

Assert no content units were downloaded besides metadata units.

**test\_verify\_all\_units\_false()**

Verify Pulp's behaviour when verify\_all\_units is false.

Assert that the checksum of the corrupted unit is unchanged, indicating that Pulp did not verify (or re-download) the checksum of the corrupted unit.

**test\_verify\_all\_units\_true()**

Verify Pulp's behaviour when verify\_all\_units is true.

Assert that the checksum of the corrupted unit is changed, indicating that Pulp did verify the checksum of the corrupted unit, and subsequently re-downloaded the unit.

**class** pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies.**OnDemandTestCase** (*methodName=''*)

Ensure the "on demand" download policy works.

**classmethod** setUpClass()

Create an RPM repository with a valid feed and sync it.

Do the following:

1. Reset Pulp, including the Squid cache.
2. Create a repository with the "on demand" download policy.
3. Sync and publish the repository.
4. Download an RPM from the published repository.
5. Download the same RPM to ensure it is served by the cache.

**test\_local\_units()**

Assert no content units were downloaded besides metadata.

**test\_repository\_units()**

Assert there is at least one content unit in the repository.

**test\_request\_history()**

Assert the initial request received a 302 Redirect.

**test\_rpm\_cache\_control\_header()**

Assert the request has the Cache-Control header set.

**test\_rpm\_cache\_lookup\_header()**

Assert the first request resulted in a cache miss from Squid.

**test\_rpm\_checksum()**

Assert the checksum of the downloaded RPM matches the metadata.

**test\_same\_rpm\_cache\_header()**

Assert the second request resulted in a cache hit from Squid.

**test\_same\_rpm\_checksum()**

Assert the checksum of the second RPM matches the metadata.

**class** pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies.**SwitchPoliciesTestCase** (*methodName=''*)

Ensure that repo's download policy can be updated and works.

Each test exercises a different download policy permutation by doing the following:

1. Create a repository configuring to one download policy

2. Read the repository and check if the download policy was properly set.
3. Update the repository to a different download policy.
4. Read the repository and check if the download policy was updated.
5. Sync the repository
6. Assert that the final download policy was used and works properly.

**assert\_background** (*repo, tasks*)

Assert that background download policy is properly working.

**assert\_immediate** (*repo, tasks*)

Assert that immediate download policy is properly working.

**assert\_on\_demand** (*repo*)

Assert that on\_demand download policy is properly working.

**repository\_setup** (*first, second*)

Set up a repository for download policy switch test.

Create a repository using the first download policy, assert it was set, update to the second download policy, assert it was set, then sync the repository and finally poll the spawned tasks.

Return a tuple with the repository and tasks.

**setUp** ()

Make sure Pulp and Squid are reset.

**test\_background\_to\_immediate** ()

Check if switching from background to immediate works.

**test\_background\_to\_on\_demand** ()

Check if switching from background to on\_demand works.

**test\_immediate\_to\_background** ()

Check if switching from immediate to background works.

**test\_immediate\_to\_on\_demand** ()

Check if switching from immediate to on\_demand works.

**test\_on\_demand\_to\_background** ()

Check if switching from on\_demand to background works.

**test\_on\_demand\_to\_immediate** ()

Check if switching from on\_demand to immediate works.

`pulp_smash.tests.pulp2.rpm.api_v2.test_download_policies.setUpModule()`

Skip tests if the RPM plugin is not installed.

## 6.73 *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_duplicate\_uploads*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_duplicate\_uploads*

Tests for how well Pulp can deal with duplicate uploads.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_duplicate_uploads.DuplicateUploadsTestCase` (*metaclass*)

Test how well Pulp can deal with duplicate unit uploads.

**do\_test** (*feed, type\_id, body, unit\_key=None*)

Test how well Pulp can deal with duplicate unit uploads.

Do the following:

1. Create a new feed-less repository.
2. Upload content and import it into the repository. Assert the upload and import was successful.
3. Upload identical content and import it into the repository.

The second upload should silently fail for all Pulp releases in the 2.x series.

**classmethod setUpClass()**

Set a class-wide variable.

**test\_iso()**

Upload duplicate ISO content. See `do_test()`.

This test targets the following issues:

- [Pulp Smash #582](#)
- [Pulp #2274](#)

**test\_rpm()**

Upload duplicate RPM content. See `do_test()`.

This test targets the following issues:

- [Pulp Smash #81](#)
- [Pulp #1406](#)

## 6.74 `pulp_smash.tests.pulp2.rpm.api_v2.test_errata`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_errata`

Test whether applying an erratum will update an RPM package version.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_errata.ApplyErratumTestCase` (*methodName='runTest'*)

Test whether applying an erratum will install referenced RPMs.

**test\_all()**

Test whether applying an erratum will install referenced RPMs.

It does the following:

1. Create, sync and publish a repository with errata and RPM packages. Two of these RPMs have the same name and different versions. The newest version is referenced by one of the errata.
2. Install the older version of the aforementioned RPM.
3. Apply the erratum, and verify that newer version of the RPM is installed.

This test targets [Pulp Smash #760](#).

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_errata.LargePackageListTestCase` (*methodName='runTest'*)

Test syncing errata with large package list.

**test\_all()**

Test syncing errata with large package list.

This test targets the following issue:

- [Pulp #2681](#)
- [Pulp Smash #656](#)

Do the following:

1. Create two repositories, each with a feed URL of `pulp_smash.constants.RPM_LARGE_UPDATEINFO`.
2. Sync both repositories. Assert that each sync finishes without errors.

## 6.75 `pulp_smash.tests.pulp2.rpm.api_v2.test_export`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_export`

Test the API's *Export Distributors* feature.

```
class pulp_smash.tests.pulp2.rpm.api_v2.test_export.BaseExportChecksumTypeTestCase (*args,
                                                                                   **kwargs)
```

Base class for repo and repo group export with checksum type tests.

```
get_export_entity ()
    Provide the export entity.
```

The entity can be either a repository or a repository group.

```
get_export_entity_type ()
    Provide the export entity type.
```

Return `repos` for repository and `repo_group` for repository group.

```
get_repomd_iso_publish_path (export_dir, distributor)
    Provide the repomd.xml publish path within an exported ISO.
```

Repository and repository group exports have a different path to repomd.xml file within the exported ISO.

```
get_repomd_publish_path (export_dir, distributor)
    Provide the repomd.xml publish path.
```

Repository and repository group exports have a different path to repomd.xml file.

```
classmethod setUpClass ()
    Create and sync a repository.
```

Also skips the test if Pulp version less than 2.9.

Children of this base class must provide a `distributors` attribute with the list of distributors to export a repository or repository group.

```
test_publish_to_dir_checksum_type ()
    Publish to a directory choosing the checksum type.
```

```
test_publish_to_web_checksum_type ()
    Publish to web choosing the checksum type.
```

```
class pulp_smash.tests.pulp2.rpm.api_v2.test_export.ExportChecksumTypeTestCase (*args,
                                                                                   **kwargs)
```

Publish a repository choosing the distributor checksum type.

```
get_export_entity ()
    Provide the export entity.
```

```
get_export_entity_type ()
    Provide the export entity type.
```

```
get_repomd_iso_publish_path (export_dir, distributor)
    Provide the repomd.xml publish path within an exported ISO.
```



**get\_repomd\_publish\_path** (*export\_dir*, *distributor*)

Provide the repomd.xml publish path.

**classmethod setUpClass** ()

Create some distributors.

Each distributor is configured with a valid checksum type.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_export.ExportDirMixin` (*\*args*,  
*\*\*kwargs*)

Mixin with repo export to dir utilities.

A mixin with methods for managing an export directory on a Pulp server. This mixin is designed to support the following work flow:

1. Create a directory. (See `create_export_dir()`.)
2. Export a repository to the directory.
3. Make the directory readable. (See `change_export_dir_owner()`.)
4. Inspect the contents of the directory.

`publish_to_dir()` conveniently executes steps 1–3. Consider using the other methods only if more granularity is needed.

A class attribute named `cfg` must be present. It should be a `pulp_smash.config.PulpSmashConfig`.

**change\_export\_dir\_owner** (*export\_dir*)

Change the owner to the running Pulp Smash user.

Update the remote path `dir` owner to the user running Pulp Smash.

**create\_export\_dir** ()

Create a directory, and ensure Pulp can export to it.

Create a directory, and set its owner and group to `apache`. If [Pulp issue 616](#) affects the current Pulp system, disable SELinux, and schedule a clean-up command that re-enables SELinux.

**Warning:** Only call this method from a unittest `test*` method. If called from elsewhere, SELinux may be left disabled.

**Returns** The path to the created directory, as a string.

**publish\_to\_dir** (*entity\_href*, *distributor\_id*)

Create an export directory, publish to it, and change its owner.

For details, see `ExportDirMixin`.

#### Parameters

- **entity\_href** – The path to an entity such as a repository or a repository group.
- **distributor\_id** – The ID of the distributor to use when exporting.

**Returns** The path to the export directory.

**sudo** ()

Return either `'` or `'sudo '`.

Return the former if root, and the latter if not.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_export.ExportDistributorTestCase` (\*args, \*\*kwargs)

Establish we can publish a repository using an export distributor.

**setUp** ()

Optionally create an export distributor.

Create an export distributor only if one is not already present. (See `setUpClass` ().)

**classmethod setUpClass** ()

Create and sync a repository. Optionally create a distributor.

Skip creating the distributor if we are testing Pulp 2.9 and it is affected by [Pulp #1928](#).

**test\_publish\_to\_dir** ()

Publish the repository to a directory on the Pulp server.

Verify that `pulp_smash.constants.RPM` is present and has a correct checksum.

This test is skipped if selinux is installed and enabled on the target system an [Pulp issue 616](#) is open.

**test\_publish\_to\_web** ()

Publish the repository to the web, and fetch the ISO file.

The ISO file should be available over both HTTP and HTTPS. Fetch it from both locations, and assert that the fetch was successful.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_export.RepoGroupExportChecksumTypeTestCase` (\*args, \*\*kwargs)

Publish a repository group choosing the distributor checksum type.

**get\_export\_entity** ()

Provide the export entity.

**get\_export\_entity\_type** ()

Provide the export entity type.

**get\_repomd\_iso\_publish\_path** (*export\_dir, distributor*)

Provide the repomd.xml publish path within an exported ISO.

**get\_repomd\_publish\_path** (*export\_dir, distributor*)

Provide the repomd.xml publish path.

**classmethod setUpClass** ()

Create required entities for publishing a repository group.

Do the following:

1. Create a repository group and add the repository created by super call.
2. Creates some distributors. Each distributor is configured with a valid checksum type.

`pulp_smash.tests.pulp2.rpm.api_v2.test_export.setUpModule` ()

Possibly skip the tests in this module.

Skip tests if [Pulp #2277](#) affects us.

## 6.76 `pulp_smash.tests.pulp2.rpm.api_v2.test_force_full`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_force_full`

Tests for publishing with the `force_full` parameter set.

When a repository is published, Pulp checks to see if certain steps can be skipped. For example, if one publishes a repository twice in a row, the second publish is a no-op, as nothing needs to be done. As of Pulp 2.9, clients can tell Pulp to perform a “full” publish. When this is done, Pulp executes all publication steps, even steps that normally would be skipped.

This module tests Pulp’s handling of “full” publishes.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_force_full.ForceFullTestCase` (*methodName='runTest'*)  
Test the `force_full` option.

Repeatedly publish a repository. Set the `force_full` option to various values, and try omitting it too.

**get\_step** (*steps, step\_type*)  
Return the task step with the given `step_type`.

#### Parameters

- **steps** – A list of dicts, as can be accessed by `call_report_task['result']['details']`.
- **step\_type** – The `step_type` of a particular step, such as `save_tar`.

**Returns** The matching step.

**Raises** An assertion error if exactly one match is not found.

**classmethod** `setUpClass` ()  
Create and sync a repository.

**test\_01\_force\_full\_false** ()  
Publish the repository and set `force_full` to false.  
A full publish should occur.

**test\_02\_force\_full\_omit** ()  
Publish the repository and omit `force_full`.  
A fast-forward publish should occur. This test targets [Pulp #1966](#).

**test\_03\_force\_full\_true** ()  
Publish the repository and set `force_full` to true.  
A full publish should occur. The “force” publish feature was introduced in Pulp 2.9, and as such, this test will skip when run against an older version of Pulp. See [Pulp #1938](#).

## 6.77 `pulp_smash.tests.pulp2.rpm.api_v2.test_iso_crud`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_iso\_crud*

Test CRUD for ISO RPM repositories.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_iso_crud.AddImporterDistributorTestCase` (*methodName='runTest'*)  
Add an importer and a distributor to an existing untyped repository.

See:

- [Associate an Importer to a Repository](#)
- [Associate a Distributor with a Repository](#)

**classmethod** `setUpClass` ()  
Create a repository and add an importer and distributor to it.  
Do the following:

1. Create a repository.
2. Read the repository's importers and distributors.
3. Add an importer and distributor to the repo.
4. Re-read the repository's importers and distributors.

**test\_add\_distributor** ()

Check the HTTP status code for adding a distributor.

**test\_add\_importer** ()

Check the HTTP status code for adding an importer.

**test\_after** ()

Verify the repository ends up with one importer and distributor.

**test\_before** ()

Verify the repository has no importer or distributors initially.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_iso_crud.CreateTestCase` (*methodName='runTest'*)  
Create an ISO RPM repo with an importer and distributor.

**classmethod** `setUpClass` ()

Create an ISO RPM repo with an importer and distributor.

**test\_attributes** ()

Assert the created repository has the requested attributes.

**test\_headers\_location** ()

Assert the response's Location header is correct.

The Location may be either an absolute or relative URL. See `pulp_smash.tests.pulp2.platform.api_v2.test_repository.CreateSuccessTestCase.test_location_header` ().

**test\_status\_code** ()

Assert the response has an HTTP 201 status code.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_iso_crud.ISOUpdateTestCase` (*methodName='runTest'*)  
Verify how ISO repos handles changes in content already in Pulp.

**check\_checksums** (*units\_pre, units\_post*)

Assert the checksums in `units_pre` and `units_post` are disjoint.

**check\_names** (*units\_pre, units\_post*)

Assert that the names in `units_pre` and `units_post` are equal.

**test\_all** ()

Verify how ISO repos handles changes in content already in Pulp.

The main goal of this test is to verify how ISO repository handles updates in content already in Pulp.

For this test two different feed urls will be used. These urls contain the same amount of units, the units have the same type and name in both urls, but different content thereafter different checksum values. To recreate this dynamic scenario of change. After the repository is synced for the first time the feed url is updated, and the repository is synced again.

This test targets the following issues:

- [Pulp Smash #715](#)
- [Pulp #2773](#)
- [Pulp #3047](#)

- Pulp #3100

Do the following:

1. Create and sync an ISO repository.
2. Update the repository's feed URL, and sync it. This simulates a change in the contents of the source ISOs.
3. Assert that number of units remain the same, but the content has changed.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_iso_crud.PulpManifestTestCase` (*methodName='runTest*)  
Ensure ISO repo properly handles PULP\_MANIFEST information.

**static parse\_pulp\_manifest** (*feed\_url*)

Parse PULP\_MANIFEST information from *feed\_url*/PULP\_MANIFEST.

**Parameters** *feed\_url* – The URL for the file feed. It will be joined with /PULP\_MANIFEST in order to find the PULP\_MANIFEST file.

**Returns** A list of dicts mapping each PULP\_MANIFEST row. The dict contains the keys name, checksum and size which represent the PULP\_MANIFEST data.

**test\_invalid\_file\_feed** ()

Create and sync a ISO repo from an invalid file feed.

Assert that the sync fails with the information that some units were not available.

**test\_valid\_file\_feed** ()

Create and sync a ISO repo from a file feed.

Assert that the number of units synced is the same as PULP\_MANIFEST lists.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_iso_crud.ReadUpdateDeleteTestCase` (*methodName='r*)  
Establish that we can interact with typed repositories as expected.

**classmethod setUpClass** ()

Create three repositories and read, update and delete them.

**test\_read** ()

Assert that the “read” call returns correct attributes.

**test\_read\_distributors** ()

Assert each read w/distributors contains info about distributors.

**test\_read\_importers** ()

Assert each read with importers contains info about importers.

**test\_status\_code** ()

Assert each response has a correct HTTP status code.

## 6.78 `pulp_smash.tests.pulp2.rpm.api_v2.test_iso_sync_publish`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_iso_sync_publish`

Tests that sync and publish ISO repositories.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_iso_sync_publish.ServeHttpsFalseTestCase` (*metho*)  
Publish w/an rsync distributor when *serve\_https* is false.

More precisely, do the following:

1. Create an ISO RPM repository. Ensure the repository has distributors of type `iso_distributor` and `iso_rsync_distributor`, and ensure the former distributor's `publish_https` attribute is false.
2. Populate the repository with some content.
3. Publish the repository with both distributors. Assert that the ISO rsync distributor successfully places files on the target system.

This test targets [Pulp #2657](#). According to this issue, the ISO rsync distributor will fail to publish files if the the ISO distributor has not published files via HTTPS.

**setUp()**

Set the `pulp_manage_rsync` boolean.

**tearDown()**

Reset the `pulp_manage_rsync` boolean.

**test\_all()**

Publish w/an rsync distributor when `serve_https` is false.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_iso_sync_publish.UploadIsoTestCase` (*methodName='runTest'*)  
Upload an ISO file into an ISO repository.

**test\_all()**

Upload an ISO file into an ISO repository.

Specifically, do the following:

1. Create an ISO repository.
2. Upload `pulp_smash.constants.FILE_URL` to the repository.
3. Publish the repository.
4. Download the published ISO, and assert it's equal to the uploaded ISO.

## 6.79 `pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist`

Tests that exercise Pulp's support for mirrorlist feeds.

The tests in this module target:

- [Pulp #175](#): “As a user, I can specify mirrorlists for rpm repository feeds.”
- [Pulp #2224](#): “Cannot sync from mirrorlists.”

The test cases in this module reference “good,” “mixed” and “bad” mirrorlist files. A “good” file contains only valid references, a “mixed” file contains both valid and invalid references, and a “bad” file contains only invalid references.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist.BadMirrorlistTestCase` (*methodName='runTest'*)  
Create a repository that references a “bad” mirrorlist file.

Do the following:

1. Create a repository. Make its importer `feed` option reference a “bad” mirrorlist file.
2. Sync the repository. Expect a failure.

**test\_all()**

Execute the test case business logic.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist.BadRelativeUrlTestCase` (*methodName='runTest'*)  
Like `BadMirrorlistTestCase`, but pass `relative_url` too.

**test\_all()**  
Execute the test case business logic.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist.GoodMirrorlistTestCase` (*methodName='runTest'*)  
Create a repository that references a “good” mirrorlist file.

Do the following:

1. Create a repository. Make its importer `feed` option reference a “good” mirrorlist file.
2. Sync and publish the repository.
3. Download and verify a file from the published repository.

**test\_all()**  
Execute the test case business logic.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist.GoodRelativeUrlTestCase` (*methodName='runTest'*)  
Like `GoodMirrorlistTestCase`, but pass `relative_url` too.

**test\_all()**  
Execute the test case business logic.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist.MixedMirrorlistTestCase` (*methodName='runTest'*)  
Create a repository that references a “mixed” mirrorlist file.

1. Create a repository. Make its importer `feed` option reference a “mixed” mirrorlist file.
2. Sync and publish the repository.
3. Download and verify a file from the published repository.

**test\_all()**  
Execute the test case business logic.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist.MixedRelativeUrlTestCase` (*methodName='runTest'*)  
Like `MixedMirrorlistTestCase`, but pass `relative_url` too.

**test\_all()**  
Execute the test case business logic.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist.UtilsMixin`  
A mixin providing methods to the test cases in this module.

Any class inheriting from this mixin must also inherit from `unittest.TestCase` or a compatible clone.

**check\_issue\_2277** (*cfg*)  
Skip the current test method if Pulp [issue #2277](#) affects us.

**check\_issue\_2321** (*cfg*)  
Skip the current test method if Pulp [issue #2321](#) affects us.

**check\_issue\_2326** (*cfg*)  
Skip the current test method if Pulp [issue #2326](#) affects us.

**check\_issue\_2363** (*cfg*)  
Skip the current test method if Pulp [issue #2363](#) affects us.

**create\_repo** (*cfg, feed, relative\_url=None*)  
Create an RPM repository with a yum importer and distributor.  
In addition, schedule the repository for deletion with `addCleanup`.

**Parameters**

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – The Pulp deployment on which to create a repository.
- **feed** – A value for the yum importer’s feed option.
- **relative\_url** – A value for the yum distributor’s `relative_url` option. If `None`, this option is not passed to Pulp.

**Returns** A detailed dict of information about the repository.

`pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist.setUpModule()`  
Maybe skip this module of tests.

`pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist.tearDownModule()`  
Delete orphan content units.

## 6.80 `pulp_smash.tests.pulp2.rpm.api_v2.test_no_op_publish`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_no\_op\_publish*

Test Pulp’s handling of no-op publishes.

As of version 2.9, Pulp has the ability to perform no-op publishes, instead of the more typical full publish. A no-op publish is one in which no files are changed, including metadata files. No-op publishes occur when all of the components — including the repository, distributor and override config — are unchanged.

Tests for this feature include the following:

- Publish a repository twice. (See *PubTwiceTestCase*.)
- Publish a repository, change it, and publish it again. (See *ChangeRepoTestCase*.)
- Publish a repository twice, with an override config the second time. (See `pulp_smash.tests.pulp2.rpm.api_v2.test_export.ExportDistributorTestCase`.)
- Publish a repository twice, with an override config both times. (See *PubTwiceWithOverrideTestCase*.)

For more information, see:

- [Pulp #1724](#)
- [Pulp #1928](#)
- [Pulp Smash #127](#)
- [Pulp Smash #232](#)

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_no_op_publish.BaseTestCase` (*methodName='runTest'*)  
Provide common behaviour for the test cases in this module.

**classmethod** `setUpClass()`

Create a repository with a distributor, and populate it.

In addition, create several variables for use by the test methods.

**test\_first\_publish()**

Assert the first publish is a full publish.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_no_op_publish.ChangeRepoTestCase` (*methodName='runTest'*)  
Publish a repository, change it, and publish it again.



**classmethod setUpClass()**

Publish a repository, change it, and publish it again.

**test\_second\_publish\_repomd()**

Assert the two publishes produce identical `repomd.xml` files.

**test\_second\_publish\_tasks()**

Assert the second publish's last task reports a no-op publish.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_no_op_publish.NoOpPublishMixin`

Provide tests for the no-op publish test cases in this module.

**test\_second\_publish\_repomd()**

Assert the two publishes produce identical `repomd.xml` files.

**test\_second\_publish\_tasks()**

Assert the second publish's last task reports a no-op publish.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_no_op_publish.PubTwiceTestCase` (*methodName='runTest'*)

Publish a repository twice.

**classmethod setUpClass()**

Publish a repository twice.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_no_op_publish.PubTwiceWithOverrideTestCase` (*methodName='runTest'*)

Publish a repository twice, with an override config both times.

**classmethod setUpClass()**

Publish a repository twice, with an override config both times.

`pulp_smash.tests.pulp2.rpm.api_v2.test_no_op_publish.get_repomd_xml_path` (*distributor\_rel\_url*)

Construct the path to a repository's `repomd.xml` file.

**Parameters** `distributor_rel_url` – A distributor's `relative_url` option.

**Returns** An string path to a `repomd.xml` file.

`pulp_smash.tests.pulp2.rpm.api_v2.test_no_op_publish.setUpModule()`

Possibly skip the tests in this module. Create and sync an RPM repo.

Skip this module of tests if Pulp is older than version 2.9. (See [Pulp #1724](#).) Then create an RPM repository with a feed and sync it. Test cases may copy data from this repository but should **not** change it.

`pulp_smash.tests.pulp2.rpm.api_v2.test_no_op_publish.tearDownModule()`

Delete the repository created by `setUpModule()`.

## 6.81 `pulp_smash.tests.pulp2.rpm.api_v2.test_orphan_remove`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_orphan\_remove*

Test Pulp's handling of orphaned content units.

This module integrates tightly with [Pulp Fixtures](#). [Pulp Smash #134](#) and [Pulp Smash #459](#) describe specific tests that should be in this module.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_orphan_remove.OrphansTestCase` (*methodName='runTest'*)

Establish that API calls related to orphans function correctly.

At a high level, this test case does the following:

1. Create an RPM repository and populate it with content. Delete the repository, thus leaving behind orphans.
2. Make several orphan-related API calls, and assert that each call has the desired effect.

**check\_one\_orphan\_deleted** (*orphans\_pre, orphans\_post, orphan*)

Ensure that a specific orphan is well and truly deleted.

**Parameters**

- **orphans\_pre** – The response to GET `pulp_smash.tests.pulp2.constants.ORPHANS_PATH` before the orphan was deleted.
- **orphans\_post** – The response to GET `pulp_smash.tests.pulp2.constants.ORPHANS_PATH` after the orphan was deleted.
- **orphan** – A dict describing the orphan that was deleted.

**Returns** Nothing.

**classmethod setUpClass** ()

Create orphans.

Create, sync and delete an RPM repository. Doing this creates orphans that the test methods can make use of.

**test\_00\_orphans\_available** ()

Assert that an expected number of orphans is present.

If the expected number of orphans is present, set a class variable indicating such. The following test methods can conditionally run or skip based on this variable. If this method fails, it may indicate that other repositories exist and have references to the same content units.

**test\_01\_get\_by\_href** ()

Get an orphan by its href.

**test\_01\_get\_by\_invalid\_type** ()

Get orphans by content type. Specify a non-existent content type.

**test\_02\_delete\_by\_href** ()

Delete an orphan by its href.

**test\_02\_delete\_by\_type\_and\_id** ()

Delete an orphan by its ID and type.

This test exercises [Pulp #1923](#).

**test\_03\_delete\_by\_content\_type** ()

Delete orphans by their content type.

**test\_04\_delete\_all** ()

Delete all orphans.

**test\_05\_no\_orphans\_exist** ()

Assert no orphans exist.

## 6.82 `pulp_smash.tests.pulp2.rpm.api_v2.test_package_paths`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_package_paths`

Tests that sync repositories whose packages are in varying locations.

The packages in a repository may be in the root of a repository, like so:

```

repository
├── bear-4.1-1.noarch.rpm
├── camel-0.1-1.noarch.rpm
├── ...
└── repodata
    ├── b83f17e552fa7a86f75811147251b4cc4f411eacfde5a187375d-primary.xml.gz
    ├── 5ec9512bc0461c579aebd3fe6d89133db5255cc1e15d529a20-other.sqlite.bz2
    └── ...

```

However, the files in the `repodata/` directory specify the paths to each file included in a repository. Consequently, other layouts are possible, like so:

```

repository
├── packages
│   └── keep-going
│       ├── bear-4.1-1.noarch.rpm
│       ├── camel-0.1-1.noarch.rpm
│       └── ...
└── repodata
    ├── b83f17e552fa7a86f75811147251b4cc4f411eacfde5a187375d-primary.xml.gz
    ├── 5ec9512bc0461c579aebd3fe6d89133db5255cc1e15d529a20-other.sqlite.bz2
    └── ...

```

The tests in this module verify that Pulp can correctly handle these situations.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_package_paths.ReuseContentTestCase` (*methodName=*  
Sync two repositories with identical content but differing layouts.

If two repositories have some identical content, then Pulp should be able to re-use that content. This is true even if the content is placed in differing locations in the two repositories. Do the following:

1. Create a pair of repositories. Give the two repositories a download policy of either on demand or background. (One of these download policies must be used to ensure that the Pulp streamer is used.) Give the two repositories differing feeds, where the feeds reference a pair of repositories with some identical content and differing layouts.
2. Sync each of the repositories.
3. Publish each of the repositories.
4. Fetch an identical content unit from each of the two repositories.

This test targets [Pulp #2354](#).

**create\_repo** (*cfg, feed, download\_policy*)

Create an RPM repository with the given feed and download policy.

Also, schedule the repository for deletion at the end of the current test. Return a detailed dict of information about the just-created repository.

**test\_all** ()

Sync two repositories w/identical content but differing layouts.

## 6.83 `pulp_smash.tests.pulp2.rpm.api_v2.test_remove_unit`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_remove_unit`

Tests for the `remove_missing` repository option.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_remove_unit.RemoveCountTestCase` (*methodName='run'*)  
Re-sync a child repository with the `remove_missing` enabled.

After removing an arbitrary number of units from the parent repository.

Do the following:

1. Create 1st repository with, feed, sync and publish it.
2. Create 2nd repository with feed pointed to 1st repository, and `remove_missing` enabled, sync.
3. Remove an arbitrary number of units from 1st repository, re-publish it.
4. Re-sync the 2nd repository. Assert that `removed_count` is equal to number of removed units.

[Pulp issue #2616](#) caused after sync with `remove_missing` option the next publish is no-op.

**test\_all** ()  
Re-sync a child repository with the `remove_missing` enabled.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_remove_unit.RemoveMissingTestCase` (*methodName='run'*)  
Test the `remove_missing` repository option.

The test procedure is as follows:

1. Create a repository, populate it with content, and publish it.
2. Create several more repositories whose “feed” attribute references the repository created in the previous step. Sync each of these child repositories.
3. Remove a content unit from the parent repository and re-publish it.
4. Re-sync each of the child repositories.

The child repositories are designed to test the following issues:

- [Pulp #1621](#)
- [Pulp #2503](#)

**classmethod** `setUpClass` ()  
Initialize class-wide variables.

**classmethod** `tearDownClass` ()  
Delete all resources named by `resources`.

**test\_01\_create\_root\_repo** ()  
Create, sync and publish a repository.  
  
The repositories created in later steps sync from this one.

**test\_02\_create\_immediate\_child** ()  
Create a child repository with the “immediate” download policy.  
  
Sync the child repository, and verify it has the same contents as the root repository.

**test\_02\_create\_on\_demand\_child** ()  
Create a child repository with the “on\_demand” download policy.  
  
Also, let the repository’s “remove\_missing” option be true. Then, sync the child repository, and verify it has the same contents as the root repository.

**test\_03\_update\_root\_repo** ()  
Remove a content unit from the root repository and republish it.

```
test_04_sync_immediate_child()
    Sync the “immediate” repository.

    Verify it has the same contents as the root repository.

test_04_sync_on_demand_child()
    Sync the “on demand” repository.

    Verify it has the same contents as the root repository.
```

## 6.84 *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_repomd*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_repomd*

Verify the *repomd.xml* file generated by a YUM distributor.

```
class pulp_smash.tests.pulp2.rpm.api_v2.test_repomd.FastForwardIntegrityTestCase (methodName=
    Ensure fast-forward publishes use files referenced by repomd.xml.
```

When Pulp performs an incremental fast-forward publish, it should copy the original repository’s *repodata/ [...]primary.xml* file to the new repository, and then modify it as needed.

According to [Pulp #1088](#), Pulp does something different: it searches for all files named *repodata/[0-9a-zA-Z]\*-primary.xml.\**, sorts them by mtime, copies the newest one to the new repository and modifies it. This behaviour typically works, because Pulp only creates one *[...]primary.xml* file in a given repository. However, this behaviour is fragile, and it’s especially likely to fail when third-party tools are used to supplement Pulp’s functionality. What Pulp *should* do is to consult the old repository’s *repomd.xml* file to find the *[...]primary.xml* file.

Do the following:

1. Create a repository with a yum distributor, sync in some content, and publish it. Verify that *[...]primary.xml* contains a certain phrase.
2. Create a second *[...]primary.xml* file in the published repository, and replace the known phrase with a new phrase. Trigger a full publish, and verify that the known phrase is present, not the new phrase.
3. Create a second *[...]primary.xml* file in the published repository, and replace the known phrase with a new phrase. Trigger an incremental publish, and verify that the known phrase is present, not the new phrase.

```
test_all()
    Ensure fast-forward publishes use files referenced by repomd.xml.
```

```
class pulp_smash.tests.pulp2.rpm.api_v2.test_repomd.RepoMDTestCase (methodName='runTest')
    Tests to ensure repomd.xml can be created and is valid.
```

```
classmethod setUpClass()
    Generate, fetch and parse a repomd.xml file.
```

Do the following:

1. Create an RPM repository with a YUM distributor and publish it.
2. Fetch the *repomd.xml* file from the distributor, and parse it.

```
test_data()
    Assert the tree’s “data” elements have correct “type” attributes.
```

```
test_tag()
    Assert the XML tree’s root element has the correct tag.
```

## 6.85 `pulp_smash.tests.pulp2.rpm.api_v2.test_repository_layout`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_repository\_layout*

Tests for the published repository layout.

Starting with Pulp 2.12, YUM distributor must publish repositories using the layout where the packages are published to into `Packages/<first_letter>` where `<first_letter>` is the first letter of a given RPM package. For example, the `bear.rpm` package will be published into `Packages/b/bear.rpm`. For more information, see [Pulp issue #1976](#).

Old versions of Pulp uses the old layout where all repository's packages were published on the root of the repository directory not inside the `Packages/<first_letter>` subdirectory.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_repository_layout.RepositoryLayoutTestCase` (*metaclass*)  
 Test the YUM distributor publishing repository layout.

**test\_all** ()

Do not use the `packages_directory` option.

Create a distributor with default options, and use it to publish the repository. Verify packages end up in the current directory, relative to the published repository's root. (This same directory contains the `repopdata` directory, and it may be changed by setting the distributor's `relative_url`.)

`pulp_smash.tests.pulp2.rpm.api_v2.test_repository_layout.get_file_hrefs` (*repopmd\_xml*)  
 Return the href of each file in a `repopmd.xml` file.

**Parameters** `repopmd_xml` – An `xml.etree.ElementTree` object representing the root of a `repopmd.xml` document.

**Returns** An iterable of hrefs, with each href as a string.

`pulp_smash.tests.pulp2.rpm.api_v2.test_repository_layout.get_package_hrefs` (*primary\_xml*)  
 Return the href of each package in a `primary.xml` file.

**Parameters** `primary_xml` – An `xml.etree.ElementTree` object representing the root of a `primary.xml` document.

**Returns** An iterable of hrefs, with each href as a string.

`pulp_smash.tests.pulp2.rpm.api_v2.test_repository_layout.get_parse_repodata_primary_xml` (*cfg, distributor, file\_path*)  
 Fetch, decompress, parse and return a `repopdata/...primary.xml.gz` file.

**Parameters**

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about the Pulp deployment being targeted.
- **distributor** – Information about a distributor. It should be a dict containing at least `{'config': {'relative_url': ...}}`.

**Returns** An `xml.etree.ElementTree` object.

`pulp_smash.tests.pulp2.rpm.api_v2.test_repository_layout.get_parse_repodata_xml` (*server\_config, distributor, file\_path*)

Fetch, parse and return an XML file from a `repodata` directory.

#### Parameters

- **server\_config** (`pulp_smash.config.PulpSmashConfig`) – Information about the Pulp deployment being targeted.
- **distributor** – Information about a distributor. It should be a dict containing at least `{'config': {'relative_url': ...}}`.
- **file\_path** – The path to an XML file, relative to the distributor’s relative URL. For example: `repodata/repomd.xml`.

**Returns** The XML document, parsed as an `xml.etree.ElementTree` object.

## 6.86 `pulp_smash.tests.pulp2.rpm.api_v2.test_repoview`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_repoview*

Tests that exercise Pulp’s repoview feature.

For more information, see:

- [Pulp #189](#): “Repoview-like functionality for browsing repositories via the web interface”
- [Yum Plugins](#) → [Yum Distributor](#) → [Optional Configuration Parameters](#)

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_repoview.RepoviewTestCase` (*methodName='runTest'*)  
Publish a repository with the repoview feature on and off.

Do the following:

1. Create an RPM repository, and add some content to it.
2. Publish the repository. Get `/pulp/repos/{rel_url}/`, and verify that no redirects occur.
3. Publish the repository with the `repoview` and `generate_sqlite` options set to true. Get `/pulp/repos/{rel_url}/`, and verify that a redirect to `/pulp/repos/{rel_url}/repoview/index.html` occurs.
4. Repeat step 2.

**test\_all()**

Publish a repository with the repoview feature on and off.

## 6.87 `pulp_smash.tests.pulp2.rpm.api_v2.test_republish`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_republish*

Tests that re-publish repositories.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_republish.RemoveOldRepodataTestCase` (*methodName='runTest'*)  
Check whether old repodata is removed when it should be.

According to [Pulp #2788](#), Pulp will retain unnecessary metadata files from previous publishes. This can be problematic for long-lived repositories, as they will eventually be filled with gobs and gobs of unnecessary data. The fix is to introduce the `remove_old_repodata` and `remove_old_repodata_threshold` options, which control for how long old metadata is retained. Each test in this test case does the following:

1. Create a repository. Ensure the distributor has several interesting settings, including `generate_sqlite` being true.

2. Upload an RPM, publish the repo, and count the number of metadata files. Assert that there are metadata files.
3. Do it again. Either assert that there are more metadata files or that there are the same number of metadata files, depending on the distributor settings.

**do\_test** (*distributor\_config\_update*)

Implement most of the test logic.

**classmethod setUpClass** ()

Set class-wide variables.

**test\_cleanup\_default** ()

Set `remove_old_repodata` to true, and the threshold at default.

Assert there are more metadata files after the second publish.

**test\_cleanup\_disabled** ()

Set `remove_old_repodata` to false, and the threshold to 0.

Assert that there are more metadata files after the second publish.

**test\_cleanup\_later** ()

Set `remove_old_repodata` to true, and the threshold to 3600.

Assert there are more metadata files after the second publish.

**test\_cleanup\_now** ()

Set `remove_old_repodata` to true, and the threshold to 0.

Assert that there are the same number of metadata files after the second publish.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_republish.UnassociateTestCase` (*methodName='runTest'*)  
Republish a repository after removing content.

Specifically, this test case does the following:

1. Create, populate and publish a repository.
2. Pick a content unit from the repository and verify it can be downloaded.
3. Remove the content unit from the repository, and re-publish it, and verify that it can't be downloaded.

**test\_all** ()

Republish a repository after removing content.

## 6.88 `pulp_smash.tests.pulp2.rpm.api_v2.test_retain_old_count`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_retain\_old\_count*

Test the `retain_old_count` feature.

When more than one version of an RPM is present in a repository and Pulp syncs from that repository, it must choose how many versions of that RPM to sync. By default, it syncs all versions of that RPM. The `retain_old_count` option lets one sync a limited number of outdated RPMs.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_retain_old_count.RetainOldCountTestCase` (*methodName='runTest'*)  
Test the `retain_old_count` feature.

**create\_sync\_repo** (*retain\_old\_count*)

Create and sync a repository. Return detailed information about it.

Implement the logic described by the `test_retain_*` methods.



**classmethod setUpClass()**

Create, populate and publish a repository.

Ensure at least two versions of an RPM are present in the repository.

**test\_retain\_one()**

Give `retain_old_count` a value of one.

Create a repository whose feed references the repository created in `setUpClass()`, and whose `retain_old_count` option is one. Sync the repository, and assert that one old version of any duplicate RPMs were copied over.

**test\_retain\_zero()**

Give `retain_old_count` a value of zero.

Create a repository whose feed references the repository created by `setUpClass()`, and whose `retain_old_count` option is zero. Sync the repository, and assert that zero old versions of any duplicate RPMs were copied over.

## 6.89 `pulp_smash.tests.pulp2.rpm.api_v2.test_rsync_distributor`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_rsync_distributor`

Test the functionality of the RPM rsync distributor.

The RPM rsync distributor lets one publish content units to a directory via rsync+ssh. A typical usage of the RPM rsync distributor is as follows:

1. Create RPM repository with yum and RPM rsync distributors.
2. Upload some content units to the repository.
3. Publish the repository with the yum distributor.
4. Publish the repository with the RPM rsync distributor.

The RPM rsync distributor may not be used by itself. One cannot create an RPM repository with just an RPM rsync distributor; and one cannot publish a repository with the RPM rsync distributor without first publishing with a yum distributor.

For more information on the RPM rsync distributor, see [Pulp #1759](#). As a quick reference, consider a repository with the following abbreviated distributor definitions:

```
[
  {
    'distributor_type_id': 'rpm_rsync_distributor',
    'config': {
      'remote': {'host': '192.168.100.32', 'root': '/home/myuser'},
      'remote_units_path': 'foo/bar/biz' # default: 'content/units'
    }
  },
  {
    'distributor_type_id': 'yum_distributor',
    'config': {'relative_url': 'rel-url/'}
  }
]
```

Following a publish with the yum and rpm rsync distributors, respectively, files will be laid out as follows:

```

/home/myuser
├── foo
│   ├── bar
│   │   ├── biz
│   │   │   ├── rpm
│   │   │   │   ├── 06
│   │   │   │   │   ├── ...
│   │   │   │   │   └── dog-4.23-1.noarch.rpm
│   │   │   │   ├── 09
│   │   │   │   │   ├── ...
│   │   │   │   │   └── crow-0.8-1.noarch.rpm
│   └── rel-url
│       ├── bear-4.1-1.noarch.rpm -> ../foo/bar/biz/rpm/a9/.../bear-4.1-1.noarch...
│       └── camel-0.1-1.noarch.rpm -> ../foo/bar/biz/rpm/92/.../camel-0.1-1.noar...

```

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_rsync_distributor.AddUnitTestCase` (*methodName='run'*)  
 Add a content unit to a repo in the middle of several publishes.

When executed, this test case does the following:

1. Create a yum repository with a yum and rsync distributor.
2. Add some content to the repository.
3. Publish the repository with its yum distributor.
4. Add additional content to the repository.
5. Publish the repository with its rsync distributor. This publish shouldn't distribute the new content unit, as the new content unit wasn't included in the most recent publish with the yum distributor.
6. Publish the repository with its yum distributor.
7. Publish the repository with its rsync distributor. This publish should distribute the new content unit, as the new content unit was included in the most recent publish with the yum distributor.

This test case targets:

- [Pulp #2532](#)
- [Pulp Smash #526](#)

**test\_all** ()

Add a content unit to a repo in the middle of several publishes.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_rsync_distributor.DeleteTestCase` (*methodName='run'*)  
 Use the `delete` RPM rsync distributor option.

Do the following:

1. Create a repository with a yum distributor and RPM rsync distributor. Add content units to the repository.
2. Publish with the yum distributor.
3. Publish with the RPM rsync distributor. Verify that the correct files are in the target directory.
4. Remove all files from the repository, and publish with the yum distributor.
5. Publish with the RPM rsync distributor, with `delete` set to `true`. Verify that all files are removed from the target directory.

This test targets [Pulp #2221](#).

**test\_all()**

Use the `delete` RPM rsync distributor option.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_rsync_distributor.ForceFullTestCase` (*methodName=*

Use the `force_full` RPM rsync distributor option.

Do the following:

1. Create a repository with a yum distributor and RPM rsync distributor. Add content units to the repository.
2. Publish with the yum distributor.
3. Publish with the RPM rsync distributor. Verify that the correct files are in the target directory.
4. Remove all files from the target directory. Publish again, and verify that:
  - The task for publishing has a result of “skipped.”
  - No files are placed in the target directory. (This tests Pulp’s fast-forward logic.)
5. Publish with the RPM rsync distributor, with `force_full` set to true. Verify that files are placed in the target directory. Skip this step if [Pulp #2202](#) is not yet fixed.

Additionally, SELinux is temporarily set to “permissive” mode on the target system if [Pulp #2199](#) is not yet fixed.

**test\_all()**

Use the `force_full` RPM rsync distributor option.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_rsync_distributor.PublishBeforeYumDistTestCase`

Publish a repo with the rsync distributor before the yum distributor.

Do the following:

1. Create a repository with a yum distributor and rsync distributor.
2. Publish with the rpm rsync distributor. Verify that:
  - The publish has a result of “skipped.”
  - No files are placed on the remote system.
3. Publish with the rpm rsync distributor again. Perform the same verification steps.

This test targets:

- [Pulp #2187](#)
- [Pulp #2722](#)

**test\_all()**

Publish the rpm rsync distributor before the yum distributor.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_rsync_distributor.PublishTwiceTestCase` (*methodName=*

Publish with a yum and rsync distributor twice.

Do the following when executed:

1. Create a yum repository with a yum and rsync distributor.
2. Add some content to the repository.
3. Publish with the yum and rsync distributor.
4. Publish with the yum and rsync distributor again.

The second publish with the rsync distributor should be a fast-forward publish, as no new units were added to the repository between the first and second publishes. Verify that the first rsync publish is not a fast-forward publish and that the second one is.

This test case targets [Pulp #2666](#).

```
static get_num_processed (publish_task)  
    Return num_processed for unit query step in publish_task.
```

```
test_all ()  
    Publish with a yum and rsync distributor twice.
```

```
class pulp_smash.tests.pulp2.rpm.api_v2.test_rsync_distributor.RemoteUnitsPathTestCase (method)  
    Exercise the remote_units_path option.
```

Do the following:

1. Create a repository with a yum distributor and RPM rsync distributor, and ensure that the latter distributor's `remote_units_path` option is set to a non-default value (not `content/units`). Add content units to the repository.
2. Publish with the yum distributor.
3. Publish with the RPM rsync distributor. Verify that files are placed in the correct directory.
4. Publish with the RPM rsync distributor, with `remote_units_path` passed as publish option. Verify that files are placed in this directory.

```
test_all ()  
    Exercise the remote_units_path option.
```

```
class pulp_smash.tests.pulp2.rpm.api_v2.test_rsync_distributor.RsyncExtraArgsTestCase (method)  
    Use the rsync_extra_args RPM rsync distributor option.
```

Do the following:

1. Create a repository with a yum distributor and RPM rsync distributor. Add content units to the repository.
2. Publish with the yum distributor.
3. Publish with the RPM rsync distributor, with `rsync_extra_args` set to `['--dry-run']`, i.e. no files should actually be copied by rsync.
4. Verify that no files are in the target directory.
5. Publish with the RPM rsync distributor, with `force_full` set to true. Note: `force_full` is needed here as Pulp is not aware that the previous calls to rsync did nothing on the target
6. Verify that all files are present in the target directory.

This test targets [Pulp #3317](#).

```
test_all ()  
    Use the rsync_extra_args RPM rsync distributor option.
```

```
class pulp_smash.tests.pulp2.rpm.api_v2.test_rsync_distributor.VerifyOptionsTestCase (method)  
    Test Pulp's verification of RPM rsync distributor configuration options.
```

Do the following:

- Repeatedly attempt to create an RPM repository with an importer and pair of distributors. Each time, pass an invalid option, or omit a required option.
- Create an RPM repository with an importer and pair of distributors. Pass valid configuration options. This demonstrates that creation failures are due to Pulp's validation logic, not some other factor.

**classmethod setUpClass()**

Create a value for the `rsync distrib`'s `remote` config section.

Using the same config for each of the test methods allows the test methods to behave more similarly.

**tearDown()**

Verify that the `remote` config section hasn't changed.

**test\_predistributor\_id()**

Pass a bogus ID as the `predistributor_id` config option.

**test\_remote\_units\_path()**

Pass an absolute path to the `remote_units_path` config option.

**test\_required\_options()**

Omit each of the required RPM `rsync distributor` config options.

**test\_root()**

Pass a relative path to the `root` configuration option.

**test\_success()**

Successfully create an RPM repo with importers and distributors.

`pulp_smash.tests.pulp2.rpm.api_v2.test_rsync_distributor.setUpModule()`

Conditionally skip the tests in this module.

Skip the tests in this module if:

- The RPM plugin is not installed on the target Pulp server.
- [Pulp #1759](#) is not implemented on the target Pulp server.
- [Pulp #3313](#) is not fixed on the target Pulp server, and the target host is running Fedora 27.

`pulp_smash.tests.pulp2.rpm.api_v2.test_rsync_distributor.tearDownModule()`

Delete orphan content units.

## 6.90 `pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_publish`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_publish`

Test the API's schedule functionality for repository publication.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_publish.CreateFailureTestCase` (*methodNotImplemented*)

Establish that schedules are not created in `documented` scenarios.

**classmethod** `setUpClass()`

Create several schedules.

Each schedule is created to test a different failure scenario.

**test\_status\_code()**

Assert that each response has the expected HTTP status code.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_publish.CreateSuccessTestCase` (*methodNotImplemented*)

Establish that we can create a schedule to publish the repository.

**classmethod** `setUpClass()`

Create a schedule to publish the repository.

Do the following:

1. Create a repository with a valid feed

2. Sync it
3. Schedule publish to run every 30 seconds

**test\_is\_enabled()**

Check if sync is enabled.

**test\_status\_code()**

Assert the response has an HTTP 201 status code.

**test\_total\_run\_count()**

Check that `total_run_count` is sane.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_publish.ReadUpdateDeleteTestCase` (*meth*)

Establish that we can [read](#), [update](#) and [delete](#) schedules.

This test case assumes the assertions in [CreateSuccessTestCase](#) hold true.

**classmethod** `setUpClass()`

Create three schedules and read, update and delete them.

**test\_read\_many()**

Assert the “read\_many” response body contains all schedules.

**test\_read\_one()**

Assert the “read\_one” response contains the correct attributes.

**test\_status\_code()**

Assert each response has a correct HTTP status code.

**test\_update()**

Assert the “update” response body has the correct attributes.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_publish.ScheduledPublishTestCase` (*meth*)

Establish that publish runs according to the specified schedule.

This test case assumes the assertions in [CreateSuccessTestCase](#) and [ReadUpdateDeleteTestCase](#) hold true.

**classmethod** `setUpClass()`

Create a schedule to publish a repo, verify the `total_run_count`.

Do the following:

1. Create a repository with a valid feed
2. Sync it
3. Schedule publish to run every 2 minutes
4. Wait for 130 seconds and read the schedule to get the number of “publish” runs

**test\_no\_failure()**

Make sure any failure ever happened.

**test\_total\_run\_count()**

Check for the expected total run count.

## 6.91 `pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_sync`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_sync`

Test the API’s schedule functionality for repository synchronization.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_sync.CreateFailureTestCase` (*methodName=*  
Establish that schedules are not created in `documented scenarios`.

**classmethod** `setUpClass` ()

Intentionally fail at creating several sync schedules for a repo.

Each schedule tests a different failure scenario.

**test\_status\_code** ()

Assert that each response has the expected HTTP status code.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_sync.CreateRepoMixin`  
Provide a method for creating a repository.

**classmethod** `create_repo` ()

Create a semi-random RPM repository with a valid RPM feed URL.

Add this repository's href to `cls.resources`. Return a two-tuple of (href, importer\_type\_id). This method requires a server config, `cls.cfg`, and a set, `cls.resources`.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_sync.CreateSuccessTestCase` (*methodName=*  
Establish that we can create a schedule to sync the repository.

**classmethod** `setUpClass` ()

Create an RPM repo with a valid feed, create a schedule to sync it.

Do the following:

1. Create a repository with a valid feed
2. Schedule sync to run every 30 seconds

**test\_enabled** ()

Verify the `enabled` attribute in the response.

**test\_status\_code** ()

Assert the response has an HTTP 201 status code.

**test\_total\_run\_count** ()

Verify the `total_run_count` attribute in the response.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_sync.ReadUpdateDeleteTestCase` (*methodName=*  
Establish that we can `read`, `update` and `delete` schedules.

This test case assumes the assertions in `CreateSuccessTestCase` hold true.

**classmethod** `setUpClass` ()

Create three schedules and read, update and delete them.

**test\_delete** ()

Assert the "delete" response body is null.

**test\_read\_many** ()

Assert the "read\_many" response body contains all schedule hrefs.

**test\_read\_one** ()

Assert the "read\_one" response contains the correct attributes.

**test\_status\_code** ()

Assert each response has a correct HTTP status code.

**test\_update** ()

Assert the "update" response body has the correct attributes.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_sync.ScheduledSyncTestCase` (*methodName=*  
Establish that sync runs according to the specified schedule.

This test case assumes the assertions in `CreateSuccessTestCase` and `ReadUpdateDeleteTestCase` hold true.

**classmethod** `setUpClass()`  
Create a schedule to sync the repo, verify the `total_run_count`.

Do the following:

1. Create a repository with a valid feed
2. Schedule sync to run every 30 seconds
3. Wait for 40 seconds and read the schedule to get the number of “sync” runs.

**test\_consecutive\_failures()**  
Assert the sync encountered no consecutive failures.

## 6.92 `pulp_smash.tests.pulp2.rpm.api_v2.test_search`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_search*

Test Pulp’s Searching facilities.

The test cases in this module searches for content units by their type. See:

- [Pulp Smash #133](#) asks for tests showing that it’s possible to search for content units by their type.
- The [Search for Units](#) API documentation is relevant.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_search.BaseSearchTestCase` (*methodName='runTest'*)  
Provide common functionality for the other test cases in this module.

**static** `get_feed_url()`  
Return a repository feed URL. Used by `setUpClass()`.

All child classes should override this method.

**get\_unit\_by\_filename** (*units, filename*)  
Return the unit with the given filename.

Test methods in child classes may find this method to be of use.

### Parameters

- **units** – An iterable of SRPM content units.
- **filename** – The filename of one of the content units.

**Returns** The content unit with the given filename.

**Raises** An assertion error if more or less than one matching unit is found.

**classmethod** `setUpClass()`  
Create and sync a repository.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_search.SearchForRpmTestCase` (*methodName='runTest'*)  
Search for rpm content units in several different ways.

**static** `get_feed_url()`  
Return an RPM repository feed URL.



**test\_include\_repos()**

Search for all “rpm” units, and include repos in the results.

Perform the following searches. Assert a unit with filename `pulp_smash.constants.RPM` is in the search results, and assert it belongs to the repository created in `BaseSearchTestCase.setUpClass()`.

GET	{'include_repos': True} (urlencoded)
POST	{'criteria': {}, 'include_repos': True}

**test\_search\_for\_all()**

Search for all “rpm” units.

Perform the following searches. Assert a unit with filename `pulp_smash.constants.RPM` is in the search results.

GET	n/a
POST	{'criteria': {}}

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_search.SearchForSrpmTestCase` (*methodName='runTest'*)  
Search for `srpm` content units in several different ways.

**static get\_feed\_url()**

Return an RPM repository feed URL.

**test\_include\_repos()**

Search for all “srpm” units, and include repos in the results.

Perform the following searches. Assert a unit with filename `pulp_smash.constants.SRPM` is in the search results, and assert it belongs to the repository created in `BaseSearchTestCase.setUpClass()`.

GET	{'include_repos': True} (urlencoded)
POST	{'criteria': {}, 'include_repos': True}

**test\_search\_for\_all()**

Search for all “srpm” units.

Perform the following searches. Assert a unit with filename `pulp_smash.constants.SRPM` is in the search results.

GET	n/a
POST	{'criteria': {}}

## 6.93 `pulp_smash.tests.pulp2.rpm.api_v2.test_service_resiliency`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_service_resiliency`

Test the resiliency of Pulp’s services.

Pulp is designed to be resilient. It should be possible for a service to disappear and reappear, with the only consequence being slower processing of tasks. This module has tests for Pulp’s resilience in the face of such issues.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_service_resiliency.MissingWorkersTestCase` (*method*)  
Test that Pulp deals well with missing workers.

When executed, this test case will do the following:

1. Ensure there is only one Pulp worker.
2. Create a repository. Let its feed reference a large repository. (For example, EPEL.)
3. Start a sync. Immediately restart the `pulp_workers` service. (It's important that `pulp_workers` be restarted, not started and stopped. For details, see [Pulp #2835](#).) This should cause the first sync to abort.
4. Update the repository. Let its feed reference a small repository. (For example, `pulp_smash.constants.RPM_UNSIGNED_FEED_URL`.)
5. Start a sync. Verify that it completes. If [Pulp #2835](#) still affects Pulp, then the worker will be broken, and the sync will never start.

**setUp()**  
Ensure there is only one Pulp worker.

**tearDown()**  
Reset the number of Pulp workers, and reset Pulp.  
Reset Pulp because `test_all()` may break Pulp.

**test\_all()**  
Test that Pulp deals well with missing workers.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_service_resiliency.TaskDispatchTestCase` (*method*)  
Test whether `httpd` dispatches a task while the broker is down.

**test\_all()**  
Test whether `httpd` dispatches a task while the broker is down.

This test targets the following issues:

- [Pulp Smash #650](#)
- [Pulp #2770](#)

This test does the following:

1. Create a repository.
2. Stop the AMQP broker. (Also, schedule it to be re-started later!)
3. Sync the repository, ignore any errors that are returned when doing so, and assert that no tasks are left in the `waiting` state.

## 6.94 `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_copies`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_copies`

Tests for repository signature checks when copying packages.

This module mimics `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_uploads`, except that packages are primarily copied into repositories, instead of being uploaded.

---

**Note:** Pulp's signature checking logic is subtle. Please read `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_uploads`.

---

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_copies.AllowAnyKeyTest`  
 Use an importer that allows unsigned packages and has no key IDs.

The importer should have the following pseudocode configuration:

```
{"require_signature": false, "allowed_keys": []}
```

**test\_signed\_packages** ()  
 Copy signed packages into a repository.  
 Assert packages are copied in.

**test\_unsigned\_packages** ()  
 Copy unsigned packages into a repository.  
 Assert packages are copied in.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_copies.AllowInvalidKeyTest`  
 Use an importer that allows unsigned packages and has an invalid key ID.

The importer should have the following pseudocode configuration:

```
{"require_signature": false, "allowed_keys": ["invalid key id"]}
```

**test\_signed\_packages** ()  
 Copy signed packages into a repository.  
 Assert no packages are copied in.

**test\_unsigned\_packages** ()  
 Copy unsigned packages into a repository.  
 Assert packages are copied in.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_copies.AllowValidKeyTest`  
 Use an importer that allows unsigned packages and has a valid key ID.

The importer should have the following pseudocode configuration:

```
{"require_signature": false, "allowed_keys": ["valid key id"]}
```

---

**Note:** Pulp's signature checking logic is subtle. Please read `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_uploads`.

---

**test\_signed\_packages** ()  
 Copy signed packages into a repository.  
 Assert packages are copied in.

**test\_unsigned\_packages** ()  
 Copy unsigned packages into a repository.  
 Assert packages are copied in.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_copies.RequireAnyKeyTest`  
 Use an importer that requires signatures and has no key IDs.

The importer should have the following pseudocode configuration:

```
{"require_signature": true, "allowed_keys": []}
```

**test\_signed\_packages ()**  
Copy signed packages into a repository.  
Assert packages are copied in.

**test\_unsigned\_packages ()**  
Copy unsigned packages into a repository.  
Assert no packages are copied in.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_copies.RequireInvalidKey`  
Use an importer that requires signatures and has an invalid key ID.

The importer should have the following pseudocode configuration:

```
{"require_signature": true, "allowed_keys": ["invalid key id"]}
```

**test\_signed\_packages ()**  
Copy signed packages into a repository.  
Assert no packages are copied in.

**test\_unsigned\_packages ()**  
Copy unsigned packages into a repository.  
Assert no packages are copied in.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_copies.RequireValidKey`  
Use an importer that requires signatures and has a valid key ID.

The importer should have the following pseudocode configuration:

```
{"require_signature": true, "allowed_keys": ["valid key id"]}
```

**test\_signed\_packages ()**  
Copy signed packages into a repository.  
Assert packages are copied in.

**test\_unsigned\_packages ()**  
Copy unsigned packages into a repository.  
Assert no packages are copied in.

`pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_copies.setUpModule ()`  
Conditionally skip tests. Create repositories with fixture data.

`pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_copies.tearDownModule ()`  
Delete repositories with fixture data.

## 6.95 *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_checked\_for\_syncs*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_checked\_for\_syncs*

Tests for repository signature checks when syncing packages.

This module mimics *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_checked\_for\_uploads*, except that packages are synced in to Pulp instead of being uploaded.

---

**Note:** Pulp's signature checking logic is subtle. Please read `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_uploads`.

---

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_syncs.AllowAnyKeyTestC`

Use an importer that allows unsigned packages and has no key IDs.

The importer should have the following pseudocode configuration:

```
{"require_signature": false, "allowed_keys": []}
```

**test\_signed\_drpm()**

Sync signed DRPMs into the repository.

Assert packages are synced in.

**test\_signed\_rpm()**

Sync signed RPMs into the repository.

Assert packages are synced in.

**test\_signed\_srpm()**

Sync signed SRPMs into the repository.

Assert packages are synced in.

**test\_unsigned\_drpms()**

Import unsigned DRPMs into a repository.

Verify packages are synced.

**test\_unsigned\_rpms()**

Import unsigned RPMs into a repository.

Verify packages are synced.

**test\_unsigned\_srpm()**

Import unsigned SRPMs into a repository.

Verify packages are synced.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_syncs.AllowInvalidKeyT`

Use an importer that allows unsigned packages and has an invalid key ID.

The importer should have the following pseudocode configuration:

```
{"require_signature": false, "allowed_keys": ["invalid key id"]}
```

**test\_signed\_packages()**

Import signed RPMs, DRPMs and SRPMs into repositories.

Assert no packages are synced.

**test\_unsigned\_drpms()**

Import unsigned DRPMs into a repository.

Assert packages are synced.

**test\_unsigned\_rpms()**

Import unsigned RPMs into a repository.

Assert packages are synced.

**test\_unsigned\_srpms ()**  
Import unsigned SRPMs into a repository.  
Assert packages are synced.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_syncs.AllowValidKeyTest`  
Use an importer that allows unsigned packages and has a valid key ID.

The importer should have the following pseudocode configuration:

```
{"require_signature": false, "allowed_keys": ["valid key id"]}
```

---

**Note:** Pulp's signature checking logic is subtle. Please read `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_uploads`.

---

**test\_signed\_drpm ()**  
Sync signed DRPMs into the repository.  
Assert packages are synced in.

**test\_signed\_rpm ()**  
Sync signed RPMs into the repository.  
Assert packages are synced in.

**test\_signed\_srpm ()**  
Sync signed SRPMs into the repository.  
Assert packages are synced in.

**test\_unsigned\_drpms ()**  
Import unsigned DRPMs into a repository.  
Assert packages are synced.

**test\_unsigned\_rpms ()**  
Import unsigned RPMs into a repository.  
Assert packages are synced.

**test\_unsigned\_srpms ()**  
Import unsigned SRPMs into a repository.  
Assert packages are synced.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_syncs.RequireAnyKeyTest`  
Use an importer that requires signatures and has no key IDs.

The importer should have the following pseudocode configuration:

```
{"require_signature": true, "allowed_keys": []}
```

**test\_signed\_drpm ()**  
Sync signed DRPMs into the repository.  
Assert packages are synced in.

**test\_signed\_rpm ()**  
Sync signed RPMs into the repository.  
Assert packages are synced in.

**test\_signed\_srpm()**  
 Sync signed SRPMs into the repository.  
 Assert packages are synced in.

**test\_unsigned\_packages()**  
 Sync unsigned RPMs, DRPMS and SRPMS into repositories.  
 Assert no packages are synced in.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_syncs.RequireInvalidKeyT`  
 Use an importer that requires signatures and has an invalid key ID.

The importer should have the following pseudocode configuration:

```
{"require_signature": true, "allowed_keys": ["invalid key id"]}
```

**test\_packages()**  
 Sync signed and unsigned RPMs, DRPMS and SRPMs into repositories.  
 Assert no packages are synced in.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_syncs.RequireValidKeyT`  
 Use an importer that requires signatures and has a valid key ID.

The importer should have the following pseudocode configuration:

```
{"require_signature": true, "allowed_keys": ["valid key id"]}
```

**test\_signed\_drpm()**  
 Sync signed DRPMS into the repository.  
 Assert packages are synced in.

**test\_signed\_rpm()**  
 Sync signed RPMs into the repository.  
 Assert packages are synced in.

**test\_signed\_srpm()**  
 Sync signed SRPMs into the repository.  
 Assert packages are synced in.

**test\_unsigned\_packages()**  
 Sync unsigned RPMs, DRPMS and SRPMS into repositories.  
 Assert no packages are synced in.

`pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_syncs.setUpModule()`  
 Conditionally skip tests.

`pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_syncs.tearDownModule()`  
 Delete orphan content units.

## 6.96 `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_uploads`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_uploads`

Tests for repository importer signature checks.

As of Pulp 2.10, it's possible to configure an RPM repository importer to perform checks on all synced-in and uploaded packages. Two new importer options are available:

**require\_signature** A boolean. If true, imported packages must be signed with a key listed in `allowed_keys`.

**allowed\_keys** A list of 32-bit key IDs, as hex characters. (e.g. `["deadbeef"]`) An empty list is treated as the list of all possible key IDs.

Beware that if a package has a signature, its signature *must* be listed in `allowed_keys`, even when `require_signature` is false. The only importer configuration that allows all packages is `{'require_signature': False, 'allowed_keys': []}`.

To test this feature, importers with at least the following options should be created:

```
{'require_signature': False, 'allowed_keys': ['invalid key id']}
{'require_signature': False, 'allowed_keys': ['valid key id']}
{'require_signature': False, 'allowed_keys': []}
{'require_signature': True, 'allowed_keys': ['invalid key id']}
{'require_signature': True, 'allowed_keys': ['valid key id']}
{'require_signature': True, 'allowed_keys': []}
```

In addition, at least the following types of packages should be imported:

```
* Signed DRPMS
* Signed RPMS
* Signed SRPMS
* Unsigned DRPMS
* Unsigned RPMS
* Unsigned SRPMS
```

Finally, importer options may be changed in some circumstances, and Pulp should gracefully handle those changes.

For more information, see [Pulp #1991](#) and [Pulp Smash #347](#).

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_uploads.AllowAnyKeyTest`

Use an importer that allows unsigned packages and has no key IDs.

The importer should have the following pseudocode configuration:

```
{"require_signature": false, "allowed_keys": []}
```

**classmethod** `setUpClass()`

Create a repository with an importer.

**test\_all\_packages()**

Import signed and unsigned DRPM, RPM & SRPM packages into the repo.

Verify that each import succeeds.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_uploads.AllowInvalidKey`

Use an importer that allows unsigned packages and has an invalid key ID.

The importer should have the following pseudocode configuration:

```
{"require_signature": false, "allowed_keys": ["invalid key id"]}
```

**classmethod** `setUpClass()`

Create a repository with an importer.

**test\_signed\_packages()**

Import signed DRPM, RPM and SRPM packages into the repository.

Verify that each import fails.



**test\_unsigned\_packages ()**

Import unsigned DRPM, RPM and SRPM packages into the repository.

Verify that each import succeeds.

**class pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_checked\_for\_uploads.AllowValidKeyT**

Use an importer that allows unsigned packages and has a valid key ID.

The importer should have the following pseudocode configuration:

```
{"require_signature": false, "allowed_keys": ["valid key id"]}
```

**classmethod setUpClass ()**

Create a repository with an importer.

**test\_all\_packages ()**

Import signed and unsigned DRPM, RPM & SRPM packages into the repo.

Verify that each import succeeds.

**class pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_checked\_for\_uploads.KeyLengthTestC**

Verify pulp rejects key IDs that are not 32-bits long.

An OpenPGP-compatible key ID (key fingerprint) is traditionally a 32-bit value. Newer OpenPGP key handling software allows for longer key IDs, and this is recommended, as it's extremely easy to find colliding key IDs.<sup>1</sup> However, Pulp allows only the short key IDs.

**test\_key\_ids ()**

Create importers with key IDs shorter and longer than 32 bits.

Pulp should prevent the importers from being created.

**class pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_checked\_for\_uploads.RequireAnyKeyT**

Use an importer that requires signatures and has no key IDs.

The importer should have the following pseudocode configuration:

```
{"require_signature": true, "allowed_keys": []}
```

**classmethod setUpClass ()**

Create a repository with an importer.

**test\_signed\_packages ()**

Import signed DRPM, RPM and SRPM packages into the repo.

Verify that each import succeeds.

**test\_unsigned\_packages ()**

Import unsigned DRPM, RPM and SRPM packages into the repo.

Verify that each import fails.

**class pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_checked\_for\_uploads.RequireInvalidID**

Use an importer that requires signatures and has an invalid key ID.

The importer should have the following pseudocode configuration:

```
{"require_signature": true, "allowed_keys": ["invalid key id"]}
```

**classmethod setUpClass ()**

Create a repository with an importer.

<sup>1</sup> <https://evil32.com/>

**test\_all\_packages** ()

Import signed and unsigned DRPM, RPM & SRPM packages into the repo.

Verify that each import fails.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_uploads.RequireValidKey`  
Use an importer that requires signatures and has a valid key ID.

The importer should have the following pseudocode configuration:

```
{"require_signature": true, "allowed_keys": ["valid key id"]}
```

**classmethod** `setUpClass` ()

Create a repository with an importer.

**test\_signed\_packages** ()

Import signed DRPM, RPM and SRPM packages into the repository.

Verify that each import succeeds.

**test\_unsigned\_packages** ()

Import unsigned DRPM, RPM and SRPM packages into the repository.

Verify that each import fails.

`pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_uploads.setUpModule` ()  
Conditionally skip tests. Cache packages to be uploaded to repos.

Skip the tests in this module if:

- The RPM plugin is unsupported.
- [Pulp #1991](#) is untestable for the version of Pulp under test.

`pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_uploads.tearDownModule` ()  
Delete the cached set of packages to be uploaded to repos.

## 6.97 `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_saved_for_packages`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_saved_for_packages`

Tests for how well Pulp can deal with package signatures.

When a package is added to an RPM repository, its signature should be stored by Pulp. This is true regardless of whether the package is an RPM, DRPM or SRPM.

Tests for this feature include the following:

- Upload signed and unsigned packages to RPM repositories. (See [UploadPackageTestCase](#).)
- Synchronize signed and unsigned packages to RPM repositories. (See [SyncPackageTestCase](#).)

For more information, see:

- [Pulp #1156](#)

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_saved_for_packages.SyncPackageTest`  
Test if Pulp saves signatures from synced-in packages.

**test\_signed\_drpm** ()

Assert signature is stored for signed drpm during sync.

**test\_signed\_rpm** ()

Assert signature is stored for signed rpm during sync.

**test\_signed\_srpm()**  
Assert signature is stored for signed srpm during sync.

**test\_unsigned\_drpm()**  
Assert no signature is stored for unsigned drpm during sync.

**test\_unsigned\_rpm()**  
Assert no signature is stored for unsigned rpm during sync.

**test\_unsigned\_srpm()**  
Assert no signature is stored for unsigned srpm during sync.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_saved_for_packages.UploadPackageTest`  
Test if Pulp saves signatures from uploaded packages.

**test\_signed\_drpm()**  
Import a signed DRPM into Pulp. Verify its signature.

**test\_signed\_rpm()**  
Import a signed RPM into Pulp. Verify its signature.

**test\_signed\_srpm()**  
Import a signed SRPM into Pulp. Verify its signature.

**test\_unsigned\_drpm()**  
Import an unsigned DRPM into Pulp. Verify it has no signature.

**test\_unsigned\_rpm()**  
Import an unsigned RPM into Pulp. Verify it has no signature.

**test\_unsigned\_srpm()**  
Import an unsigned SRPM into Pulp. Verify it has no signature.

## 6.98 `pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish`

Tests that sync and publish RPM repositories.

For information on repository sync and publish operations, see [Synchronization and Publication](#).

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish.ChangeFeedTestCase` (*methodName='runTest'*)  
Sync a repository, change its feed, and sync it again.

Specifically, the test case procedure is as follows:

1. Create three repositories — call them A, B and C.
2. Populate repository A and B with identical content, and publish them.
3. Set C's feed to repository A. Sync and publish repository C.
4. Set C's feed to repository B. Sync and publish repository C.
5. Download an RPM from repository C.

The entire procedure should succeed. This test case targets [Pulp #1922](#).

**create\_sync\_publish\_repo** (*body*)  
Create, sync and publish a repository.

Also, schedule the repository for deletion.

**Parameters** `body` – A dict of information to use when creating the repository.

**Returns** A detailed dict of information about the repository.

**get\_feed** (*repo*)

Build the feed to an RPM repository's distributor.

**test\_all** ()

Sync a repository, change its feed, and sync it again.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish.ErrorReportTestCase` (*methodName='run'*)  
Test whether an error report contains sufficient information.

**test\_all** ()

Test whether an error report contains sufficient information.

Do the following:

1. Create and sync a repository using an invalid feed URL.
2. Get a reference to the task containing error information.
3. Assert that:
  - The error description is sufficiently verbose. See [Pulp #1376](#) and [Pulp Smash #525](#).
  - The traceback is non-null. See [Pulp #1455](#).

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish.NonExistentRepoTestCase` (*methodName='run'*)  
Perform actions on non-existent repositories.

This test targets [Pulp Smash #157](#).

**setUp** ()

Set variables used by each test case.

**test\_publish** ()

Publish a non-existent repository.

**test\_sync** ()

Sync a non-existent repository.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish.SyncDrpmRepoTestCase` (*methodName='run'*)  
Test one can create and sync an RPM repository with an DRPM feed.

**static get\_feed\_url** ()

Return an DRPM repository feed URL.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish.SyncInParallelTestCase` (*methodName='run'*)  
Sync several repositories in parallel.

**test\_all** ()

Sync several repositories in parallel.

Specifically, do the following:

1. Create several repositories. Ensure each repository has an importer whose feed references a repository containing one or more errata.
2. Sync each repository. Assert each sync completed successfully.
3. Get a summary of information about each repository, and assert the repo has an appropriate number of errata.

[Pulp #2721](#) describes how a race condition can occur when multiple repos with identical errata are synced at the same time. This test case attempts to trigger that race condition.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish.SyncInvalidMetadataTestCase` (*method*)  
 Sync various repositories with invalid metadata.

When a repository with invalid metadata is encountered, Pulp should gracefully fail. This test case targets [Pulp #1287](#).

**do\_test** (*feed\_url*)  
 Implement the logic described by each of the `test*` methods.

**classmethod** `tearDownClass` ()  
 Delete orphan content units.

**test\_incomplete\_filelists** ()  
 Sync a repository with an incomplete `filelists.xml` file.

**test\_incomplete\_other** ()  
 Sync a repository with an incomplete `other.xml` file.

**test\_missing\_filelists** ()  
 Sync a repository that's missing its `filelists.xml` file.

**test\_missing\_other** ()  
 Sync a repository that's missing its `other.xml` file.

**test\_missing\_primary** ()  
 Sync a repository that's missing its `primary.xml` file.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish.SyncRepoBaseTestCase` (*methodName='run'*)  
 A parent class for repository synchronization test cases.

`get_feed_url()` should be overridden by concrete child classes. This method's response is used when setting the repository's importer feed URL.

**static** `get_feed_url` ()  
 Return an RPM repository feed URL. Should be overridden.

**Raises** `NotImplementedError` if not overridden by a child class.

**classmethod** `setUpClass` ()  
 Create an RPM repository with a valid feed and sync it.

**test\_start\_sync\_code** ()  
 Assert the call to sync a repository returns an HTTP 202.

**test\_task\_progress\_report** ()  
 Assert no task's progress report contains error details.

Other assertions about the final state of each task are handled by the client's response handler. (For more information, see the source of `pulp_smash.api.safe_handler()`.)

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish.SyncRpmRepoTestCase` (*methodName='run'*)  
 Test one can create and sync an RPM repository with an RPM feed.

**static** `get_feed_url` ()  
 Return an RPM repository feed URL.

**test\_no\_change\_in\_second\_sync** ()  
 Verify that syncing a second time has no changes.

If the repository have not changed then Pulp must state that anything was changed when doing a second sync.

**test\_unit\_count\_on\_repo** ()  
 Verify that the sync added the correct number of units to the repo.

Read the repository and examine its `content_unit_counts` attribute. Compare these attributes to metadata from the remote repository. Expected values are currently hard-coded into this test.

```
class pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish.SyncSrpmRepoTestCase (methodName='runTest')
    Test one can create and sync an RPM repository with an SRPM feed.

    static get_feed_url ()
        Return an SRPM repository feed URL.
```

## 6.99 *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_tasks*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_tasks*

Verify that operations can be performed over Tasks.

For information on tasks operations, see [REST API Task Management and Admin Client Tasks](#).

```
class pulp_smash.tests.pulp2.rpm.api_v2.test_tasks.TasksOperationsTestCase (methodName='runTest')
    Perform different operations over tasks.
```

This test targets the following issues:

- Pulp Smash #108
- Pulp Smash #142
- Pulp issue #1418
- Pulp issue #1483
- Pulp issue #1664

```
test_all ()
    Perform different operation over tasks.
```

Do the following:

1. Create, sync and publish a repository.
2. List current tasks.
3. Search tasks.
4. Polling a specific task progress.
5. Delete finished tasks.
6. Purge tasks.

## 6.100 *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_unassociate*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.test\_unassociate*

Test Unassociating Content Units from a Repository for RPM.

```
class pulp_smash.tests.pulp2.rpm.api_v2.test_unassociate.RemoveUnitsTestCase (methodName='runTest')
    Remove units of various types from a synced repository.
```

```
do_remove_unit (type_id, repo)
    Remove a content unit from the repository.
```

Do the following:

1. Note the repository's `last_unit_removed` field.
2. Sleep for at least one second.
3. Remove a unit of type `type_id` from the repository.
4. Note the repository's `last_unit_removed` field.

When the first unit is removed, assert that `last_unit_removed` changes from null to a non-null value. When each subsequent unit is removed, assert that `last_unit_removed` increments.

**do\_test** (*feed, type\_ids*)

Remove units from a repo and make assertions about it.

Do the following:

1. Create and sync a repository with the given *feed*.
2. For each type ID in *type\_ids*, remove a content unit of that type from the repository. See `do_remove_unit()`.
3. Assert the correct units are still in the repository. The repository should have all the units that were originally synced into the repository, minus those that have been removed.
4. Remove a non-existent unit from the repository. Assert that the `last_unit_removed` timestamp was not updated.

**get\_repo\_last\_unit\_removed** (*repo*)

Get the repository's `last_unit_removed` attribute.

**setUp** ()

Set variables used by each test case.

**test\_drpm** ()

Un-associate units from a DRPM repo. See `do_test()`.

**test\_rpm** ()

Un-associate units from a RPM repo. See `do_test()`.

**test\_srpm** ()

Un-associate units from a SRPM repo. See `do_test()`.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_unassociate.RepublishTestCase` (*methodName='runTest*  
Repeatedly publish a repository, with different content each time.

Specifically, do the following:

1. Create a repository.
2. Add a content unit to the repository. Publish the repository.
3. Unassociate the content unit and repository. Publish the repository.

Verify that:

- The `last_unit_added`, `last_unit_removed` and `last_publish` timestamps are correct.
- The content unit in question is only available when associated with the repository.

**get\_repo** ()

Get detailed information about the repository.

**classmethod setUpClass** ()

Create a repository.

**classmethod tearDownClass** ()

Remove the created repository and any orphans.

**test\_01\_add\_unit** ()

Add a content unit to the repository. Publish the repository.

**test\_02\_find\_unit** ()

Search for the content unit. Assert it is available.

**test\_03\_unassociate\_unit** ()

Unassociate the unit from the repository. Publish the repository.

**test\_04\_find\_unit** ()

Search for the content unit. Assert it isn't available.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_unassociate.SelectiveAssociateTestCase` (*methodN*)  
Ensure Pulp only associate needed content.

Test steps:

1. Create and sync an RPM repository.
2. Unassociate some RPMs from the repository created on the previous step.
3. Sync the repository again and check if only the missing units were associated.

See [Pulp #2457](#)

**test\_all** ()

Check if Pulp only associate missing repo content.

`pulp_smash.tests.pulp2.rpm.api_v2.test_unassociate.setUpModule` ()  
Maybe skip this module of tests.

## 6.101 `pulp_smash.tests.pulp2.rpm.api_v2.test_unavailable_checksum`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_unavailable_checksum`

Tests that publish repositories with unavailable checksum types.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_unavailable_checksum.UnavailableChecksumTestC`  
Publish a lazily-synced repository with unavailable checksum types.

**do\_test** (*feed, type\_id*)

Publish a repository with an invalid checksum.

Do the following:

1. Create and sync repository of type `type_id` and with the given feed. Ensure the repository's importer has a deferred/lazy download policy.
2. Determine which checksum type the units in the repository use. (As of this writing, Pulp can handle md5, sha1 and sha256 checksum types.)
3. Publish the repository with checksum types different from what the units in the repository use. Assert the publish fails.

This test targets [Pulp Smash #287](#).

**test\_drpm** ()

Publish a DRPM repo. See `do_test` ().

**test\_rpm** ()

Publish a RPM repo. See `do_test` ().



**test\_srpm()**

Publish a SRPM repo. See *do\_test()*.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_unavailable_checksum.UpdatedChecksumTestCase` (*n*)

Ensure that the updated `checksum_type` is present on the repo metadata.

Do the following:

1. Create, sync and publish a repository with checksum type “sha256”.
2. After that several XML files - part of repodata will be inspected.
  - primary.xml** Assert that the given checksum type is the only one present.
  - filelists.xml and other.xml** Assert that the length of `pkgid` is according to the given checksum type.
  - prestodelta.xml** Assert that the given checksum type is the only one present.

For `sha256` the length of `pkgid` should be 64 hex digits, and for `sha1` the length should be 40 hex digits. For DRPM repositories the `prestodelta.xml` will be inspected as well.
3. Update the checksum type to “sha1”, and use option `force_full` set as `True`. `force_full` will force a complete re-publish to happen. Re-publish the repository.
4. All aforementioned assertions performed on the step 2 will be executed again to assure that new checksum type was updating properly.

This test targets [Pulp Smash #286](#).

**do\_test** (*feed*)

Verify `checksum_type` is updated on the repo metadata.

**test\_drpm()**

Verify updated checksum in a DRPM repo. See *do\_test()*.

**test\_rpm()**

Verify update checksum in a RPM repo. See *do\_test()*.

**test\_srpm()**

Verify updated checksum in a SRPM repo. See *do\_test()*.

**verify\_filelists\_xml** (*cfg, distributor, checksum\_type*)

Verify a published repo’s `filelists.xml` uses the given checksum.

**verify\_other\_xml** (*cfg, distributor, checksum\_type*)

Verify a published repo’s `other.xml` uses the given checksum.

**verify\_pkgid\_len** (*pkgid\_len, checksum\_type*)

Perform assertion based on the given checksum type.

Based on the checksum type provided different assertions will be performed over the length of `pkgid`.

**verify\_presto\_delta\_xml** (*cfg, distributor, checksum\_type*)

Verify a published repo’s `prestodelta.xml` uses given checksum.

**verify\_primary\_xml** (*cfg, distributor, checksum\_type*)

Verify a published repo’s `primary.xml` uses the given checksum.

## 6.102 `pulp_smash.tests.pulp2.rpm.api_v2.test_updateinfo`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_updateinfo`

Test the `updateinfo.xml` files published by Pulp's yum distributor.

The purpose of an `updateinfo.xml` file is to document the errata (i.e. maintenance patches) provided by a repository. For an overview of the structure and contents of such a file, see [openSUSE:Standards Rpm Metadata UpdateInfo](#). Beware that yum and dnf do not adhere to the openSUSE standards. We link to their standard anyway because it's easier to understand than yum or dnf's source code. (!)

One discrepancy is in the schema for the `<pkglist>` element. According to the yum source code, it has the following structure:

```
<!ELEMENT pkglist (collection+)>
<!ELEMENT collection (name?, package+)>
  <!ATTLIST collection short CDATA #IMPLIED>
  <!ATTLIST collection name CDATA #IMPLIED>
<!ELEMENT name (#PCDATA)>
```

Here's a concrete example of what that might look like:

```
<pkglist>
  <collection name="..." short="...">
    <name>...</name>
    <package>...</package>
    <package>...</package>
  </collection>
</pkglist>
```

yum (and, therefore, dnf) allows a `<collection>` element to have "name" and "short" attributes. openSUSE does not.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_updateinfo.CleanUpTestCase` (*methodName='runTest'*)  
Test whether old `updateinfo.xml` files are cleaned up.

Do the following:

1. Create, populate and publish a repository. Verify that an `updateinfo.xml` file is present and can be downloaded.
2. Add an additional content unit to the repository, and publish it again. Verify that the `updateinfo.xml` file created by the first publish is no longer available, and that a new `updateinfo.xml` file is available.

This procedure targets [Pulp #2096](#). Note that the second publish must be an incremental publish.

**get\_updateinfo\_xml\_href** ()  
Return the path to the `updateinfo.xml` file.

**classmethod setUpClass** ()  
Create and sync a repository.

**classmethod tearDownClass** ()  
Remove the created repository and any orphans.

**test\_01\_first\_publish** ()  
Populate and publish the repository.

**test\_02\_second\_publish** ()  
Add an additional content unit and publish the repository again.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_updateinfo.OpenSuseErrataTestCase` (*methodName='runTest'*)  
Test Pulp's handling of openSUSE errata.

Do the following:

1. Create, sync and publish a repository. Let its feed URL reference `pulp_smash.constants.OPENSUSE_FEED_URL`. Also, let it have an “on demand” download policy, so that time isn’t spent syncing a potentially large amount of data.
2. Download the published errata, and make it available to the remaining test methods.

This test targets:

- Pulp #3377
- Pulp Smash #904

**Warning:** This test is extremely slow, due to the heavy single-threaded workload incurred by parsing a large production-grade repository’s metadata.

**classmethod setUpClass()**

Create class-wide variables.

**test\_01\_create\_sync\_publish()**

Create, sync, and publish an openSUSE repository.

**test\_02\_relogin\_suggested()**

Assert `relogin_suggested` element are present.

**test\_02\_restart\_suggested()**

Assert `restart_suggested` element are present.

**test\_02\_update\_issued\_dates()**

Assert ‘date’ attributes are formatted as seconds since epoch.

For each element matching XPath `/updates/update/issued`, verify that its date attribute looks like seconds since the epoch.

**test\_02\_updated()**

Assert `<updated>` elements are absent.

Assert that no elements match XPath `/updates/update/updated`.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_updateinfo.PkglistsTestCase` (*methodName='runTest'*)  
Sync a repository whose updateinfo file has multiple pkglist sections.

This test case targets Pulp #2227.

**test\_all()**

Sync a repo whose updateinfo file has multiple pkglist sections.

Specifically, do the following:

1. Create, sync and publish an RPM repository whose feed is set to `pulp_smash.constants.RPM_PKGLISTS_UPDATEINFO_FEED_URL`.
2. Fetch and parse the published repository’s `updateinfo.xml` file.

Verify that the `updateinfo.xml` file has three packages whose `<filename>` elements have the following text:

- penguin-0.9.1-1.noarch.rpm
- shark-0.1-1.noarch.rpm
- walrus-5.21-1.noarch.rpm

Note that Pulp is free to change the structure of a source repository at will. For example, the source repository has three `<collection>` elements, the published repository can have one, two or three `<collection>` elements. Assertions are not made about these details.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_updateinfo.UpdateInfoTestCase` (*methodName='runTest'*)  
Tests to ensure `updateinfo.xml` can be created and is valid.

**classmethod** `setUpClass` ()

Create, populate and publish a repository.

More specifically, do the following:

1. Create an RPM repository with a distributor.
2. Populate the repository with an RPM and two errata, where one erratum references the RPM, and the other does not.
3. Publish the repository Fetch and parse its `updateinfo.xml` file.

**test\_erratum** ()

Assert the erratum generated by Pulp is correct.

Walk through each top-level element of the erratum which was generated during this test case's set-up and uploaded to Pulp. For each element, verify that the `updateinfo.xml` file generated by Pulp has a corresponding entry. Each of the `verify_*` methods on this test case implement the test logic for a single element.

**test\_one\_task\_per\_import** ()

Assert only one task is spawned per erratum upload.

**test\_reboot\_not\_suggested** ()

Assert the update info tree does not suggest a spurious reboot.

The errata uploaded by this test case do not suggest that a reboot be applied. As a result, the relevant `<update>` element in the `updateinfo.xml` file should not have a `<reboot_suggested>` tag. Verify that this is so. See [Pulp #2032](#).

---

**Note:** In previous versions of Pulp, if no reboot should be applied, a `<reboot_suggested>False</reboot_suggested>` element would be present. See [Pulp #1782](#).

---

**test\_tasks\_result** ()

Assert each task's result success flag (if present) is true.

This test assumes `test_one_task_per_import ()` passes.

**test\_tasks\_state** ()

Assert each task's state is "finished".

This test assumes `test_one_task_per_import ()` passes.

**test\_update\_elements** ()

Assert there is one "update" element in `updateinfo.xml`.

**test\_updates\_element** ()

Assert `updateinfo.xml` has a root element named `updates`.

**verify\_description** (*erratum, update\_element*)

Verify `erratum` and `update_element` have same description.

**verify\_id** (*erratum, update\_element*)

Verify `erratum` and `update_element` have the same id.

**verify\_issued** (*erratum, update\_element*)  
Verify *erratum* and *update\_element* have the same issued.

**verify\_pkglist** (*erratum, update\_element*)  
Verify *erratum* and *update\_element* have the same pkglist.

**verify\_references** (*erratum, update\_element*)  
Verify *erratum* and *update\_element* have same references.

**verify\_solution** (*erratum, update\_element*)  
Verify *erratum* and *update\_element* have the same solution.

**verify\_status** (*erratum, update\_element*)  
Verify *erratum* and *update\_element* have the same status.

**verify\_title** (*erratum, update\_element*)  
Verify *erratum* and *update\_element* have the same title.

**verify\_type** (*erratum, update\_element*)  
Verify *erratum* and *update\_element* have the same type.

**verify\_version** (*erratum, update\_element*)  
Verify *erratum* and *update\_element* have the same version.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_updateinfo.UpdateRepoTestCase` (*methodName='runTest'*)  
Verify `updateinfo.xml` changes as its repo changes.

**classmethod** `setUpClass` ()  
Create an RPM repository with a feed and distributor.

**test\_01\_sync\_publish** ()  
Sync and publish the repository.

When executed, this test method will fetch `updateinfo.xml` and verify that:

- An `<update>` with an `<id>` of `pulp_smash.constants.RPM_ERRATUM_ID` is present, and
- one of its child `<package>` elements has a “name” attribute equal to `pulp_smash.constants.RPM_ERRATUM_RPM_NAME`.

**test\_02\_unassociate\_publish** ()  
Unassociate a content unit and publish the repository.  
Fetch `updateinfo.xml`. Verify that an `<update>` with an `<id>` of `pulp_smash.constants.RPM_ERRATUM_ID` is not present.

`pulp_smash.tests.pulp2.rpm.api_v2.test_updateinfo.setUpModule` ()  
Possibly skip the tests in this module.

Skip tests if Pulp #2277 affects us.

## 6.103 `pulp_smash.tests.pulp2.rpm.api_v2.test_upload_publish`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.api_v2.test_upload_publish`

Tests that upload to and publish RPM repositories.

For information on repository upload and publish operations, see [Uploading Content and Publication](#).

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_upload_publish.UploadDrpmTestCase` (*methodName='runTest'*)  
Test whether one can upload a DRPM into a repository.

Specifically, this method does the following:

1. Create a yum repository.
2. Upload a DRPM into the repository.
3. Search for all content units in the repository.

This test case targets [Pulp Smash #336](#)

**test\_all()**

Import a DRPM into a repository and search it for content units.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_upload_publish.UploadDrpmTestCaseWithChecksum`  
Test whether one can upload a DRPM into a repository.

[Pulp issue #2627](#) caused uploading to fail when “checksumtype” was specified.

This test case targets [Pulp Smash #585](#)

**classmethod setUpClass()**

Import a DRPM into a repository and search it for content units.

Specifically, this method does the following:

1. Create a yum repository.
2. **Upload a DRPM into the repository with “checksumtype” set to “sha256”**
3. Search for all content units in the repository.

**test\_all()**

Test that uploading DRPM with checksumtype specified works.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_upload_publish.UploadInvalidRPMTTestCase` (*method*)  
Test that upload fails and error is raised when upload invalid RPM.

**test\_all()**

Test whether one invalid RPM upload fails and produces error details.

This test targets the following issues.

- [Pulp Smash #544](#)
- [Pulp #2543](#)
- [Pulp #3090](#)

Do the following:

1. Create a RPM repository.
2. Upload an invalid RPM to repository. Assert that upload fails, and that the returned error contains a descriptive message.
3. Verify that the repository contains no RPMs.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_upload_publish.UploadRpmTestCase` (*methodName='run'*)  
Test whether one can upload, associate and publish RPMs.

The test procedure is as follows:

1. Create a pair of repositories.
2. Upload an RPM to the first repository, and publish it.
3. Copy the RPM to the second repository, and publish it.

**classmethod setUpClass()**

Create a pair of RPM repositories.

**classmethod** `tearDownClass()`

Clean up resources created during the test.

**test\_01\_upload\_publish()**

Upload an RPM to the first repository, and publish it.

Execute `verify_repo_search()` and `verify_repo_download()`.

**test\_02\_copy\_publish()**

Copy and RPM from the first repo to the second, and publish it.

Execute `verify_repo_search()` and `verify_repo_download()`.

**test\_03\_compare\_repos()**

Verify the two repositories contain the same content unit.

**verify\_repo\_download(repo)**

Download `pulp_smash.constants.RPM` from the given `repo`.

Verify that it is exactly equal to the one uploaded earlier.

**verify\_repo\_search(repo)**

Search for units in the given `repo`.

Verify that only one content unit is in `repo`, and that several of its metadata attributes are correct. This test targets [Pulp #2365](#) and [Pulp #2754](#)

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_upload_publish.UploadSrpmTestCase` (*methodName='runTest'*)  
Test whether one can upload a SRPM into a repository.

This test case targets [Pulp Smash #402](#)

**classmethod** `setUpClass()`

Import a SRPM into a repository and search it for content units.

Specifically, this method does the following:

1. Create a yum repository.
2. Upload a SRPM into the repository.
3. Search for all content units in the repository.

**test\_srpm\_file\_name\_is\_correct()**

Test if SRPM extracted correct metadata for creating filename.

**test\_srpm\_uploaded\_successfully()**

Test if SRPM has been uploaded successfully.

**test\_status\_code\_units()**

Verify the HTTP status code for repo units response.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_upload_publish.UploadedDrpmChecksumTypeTestCase`  
Verify uploaded DRPMs have checksums of the requested type.

**test\_all()**

Verify uploaded DRPMs have checksums of the requested type.

Specifically, this method does the following:

1. Create a yum repository.
2. Upload a DRPM into the repository with “checksumtype” set to “md5”.
3. Assert that “checksumtype” was set to “md5”.
4. Assert that checksum value was calculated according to “md5”.

This test targets:

- [Pulp #2774](#)
- [Pulp Smash #663](#)

**class** `pulp_smash.tests.pulp2.rpm.api_v2.test_upload_publish.VendorInfoTestCase` (*methodName='runTest'*)  
 Test whether the vendor info is present in case of sync and upload.

This tests case targets the following issues:

- [Pulp Smash #680](#)
- [Pulp #2781](#)

**do\_test** (*repo*)  
 Verify that the given `repo` has an RPM with vendor data.

Perform the following checks:

- Search `repo` for RPMs and filter with a valid unit license. Assert that one search result is returned, and that it has vendor metadata.
- Search `repo` for RPMs and filter with a valid unit vendor. Assert that one search result is returned, and that it has vendor metadata.
- Search `repo` for RPMs and filter with an invalid unit license. Assert that no search results are returned.
- Search `repo` for RPMs and filter with an invalid unit vendor. Assert that no search results are returned.

The license-based searches serve as a sanity check. They show that the search syntax is correct.

**classmethod** `setUpClass` ()  
 Create class-wide variables.

**test\_sync** ()  
 Test whether Pulp recognizes a synced RPM's vendor information.

Create a repository, sync in an RPM with a non-null vendor, and perform several checks. See `do_test()`.

**test\_upload** ()  
 Test whether Pulp recognizes an uploaded RPM's vendor information.

Create a repository, upload an RPM with a non-null vendor, and perform several checks. See `do_test()`.

## 6.104 `pulp_smash.tests.pulp2.rpm.api_v2.utils`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.api\_v2.utils*

Utility functions for RPM API tests.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.utils.DisableSELinuxMixin`  
 A mixin providing the ability to temporarily disable SELinux.

**maybe\_disable\_selinux** (*cfg, pulp\_issue\_id*)  
 Disable SELinux if appropriate.

If the given Pulp issue is unresolved, and if SELinux is installed and enforcing on the target Pulp system, then disable SELinux and schedule it to be re-enabled. (Method `addCleanup` is used for the schedule.)

### Parameters



- **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about the Pulp deployment being targeted.
- **pulp\_issue\_id** – The (integer) ID of a [Pulp issue](#). If the referenced issue is fixed in the Pulp system under test, this method immediately returns.

**Returns** Nothing.

**class** `pulp_smash.tests.pulp2.rpm.api_v2.utils.TemporaryUserMixin`

A mixin providing the ability to create a temporary user.

A typical usage of this mixin is as follows:

```
ssh_user, priv_key = self.make_user(cfg)
ssh_identity_file = self.write_private_key(cfg, priv_key)
```

This mixin requires that the `unittest.TestCase` class from the standard library be a parent class.

**static delete\_user** (*cfg, username*)

Delete a user.

The Pulp rsync distributor has a habit of leaving (idle?) SSH sessions open even after publishing a repository. When executed, this function will:

1. Poll the process list until all processes belonging to `username` have died, or raise a `unittest.SkipTest` exception if the time limit is exceeded.
2. Delete `username`.

**make\_user** (*cfg*)

Create a user account with a home directory and an SSH keypair.

In addition, schedule the user for deletion with `self.addCleanup`.

**Parameters** **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about the host being targeted.

**Returns** A (`username, private_key`) tuple.

**write\_private\_key** (*cfg, private\_key*)

Write the given private key to a file on disk.

Ensure that the file is owned by user “apache” and has permissions of 600. In addition, schedule the key for deletion with `self.addCleanup`.

**Parameters** **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about the host being targeted.

**Returns** The path to the private key on disk, as a string.

`pulp_smash.tests.pulp2.rpm.api_v2.utils.gen_distributor()`

Return a semi-random dict for use in creating a YUM distributor.

`pulp_smash.tests.pulp2.rpm.api_v2.utils.gen_repo()`

Return a semi-random dict for use in creating an RPM repository.

`pulp_smash.tests.pulp2.rpm.api_v2.utils.gen_repo_group()`

Return a semi-random dict for use in creating a RPM repository group.

`pulp_smash.tests.pulp2.rpm.api_v2.utils.get_dists_by_type_id(cfg, repo)`

Return the named repository’s distributors, keyed by their type IDs.

**Parameters**

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about a Pulp host.

- **repo\_href** – A dict of information about a repository.

**Returns** A dict in the form `{'type_id': {distributor_info}}`.

```
pulp_smash.tests.pulp2.rpm.api_v2.utils.get_repodata(cfg, distributor, type_, response_handler=None, repomd_xml=None)
```

Download a file of the given `type_` from a `repodata/` directory.

#### Parameters

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about a Pulp host.
- **distributor** – A dict of information about a repository distributor.
- **type** – The type of file to fetch from a repository’s `repodata/` directory. Valid values might be “updateinfo” or “group”.
- **response\_handler** – The callback function used by `pulp_smash.api.Client` after downloading the `repomd.xml` file. Defaults to `xml_handler()`. Use `pulp_smash.api.safe_handler()` if you want the raw response.
- **repomd\_xml** – A `repomd.xml` file as an `ElementTree`. If not given, `get_repodata_repomd_xml()` is consulted.

**Returns** Whatever is dictated by `response_handler`.

```
pulp_smash.tests.pulp2.rpm.api_v2.utils.get_repodata_repomd_xml(cfg, distributor, response_handler=None)
```

Download the given repository’s `repodata/repomd.xml` file.

#### Parameters

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about a Pulp host.
- **distributor** – A dict of information about a repository distributor.
- **response\_handler** – The callback function used by `pulp_smash.api.Client` after downloading the `repomd.xml` file. Defaults to `xml_handler()`. Use `pulp_smash.api.safe_handler()` if you want the raw response.

**Returns** Whatever is dictated by `response_handler`.

```
pulp_smash.tests.pulp2.rpm.api_v2.utils.get_rpm_names_versions(cfg, repo)
```

Get a dict of a repository’s RPMs and their versions.

#### Parameters

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about a Pulp app.
- **repo** – A dict of information about a repository.

**Returns** The name and versions of each package in the repository, with the versions sorted in ascending order. For example: `{'walrus': ['0.71', '5.21']}`.

```
pulp_smash.tests.pulp2.rpm.api_v2.utils.get_unit(cfg, distributor, unit_name, primary_xml=None)
```

Download a file from a published repository.

A typical invocation is as follows:

```
>>> foo_rpm = get_unit(cfg, repo['distributors'][0], 'foo.rpm')
```

If multiple units are being fetched, efficiency can be improved by passing in a parsed `primary.xml` file:

```

>>> distributor = repo['distributors'][0]
>>> primary_xml = get_repodata(cfg, distributor, 'primary')
>>> foo_rpm = get_unit(cfg, distributor, 'foo.rpm', primary_xml)
>>> bar_rpm = get_unit(cfg, distributor, 'bar.rpm', primary_xml)

```

**Parameters**

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about a Pulp host.
- **distributor** – A dict of information about a repository distributor.
- **unit\_name** – The name of a content unit to be fetched. For example: “bear-4.1-1.noarch.rpm”.
- **primary\_xml** – A `primary.xml` file as an `ElementTree`. If not given, `get_repodata()` is consulted.

**Returns** A raw response. The unit is available as `response.content`.

`pulp_smash.tests.pulp2.rpm.api_v2.utils.set_pulp_manage_rsync(cfg, boolean)`  
Set the `pulp_manage_rsync` SELinux policy.

If the `setsebool` executable is not available, return. (This is the case if SELinux isn’t installed on the system under test.) Otherwise, set the `pulp_manage_rsync` SELinux policy on or off, depending on the truthiness of `boolean`.

For more information on the `pulp_manage_rsync` SELinux policy, see [ISO rsync Distributor → Configuration](#).

**Parameters**

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about a Pulp host.
- **boolean** – Either `True` or `False`.

**Returns** Information about the executed command, or `None` if no command was executed.

**Return type** `pulp_smash.cli.CompletedProcess`

`pulp_smash.tests.pulp2.rpm.api_v2.utils.xml_handler(_, response)`  
Decode a response as if it is XML.

This API response handler is useful for fetching XML files made available by an RPM repository. When it handles a response, it will check the status code of `response`, decompress the response if the request URL ended in `.gz`, and return an `xml.etree.Element` instance built from the response body.

Note:

- The entire response XML is loaded and parsed before returning, so this may be unsafe for use with large XML files.
- The `Content-Type` and `Content-Encoding` response headers are ignored due to <https://pulp.plan.io/issues/1781>.

## 6.105 `pulp_smash.tests.pulp2.rpm.cli`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.cli*

Tests that communicate with the server via the CLI.

## 6.106 *pulp\_smash.tests.pulp2.rpm.cli.test\_character\_encoding*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.cli.test\_character\_encoding*

Tests for Pulp’s character encoding handling.

RPM files have metadata embedded in their headers. This metadata should be encoded as utf-8, and Pulp should gracefully handle cases where invalid byte sequences are encountered.

**class** `pulp_smash.tests.pulp2.rpm.cli.test_character_encoding.UploadNonAsciiTestCase` (*methodName*)  
Test whether one can upload an RPM with non-ascii metadata.

Specifically, do the following:

1. Create an RPM repository.
2. Upload and import `pulp_smash.constants.RPM_WITH_NON_ASCII_URL` into the repository.

**test\_all** ()  
Test whether one can upload an RPM with non-ascii metadata.

**class** `pulp_smash.tests.pulp2.rpm.cli.test_character_encoding.UploadNonUtf8TestCase` (*methodName*)  
Test whether one can upload an RPM with non-utf-8 metadata.

Specifically, do the following:

1. Create an RPM repository.
2. Upload and import `pulp_smash.constants.RPM_WITH_NON_UTF_8_URL` into the repository.

This test case targets Pulp #1903.

**test\_all** ()  
Test whether one can upload an RPM with non-utf-8 metadata.

`pulp_smash.tests.pulp2.rpm.cli.test_character_encoding.setUpModule` ()  
Execute pulp-admin login.

## 6.107 *pulp\_smash.tests.pulp2.rpm.cli.test\_copy\_units*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.cli.test\_copy\_units*

Tests that copy units from one repository to another.

**class** `pulp_smash.tests.pulp2.rpm.cli.test_copy_units.CopyLangpacksTestCase` (*methodName*=’runTest’)  
Copy langpacks from one repository to another.

This test case verifies that it is possible to use the `pulp-admin rpm repo copy langpacks` command to copy langpacks from one repository to another. See Pulp Smash #255.

**test\_all** ()  
Copy langpacks from one repository to another.

Assert that:

- `pulp-admin` does not produce any errors.
- A non-zero number of langpacks are present in the target repository.

**class** `pulp_smash.tests.pulp2.rpm.cli.test_copy_units.CopyRecursiveTestCase` (*methodName*=’runTest’)  
Recursively copy a “chimpanzee” unit from one repository to another.

This test case verifies that it is possible to use the `pulp-admin rpm repo copy` command to recursively copy units from one repository to another. See [Pulp Smash #107](#).

**test\_all()**

Recursively copy a “chimpanzee” unit from one repository to another.

“chimpanzee” depends on “walrus,” and there are multiple versions of “walrus” in the source repository. Verify that one “walrus” unit has been copied to the target repository, and that the newer one has been copied.

**class** `pulp_smash.tests.pulp2.rpm.cli.test_copy_units.CopyTestCase` (*methodName='runTest'*)

Copy a “chimpanzee” unit from one repository to another.

This test case verifies that it is possible to use the `pulp-admin rpm repo copy` command to copy a single unit from one repository to another.

**test\_all()**

Copy a “chimpanzee” unit from one repository to another.

Verify that only the “chimpanzee” unit is in the target repository.

**class** `pulp_smash.tests.pulp2.rpm.cli.test_copy_units.UpdateRpmTestCase` (*methodName='runTest'*)

Update an RPM in a repository and on a host.

Do the following:

1. Create two repositories. Populate the first, and leave the second empty.
2. Pick an RPM with at least two versions.
3. Copy the older version of the RPM from the first repository to the second, and publish the second repository.
4. Pick a host system capable of installing RPMs. (By default, this is the system hosting Pulp.) Make it add the second repository as a source of packages, and make it install the RPM.
5. Copy the newer version of the RPM from the first repository to the second, and publish the second repository.
6. Make the host install the newer RPM with `yum update rpm_name`, or a similar command.

This test case targets [Pulp Smash #311](#).

**test\_all()**

Update an RPM in a repository and on a host.

**class** `pulp_smash.tests.pulp2.rpm.cli.test_copy_units.UtilsMixin`

A mixin providing useful tools to unittest subclasses.

Any class inheriting from this mixin must also inherit from `unittest.TestCase` or a compatible clone.

**create\_repo** (*cfg*)

Create a repository and schedule it for deletion.

**Parameters** *cfg* (`pulp_smash.config.PulpSmashConfig`) – The Pulp system on which to create a repository.

**Returns** The repository’s ID.

`pulp_smash.tests.pulp2.rpm.cli.test_copy_units.setUpModule()`

Possibly skip tests. Create and sync an RPM repository.

Skip tests in this module if the RPM plugin is not installed on the target Pulp server. Then create an RPM repository with a feed and sync it. Test cases may copy data from this repository but should **not** change it.

`pulp_smash.tests.pulp2.rpm.cli.test_copy_units.tearDownModule()`  
Delete the repository created by `setUpModule`.

## 6.108 `pulp_smash.tests.pulp2.rpm.cli.test_environments`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.cli.test\_environments*

Tests for RPM package environments.

**class** `pulp_smash.tests.pulp2.rpm.cli.test_environments.UploadPackageEnvTestCase` (*methodName='setUpClass'*)  
Test whether Pulp can upload package environments into a repository.

This test case covers [Pulp #1003](#) and the corresponding Pulp Smash issue [Pulp Smash #319](#). The following test steps are based on official [Pulp RPM Recipes](#).

1. Create and sync a repository.
2. Upload the environment into this repo and check if there's any error.

**classmethod** `setUpClass()`  
Create and sync a repository.

**classmethod** `tearDownClass()`  
Destroy the repository.

**test\_upload\_environment()**  
Test if package environments can be uploaded.

## 6.109 `pulp_smash.tests.pulp2.rpm.cli.test_langpacks`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.cli.test\_langpacks*

Tests for Pulp's langpack support.

**class** `pulp_smash.tests.pulp2.rpm.cli.test_langpacks.UploadAndRemoveLangpacksTestCase` (*methodName='setUpClass'*)  
Test whether one can upload to and remove langpacks from a repository.

This test targets [Pulp Smash #270](#). The test steps are as follows:

1. Create a repository.
2. Upload langpacks to the repository. Verify the correct number of langpacks are present.
3. Remove langpacks from the repository. Verify that no langpacks are present.

**classmethod** `setUpClass()`  
Create a repository.

**classmethod** `tearDownClass()`  
Delete the repository created by `setUpClass()`.

**test\_01\_upload\_langpacks()**  
Upload a langpack to the repository.

**test\_02\_remove\_langpacks()**  
Remove all langpacks from the repository.

## 6.110 *pulp\_smash.tests.pulp2.rpm.cli.test\_process\_recycling*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.cli.test\_process\_recycling*

Test Pulp's ability to recycle processes.

**class** `pulp_smash.tests.pulp2.rpm.cli.test_process_recycling.MaxTasksPerChildTestCase` (*method*)  
 Test Pulp's handling of its `PULP_MAX_TASKS_PER_CHILD` setting.

The `PULP_MAX_TASKS_PER_CHILD` setting controls how many tasks a worker process executes before being destroyed. Setting this option to a low value, like 2, ensures that processes don't have a chance to consume large amounts of memory.

Test this feature by doing the following:

1. Use `ps` to verify that no Pulp worker processes have the `--maxtasksperchild` option set.
2. Set `PULP_MAX_TASKS_PER_CHILD` and restart Pulp. Use `ps` to verify that all Pulp worker processes were invoked with the `--maxtasksperchild` option.
3. Execute a sync and publish. No errors should be reported.
4. Unset the `PULP_MAX_TASKS_PER_CHILD` option and restart Pulp. Use `ps` to verify that no Pulp worker processes have the `--maxtasksperchild` option set.

For more information, see [Pulp #2172](#).

**test\_all** ()  
 Test Pulp's handling of its `PULP_MAX_TASKS_PER_CHILD` setting.

`pulp_smash.tests.pulp2.rpm.cli.test_process_recycling.get_pulp_worker_procs` (*cfg*)  
 Use `ps aux` to get information about each Pulp worker process.

**Parameters** `cfg` (`pulp_smash.config.PulpSmashConfig`) – Information about the Pulp deployment being targeted.

**Returns** An iterable of strings, one per line of matching output.

`pulp_smash.tests.pulp2.rpm.cli.test_process_recycling.setUpModule` ()  
 Conditionally skip this module, and execute `pulp-admin login`.

## 6.111 *pulp\_smash.tests.pulp2.rpm.cli.test\_retain\_old\_count*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.cli.test\_retain\_old\_count*

Test the `retain_old_count` feature.

When more than one version of an RPM is present in a repository and Pulp syncs from that repository, it must choose how many versions of that RPM to sync. By default, it syncs all versions of that RPM. The `retain_old_count` option lets one sync a limited number of outdated RPMs.

**class** `pulp_smash.tests.pulp2.rpm.cli.test_retain_old_count.RetainOldCountTestCase` (*methodName*)  
 Test the `retain_old_count` feature.

This test targets [Pulp #2785](#).

**create\_sync\_repo** (*retain\_old\_count*)  
 Create and sync a repository. Return information about it.  
 Implement the logic described by the `test_retain_*` methods.

**classmethod setUpClass()**

Create, populate and publish a repository.

Ensure at least two versions of an RPM are present in the repository.

**classmethod tearDownClass()**

Destroy the repository created by `setUpClass()`.

**test\_retain\_one()**

Give `retain_old_count` a value of one.

Create a repository whose feed references the repository created in `setUpClass()`, and whose `retain_old_count` option is one. Sync the repository, and assert that one old version of any duplicate RPMs were copied over.

**test\_retain\_zero()**

Give `retain_old_count` a value of zero.

Create a repository whose feed references the repository created by `setUpClass()`, and whose `retain_old_count` option is zero. Sync the repository, and assert that zero old versions of any duplicate RPMs were copied over.

## 6.112 `pulp_smash.tests.pulp2.rpm.cli.test_search`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.cli.test_search`

Tests that perform searches.

**class** `pulp_smash.tests.pulp2.rpm.cli.test_search.SearchReposWithFiltersTestCase` (*methodName=*

Search for repositories, and use filters to limit matches.

This test case targets [Pulp #1784](#) and [Pulp Smash #184](#). The [repository search](#) documentation describes the CLI search syntax.

**static gen\_commands** (*repo\_id*)

Generate the commands used by the test methods.

Commands with the following filters are returned:

```
--filters {'id': '...'}
--filters {'repo_id': '...'}
--str-eq id=...
--str-eq repo_id=...
```

**classmethod setUpClass()**

Create a repository.

**classmethod tearDownClass()**

Delete the repository created by `setUpClass()`.

**test\_negative\_searches()**

Search for the repository with a non-matching repository ID.

**test\_positive\_searches()**

Search for the repository with a matching repository ID.



## 6.113 *pulp\_smash.tests.pulp2.rpm.cli.test\_sync*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.cli.test\_sync*

Tests that sync RPM repositories.

**class** `pulp_smash.tests.pulp2.rpm.cli.test_sync.ForceSyncTestCase` (*methodName='runTest'*)  
Test whether one can force Pulp to perform a full sync.

This test case targets [Pulp #1982](#) and [Pulp Smash #353](#). The test procedure is as follows:

1. Create and sync a repository.
2. Remove some number of RPMs from `/var/lib/pulp/content/units/rpm/`. Verify they are missing.
3. Sync the repository. Verify the RPMs are still missing.
4. Sync the repository with `--force-full true`. Verify all RPMs are present.

**test\_all()**  
Test whether one can force Pulp to perform a full sync.

**class** `pulp_smash.tests.pulp2.rpm.cli.test_sync.RemovedContentTestCase` (*methodName='runTest'*)  
Test whether Pulp can re-sync content into a repository.

This test case targets [Pulp #1775](#) and the corresponding Pulp Smash issue, [Pulp Smash #243](#).

1. Create and sync a repository. Select a content unit.
2. Delete the content unit from the repository, and verify it's absent.
3. Sync the repository, and verify that the content unit is present.

**test\_all()**  
Test whether Pulp can re-sync content into a repository.

`pulp_smash.tests.pulp2.rpm.cli.test_sync.get_rpm_names` (*cfg, repo\_id*)  
Get a list of names of all packages in a repository.

### Parameters

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about a Pulp deployment.
- **repo\_id** – A RPM repository ID.

**Returns** The names of all modules in a repository, as an `list`.

`pulp_smash.tests.pulp2.rpm.cli.test_sync.setUpModule()`  
Execute `pulp-admin login` and reset Pulp.

For `RemovedContentTestCase` to function correctly, we require that all of the content units on Pulp's filesystem belong to the repository created by that test case. Resetting Pulp guarantees that this is so. Ideally, all test cases would clean up after themselves so that no resets are necessary.

`pulp_smash.tests.pulp2.rpm.cli.test_sync.sync_repo` (*cfg, repo\_id, force\_sync=False*)  
Sync an RPM repository.

### Parameters

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about a Pulp deployment.
- **repo\_id** – A RPM repository ID.

- **repo\_id** – A boolean flag to denote if is a force-full sync.

**Returns** A `pulp_smash.cli.CompletedProcess`.

## 6.114 `pulp_smash.tests.pulp2.rpm.cli.test_upload`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.cli.test_upload`

Tests that upload content units into repositories.

**class** `pulp_smash.tests.pulp2.rpm.cli.test_upload.UploadDrpmTestCase` (*methodName='runTest'*)  
Test whether one can upload a DRPM into a repository.

This test case targets [Pulp Smash #336](#) and [Pulp Smash #585](#)

**test\_upload()**

Create a repository and upload DRPMs into it.

Specifically, do the following:

1. Create a yum repository.
2. Download a DRPM file.
3. Upload the DRPM into it. Use `pulp-admin` to verify its presence in the repository.
4. Upload the same DRPM into the same repository, and use the `--skip-existing` flag during the upload. Verify that Pulp skips the upload.

**test\_upload\_with\_checksumtype()**

Create a repository and upload DRPMs into it.

Specifically, do the following:

1. Create a yum repository.
2. Download a DRPM file.
3. Upload the DRPM into it specifying the checksumtype
4. Use `pulp-admin` to verify its presence in the repository.
5. Upload the same DRPM into the same repository, and use the `--skip-existing` flag during the upload. Verify that Pulp skips the upload.

`pulp_smash.tests.pulp2.rpm.cli.test_upload.setUpModule()`

Execute `pulp-admin login` on the target Pulp system.

## 6.115 `pulp_smash.tests.pulp2.rpm.cli.utils`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp2.rpm.cli.utils`

Utility functions for RPM CLI tests.

`pulp_smash.tests.pulp2.rpm.cli.utils.count_langpacks` (*server\_config, repo\_id*)

Tell how many langpack content units are in the given repository.

**Parameters**

- **server\_config** (`pulp_smash.config.PulpSmashConfig`) – Information about the Pulp deployment being targeted.

- **repo\_id** – A repository ID.

**Returns** The number of langpacks in the named repository, as an integer.

## 6.116 *pulp\_smash.tests.pulp2.rpm.utils*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.rpm.utils*

Utilities for RPM tests.

`pulp_smash.tests.pulp2.rpm.utils.check_issue_2277` (*cfg*)

Return true if Pulp #2277 affects the targeted Pulp system.

**Parameters** **cfg** (`pulp_smash.config.PulpSmashConfig`) – The Pulp system under test.

`pulp_smash.tests.pulp2.rpm.utils.check_issue_2354` (*cfg*)

Return true if Pulp #2354 affects the targeted Pulp system.

**Parameters** **cfg** (`pulp_smash.config.PulpSmashConfig`) – The Pulp system under test.

`pulp_smash.tests.pulp2.rpm.utils.check_issue_2387` (*cfg*)

Return true if Pulp #2387 affects the targeted Pulp system.

**Parameters** **cfg** (`pulp_smash.config.PulpSmashConfig`) – The Pulp system under test.

`pulp_smash.tests.pulp2.rpm.utils.check_issue_2620` (*cfg*)

Return true if Pulp #2620 affects the targeted Pulp system.

**Parameters** **cfg** (`pulp_smash.config.PulpSmashConfig`) – The Pulp system under test.

`pulp_smash.tests.pulp2.rpm.utils.check_issue_2798` (*cfg*)

Return true if Pulp #2798 affects the targeted Pulp system.

**Parameters** **cfg** (`pulp_smash.config.PulpSmashConfig`) – The Pulp system under test.

`pulp_smash.tests.pulp2.rpm.utils.check_issue_2844` (*cfg*)

Return true if Pulp #2844 affects the targeted Pulp system.

**Parameters** **cfg** (`pulp_smash.config.PulpSmashConfig`) – The Pulp system under test.

`pulp_smash.tests.pulp2.rpm.utils.check_issue_3104` (*cfg*)

Return true if Pulp #3104 affects the targeted Pulp system.

**Parameters** **cfg** (`pulp_smash.config.PulpSmashConfig`) – The Pulp system under test.

`pulp_smash.tests.pulp2.rpm.utils.gen_yum_config_file` (*cfg*, *repositoryid*, *\*\*kwargs*)

Generate a yum configuration file and write it to `/etc/yum.repos.d/`.

Generate a yum configuration file containing a single repository section, and write it to `/etc/yum.repos.d/{repositoryid}.repo`.

**Parameters**

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – The system on which to create a yum configuration file.
- **repositoryid** – The section's `repositoryid`. Used when naming the configuration file and populating the brackets at the head of the file. For details, see `yum.conf(5)`.
- **kwargs** – Section options. Each kwarg corresponds to one option. For details, see `yum.conf(5)`.

**Returns** The path to the yum configuration file.

`pulp_smash.tests.pulp2.rpm.utils.os_is_rhel6(cfg)`

Return True if the server runs RHEL 6, or False otherwise.

**Parameters** `cfg` (`pulp_smash.config.PulpSmashConfig`) – Information about the system being targeted.

**Returns** True or false.

`pulp_smash.tests.pulp2.rpm.utils.set_up_module()`

Skip tests if Pulp 2 isn't under test or if RPM isn't installed.

## 6.117 `pulp_smash.tests.pulp2.utils`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp2.utils*

Utility functions for Pulp 2 tests.

`pulp_smash.tests.pulp2.utils.get_unit_types()`

Tell which unit types are supported by the target Pulp server.

Each Pulp plugin adds one (or more?) content unit types to Pulp, and each content unit type has a unique identifier. For example, the Python plugin<sup>1</sup> adds the Python content unit type<sup>2</sup>, and Python content units have an ID of `python_package`. This function queries the server and returns those unit type IDs.

**Returns** A set of content unit type IDs. For example: `{'ostree', 'python_package'}`.

`pulp_smash.tests.pulp2.utils.require_issue_3159()`

Skip tests if Fedora 27 is under test and [Pulp #3159](#) is open.

`pulp_smash.tests.pulp2.utils.require_pulp_2()`

Skip tests if Pulp 2 isn't under test.

`pulp_smash.tests.pulp2.utils.require_unit_types(required_unit_types)`

Skip tests if one or more unit types aren't supported.

**Parameters** `required_unit_types` – A set of unit types IDs, e.g. `{'ostree'}`.

## 6.118 `pulp_smash.tests.pulp3`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3*

Tests for Pulp 3.

## 6.119 `pulp_smash.tests.pulp3.constants`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.constants*

Constants for Pulp 3 tests.

---

<sup>1</sup> [http://docs.pulpproject.org/plugins/pulp\\_python/](http://docs.pulpproject.org/plugins/pulp_python/)

<sup>2</sup> [http://docs.pulpproject.org/plugins/pulp\\_python/reference/python-type.html](http://docs.pulpproject.org/plugins/pulp_python/reference/python-type.html)

## 6.120 *pulp\_smash.tests.pulp3.file*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.file*

Tests for file plugin.

## 6.121 *pulp\_smash.tests.pulp3.file.api\_v3*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.file.api\_v3*

Tests that communicate with file plugin via the v3 API.

## 6.122 *pulp\_smash.tests.pulp3.file.api\_v3.test\_crud\_publications*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.file.api\_v3.test\_crud\_publications*

Tests that perform actions over publications.

**class** `pulp_smash.tests.pulp3.file.api_v3.test_crud_publications.PublicationsTestCase` (*methodN*)

Perform actions over publications.

**classmethod** `setUpClass()`

Create class-wide variables.

**classmethod** `tearDownClass()`

Clean class-wide variables.

**test\_01\_create\_publication()**

Create a publication.

**test\_02\_read\_publication()**

Read a publication by its href.

**test\_02\_read\_publications()**

Read a publication by its repository version.

**test\_03\_read\_publications()**

Read a publication by its publisher.

**test\_04\_read\_publications()**

Read a publication by its created time.

**test\_05\_read\_publications()**

Read a publication by its distribution.

**test\_06\_delete()**

Delete a publication.

## 6.123 *pulp\_smash.tests.pulp3.file.api\_v3.test\_crud\_content\_unit*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.file.api\_v3.test\_crud\_content\_unit*

Tests that perform actions over content unit.

**class** `pulp_smash.tests.pulp3.file.api_v3.test_crud_content_unit.ContentUnitTestCase` (*methodN*)  
CRUD content unit.

This test targets the following issues:

- [Pulp #2872](#)
- [Pulp Smash #870](#)

**classmethod** `setUpClass()`  
Create class-wide variable.

**classmethod** `tearDownClass()`  
Clean class-wide variable.

**test\_01\_create\_content\_unit()  
Create content unit.**

**test\_02\_read\_content\_unit()  
Read a content unit by its href.**

**test\_02\_read\_content\_units()  
Read a content unit by its relative\_path.**

**test\_03\_fully\_update()  
Attempt to update a content unit using HTTP PUT.  
  
This HTTP method is not supported and a HTTP exception is expected.**

**test\_03\_partially\_update()  
Attempt to update a content unit using HTTP PATCH.  
  
This HTTP method is not supported and a HTTP exception is expected.**

**class** `pulp_smash.tests.pulp3.file.api_v3.test_crud_content_unit.DeleteContentUnitRepoVersion`  
Test whether content unit used by a repo version can be deleted.

This test targets the following issues:

- [Pulp #3418](#)
- [Pulp Smash #900](#)

**test\_all()  
Test whether content unit used by a repo version can be deleted.**

Do the following:

1. Sync content to a repository.
2. Attempt to delete a content unit present in a repository version. Assert that a HTTP exception was raised.
3. Assert that number of content units present on the repository does not change after the attempt to delete one content unit.

## 6.124 `pulp_smash.tests.pulp3.file.api_v3.test_crud_publishers`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp3.file.api_v3.test_crud_publishers`

Tests that CRUD publishers.

**class** `pulp_smash.tests.pulp3.file.api_v3.test_crud_publishers.CRUDPublishersTestCase` (*methodN*)  
CRUD publishers.

**classmethod setUpClass ()**

Create class-wide variables.

In order to create a publisher a repository has to be created first.

**classmethod tearDownClass ()**

Clean class-wide variable.

**test\_01\_create\_publisher ()**

Create a publisher.

**test\_02\_read\_publisher ()**

Read a publisher by its href.

**test\_02\_read\_publishers ()**

Read a publisher by its name.

**test\_03\_partially\_update ()**

Update a publisher using HTTP PATCH.

**test\_04\_fully\_update ()**

Update a publisher using HTTP PUT.

**test\_05\_delete ()**

Delete a publisher.

## 6.125 *pulp\_smash.tests.pulp3.file.api\_v3.test\_crud\_remotes*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.file.api\_v3.test\_crud\_remotes*

Tests that CRUD remotes.

**class** `pulp_smash.tests.pulp3.file.api_v3.test_crud_remotes.CRUDRemotesTestCase` (*methodName='runTest'*)  
 CRUD remotes.

**classmethod setUpClass ()**

Create class-wide variables.

In order to create an remote a repository has to be created first.

**classmethod tearDownClass ()**

Clean class-wide variable.

**test\_01\_create\_remote ()**

Create an remote.

**test\_02\_read\_remote ()**

Read an remote by its href.

**test\_02\_read\_remotes ()**

Read an remote by its name.

**test\_03\_partially\_update ()**

Update an remote using HTTP PATCH.

**test\_04\_fully\_update ()**

Update an remote using HTTP PUT.

**test\_05\_delete ()**

Delete an remote.

## 6.126 *pulp\_smash.tests.pulp3.file.api\_v3.test\_download\_content*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.file.api\_v3.test\_download\_content*

Tests that verify download of content served by Pulp.

**class** `pulp_smash.tests.pulp3.file.api_v3.test_download_content.DownloadContentTestCase` (*methodName='runTest'*)  
Verify whether content served by pulp can be downloaded.

**test\_all** ()

Verify whether content served by pulp can be downloaded.

The process of publishing content is more involved in Pulp 3 than it was under Pulp 2. Given a repository, the process is as follows:

1. Create a publication from the repository. (The latest repository version is selected if no version is specified.) A publication is a repository version plus metadata.
2. Create a distribution from the publication. The distribution defines at which URLs a publication is available, e.g. `http://example.com/content/pub-name/` and `https://example.com/content/pub-name/`.

Do the following:

1. Create, populate, publish, and distribute a repository.
2. Select a random content unit in the distribution. Download that content unit from Pulp, and verify that the content unit has the same checksum when fetched directly from Pulp-Fixtures.

This test targets the following issues:

- Pulp #2895
- Pulp Smash #872

## 6.127 *pulp\_smash.tests.pulp3.file.api\_v3.test\_orphans*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.file.api\_v3.test\_orphans*

Tests that perform actions over orphan files.

**class** `pulp_smash.tests.pulp3.file.api_v3.test_orphans.DeleteOrphansTestCase` (*methodName='runTest'*)  
Test whether orphans files can be clean up.

An orphan artifact is an artifact that is not in any content units. An orphan content unit is a content unit that is not in any repository version.

This test targets the following issues:

- Pulp #3442
- Pulp Smash #914

**classmethod** `setUpClass` ()

Create class-wide variables.

**test\_clean\_orphan\_artifact** ()

Test whether orphan artifacts units can be clean up.

**test\_clean\_orphan\_content\_unit** ()

Test whether orphan content units can be clean up.

Do the following:



1. Create, and sync a repo.
2. Remove a content unit from the repo. This will create a second repository version, and create an orphan content unit.
3. Assert that content unit that was removed from the repo and its artifact are present on disk.
4. Delete orphans.
5. Assert that the orphan content unit was cleaned up, and its artifact is not present on disk.

## 6.128 *pulp\_smash.tests.pulp3.file.api\_v3.test\_publish*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.file.api\_v3.test\_publish*

Tests that publish file plugin repositories.

**class** `pulp_smash.tests.pulp3.file.api_v3.test_publish.PublishAnyRepoVersionTestCase` (*methodNotImplemented*)  
 Test whether a particular repository version can be published.

This test targets the following issues:

- Pulp #3324
- Pulp Smash #897

**test\_all** ()

Test whether a particular repository version can be published.

1. Create a repository with at least 2 repository versions.
2. Create a publication by supplying the latest `repository_version`.
3. Assert that the publication `repository_version` attribute points to the latest repository version.
4. Create a publication by supplying the non-latest `repository_version`.
5. Assert that the publication `repository_version` attribute points to the supplied repository version.
6. Assert that an exception is raised when providing two different repository versions to be published at same time.

## 6.129 *pulp\_smash.tests.pulp3.file.api\_v3.test\_repo\_version*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.file.api\_v3.test\_repo\_version*

Tests related to repository version.

**class** `pulp_smash.tests.pulp3.file.api_v3.test_repo_version.AddRemoveContentTestCase` (*methodNotImplemented*)  
 Add and remove content to a repository. Verify side-effects.

A new repository version is automatically created each time content is added to or removed from a repository. Furthermore, it's possible to inspect any repository version and discover which content is present, which content was removed, and which content was added. This test case explores these features.

This test targets the following issues:

- Pulp #3059
- Pulp #3234

- [Pulp Smash #878](#)

**get\_content\_summary** (*repo*)

Get the `content_summary` for the given repository.

**classmethod setUpClass** ()

Create class-wide variables.

**classmethod tearDownClass** ()

Destroy resources created by test methods.

**test\_01\_create\_repository** ()

Create a repository.

Assert that:

- The `_versions_href` API call is correct.
- The `_latest_version_href` API call is correct.

**test\_02\_sync\_content** ()

Sync content into the repository.

Assert that:

- The `_versions_href` API call is correct.
- The `_latest_version_href` API call is correct.
- The `_latest_version_href + content/` API call is correct.
- The `_latest_version_href + added_content/` API call is correct.
- The `_latest_version_href + removed_content/` API call is correct.
- The `content_summary` attribute is correct.

**test\_03\_remove\_content** ()

Remove content from the repository.

Make roughly the same assertions as `test_02_sync_content ()`.

**test\_04\_add\_content** ()

Add content to the repository.

Make roughly the same assertions as `test_02_sync_content ()`.

**class** `pulp_smash.tests.pulp3.file.api_v3.test_repo_version.AddRemoveRepoVersionTestCase` (*metaclass*)

Create and delete repository versions.

This test targets the following issues:

- [Pulp #3219](#)
- [Pulp Smash #871](#)

**setUp** ()

Create a repository and give it nine new versions.

**classmethod setUpClass** ()

Add content to Pulp.

**test\_delete\_first\_version** ()

Delete the first repository version.

**test\_delete\_last\_version()**

Delete the last repository version.

Create a new repository version from the second-to-last repository version. Verify that the content unit from the old last repository version is not in the new last repository version.

**test\_delete\_middle\_version()**

Delete a middle version.

**test\_delete\_publication()**

Delete a publication.

Delete a repository version, and verify the associated publication is also deleted.

**class** `pulp_smash.tests.pulp3.file.api_v3.test_repo_version.ContentImmutableRepoVersionTest`

Test whether the content present in a repo version is immutable.

This test targets the following issue:

- [Pulp Smash #953](#)

**test\_all()**

Test whether the content present in a repo version is immutable.

Do the following:

1. Create a repository that has at least one repository version.
2. Attempt to update the content of a repository version.
3. Assert that an HTTP exception is raised.
4. Assert that the repository version was not updated.

## 6.130 `pulp_smash.tests.pulp3.file.api_v3.test_sync`

Location: *Pulp Smash* → *API Documentation* → `pulp_smash.tests.pulp3.file.api_v3.test_sync`

Tests that sync file plugin repositories.

**class** `pulp_smash.tests.pulp3.file.api_v3.test_sync.MultiResourceLockingTestCase` (*methodName=''*)

Verify multi-resourcing locking.

This test targets the following issues:

- [Pulp #3186](#)
- [Pulp Smash #879](#)

**test\_all()**

Verify multi-resourcing locking.

Do the following:

1. Create a repository, and a remote.
2. Update the remote to point to a different url.
3. Immediately run a sync. The sync should fire after the update and sync from the second url.
4. Assert that remote url was updated.
5. Assert that the number of units present in the repository is according to the updated url.

**class** `pulp_smash.tests.pulp3.file.api_v3.test_sync.SyncChangeRepoVersionTestCase` (*methodName='runTest'*)  
Verify whether sync of repository updates repository version.

**test\_all** ()

Verify whether the sync of a repository updates its version.

This test explores the design choice stated in the [Pulp #3308](#) that a new repository version is created even if the sync does not add or remove any content units. Even without any changes to the remote if a new sync occurs, a new repository version is created.

Do the following:

1. Create a repository, and an remote.
2. Sync the repository an arbitrary number of times.
3. Verify that the repository version is equal to the previous number of syncs.

**class** `pulp_smash.tests.pulp3.file.api_v3.test_sync.SyncFileRepoTestCase` (*methodName='runTest'*)  
Sync repositories with the file plugin.

**classmethod** `setUpClass` ()

Create class-wide variables.

**test\_sync** ()

Sync repositories with the file plugin.

In order to sync a repository an remote has to be associated within this repository. When a repository is created this version field is set as None. After a sync the repository version is updated.

Do the following:

1. Create a repository, and an remote.
2. Assert that repository version is None.
3. Sync the remote.
4. Assert that repository version is not None.
5. Sync the remote one more time.
6. Assert that repository version is different from the previous one.

## 6.131 `pulp_smash.tests.pulp3.file.api_v3.test_unlinking_repo`

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.file.api\_v3.test\_unlinking\_repo*

Tests that perform action over remotes and publishers.

**class** `pulp_smash.tests.pulp3.file.api_v3.test_unlinking_repo.RemotesPublishersTestCase` (*methodName='runTest'*)  
Verify publisher and remote can be used with different repos.

**test\_all** ()

Verify publisher and remote can be used with different repos.

This test explores the design choice stated in [Pulp #3341](#) that remove the FK from publishers and remotes to repository. Allowing remotes and publishers to be used with different repositories.

Do the following:

1. Create an remote, and a publisher.
2. Create 2 repositories.

3. Sync both repositories using the same remote.
4. Assert that the two repositories have the same contents.
5. Publish both repositories using the same publisher.
6. Assert that each generated publication has the same publisher, but are associated with different repositories.

### 6.132 *pulp\_smash.tests.pulp3.file.api\_v3.utils*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.file.api\_v3.utils*

Utilities for file plugin tests.

`pulp_smash.tests.pulp3.file.api_v3.utils.gen_publisher()`  
Return a semi-random dict for use in creating a publisher.

`pulp_smash.tests.pulp3.file.api_v3.utils.gen_remote()`  
Return a semi-random dict for use in creating an remote.

### 6.133 *pulp\_smash.tests.pulp3.file.utils*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.file.utils*

Utilities for tests for the file plugin.

`pulp_smash.tests.pulp3.file.utils.set_up_module()`  
Skip tests Pulp 3 isn't under test or if pulp-file isn't installed.

### 6.134 *pulp\_smash.tests.pulp3.pulpcore*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.pulpcore*

Tests for Pulp 3's core.

### 6.135 *pulp\_smash.tests.pulp3.pulpcore.api\_v3*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.pulpcore.api\_v3*

Tests that communicate with Pulp 3 via the v3 API.

### 6.136 *pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_api\_docs*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_api\_docs*

Test related to the api docs page.

**class** `pulp_smash.tests.pulp3.pulpcore.api_v3.test_api_docs.ApiDocsTestCase` (*methodName='runTest'*)  
Test whether API auto generated docs are available.

This test targets the following issues:

- [Pulp #3552](#)
- [Pulp Smash #893](#)

**setUp()**  
Create an API Client.

**test\_http\_method()**  
Get API documentation with an HTTP method other than GET.  
Assert an error is returned.

**test\_no\_credentials()**  
Get API documentation with no credentials.  
Assert the API documentation is returned.

**test\_valid\_credentials()**  
Get API documentation with valid credentials.  
Assert the API documentation is returned.

## 6.137 *pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_auth*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_auth*

Tests for Pulp 3's authentication API.

For more information, see the documentation on [Authentication](#).

```
class pulp_smash.tests.pulp3.pulpcore.api_v3.test_auth.AuthTestCase (methodName='runTest')
    Test Pulp3 Authentication.

    classmethod setUpClass ()
        Create class-wide variables.

    test_base_auth_failure ()
        Perform HTTP basic authentication with invalid credentials.

        Assert that a response indicating failure is returned.

    test_base_auth_success ()
        Perform HTTP basic authentication with valid credentials.

        Assert that a response indicating success is returned.

    test_jwt_failure ()
        Perform JWT authentication with invalid credentials.

        Assert that a response indicating failure is returned.

    test_jwt_success ()
        Perform JWT authentication with valid credentials.

        Assert that a response indicating success is returned.

class pulp_smash.tests.pulp3.pulpcore.api_v3.test_auth.JWTResetTestCase (methodName='runTest')
    Perform series of tests related to JWT reset.

    setUp ()
        Create a user and several JWT tokens for that user.

        Also, verify that the tokens are valid.
```

**test\_delete\_user ()**

Delete the user, and verify their tokens are invalid.

**test\_reset\_tokens ()**

Repeatedly reset the user's tokens, and verify they're invalid.

Repeatedly resetting tokens ensures that token resets work even when a user has no tokens.

## 6.138 *pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_crd\_artifacts*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_crd\_artifacts*

Tests that perform actions over artifacts.

**class** `pulp_smash.tests.pulp3.pulpcore.api_v3.test_crd_artifacts.ArtifactTestCase` (*methodName=*  
Perform actions over an artifact.

**classmethod** `setUpClass ()`

Create class-wide variable.

**test\_01\_create ()**

Create an artifact by uploading a file.

This test explores the design choice stated in [Pulp #2843](#) that an artifact can be created using HTTP POST with a body of request that contains a multipart form data.

This test targets the following issues:

- [Pulp #2843](#)
- [Pulp Smash #726](#)

Do the following:

1. Download a file in memory.
2. Upload the just downloaded file to pulp.
3. Verify that the checksum of the just created artifact is equal to the checksum of the file that was uploaded.

**test\_02\_read ()**

Read an artifact by its href.

**test\_03\_delete ()**

Delete an artifact.

**class** `pulp_smash.tests.pulp3.pulpcore.api_v3.test_crd_artifacts.ArtifactsDeleteFileSystemT`  
Delete an artifact, it is removed from the filesystem.

This test targets the following issues:

- [Pulp #3508](#)
- [Pulp Smash #908](#)

**test\_all ()**

Delete an artifact, it is removed from the filesystem.

Do the following:

1. Create an artifact, and verify it is present on the filesystem.
2. Delete the artifact, and verify it is absent on the filesystem.

## 6.139 *pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_crud\_distributions*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_crud\_distributions*

Tests that CRUD distributions.

```
class pulp_smash.tests.pulp3.pulpcore.api_v3.test_crud_distributions.CRUDDistributionsTest
    CRUD distributions.

    classmethod setUpClass ()
        Create class wide-variables.

    test_01_create_distribution ()
        Create a distribution.

    test_02_read_distribution ()
        Read a distribution by its _href.

    test_02_read_distributions ()
        Read a distribution by its name.

    test_03_partially_update ()
        Update a distribution using HTTP PATCH.

    test_04_fully_update ()
        Update a distribution using HTTP PUT.

    test_05_delete ()
        Delete a distribution.
```

## 6.140 *pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_crud\_repos*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_crud\_repos*

Tests that CRUD repositories.

```
class pulp_smash.tests.pulp3.pulpcore.api_v3.test_crud_repos.CRUDRepoTestCase (methodName='run')
    CRUD repositories.

    do_fully_update_attr (attr)
        Update a repository attribute using HTTP PUT.

        Parameters attr – The name of the attribute to update. For example, “description.” The attribute to update must be a string.

    do_partially_update_attr (attr)
        Update a repository attribute using HTTP PATCH.

        Parameters attr – The name of the attribute to update. For example, “description.” The attribute to update must be a string.

    setUp ()
        Create an API client.

    classmethod setUpClass ()
        Create class-wide variables.

    test_01_create_repo ()
        Create repository.
```



```

test_02_read_all_repos ()
    Ensure name is displayed when listing repositories.

test_02_read_repo ()
    Read a repository by its href.

test_02_read_repos ()
    Read the repository by its name.

test_03_fully_update_desc ()
    Update a repository's description using HTTP PUT.

test_03_fully_update_name ()
    Update a repository's name using HTTP PUT.

test_03_partially_update_desc ()
    Update a repository's description using HTTP PATCH.

test_03_partially_update_name ()
    Update a repository's name using HTTP PATCH.

test_04_delete_repo ()
    Delete a repository.

```

## 6.141 *pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_crud\_users*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_crud\_users*

Tests that CRUD users.

```

class pulp_smash.tests.pulp3.pulpcore.api_v3.test_crud_users.UsersCRUDTestCase (methodName='runTest')
    CRUD users.

    setUp ()
        Create an API client.

    classmethod setUpClass ()
        Create class-wide variables.

    test_01_create_user ()
        Create a user.

    test_02_read_user ()
        Read a user by its _href.

    test_02_read_username ()
        Read a user by its username.

    test_02_read_users ()
        Read all users. Verify that the created user is in the results.

    test_03_fully_update_user ()
        Update a user info using HTTP PUT.

    test_03_partially_update_user ()
        Update a user info using HTTP PATCH.

    test_04_delete_user ()
        Delete an user.

```

## 6.142 *pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_status*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_status*

Test the status page.

**class** `pulp_smash.tests.pulp3.pulpcore.api_v3.test_status.StatusTestCase` (*methodName='runTest'*)

Tests related to the status page.

This test explores the following issues:

- Pulp #2804
- Pulp #2867
- Pulp #3544
- Pulp Smash #755

**setUp** ()

Make an API client.

**test\_get\_authenticated** ()

GET the status path with valid credentials.

Verify the response with `verify_get_response()`.

**test\_get\_unauthenticated** ()

GET the status path with no credentials.

Verify the response with `verify_get_response()`.

**test\_post\_authenticated** ()

POST the status path with valid credentials.

Assert an error is returned.

**verify\_get\_response** (*status*)

Verify the response to an HTTP GET call.

Verify that several attributes and have the correct type or value.

## 6.143 *pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_workers*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_workers*

Tests related to the workers.

**class** `pulp_smash.tests.pulp3.pulpcore.api_v3.test_workers.WorkersTestCase` (*methodName='runTest'*)

Test actions over workers.

This test targets the following issues:

- Pulp #3143
- Pulp Smash #945

**classmethod setUpClass** ()

Create an API Client.

**test\_01\_read\_all\_workers** ()

Read all workers.

Pick a random worker to be used for the next assertions.

**test\_02\_read\_worker()**  
Read a worker by its `_href`.

**test\_02\_read\_workers()**  
Read a worker by its name.

**test\_03\_positive\_filters()**  
Read a worker using a set of query parameters.

**test\_04\_negative\_filters()**  
Read a worker with a query that does not match any worker.

**test\_05\_http\_method()**  
Use an HTTP method different than GET.  
Assert an error is raised.

## 6.144 *pulp\_smash.tests.pulp3.pulpcore.utils*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.pulpcore.utils*

Utilities for Pulpcore tests.

`pulp_smash.tests.pulp3.pulpcore.utils.gen_distribution()`  
Return a semi-random dict for use in creating a distribution.

`pulp_smash.tests.pulp3.pulpcore.utils.gen_repo()`  
Return a semi-random dict for use in creating a repository.

`pulp_smash.tests.pulp3.pulpcore.utils.set_up_module()`  
Skip tests Pulp 3 isn't under test or if pulpcore isn't installed.

## 6.145 *pulp\_smash.tests.pulp3.utils*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.tests.pulp3.utils*

Utility functions for Pulp 3 tests.

**class** `pulp_smash.tests.pulp3.utils.JWTAuth(token, header_format='Bearer')`  
A class that enables JWT authentication with the Requests library.

For more information, see the Requests documentation on [custom authentication](#).

`pulp_smash.tests.pulp3.utils.delete_orphans(cfg=None)`  
Clean all content units present in pulp.

An orphaned artifact is an artifact that is not in any content units. An orphaned content unit is a content unit that is not in any repository version.

**Parameters** `cfg` (`pulp_smash.config.PulpSmashConfig`) – Information about the Pulp host.

`pulp_smash.tests.pulp3.utils.delete_repo_version(repo, version_href=None)`  
Delete a given repository version.

**Parameters**

- **repo** – A dict of information about the repository.
- **version\_href** – The repository version that should be deleted.

**Returns** A tuple. The tasks spawned by Pulp.

`pulp_smash.tests.pulp3.utils.get_added_content(repo, version_href=None)`  
Read the added content of a given repository version.

**Parameters**

- **repo** – A dict of information about a repository.
- **version\_href** – The repository version to read. If none, read the latest repository version.

**Returns** A dict of information about the content added since the previous repository version.

`pulp_smash.tests.pulp3.utils.get_artifact_paths(repo, version_href=None)`  
Return the paths of artifacts present in a given repository version.

**Parameters**

- **repo** – A dict of information about the repository.
- **version\_href** – The repository version to read.

**Returns** A set with the paths of units present in a given repository.

`pulp_smash.tests.pulp3.utils.get_auth(cfg=None)`  
Return a random authentication object.

By default, `pulp_smash.api.Client` uses the same authentication method (HTTP BASIC) for every request. While this is a sane default, it doesn't let tests exercise other authentication procedures. This function returns a random authentication object. To demonstrate how this object can be used, here's an example showing how to create a user:

```
>>> from pulp_smash.api import Client
>>> from pulp_smash.config import get_config
>>> from pulp_smash.tests.pulp3.utils import get_auth
>>> from pulp_smash.tests.pulp3.constants import USER_PATH
>>> cfg = get_config()
>>> client = api.Client(cfg, api.json_handler)
>>> client.request_kwargs['auth'] = get_auth()
>>> client.post(USER_PATH, {
>>>     'username': 'superuser',
>>>     'password': 'admin',
>>>     'is_superuser': True
>>> })
```

The returned object can also be used directly with `Requests`. For more information, see the [Requests Authentication](#) documentation.

**Parameters** `cfg` (`pulp_smash.config.PulpSmashConfig`) – Information about a Pulp app.

**Returns** A random authentication object.

`pulp_smash.tests.pulp3.utils.get_content(repo, version_href=None)`  
Read the content units of a given repository.

**Parameters**

- **repo** – A dict of information about the repository.
- **version\_href** – The repository version to read. If none, read the latest repository version.

**Returns** A dict of information about the content units present in a given repository version.

`pulp_smash.tests.pulp3.utils.get_content_unit_paths(repo)`

Return the relative path of content units present in a given repository.

**Parameters** `repo` – A dict of information about the repository.

**Returns** A list with the paths of units present in a given repository.

`pulp_smash.tests.pulp3.utils.get_plugins(cfg=None)`

Return the set of plugins installed on the Pulp application.

Pulp's API endpoint for reporting plugins and their versions doesn't work correctly at this time. Some hacks are implemented to discover which plugins are installed. As a result, not all plugins are returned.

**Parameters** `cfg` (`pulp_smash.config.PulpSmashConfig`) – Information about the Pulp application under test.

**Returns** A set of plugin names, e.g. {'pulpcore', 'pulp\_file'}.

`pulp_smash.tests.pulp3.utils.get_removed_content(repo, version_href=None)`

Read the removed content of a given repository version.

**Parameters**

- `repo` – A dict of information about the repository.
- `version_href` – The repository version to read. If none, read the latest repository version.

**Returns** A dict of information about the content removed since the previous repository version.

`pulp_smash.tests.pulp3.utils.get_repo_versions(repo)`

Return hrefs of repository versions.

**Parameters** `repo` – A dict of information about the repository.

**Returns** A sorted list with the hrefs of repository versions.

`pulp_smash.tests.pulp3.utils.publish_repo(cfg, publisher, repo, version_href=None)`

Publish a repository.

**Parameters**

- `cfg` (`pulp_smash.config.PulpSmashConfig`) – Information about the Pulp host.
- `publisher` – A dict of information about the publisher of the repository to be published.
- `repo` – A dict of information about the repository.
- `version_href` – The repository version to be published.

**Returns** A publication. A dict of information about the just created publication.

`pulp_smash.tests.pulp3.utils.require_pulp_3()`

Skip tests if Pulp 3 isn't under test.

`pulp_smash.tests.pulp3.utils.require_pulp_plugins(required_plugins)`

Skip tests if one or more plugins are missing.

**Parameters** `required_plugins` – A set of plugin names, e.g. {'pulp-file'}.

`pulp_smash.tests.pulp3.utils.sync_repo(cfg, remote, repo)`

Sync a repository.

**Parameters**

- `cfg` (`pulp_smash.config.PulpSmashConfig`) – Information about the Pulp host.
- `remote` – A dict of information about the remote of the repository to be synced.

- **repo** – A dict of information about the repository.

**Returns** The server’s response. Call `.json()` on the response to get a call report.

## 6.146 *pulp\_smash.utils*

Location: *Pulp Smash* → *API Documentation* → *pulp\_smash.utils*

Utility functions for Pulp tests.

This module may make use of *pulp\_smash.api* and *pulp\_smash.cli*, but the reverse should not be done.

**class** `pulp_smash.utils.BaseAPICrudTestCase` (*methodName='runTest'*)

A parent class for API CRUD test cases.

*create\_body()* and *update\_body()* should be overridden by concrete child classes. The bodies of these two methods are encoded to JSON and used as the bodies of HTTP requests for creating and updating a repository, respectively. Be careful to return appropriate data when overriding these methods: the various `test*` methods assume the repository is fairly simple.

Relevant Pulp documentation:

**Create** <http://docs.pulpproject.org/en/latest/dev-guide/integration/rest-api/repo/cud.html#create-a-repository>

**Read** <http://docs.pulpproject.org/en/latest/dev-guide/integration/rest-api/repo/retrieval.html#retrieve-a-single-repository>

**Update** <http://docs.pulpproject.org/en/latest/dev-guide/integration/rest-api/repo/cud.html#update-a-repository>

**Delete** <http://docs.pulpproject.org/en/latest/dev-guide/integration/rest-api/repo/cud.html#delete-a-repository>

**static** `create_body()`

Return a dict for creating a repository. Should be overridden.

**Raises** `NotImplementedError` if not implemented by a child class.

**classmethod** `setUpClass()`

Create, update, read and delete a repository.

**test\_create()**

Assert the created repository has all requested attributes.

Walk through each of the attributes returned by *create\_body()* and verify the attribute is present in the repository.

NOTE: Any attribute whose name starts with `importer` or `distributor` is not verified.

**test\_importer\_config()**

Validate the `config` attribute of each importer.

**test\_importer\_type\_id()**

Validate the repo importer’s `importer_type_id` attribute.

**test\_number\_importers()**

Assert the repository has one importer.

**test\_read()**

Assert the repo update response has the requested changes.

**test\_status\_codes()**

Assert each response has a correct status code.

**test\_update()**

Assert the repo update response has the requested changes.

**static update\_body()**

Return a dict for updating a repository. Should be overridden.

**Raises** `NotImplementedError` if not implemented by a child class.

**class** `pulp_smash.utils.BaseAPITestCase` (*methodName='runTest'*)

A class with behaviour that is of use in many API test cases.

This test case provides set-up and tear-down behaviour that is common to many API test cases. It is not necessary to use this class as the parent of all API test cases, but it serves well in many cases.

**classmethod** `setUpClass()`

Provide a server config and an iterable of resources to delete.

The following class attributes are created this method:

**cfg** A `pulp_smash.config.PulpSmashConfig` object.

**resources** A set object. If a child class creates some resources that should be deleted when the test is complete, the child class should add that resource's href to this set.

**classmethod** `tearDownClass()`

Delete all resources named by `resources`.

**class** `pulp_smash.utils.DuplicateUploadsMixin`

A mixin that adds tests for the “duplicate upload” test cases.

Consider the following procedure:

1. Create a new feed-less repository of any content unit type.
2. Upload a content unit into the repository.
3. Upload the same content unit into the same repository.

The second upload should silently fail for all Pulp releases in the 2.x series. See:

- <https://pulp.plan.io/issues/1406>
- <https://github.com/PulpQE/pulp-smash/issues/81>

This mixin adds tests for this case. Child classes should do the following:

- Create a repository. Content units will be uploaded into this repository.
- Create a class or instance attribute named `upload_import_unit_args`. It should be an iterable whose contents match the signature of `upload_import_unit()`.

**test\_01\_first\_upload()**

Upload a content unit to a repository.

**test\_02\_second\_upload()**

Upload the same content unit to the same repository.

**class** `pulp_smash.utils.SmokeTest`

A class for identifying smoke tests.

Classes that inherit from this class are considered smoke tests, and may be returned by Pulp Smash's CLI. (See `pulp_smash.pulp_smash_cli`.)

`pulp_smash.utils.get_broker` (*server\_config*)

Build an object for managing the target system's AMQP broker.

Talk to the host named by `server_config` and use simple heuristics to determine which AMQP broker is installed. If Qpid or RabbitMQ appear to be installed, return the name of that service. Otherwise, raise an exception.

**Parameters** `server_config` (`pulp_smash.config.PulpSmashConfig`) – Information about the system on which an AMQP broker exists.

**Returns** A string such as ‘qpid’ or ‘rabbitmq’.

**Raises** `pulp_smash.exceptions.NoKnownBrokerError` – If unable to find any AMQP brokers on the target system.

`pulp_smash.utils.get_sha256_checksum(url)`

Return the sha256 checksum of the file at the given URL.

When a URL is encountered for the first time, do the following:

1. Download the file and calculate its sha256 checksum.
2. Cache the URL-checksum pair.
3. Return the checksum.

On subsequent calls, return a cached checksum.

`pulp_smash.utils.http_get(url, **kwargs)`

Issue a HTTP request to the `url` and return the response content.

This is useful for downloading file contents over HTTP[S].

**Parameters**

- `url` – the URL where the content should be get.
- `kwargs` – additional kwargs to be passed to `requests.get`.

**Returns** the response content of a GET request to `url`.

`pulp_smash.utils.os_is_f26(cfg, pulp_system=None)`

Return True if the server runs Fedora 26, or False otherwise.

**Parameters**

- `cfg` (`pulp_smash.config.PulpSmashConfig`) – Information about the system being targeted.
- `pulp_system` – A `pulp_smash.config.PulpSystem` to target, instead of the default chosen by `pulp_smash.cli.Client`.

**Returns** True or false.

`pulp_smash.utils.os_is_f27(cfg, pulp_system=None)`

Return True if the server runs Fedora 27, or False otherwise.

**Parameters**

- `cfg` (`pulp_smash.config.PulpSmashConfig`) – Information about the system being targeted.
- `pulp_system` – A `pulp_smash.config.PulpSystem` to target, instead of the default chosen by `pulp_smash.cli.Client`.

**Returns** True or false.

`pulp_smash.utils.publish_repo(cfg, repo, json=None)`

Publish a repository.



**Parameters**

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about the Pulp host.
- **repo** – A dict of detailed information about the repository to be published.
- **json** – Data to be encoded as JSON and sent as the request body. Defaults to `{'id': repo['distributors'][0]['id']}`.

**Raises** `ValueError` when `json` is not passed, and `repo` does not have exactly one distributor.

**Returns** The server's reponse. Call `.json()` on the response to get a call report.

`pulp_smash.utils.pulp_admin_login(server_config)`

Execute `pulp-admin login`.

**Parameters** **server\_config** (`pulp_smash.config.PulpSmashConfig`) – Information about the Pulp server being targeted.

**Returns** The completed process.

**Return type** `pulp_smash.cli.CompletedProcess`

`pulp_smash.utils.reset_pulp(server_config)`

Stop Pulp, reset its database, remove certain files, and start it.

**Parameters** **server\_config** (`pulp_smash.config.PulpSmashConfig`) – Information about the Pulp server being targeted.

**Returns** Nothing.

`pulp_smash.utils.reset_squid(cfg)`

Stop Squid, reset its cache directory, and restart it.

**Parameters** **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about a Pulp host.

**Returns** Nothing.

`pulp_smash.utils.search_units(cfg, repo, criteria=None, response_handler=None)`

Find content units in a `repo`.

**Parameters**

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about the Pulp host.
- **repo** – A dict of detailed information about the repository.
- **criteria** – A dict of criteria to pass in the search body. Defaults to an empty dict.
- **response\_handler** – The callback function used by `pulp_smash.api.Client` after searching. Defaults to `pulp_smash.api.json_handler()`.

**Returns** Whatever is dictated by `response_handler`.

`pulp_smash.utils.sync_repo(cfg, repo)`

Sync a repository.

**Parameters**

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about the Pulp host.
- **repo** – A dict of detailed information about the repository to be synced.

**Returns** The server's reponse. Call `.json()` on the response to get a call report.

`pulp_smash.utils.upload_import_erratum(server_config, erratum, repo_href)`

Upload an erratum to a Pulp server and import it into a repository.

For most content types, use `upload_import_unit()`.

#### Parameters

- **server\_config** (`pulp_smash.config.PulpSmashConfig`) – Information about the Pulp server being targeted.
- **erratum** – A dict, with keys such as “id,” “status,” “issued,” and “references.”
- **repo\_href** – The path to the repository into which `erratum` will be imported.

**Returns** The call report returned when importing the erratum.

`pulp_smash.utils.upload_import_unit(cfg, unit, import_params, repo)`

Upload a content unit to a Pulp server and import it into a repository.

This procedure only works for some unit types, such as `rpm` or `python_package`. Others, like `package_group`, require an alternate procedure. The procedure encapsulated by this function is as follows:

1. Create an upload request.
2. Upload the content unit to Pulp, in small chunks.
3. Import the uploaded content unit into a repository.
4. Delete the upload request.

The default set of parameters sent to Pulp during step 3 are:

```
{'unit_key': {}, 'upload_id': '...'}
```

The actual parameters required by Pulp depending on the circumstances, and the parameters sent to Pulp may be customized via the `import_params` argument. For example, if uploading a Python content unit, `import_params` should be the following:

```
{'unit_key': {'filename': '...'}, 'unit_type_id': 'python_package'}
```

This would result in the following upload parameters being used:

```
{
  'unit_key': {'filename': '...'},
  'unit_type_id': 'python_package',
  'upload_id': '...',
}
```

#### Parameters

- **cfg** (`pulp_smash.config.PulpSmashConfig`) – Information about a Pulp host.
- **unit** – The unit to be uploaded and imported, as a binary blob.
- **import\_params** – A dict of parameters to be merged into the default set of import parameters during step 3.
- **repo** – A dict of information about the target repository.

**Returns** The call report returned when importing the unit.

`pulp_smash.utils.uuid4()`

Return a random UUID4 as a string.

## 6.147 tests

Location: *Pulp Smash* → *API Documentation* → *tests*

Unit tests for Pulp Smash.

This package and its sub-packages contain tests for Pulp Smash. These tests verify that Pulp Smash's internal functions and libraries function correctly.

These tests are entirely different from the tests in *pulp\_smash.tests*.

## 6.148 tests.test\_api

Location: *Pulp Smash* → *API Documentation* → *tests.test\_api*

Unit tests for *pulp\_smash.api*.

**class** `tests.test_api.ClientTestCase` (*methodName='runTest'*)

Tests for *pulp\_smash.api.Client*.

**classmethod** `setUpClass()`

Assert methods delegate to *pulp\_smash.api.Client.request()*.

All methods on *pulp\_smash.api.Client*, such as *pulp\_smash.api.Client.delete()*, should delegate to *pulp\_smash.api.Client.request()*. Mock out `request` and call the other methods.

**test\_called\_once()**

Assert each method calls `request` exactly once.

**test\_http\_action()**

Assert each method calls `request` with the right HTTP action.

**class** `tests.test_api.ClientTestCase2` (*methodName='runTest'*)

More tests for *pulp\_smash.api.Client*.

**test\_json\_arg()**

Assert methods with a `json` argument pass on that argument.

**test\_response\_handler()**

Assert `__init__` saves the `response_handler` argument.

The argument should be saved as an instance attribute.

**class** `tests.test_api.CodeHandlerTestCase` (*methodName='runTest'*)

Tests for *pulp\_smash.api.code\_handler()*.

**test\_202\_check\_skipped()**

Assert HTTP 202 responses are not treated specially.

**test\_raise\_for\_status()**

Assert `response.raise_for_status()` is called.

**test\_return()**

Assert the passed-in `response` is returned.

**class** `tests.test_api.EchoHandlerTestCase` (*methodName='runTest'*)

Tests for *pulp\_smash.api.echo\_handler()*.

**test\_202\_check\_skipped()**

Assert HTTP 202 responses are not treated specially.

**test\_raise\_for\_status()**  
Assert `response.raise_for_status()` is not called.

**test\_return()**  
Assert the passed-in response is returned.

**class tests.test\_api.JsonHandlerTestCase** (*methodName='runTest'*)  
Tests for `pulp_smash.api.json_handler()`.

**test\_202\_check\_run()**  
Assert HTTP 202 responses are treated specially.

**test\_204\_check\_run()**  
Assert HTTP 204 responses are treated specially.

**test\_raise\_for\_status()**  
Assert `response.raise_for_status()` is called.

**test\_return()**  
Assert the JSON-decoded body of response is returned.

**class tests.test\_api.SafeHandlerTestCase** (*methodName='runTest'*)  
Tests for `pulp_smash.api.safe_handler()`.

**test\_202\_check\_run()**  
Assert HTTP 202 responses are treated specially.

**test\_raise\_for\_status()**  
Assert `response.raise_for_status()` is called.

**test\_return()**  
Assert the passed-in response is returned.

## 6.149 *tests.test\_cli*

Location: *Pulp Smash* → *API Documentation* → *tests.test\_cli*

Unit tests for `pulp_smash.cli`.

**class tests.test\_cli.ClientTestCase** (*methodName='runTest'*)  
Tests for `pulp_smash.cli.Client`.

**test\_default\_response\_handler()**  
Assert the default response handler checks return codes.

**test\_explicit\_local\_transport()**  
Assert it is possible to explicitly ask for a “local” transport.

**test\_explicit\_pulp\_system()**  
Assert it is possible to explicitly target a pulp cli PulpSystem.

**test\_explicit\_response\_handler()**  
Assert it is possible to explicitly set a response handler.

**test\_implicit\_local\_transport()**  
Assert it is possible to implicitly ask for a “local” transport.

**test\_implicit\_pulp\_system()**  
Assert it is possible to implicitly target a pulp cli PulpSystem.

**class tests.test\_cli.CodeHandlerTestCase** (*methodName='runTest'*)  
Tests for `pulp_smash.cli.code_handler()`.

```

classmethod setUpClass()
    Call the function under test, and record inputs and outputs.

test_check_returncode()
    Assert completed_proc.check_returncode() is not called.

test_input_returned()
    Assert the passed-in completed_proc is returned.

class tests.test_cli.CompletedProcessTestCase (methodName='runTest')
    Tests for pulp_smash.cli.CompletedProcess.

    setUp()
        Generate kwargs that can be used to instantiate a completed proc.

    test_can_eval()
        Assert __repr__() can be parsed by eval().

    test_check_returncode_nonzero()
        Call check_returncode when returncode is not zero.

    test_check_returncode_zero()
        Call check_returncode when returncode is zero.

    test_init()
        Assert all constructor arguments are saved as instance attrs.

class tests.test_cli.EchoHandlerTestCase (methodName='runTest')
    Tests for pulp_smash.cli.echo_handler().

    classmethod setUpClass()
        Call the function under test, and record inputs and outputs.

    test_check_returncode()
        Assert completed_proc.check_returncode() is not called.

    test_input_returned()
        Assert the passed-in completed_proc is returned.

```

## 6.150 *tests.test\_config*

Location: *Pulp Smash* → *API Documentation* → *tests.test\_config*

Unit tests for `pulp_smash.config`.

```

class tests.test_config.ConvertOldConfigTestCase (methodName='runTest')
    Test pulp_smash.config.convert_old_config().

    test_convert_old_config()
        Assert the conversion works.

class tests.test_config.GetConfigFilePathTestCase (methodName='runTest')
    Test pulp_smash.PulpSmashConfig.get_config_file_path.

    test_failures()
        Assert the method raises an exception when no config is found.

    test_success()
        Assert the method returns a path when a config file is found.

class tests.test_config.GetConfigTestCase (methodName='runTest')
    Test pulp_smash.config.get_config().

```

**test\_cache\_empty()**  
A config is read from disk if the cache is empty.

**test\_cache\_full()**  
No config is read from disk if the cache is populated.

**class tests.test\_config.GetRequestsKwargsTestCase** (*methodName='runTest'*)  
Test `pulp_smash.config.PulpSmashConfig.get_requests_kwargs()`.

**classmethod setUpClass()**  
Create a mock server config and call the method under test.

**test\_cfg\_auth()**  
Assert that the method does not alter the config's auth.

**test\_kwargs()**  
Assert that the method returns correct values.

**test\_kwargs\_auth()**  
Assert that the method converts auth to a tuple.

**class tests.test\_config.HelperMethodsTestCase** (*methodName='runTest'*)  
Test `pulp_smash.config.PulpSmashConfig()` helper methods.

**setUp()**  
Generate contents for a configuration file.

**test\_get\_systems()**  
`get_systems` returns proper result.

**test\_services\_for\_roles()**  
`services_for_roles` returns proper result.

**class tests.test\_config.InitTestCase** (*methodName='runTest'*)  
Test `pulp_smash.config.PulpSmashConfig` instantiation.

**classmethod setUpClass()**  
Generate some attributes and use them to instantiate a config.

**test\_private\_attrs()**  
Assert that private attributes have been set.

**test\_public\_attrs()**  
Assert that public attributes have correct values.

**class tests.test\_config.PulpSmashConfigFileTestCase** (*methodName='runTest'*)  
Verify the `PULP_SMASH_CONFIG_FILE` environment var is respected.

**test\_var\_set()**  
Set the environment variable.

**test\_var\_unset()**  
Do not set the environment variable.

**class tests.test\_config.ReadTestCase** (*methodName='runTest'*)  
Test `pulp_smash.config.PulpSmashConfig.read()`.

**test\_read\_config\_file()**  
Ensure Pulp Smash can read the config file.

**test\_read\_old\_config\_file()**  
Ensure Pulp Smash can read old config file format.

```

class tests.test_config.ReprTestCase (methodName='runTest')
    Test calling repr on a pulp_smash.config.PulpSmashConfig.

    classmethod setUpClass ()
        Generate attributes and call the method under test.

    test_can_eval ()
        Assert that the result can be parsed by eval.

    test_is_sane ()
        Assert that the result is in an expected set of results.

class tests.test_config.ValidateConfigTestCase (methodName='runTest')
    Test pulp_smash.config.validate_config ().

    test_config_missing_roles ()
        Missing required roles in config raises an exception.

    test_invalid_config ()
        An invalid config raises an exception.

    test_valid_config ()
        A valid config does not raise an exception.

```

## 6.151 *tests.test\_pulp\_smash\_cli*

Location: *Pulp Smash* → *API Documentation* → *tests.test\_pulp\_smash\_cli*

Unit tests for *pulp\_smash.pulp\_smash\_cli*.

```

class tests.test_pulp_smash_cli.BasePulpSmashCliTestCase (methodName='runTest')
    Base class for all pulp_smash_cli tests.

    setUp ()
        Configure a CliRunner.

class tests.test_pulp_smash_cli.MissingSettingsFileMixin
    Test missing settings file.

    Classes that inherit from this mixin should provide the settings_subcommand attribute set to the settings
    subcommand to run.

    test_missing_settings_file ()
        Ensure show outputs proper settings file.

class tests.test_pulp_smash_cli.SettingsCreateTestCase (methodName='runTest')
    Test pulp_smash.pulp_smash_cli.settings_create command.

    setUp ()
        Generate a default expected config dict.

    test_create_defaults_and_verify ()
        Create settings file with defaults and custom SSL certificate.

    test_create_other_values ()
        Create settings file with custom values.

    test_create_with_defaults ()
        Create settings file with default values values.

    test_settings_already_exists ()
        Create settings file by overriding existing one.

```

```
class tests.test_pulp_smash_cli.SettingsPathTestCase (methodName='runTest')
    Test pulp_smash.pulp_smash_cli.settings_path command.

    test_settings_path()
        Ensure path outputs proper settings file path.

class tests.test_pulp_smash_cli.SettingsShowTestCase (methodName='runTest')
    Test pulp_smash.pulp_smash_cli.settings_show command.

    test_settings_show()
        Ensure show outputs proper settings file.

class tests.test_pulp_smash_cli.SettingsValidateTestCase (methodName='runTest')
    Test pulp_smash.pulp_smash_cli.settings_validate command.

    test_invalid_config()
        Ensure validate fails on invalid config file schema.

    test_old_config_alert()
        Ensure validate notifies about the old config format.

    test_valid_config()
        Ensure validate does not complain about valid settings.

class tests.test_pulp_smash_cli.SmokeTestsTestCase (methodName='runTest')
    Test pulp_smash.pulp_smash_cli.smoke_tests command.

    test_all()
        Execute the CLI command.

        Assert that each line of output names a test case, and each of those test cases inherits from pulp_smash.
        utils.SmokeTest.
```

## 6.152 *tests.test\_selectors*

Location: *Pulp Smash* → *API Documentation* → *tests.test\_selectors*

Unit tests for *pulp\_smash.selectors*.

```
class tests.test_selectors.BugIsTestableTestCase (methodName='runTest')
    Test pulp_smash.selectors.bug_is_testable() and its partner.

    test_connection_error()
        Make the dependent function raise a connection error.

    test_testable_status()
        Assert the method correctly handles “testable” bug statuses.

    test_unknown_status()
        Assert the method correctly handles an unknown bug status.

    test_untestable_status()
        Assert the method correctly handles “untestable” bug statuses.

class tests.test_selectors.ConvertTPRTestCase (methodName='runTest')
    Test method_convert_tpr.

    test_empty_version_string()
        Assert version_string is converted if it is an empty string.

    test_invalid_version_string()
        Assert an exception is raised if version_string is invalid.
```



**test\_valid\_version\_string()**  
Assert `version_string` is converted if it is valid.

**class** `tests.test_selectors.GetBugTestCase` (*methodName='runTest'*)  
Test method `_get_bug`.

**test\_invalid\_bug\_id()**  
Assert an exception is raised if `bug_id` isn't an integer.

**class** `tests.test_selectors.GetTPRTestCase` (*methodName='runTest'*)  
Test method `_get_tpr`.

**test\_failure()**  
Assert the method raises the correct exception no TPR is present.

**test\_success()**  
Assert the method returns the target platform release if present.

## 6.153 *tests.test\_utils*

Location: *Pulp Smash* → *API Documentation* → *tests.test\_utils*

Unit tests for *pulp\_smash.utils*.

**class** `tests.test_utils.BaseAPITestCase` (*methodName='runTest'*)  
Test *pulp\_smash.utils.BaseAPITestCase*.

**classmethod** `setUpClass()`  
Define a child class. Call `setup` and `teardown` methods on it.

We define a child class in order to avoid altering *pulp\_smash.utils.BaseAPITestCase*. Calling class methods on it would do so.

**test\_set\_up\_class()**  
Assert method `setUpClass` creates correct class attributes.

Verify that the method creates attributes named `cfg` and `resources`.

**test\_tear\_down\_class()**  
Call method `tearDownClass`, and assert it deletes each resource.

*pulp\_smash.api.Client.delete()* should be called once for each resource listed in `resources`, and once for *pulp\_smash.tests.pulp2.constants.ORPHANS\_PATH*.

**class** `tests.test_utils.GetBrokerTestCase` (*methodName='runTest'*)  
Test *pulp\_smash.utils.get\_broker()*.

**test\_failure()**  
Fail to generate a broker service management object.

Assert that *pulp\_smash.exceptions.NoKnownBrokerError* is raised if the function cannot find a broker.

**test\_success()**  
Successfully generate a broker service management object.

Assert that:

- `get_broker(...)` returns a string.
- The `server_config` argument is passed to the service object.
- The “qpidd” broker is the preferred broker.

```
class tests.test_utils.GetSha256ChecksumTestCase (methodName='runTest')
    Test pulp_smash.utils.get_sha256_checksum().

    test_all ()
        Call the function three times, with two URLs.

        Call the function with the first URL, the second URL and the first URL again. Verify that:

        

- No download is attempted during the third call.
- The first and second calls return different checksums.
- The first and third calls return identical checksums.

class tests.test_utils.IsRootTestCase (methodName='runTest')
    Test pulp_smash.utils.is_root.

    test_false ()
        Assert the method returns False when non-root.

    test_true ()
        Assert the method returns True when root.

class tests.test_utils.OsIsF26TestCase (methodName='runTest')
    Test pulp_smash.utils.os_is_f26().

    test_returncode_nonzero ()
        Assert false is returned if the CLI command returns non-zero.

    test_returncode_zero ()
        Assert true is returned if the CLI command returns zero.

class tests.test_utils.PulpAdminLoginTestCase (methodName='runTest')
    Test pulp_smash.utils.pulp_admin_login().

    test_run ()
        Assert the function executes cli.Client.run.

class tests.test_utils.SearchUnitsTestCase (methodName='runTest')
    Test pulp_smash.utils.search_units().

    test_defaults ()
        Verify that default parameters are correctly set.

class tests.test_utils.SyncRepoTestCase (methodName='runTest')
    Test pulp_smash.utils.sync_repo().

    test_post ()
        Assert the function makes an HTTP POST request.

class tests.test_utils.UUID4TestCase (methodName='runTest')
    Test pulp_smash.utils.uuid4().

    test_type ()
        Assert the method returns a unicode string.

class tests.test_utils.UploadImportErratumTestCase (methodName='runTest')
    Test pulp_smash.utils.upload_import_unit().

    test_post ()
        Assert the function makes an HTTP POST request.

class tests.test_utils.UploadImportUnitTestCase (methodName='runTest')
    Test pulp_smash.utils.upload_import_unit().
```

**test\_post** ()

Assert the function makes an HTTP POST request.



---

## Python Module Index

---

### p

pulp\_smash, 19  
pulp\_smash.api, 19  
pulp\_smash.cli, 23  
pulp\_smash.config, 27  
pulp\_smash.constants, 31  
pulp\_smash.exceptions, 37  
pulp\_smash.pulp\_smash\_cli, 38  
pulp\_smash.selectors, 38  
pulp\_smash.tests, 39  
pulp\_smash.tests.pulp2, 41  
pulp\_smash.tests.pulp2.constants, 41  
pulp\_smash.tests.pulp2.docker, 42  
pulp\_smash.tests.pulp2.docker.api\_v2, 42  
pulp\_smash.tests.pulp2.docker.api\_v2.test\_copy, 42  
pulp\_smash.tests.pulp2.docker.api\_v2.test\_crud, 43  
pulp\_smash.tests.pulp2.docker.api\_v2.test\_duplicate\_uploads, 44  
pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync, 44  
pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync\_publish, 45  
pulp\_smash.tests.pulp2.docker.api\_v2.test\_tags, 48  
pulp\_smash.tests.pulp2.docker.api\_v2.test\_upload, 49  
pulp\_smash.tests.pulp2.docker.api\_v2.utils, 50  
pulp\_smash.tests.pulp2.docker.cli, 51  
pulp\_smash.tests.pulp2.docker.cli.test\_crud, 51  
pulp\_smash.tests.pulp2.docker.cli.test\_sync\_publish, 53  
pulp\_smash.tests.pulp2.docker.cli.utils, 53  
pulp\_smash.tests.pulp2.docker.utils, 54  
pulp\_smash.tests.pulp2.ostree, 54  
pulp\_smash.tests.pulp2.ostree.api\_v2, 54  
pulp\_smash.tests.pulp2.ostree.api\_v2.test\_copy, 54  
pulp\_smash.tests.pulp2.ostree.api\_v2.test\_crud, 55  
pulp\_smash.tests.pulp2.ostree.api\_v2.test\_publish, 57  
pulp\_smash.tests.pulp2.ostree.api\_v2.test\_sync, 57  
pulp\_smash.tests.pulp2.ostree.utils, 58  
pulp\_smash.tests.pulp2.platform, 58  
pulp\_smash.tests.pulp2.platform.api\_v2, 58  
pulp\_smash.tests.pulp2.platform.api\_v2.test\_consume, 59  
pulp\_smash.tests.pulp2.platform.api\_v2.test\_content, 59  
pulp\_smash.tests.pulp2.platform.api\_v2.test\_login, 60  
pulp\_smash.tests.pulp2.platform.api\_v2.test\_repository, 60  
pulp\_smash.tests.pulp2.platform.api\_v2.test\_search, 62  
pulp\_smash.tests.pulp2.platform.api\_v2.test\_user, 64  
pulp\_smash.tests.pulp2.platform.cli, 66  
pulp\_smash.tests.pulp2.platform.cli.test\_pulp\_manage, 66  
pulp\_smash.tests.pulp2.platform.cli.test\_selinux, 67  
pulp\_smash.tests.pulp2.platform.utils, 68  
pulp\_smash.tests.pulp2.puppet, 68  
pulp\_smash.tests.pulp2.puppet.api\_v2, 68  
pulp\_smash.tests.pulp2.puppet.api\_v2.test\_crud, 69  
pulp\_smash.tests.pulp2.puppet.api\_v2.test\_duplicate

69	pulp_smash.tests.pulp2.puppet.api_v2.test_no_op_publication	96	pulp_smash.tests.pulp2.rpm.api_v2.test_no_op_publication
69	pulp_smash.tests.pulp2.puppet.api_v2.test_orphan_removal	98	pulp_smash.tests.pulp2.rpm.api_v2.test_orphan_removal
70	pulp_smash.tests.pulp2.puppet.api_v2.utils	99	pulp_smash.tests.pulp2.rpm.api_v2.test_package_path
72	pulp_smash.tests.pulp2.puppet.cli, 72	100	pulp_smash.tests.pulp2.rpm.api_v2.test_remove_unit
	pulp_smash.tests.pulp2.puppet.cli.test_sync,	101	pulp_smash.tests.pulp2.rpm.api_v2.test_repomd,
73	pulp_smash.tests.pulp2.puppet.utils, 74	103	pulp_smash.tests.pulp2.rpm.api_v2.test_repository
	pulp_smash.tests.pulp2.python, 74	104	pulp_smash.tests.pulp2.rpm.api_v2.test_repoview,
	pulp_smash.tests.pulp2.python.api_v2,	105	pulp_smash.tests.pulp2.rpm.api_v2.test_republish,
74	pulp_smash.tests.pulp2.python.api_v2.test_crud,	105	pulp_smash.tests.pulp2.rpm.api_v2.test_retain_old_content,
74	pulp_smash.tests.pulp2.python.api_v2.test_duplicate_uploads,	106	pulp_smash.tests.pulp2.rpm.api_v2.test_republish,
74	pulp_smash.tests.pulp2.python.api_v2.test_sync_publish,	107	pulp_smash.tests.pulp2.rpm.api_v2.test_rsync_distribution,
75	pulp_smash.tests.pulp2.python.api_v2.utils,	107	pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_publication,
76	pulp_smash.tests.pulp2.python.utils, 76	111	pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_sync,
	pulp_smash.tests.pulp2.rpm, 76	112	pulp_smash.tests.pulp2.rpm.api_v2.test_search,
	pulp_smash.tests.pulp2.rpm.api_v2, 77	114	pulp_smash.tests.pulp2.rpm.api_v2.test_service_resources,
	pulp_smash.tests.pulp2.rpm.api_v2.test_broker,	115	pulp_smash.tests.pulp2.rpm.api_v2.test_signatures,
77	pulp_smash.tests.pulp2.rpm.api_v2.test_content_metadata,	116	pulp_smash.tests.pulp2.rpm.api_v2.test_signatures,
78	pulp_smash.tests.pulp2.rpm.api_v2.test_content_metadata,	118	pulp_smash.tests.pulp2.rpm.api_v2.test_signatures,
78	pulp_smash.tests.pulp2.rpm.api_v2.test_content_metadata,	121	pulp_smash.tests.pulp2.rpm.api_v2.test_signatures,
81	pulp_smash.tests.pulp2.rpm.api_v2.test_content_metadata,	124	pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publication,
82	pulp_smash.tests.pulp2.rpm.api_v2.test_content_metadata,	125	pulp_smash.tests.pulp2.rpm.api_v2.test_tasks,
83	pulp_smash.tests.pulp2.rpm.api_v2.test_content_metadata,	128	pulp_smash.tests.pulp2.rpm.api_v2.test_unassociate,
84	pulp_smash.tests.pulp2.rpm.api_v2.test_content_metadata,	128	pulp_smash.tests.pulp2.rpm.api_v2.test_unavailable,
85	pulp_smash.tests.pulp2.rpm.api_v2.test_content_metadata,	130	pulp_smash.tests.pulp2.rpm.api_v2.test_updateinfo,
88	pulp_smash.tests.pulp2.rpm.api_v2.test_content_metadata,	131	pulp_smash.tests.pulp2.rpm.api_v2.test_upload_publication,
89	pulp_smash.tests.pulp2.rpm.api_v2.test_content_metadata,	135	pulp_smash.tests.pulp2.rpm.api_v2.test_upload_publication,
90	pulp_smash.tests.pulp2.rpm.api_v2.test_content_metadata,	138	pulp_smash.tests.pulp2.rpm.api_v2.test_upload_publication,
92	pulp_smash.tests.pulp2.rpm.api_v2.test_content_metadata,	141	pulp_smash.tests.pulp2.rpm.cli, 141
93	pulp_smash.tests.pulp2.rpm.api_v2.test_content_metadata,		pulp_smash.tests.pulp2.rpm.cli.test_character_encoding,
95	pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlists,		

pulp\_smash.tests.pulp2.rpm.cli.test\_copy\_pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_crud\_artifacts, 142

pulp\_smash.tests.pulp2.rpm.cli.test\_environment\_pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_crud\_distribution, 144

pulp\_smash.tests.pulp2.rpm.cli.test\_language\_packages\_pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_crud\_repository, 144

pulp\_smash.tests.pulp2.rpm.cli.test\_process\_pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_crud\_user, 145

pulp\_smash.tests.pulp2.rpm.cli.test\_retain\_pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_status, 145

pulp\_smash.tests.pulp2.rpm.cli.test\_search\_pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_workers, 146

pulp\_smash.tests.pulp2.rpm.cli.test\_sync\_pulp\_smash.tests.pulp3.pulpcore.utils, 147

pulp\_smash.tests.pulp2.rpm.cli.test\_upload\_pulp\_smash.tests.pulp3.utils, 165  
pulp\_smash.utils, 168

pulp\_smash.tests.pulp2.rpm.cli.utils, 148

pulp\_smash.tests.pulp2.rpm.utils, 149

pulp\_smash.tests.pulp2.utils, 150

pulp\_smash.tests.pulp3, 150

pulp\_smash.tests.pulp3.constants, 150

pulp\_smash.tests.pulp3.file, 151

pulp\_smash.tests.pulp3.file.api\_v3, 151

pulp\_smash.tests.pulp3.file.api\_v3.test\_crud\_publications, 151

pulp\_smash.tests.pulp3.file.api\_v3.test\_crud\_content\_unit, 151

pulp\_smash.tests.pulp3.file.api\_v3.test\_crud\_publishers, 152

pulp\_smash.tests.pulp3.file.api\_v3.test\_crud\_remotes, 153

pulp\_smash.tests.pulp3.file.api\_v3.test\_download\_content, 154

pulp\_smash.tests.pulp3.file.api\_v3.test\_orphans, 154

pulp\_smash.tests.pulp3.file.api\_v3.test\_publish, 155

pulp\_smash.tests.pulp3.file.api\_v3.test\_repo\_version, 155

pulp\_smash.tests.pulp3.file.api\_v3.test\_sync, 157

pulp\_smash.tests.pulp3.file.api\_v3.test\_unlinking\_repo, 158

pulp\_smash.tests.pulp3.file.api\_v3.utils, 159

pulp\_smash.tests.pulp3.file.utils, 159

pulp\_smash.tests.pulp3.pulpcore, 159

pulp\_smash.tests.pulp3.pulpcore.api\_v3, 159

pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_api\_docs, 159

pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_auth, 160

**t**

tests, 173

tests.test\_api, 173

tests.test\_cli, 174

tests.test\_config, 175

tests.test\_pulp\_smash\_cli, 177

tests.test\_selectors, 178

tests.test\_publications, 179







BaseAPITestCase (class in tests.test\_utils), 179

BaseExportChecksumTypeTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_export), 90

BasePulpSmashCliTestCase (class in tests.test\_pulp\_smash\_cli), 177

BaseSearchTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_search), 114

BaseServiceManager (class in pulp\_smash.cli), 23

BaseTestCase (class in pulp\_smash.tests.pulp2.platform.cli.test\_pulp\_manage\_db), 66

BaseTestCase (class in pulp\_smash.tests.pulp2.python.api\_v2.test\_sync\_publish), 75

BaseTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_no\_op\_publish), 98

BasicTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_content\_applicability), 81

BindConsumerTestCase (class in pulp\_smash.tests.pulp2.platform.api\_v2.test\_consumer), 59

BrokerTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_broker), 77

bug\_is\_testable() (in module pulp\_smash.selectors), 38

bug\_is\_untestable() (in module pulp\_smash.selectors), 38

BugIsTestableTestCase (class in tests.test\_selectors), 178

BugStatusUnknownError, 37

BugTPRMissingError, 37

**C**

CALL\_REPORT\_KEYS (in module pulp\_smash.tests.pulp2.constants), 41

CalledProcessError, 37

CallReportError, 37

CELERY\_LABEL (in module pulp\_smash.tests.pulp2.platform.cli.test\_selinux), 67

change\_export\_dir\_owner() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_export\_dir\_owner.method), 91

ChangeFeedTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_sync\_publish), 125

ChangeRepoTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_no\_op\_publish), 98

check\_checksums() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_iso\_crud.ISOUpdateTestCase.method), 94

check\_issue\_2277() (in module pulp\_smash.tests.pulp2.rpm.utils), 149

check\_issue\_2277() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_mirrorlist.UpdateTestCase.method), 97

check\_issue\_2321() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_mirrorlist.UpdateTestCase.method), 97

check\_issue\_2326() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_mirrorlist.UpdateTestCase.method), 97

check\_issue\_2354() (in module pulp\_smash.tests.pulp2.rpm.utils), 149

check\_issue\_2363() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_mirrorlist.UpdateTestCase.method), 97

check\_issue\_2387() (in module pulp\_smash.tests.pulp2.rpm.utils), 149

check\_issue\_2620() (in module pulp\_smash.tests.pulp2.rpm.utils), 149

check\_issue\_2798() (in module pulp\_smash.tests.pulp2.rpm.utils), 149

check\_issue\_2844() (in module pulp\_smash.tests.pulp2.rpm.utils), 149

check\_issue\_3104() (in module pulp\_smash.tests.pulp2.rpm.utils), 149

check\_names() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_iso\_crud.ISOUpdateTestCase.method), 94

check\_one\_orphan\_deleted() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_orphan\_remove.OrphanRemoveTestCase.method), 99

check\_returncode() (pulp\_smash.cli.CompletedProcess.method), 24

CleanUpTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_updateinfo), 132

Client (class in pulp\_smash.api), 19

Client (class in pulp\_smash.cli), 23

ClientTestCase (class in tests.test\_api), 173

ClientTestCase (class in tests.test\_cli), 174

ClientTestCase2 (class in tests.test\_api), 173

code\_handler() (in module pulp\_smash.api), 22

code\_handler() (in module pulp\_smash.cli), 27

CodeHandlerTestCase (class in tests.test\_api), 173

CodeHandlerTestCase (class in tests.test\_cli), 174

CompletedProcess (class in pulp\_smash.cli), 24

CompletedProcessTestCase (class in tests.test\_cli), 175

CONFIG\_JSON\_SCHEMA (in module pulp\_smash.config), 28

ConfigFileNotFoundError, 37

ConfigFileSectionNotFoundError, 37

ConfigValidationError, 37

CONFLICTING\_SERVICES (in module pulp\_smash.tests.pulp2.platform.cli.test\_pulp\_manage\_db), 66

CONSUMERS\_ACTIONS\_CONTENT\_REGENERATE\_APPLICABILITY (in module pulp\_smash.tests.pulp2.constants), 41

CONSUMERS_CONTENT_APPLICABILITY_PATH (in module pulp_smash.tests.pulp2.constants), 41	create_body() (pulp_smash.tests.pulp2.python.api_v2.test_crud.CRUDTest static method), 74
CONSUMERS_PATH (in module pulp_smash.tests.pulp2.constants), 41	create_body() (pulp_smash.tests.pulp2.rpm.api_v2.test_crud.CrudTest static method), 84
CONTENT_APPLICABILITY_REPORT_SCHEMA (in module pulp_smash.tests.pulp2.rpm.api_v2.test_crud), 82	create_body() (pulp_smash.tests.pulp2.rpm.api_v2.test_crud.CrudWithFeed static method), 84
CONTENT_SOURCES_PATH (in module pulp_smash.tests.pulp2.constants), 41	create_content_applicability(pulp_smash.utils.BaseAPICrudTest static method), 168
CONTENT_UNITS_PATH (in module pulp_smash.tests.pulp2.constants), 41	create_docker_repo() (in module pulp_smash.tests.pulp2.docker.api_v2.test_tags), 48
CONTENT_UPLOAD_PATH (in module pulp_smash.tests.pulp2.constants), 41	create_export_dir() (pulp_smash.tests.pulp2.rpm.api_v2.test_export.Export method), 91
ContentImmutableRepoVersionTestCase (class in pulp_smash.tests.pulp3.file.api_v3.test_repo_versions), 157	create_repo() (pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist.UtilsMixi method), 97
ContentUnitTestCase (class in pulp_smash.tests.pulp3.file.api_v3.test_crud_content_unit), 151	create_repo() (pulp_smash.tests.pulp2.rpm.api_v2.test_package_paths.Reus method), 101
convert_old_config() (in module pulp_smash.config), 31	create_repo() (pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_sync.Crea class method), 113
ConvertOldConfigTestCase (class in tests.test_config), 175	create_repo() (pulp_smash.tests.pulp2.rpm.cli.test_copy_units.UtilsMixi method), 143
ConvertTPRTestCase (class in tests.test_selectors), 178	create_sync_publish_repo() (pulp_smash.tests.pulp2.docker.api_v2.utils.SyncPublishMixi method), 50
CopyErrataRecursiveTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_copy), 83	create_sync_publish_repo() (pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish.ChangeFe method), 125
CopyLangpacksTestCase (class in pulp_smash.tests.pulp2.rpm.cli.test_copy_units), 142	create_sync_repo() (pulp_smash.tests.pulp2.rpm.api_v2.test_retain_old_cou method), 106
CopyRecursiveTestCase (class in pulp_smash.tests.pulp2.rpm.cli.test_copy_units), 142	create_sync_repo() (pulp_smash.tests.pulp2.rpm.cli.test_retain_old_count.R method), 145
CopyTestCase (class in pulp_smash.tests.pulp2.rpm.cli.test_copy_units), 143	CreateDistributorsTestCase (class in pulp_smash.tests.pulp2.ostree.api_v2.test_crud), 55
CopyV1ContentTestCase (class in pulp_smash.tests.pulp2.docker.api_v2.test_copy), 42	CreateFailureTestCase (class in pulp_smash.tests.pulp2.platform.api_v2.test_repository), 60
CopyV2ContentTestCase (class in pulp_smash.tests.pulp2.docker.api_v2.test_copy), 42	CreateFailureTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_publish), 111
count_langpacks() (in module pulp_smash.tests.pulp2.rpm.cli.utils), 148	CreateFailureTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_sync), 112
create_body() (pulp_smash.tests.pulp2.docker.api_v2.test_crud.CrudTest static method), 43	CreateRepoMixin (class in pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_sync), 113
create_body() (pulp_smash.tests.pulp2.docker.api_v2.test_crud.CrudWithFeed static method), 43	CreateSuccessTestCase (class in pulp_smash.tests.pulp2.platform.api_v2.test_repository), 111
create_body() (pulp_smash.tests.pulp2.ostree.api_v2.test_crud.CrudTest static method), 56	CreateSuccessTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_publish), 111
create_body() (pulp_smash.tests.pulp2.ostree.api_v2.test_crud.CrudWithFeed static method), 56	CreateUnitTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_sync), 111
create_body() (pulp_smash.tests.pulp2.puppet.api_v2.test_crud.CrudTest static method), 69	

113		delete_orphans()	(in	module
CreateTestCase	(class	in	pulp_smash.tests.pulp3.utils), 165	
	pulp_smash.tests.pulp2.docker.cli.test_crud),	delete_repo_version()	(in	module
51		pulp_smash.tests.pulp3.utils), 165		
CreateTestCase	(class	in	delete_user() (pulp_smash.tests.pulp2.rpm.api_v2.utils.TemporaryUserMixi	
	pulp_smash.tests.pulp2.platform.api_v2.test_user),	static method), 139		
64		DeleteContentUnitRepoVersionTestCase	(class	in
CreateTestCase	(class	in	pulp_smash.tests.pulp3.file.api_v3.test_crud_content_unit),	
	pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish),	152		
70		DeleteOrphansTestCase	(class	in
CreateTestCase	(class	in	pulp_smash.tests.pulp3.file.api_v3.test_orphans),	
	pulp_smash.tests.pulp2.rpm.api_v2.test_iso_crud),	154		
94		DeleteTestCase	(class	in
CRUDDistributionsTestCase	(class	in	pulp_smash.tests.pulp2.rpm.api_v2.test_rsycn_distributor),	
	pulp_smash.tests.pulp3.pulpcore.api_v3.test_crud_distributi	168),		
162		DeleteV2TestCase	(class	in
CRUDPublishersTestCase	(class	in	pulp_smash.tests.pulp2.docker.cli.test_crud),	
	pulp_smash.tests.pulp3.file.api_v3.test_crud_publishers),	51		
152		DisableSELinuxMixin	(class	in
CRUDRemotesTestCase	(class	in	pulp_smash.tests.pulp2.rpm.api_v2.utils),	
	pulp_smash.tests.pulp3.file.api_v3.test_crud_remotes),	138		
153		do_fully_update_attr()	(pulp_smash.tests.pulp3.pulpcore.api_v3.test_crud_r	
CRUDRepoTestCase	(class	in	method), 162	
	pulp_smash.tests.pulp3.pulpcore.api_v3.test_crud_repos),	do_partially_update_attr()	(pulp_smash.tests.pulp3.pulpcore.api_v3.test_crud_repos.CRUDI	
162		method), 162		
CrudTestCase	(class	in	pulp_smash.tests.pulp2.docker.api_v2.test_crud),	
	do_remove_unit() (pulp_smash.tests.pulp2.rpm.api_v2.test_unassociate.Re	method), 128		
43		do_test() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.RepoRe		
CrudTestCase	(class	in	pulp_smash.tests.pulp2.ostree.api_v2.test_crud),	
	do_test() (pulp_smash.tests.pulp2.rpm.api_v2.test_duplicate_uploads.Dupli	method), 88		
56		do_test() (pulp_smash.tests.pulp2.rpm.api_v2.test_republish.RemoveOldRe		
CRUDTestCase	(class	in	pulp_smash.tests.pulp2.puppet.api_v2.test_crud),	
	do_test() (pulp_smash.tests.pulp2.rpm.api_v2.test_republish.RemoveOldRe	method), 106		
69		do_test() (pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish.SyncInvali		
CRUDTestCase	(class	in	pulp_smash.tests.pulp2.python.api_v2.test_crud),	
	do_test() (pulp_smash.tests.pulp2.rpm.api_v2.test_unassociate.RemoveUnit	method), 129		
74		do_test() (pulp_smash.tests.pulp2.rpm.api_v2.test_unavailable_checksum.U		
CrudTestCase	(class	in	pulp_smash.tests.pulp2.rpm.api_v2.test_crud),	
	do_test() (pulp_smash.tests.pulp2.rpm.api_v2.test_unavailable_checksum.U	method), 130		
84		do_test() (pulp_smash.tests.pulp2.rpm.api_v2.test_unavailable_checksum.U		
CrudWithFeedTestCase	(class	in	pulp_smash.tests.pulp2.docker.api_v2.test_crud),	
	do_test() (pulp_smash.tests.pulp2.rpm.api_v2.test_upload_publish.VendorIn	method), 131		
43		do_test() (pulp_smash.tests.pulp2.rpm.api_v2.test_upload_publish.VendorIn		
56		method), 138		
CrudWithFeedTestCase	(class	in	DOCKER_IMAGE_URL	(in
	pulp_smash.tests.pulp2.ostree.api_v2.test_crud),	pulp_smash.constants), 31		module
84		DOCKER_UPSTREAM_NAME	(in	module
CrudWithFeedTestCase	(class	in	pulp_smash.constants), 31	
	pulp_smash.tests.pulp2.rpm.api_v2.test_crud),	DOCKER_UPSTREAM_NAME_NOLIST	(in	module
84		pulp_smash.constants), 32		
<b>D</b>		DOCKER_V1_FEED_URL	(in	module
default_config_file_path	(pulp_smash.config.PulpSmashConfig	pulp_smash.constants), 32		
attribute), 29		DOCKER_V2_FEED_URL	(in	module
delete()	(pulp_smash.api.Client method), 21	pulp_smash.constants), 32		

- F**
- DockerTagTestCase (class in `pulp_smash.tests.pulp2.docker.api_v2.test_tags`), 48
  - DownloadContentTestCase (class in `pulp_smash.tests.pulp3.file.api_v3.test_download_content`), 154
  - DRPM (in module `pulp_smash.constants`), 32
  - DRPM\_SIGNED\_FEED\_COUNT (in module `pulp_smash.constants`), 32
  - DRPM\_SIGNED\_FEED\_URL (in module `pulp_smash.constants`), 32
  - DRPM\_SIGNED\_URL (in module `pulp_smash.constants`), 32
  - DRPM\_UNSIGNED\_FEED\_COUNT (in module `pulp_smash.constants`), 32
  - DRPM\_UNSIGNED\_FEED\_URL (in module `pulp_smash.constants`), 32
  - DRPM\_UNSIGNED\_URL (in module `pulp_smash.constants`), 32
  - DuplicateUploadsMixin (class in `pulp_smash.utils`), 169
  - DuplicateUploadsTestCase (class in `pulp_smash.tests.pulp2.docker.api_v2.test_duplicate_uploads`), 44
  - DuplicateUploadsTestCase (class in `pulp_smash.tests.pulp2.puppet.api_v2.test_duplicate_uploads`), 69
  - DuplicateUploadsTestCase (class in `pulp_smash.tests.pulp2.python.api_v2.test_duplicate_uploads`), 75
  - DuplicateUploadsTestCase (class in `pulp_smash.tests.pulp2.rpm.api_v2.test_duplicate_uploads`), 88
  - FailureTestCase (class in `pulp_smash.tests.pulp2.platform.api_v2.test_content_applicability`), 59
  - FastForwardIntegrityTestCase (class in `pulp_smash.tests.pulp2.rpm.api_v2.test_repodm`), 103
  - FeedURLUnquoteTestCase (class in `pulp_smash.tests.pulp2.rpm.api_v2.test_crud`), 84
  - FieldsTestCase (class in `pulp_smash.tests.pulp2.platform.api_v2.test_search`), 62
  - FieldTestCase (class in `pulp_smash.tests.pulp2.platform.api_v2.test_search`), 62
  - FILE2\_FEED\_URL (in module `pulp_smash.constants`), 32
  - FILE2\_URL (in module `pulp_smash.constants`), 32
  - FILE\_FEED\_COUNT (in module `pulp_smash.constants`), 32
  - FILE\_FEED\_URL (in module `pulp_smash.constants`), 32
  - FILE\_LARGE\_FEED\_URL (in module `pulp_smash.constants`), 32
  - FILE\_MASKED\_FEED\_URL (in module `pulp_smash.constants`), 33
  - FILE\_URL (in module `pulp_smash.constants`), 33
  - FileLabelsTestCase (class in `pulp_smash.tests.pulp2.platform.cli.test_selinux`), 67
  - FiltersIdTestCase (class in `pulp_smash.tests.pulp2.platform.api_v2.test_search`), 63
  - FilterTestCase (class in `pulp_smash.tests.pulp2.ostree.api_v2.test_copy`), 54
  - FixFileCorruptionTestCase (class in `pulp_smash.tests.pulp2.rpm.api_v2.test_download_policies`), 86
  - ForceFullTestCase (class in `pulp_smash.tests.pulp2.rpm.api_v2.test_force_full`), 93
  - ForceFullTestCase (class in `pulp_smash.tests.pulp2.rpm.api_v2.test_rsnc_distributor`), 109
  - ForceSyncTestCase (class in `pulp_smash.tests.pulp2.rpm.cli.test_sync`), 147
- E**
- echo\_handler() (in module `pulp_smash.api`), 22
  - echo\_handler() (in module `pulp_smash.cli`), 27
  - EchoHandlerTestCase (class in `tests.test_api`), 173
  - EchoHandlerTestCase (class in `tests.test_cli`), 175
  - ERROR\_KEYS (in module `pulp_smash.tests.pulp2.constants`), 41
  - ErrorReportTestCase (class in `pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish`), 126
  - ExportChecksumTypeTestCase (class in `pulp_smash.tests.pulp2.rpm.api_v2.test_export`), 90
  - ExportDirMixin (class in `pulp_smash.tests.pulp2.rpm.api_v2.test_export`), 91
  - ExportDistributorTestCase (class in `pulp_smash.tests.pulp2.rpm.api_v2.test_export`), 91
- G**
- gen\_commands() (`pulp_smash.tests.pulp2.rpm.cli.test_search.SearchRepos`), 191

static method), 146

gen\_distribution() (in module pulp\_smash.tests.pulp3.pulpcore.utils), 165

gen\_distributor() (in module pulp\_smash.tests.pulp2.docker.api\_v2.utils), 51

gen\_distributor() (in module pulp\_smash.tests.pulp2.ostree.utils), 58

gen\_distributor() (in module pulp\_smash.tests.pulp2.puppet.api\_v2.utils), 72

gen\_distributor() (in module pulp\_smash.tests.pulp2.python.api\_v2.utils), 76

gen\_distributor() (in module pulp\_smash.tests.pulp2.rpm.api\_v2.utils), 139

gen\_install\_distributor() (in module pulp\_smash.tests.pulp2.puppet.api\_v2.utils), 72

gen\_publisher() (in module pulp\_smash.tests.pulp3.file.api\_v3.utils), 159

gen\_remote() (in module pulp\_smash.tests.pulp3.file.api\_v3.utils), 159

gen\_repo() (in module pulp\_smash.tests.pulp2.docker.api\_v2.utils), 51

gen\_repo() (in module pulp\_smash.tests.pulp2.ostree.utils), 58

gen\_repo() (in module pulp\_smash.tests.pulp2.puppet.api\_v2.utils), 72

gen\_repo() (in module pulp\_smash.tests.pulp2.python.api\_v2.utils), 76

gen\_repo() (in module pulp\_smash.tests.pulp2.rpm.api\_v2.utils), 139

gen\_repo() (in module pulp\_smash.tests.pulp3.pulpcore.utils), 165

gen\_repo\_group() (in module pulp\_smash.tests.pulp2.rpm.api\_v2.utils), 139

gen\_yum\_config\_file() (in module pulp\_smash.tests.pulp2.rpm.utils), 149

get() (pulp\_smash.api.Client method), 21

get\_added\_content() (in module pulp\_smash.tests.pulp3.utils), 166

get\_artifact\_paths() (in module pulp\_smash.tests.pulp3.utils), 166

get\_auth() (in module pulp\_smash.tests.pulp3.utils), 166

get\_base\_url() (pulp\_smash.config.PulpSmashConfig method), 29

get\_broker() (in module pulp\_smash.utils), 169

get\_config() (in module pulp\_smash.config), 31

get\_config\_file\_path() (pulp\_smash.config.PulpSmashConfig method), 29

get\_content() (in module pulp\_smash.tests.pulp3.utils), 166

get\_content\_summary() (pulp\_smash.tests.pulp3.file.api\_v3.test\_repo\_versions method), 156

get\_content\_unit\_paths() (in module pulp\_smash.tests.pulp3.utils), 167

get\_details() (in module pulp\_smash.tests.pulp2.python.api\_v2.test\_sync\_publish), 76

get\_dists\_by\_type\_id() (in module pulp\_smash.tests.pulp2.rpm.api\_v2.utils), 139

get\_export\_entity() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_export.BaseExport method), 90

get\_export\_entity() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_export.Export method), 90

get\_export\_entity() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_export.RepoGroup method), 92

get\_export\_entity\_type() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_export.BaseExport method), 90

get\_export\_entity\_type() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_export.Export method), 90

get\_export\_entity\_type() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_export.RepoGroup method), 92

get\_feed() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_sync\_publish.ChangeFeed method), 126

get\_feed\_url() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_search.BaseSearcher static method), 114

get\_feed\_url() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_search.SearchForRepos static method), 114

get\_feed\_url() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_search.SearchForStreams static method), 115

get\_feed\_url() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_sync\_publish.SyncPublisher static method), 126

get\_feed\_url() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_sync\_publish.SyncPublisher static method), 127

get\_feed\_url() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_sync\_publish.SyncPublisher static method), 127

get\_feed\_url() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_sync\_publish.SyncPublisher static method), 128

get\_file\_hrefs() (in module pulp\_smash.tests.pulp2.rpm.api\_v2.test\_repository\_layout), 104

get\_latest\_tags() (pulp\_smash.tests.pulp2.docker.api\_v2.test\_tags.DockerTags method), 48

get\_manifests() (pulp\_smash.tests.pulp2.docker.api\_v2.test\_tags.DockerTags method), 48

get\_num\_processed() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_rsync\_distribution static method), 110

[get\\_num\\_units\\_in\\_repo\(\)](#) (in module `pulp_smash.tests.pulp2.puppet.cli.test_sync`), 73  
[get\\_package\\_hrefs\(\)](#) (in module `pulp_smash.tests.pulp2.rpm.api_v2.test_repository_layout`), 104  
[get\\_parse\\_repodata\\_primary\\_xml\(\)](#) (in module `pulp_smash.tests.pulp2.rpm.api_v2.test_repository_layout`), 104  
[get\\_parse\\_repodata\\_xml\(\)](#) (in module `pulp_smash.tests.pulp2.rpm.api_v2.test_repository_layout`), 104  
[get\\_plugins\(\)](#) (in module `pulp_smash.tests.pulp3.utils`), 167  
[get\\_pulp\\_worker\\_procs\(\)](#) (in module `pulp_smash.tests.pulp2.rpm.cli.test_process_recycling`), 145  
[get\\_removed\\_content\(\)](#) (in module `pulp_smash.tests.pulp3.utils`), 167  
[get\\_repo\(\)](#) (`pulp_smash.tests.pulp2.rpm.api_v2.test_unassociate.RepublishTest` method), 129  
[get\\_repo\\_last\\_unit\\_removed\(\)](#) (`pulp_smash.tests.pulp2.rpm.api_v2.test_unassociate.RepublishTest` method), 129  
[get\\_repo\\_path\(\)](#) (in module `pulp_smash.tests.pulp2.python.api_v2.test_sync_publish`), 76  
[get\\_repo\\_versions\(\)](#) (in module `pulp_smash.tests.pulp3.utils`), 167  
[get\\_repodata\(\)](#) (in module `pulp_smash.tests.pulp2.rpm.api_v2.utils`), 140  
[get\\_repodata\\_repomd\\_xml\(\)](#) (in module `pulp_smash.tests.pulp2.rpm.api_v2.utils`), 140  
[get\\_repomd\\_iso\\_publish\\_path\(\)](#) (`pulp_smash.tests.pulp2.rpm.api_v2.test_export.BaseExportChecksumTypeTest` method), 90  
[get\\_repomd\\_iso\\_publish\\_path\(\)](#) (`pulp_smash.tests.pulp2.rpm.api_v2.test_export.ExportChecksumTypeTest` method), 90  
[get\\_repomd\\_iso\\_publish\\_path\(\)](#) (`pulp_smash.tests.pulp2.rpm.api_v2.test_export.RepoGroupExportChecksumTypeTest` method), 92  
[get\\_repomd\\_publish\\_path\(\)](#) (`pulp_smash.tests.pulp2.rpm.api_v2.test_export.BaseExportChecksumTypeTest` method), 90  
[get\\_repomd\\_publish\\_path\(\)](#) (`pulp_smash.tests.pulp2.rpm.api_v2.test_export.ExportChecksumTypeTest` method), 90  
[get\\_repomd\\_publish\\_path\(\)](#) (`pulp_smash.tests.pulp2.rpm.api_v2.test_export.RepoGroupExportChecksumTypeTest` method), 92  
[get\\_repomd\\_xml\\_path\(\)](#) (in module `pulp_smash.tests.pulp2.rpm.api_v2.test_no_op_publish`), 99  
[get\\_requests\\_kwargs\(\)](#) (`pulp_smash.config.PulpSmashConfig` method), 30  
[get\\_repo\\_abs\\_path\(\)](#) (`pulp_smash.tests.pulp2.rpm.api_v2.test_download_publish` class method), 86  
[get\\_rpm\\_names\(\)](#) (in module `pulp_smash.tests.pulp2.rpm.cli.test_sync`), 147  
[get\\_rpm\\_names\\_versions\(\)](#) (in module `pulp_smash.tests.pulp2.rpm.api_v2.utils`), 140  
[get\\_sha256\\_checksum\(\)](#) (in module `pulp_smash.utils`), 170  
[get\\_step\(\)](#) (`pulp_smash.tests.pulp2.rpm.api_v2.test_force_full.ForceFullTest` method), 93  
[get\\_systems\(\)](#) (`pulp_smash.config.PulpSmashConfig` method), 30  
[get\\_unit\(\)](#) (in module `pulp_smash.tests.pulp2.rpm.api_v2.utils`), 114  
[get\\_unit\\_by\\_filename\(\)](#) (`pulp_smash.tests.pulp2.rpm.api_v2.test_search.BaseSearchTest` method), 114  
[get\\_unit\\_by\\_type\(\)](#) (`pulp_smash.tests.pulp2.rpm.api_v2.test_search.BaseSearchTest` method), 114  
[get\\_updateinfo\\_xml\\_href\(\)](#) (`pulp_smash.tests.pulp2.rpm.api_v2.test_updateinfo.CleanUpTest` method), 132  
[get\\_upstream\\_name\(\)](#) (in module `pulp_smash.tests.pulp2.docker.utils`), 54  
[GetBrokerTestCase](#) (class in `tests.test_utils`), 179  
[GetBugTestCase](#) (class in `tests.test_selectors`), 179  
[GetConfigFilePathTestCase](#) (class in `tests.test_config`), 175  
[GetConfigTestCase](#) (class in `tests.test_config`), 175  
[GetRequestsKwargsTestCase](#) (class in `tests.test_config`), 176  
[GetStepOfChecksumTypeTest](#) (class in `tests.test_utils`), 179  
[GetTPRTestCase](#) (class in `tests.test_selectors`), 179  
[GoodChecksumTypeTest](#) (class in `pulp_smash.cli`), 25  
[GoodMirrorlistTestCase](#) (class in `pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist`), 41  
[GoodRelativeUrlTestCase](#) (class in `pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist`), 41  
[GROUP\\_CALL\\_REPORT\\_KEYS](#) (in module `pulp_smash.tests.pulp2.constants`), 41  
[head\(\)](#) (`pulp_smash.api.Client` method), 21  
[health\\_check\(\)](#) (`pulp_smash.tests.pulp2.rpm.api_v2.test_broker.BrokerTest` method), 77  
[HelperMethodsTestCase](#) (class in `tests.test_config`), 176

hostname (pulp\_smash.config.PulpSystem attribute), 30  
 http\_get() (in module pulp\_smash.utils), 170  
 HTTPD\_LABEL (in module pulp\_smash.tests.pulp2.platform.cli.test\_selinux), 67

**I**

import\_upload() (in module pulp\_smash.tests.pulp2.docker.api\_v2.test\_tags), 49  
 InitTestCase (class in tests.test\_config), 176  
 install() (pulp\_smash.cli.PackageManager method), 26  
 InstallDistributorTestCase (class in pulp\_smash.tests.pulp2.puppet.api\_v2.test\_install\_manifest), 69  
 InstallDistributorThrowsOnErrorTestCase (class in pulp\_smash.tests.pulp2.puppet.api\_v2.test\_install\_manifest), 69  
 InvalidFeedTestCase (class in pulp\_smash.tests.pulp2.docker.cli.test\_sync\_publish), 53  
 InvalidHeadersTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_content\_streams), 82  
 ISOUpdateTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_iso\_crud), 94  
 IsRootTestCase (class in tests.test\_utils), 180

**J**

json\_handler() (in module pulp\_smash.api), 22  
 JsonHandlerTestCase (class in tests.test\_api), 174  
 JWTAuth (class in pulp\_smash.tests.pulp3.utils), 165  
 JWTResetTestCase (class in pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_auth), 160

**K**

KeyLengthTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_checked\_for\_uploads), 123

**L**

label (pulp\_smash.tests.pulp2.platform.cli.test\_selinux.Process attribute), 68  
 LargePackageListTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_errata), 89  
 LastUnitAddedTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_crud), 84  
 LimitSkipTestCase (class in pulp\_smash.tests.pulp2.platform.api\_v2.test\_search), 63

LOGIN\_KEYS (in module pulp\_smash.tests.pulp2.constants), 41  
 LOGIN\_PATH (in module pulp\_smash.tests.pulp2.constants), 41  
 LoginTestCase (class in pulp\_smash.tests.pulp2.platform.api\_v2.test\_login), 60

**M**

make\_crane\_client() (pulp\_smash.tests.pulp2.docker.api\_v2.utils.SyncPublishMixin static method), 50  
 make\_user() (pulp\_smash.tests.pulp2.rpm.api\_v2.utils.TemporaryUserMixin method), 139  
 MANIFEST\_LIST\_V2 (in module pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync\_publish), 45  
 MANIFEST\_V1 (in module pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync\_publish), 45  
 MANIFEST\_V2 (in module pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync\_publish), 45  
 MaxTasksPerChildTestCase (class in pulp\_smash.tests.pulp2.rpm.cli.test\_process\_recycling), 145  
 maybe\_disable\_selinux() (pulp\_smash.tests.pulp2.rpm.api\_v2.utils.DisableSELinuxMixin method), 138  
 MinimalTestCase (class in pulp\_smash.tests.pulp2.platform.api\_v2.test\_search), 63  
 MissingSettingsFileMixin (class in tests.test\_pulp\_smash\_cli), 177  
 MissingWorkersTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_service\_resiliency), 115  
 MixedMirrorlistTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_mirrorlist), 97  
 MixedRelativeUrlTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_mirrorlist), 97  
 MtimeTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_copy), 83  
 MultiResourceLockingTestCase (class in pulp\_smash.tests.pulp3.file.api\_v3.test\_sync), 157

**N**

NegativeTestCase (class in pulp\_smash.tests.pulp2.platform.cli.test\_pulp\_manage\_db), 66



NoAmd64LinuxTestCase (class in pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync\_publication\_TYPES\_PATH (in module pulp\_smash.tests.pulp2.constants), 41  
45

NoKnownBrokerError, 37 poll\_spawned\_tasks() (in module pulp\_smash.api), 22

NoKnownPackageManagerError, 37 poll\_task() (in module pulp\_smash.api), 22

NoKnownServiceManagerError, 38 PositiveTestCase (class in pulp\_smash.tests.pulp2.platform.cli.test\_pulp\_manage\_db), 67

NonExistentRepoTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_crud), 84  
84 post() (pulp\_smash.api.Client method), 21

NonExistentRepoTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_sync\_publication), 126  
126 Process (class in pulp\_smash.tests.pulp2.platform.cli.test\_selinux), 67

NonNamespacedImageTestCase (class in pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync\_publication), 46  
46 ProcessLabelsTestCase (class in pulp\_smash.tests.pulp2.platform.cli.test\_selinux), 68

NoOpPublishMixin (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_no\_op\_publication), 99  
99 PS\_FIELDS (in module pulp\_smash.tests.pulp2.platform.cli.test\_selinux), 67

PublicationsTestCase (class in pulp\_smash.tests.pulp3.file.api\_v3.test\_crd\_publications), 151  
151

OnDemandTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies), 87  
87 publish\_repo() (in module pulp\_smash.tests.pulp3.utils), 170  
170 publish\_repo() (in module pulp\_smash.utils), 170

OPENSUSE\_FEED\_URL (in module pulp\_smash.constants), 33  
33 publish\_to\_dir() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_export.ExportDir method), 91

OpenSuseErrataTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_updateinfo), 132  
132 PublishAnyRepoVersionTestCase (class in pulp\_smash.tests.pulp3.file.api\_v3.test\_publish), 155  
155

OPTIONAL\_ROLES (in module pulp\_smash.config), 28  
28 PublishBeforeYumDistTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_rsync\_distributor), 109  
109

options() (pulp\_smash.api.Client method), 21  
21 PublishTestCase (class in pulp\_smash.tests.pulp2.ostree.api\_v2.test\_publish), 57  
57

ORPHANS\_PATH (in module pulp\_smash.tests.pulp2.constants), 41  
41 PublishTestCase (class in pulp\_smash.tests.pulp2.puppet.api\_v2.test\_sync\_publication), 70  
70

OrphansTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_orphan\_remove), 99  
99 PublishTwiceTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_rsync\_distributor), 109  
109

os\_is\_f26() (in module pulp\_smash.utils), 170  
170 PubTwiceTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_no\_op\_publication), 99  
99

os\_is\_f27() (in module pulp\_smash.utils), 170  
170

os\_is\_rhel6() (in module pulp\_smash.tests.pulp2.rpm.utils), 149  
149 PubTwiceWithOverrideTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_no\_op\_publication), 99  
99

OsIsF26TestCase (class in tests.test\_utils), 180  
180

OSTREE\_BRANCHES (in module pulp\_smash.constants), 33  
33

OSTREE\_FEED (in module pulp\_smash.constants), 33  
33

**P**

PackageManager (class in pulp\_smash.cli), 26  
26

ParallelTestCase (class in pulp\_smash.tests.pulp2.platform.api\_v2.test\_content\_applicability), 59  
59 pulp\_admin\_login() (in module pulp\_smash.utils), 171  
171

parse\_pulp\_manifest() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_iso\_crud.PulpManifestTestCase static method), 95  
95 PULP\_FIXTURES\_BASE\_URL (in module pulp\_smash.constants), 33  
33

patch() (pulp\_smash.api.Client method), 21  
21 PULP\_FIXTURES\_KEY\_ID (in module pulp\_smash.constants), 33  
33

PkglistsTestCase (class in pulp\_smash.tests.pulp2.constants), 41  
41 PULP\_SERVICES (in module pulp\_smash), 19  
19

pulp\_smash (module), 19  
19

- pulp\_smash.api (module), 19
- pulp\_smash.cli (module), 23
- pulp\_smash.config (module), 27
- pulp\_smash.constants (module), 31
- pulp\_smash.exceptions (module), 37
- pulp\_smash.pulp\_smash\_cli (module), 38
- pulp\_smash.selectors (module), 38
- pulp\_smash.tests (module), 39
- pulp\_smash.tests.pulp2 (module), 41
- pulp\_smash.tests.pulp2.constants (module), 41
- pulp\_smash.tests.pulp2.docker (module), 42
- pulp\_smash.tests.pulp2.docker.api\_v2 (module), 42
- pulp\_smash.tests.pulp2.docker.api\_v2.test\_copy (module), 42
- pulp\_smash.tests.pulp2.docker.api\_v2.test\_crud (module), 43
- pulp\_smash.tests.pulp2.docker.api\_v2.test\_duplicate\_uploads (module), 44
- pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync (module), 44
- pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync\_publish (module), 45
- pulp\_smash.tests.pulp2.docker.api\_v2.test\_tags (module), 48
- pulp\_smash.tests.pulp2.docker.api\_v2.test\_upload (module), 49
- pulp\_smash.tests.pulp2.docker.api\_v2.utils (module), 50
- pulp\_smash.tests.pulp2.docker.cli (module), 51
- pulp\_smash.tests.pulp2.docker.cli.test\_crud (module), 51
- pulp\_smash.tests.pulp2.docker.cli.test\_sync\_publish (module), 53
- pulp\_smash.tests.pulp2.docker.cli.utils (module), 53
- pulp\_smash.tests.pulp2.docker.utils (module), 54
- pulp\_smash.tests.pulp2.ostree (module), 54
- pulp\_smash.tests.pulp2.ostree.api\_v2 (module), 54
- pulp\_smash.tests.pulp2.ostree.api\_v2.test\_copy (module), 54
- pulp\_smash.tests.pulp2.ostree.api\_v2.test\_crud (module), 55
- pulp\_smash.tests.pulp2.ostree.api\_v2.test\_publish (module), 57
- pulp\_smash.tests.pulp2.ostree.api\_v2.test\_sync (module), 57
- pulp\_smash.tests.pulp2.ostree.utils (module), 58
- pulp\_smash.tests.pulp2.platform (module), 58
- pulp\_smash.tests.pulp2.platform.api\_v2 (module), 58
- pulp\_smash.tests.pulp2.platform.api\_v2.test\_consumer (module), 59
- pulp\_smash.tests.pulp2.platform.api\_v2.test\_content\_applicability (module), 59
- pulp\_smash.tests.pulp2.platform.api\_v2.test\_login (module), 60
- pulp\_smash.tests.pulp2.platform.api\_v2.test\_repository (module), 60
- pulp\_smash.tests.pulp2.platform.api\_v2.test\_search (module), 62
- pulp\_smash.tests.pulp2.platform.api\_v2.test\_user (module), 64
- pulp\_smash.tests.pulp2.platform.cli (module), 66
- pulp\_smash.tests.pulp2.platform.cli.test\_pulp\_manage\_db (module), 66
- pulp\_smash.tests.pulp2.platform.cli.test\_selinux (module), 67
- pulp\_smash.tests.pulp2.platform.utils (module), 68
- pulp\_smash.tests.pulp2.puppet (module), 68
- pulp\_smash.tests.pulp2.puppet.api\_v2 (module), 68
- pulp\_smash.tests.pulp2.puppet.api\_v2.test\_crud (module), 69
- pulp\_smash.tests.pulp2.puppet.api\_v2.test\_duplicate\_uploads (module), 69
- pulp\_smash.tests.pulp2.puppet.api\_v2.test\_install\_distributor (module), 69
- pulp\_smash.tests.pulp2.puppet.api\_v2.test\_sync\_publish (module), 70
- pulp\_smash.tests.pulp2.puppet.api\_v2.utils (module), 72
- pulp\_smash.tests.pulp2.puppet.cli (module), 72
- pulp\_smash.tests.pulp2.puppet.cli.test\_sync (module), 73
- pulp\_smash.tests.pulp2.puppet.utils (module), 74
- pulp\_smash.tests.pulp2.python (module), 74
- pulp\_smash.tests.pulp2.python.api\_v2 (module), 74
- pulp\_smash.tests.pulp2.python.api\_v2.test\_crud (module), 74
- pulp\_smash.tests.pulp2.python.api\_v2.test\_duplicate\_uploads (module), 74
- pulp\_smash.tests.pulp2.python.api\_v2.test\_sync\_publish (module), 75
- pulp\_smash.tests.pulp2.python.api\_v2.utils (module), 76
- pulp\_smash.tests.pulp2.python.utils (module), 76
- pulp\_smash.tests.pulp2.rpm (module), 76
- pulp\_smash.tests.pulp2.rpm.api\_v2 (module), 77
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_broker (module), 77
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_character\_encoding (module), 78
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_comps\_xml (module), 78
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_content\_applicability (module), 81
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_content\_sources (module), 82
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_copy (module), 83
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_crud (module), 84
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies (module), 85
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_duplicate\_uploads (module), 88

- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_errata (module), 89
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_export (module), 90
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_force\_full (module), 92
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_iso\_crud (module), 93
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_iso\_sync\_publish (module), 95
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_mirrorlist (module), 96
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_no\_op\_publish (module), 98
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_orphan\_remove (module), 99
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_package\_paths (module), 100
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_remove\_unit (module), 101
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_repomd (module), 103
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_repository\_layout (module), 104
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_repoview (module), 105
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_republish (module), 105
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_retain\_old\_count (module), 106
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_rsync\_distributor (module), 107
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_schedule\_publish (module), 111
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_schedule\_sync (module), 112
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_search (module), 114
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_service\_resiliency (module), 115
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_checked\_for\_copies (module), 116
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_checked\_for\_syncable (module), 118
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_checked\_for\_uploads (module), 121
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_saved\_for\_packages (module), 124
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_sync\_publish (module), 125
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_tasks (module), 128
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_unassociate (module), 128
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_unavailable\_checksum (module), 130
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_updateinfo (module), 131
- pulp\_smash.tests.pulp2.rpm.api\_v2.test\_upload\_publish (module), 135
- pulp\_smash.tests.pulp2.rpm.api\_v2.utils (module), 138
- pulp\_smash.tests.pulp2.rpm.cli (module), 141
- pulp\_smash.tests.pulp2.rpm.cli.test\_character\_encoding (module), 142
- pulp\_smash.tests.pulp2.rpm.cli.test\_copy\_units (module), 142
- pulp\_smash.tests.pulp2.rpm.cli.test\_environments (module), 144
- pulp\_smash.tests.pulp2.rpm.cli.test\_langpacks (module), 144
- pulp\_smash.tests.pulp2.rpm.cli.test\_process\_recycling (module), 145
- pulp\_smash.tests.pulp2.rpm.cli.test\_retain\_old\_count (module), 145
- pulp\_smash.tests.pulp2.rpm.cli.test\_search (module), 146
- pulp\_smash.tests.pulp2.rpm.cli.test\_sync (module), 147
- pulp\_smash.tests.pulp2.rpm.cli.test\_upload (module), 148
- pulp\_smash.tests.pulp2.rpm.cli.utils (module), 148
- pulp\_smash.tests.pulp2.rpm.utils (module), 149
- pulp\_smash.tests.pulp2.utils (module), 150
- pulp\_smash.tests.pulp3 (module), 150
- pulp\_smash.tests.pulp3.constants (module), 150
- pulp\_smash.tests.pulp3.file (module), 151
- pulp\_smash.tests.pulp3.file.api\_v3 (module), 151
- pulp\_smash.tests.pulp3.file.api\_v3.test\_crd\_publications (module), 151
- pulp\_smash.tests.pulp3.file.api\_v3.test\_crud\_content\_unit (module), 151
- pulp\_smash.tests.pulp3.file.api\_v3.test\_crud\_publishers (module), 152
- pulp\_smash.tests.pulp3.file.api\_v3.test\_crud\_remotes (module), 153
- pulp\_smash.tests.pulp3.file.api\_v3.test\_download\_content (module), 154
- pulp\_smash.tests.pulp3.file.api\_v3.test\_orphans (module), 154
- pulp\_smash.tests.pulp3.file.api\_v3.test\_publish (module), 155
- pulp\_smash.tests.pulp3.file.api\_v3.test\_repo\_version (module), 155
- pulp\_smash.tests.pulp3.file.api\_v3.test\_sync (module), 157
- pulp\_smash.tests.pulp3.file.api\_v3.test\_unlinking\_repo (module), 158
- pulp\_smash.tests.pulp3.file.api\_v3.utils (module), 159
- pulp\_smash.tests.pulp3.file.utils (module), 159
- pulp\_smash.tests.pulp3.pulpcore (module), 159

- pulp\_smash.tests.pulp3.pulpcore.api\_v3 (module), 159
- pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_api\_docs (module), 159
- pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_auth (module), 160
- pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_crd\_artifacts (module), 161
- pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_crud\_distributions (module), 162
- pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_crud\_repos (module), 162
- pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_crud\_users (module), 163
- pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_status (module), 164
- pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_workers (module), 164
- pulp\_smash.tests.pulp3.pulpcore.utils (module), 165
- pulp\_smash.tests.pulp3.utils (module), 165
- pulp\_smash.utils (module), 168
- PulpAdminLoginTestCase (class in tests.test\_utils), 180
- PulpDistributionTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_crud), 85
- PulpManifestTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_iso\_crud), 95
- PulpSmashConfig (class in pulp\_smash.config), 28
- PulpSmashConfigFileTestCase (class in tests.test\_config), 176
- PulpSystem (class in pulp\_smash.config), 30
- PUPPET\_FEED\_2 (in module pulp\_smash.constants), 33
- PUPPET\_MODULE\_1 (in module pulp\_smash.constants), 33
- PUPPET\_MODULE\_2 (in module pulp\_smash.constants), 33
- PUPPET\_MODULE\_URL\_1 (in module pulp\_smash.constants), 33
- PUPPET\_MODULE\_URL\_2 (in module pulp\_smash.constants), 34
- PUPPET\_QUERY\_2 (in module pulp\_smash.constants), 34
- put() (pulp\_smash.api.Client method), 21
- PYTHON\_EGG\_URL (in module pulp\_smash.constants), 34
- PYTHON\_PYPI\_FEED\_URL (in module pulp\_smash.constants), 34
- PYTHON\_WHEEL\_URL (in module pulp\_smash.constants), 34
- R**
- read() (pulp\_smash.config.PulpSmashConfig method), 30
- ReadTestCase (class in tests.test\_config), 176
- ReadUpdateDeleteTestCase (class in pulp\_smash.tests.pulp2.platform.api\_v2.test\_repository), 61
- ReadUpdateDeleteTestCase (class in pulp\_smash.tests.pulp2.platform.api\_v2.test\_user), 65
- ReadUpdateDeleteTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_iso\_crud), 95
- ReadUpdateDeleteTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_schedule\_publish), 112
- ReadUpdateDeleteTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_schedule\_sync), 113
- RemotesPublishersTestCase (class in pulp\_smash.tests.pulp3.file.api\_v3.test\_unlinking\_repo), 158
- RemoteUnitsPathTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_rsync\_distributor), 110
- RemoveCountTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_remove\_unit), 101
- RemovedContentTestCase (class in pulp\_smash.tests.pulp2.rpm.cli.test\_sync), 147
- RemoveMissingTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_remove\_unit), 102
- RemoveOldRepodataTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_republish), 105
- RemoveUnitsTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_unassociate), 128
- repo\_copy() (in module pulp\_smash.tests.pulp2.docker.cli.utils), 53
- repo\_create() (in module pulp\_smash.tests.pulp2.docker.cli.utils), 53
- repo\_delete() (in module pulp\_smash.tests.pulp2.docker.cli.utils), 53
- repo\_list() (in module pulp\_smash.tests.pulp2.docker.cli.utils), 53
- repo\_publish() (in module pulp\_smash.tests.pulp2.docker.cli.utils), 53
- repo\_search() (in module pulp\_smash.tests.pulp2.docker.cli.utils), 53
- repo\_sync() (in module pulp\_smash.tests.pulp2.docker.cli.utils), 53
- repo\_update() (in module pulp\_smash.tests.pulp2.docker.cli.utils), 53
- RepoGroupExportChecksumTypeTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_export),

<p>92</p> <p>RepoMDTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_repomd), 103</p> <p>RepoRegistryIdTestCase (class in pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish), 46</p> <p>REPOSITORY_EXPORT_DISTRIBUTOR (in module pulp_smash.tests.pulp2.constants), 41</p> <p>REPOSITORY_GROUP_EXPORT_DISTRIBUTOR (in module pulp_smash.tests.pulp2.constants), 42</p> <p>REPOSITORY_GROUP_PATH (in module pulp_smash.tests.pulp2.constants), 42</p> <p>REPOSITORY_PATH (in module pulp_smash.tests.pulp2.constants), 42</p> <p>repository_setup() (pulp_smash.tests.pulp2.rpm.api_v2.test_download_policies.SwitchPoliciesTestCase method), 88</p> <p>RepositoryGroupCrudTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_crud), 85</p> <p>RepositoryLayoutTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_repository_layout), 104</p> <p>RepoviewTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_repoview), 105</p> <p>ReprTestCase (class in tests.test_config), 176</p> <p>RepublishTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_unassociate), 129</p> <p>request() (pulp_smash.api.Client method), 21</p> <p>require() (in module pulp_smash.selectors), 38</p> <p>require_issue_3159() (in module pulp_smash.tests.pulp2.utils), 150</p> <p>require_pulp_2() (in module pulp_smash.tests.pulp2.utils), 150</p> <p>require_pulp_3() (in module pulp_smash.tests.pulp3.utils), 167</p> <p>require_pulp_plugins() (in module pulp_smash.tests.pulp3.utils), 167</p> <p>require_unit_types() (in module pulp_smash.tests.pulp2.utils), 150</p> <p>RequireAnyKeyTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_compids), 117</p> <p>RequireAnyKeyTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_compids), 120</p> <p>RequireAnyKeyTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_compids), 123</p> <p>REQUIRED_ROLES (in module pulp_smash.config), 30</p> <p>REQUIRED_SERVICES (in module pulp_smash.tests.pulp2.platform.cli.test_pulp_manage_db), pulp_smash.constants), 35</p>	<p>67</p> <p>RequireInvalidKeyTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_compids), 118</p> <p>RequireInvalidKeyTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_compids), 121</p> <p>RequireInvalidKeyTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_compids), 123</p> <p>RequireValidKeyTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_compids), 118</p> <p>RequireValidKeyTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_compids), 124</p> <p>reset_pulp() (in module pulp_smash.utils), 171</p> <p>reset_squid() (in module pulp_smash.utils), 171</p> <p>restart() (pulp_smash.cli.BaseServiceManager method), 23</p> <p>restart() (pulp_smash.cli.GlobalServiceManager method), 25</p> <p>restart() (pulp_smash.cli.ServiceManager method), 27</p> <p>RetainOldCountTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_retain_old_count), 106</p> <p>RetainOldCountTestCase (class in pulp_smash.tests.pulp2.rpm.cli.test_retain_old_count), 145</p> <p>ReuseContentTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_package_paths), 101</p> <p>ROLES (in module pulp_smash.config), 31</p> <p>roles (pulp_smash.config.PulpSystem attribute), 30</p> <p>RPM (in module pulp_smash.constants), 34</p> <p>RPM2 (in module pulp_smash.constants), 34</p> <p>RPM2_UNSIGNED_URL (in module pulp_smash.constants), 34</p> <p>RPM_ALT_LAYOUT_FEED_URL (in module pulp_smash.constants), 34</p> <p>RPM_CHECK_ALL_FOR_COMPIDS (in module pulp_smash.constants), 34</p> <p>RPM_ERRATUM_COUNT (in module pulp_smash.constants), 35</p> <p>RPM_ERRATUM_FEED_URL (in module pulp_smash.constants), 35</p> <p>RPM_ERRATUM_RPM_NAME (in module pulp_smash.constants), 35</p> <p>RPM_INCOMPLETE_FILELISTS_FEED_URL (in module pulp_smash.constants), 35</p> <p>RPM_INCOMPLETE_OTHER_FEED_URL (in module pulp_smash.constants), 35</p>
--	---

RPM_INVALID_FEED_URL	(in module pulp_smash.constants), 35	pulp_smash.tests.pulp2.rpm.api_v2.test_content_applicability), 82
RPM_INVALID_URL	(in module pulp_smash.constants), 35	RPMDistributorTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_crud), 85
RPM_LARGE_UPDATEINFO	(in module pulp_smash.constants), 35	RsyncExtraArgsTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_rsync_distributor), 110
RPM_MIRRORLIST_BAD	(in module pulp_smash.constants), 35	run() (pulp_smash.cli.Client method), 24
RPM_MIRRORLIST_GOOD	(in module pulp_smash.constants), 35	<b>S</b>
RPM_MIRRORLIST_LARGE	(in module pulp_smash.constants), 35	safe_handler() (in module pulp_smash.api), 22
RPM_MIRRORLIST_MIXED	(in module pulp_smash.constants), 35	SafeHandlerTestCase (class in tests.test_api), 174
RPM_MISSING_FILELISTS_FEED_URL	(in module pulp_smash.constants), 35	ScheduledPublishTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_publish), 112
RPM_MISSING_OTHER_FEED_URL	(in module pulp_smash.constants), 35	ScheduledSyncTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_sync), 113
RPM_MISSING_PRIMARY_FEED_URL	(in module pulp_smash.constants), 35	search_units() (in module pulp_smash.utils), 171
RPM_NAMESPACES	(in module pulp_smash.constants), 35	SearchForRpmTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_search), 114
RPM_PKGLISTS_UPDATEINFO_FEED_URL	(in module pulp_smash.constants), 36	SearchForSrpmTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_search), 115
RPM_SIGNED_FEED_COUNT	(in module pulp_smash.constants), 36	SearchReposWithFiltersTestCase (class in pulp_smash.tests.pulp2.rpm.cli.test_search), 146
RPM_SIGNED_FEED_URL	(in module pulp_smash.constants), 36	SearchTestCase (class in pulp_smash.tests.pulp2.platform.api_v2.test_user), 65
RPM_SIGNED_URL	(in module pulp_smash.constants), 36	SearchUnitsTestCase (class in tests.test_utils), 180
RPM_UNSIGNED_FEED_COUNT	(in module pulp_smash.constants), 36	SelectiveAssociateTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_unassociate), 130
RPM_UNSIGNED_FEED_URL	(in module pulp_smash.constants), 36	SeriesTestCase (class in pulp_smash.tests.pulp2.platform.api_v2.test_content_applicability), 60
RPM_UNSIGNED_URL	(in module pulp_smash.constants), 36	ServiceManagerFalseTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_iso_sync_publish), 95
RPM_UPDATED_INFO_FEED_URL	(in module pulp_smash.constants), 36	ServiceManager (class in pulp_smash.cli), 26
RPM_WITH_ERRATUM_METADATA	(in module pulp_smash.tests.pulp2.rpm.api_v2.test_content_applicability), 82	services_for_roles() (pulp_smash.config.PulpSmashConfig static method), 30
RPM_WITH_NON_ASCII_URL	(in module pulp_smash.constants), 36	set_pulp_manage_rsync() (in module pulp_smash.tests.pulp2.rpm.api_v2.utils), 141
RPM_WITH_NON_UTF_8_URL	(in module pulp_smash.constants), 36	set_up_module() (in module pulp_smash.tests.pulp2.docker.utils), 54
RPM_WITH_PULP_DISTRIBUTION_FEED_URL	(in module pulp_smash.constants), 36	set_up_module() (in module pulp_smash.tests.pulp2.ostree.utils), 58
RPM_WITH_VENDOR	(in module pulp_smash.constants), 36	set_up_module() (in module pulp_smash.tests.pulp2.platform.utils), 68
RPM_WITH_VENDOR_FEED_URL	(in module pulp_smash.constants), 36	
RPM_WITH_VENDOR_URL	(in module pulp_smash.constants), 36	
RPM_WITHOUT_ERRATUM_METADATA	(in module pulp_smash.constants), 36	



- setUpClass() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_content\_applicability.ParallelTestCases class method), 59
- setUpClass() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_content\_applicability.ParallelTestCases class method), 81
- setUpClass() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_content\_applicability.ParallelTestCases class method), 82
- setUpClass() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_content\_applicability.ParallelTestCases class method), 82
- setUpClass() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_content\_applicability.ParallelTestCases class method), 85
- setUpClass() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_content\_applicability.ParallelTestCases class method), 86
- setUpClass() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_content\_applicability.ParallelTestCases class method), 86
- setUpClass() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_content\_applicability.ParallelTestCases class method), 87
- setUpClass() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_content\_applicability.ParallelTestCases class method), 89
- setUpClass() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_content\_applicability.ParallelTestCases class method), 90
- setUpClass() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_content\_applicability.ParallelTestCases class method), 91
- setUpClass() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_content\_applicability.ParallelTestCases class method), 92
- setUpClass() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_content\_applicability.ParallelTestCases class method), 92
- setUpClass() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_content\_applicability.ParallelTestCases class method), 93
- setUpClass() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_content\_applicability.ParallelTestCases class method), 93
- setUpClass() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_content\_applicability.ParallelTestCases class method), 94
- setUpClass() (pulp\_smash.tests.pulp2.platform.cli.test\_pulp\_cli.PublishTestCases class method), 95
- setUpClass() (pulp\_smash.tests.pulp2.platform.cli.test\_selinux.PublishTestCases class method), 98
- setUpClass() (pulp\_smash.tests.pulp2.platform.cli.test\_selinux.PublishTestCases class method), 98
- setUpClass() (pulp\_smash.tests.pulp2.puppet.api\_v2.test\_duplicate\_publish.PublishTestCases class method), 99
- setUpClass() (pulp\_smash.tests.pulp2.puppet.api\_v2.test\_duplicate\_publish.PublishTestCases class method), 99
- setUpClass() (pulp\_smash.tests.pulp2.puppet.api\_v2.test\_duplicate\_publish.PublishTestCases class method), 100
- setUpClass() (pulp\_smash.tests.pulp2.puppet.api\_v2.test\_duplicate\_publish.PublishTestCases class method), 102
- setUpClass() (pulp\_smash.tests.pulp2.puppet.api\_v2.test\_duplicate\_publish.PublishTestCases class method), 103
- setUpClass() (pulp\_smash.tests.pulp2.python.api\_v2.test\_duplicate\_publish.PublishTestCases class method), 106
- setUpClass() (pulp\_smash.tests.pulp2.python.api\_v2.test\_duplicate\_publish.PublishTestCases class method), 106
- setUpClass() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_complex\_repo.RepublishTestCases class method), 110
- setUpClass() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_complex\_repo.RepublishTestCases class method), 111





setUpModule()	(in module pulp_smash.tests.pulp2.docker.api_v2.test_tags),	setUpModule()	(in module pulp_smash.tests.pulp2.rpm.cli.test_copy_units),
	49		143
setUpModule()	(in module pulp_smash.tests.pulp2.docker.api_v2.test_upload),	setUpModule()	(in module pulp_smash.tests.pulp2.rpm.cli.test_process_recycling),
	49		145
setUpModule()	(in module pulp_smash.tests.pulp2.docker.cli.test_sync_publish),	setUpModule()	(in module pulp_smash.tests.pulp2.rpm.cli.test_sync),
	53		147
setUpModule()	(in module pulp_smash.tests.pulp2.platform.api_v2.test_search),	setUpModule()	(in module pulp_smash.tests.pulp2.rpm.cli.test_upload),
	64		148
setUpModule()	(in module pulp_smash.tests.pulp2.platform.cli.test_pulp_manifests),	skip_if()	(in module pulp_smash.selectors), 39
	67	SmokeTest	(class in pulp_smash.utils), 169
		SmokeTestsTestCase	(class in tests.test_pulp_smash_cli), 178
setUpModule()	(in module pulp_smash.tests.pulp2.puppet.cli.test_sync),	SortTestCase	(class in pulp_smash.tests.pulp2.platform.api_v2.test_search), 64
	73		
setUpModule()	(in module pulp_smash.tests.pulp2.rpm.api_v2.test_comps_x86_64),	SRPM	(in module pulp_smash.constants), 36
	81	SRPM_SIGNED_FEED_COUNT	(in module pulp_smash.constants), 36
setUpModule()	(in module pulp_smash.tests.pulp2.rpm.api_v2.test_download_policies),	SRPM_SIGNED_FEED_URL	(in module pulp_smash.constants), 36
	88		
setUpModule()	(in module pulp_smash.tests.pulp2.rpm.api_v2.test_export),	SRPM_SIGNED_URL	(in module pulp_smash.constants), 36
	92	SRPM_UNSIGNED_FEED_COUNT	(in module pulp_smash.constants), 37
setUpModule()	(in module pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist),	SRPM_UNSIGNED_FEED_URL	(in module pulp_smash.constants), 37
	98		
setUpModule()	(in module pulp_smash.tests.pulp2.rpm.api_v2.test_no_op_publish),	SRPM_UNSIGNED_URL	(in module pulp_smash.constants), 37
	99		
setUpModule()	(in module pulp_smash.tests.pulp2.rpm.api_v2.test_rsnc_distributor),	start()	(pulp_smash.cli.BaseServiceManager method), 23
	111	start()	(pulp_smash.cli.GlobalServiceManager method), 27
		start()	(pulp_smash.cli.ServiceManager method), 27
setUpModule()	(in module pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_signatures),	StatusTestCase	(class in tests.pulp3.pulpcore.api_v3.test_status), 164
	118		
setUpModule()	(in module pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_signatures),	stop()	(pulp_smash.cli.BaseServiceManager method), 23
	121	stop()	(pulp_smash.cli.GlobalServiceManager method), 26
		stop()	(pulp_smash.cli.ServiceManager method), 27
setUpModule()	(in module pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for_signatures),	ExportDirMixin	(class in pulp2.rpm.api_v2.test_export.ExportDirMixin method), 91
	124		
setUpModule()	(in module pulp_smash.tests.pulp2.rpm.api_v2.test_unassociate),	SwitchPoliciesTestCase	(class in pulp_smash.tests.pulp2.rpm.api_v2.test_download_policies), 87
	130		
setUpModule()	(in module pulp_smash.tests.pulp2.rpm.api_v2.test_updateinfo),	sync_repo()	(in module pulp_smash.tests.pulp2.rpm.cli.test_sync), 147
	135		
setUpModule()	(in module pulp_smash.tests.pulp2.rpm.cli.test_character_encoding),	sync_repo()	(in module pulp_smash.tests.pulp3.utils), 167
	142	sync_repo()	(in module pulp_smash.utils), 171

sync_repo() (pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish.PublishRepoValidFeedTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish), 71	SyncRpmRepoValidFeedTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish), 128
SyncChangeRepoVersionTestCase (class in pulp_smash.tests.pulp3.file.api_v3.test_sync), 157	SyncTestCase (class in pulp_smash.tests.pulp2.ostree.api_v2.test_sync), 58
SyncDownloadedContentTestCase (class in pulp_smash.tests.pulp2.puppet.cli.test_sync), 73	SyncTestCase (class in pulp_smash.tests.pulp2.python.api_v2.test_sync_publish), 75
SyncDrpmRepoTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish), 126	SyncValidFeedTestCase (class in pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish), 71
SyncFileRepoTestCase (class in pulp_smash.tests.pulp3.file.api_v3.test_sync), 158	SyncValidManifestFeedTestCase (class in pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish), 72
SyncFromPuppetForgeTestCase (class in pulp_smash.tests.pulp2.puppet.cli.test_sync), 73	<b>T</b>
SyncInParallelTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish), 126	TaskDispatchTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_service_resiliency), 116
SyncInvalidBranchesTestCase (class in pulp_smash.tests.pulp2.ostree.api_v2.test_sync), 57	TaskReportError, 38
SyncInvalidFeedTestCase (class in pulp_smash.tests.pulp2.ostree.api_v2.test_sync), 57	TASKS_PATH (in module pulp_smash.tests.pulp2.constants), 42
SyncInvalidFeedTestCase (class in pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish), 71	TasksOperationsTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_tasks), 128
SyncInvalidMetadataTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish), 126	TaskTimedOutError, 38
SyncMissingAttrsTestCase (class in pulp_smash.tests.pulp2.ostree.api_v2.test_sync), 57	tearDown() (pulp_smash.tests.pulp2.docker.cli.test_crud.CreateTestCase method), 51
SyncNoFeedTestCase (class in pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish), 71	tearDown() (pulp_smash.tests.pulp2.platform.cli.test_pulp_manage_db.BaseTestCase method), 66
SyncPackageTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_and_downloads), 124	tearDown() (pulp_smash.tests.pulp2.rpm.api_v2.test_broker.BrokerTestCase method), 77
SyncPublishMixin (class in pulp_smash.tests.pulp2.docker.api_v2.utils), 50	tearDown() (pulp_smash.tests.pulp2.rpm.api_v2.test_iso_sync_publish.ServiceTestCase method), 96
SyncRepoBaseTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish), 127	tearDown() (pulp_smash.tests.pulp2.rpm.api_v2.test_rsync_distributor.VerifierTestCase method), 111
SyncRepoTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_comps_xml), 79	tearDown() (pulp_smash.tests.pulp2.rpm.api_v2.test_service_resiliency.MisconfiguredTestCase method), 116
SyncRepoTestCase (class in tests.test_utils), 180	tearDownClass() (pulp_smash.tests.pulp2.docker.api_v2.test_copy.CopyV1TestCase class method), 42
SyncRpmRepoTestCase (class in pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish), 127	tearDownClass() (pulp_smash.tests.pulp2.docker.api_v2.test_copy.CopyV2TestCase class method), 43
	tearDownClass() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.PublishTestCase class method), 46
	tearDownClass() (pulp_smash.tests.pulp2.docker.cli.test_crud.UpdateDistributionTestCase class method), 52
	tearDownClass() (pulp_smash.tests.pulp2.docker.cli.test_crud.UpdateEnabledTestCase class method), 52
	tearDownClass() (pulp_smash.tests.pulp2.docker.cli.test_crud.UpdateEnabledTestCase class method), 52
	tearDownClass() (pulp_smash.tests.pulp2.python.api_v2.test_sync_publish.PublishTestCase class method), 75

tearDownClass() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_content\_sources.InvalidHeadersTestCase class method), 81

tearDownClass() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_content\_sources.InvalidHeadersTestCase class method), 82

tearDownClass() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_content\_sources.InvalidHeadersTestCase class method), 82

tearDownClass() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_remove\_unit.RemoveMissingTestCase class method), 102

tearDownClass() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_sync\_publish.SyncInvalidMetadataTestCase class method), 127

tearDownClass() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_unassociate.RepublishTestCase class method), 129

tearDownClass() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_update\_orphans.OrphanRemoveTestCase class method), 132

tearDownClass() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_upload\_publish.UploadRPMTCase class method), 136

tearDownClass() (pulp\_smash.tests.pulp2.rpm.cli.test\_environments.UploadPackageEnvTestCase class method), 144

tearDownClass() (pulp\_smash.tests.pulp2.rpm.cli.test\_langpacks.UploadAndRemoveLangpacksTestCase class method), 144

tearDownClass() (pulp\_smash.tests.pulp2.rpm.cli.test\_retain\_old\_content.RetainOldContentTestCase class method), 146

tearDownClass() (pulp\_smash.tests.pulp2.rpm.cli.test\_search.SearchReposWithFilterTestCase class method), 146

tearDownClass() (pulp\_smash.tests.pulp3.file.api\_v3.test\_crud\_publications.PublicationsTestCase class method), 151

tearDownClass() (pulp\_smash.tests.pulp3.file.api\_v3.test\_crud\_content\_publish.PublishTestCase class method), 152

tearDownClass() (pulp\_smash.tests.pulp3.file.api\_v3.test\_crud\_publishers.CRUDPublishersTestCase class method), 153

tearDownClass() (pulp\_smash.tests.pulp3.file.api\_v3.test\_crud\_remote\_content.RemoteContentTestCase class method), 153

tearDownClass() (pulp\_smash.tests.pulp3.file.api\_v3.test\_repo\_version.AddRemoveContentTestCase class method), 156

tearDownClass() (pulp\_smash.tests.pulp3.file.api\_v3.test\_crud\_repositories.RepositoriesTestCase class method), 162

tearDownModule() (in module pulp\_smash.tests.pulp2.platform.api\_v2.test\_search), 64

tearDownModule() (in module pulp\_smash.tests.pulp2.platform.cli.test\_pulp\_manage\_db), 67

tearDownModule() (in module pulp\_smash.tests.pulp2.rpm.api\_v2.test\_mirrorlist), 98

tearDownModule() (in module pulp\_smash.tests.pulp2.rpm.api\_v2.test\_no\_op\_publish), 99

tearDownModule() (in module pulp\_smash.tests.pulp2.rpm.api\_v2.test\_rsynchronizing\_distributor), 111

tearDownModule() (in module pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_set\_the\_kit\_for\_repo), 118

tearDownModule() (in module pulp\_smash.tests.pulp2.pyhton.api\_v2.test\_sync\_publish), 75

tearDownModule() (in module pulp\_smash.tests.pulp2.pyhton.api\_v2.test\_sync\_publish), 76

tearDownModule() (in module pulp\_smash.tests.pulp2.pyhton.api\_v2.test\_sync\_publish), 76

test_01_first_upload() (pulp_smash.utils.DuplicateUploadsMixin method), 169	(pulp_smash.tests.pulp2.rpm.api_v2.test_force_full.ForceFullTest method), 93
test_01_force_full_false() (pulp_smash.tests.pulp2.rpm.api_v2.test_force_full.ForceFullTest method), 93	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_01_get_by_href() (pulp_smash.tests.pulp2.rpm.api_v2.test_orphan_remove.OrphanTest method), 100	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_01_get_by_invalid_type() (pulp_smash.tests.pulp2.rpm.api_v2.test_orphan_remove.OrphanTest method), 100	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_01_read_all_workers() (pulp_smash.tests.pulp3.pulpcore.api_v3.test_workers.WorkerTest method), 164	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_01_set_up() (pulp_smash.tests.pulp2.docker.api_v2.test_copy_content.CopyViaContentTest method), 42	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_01_set_up() (pulp_smash.tests.pulp2.docker.api_v2.test_copy_content.CopyViaContentTest method), 43	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_01_set_up() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_01_sync_publish() (pulp_smash.tests.pulp2.rpm.api_v2.test_upload_publish.UploadRpmTest method), 135	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_01_upload_langpacks() (pulp_smash.tests.pulp2.rpm.cli.test_langpacks.UploadAndRemoveLangpacksTest method), 144	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_01_upload_publish() (pulp_smash.tests.pulp2.rpm.api_v2.test_upload_publish.UploadRpmTest method), 137	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_02_copy_images() (pulp_smash.tests.pulp2.docker.api_v2.test_copy_content.CopyViaContentTest method), 42	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_02_copy_manifest_lists() (pulp_smash.tests.pulp2.docker.api_v2.test_copy_content.CopyViaContentTest method), 43	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_02_copy_manifests() (pulp_smash.tests.pulp2.docker.api_v2.test_copy_content.CopyViaContentTest method), 43	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_02_copy_publish() (pulp_smash.tests.pulp2.rpm.api_v2.test_upload_publish.UploadRpmTest method), 137	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_02_copy_tags() (pulp_smash.tests.pulp2.docker.api_v2.test_copy_content.CopyViaContentTest method), 43	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_02_create_immediate_child() (pulp_smash.tests.pulp2.rpm.api_v2.test_remove_unit.RemoveMissingTest method), 102	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_02_create_on_demand_child() (pulp_smash.tests.pulp2.rpm.api_v2.test_remove_unit.RemoveMissingTest method), 102	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_02_delete_by_href() (pulp_smash.tests.pulp2.rpm.api_v2.test_orphan_remove.OrphanTest method), 100	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_02_delete_by_type_and_id() (pulp_smash.tests.pulp2.rpm.api_v2.test_orphan_remove.OrphanTest method), 100	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_02_find_unit() (pulp_smash.tests.pulp2.rpm.api_v2.test_unassociated.PublishTest method), 130	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46
test_02_force_full_omit() (pulp_smash.tests.pulp2.rpm.api_v2.test_force_full.ForceFullTest method), 93	test_02_get_manifest_list() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.NoAmc method), 46



test_04_read_publications() (pulp_smash.tests.pulp3.file.api_v3.test_crud_publications.PublishTestCases method), 57	test_all() (pulp_smash.tests.pulp2.ostree.api_v2.test_publish.PublishTestCases method), 57
test_04_sync_immediate_child() (pulp_smash.tests.pulp2.rpm.api_v2.test_remove_unit.RemoveMissingTestCases method), 102	test_all() (pulp_smash.tests.pulp2.platform.api_v2.test_consumer.BindConsumerTestCases method), 52
test_04_sync_on_demand_child() (pulp_smash.tests.pulp2.rpm.api_v2.test_remove_unit.RemoveMissingTestCases method), 103	test_all() (pulp_smash.tests.pulp2.puppet.api_v2.test_install_distributor.InstallDistributorTestCases method), 69
test_05_delete() (pulp_smash.tests.pulp3.file.api_v3.test_crud_publications.PublishTestCases method), 153	test_all() (pulp_smash.tests.pulp2.puppet.api_v2.test_install_distributor.InstallDistributorTestCases method), 70
test_05_delete() (pulp_smash.tests.pulp3.file.api_v3.test_crud_publications.PublishTestCases method), 153	test_all() (pulp_smash.tests.pulp2.puppet.api_v2.test_install_distributor.InstallDistributorTestCases method), 71
test_05_delete() (pulp_smash.tests.pulp3.pulpcore.api_v3.test_crud_publications.PublishTestCases method), 162	test_all() (pulp_smash.tests.pulp2.puppet.api_v2.test_install_distributor.InstallDistributorTestCases method), 78
test_05_http_method() (pulp_smash.tests.pulp3.pulpcore.api_v3.test_crud_publications.PublishTestCases method), 165	test_all() (pulp_smash.tests.pulp2.puppet.api_v2.test_install_distributor.InstallDistributorTestCases method), 78
test_05_no_orphans_exist() (pulp_smash.tests.pulp2.rpm.api_v2.test_orphan_remove.OrphanRemoveTestCases method), 100	test_all() (pulp_smash.tests.pulp2.puppet.api_v2.test_install_distributor.InstallDistributorTestCases method), 81
test_05_read_publications() (pulp_smash.tests.pulp3.file.api_v3.test_crud_publications.PublishTestCases method), 151	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_copy.CopyErrataRecursiveTestCases method), 83
test_06_delete() (pulp_smash.tests.pulp3.file.api_v3.test_crud_publications.PublishTestCases method), 151	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_copy.CopyErrataRecursiveTestCases method), 83
test_202_check_run() (tests.test_api.JsonHandlerTestCases method), 174	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_copy.CopyErrataRecursiveTestCases method), 83
test_202_check_run() (tests.test_api.SafeHandlerTestCases method), 174	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_copy.MtimeTestCases method), 83
test_202_check_skipped() (tests.test_api.CodeHandlerTestCases method), 173	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_crud.FeedURLUnquoteTestCases method), 84
test_202_check_skipped() (tests.test_api.EchoHandlerTestCases method), 173	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_crud.PulpDistributionTestCases method), 85
test_204_check_run() (tests.test_api.JsonHandlerTestCases method), 174	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_errata.ApplyErratumTestCases method), 89
test_add_distributor() (pulp_smash.tests.pulp2.rpm.api_v2.test_iso_crud.ISOUpdateTestCases method), 94	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_errata.LargePackageListTestCases method), 89
test_add_importer() (pulp_smash.tests.pulp2.rpm.api_v2.test_iso_crud.ISOUpdateTestCases method), 94	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_iso_crud.ISOUpdateTestCases method), 94
test_after() (pulp_smash.tests.pulp2.rpm.api_v2.test_iso_crud.ISOUpdateTestCases method), 94	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_iso_sync_publish.ServeHTTPTestCases method), 96
test_all() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.PublishTestCases method), 46	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_iso_sync_publish.UploadTestCases method), 96
test_all() (pulp_smash.tests.pulp2.docker.api_v2.test_sync_publish.PublishTestCases method), 46	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist.BadMirrorlistTestCases method), 96
test_all() (pulp_smash.tests.pulp2.docker.api_v2.test_upload_to_repo.UploadToRepoTestCases method), 49	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist.BadRelativeURLTestCases method), 97
test_all() (pulp_smash.tests.pulp2.docker.cli.test_sync_publish.PublishTestCases method), 53	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist.GoodMirrorlistTestCases method), 97
test_all() (pulp_smash.tests.pulp2.ostree.api_v2.test_copy.FileTestCases method), 55	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist.GoodRelativeURLTestCases method), 97
test_all() (pulp_smash.tests.pulp2.ostree.api_v2.test_crud.UploadToRepoTestCases method), 55	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist.MixedMirrorlistTestCases method), 97
	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_mirrorlist.MixedRelativeURLTestCases method), 97
	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_package_paths.ReuseContentTestCases method), 101
	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_remove_unit.RemoveContentTestCases method), 102
	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_repomd.FastForwardInteractionsTestCases method), 103
	test_all() (pulp_smash.tests.pulp2.rpm.api_v2.test_repository_layout.RepositoryLayoutTestCases method), 103

method), 104

test\_all() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_repoviewer.RepoViewTestCases (pulp\_smash.tests.pulp2.rpm.cli.test\_process\_recycling.MaxTasks (pulp\_smash.tests.pulp2.rpm.cli.test\_sync.ForceSyncTestCase (pulp\_smash.tests.pulp2.rpm.cli.test\_sync.RemovedContentTestCase (pulp\_smash.tests.pulp2.rpm.cli.test\_sync.DeletedContentTestCase (pulp\_smash.tests.pulp2.rpm.cli.test\_sync.DownloadContentTestCase (pulp\_smash.tests.pulp2.rpm.cli.test\_sync.PublishAnyRepoTestCase (pulp\_smash.tests.pulp2.rpm.cli.test\_sync.ContentImmutableTestCase (pulp\_smash.tests.pulp2.rpm.cli.test\_sync.MultiResourceLockTestCase (pulp\_smash.tests.pulp2.rpm.cli.test\_sync.SyncChangeRepoVersionTestCase (pulp\_smash.tests.pulp2.rpm.cli.test\_sync.UnlinkingRepoTestCase (pulp\_smash.tests.pulp2.rpm.cli.test\_sync.ArtifactsTestCase (pulp\_smash.tests.pulp2.rpm.cli.test\_sync.ChangeFeedTestCase (pulp\_smash.tests.pulp2.rpm.cli.test\_sync.ReportsTestCase (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_checksums.ChecksumsTestCase (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_checksums.SignedPkgCase (pulp\_smash.tests.pulp2.platform.api\_v2.test\_search.SortTestCases (pulp\_smash.tests.pulp2.platform.api\_v2.test\_repository.CreateRepositoryTestCase (pulp\_smash.tests.pulp2.platform.api\_v2.test\_iso\_crud.CreateTestCases (pulp\_smash.tests.pulp2.platform.api\_v2.test\_user.CreateTestCases (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies.SwitchBackgroundToOnDemandTestCase (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies.SwitchOnDemandToBackgroundTestCase (pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_auth.AuthTestCase (pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_auth.AuthTestCase (pulp\_smash.tests.pulp2.docker.cli.test\_crud.CreateTestCase (pulp\_smash.tests.pulp2.docker.cli.test\_crud.UpdateRpmTestCase





(tests.test\_pulp\_smash\_cli.SettingsCreateTestCase method), 113

method), 177

test\_data() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_repomd.RepoMDTestCases method), 134

test\_data\_gone() (pulp\_smash.tests.pulp2.docker.cli.test\_crud.DeleteV1TestCases method), 52

test\_default\_default() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_comps(pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync\_publish.PublishTestCases method), 79

test\_default\_response\_handler() (tests.test\_cli.ClientTestCase method), 174

test\_default\_uservisible() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_comps\_xml.UploadPackageGroupsTestCases method), 79

test\_defaults() (tests.test\_utils.SearchUnitsTestCase method), 180

test\_delete() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_crud.NonExistentRepoTestCases method), 85

test\_delete() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_schedule\_sync.ReadUpdateDeleteTestCases method), 113

test\_delete\_first\_version() (pulp\_smash.tests.pulp3.file.api\_v3.test\_repo\_version.AddRemoveVersionTestCases method), 156

test\_delete\_last\_version() (pulp\_smash.tests.pulp3.file.api\_v3.test\_repo\_version.AddRemoveVersionTestCases method), 156

test\_delete\_middle\_version() (pulp\_smash.tests.pulp3.file.api\_v3.test\_repo\_version.AddRemoveVersionTestCases method), 157

test\_delete\_publication() (pulp\_smash.tests.pulp3.file.api\_v3.test\_repo\_publication.AddRemovePublicationTestCases method), 157

test\_delete\_user() (pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_auth.WithRoleTestCases method), 160

test\_descending() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_search(SortTestCases method), 64

test\_display\_order\_occurrences() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_comps\_xml.UploadPackageGroupsTestCases method), 79

test\_display\_order\_value() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_comps\_xml.UploadPackageGroupsTestCases method), 79

test\_drpm() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_unassociate.RemoveUnitsTestCases method), 129

test\_drpm() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_unavailable\_checksums.ChecksumTestCases method), 130

test\_drpm() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_unavailable\_checksums.UpdatedChecksumTestCases method), 131

test\_dry\_run() (pulp\_smash.tests.pulp2.platform.cli.test\_pulp\_management.PositiveTestCases method), 67

test\_duplicate\_ids() (pulp\_smash.tests.pulp2.docker.cli.test\_crud.CreateTestCases method), 51

test\_empty\_version\_string() (tests.test\_selectors.ConvertTPRTestCases method), 178

test\_enabled() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_schedule\_sync.InheritanceTestCases method), 136

test\_erratum() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_updateinfo.UpdateInfoTestCases method), 134

test\_error\_details() (pulp\_smash.tests.pulp2.puppet.api\_v2.test\_sync\_publish.PublishTestCases method), 71

test\_exception\_keys\_json() (pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync\_publish.PublishTestCases method), 61

test\_explicit\_local\_transport() (tests.test\_cli.ClientTestCase method), 174

test\_explicit\_pulp\_system() (tests.test\_cli.ClientTestCase method), 174

test\_explicit\_response\_handler() (tests.test\_cli.ClientTestCase method), 174

test\_failure() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_login.LoginTestCases method), 66

test\_failure() (tests.test\_selectors.GetTPRTestCases method), 179

test\_failure() (tests.test\_utils.GetBrokerTestCases method), 175

test\_false() (tests.test\_utils.IsRootTestCases method), 180

test\_add\_remove\_version() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_search.FieldTestCases method), 62

test\_fields() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_search.FieldsTestCases method), 63

test\_first\_level\_element() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_no\_op\_publish.PublishTestCases method), 98

test\_search() (SortTestCases method), 71

test\_get\_authenticated() (pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_status.TestCases method), 47

test\_get\_crane\_repositories() (pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync\_publish.V1RegistryTestCases method), 47

test\_get\_crane\_repositories\_v1() (pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync\_publish.V2RegistryTestCases method), 47

test\_get\_manifest\_list() (pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync\_publish.PublishTestCases method), 47

test\_get\_manifest\_v1() (pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync\_publish.PublishTestCases method), 48

test\_get\_manifest\_v2() (pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync\_publish.PublishTestCases method), 48

test\_get\_systems() (tests.test\_config.HelperMethodsTestCases method), 176

test\_legacy\_numbered\_suite() (tests.test\_config.HelperMethodsTestCases method), 176

(pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_status.StatusTestCases method), 179

test\_global\_search() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_user\_search.SearchTestCase method), 65

test\_has\_groups() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_comps\_xml\_upload.PackageGroupsTestCase method), 80

test\_headers\_location() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_iso\_crud.CreateTestCase method), 94

test\_http\_action() (tests.test\_api.ClientTestCase method), 173

test\_http\_method() (pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_invalid\_docs(ApiDocsTestCases method), 160

test\_httpd() (pulp\_smash.tests.pulp2.platform.cli.test\_selinux.ProcessLabel(TestCase pulp\_smash.tests.pulp2.ostree.api\_v2.test\_crud.UpdateDiskTestCase method), 68

test\_id\_notes() (pulp\_smash.tests.pulp2.puppet.api\_v2.test\_sync\_publish.CreateTestCase method), 70

test\_ids\_alone() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_comps\_xml\_upload.PackageGroupsTestCase method), 80

test\_ids\_unique() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_comps\_xml\_upload.PackageGroupsTestCase method), 80

test\_immediate\_to\_background() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies.SwitchPoliciesTestCase method), 88

test\_immediate\_to\_on\_demand() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies.SwitchPoliciesTestCase method), 88

test\_implicit\_local\_transport() (tests.test\_cli.ClientTestCase method), 174

test\_implicit\_pulp\_system() (tests.test\_cli.ClientTestCase method), 174

test\_importer\_config() (pulp\_smash.tests.pulp2.puppet.api\_v2.test\_sync\_publish.CreateTestCase method), 70

test\_importer\_config() (pulp\_smash.utils.BaseAPICrudTestCase method), 168

test\_importer\_type\_id() (pulp\_smash.tests.pulp2.puppet.api\_v2.test\_sync\_publish.CreateTestCase method), 70

test\_importer\_type\_id() (pulp\_smash.utils.BaseAPICrudTestCase method), 168

test\_include\_repos() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_search.SearchForRpmTestCase method), 114

test\_include\_repos() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_search.SearchForStmTestCase method), 115

test\_incomplete\_filelists() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_sync\_publish.SyncInvalidMetadataTestCase method), 127

test\_incomplete\_other() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_sync\_publish.SyncInvalidMetadataTestCase method), 127

test\_init() (tests.test\_cli.CompletedProcessTestCase method), 175

test\_input\_returned() (tests.test\_cli.CodeHandlerTestCase method), 175

test\_input\_returned() (tests.test\_cli.EchoHandlerTestCase method), 175

test\_invalid\_bug\_id() (tests.test\_selectors.GetBugTestCase method), 179

test\_invalid\_config() (tests.test\_config.ValidateConfigTestCase method), 179

test\_invalid\_config() (tests.test\_pulp\_smash\_cli.SettingsValidateTestCase method), 179

test\_invalid\_file\_feed() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_iso\_crud.CreateTestCase method), 94

test\_invalid\_upstream\_name() (pulp\_smash.tests.pulp2.docker.api\_v2.test\_sync.UpstreamNameTestCase method), 44

test\_invalid\_docs() (pulp\_smash.tests.pulp2.ostree.api\_v2.test\_crud.CreateDiskTestCase method), 55

test\_invalid\_labels() (pulp\_smash.tests.pulp2.ostree.api\_v2.test\_crud.UpdateDiskTestCase method), 56

test\_invalid\_upload() (pulp\_smash.tests.pulp2.ostree.api\_v2.test\_crud.CreateDiskTestCase method), 55

test\_invalid\_upload() (pulp\_smash.tests.pulp2.ostree.api\_v2.test\_crud.UpdateDiskTestCase method), 56

test\_invalid\_v3() (pulp\_smash.tests.pulp2.ostree.api\_v2.test\_crud.UpdateDiskTestCase method), 56

test\_invalid\_version\_string() (tests.test\_selectors.ConvertTPRTestCase method), 179

test\_is\_enabled() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_schedule\_publish.PublishTestCase method), 112

test\_is\_sane() (tests.test\_config.ReprTestCase method), 177

test\_iso() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_duplicate\_uploads.DuplicateUploadTestCase method), 179

test\_json\_arg() (tests.test\_api.ClientTestCase2 method), 173

test\_jwt\_failure() (pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_auth.AuthTestCase method), 160

test\_jwt\_success() (pulp\_smash.tests.pulp3.pulpcore.api\_v3.test\_auth.AuthTestCase method), 160

test\_key\_ids() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_checked.CheckSignaturesTestCase method), 179

test\_kwargs() (tests.test\_config.GetRequestsKwargsTestCase method), 179

test\_kwargs\_auth() (tests.test\_config.GetRequestsKwargsTestCase method), 176

test\_publish\_sync\_links\_invalid\_metadata() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_comps\_xml.SyncRepoTestCase method), 179

test\_list\_content\_sources() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_content\_sources.ValidHostTestCase method), 82

test\_local\_units() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies.SwitchPoliciesTestCase method), 87

test\_location\_header() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_repository.RepositoryTestCase method), 61

test\_location\_header() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_repository.RepositoryTestCase method), 61

method), 61	(pulp_smash.tests.pulp2.rpm.api_v2.test_updateinfo.UpdateInfoT
test_login_filter_exclusion() (pulp_smash.tests.pulp2.platform.api_v2.test_user.CreateTask method), 134	method), 134
method), 65	(pulp_smash.tests.pulp2.rpm.api_v2.test_comps_xml.UploadPack
test_login_filter_inclusion() (pulp_smash.tests.pulp2.platform.api_v2.test_user.CreateTask method), 80	method), 80
method), 66	(pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checke
test_malloc() (pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish.PublishTestCases method), 65	method), 65
test_matching_query() (pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish.PublishTestCases method), 71	method), 71
test_missing_filelists() (pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish.PublishTestCases method), 127	method), 127
test_missing_other() (pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish.PublishTestCases method), 127	method), 127
test_missing_primary() (pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish.PublishTestCases method), 127	method), 127
test_missing_settings_file() (tests.test_pulp_smash_cli.MissingSettingsFileMixin method), 177	method), 180
test_negative() (pulp_smash.tests.pulp2.rpm.api_v2.test_content_applicability.BasicTestCases method), 81	method), 180
test_negative_searches() (pulp_smash.tests.pulp2.rpm.cli.test_search.Search method), 146	method), 180
test_no_change_in_second_sync() (pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish.PublishTestCases method), 127	method), 180
test_no_credentials() (pulp_smash.tests.pulp3.pulpcore.api_v3.test_api_docs.ApiDocsTestCases method), 160	method), 180
test_no_failure() (pulp_smash.tests.pulp2.rpm.api_v2.test_scheduled_publish.PublishTestCases method), 112	method), 180
test_non_matching_query() (pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish.SyncValidFeedTestCases method), 72	method), 180
test_number_importers() (pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish.CreateTestCases method), 70	method), 180
test_number_importers() (pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish.CreateTestCases method), 168	method), 180
test_number_tasks() (pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish.SyncInvalidFeedTestCases method), 71	method), 180
test_number_tasks() (pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish.SyncInvalidFeedTestCases method), 72	method), 180
test_old_config_alert() (tests.test_pulp_smash_cli.SettingsValidationTestCases method), 178	method), 180
test_on_demand_to_background() (pulp_smash.tests.pulp2.rpm.api_v2.test_download_policies.SwitchPoliciesTestCases method), 88	method), 180
test_on_demand_to_immediate() (pulp_smash.tests.pulp2.rpm.api_v2.test_download_policies.SwitchPoliciesTestCases method), 88	method), 180
test_one_task_per_import() (pulp_smash.tests.pulp2.rpm.api_v2.test_comps_xml.UploadPackageGroupTestCases method), 80	method), 180
test_one_task_per_import() (pulp_smash.tests.pulp2.rpm.api_v2.test_comps_xml.UploadPackageGroupTestCases method), 80	method), 180

method), 173

test\_raise\_for\_status() (tests.test\_api.EchoHandlerTestCase method), 173

test\_raise\_for\_status() (tests.test\_api.JsonHandlerTestCase method), 174

test\_raise\_for\_status() (tests.test\_api.SafeHandlerTestCase method), 174

test\_read() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_repository.ReadUpdateDeleteTestCase method), 61

test\_read() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_crud.RepositoryCreateUpdateDeleteTestCase method), 85

test\_read() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_iso\_crud.ReadUpdateDeleteTestCase method), 95

test\_read() (pulp\_smash.utils.BaseAPICrudTestCase method), 168

test\_read\_config\_file() (tests.test\_config.ReadTestCase method), 176

test\_read\_details() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_repository.ReadUpdateDeleteTestCase method), 62

test\_read\_distributors() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_resource.ReadUpdateDeleteTestCase method), 95

test\_read\_imp\_distrib() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_repository.ReadUpdateDeleteTestCase method), 62

test\_read\_importers() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_iso\_crud.ReadUpdateDeleteTestCase method), 95

test\_read\_many() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_schedule\_publish.ReadUpdateDeleteTestCase method), 112

test\_read\_many() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_schedule\_sync.ReadUpdateDeleteTestCase method), 113

test\_read\_old\_config\_file() (tests.test\_config.ReadTestCase method), 176

test\_read\_one() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_schedule\_publish.ReadUpdateDeleteTestCase method), 112

test\_read\_one() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_schedule\_sync.ReadUpdateDeleteTestCase method), 113

test\_reboot\_not\_suggested() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_updateinfo.UpdateInfoTestCase method), 134

test\_refresh\_content\_sources() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_content\_sources.ValidHeaderTestCase method), 82

test\_refresh\_content\_sources() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_content\_sources.ValidHeadersTestCase method), 83

test\_remote\_units\_path() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_rsyc\_distributors.VerifyOptionsTestCase method), 111

test\_repo\_gone() (pulp\_smash.tests.pulp2.docker.cli.test\_crud.DeleteV2TestCases method), 52

test\_repo\_local\_units() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies.BackgroundTestCase method), 86

test\_repo\_registry\_id\_flag() (pulp\_smash.tests.pulp2.docker.cli.test\_crud.UpdateDistributorsTestCase method), 52

test\_repo\_units\_consistency() (pulp\_smash.tests.pulp2.puppet.api\_v2.test\_sync\_publish.PublishTestCase method), 71

test\_repository\_units() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies.BackgroundTestCase method), 87

test\_request\_history() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies.BackgroundTestCase method), 87

test\_request\_history() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies.BackgroundTestCase method), 87

test\_required\_options() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_rsync\_distrosync.VerifyOptionsTestCase method), 174

test\_required\_stopped() (pulp\_smash.tests.pulp2.platform.cli.test\_pulp\_manage\_db.NegativeTestCase method), 66

test\_reserved\_resource\_worker\_0() (pulp\_smash.tests.pulp2.platform.cli.test\_selinux.ProcessLabelsTestCase method), 68

test\_repository\_read\_duplicate\_test\_cases() (pulp\_smash.tests.pulp2.platform.cli.test\_selinux.ProcessLabelsTestCase method), 68

test\_resource\_read\_duplicate\_test\_cases() (pulp\_smash.tests.pulp2.platform.cli.test\_selinux.ProcessLabelsTestCase method), 68

test\_repository\_read\_duplicate\_test\_cases() (pulp\_smash.tests.pulp2.platform.cli.test\_selinux.ProcessLabelsTestCase method), 68

test\_response\_handler() (tests.test\_api.ClientTestCase2 method), 173

test\_result\_ids() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_search.FiltersTestCase method), 63

test\_result\_ids() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_search.FiltersTestCase method), 63

test\_results() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_search.LimitSkipTestCase method), 63

test\_schedule\_publish() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_retain\_old\_count.RetainOldCountTestCase method), 107

test\_schedule\_sync() (pulp\_smash.tests.pulp2.rpm.cli.test\_retain\_old\_count.RetainOldCountTestCase method), 146

test\_retain\_zero() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_retain\_old\_count.RetainOldCountTestCase method), 146

test\_retain\_zero() (pulp\_smash.tests.pulp2.rpm.cli.test\_retain\_old\_count.RetainOldCountTestCase method), 146

test\_return\_valid\_headers\_test\_cases() (tests.test\_api.CodeHandlerTestCase method), 173

test\_return() (tests.test\_api.EchoHandlerTestCase method), 174

test\_return() (tests.test\_api.JsonHandlerTestCase method), 174

test\_return() (tests.test\_api.SafeHandlerTestCase method), 174

test\_returncode\_zero() (tests.test\_utils.OsIsF26TestCase method), 180

test\_returncode\_zero() (tests.test\_utils.OsIsF26TestCase method), 180

test\_distribution\_test\_cases() (pulp\_smash.tests.pulp2.docker.cli.test\_crud.UpdateDistributorsTestCase method), 52

(pulp\_smash.tests.pulp2.platform.api\_v2.test\_user\_search\_test\_case\_for\_roles() (tests.test\_config.HelperMethodsTestCase method), 66

test\_roles\_filter\_inclusion() (pulp\_smash.tests.pulp2.platform.api\_v2.test\_user.SearchTestCase method), 66

test\_root() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_comps\_xml.UploadPackageCleanupTestCasesSettingsCreateTestCase method), 80

test\_root() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_rsync\_distribution\_verify\_options\_test\_case pulp\_smash\_cli.SettingsPathTestCase method), 111

test\_rpm() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_duplicate\_test\_settings\_display\_updates\_test\_case pulp\_smash\_cli.SettingsShowTestCase method), 89

test\_rpm() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_unassociated\_remove\_unit\_test\_case pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_check\_method), 129

test\_rpm() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_unavailable\_checks\_drpm() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_check\_method), 130

test\_rpm() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_unavailable\_checks\_drpm() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_check\_method), 131

test\_rpm\_cache\_control\_header() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies\_on\_demand\_test\_case pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_save\_method), 87

test\_rpm\_cache\_lookup\_header() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies\_on\_demand\_test\_case pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_save\_method), 87

test\_rpm\_checksum() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies\_on\_demand\_test\_case pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_save\_method), 86

test\_rpm\_checksum() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies\_on\_demand\_test\_case pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_save\_method), 87

test\_run() (tests.test\_utils.PulpAdminLoginTestCase test\_signed\_packages() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_save\_method), 180

test\_same\_rpm\_cache\_header() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies\_on\_demand\_test\_case pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_save\_method), 87

test\_same\_rpm\_checksum() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_download\_policies\_on\_demand\_test\_case pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_save\_method), 87

test\_search\_for\_all() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signed\_packages() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_save\_method), 115

test\_search\_for\_all() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signed\_packages() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_save\_method), 115

test\_second\_level\_elements() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_comps\_xml.SyncReplicasCheck method), 79

test\_second\_publish\_repomd() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_no\_op\_publish\_signing\_repomd\_test\_case pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_check\_method), 99

test\_second\_publish\_repomd() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_no\_op\_publish.NoOpPublishMixin test\_signed\_rpm() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_check\_method), 99

test\_second\_publish\_tasks() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_no\_op\_publish\_signing\_repomd\_test\_case pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_check\_method), 99

test\_second\_publish\_tasks() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_no\_op\_publish.NoOpPublishMixin test\_signed\_rpm() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_signatures\_save\_method), 99



method), 73	test_unsigned_drpm() (pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_
test_tag() (pulp_smash.tests.pulp2.rpm.api_v2.test_repomd.RepoMDTestCases	method), 125
method), 103	test_unsigned_drpm() (pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_
test_task_error_traceback()	method), 125
(pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish.SyncInvalidFeedTestCases	method), 119
method), 71	test_unsigned_drpm() (pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_
test_task_progress_report()	method), 119
(pulp_smash.tests.pulp2.ostree.api_v2.test_sync.SyncTestCase method), 58	test_unsigned_drpm() (pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_
method), 58	method), 120
test_task_progress_report()	test_publish.SyncValidManifestFeedTestCase
(pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish.SyncValidManifestFeedTestCases	(pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for
method), 72	method), 117
test_task_progress_report()	test_publish.SyncRepoBakeTestCase
(pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish.SyncRepoBakeTestCases	(pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for
method), 127	method), 117
test_tasks_result() (pulp_smash.tests.pulp2.rpm.api_v2.test_comps_xmlUploadPackageGroupsTestCase	test_unsigned_packages()
method), 80	(pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for
test_tasks_result() (pulp_smash.tests.pulp2.rpm.api_v2.test_updateinfoUploadInfoTestCase	method), 117
method), 134	test_unsigned_packages()
test_tasks_state() (pulp_smash.tests.pulp2.rpm.api_v2.test_comps_xmlUploadPackageGroupsTestCase	(pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for
method), 80	method), 118
test_tasks_state() (pulp_smash.tests.pulp2.rpm.api_v2.test_updateinfoUploadInfoTestCase	test_unsigned_packages()
method), 134	(pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for
test_tear_down_class() (tests.test_utils.BaseAPITestCase	method), 118
method), 179	test_unsigned_packages()
test_testable_status() (tests.test_selectors.BugIsTestableTestCase	(pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for
method), 178	method), 121
test_total_run_count() (pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_publish.CreateSuccessTestCase	test_unsigned_packages()
method), 112	(pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for
test_total_run_count() (pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_publish.SyncPublishTestCase	method), 121
method), 112	test_unsigned_packages()
test_total_run_count() (pulp_smash.tests.pulp2.rpm.api_v2.test_schedule_publish.SyncPublishTestCase	(pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for
method), 113	method), 121
test_translated_string_count()	(pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for
(pulp_smash.tests.pulp2.rpm.api_v2.test_comps_xmlUploadPackageGroupsTestCase	method), 123
method), 80	(pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for
test_translated_string_values()	method), 123
(pulp_smash.tests.pulp2.rpm.api_v2.test_comps_xmlUploadPackageGroupsTestCase	method), 123
method), 80	test_unsigned_packages()
test_true() (tests.test_utils.IsRootTestCase method), 180	(pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for
test_type() (tests.test_utils.UUID4TestCase method), 180	method), 123
test_unit_count_on_repo()	test_unsigned_packages()
(pulp_smash.tests.pulp2.rpm.api_v2.test_sync_publish.SyncRepoTestCases	(pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_checked_for
method), 127	method), 125
test_unit_integrity() (pulp_smash.tests.pulp2.puppet.api_v2.test_sync_publish.PublishTestCase	test_unsigned_rpm() (pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_s
method), 71	test_unsigned_rpm() (pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_s
test_units_after_download()	method), 125
(pulp_smash.tests.pulp2.rpm.api_v2.test_download_policy_fix_fix_group_fix_group_fix_group_fix_group	test_unsigned_rpm() (pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_c
method), 86	method), 119
test_units_before_download()	test_unsigned_rpms() (pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_c
(pulp_smash.tests.pulp2.rpm.api_v2.test_download_policy_fix_fix_group_fix_group_fix_group_fix_group	test_unsigned_rpms() (pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_c
method), 87	method), 120
test_unknown_status() (tests.test_selectors.BugIsTestableTestCase	test_unsigned_srpm() (pulp_smash.tests.pulp2.rpm.api_v2.test_signatures_s
method), 178	





(pulp\_smash.tests.pulp2.docker.cli.test\_crud.CreateTestCase.pulp\_smash.tests.pulp2.rpm.api\_v2.test\_updateinfo), method), 51 135

test\_workers\_running() (pulp\_smash.tests.pulp2.platform.cli.test\_updateinfo.NegativeTestCase in method), 67 pulp\_smash.tests.pulp2.rpm.cli.test\_copy\_units), 143

tests (module), 173

tests.test\_api (module), 173

tests.test\_cli (module), 174

tests.test\_config (module), 175

tests.test\_pulp\_smash\_cli (module), 177

tests.test\_selectors (module), 178

tests.test\_utils (module), 179

## U

UnassociateTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_republish), 106

UnavailableChecksumTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_unavailable\_checksum), 130

uninstall() (pulp\_smash.cli.PackageManager method), 26

update\_body() (pulp\_smash.tests.pulp2.docker.api\_v2.test\_crud.CrudTestCase static method), 43

update\_body() (pulp\_smash.tests.pulp2.ostree.api\_v2.test\_crud.CrudTestCase static method), 56

update\_body() (pulp\_smash.tests.pulp2.puppet.api\_v2.test\_crud.CrudTestCase static method), 69

update\_body() (pulp\_smash.tests.pulp2.python.api\_v2.test\_crud.CRUDTestCase static method), 74

update\_body() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_crud.CrudTestCase static method), 84

update\_body() (pulp\_smash.tests.pulp2.rpm.api\_v2.test\_crud.CrudTestCase static method), 169

UpdatedChecksumTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_unavailable\_checksum), 131

UpdateDistributorsTestCase (class in pulp\_smash.tests.pulp2.ostree.api\_v2.test\_crud), 56

UpdateDistributorTestCase (class in pulp\_smash.tests.pulp2.docker.cli.test\_crud), 52

UpdateEnableV1TestCase (class in pulp\_smash.tests.pulp2.docker.cli.test\_crud), 52

UpdateEnableV2TestCase (class in pulp\_smash.tests.pulp2.docker.cli.test\_crud), 52

UpdateImportersTestCase (class in pulp\_smash.tests.pulp2.ostree.api\_v2.test\_crud), 57

UpdateInfoTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_updateinfo), 134

UpdateRepoTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_updateinfo), 135

UploadAndRemoveLangpacksTestCase (class in pulp\_smash.tests.pulp2.rpm.cli.test\_langpacks), 144

UploadDrpmTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_upload\_publish), 135

UploadDrpmTestCase (class in pulp\_smash.tests.pulp2.rpm.cli.test\_upload), 148

UploadDrpmTestCaseWithChecksumType (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_upload\_publish), 136

UploadDrpmChecksumTypeTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_upload\_publish), 137

UploadImportErratumTestCase (class in tests.test\_utils), 180

UploadImportUnitTestCase (class in tests.test\_utils), 180

UploadInvalidRPMTTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_upload\_publish), 136

UploadIsoTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_iso\_sync\_publish), 96

UploadManifestListV2TestCase (class in pulp\_smash.tests.pulp2.docker.api\_v2.test\_upload), 49

UploadNonAsciiTestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_character\_encoding), 78

UploadNonAsciiTestCase (class in pulp\_smash.tests.pulp2.rpm.cli.test\_character\_encoding), 142

UploadNonUtf8TestCase (class in pulp\_smash.tests.pulp2.rpm.api\_v2.test\_character\_encoding), 78

UploadNonUtf8TestCase (class in pulp\_smash.tests.pulp2.rpm.cli.test\_character\_encoding), 142

UploadPackageEnvTestCase (class in pulp\_smash.tests.pulp2.rpm.cli.test\_environments), 144

[UploadPackageGroupsTestCase](#) (class in [verify\\_description\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_updateinfo.UpdateInfo](#)), [pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_comps\\_xml](#), method), [134](#)  
[79](#) [verify\\_filelists\\_xml\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_unavailable\\_checksum](#), method), [131](#)  
[UploadPackageTestCase](#) (class in [verify\\_filelists\\_xml\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_unavailable\\_checksum](#)), [pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_signature\\_verified\\_for\\_release\(\)](#) ([pulp\\_smash.tests.pulp3.pulpcore.api\\_v3.test\\_status.Success](#)), method), [164](#)  
[125](#) [verify\\_id\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_updateinfo.UpdateInfo](#)), [134](#)  
[UploadRpmTestCase](#) (class in [verify\\_id\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_updateinfo.UpdateInfo](#)), [pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_upload\\_publish](#), method), [134](#)  
[136](#) [verify\\_issued\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_updateinfo.UpdateInfo](#)), [134](#)  
[UploadSrpmTestCase](#) (class in [verify\\_issued\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_updateinfo.UpdateInfo](#)), [pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_upload\\_publish](#), method), [131](#)  
[137](#) [verify\\_package\\_types\(\)](#) ([pulp\\_smash.tests.pulp2.python.api\\_v2.test\\_sync\\_publish](#)), [75](#)  
[UploadTestCase](#) (class in [verify\\_package\\_types\(\)](#) ([pulp\\_smash.tests.pulp2.python.api\\_v2.test\\_sync\\_publish](#)), [pulp\\_smash.tests.pulp2.python.api\\_v2.test\\_sync\\_publish](#), method), [75](#)  
[76](#) [verify\\_pkgid\\_len\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_unavailable\\_checksum](#), method), [131](#)  
[UploadTwiceTestCase](#) (class in [verify\\_pkgid\\_len\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_unavailable\\_checksum](#)), [pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_comps\\_xml](#), method), [131](#)  
[81](#) [verify\\_pkglist\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_updateinfo.UpdateInfo](#)), [135](#)  
[UpstreamNameTestsMixin](#) (class in [verify\\_presto\\_delta\\_xml\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_unavailable\\_checksum](#)), [pulp\\_smash.tests.pulp2.docker.api\\_v2.test\\_sync](#), method), [131](#)  
[44](#) [verify\\_primary\\_xml\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_unavailable\\_checksum](#)), [131](#)  
[UpstreamNameV1TestCase](#) (class in [verify\\_primary\\_xml\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_unavailable\\_checksum](#)), [pulp\\_smash.tests.pulp2.docker.api\\_v2.test\\_sync](#), method), [131](#)  
[44](#) [verify\\_references\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_updateinfo.UpdateInfo](#)), [135](#)  
[UpstreamNameV2TestCase](#) (class in [verify\\_references\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_updateinfo.UpdateInfo](#)), [pulp\\_smash.tests.pulp2.docker.api\\_v2.test\\_sync](#), method), [135](#)  
[45](#) [verify\\_repo\\_download\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_upload\\_publish](#)), [137](#)  
[USER\\_PATH](#) (in module [verify\\_repo\\_search\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_upload\\_publish](#)), [pulp\\_smash.tests.pulp2.constants](#)), [42](#)  
[137](#) [verify\\_solution\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_updateinfo.UpdateInfo](#)), [135](#)  
[UsersCRUDTestCase](#) (class in [verify\\_solution\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_updateinfo.UpdateInfo](#)), [pulp\\_smash.tests.pulp3.pulpcore.api\\_v3.test\\_crud\\_users](#), method), [135](#)  
[163](#) [verify\\_status\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_updateinfo.UpdateInfo](#)), [135](#)  
[UtilsMixin](#) (class in [pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_mirrorlist](#), method), [135](#)  
[97](#) [verify\\_sync\(\)](#) ([pulp\\_smash.tests.pulp2.python.api\\_v2.test\\_sync\\_publish.Base](#)), [75](#)  
[UtilsMixin](#) (class in [pulp\\_smash.tests.pulp2.rpm.cli.test\\_copy\\_units](#), method), [75](#)  
[143](#) [verify\\_title\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_updateinfo.UpdateInfo](#)), [135](#)  
[uuid4\(\)](#) (in module [pulp\\_smash.utils](#)), [172](#)  
[135](#) [verify\\_type\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_updateinfo.UpdateInfo](#)), [135](#)  
[UUID4TestCase](#) (class in [tests.test\\_utils](#)), [180](#)  
[135](#) [verify\\_v1\\_repo\(\)](#) ([pulp\\_smash.tests.pulp2.docker.api\\_v2.test\\_sync\\_publish.Base](#)), [47](#)  
**V** [verify\\_version\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_updateinfo.UpdateInfo](#)), [135](#)  
[V1RegistryTestCase](#) (class in [verify\\_version\(\)](#) ([pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_updateinfo.UpdateInfo](#)), [pulp\\_smash.tests.pulp2.docker.api\\_v2.test\\_sync\\_publish](#), method), [135](#)  
[47](#) [VerifyOptionsTestCase](#) (class in [pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_rsync\\_distributor](#)), [110](#)  
[V2RegistryTestCase](#) (class in [pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_rsync\\_distributor](#)), [pulp\\_smash.tests.pulp2.docker.api\\_v2.test\\_sync\\_publish](#), [110](#)  
[47](#) [validate\\_config\(\)](#) (in module [pulp\\_smash.config](#)), [31](#)  
[110](#) **W**  
[ValidateConfigTestCase](#) (class in [tests.test\\_config](#)), [177](#)  
[ValidHeadersTestCase](#) (class in [WorkersTestCase](#) (class in [pulp\\_smash.tests.pulp3.pulpcore.api\\_v3.test\\_workers](#)), [pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_content\\_sources](#)), [164](#)  
[82](#) [write\\_manifest\\_list\(\)](#) (in module [pulp\\_smash.tests.pulp2.docker.utils](#)), [54](#)  
[VendorInfoTestCase](#) (class in [write\\_manifest\\_list\(\)](#) (in module [pulp\\_smash.tests.pulp2.docker.utils](#)), [pulp\\_smash.tests.pulp2.rpm.api\\_v2.test\\_upload\\_publish](#)), [138](#)  
[138](#)

`write_private_key()` (`pulp_smash.tests.pulp2.rpm.api_v2.utils.TemporaryUserMixin`  
method), 139

## X

`xml_handler()` (in `module`  
`pulp_smash.tests.pulp2.rpm.api_v2.utils`),  
141