
pyexcel-io Documentation

Release 0.2.6

Onni Software Ltd.

January 11, 2017

1	Introduction	3
2	Installation	5
2.1	API changes from 0.1.0 to 0.2.0	6
2.2	Working with CSV format	6
2.3	Read partial data	8
2.4	Saving multiple sheets as CSV format	9
2.5	File formats: .csvz and .tsvz	11
2.6	Working with sqlalchemy	12
2.7	Working with django database	16
2.8	Working with xls, xlsx, and ods formats	18
3	API	21
3.1	pyexcel_io.get_data	21
3.2	pyexcel_io.save_data	21
4	Indices and tables	23

Author C.W.

Source code <http://github.com/pyexcel/pyexcel-io.git>

Issues <http://github.com/pyexcel/pyexcel-io/issues>

License New BSD License

Development 0.2.6

Released 0.2.5

Generated January 11, 2017

Introduction

pyexcel-io provides **one** application programming interface(API) to read and write data in different excel formats. It makes information processing involving excel files a simple task. The data in excel files can be turned into an ordered dictionary with least code. This library focuses on data processing using excel files as storage media hence fonts, colors and charts were not and will not be considered.

It was created due to the lack of uniform programming interface to access data in different excel formats. A developer needs to use different methods of different libraries to read the same data in different excel formats, hence the resulting code is cluttered and unmaintainable. This is a challenge posed by users who do not know or care about the differences in excel file formats. Instead of educating the users about the specific excel format a data processing application supports, the library takes up the challenge and promises to support all known excel formats.

All great work have done by individual library developers. This library unites only the data access API. With that said, **pyexcel-io** also bring something new on the table: “*csvz*” and “*tsvz*” format, new format names as of 2014. They are invented and supported by **pyexcel-io**.

Installation

You can install it via pip:

```
$ pip install pyexcel-io
```

or clone it and install it:

```
$ git clone http://github.com/pyexcel/pyexcel-io.git
$ cd pyexcel-io
$ python setup.py install
```

For individual excel file formats, please install them as you wish:

Table 2.1: A list of file formats supported by external plugins

Package name	Supported file formats	Dependencies	Python versions
pyexcel-io	csv, csvz ¹ , tsv, tsvz ²		2.6, 2.7, 3.3, 3.4, 3.5, pypy
pyexcel-xls	xls, xlsx(read only), xlsx(read only)	xlrd , xlwt	same as above
pyexcel-xlsx	xlsx	openpyxl	same as above
pyexcel-xlsxw	xlsx(write only)	XlsxWriter	same as above
pyexcel-ods3	ods	ezodf , lxml	2.6, 2.7, 3.3, 3.4 3.5
pyexcel-ods	ods	odfpy	same as above

After that, you can start get and save data in the loaded format. There are two plugins for the same file format, e.g. [pyexcel-ods3](#) and [pyexcel-ods](#). If you want to choose one, please try pip uninstall the un-wanted one. And if you want to have both installed but wanted to use one of them for a function call(or file type) and the other for another function call(or file type), you can pass on “library” option to `get_data` and `save_data`.

Table 2.2: Plugin compatibility table

pyexcel-io	xls	xlsx	ods	ods3	xlsxw
0.2.2	0.2.2	0.2.2	0.2.1	0.2.1	0.0.1
0.2.0+	0.2.0+	0.2.0+	0.2.0	0.2.0	0.0.1

Note: [pyexcel-text](#) is no longer a plugin of [pyexcel-io](#) but a direct plugin of [pyexcel](#)

¹zipped csv file

²zipped tsv file

2.1 API changes from 0.1.0 to 0.2.0

pyexcel-io version 0.2.0 is not 100% backward compatible and requires version 0.2.0 of its plugins to function seamlessly. Here are the differences.

2.1.1 `get_data` returns a dictionary of two dimensional array always

Version 0.1.0 and elder, `get_data` returns a two dimensional array if there is only one sheet and returns a dictionary of two dimensional array otherwise. This behaviour has removed in 0.2.0

2.1.2 `load_data` is deprecated and should not be used

Version 0.1.0 and elder, `load_data` was used by pyexcel and maybe by others. Version 0.2.0 discourage you from using it as it will be removed at some point in the future.

2.1.3 `auto_dectect_datetime`

The datetime formats are:

1. `%Y-%m-%d`
2. `%Y-%m-%d %H:%M:%S`
3. `%Y-%m-%d %H:%M:%S.%f`

Any other datetime formats will be thrown as `ValueError`

2.1.4 'library' option is added

In order to have overlapping plugins co-exist, 'library' option is added to `get_data` and `save_data`.

2.2 Working with CSV format

Please note that csv reader load data in a lazy manner. It ignores excessive trailing cells that has `None` value. For example, the following csv content:

```
1,2,,,,,  
3,4,,,,,  
5,,,,,,
```

would end up as:

```
1,2  
3,4  
5,
```

2.2.1 Write to a csv file

Here's the sample code to write an array to a csv file

```
>>> import datetime
>>> from pyexcel_io import save_data
>>> data = [
...     [1, 2.0, 3.0],
...     [
...         datetime.date(2016, 5, 4),
...         datetime.datetime(2016, 5, 4, 17, 39, 12),
...         datetime.datetime(2016, 5, 4, 17, 40, 12, 100)
...     ]
... ]
>>> save_data("your_file.csv", data)
```

Let's verify the file content:

```
>>> with open("your_file.csv", "r") as csvfile:
...     for line in csvfile.readlines():
...         print(line.strip())
1,2.0,3.0
2016-05-04,2016-05-04 17:39:12,2016-05-04 17:40:12.000100
```

Change line endings

By default, python csv module provides windows line ending 'rn'. In order to change it, you can do:

```
>>> save_data("your_file.csv", data, lineterminator='\n')
```

2.2.2 Read from a csv file

And we can read the written csv file back as the following code:

```
>>> from pyexcel_io import get_data
>>> import pprint
>>> data = get_data("your_file.csv")
>>> pprint.pprint(data['your_file.csv'])
[[1, 2.0, 3.0],
 [datetime.date(2016, 5, 4),
  datetime.datetime(2016, 5, 4, 17, 39, 12),
  datetime.datetime(2016, 5, 4, 17, 40, 12, 100)]]
```

As you can see, pyexcel-io not only reads the csv file back but also recognizes the data types: *int*, *float*, *date* and *datetime*. However, it does give your cpu some extra job. When you are handling a large csv file and the cpu budget is of your concern, you may switch off the type detection feature. For example, let's switch all off:

```
>>> data = get_data("your_file.csv", auto_detect_float=False, auto_detect_datetime=False)
>>> import json
>>> json.dumps(data['your_file.csv'])
'[[1, "2.0", "3.0"], ["2016-05-04", "2016-05-04 17:39:12", "2016-05-04 17:40:12.000100"]]'
```

In addition to *auto_detect_float* and *auto_detect_datetime*, there is another flag named *auto_detect_int*, which becomes active only if *auto_detect_float* is *True*. Now, let's play a bit with *auto_detect_int*:

```
>>> data = get_data("your_file.csv", auto_detect_int=False)
>>> pprint.pprint(data['your_file.csv'])
[[1.0, 2.0, 3.0],
 [datetime.date(2016, 5, 4),
  datetime.datetime(2016, 5, 4, 17, 39, 12),
  datetime.datetime(2016, 5, 4, 17, 40, 12, 100)]]
```

As you see, all numeric data are identified as float type. If you looked a few paragraphs above, you would notice `auto_detect_int` affected `[1, 2, ..]` in the first row.

2.2.3 Write a csv to memory

Here's the sample code to write a dictionary as a csv into memory:

```
>>> from pyexcel_io import save_data
>>> data = [[1, 2, 3], [4, 5, 6]]
>>> io = StringIO()
>>> save_data(io, data)
>>> # do something with the io
>>> # In reality, you might give it to your http response
>>> # object for downloading
```

2.2.4 Read from a csv from memory

Continue from previous example:

```
>>> # This is just an illustration
>>> # In reality, you might deal with csv file upload
>>> # where you will read from requests.FILES['YOUR_XL_FILE']
>>> import json
>>> data = get_data(io)
>>> print(json.dumps(data))
{"csv": [[1, 2, 3], [4, 5, 6]]}
```

2.3 Read partial data

When you are dealing with huge amount of data, obviously you would not like to fill up your memory with those data. Here is a the feature to support pagination of your data.

Let's assume the following file is a huge csv file:

```
>>> import datetime
>>> from pyexcel_io import save_data
>>> data = [
...     [1, 21, 31],
...     [2, 22, 32],
...     [3, 23, 33],
...     [4, 24, 34],
...     [5, 25, 35],
...     [6, 26, 36]
... ]
>>> save_data("your_file.csv", data)
```

And let's pretend to read partial data:

```
>>> from pyexcel_io import get_data
>>> data = get_data("your_file.csv", start_row=2, row_limit=3)
>>> data['your_file.csv']
[[3, 23, 33], [4, 24, 34], [5, 25, 35]]
```

And you could as well do the same for columns:

```
>>> data = get_data("your_file.csv", start_column=1, column_limit=2)
>>> data['your_file.csv']
[[21, 31], [22, 32], [23, 33], [24, 34], [25, 35], [26, 36]]
```

Obvious, you could do both at the same time:

```
>>> data = get_data("your_file.csv",
...     start_row=2, row_limit=3,
...     start_column=1, column_limit=2)
>>> data['your_file.csv']
[[23, 33], [24, 34], [25, 35]]
```

The pagination support is available across all pyexcel-io plugins.

Rendering(Formatting) the data

You might want to do custom rendering on your data obtained. *row_renderer* was added since version 0.2.3. Here is how you can use it.

Let's assume the following file:

```
>>> import datetime
>>> from pyexcel_io import save_data
>>> data = [
...     [1, 21, 31],
...     [2, 22, 32],
...     [3, 23, 33]
... ]
>>> save_data("your_file.csv", data)
```

And let's read them back:

```
>>> from pyexcel_io import get_data
>>> data = get_data("your_file.csv")
>>> data['your_file.csv']
[[1, 21, 31], [2, 22, 32], [3, 23, 33]]
```

And you may want use *row_renderer* to customize it to string:

```
>>> def my_renderer(row):
...     return [str(element) for element in row]
>>> data = get_data("your_file.csv", row_renderer=my_renderer)
>>> data['your_file.csv']
[['1', '21', '31'], ['2', '22', '32'], ['3', '23', '33']]
```

2.4 Saving multiple sheets as CSV format

2.4.1 Write to multiple sibling csv files

Here's the sample code to write a dictionary to multiple sibling csv files:

```
>>> from pyexcel_io import save_data
>>> data = OrderedDict() # from collections import OrderedDict
>>> data.update({"Sheet 1": [[1, 2, 3], [4, 5, 6]]})
>>> data.update({"Sheet 2": [{"row 1", "row 2", "row 3"}]})
>>> save_data("your_file.csv", data)
```

2.4.2 Read from multiple sibling csv files

Here's the sample code:

```
>>> from pyexcel_io import get_data
>>> data = get_data("your_file.csv")
>>> import json
>>> print(json.dumps(data))
{"Sheet 1": [[1, 2, 3], [4, 5, 6]], "Sheet 2": [{"row 1", "row 2", "row 3"}]}
```

Here is what you would get:

```
>>> import glob
>>> list = glob.glob("your_file_*.csv")
>>> json.dumps(sorted(list))
'["your_file__Sheet 1__0.csv", "your_file__Sheet 2__1.csv"]'
```

2.4.3 Write multiple sibling csv files to memory

Here's the sample code to write a dictionary of named two dimensional array into memory:

```
>>> from pyexcel_io import save_data
>>> data = OrderedDict()
>>> data.update({"Sheet 1": [[1, 2, 3], [4, 5, 6]]})
>>> data.update({"Sheet 2": [[7, 8, 9], [10, 11, 12]]})
>>> io = StringIO()
>>> save_data(io, data)
>>> # do something with the io
>>> # In reality, you might give it to your http response
>>> # object for downloading
```

2.4.4 Read multiple sibling csv files from memory

Continue from previous example:

```
>>> # This is just an illustration
>>> # In reality, you might deal with csv file upload
>>> # where you will read from requests.FILES['YOUR_XL_FILE']
>>> data = get_data(io)
>>> print(json.dumps(data))
{"Sheet 1": [[1, 2, 3], [4, 5, 6]], "Sheet 2": [[7, 8, 9], [10, 11, 12]]}
```

2.5 File formats: .csvz and .tsvz

2.5.1 Introduction

'csvz' and 'tsvz' are newly invented excel file formats by pyexcel. Simply put, 'csvz' is the zipped content of one or more csv file(s). 'tsvz' is the twin brother of 'csvz'. They are similiar to the implementation of xlsx format, which is a zip of excel content in xml format.

The obvious tangile benefit of zipped csv over normal csv is the reduced file size. However, the drawback is the need of unzipping software.

2.5.2 Single Sheet

When a single sheet is to be saved, the resulting csvz file will be a zip file that contains one csv file bearing the name of `Sheet`.

```
>>> from pyexcel_io import save_data
>>> data = [[1,2,3]]
>>> save_data("myfile.csvz", data)
>>> import zipfile
>>> zip = zipfile.ZipFile("myfile.csvz", 'r')
>>> zip.namelist()
['pyexcel_sheet1.csv']
>>> zip.close()
```

And it can be read out as well and can be saved in any other supported format.

```
>>> from pyexcel_io import get_data
>>> data = get_data("myfile.csvz")
>>> import json
>>> json.dumps(data)
'{"pyexcel_sheet1": [[1, 2, 3]]}'
```

2.5.3 Multiple Sheet Book

When multiple sheets are to be saved as a book, the resulting csvz file will be a zip file that contains each sheet as a csv file name

```
>>> from pyexcel_io._compact import OrderedDict
>>> content = OrderedDict()
>>> content.update({
...     'Sheet 1':
...     [
...         [1.0, 2.0, 3.0],
...         [4.0, 5.0, 6.0],
...         [7.0, 8.0, 9.0]
...     ]
... })
>>> content.update({
...     'Sheet 2':
...     [
...         ['X', 'Y', 'Z'],
...         [1.0, 2.0, 3.0],
...         [4.0, 5.0, 6.0]
...     ]
... })
```

```

... })
>>> content.update({
...     'Sheet 3':
...     [
...         ['O', 'P', 'Q'],
...         [3.0, 2.0, 1.0],
...         [4.0, 3.0, 2.0]
...     ]
... })
>>> save_data("mybook.csvz", content)
>>> import zipfile
>>> zip = zipfile.ZipFile("mybook.csvz", 'r')
>>> zip.namelist()
['Sheet 1.csv', 'Sheet 2.csv', 'Sheet 3.csv']
>>> zip.close()

```

The csvz book can be read back with two lines of code. And once it is read out, it can be saved in any other supported format.

```

>>> book2 = get_data("mybook.csvz")
>>> json.dumps(book2)
'{"Sheet 1": [[1.0, 2.0, 3.0], [4.0, 5.0, 6.0], [7.0, 8.0, 9.0]], "Sheet 2": [{"X", "Y", "Z"}, [1.0,

```

2.5.4 Open csvz without pyexcel-io

All you need is a unzipping software. I would recommend 7zip which is open source and is available on all available OS platforms.

On latest Windows platform (windows 8), zip file is supported so just give the “csvz” file a file extension as “.zip”. The file can be opened by File Explorer.

2.6 Working with sqlalchemy

Suppose we have a pure sql database connection via sqlalchemy:

```

>>> from sqlalchemy import create_engine
>>> from sqlalchemy.ext.declarative import declarative_base
>>> from sqlalchemy import Column, Integer, String, Float, Date
>>> from sqlalchemy.orm import sessionmaker
>>> engine=create_engine("sqlite:///sqlalchemy.db")
>>> Base=declarative_base()
>>> Session=sessionmaker(bind=engine)

```

2.6.1 Write data to a database table

Assume we have the following database table:

```

>>> class Pyexcel(Base):
...     __tablename__='pyexcel'
...     id=Column(Integer, primary_key=True)
...     name=Column(String)
...     weight=Column(Float)
...     birth=Column(Date)

```


Let's clear the database and create previous table in the database:

```
>>> Base.metadata.create_all(engine)
```

And suppose we have the following data structure to be saved:

```
>>> import datetime
>>> data = [
...     ['birth', 'id', 'name', 'weight'],
...     [datetime.date(2014, 11, 11), 0, 'Adam', 11.25],
...     [datetime.date(2014, 11, 12), 1, 'Smith', 12.25]
... ]
```

Here's the actual code to achieve it:

```
>>> from pyexcel_io import save_data
>>> from pyexcel_io.constants import DB_SQL, DEFAULT_SHEET_NAME
>>> from pyexcel_io.database.sql import SQLTableImporter, SQLTableImportAdapter
>>> mysession = Session()
>>> importer = SQLTableImporter(mysession)
>>> adapter = SQLTableImportAdapter(Pyexcel)
>>> adapter.column_names = data[0]
>>> importer.append(adapter)
>>> save_data(importer, {adapter.get_name(): data[1:]}, file_type=DB_SQL)
```

Please note that, the data dict shall have table name as its key. Now let's verify the data:

```
>>> from pyexcel_io.utils import from_query_sets
>>> query_sets=mysession.query(Pyexcel).all()
>>> results = from_query_sets(data[0], query_sets)
>>> import json
>>> json.dumps(list(results))
'[["birth", "id", "name", "weight"], ["2014-11-11", 0, "Adam", 11.25], ["2014-11-12", 1, "Smith", 12.25]]'
```

2.6.2 Read data from a database table

Let's use previous data for reading and see if we could get them via `get_data()` :

```
>>> from pyexcel_io import get_data
>>> from pyexcel_io.database.sql import SQLTableExporter, SQLTableExportAdapter
>>> exporter = SQLTableExporter(mysession)
>>> adapter = SQLTableExportAdapter(Pyexcel)
>>> exporter.append(adapter)
>>> data = get_data(exporter, file_type=DB_SQL)
>>> json.dumps(list(data['pyexcel']))
'[["birth", "id", "name", "weight"], ["2014-11-11", 0, "Adam", 11.25], ["2014-11-12", 1, "Smith", 12.25]]'
```

Read a subset from the table:

```
>>> exporter = SQLTableExporter(mysession)
>>> adapter = SQLTableExportAdapter(Pyexcel, ['birth'])
>>> exporter.append(adapter)
>>> data = get_data(exporter, file_type=DB_SQL)
>>> json.dumps(list(data['pyexcel']))
'[["birth"], ["2014-11-11"], ["2014-11-12"]]'
```

2.6.3 Write data to multiple tables

Before we start, let's clear off previous table:

```
>>> Base.metadata.drop_all(engine)
```

Now suppose we have these more complex tables:

```
>>> from sqlalchemy import ForeignKey, DateTime
>>> from sqlalchemy.orm import relationship, backref
>>> import sys
>>> class Post(Base):
...     __tablename__ = 'post'
...     id = Column(Integer, primary_key=True)
...     title = Column(String(80))
...     body = Column(String(100))
...     pub_date = Column(DateTime)
...
...     category_id = Column(Integer, ForeignKey('category.id'))
...     category = relationship('Category',
...                             backref=backref('posts', lazy='dynamic'))
...
...     def __init__(self, title, body, category, pub_date=None):
...         self.title = title
...         self.body = body
...         if pub_date is None:
...             pub_date = datetime.utcnow()
...         self.pub_date = pub_date
...         self.category = category
...
...     def __repr__(self):
...         return '<Post %r>' % self.title
...
>>> class Category(Base):
...     __tablename__ = 'category'
...     id = Column(Integer, primary_key=True)
...     name = Column(String(50))
...
...     def __init__(self, name):
...         self.name = name
...
...     def __repr__(self):
...         return '<Category %r>' % self.name
...     def __str__(self):
...         return self.__repr__()
```

Let's clear the database and create previous table in the database:

```
>>> Base.metadata.create_all(engine)
```

Suppose we have these data:

```
>>> data = {
...     "Category": [
...         ["id", "name"],
...         [1, "News"],
...         [2, "Sports"]
...     ],
...     "Post": [
...         ["id", "title", "body", "pub_date", "category"],
```

```

...         [1, "Title A", "formal", datetime.datetime(2015,1,20,23,28,29), "News"],
...         [2, "Title B", "informal", datetime.datetime(2015,1,20,23,28,30), "Sports"]
...     ]
... }

```

Both table has gotten initialization functions:

```

>>> def category_init_func(row):
...     c = Category(row['name'])
...     c.id = row['id']
...     return c

```

and particularly **Post** has a foreign key to **Category**, so we need to query **Category** out and assign it to **Post** instance

```

>>> def post_init_func(row):
...     c = mysession.query(Category).filter_by(name=row['category']).first()
...     p = Post(row['title'], row['body'], c, row['pub_date'])
...     return p

```

Here's the code to update both:

```

>>> tables = {
...     "Category": [Category, data['Category'][0], None, category_init_func],
...     "Post": [Post, data['Post'][0], None, post_init_func]
... }
>>> from pyexcel_io_compact import OrderedDict
>>> importer = SQLTableImporter(mysession)
>>> adapter1 = SQLTableImportAdapter(Category)
>>> adapter1.column_names = data['Category'][0]
>>> adapter1.row_initializer = category_init_func
>>> importer.append(adapter1)
>>> adapter2 = SQLTableImportAdapter(Post)
>>> adapter2.column_names = data['Post'][0]
>>> adapter2.row_initializer = post_init_func
>>> importer.append(adapter2)
>>> to_store = OrderedDict()
>>> to_store.update({adapter1.get_name(): data['Category'][1:]})
>>> to_store.update({adapter2.get_name(): data['Post'][1:]})
>>> save_data(importer, to_store, file_type=DB_SQL)

```

Let's verify what do we have in the database:

```

>>> query_sets = mysession.query(Category).all()
>>> results = from_query_sets(data['Category'][0], query_sets)
>>> import json
>>> json.dumps(list(results))
'[[{"id", "name"}, [1, "News"], [2, "Sports"]]'
>>> query_sets = mysession.query(Post).all()
>>> results = from_query_sets(["id", "title", "body", "pub_date"], query_sets)
>>> json.dumps(list(results))
'[[{"id", "title", "body", "pub_date"}, [1, "Title A", "formal", "2015-01-20T23:28:29"], [2, "Title B

```

Skipping existing record

When you import data into a database that has data already, you can skip existing record if `pyexcel_io.PyexcelSQLSkipRowException` is raised. Example can be found here in [test code](#).

Update existing record

When you import data into a database that has data already, you can update an existing record if you can query it from the database and set the data yourself and most importantly return it. You can find an example in [test skipping row](#)

2.6.4 Read data from multiple tables

Let's use previous data for reading and see if we could get them via `get_data()` :

```
>>> exporter = SQLTableExporter(mysession)
>>> adapter = SQLTableExportAdapter(Category)
>>> exporter.append(adapter)
>>> adapter = SQLTableExportAdapter(Post)
>>> exporter.append(adapter)
>>> data = get_data(exporter, file_type=DB_SQL)
>>> json.dumps(data)
'{"category": [{"id", "name"}, [1, "News"], [2, "Sports"]], "post": [{"body", "category_id", "id", "p
```

What if we read a subset per each table

```
>>> exporter = SQLTableExporter(mysession)
>>> adapter = SQLTableExportAdapter(Category, ['name'])
>>> exporter.append(adapter)
>>> adapter = SQLTableExportAdapter(Post, ['title'])
>>> exporter.append(adapter)
>>> data = get_data(exporter, file_type=DB_SQL)
>>> json.dumps(data)
'{"category": [{"name"}, ["News"], ["Sports"]], "post": [{"title"}, ["Title A"], ["Title B"]}]'
```

2.7 Working with django database

This section shows the way to write and read from django database. Because it is “heavy” to include a django site here to show you. A mocked django model is used here to demonstrate it:

```
>>> class FakeDjangoModel:
...     def __init__(self):
...         self.objects = Objects()
...         self._meta = Meta()
...
...     def __call__(self, **keywords):
...         return keywords
```

Note: You can visit [django-excel documentation](#) if you would prefer a real django model to be used in tutorial.

2.7.1 Write data to a django model

Let's suppose we have a django model:

```
>>> from pyexcel_io import save_data
>>> from pyexcel_io.constants import DB_DJANGO, DEFAULT_SHEET_NAME
>>> from pyexcel_io.database.django import DjangoModelImporter, DjangoModelExporter
```

```
>>> from pyexcel_io.database.django import DjangoModelImportAdapter, DjangoModelExportAdapter
>>> model = FakeDjangoModel()
```

Suppose you have these data:

```
>>> data = [
...     ["X", "Y", "Z"],
...     [1, 2, 3],
...     [4, 5, 6]
... ]
>>> importer = DjangoModelImporter()
>>> adapter = DjangoModelImportAdapter(model)
>>> adapter.set_column_names(data[0])
>>> importer.append(adapter)
>>> save_data(importer, {adapter.get_name(): data[1:]}, file_type=DB_DJANGO)
>>> import pprint
>>> pprint.pprint(model.objects.objs)
[{'X': 1, 'Y': 2, 'Z': 3}, {'X': 4, 'Y': 5, 'Z': 6}]
```

2.7.2 Read data from a django model

Continue from previous example, you can read this back:

```
>>> from pyexcel_io import get_data
>>> exporter = DjangoModelExporter()
>>> adapter = DjangoModelExportAdapter(model)
>>> exporter.append(adapter)
>>> data = get_data(exporter, file_type=DB_DJANGO)
>>> data
OrderedDict([('Sheet0', [['X', 'Y', 'Z'], [1, 2, 3], [4, 5, 6]])])
```

Read a sub set of the columns:

```
>>> exporter = DjangoModelExporter()
>>> adapter = DjangoModelExportAdapter(model, ['X'])
>>> exporter.append(adapter)
>>> data = get_data(exporter, file_type=DB_DJANGO)
>>> data
OrderedDict([('Sheet0', [['X'], [1], [4]])])
```

2.7.3 Write data into multiple models

Suppose you have the following data to be stored in the database:

```
>>> data = {
...     "Sheet1": [['X', 'Y', 'Z'], [1, 4, 7], [2, 5, 8], [3, 6, 9]],
...     "Sheet2": [['A', 'B', 'C'], [1, 4, 7], [2, 5, 8], [3, 6, 9]]
... }
```

And want to save them to two django models:

```
>>> model1 = FakeDjangoModel()
>>> model2 = FakeDjangoModel()
```

In order to store a dictionary data structure, you need to do some transformation:

```
>>> importer = DjangoModelImporter()
>>> adapter1 = DjangoModelImportAdapter(model1)
>>> adapter1.set_column_names(data['Sheet1'][0])
>>> adapter2 = DjangoModelImportAdapter(model2)
>>> adapter2.set_column_names(data['Sheet2'][0])
>>> importer.append(adapter1)
>>> importer.append(adapter2)
>>> to_store = {
...     adapter1.get_name(): data['Sheet1'][1:],
...     adapter2.get_name(): data['Sheet2'][1:]
... }
>>> save_data(importer, to_store, file_type=DB_DJANGO)
>>> pprint.pprint(model1.objects.objs)
[{'X': 1, 'Y': 4, 'Z': 7}, {'X': 2, 'Y': 5, 'Z': 8}, {'X': 3, 'Y': 6, 'Z': 9}]
>>> pprint.pprint(model2.objects.objs)
[{'A': 1, 'B': 4, 'C': 7}, {'A': 2, 'B': 5, 'C': 8}, {'A': 3, 'B': 6, 'C': 9}]
```

2.7.4 Read content from multiple tables

Here's what you need to do:

```
>>> exporter = DjangoModelExporter()
>>> adapter1 = DjangoModelExportAdapter(model1)
>>> adapter2 = DjangoModelExportAdapter(model2)
>>> exporter.append(adapter1)
>>> exporter.append(adapter2)
>>> data = get_data(exporter, file_type=DB_DJANGO)
>>> data
OrderedDict([('Sheet1', [['X', 'Y', 'Z'], [1, 4, 7], [2, 5, 8], [3, 6, 9]]), ('Sheet2', [['A', 'B',
```

What if we need only a subset of each model

```
>>> exporter = DjangoModelExporter()
>>> adapter1 = DjangoModelExportAdapter(model1, ['X'])
>>> adapter2 = DjangoModelExportAdapter(model2, ['A'])
>>> exporter.append(adapter1)
>>> exporter.append(adapter2)
>>> data = get_data(exporter, file_type=DB_DJANGO)
>>> data
OrderedDict([('Sheet1', [['X'], [1], [2], [3]]), ('Sheet2', [['A'], [1], [2], [3]])])
```

2.8 Working with xls,xlsx, and ods formats

Note: No longer, you will need to do explicit imports for pyexcel-io extensions. Instead, you install them and manage them via pip.

2.8.1 Work with physical file

Here's what is needed:

```
>>> from pyexcel_io import save_data
>>> data = [[1,2,3]]
>>> save_data("test.xls", data)
```

And you can also get the data back:

```
>>> from pyexcel_io import get_data
>>> data = get_data("test.xls")
>>> data['pyexcel_sheet1']
[[1, 2, 3]]
```

2.8.2 Work with memory file

Here is the sample code to work with memory file:

```
>>> from pyexcel_io.book import RWManager
>>> io = RWManager.get_io("xls")
>>> data = [[1,2,3]]
>>> save_data(io, data, "xls")
```

The difference is that you have mention file type if you use `pyexcel_io.save_data()`

And you can also get the data back:

```
>>> data = get_data(io, "xls")
>>> data['pyexcel_sheet1']
[[1, 2, 3]]
```

The same applies to `pyexcel_io.get_data()`.

2.8.3 Other formats

As illustrated above, you can start to play with pyexcel-xlsx, pyexcel-ods and pyexcel-ods3 plugins.

<code>get_data(afile[, file_type, streaming])</code>	Get data from an excel file source
<code>save_data(afile, data[, file_type])</code>	Save data to an excel file source

3.1 pyexcel_io.get_data

`pyexcel_io.get_data` (*afile*, *file_type=None*, *streaming=False*, ***keywords*)
Get data from an excel file source

Parameters

- **filename** – actual file name, a file stream or actual content
- **sheet_name** – the name of the sheet to be loaded
- **sheet_index** – the index of the sheet to be loaded
- **file_type** – used only when filename is not a physical file name
- **keywords** – any other parameters

Returns an array if it is a single sheet, an ordered dictionary otherwise

3.2 pyexcel_io.save_data

`pyexcel_io.save_data` (*afile*, *data*, *file_type=None*, ***keywords*)
Save data to an excel file source

Your data can be an array or an ordered dictionary

Parameters

- **filename** – actual file name, a file stream or actual content
- **data** – the data to be saved
- **file_type** – used only when filename is not a physical file name
- **keywords** – any other parameters that python csv module's `'fmtparams'`
<<https://docs.python.org/release/3.1.5/library/csv.html#dialects-and-formatting-parameters>>'_'

Indices and tables

- `genindex`
- `modindex`
- `search`

G

`get_data()` (in module `pyexcel_io`), 21

S

`save_data()` (in module `pyexcel_io`), 21