

---

# **python-gitlab Documentation**

*Release 1.5.1*

**Gauvain Pocentek, Mika Mäenpää**

**Jun 23, 2018**



---

# Contents

---

<b>1</b>	<b>Installation</b>	<b>3</b>
<b>2</b>	<b>gitlab CLI usage</b>	<b>5</b>
2.1	Configuration . . . . .	5
2.2	CLI . . . . .	6
2.3	Examples . . . . .	7
<b>3</b>	<b>Getting started with the API</b>	<b>9</b>
3.1	gitlab.Gitlab class . . . . .	9
3.2	Managers . . . . .	10
3.3	Gitlab Objects . . . . .	11
3.4	Base types . . . . .	11
3.5	Lazy objects . . . . .	11
3.6	Pagination . . . . .	11
3.7	Sudo . . . . .	12
3.8	Advanced HTTP configuration . . . . .	12
<b>4</b>	<b>Switching to GitLab API v4</b>	<b>15</b>
4.1	Using the v4 API . . . . .	15
4.2	Changes between v3 and v4 API . . . . .	15
<b>5</b>	<b>API examples</b>	<b>17</b>
5.1	Access requests . . . . .	17
5.2	Award Emojis . . . . .	18
5.3	Badges . . . . .	19
5.4	Branches . . . . .	20
5.5	Protected branches . . . . .	21
5.6	Broadcast messages . . . . .	22
5.7	Pipelines and Jobs . . . . .	22
5.8	Commits . . . . .	28
5.9	Deploy keys . . . . .	30
5.10	Deployments . . . . .	32
5.11	Discussions . . . . .	32
5.12	Environments . . . . .	34
5.13	Events . . . . .	35
5.14	Epics . . . . .	36
5.15	Features flags . . . . .	37

5.16	Geo nodes	38
5.17	Groups	38
5.18	Issues	42
5.19	Issue boards	45
5.20	Labels	47
5.21	Notification settings	48
5.22	Merge requests	49
5.23	Merge request approvals settings	52
5.24	Milestones	52
5.25	Namespaces	54
5.26	Notes	54
5.27	Pages domains	55
5.28	Projects	56
5.29	Runners	68
5.30	Search API	70
5.31	Settings	71
5.32	Snippets	71
5.33	System hooks	72
5.34	Templates	73
5.35	Todos	75
5.36	Users and current user	76
5.37	Sidekiq metrics	81
5.38	Wiki pages	82
<b>6</b>	<b>gitlab package</b>	<b>83</b>
6.1	Subpackages	83
6.2	Submodules	151
6.3	gitlab.base module	151
6.4	gitlab.cli module	153
6.5	gitlab.config module	153
6.6	gitlab.const module	153
6.7	gitlab.exceptions module	153
6.8	gitlab.mixins module	157
6.9	gitlab.utils module	163
6.10	Module contents	163
<b>7</b>	<b>Release notes</b>	<b>169</b>
7.1	Changes from 1.4 to 1.5	169
7.2	Changes from 1.3 to 1.4	169
7.3	Changes from 1.2 to 1.3	170
7.4	Changes from 1.1 to 1.2	170
7.5	Changes from 1.0.2 to 1.1	170
7.6	Changes from 0.21 to 1.0.0	171
7.7	Changes from 0.20 to 0.21	171
7.8	Changes from 0.19 to 0.20	171
<b>8</b>	<b>ChangeLog</b>	<b>173</b>
8.1	Version 1.5.1 - 2018-06-23	173
8.2	Version 1.5.0 - 2018-06-22	173
8.3	Version 1.4.0 - 2018-05-19	175
8.4	Version 1.3.0 - 2018-02-18	175
8.5	Version 1.2.0 - 2018-01-01	176
8.6	Version 1.1.0 - 2017-11-03	177
8.7	Version 1.0.2 - 2017-09-29	178

8.8	Version 1.0.1 - 2017-09-21	178
8.9	Version 1.0.0 - 2017-09-08	178
8.10	Version 0.21.2 - 2017-06-11	179
8.11	Version 0.21.1 - 2017-05-25	179
8.12	Version 0.21 - 2017-05-24	179
8.13	Version 0.20 - 2017-03-25	180
8.14	Version 0.19 - 2017-02-21	180
8.15	Version 0.18 - 2016-12-27	180
8.16	Version 0.17 - 2016-12-02	181
8.17	Version 0.16 - 2016-10-16	182
8.18	Version 0.15.1 - 2016-10-16	182
8.19	Version 0.15 - 2016-08-28	182
8.20	Version 0.14 - 2016-08-07	183
8.21	Version 0.13 - 2016-05-16	184
8.22	Version 0.12.2 - 2016-03-19	185
8.23	Version 0.12.1 - 2016-02-03	186
8.24	Version 0.12 - 2016-02-03	186
8.25	Version 0.11.1 - 2016-01-17	186
8.26	Version 0.11 - 2016-01-09	187
8.27	Version 0.10 - 2015-12-29	187
8.28	Version 0.9.2 - 2015-07-11	187
8.29	Version 0.9.1 - 2015-05-15	187
8.30	Version 0.9 - 2015-05-15	188
8.31	Version 0.8 - 2014-10-26	188
8.32	Version 0.7 - 2014-08-21	188
8.33	Version 0.6 - 2014-01-16	189
8.34	Version 0.5 - 2013-12-26	189
8.35	Version 0.4 - 2013-09-26	189
8.36	Version 0.3 - 2013-08-27	189
8.37	Version 0.2 - 2013-08-08	190
8.38	Version 0.1 - 2013-07-08	190
<b>9</b>	<b>Indices and tables</b>	<b>191</b>
	<b>Python Module Index</b>	<b>193</b>



Contents:





# CHAPTER 1

---

## Installation

---

python-gitlab is compatible with Python 2.7 and 3.4+.

Use **pip** to install the latest stable version of python-gitlab:

```
$ sudo pip install --upgrade python-gitlab
```

The current development version is available on [github](https://github.com). Use **git** and **python setup.py** to install it:

```
$ git clone https://github.com/python-gitlab/python-gitlab
$ cd python-gitlab
$ sudo python setup.py install
```



`python-gitlab` provides a **gitlab** command-line tool to interact with GitLab servers. It uses a configuration file to define how to connect to the servers.

## 2.1 Configuration

### 2.1.1 Files

`gitlab` looks up 2 configuration files by default:

**`/etc/python-gitlab.cfg`** System-wide configuration file

**`~/.python-gitlab.cfg`** User configuration file

You can use a different configuration file with the `--config-file` option.

### 2.1.2 Content

The configuration file uses the INI format. It contains at least a `[global]` section, and a specific section for each GitLab server. For example:

```
[global]
default = somewhere
ssl_verify = true
timeout = 5

[somewhere]
url = https://some.whe.re
private_token = vTbFeqJYCY3sibBP7BZM
api_version = 3

[elsewhere]
```

(continues on next page)

(continued from previous page)

```
url = http://else.whe.re:8080
private_token = CkqsjqcQSFH5FQKDccu4
timeout = 1
```

The default option of the [global] section defines the GitLab server to use if no server is explicitly specified with the `--gitlab` CLI option.

The [global] section also defines the values for the default connection parameters. You can override the values in each GitLab server section.

Table 1: Global options

Option	Possible values	Description
<code>ssl_verify</code>	<code>True</code> , <code>False</code> , or a <code>str</code>	Verify the SSL certificate. Set to <code>False</code> to disable verification, though this will create warnings. Any other value is interpreted as path to a <code>CA_BUNDLE</code> file or directory with certificates of trusted CAs.
<code>timeout</code>	Integer	Number of seconds to wait for an answer before failing.
<code>api_version</code>	3 or 4	The API version to use to make queries. Requires <code>python-gitlab &gt;= 1.3.0</code> .
<code>per_page</code>	Integer between 1 and 100	The number of items to return in listing queries. GitLab limits the value at 100.

You must define the `url` in each GitLab server section.

Only one of `private_token` or `oauth_token` should be defined. If neither are defined an anonymous request will be sent to the Gitlab server, with very limited permissions.

Table 2: GitLab server options

Option	Description
<code>url</code>	URL for the GitLab server
<code>private_token</code>	Your user token. Login/password is not supported. Refer to <a href="#">the official documentation</a> to learn how to obtain a token.
<code>oauth_token</code>	An OAuth token for authentication. The Gitlab server must be configured to support this authentication method.
<code>api_version</code>	GitLab API version to use (3 or 4). Defaults to 4 since version 1.3.0.
<code>http_username</code>	Username for optional HTTP authentication
<code>http_password</code>	Password for optional HTTP authentication

## 2.2 CLI

### 2.2.1 Objects and actions

The `gitlab` command expects two mandatory arguments. The first one is the type of object that you want to manipulate. The second is the action that you want to perform. For example:

```
$ gitlab project list
```

Use the `--help` option to list the available object types and actions:

```
$ gitlab --help
$ gitlab project --help
```

Some actions require additional parameters. Use the `--help` option to list mandatory and optional arguments for an action:

```
$ gitlab project create --help
```

## 2.2.2 Optional arguments

Use the following optional arguments to change the behavior of `gitlab`. These options must be defined before the mandatory arguments.

**--verbose, -v** Outputs detail about retrieved objects. Available for legacy (default) output only.

**--config-file, -c** Path to a configuration file.

**--gitlab, -g** ID of a GitLab server defined in the configuration file.

**--output, -o** Output format. Defaults to a custom format. Can also be `yaml` or `json`.

**--fields, -f** Comma-separated list of fields to display (`yaml` and `json` output formats only). If not used, all the object fields are displayed.

Example:

```
$ gitlab -o yaml -f id,permissions -g elsewhere -c /tmp/gl.cfg project list
```

## 2.3 Examples

List the projects (paginated):

```
$ gitlab project list
```

List all the projects:

```
$ gitlab project list --all
```

Limit to 5 items per request, display the 1st page only

```
$ gitlab project list --page 1 --per-page 5
```

Get a specific project (id 2):

```
$ gitlab project get --id 2
```

Get a specific user by id:

```
$ gitlab user get --id 3
```

Get a list of snippets for this project:

```
$ gitlab project-issue list --project-id 2
```

Delete a snippet (id 3):

```
$ gitlab project-snippet delete --id 3 --project-id 2
```

Update a snippet:

```
$ gitlab project-snippet update --id 4 --project-id 2 \  
  --code "My New Code"
```

Create a snippet:

```
$ gitlab project-snippet create --project-id 2  
Impossible to create object (Missing attribute(s): title, file-name, code)  
$ # oops, let's add the attributes:  
$ gitlab project-snippet create --project-id 2 --title "the title" \  
  --file-name "the name" --code "the code"
```

Define the status of a commit (as would be done from a CI tool for example):

```
$ gitlab project-commit-status create --project-id 2 \  
  --commit-id a43290c --state success --name ci/jenkins \  
  --target-url http://server/build/123 \  
  --description "Jenkins build succeeded"
```

Use sudo to act as another user (admin only):

```
$ gitlab project create --name user_project1 --sudo username
```

List values are comma-separated:

```
$ gitlab issue list --labels foo,bar
```

### 2.3.1 Reading values from files

You can make `gitlab` read values from files instead of providing them on the command line. This is handy for values containing new lines for instance:

```
$ cat > /tmp/description << EOF  
This is the description of my project.  
  
It is obviously the best project around  
EOF  
$ gitlab project create --name SuperProject --description @/tmp/description
```

---

## Getting started with the API

---

python-gitlab supports both GitLab v3 and v4 APIs. To use the v3 make sure to

**Note:** To use the v3 make sure to install python-gitlab 1.4. Only the v4 API is documented here. See the documentation of earlier version for the v3 API.

---

### 3.1 gitlab.Gitlab class

To connect to a GitLab server, create a `gitlab.Gitlab` object:

```
import gitlab

# private token or personal token authentication
gl = gitlab.Gitlab('http://10.0.0.1', private_token='JVNSEs8EwWRx5yDxM5q')

# oauth token authentication
gl = gitlab.Gitlab('http://10.0.0.1', oauth_token='my_long_token_here')

# username/password authentication (for GitLab << 10.2)
gl = gitlab.Gitlab('http://10.0.0.1', email='jdoe', password='s3cr3t')

# anonymous gitlab instance, read-only for public resources
gl = gitlab.Gitlab('http://10.0.0.1')

# make an API request to create the gl.user object. This is mandatory if you
# use the username/password authentication.
gl.auth()
```

You can also use configuration files to create `gitlab.Gitlab` objects:

```
gl = gitlab.Gitlab.from_config('somewhere', ['/tmp/gl.cfg'])
```

See the *Configuration* section for more information about configuration files.

### 3.1.1 Note on password authentication

The `/session` API endpoint used for username/password authentication has been removed from GitLab in version 10.2, and is not available on gitlab.com anymore. Personal token authentication is the preferred authentication method.

If you need username/password authentication, you can use cookie-based authentication. You can use the web UI form to authenticate, retrieve cookies, and then use a custom `requests.Session` object to connect to the GitLab API. The following code snippet demonstrates how to automate this: <https://gist.github.com/gpocentek/bd4c3fbf8a6ce226ebddc4aad6b46c0a>.

See [issue 380](#) for a detailed discussion.

## 3.2 Managers

The `gitlab.Gitlab` class provides managers to access the GitLab resources. Each manager provides a set of methods to act on the resources. The available methods depend on the resource type.

Examples:

```
# list all the projects
projects = gl.projects.list()
for project in projects:
    print(project)

# get the group with id == 2
group = gl.groups.get(2)
for group in groups:
    print()

# create a new user
user_data = {'email': 'jen@foo.com', 'username': 'jen', 'name': 'Jen'}
user = gl.users.create(user_data)
print(user)
```

You can list the mandatory and optional attributes for object creation and update with the manager's `get_create_attrs()` and `get_update_attrs()` methods. They return 2 tuples, the first one is the list of mandatory attributes, the second one the list of optional attribute:

```
# v4 only
print(gl.projects.get_create_attrs())
(('name',), ('path', 'namespace_id', ...))
```

The attributes of objects are defined upon object creation, and depend on the GitLab API itself. To list the available information associated with an object use the `attributes` attribute:

```
project = gl.projects.get(1)
print(project.attributes)
```

Some objects also provide managers to access related GitLab resources:

```
# list the issues for a project
project = gl.projects.get(1)
issues = project.issues.list()
```



### 3.3 Gitlab Objects

You can update or delete a remote object when it exists locally:

```
# update the attributes of a resource
project = gl.projects.get(1)
project.wall_enabled = False
# don't forget to apply your changes on the server:
project.save()

# delete the resource
project.delete()
```

Some classes provide additional methods, allowing more actions on the GitLab resources. For example:

```
# star a git repository
project = gl.projects.get(1)
project.star()
```

### 3.4 Base types

The `gitlab` package provides some base types.

- `gitlab.Gitlab` is the primary class, handling the HTTP requests. It holds the GitLab URL and authentication information.
- `gitlab.base.RESTObject` is the base class for all the GitLab v4 objects. These objects provide an abstraction for GitLab resources (projects, groups, and so on).
- `gitlab.base.RESTManager` is the base class for v4 objects managers, providing the API to manipulate the resources and their attributes.

### 3.5 Lazy objects

To avoid useless API calls to the server you can create lazy objects. These objects are created locally using a known ID, and give access to other managers and methods.

The following example will only make one API call to the GitLab server to star a project (the previous example used 2 API calls):

```
# star a git repository
project = gl.projects.get(1, lazy=True) # no API call
project.star() # API call
```

### 3.6 Pagination

You can use pagination to iterate over long lists. All the Gitlab objects listing methods support the `page` and `per_page` parameters:

```
ten_first_groups = gl.groups.list(page=1, per_page=10)
```

**Warning:** The first page is page 1, not page 0.

By default GitLab does not return the complete list of items. Use the `all` parameter to get all the items when using listing methods:

```
all_groups = gl.groups.list(all=True)
all_owned_projects = gl.projects.owned(all=True)
```

You can define the `per_page` value globally to avoid passing it to every `list()` method call:

```
gl = gitlab.Gitlab(url, token, per_page=50)
```

`list()` methods can also return a generator object which will handle the next calls to the API when required. This is the recommended way to iterate through a large number of items:

```
items = gl.groups.list(as_list=False)
for item in items:
    print(item.attributes)
```

The generator exposes extra listing information as received by the server:

- `current_page`: current page number (first page is 1)
- `prev_page`: if `None` the current page is the first one
- `next_page`: if `None` the current page is the last one
- `per_page`: number of items per page
- `total_pages`: total number of pages available
- `total`: total number of items in the list

## 3.7 Sudo

If you have the administrator status, you can use `sudo` to act as another user. For example:

```
p = gl.projects.create({'name': 'awesome_project'}, sudo='user1')
```

## 3.8 Advanced HTTP configuration

`python-gitlab` relies on `requests.Session` objects to perform all the HTTP requests to the Gitlab servers.

You can provide your own `Session` object with custom configuration when you create a `Gitlab` object.

### 3.8.1 Context manager

You can use `Gitlab` objects as context managers. This makes sure that the `requests.Session` object associated with a `Gitlab` instance is always properly closed when you exit a `with` block:

```
with gitlab.Gitlab(host, token) as gl:
    gl.projects.list()
```

**Warning:** The context manager will also close the custom `Session` object you might have used to build a Gitlab instance.

### 3.8.2 Proxy configuration

The following sample illustrates how to define a proxy configuration when using python-gitlab:

```
import gitlab
import requests

session = requests.Session()
session.proxies = {
    'https': os.environ.get('https_proxy'),
    'http': os.environ.get('http_proxy'),
}
gl = gitlab.gitlab(url, token, api_version=4, session=session)
```

Reference: <http://docs.python-requests.org/en/master/user/advanced/#proxies>

### 3.8.3 Client side certificate

The following sample illustrates how to use a client-side certificate:

```
import gitlab
import requests

session = requests.Session()
session.cert = ('/path/to/client.cert', '/path/to/client.key')
gl = gitlab.gitlab(url, token, api_version=4, session=session)
```

Reference: <http://docs.python-requests.org/en/master/user/advanced/#client-side-certificates>

### 3.8.4 Rate limits

python-gitlab obeys the rate limit of the GitLab server by default. On receiving a 429 response (Too Many Requests), python-gitlab sleeps for the amount of time in the `Retry-After` header that GitLab sends back.

If you don't want to wait, you can disable the rate-limiting feature, by supplying the `obey_rate_limit` argument.

```
import gitlab
import requests

gl = gitlab.gitlab(url, token, api_version=4)
gl.projects.list(all=True, obey_rate_limit=False)
```

**Warning:** You will get an Exception, if you then go over the rate limit of your GitLab instance.



---

## Switching to GitLab API v4

---

GitLab provides a new API version (v4) since its 9.0 release. `python-gitlab` provides support for this new version, but the python API has been modified to solve some problems with the existing one.

GitLab will stop supporting the v3 API soon, and you should consider switching to v4 if you use a recent version of GitLab ( $\geq 9.0$ ), or if you use <http://gitlab.com>.

### 4.1 Using the v4 API

`python-gitlab` uses the v4 API by default since the 1.3.0 release. To use the old v3 API, explicitly define `api_version` in the `Gitlab` constructor:

```
gl = gitlab.Gitlab(..., api_version=3)
```

If you use the configuration file, also explicitly define the version:

```
[my_gitlab]
...
api_version = 3
```

### 4.2 Changes between v3 and v4 API

For a list of GitLab (upstream) API changes, see [https://docs.gitlab.com/ce/api/v3\\_to\\_v4.html](https://docs.gitlab.com/ce/api/v3_to_v4.html).

The `python-gitlab` API reflects these changes. But also consider the following important changes in the python API:

- managers and objects don't inherit from `GitlabObject` and `BaseManager` anymore. They inherit from `RESTManager` and `RESTObject`.
- You should only use the managers to perform CRUD operations.

The following v3 code:

```
gl = gitlab.Gitlab(...)
p = Project(gl, project_id)
```

Should be replaced with:

```
gl = gitlab.Gitlab(...)
p = gl.projects.get(project_id)
```

- Listing methods (`manager.list()` for instance) can now return generators (*RESTObjectList*). They handle the calls to the API when needed to fetch new items.

By default you will still get lists. To get generators use `as_list=False`:

```
all_projects_g = gl.projects.list(as_list=False)
```

- The “nested” managers (for instance `gl.project_issues` or `gl.group_members`) are not available anymore. Their goal was to provide a direct way to manage nested objects, and to limit the number of needed API calls.

To limit the number of API calls, you can now use `get()` methods with the `lazy=True` parameter. This creates shallow objects that provide usual managers.

The following v3 code:

```
issues = gl.project_issues.list(project_id=project_id)
```

Should be replaced with:

```
issues = gl.projects.get(project_id, lazy=True).issues.list()
```

This will make only one API call, instead of two if `lazy` is not used.

- The following *Gitlab* methods should not be used anymore for v4:
  - `list()`
  - `get()`
  - `create()`
  - `update()`
  - `delete()`
- If you need to perform HTTP requests to the GitLab server (which you shouldn't), you can use the following *Gitlab* methods:
  - `http_request`
  - `http_get`
  - `http_list`
  - `http_post`
  - `http_put`
  - `http_delete`

### 5.1 Access requests

Users can request access to groups and projects.

When access is granted the user should be given a numerical access level. The following constants are provided to represent the access levels:

- `gitlab.GUEST_ACCESS: 10`
- `gitlab.REPORTER_ACCESS: 20`
- `gitlab.DEVELOPER_ACCESS: 30`
- `gitlab.MASTER_ACCESS: 40`
- `gitlab.OWNER_ACCESS: 50`

#### 5.1.1 References

- v4 API:
  - `gitlab.v4.objects.ProjectAccessRequest`
  - `gitlab.v4.objects.ProjectAccessRequestManager`
  - `gitlab.v4.objects.Project.accessrequests`
  - `gitlab.v4.objects.GroupAccessRequest`
  - `gitlab.v4.objects.GroupAccessRequestManager`
  - `gitlab.v4.objects.Group.accessrequests`
- GitLab API: [https://docs.gitlab.com/ce/api/access\\_requests.html](https://docs.gitlab.com/ce/api/access_requests.html)

## 5.1.2 Examples

List access requests from projects and groups:

```
p_ars = project.accessrequests.list()
g_ars = group.accessrequests.list()
```

Create an access request:

```
p_ar = project.accessrequests.create({})
g_ar = group.accessrequests.create({})
```

Approve an access request:

```
ar.approve() # defaults to DEVELOPER level
ar.approve(access_level=gitlab.MASTER_ACCESS) # explicitly set access level
```

Deny (delete) an access request:

```
project.accessrequests.delete(user_id)
group.accessrequests.delete(user_id)
# or
ar.delete()
```

## 5.2 Award Emojis

### 5.2.1 Reference

- v4 API:
  - `gitlab.v4.objects.ProjectIssueAwardEmoji`
  - `gitlab.v4.objects.ProjectIssueNoteAwardEmoji`
  - `gitlab.v4.objects.ProjectMergeRequestAwardEmoji`
  - `gitlab.v4.objects.ProjectMergeRequestNoteAwardEmoji`
  - `gitlab.v4.objects.ProjectSnippetAwardEmoji`
  - `gitlab.v4.objects.ProjectSnippetNoteAwardEmoji`
  - `gitlab.v4.objects.ProjectIssueAwardEmojiManager`
  - `gitlab.v4.objects.ProjectIssueNoteAwardEmojiManager`
  - `gitlab.v4.objects.ProjectMergeRequestAwardEmojiManager`
  - `gitlab.v4.objects.ProjectMergeRequestNoteAwardEmojiManager`
  - `gitlab.v4.objects.ProjectSnippetAwardEmojiManager`
  - `gitlab.v4.objects.ProjectSnippetNoteAwardEmojiManager`
- GitLab API: [https://docs.gitlab.com/ce/api/award\\_emoji.html](https://docs.gitlab.com/ce/api/award_emoji.html)



## 5.2.2 Examples

List emojis for a resource:

```
emojis = obj.awardemojis.list()
```

Get a single emoji:

```
emoji = obj.awardemojis.get(emoji_id)
```

Add (create) an emoji:

```
emoji = obj.awardemojis.create({'name': 'tractor'})
```

Delete an emoji:

```
emoji.delete
# or
obj.awardemojis.delete(emoji_id)
```

## 5.3 Badges

Badges can be associated with groups and projects.

### 5.3.1 Reference

- v4 API:
  - *gitlab.v4.objects.GroupBadge*
  - *gitlab.v4.objects.GroupBadgeManager*
  - *gitlab.v4.objects.Group.badges*
  - *gitlab.v4.objects.ProjectBadge*
  - *gitlab.v4.objects.ProjectBadgeManager*
  - *gitlab.v4.objects.Project.badges*
- GitLab API:
  - [https://docs.gitlab.com/ce/api/group\\_badges.html](https://docs.gitlab.com/ce/api/group_badges.html)
  - [https://docs.gitlab.com/ce/api/project\\_badges.html](https://docs.gitlab.com/ce/api/project_badges.html)

### 5.3.2 Examples

List badges:

```
badges = group_or_project.badges.list()
```

Get ad badge:

```
badge = group_or_project.badges.get(badge_id)
```

Create a badge:

```
badge = group_or_project.badges.create({'link_url': link, 'image_url': image_link})
```

Update a badge:

```
badge.image_link = new_link
badge.save()
```

Delete a badge:

```
badge.delete()
```

Render a badge (preview the generate URLs):

```
output = group_or_project.badges.render(link, image_link)
print(output['rendered_link_url'])
print(output['rendered_image_url'])
```

## 5.4 Branches

### 5.4.1 References

- v4 API:
  - `gitlab.v4.objects.ProjectBranch`
  - `gitlab.v4.objects.ProjectBranchManager`
  - `gitlab.v4.objects.Project.branches`
- GitLab API: <https://docs.gitlab.com/ce/api/branches.html>

### 5.4.2 Examples

Get the list of branches for a repository:

```
branches = project.branches.list()
```

Get a single repository branch:

```
branch = project.branches.get('master')
```

Create a repository branch:

```
branch = project.branches.create({'branch': 'feature1',
                                  'ref': 'master'})
```

Delete a repository branch:

```
project.branches.delete('feature1')
# or
branch.delete()
```

Protect/unprotect a repository branch:

```
branch.protect()
branch.unprotect()
```

**Note:** By default, developers are not authorized to push or merge into protected branches. This can be changed by passing `developers_can_push` or `developers_can_merge`:

```
branch.protect(developers_can_push=True, developers_can_merge=True)
```

Delete the merged branches for a project:

```
project.delete_merged_branches()
```

## 5.5 Protected branches

You can define a list of protected branch names on a repository. Names can use wildcards (\*).

### 5.5.1 References

- v4 API:
  - `gitlab.v4.objects.ProjectProtectedBranch`
  - `gitlab.v4.objects.ProjectProtectedBranchManager`
  - `gitlab.v4.objects.Project.protectedbranches`
- GitLab API: [https://docs.gitlab.com/ce/api/protected\\_branches.html#protected-branches-api](https://docs.gitlab.com/ce/api/protected_branches.html#protected-branches-api)

### 5.5.2 Examples

Get the list of protected branches for a project:

```
p_branches = project.protectedbranches.list()
```

Get a single protected branch:

```
p_branch = project.protectedbranches.get('master')
```

Create a protected branch:

```
p_branch = project.protectedbranches.create({
    'name': '*-stable',
    'merge_access_level': gitlab.DEVELOPER_ACCESS,
    'push_access_level': gitlab.MASTER_ACCESS
})
```

Delete a protected branch:

```
project.protectedbranches.delete('*-stable')
# or
p_branch.delete()
```

## 5.6 Broadcast messages

You can use broadcast messages to display information on all pages of the gitlab web UI. You must have administration permissions to manipulate broadcast messages.

### 5.6.1 References

- v4 API:
  - `gitlab.v4.objects.BroadcastMessage`
  - `gitlab.v4.objects.BroadcastMessageManager`
  - `gitlab.Gitlab.broadcastmessages`
- GitLab API: [https://docs.gitlab.com/ce/api/broadcast\\_messages.html](https://docs.gitlab.com/ce/api/broadcast_messages.html)

### 5.6.2 Examples

List the messages:

```
msgs = gl.broadcastmessages.list()
```

Get a single message:

```
msg = gl.broadcastmessages.get(msg_id)
```

Create a message:

```
msg = gl.broadcastmessages.create({'message': 'Important information'})
```

The date format for the `starts_at` and `ends_at` parameters is `YYYY-MM-ddThh:mm:ssZ`.

Update a message:

```
msg.font = '#444444'  
msg.color = '#999999'  
msg.save()
```

Delete a message:

```
gl.broadcastmessages.delete(msg_id)  
# or  
msg.delete()
```

## 5.7 Pipelines and Jobs

### 5.7.1 Project pipelines

A pipeline is a group of jobs executed by GitLab CI.

## Reference

- v4 API:
  - `gitlab.v4.objects.ProjectPipeline`
  - `gitlab.v4.objects.ProjectPipelineManager`
  - `gitlab.v4.objects.Project.pipelines`
- GitLab API: <https://docs.gitlab.com/ce/api/pipelines.html>

## Examples

List pipelines for a project:

```
pipelines = project.pipelines.list()
```

Get a pipeline for a project:

```
pipeline = project.pipelines.get(pipeline_id)
```

Create a pipeline for a particular reference:

```
pipeline = project.pipelines.create({'ref': 'master'})
```

Retry the failed builds for a pipeline:

```
pipeline.retry()
```

Cancel builds in a pipeline:

```
pipeline.cancel()
```

## 5.7.2 Triggers

Triggers provide a way to interact with the GitLab CI. Using a trigger a user or an application can run a new build/job for a specific commit.

## Reference

- v4 API:
  - `gitlab.v4.objects.ProjectTrigger`
  - `gitlab.v4.objects.ProjectTriggerManager`
  - `gitlab.v4.objects.Project.triggers`
- GitLab API: [https://docs.gitlab.com/ce/api/pipeline\\_triggers.html](https://docs.gitlab.com/ce/api/pipeline_triggers.html)

## Examples

List triggers:

```
triggers = project.triggers.list()
```

Get a trigger:

```
trigger = project.triggers.get(trigger_token)
```

Create a trigger:

```
trigger = project.triggers.create({'description': 'mytrigger'})
```

Remove a trigger:

```
project.triggers.delete(trigger_token)
# or
trigger.delete()
```

Full example with wait for finish:

```
def get_or_create_trigger(project):
    trigger_decription = 'my_trigger_id'
    for t in project.triggers.list():
        if t.description == trigger_decription:
            return t
    return project.triggers.create({'description': trigger_decription})

trigger = get_or_create_trigger(project)
pipeline = project.trigger_pipeline('master', trigger.token, variables={"DEPLOY_ZONE": "us-west1"})
while pipeline.finished_at is None:
    pipeline.refresh()
    os.sleep(1)
```

## 5.7.3 Pipeline schedule

You can schedule pipeline runs using a cron-like syntax. Variables can be associated with the scheduled pipelines.

### Reference

- v4 API
  - `gitlab.v4.objects.ProjectPipelineSchedule`
  - `gitlab.v4.objects.ProjectPipelineScheduleManager`
  - `gitlab.v4.objects.Project.pipelineschedules`
  - `gitlab.v4.objects.ProjectPipelineScheduleVariable`
  - `gitlab.v4.objects.ProjectPipelineScheduleVariableManager`
  - `gitlab.v4.objects.Project.pipelineschedules`
- GitLab API: [https://docs.gitlab.com/ce/api/pipeline\\_schedules.html](https://docs.gitlab.com/ce/api/pipeline_schedules.html)

## Examples

List pipeline schedules:

```
scheds = project.pipelineschedules.list()
```

Get a single schedule:

```
sched = projects.pipelineschedules.get(schedule_id)
```

Create a new schedule:

```
sched = project.pipelineschedules.create({
    'ref': 'master',
    'description': 'Daily test',
    'cron': '0 1 * * *'})
```

Update a schedule:

```
sched.cron = '1 2 * * *'
sched.save()
```

Delete a schedule:

```
sched.delete()
```

Create a schedule variable:

```
var = sched.variables.create({'key': 'foo', 'value': 'bar'})
```

Edit a schedule variable:

```
var.value = 'new_value'
var.save()
```

Delete a schedule variable:

```
var.delete()
```

## 5.7.4 Projects and groups variables

You can associate variables to projects and groups to modify the build/job scripts behavior.

### Reference

- v4 API
  - `gitlab.v4.objects.ProjectVariable`
  - `gitlab.v4.objects.ProjectVariableManager`
  - `gitlab.v4.objects.Project.variables`
  - `gitlab.v4.objects.GroupVariable`
  - `gitlab.v4.objects.GroupVariableManager`
  - `gitlab.v4.objects.Group.variables`

- GitLab API
  - [https://docs.gitlab.com/ce/api/project\\_level\\_variables.html](https://docs.gitlab.com/ce/api/project_level_variables.html)
  - [https://docs.gitlab.com/ce/api/group\\_level\\_variables.html](https://docs.gitlab.com/ce/api/group_level_variables.html)

## Examples

List variables:

```
p_variables = project.variables.list()
g_variables = group.variables.list()
```

Get a variable:

```
p_var = project.variables.get('key_name')
g_var = group.variables.get('key_name')
```

Create a variable:

```
var = project.variables.create({'key': 'key1', 'value': 'value1'})
var = group.variables.create({'key': 'key1', 'value': 'value1'})
```

Update a variable value:

```
var.value = 'new_value'
var.save()
```

Remove a variable:

```
project.variables.delete('key_name')
group.variables.delete('key_name')
# or
var.delete()
```

## 5.7.5 Jobs

Jobs are associated to projects, pipelines and commits. They provide information on the jobs that have been run, and methods to manipulate them.

### Reference

- v4 API
  - `gitlab.v4.objects.ProjectJob`
  - `gitlab.v4.objects.ProjectJobManager`
  - `gitlab.v4.objects.Project.jobs`
- GitLab API: <https://docs.gitlab.com/ce/api/jobs.html>



## Examples

Jobs are usually automatically triggered, but you can explicitly trigger a new job:

```
project.trigger_build('master', trigger_token,
                     {'extra_var1': 'foo', 'extra_var2': 'bar'})
```

List jobs for the project:

```
jobs = project.jobs.list()
```

Get a single job:

```
project.jobs.get(job_id)
```

List the jobs of a pipeline:

```
project = gl.projects.get(project_id)
pipeline = project.pipelines.get(pipeline_id)
jobs = pipeline.jobs.list()
```

**Note:** Job methods (play, cancel, and so on) are not available on `ProjectPipelineJob` objects. To use these methods create a `ProjectJob` object:

```
pipeline_job = pipeline.jobs.list()[0]
job = project.jobs.get(pipeline_job.id, lazy=True)
job.retry()
```

Get the artifacts of a job:

```
build_or_job.artifacts()
```

**Warning:** Artifacts are entirely stored in memory in this example.

You can download artifacts as a stream. Provide a callable to handle the stream:

```
class Foo(object):
    def __init__(self):
        self._fd = open('artifacts.zip', 'wb')

    def __call__(self, chunk):
        self._fd.write(chunk)

target = Foo()
build_or_job.artifacts(streamed=True, action=target)
del(target) # flushes data on disk
```

You can also directly stream the output into a file, and unzip it afterwards:

```
zipfn = "__artifacts.zip"
with open(zipfn, "wb") as f:
    build_or_job.artifacts(streamed=True, action=f.write)
subprocess.run(["unzip", "-bo", zipfn])
os.unlink(zipfn)
```

Get a single artifact file:

```
build_or_job.artifact('path/to/file')
```

Mark a job artifact as kept when expiration is set:

```
build_or_job.keep_artifacts()
```

Get a job trace:

```
build_or_job.trace()
```

**Warning:** Traces are entirely stored in memory unless you use the streaming feature. See *the artifacts example*.

Cancel/retry a job:

```
build_or_job.cancel()  
build_or_job.retry()
```

Play (trigger) a job:

```
build_or_job.play()
```

Erase a job (artifacts and trace):

```
build_or_job.erase()
```

## 5.8 Commits

### 5.8.1 Commits

#### Reference

- v4 API:
  - `gitlab.v4.objects.ProjectCommit`
  - `gitlab.v4.objects.ProjectCommitManager`
  - `gitlab.v4.objects.Project.commits`

#### Examples

List the commits for a project:

```
commits = project.commits.list()
```

You can use the `ref_name`, `since` and `until` filters to limit the results:

```
commits = project.commits.list(ref_name='my_branch')  
commits = project.commits.list(since='2016-01-01T00:00:00Z')
```

Create a commit:

```
# See https://docs.gitlab.com/ce/api/commits.html#create-a-commit-with-multiple-files-
↪and-actions
# for actions detail
data = {
    'branch_name': 'master', # v3
    'branch': 'master', # v4
    'commit_message': 'blah blah blah',
    'actions': [
        {
            'action': 'create',
            'file_path': 'README.rst',
            'content': open('path/to/file.rst').read(),
        },
        {
            # Binary files need to be base64 encoded
            'action': 'create',
            'file_path': 'logo.png',
            'content': base64.b64encode(open('logo.png').read()),
            'encoding': 'base64',
        }
    ]
}

commit = project.commits.create(data)
```

Get a commit detail:

```
commit = project.commits.get('e3d5a71b')
```

Get the diff for a commit:

```
diff = commit.diff()
```

Cherry-pick a commit into another branch:

```
commit.cherry_pick(branch='target_branch')
```

Get the references the commit has been pushed to (branches and tags):

```
commit.refs() # all references
commit.refs('tag') # only tags
commit.refs('branch') # only branches
```

List the merge requests related to a commit:

```
commit.merge_requests()
```

## 5.8.2 Commit comments

### Reference

- v4 API:
  - `gitlab.v4.objects.ProjectCommitComment`
  - `gitlab.v4.objects.ProjectCommitCommentManager`

- `gitlab.v4.objects.Commit.comments`
- GitLab API: <https://docs.gitlab.com/ce/api/commits.html>

## Examples

Get the comments for a commit:

```
comments = commit.comments.list()
```

Add a comment on a commit:

```
# Global comment
commit = commit.comments.create({'note': 'This is a nice comment'})
# Comment on a line in a file (on the new version of the file)
commit = commit.comments.create({'note': 'This is another comment',
                                'line': 12,
                                'line_type': 'new',
                                'path': 'README.rst'})
```

## 5.8.3 Commit status

### Reference

- v4 API:
  - `gitlab.v4.objects.ProjectCommitStatus`
  - `gitlab.v4.objects.ProjectCommitStatusManager`
  - `gitlab.v4.objects.Commit.statuses`
- GitLab API: <https://docs.gitlab.com/ce/api/commits.html>

## Examples

List the statuses for a commit:

```
statuses = commit.statuses.list()
```

Change the status of a commit:

```
commit.statuses.create({'state': 'success'})
```

## 5.9 Deploy keys

### 5.9.1 Deploy keys

#### Reference

- v4 API:
  - `gitlab.v4.objects.DeployKey`

- `gitlab.v4.objects.DeployKeyManager`
- `gitlab.Gitlab.deploykeys`
- GitLab API: [https://docs.gitlab.com/ce/api/deploy\\_keys.html](https://docs.gitlab.com/ce/api/deploy_keys.html)

## Examples

List the deploy keys:

```
keys = gl.deploykeys.list()
```

## 5.9.2 Deploy keys for projects

Deploy keys can be managed on a per-project basis.

### Reference

- v4 API:
  - `gitlab.v4.objects.ProjectKey`
  - `gitlab.v4.objects.ProjectKeyManager`
  - `gitlab.v4.objects.Project.keys`
- GitLab API: [https://docs.gitlab.com/ce/api/deploy\\_keys.html](https://docs.gitlab.com/ce/api/deploy_keys.html)

## Examples

List keys for a project:

```
keys = project.keys.list()
```

Get a single deploy key:

```
key = project.keys.get(key_id)
```

Create a deploy key for a project:

```
key = project.keys.create({'title': 'jenkins key',
                          'key': open('/home/me/.ssh/id_rsa.pub').read()})
```

Delete a deploy key for a project:

```
key = project.keys.list(key_id)
# or
key.delete()
```

Enable a deploy key for a project:

```
project.keys.enable(key_id)
```

Disable a deploy key for a project:

```
project_key.delete()
```

## 5.10 Deployments

### 5.10.1 Reference

- v4 API:
  - `gitlab.v4.objects.ProjectDeployment`
  - `gitlab.v4.objects.ProjectDeploymentManager`
  - `gitlab.v4.objects.Project.deployments`
- GitLab API: <https://docs.gitlab.com/ce/api/deployments.html>

### 5.10.2 Examples

List deployments for a project:

```
deployments = project.deployments.list()
```

Get a single deployment:

```
deployment = project.deployments.get(deployment_id)
```

## 5.11 Discussions

Discussions organize the notes in threads. See the *Notes* chapter for more information about notes.

Discussions are available for project issues, merge requests, snippets and commits.

### 5.11.1 Reference

- v4 API:
  - Issues:
    - `gitlab.v4.objects.ProjectIssueDiscussion`
    - `gitlab.v4.objects.ProjectIssueDiscussionManager`
    - `gitlab.v4.objects.ProjectIssueDiscussionNote`
    - `gitlab.v4.objects.ProjectIssueDiscussionNoteManager`
    - `gitlab.v4.objects.ProjectIssue.notes`
  - MergeRequests:
    - `gitlab.v4.objects.ProjectMergeRequestDiscussion`
    - `gitlab.v4.objects.ProjectMergeRequestDiscussionManager`
    - `gitlab.v4.objects.ProjectMergeRequestDiscussionNote`

- `gitlab.v4.objects.ProjectMergeRequestDiscussionNoteManager`
- `gitlab.v4.objects.ProjectMergeRequest.notes`

Snippets:

- `gitlab.v4.objects.ProjectSnippetDiscussion`
- `gitlab.v4.objects.ProjectSnippetDiscussionManager`
- `gitlab.v4.objects.ProjectSnippetDiscussionNote`
- `gitlab.v4.objects.ProjectSnippetDiscussionNoteManager`
- `gitlab.v4.objects.ProjectSnippet.notes`

- GitLab API: <https://docs.gitlab.com/ce/api/discussions.html>

## 5.11.2 Examples

List the discussions for a resource (issue, merge request, snippet or commit):

```
discussions = resource.discussions.list()
```

Get a single discussion:

```
discussion = resource.discussion.get(discussion_id)
```

You can access the individual notes in the discussion through the `notes` attribute. It holds a list of notes in chronological order:

```
# `resource.notes` is a DiscussionNoteManager, so we need to get the
# object notes using `attributes`
for note in discussion.attributes['notes']:
    print(note['body'])
```

---

**Note:** The notes are dicts, not objects.

---

You can add notes to existing discussions:

```
new_note = discussion.notes.create({'body': 'Episode IV: A new note'})
```

You can get and update a single note using the `*DiscussionNote` resources:

```
discussion = resource.discussion.get(discussion_id)
# Get the latest note's id
note_id = discussion.attributes['note'][-1]['id']
last_note = discussion.notes.get(note_id)
last_note.body = 'Updated comment'
last_note.save()
```

Create a new discussion:

```
discussion = resource.discussion.create({'body': 'First comment of discussion'})
```

You can comment on merge requests and commit diffs. Provide the position dict to define where the comment should appear in the diff:

```
mr_diff = mr.diffs.get(diff_id)
mr.discussions.create({'body': 'Note content',
                      'position': {
                          'base_sha': mr_diff.base_commit_sha,
                          'start_sha': mr_diff.start_commit_sha,
                          'head_sha': mr_diff.head_commit_sha,
                          'position_type': 'text',
                          'new_line': 1,
                          'old_path': 'README.rst',
                          'new_path': 'README.rst'}
                      })
```

Resolve / unresolve a merge request discussion:

```
mr_d = mr.discussions.get(d_id)
mr_d.resolved = True # True to resolve, False to unresolve
mr_d.save()
```

Delete a comment:

```
discussions.notes.delete(note_id)
# or
note.delete()
```

## 5.12 Environments

### 5.12.1 Reference

- v4 API:
  - `gitlab.v4.objects.ProjectEnvironment`
  - `gitlab.v4.objects.ProjectEnvironmentManager`
  - `gitlab.v4.objects.Project.environments`
- GitLab API: <https://docs.gitlab.com/ce/api/environments.html>

### 5.12.2 Examples

List environments for a project:

```
environments = project.environments.list()
```

Create an environment for a project:

```
environment = project.environments.create({'name': 'production'})
```

Update an environment for a project:

```
environment.external_url = 'http://foo.bar.com'
environment.save()
```

Delete an environment for a project:



```
environment = project.environments.delete(environment_id)
# or
environment.delete()
```

Stop an environments:

```
environment.stop()
```

## 5.13 Events

### 5.13.1 Reference

- v4 API:
  - `gitlab.v4.objects.Event`
  - `gitlab.v4.objects.EventManager`
  - `gitlab.Gitlab.events`
  - `gitlab.v4.objects.ProjectEvent`
  - `gitlab.v4.objects.ProjectEventManager`
  - `gitlab.v4.objects.Project.events`
  - `gitlab.v4.objects.UserEvent`
  - `gitlab.v4.objects.UserEventManager`
  - `gitlab.v4.objects.User.events`
- GitLab API: <https://docs.gitlab.com/ce/api/events.html>

### 5.13.2 Examples

You can list events for an entire Gitlab instance (admin), users and projects. You can filter you events you want to retrieve using the `action` and `target_type` attributes. The possible values for these attributes are available on the [gitlab documentation](#).

List all the events (paginated):

```
events = gl.events.list()
```

List the issue events on a project:

```
events = project.events.list(target_type='issue')
```

List the user events:

```
events = project.events.list()
```

## 5.14 Epics

### 5.14.1 Epics

#### Reference

- v4 API:
  - `gitlab.v4.objects.GroupEpic`
  - `gitlab.v4.objects.GroupEpicManager`
  - `gitlab.Gitlab.Group.epics`
- GitLab API: <https://docs.gitlab.com/ee/api/epics.html> (EE feature)

#### Examples

List the epics for a group:

```
epics = groups.epics.list()
```

Get a single epic for a group:

```
epic = group.epics.get(epic_iid)
```

Create an epic for a group:

```
epic = group.epics.create({'title': 'My Epic'})
```

Edit an epic:

```
epic.title = 'New title'  
epic.labels = ['label1', 'label2']  
epic.save()
```

Delete an epic:

```
epic.delete()
```

### 5.14.2 Epics issues

#### Reference

- v4 API:
  - `gitlab.v4.objects.GroupEpicIssue`
  - `gitlab.v4.objects.GroupEpicIssueManager`
  - `gitlab.Gitlab.GroupEpic.issues`
- GitLab API: [https://docs.gitlab.com/ee/api/epic\\_issues.html](https://docs.gitlab.com/ee/api/epic_issues.html) (EE feature)

## Examples

List the issues associated with an issue:

```
ei = epic.issues.list()
```

Associate an issue with an epic:

```
# use the issue id, not its iid
ei = epic.issues.create({'issue_id': 4})
```

Move an issue in the list:

```
ei.move_before_id = epic_issue_id_1
# or
ei.move_after_id = epic_issue_id_2
ei.save()
```

Delete an issue association:

```
ei.delete()
```

## 5.15 Features flags

### 5.15.1 Reference

- v4 API:
  - `gitlab.v4.objects.Feature`
  - `gitlab.v4.objects.FeatureManager`
  - `gitlab.Gitlab.features`
- GitLab API: <https://docs.gitlab.com/ce/api/features.html>

### 5.15.2 Examples

List features:

```
features = gl.features.list()
```

Create or set a feature:

```
feature = gl.features.set(feature_name, True)
feature = gl.features.set(feature_name, 30)
```

Delete a feature:

```
feature.delete()
```

## 5.16 Geo nodes

### 5.16.1 Reference

- v4 API:
  - `gitlab.v4.objects.GeoNode`
  - `gitlab.v4.objects.GeoNodeManager`
  - `gitlab.Gitlab.geonodes`
- GitLab API: [https://docs.gitlab.com/ee/api/geo\\_nodes.html](https://docs.gitlab.com/ee/api/geo_nodes.html) (EE feature)

### 5.16.2 Examples

List the geo nodes:

```
nodes = gl.geonodes.list()
```

Get the status of all the nodes:

```
status = gl.geonodes.status()
```

Get a specific node and its status:

```
node = gl.geonodes.get(node_id)
node.status()
```

Edit a node configuration:

```
node.url = 'https://secondary.mygitlab.domain'
node.save()
```

Delete a node:

```
node.delete()
```

List the sync failure on the current node:

```
failures = gl.geonodes.current_failures()
```

## 5.17 Groups

### 5.17.1 Groups

#### Reference

- v4 API:
  - `gitlab.v4.objects.Group`
  - `gitlab.v4.objects.GroupManager`
  - `gitlab.Gitlab.groups`

- GitLab API: <https://docs.gitlab.com/ce/api/groups.html>

## Examples

List the groups:

```
groups = gl.groups.list()
```

Get a group's detail:

```
group = gl.groups.get(group_id)
```

List a group's projects:

```
projects = group.projects.list()
```

You can filter and sort the result using the following parameters:

- `archived`: limit by archived status
- `visibility`: limit by visibility. Allowed values are `public`, `internal` and `private`
- `search`: limit to groups matching the given value
- `order_by`: sort by criteria. Allowed values are `id`, `name`, `path`, `created_at`, `updated_at` and `last_activity_at`
- `sort`: sort order: `asc` or `desc`
- `ci_enabled_first`: return CI enabled groups first

Create a group:

```
group = gl.groups.create({'name': 'group1', 'path': 'group1'})
```

Update a group:

```
group.description = 'My awesome group'
group.save()
```

Remove a group:

```
gl.group.delete(group_id)
# or
group.delete()
```

## 5.17.2 Subgroups

### Reference

- v4 API:
  - `gitlab.v4.objects.GroupSubgroup`
  - `gitlab.v4.objects.GroupSubgroupManager`
  - `gitlab.v4.objects.Group.subgroups`

## Examples

List the subgroups for a group:

```
subgroups = group.subgroups.list()

# The GroupSubgroup objects don't expose the same API as the Group
# objects. If you need to manipulate a subgroup as a group, create a new
# Group object:
real_group = gl.groups.get(subgroup_id, lazy=True)
real_group.issues.list()
```

### 5.17.3 Group custom attributes

#### Reference

- v4 API:
  - `gitlab.v4.objects.GroupCustomAttribute`
  - `gitlab.v4.objects.GroupCustomAttributeManager`
  - `gitlab.v4.objects.Group.customattributes`
- GitLab API: [https://docs.gitlab.com/ce/api/custom\\_attributes.html](https://docs.gitlab.com/ce/api/custom_attributes.html)

#### Examples

List custom attributes for a group:

```
attrs = group.customattributes.list()
```

Get a custom attribute for a group:

```
attr = group.customattributes.get(attr_key)
```

Set (create or update) a custom attribute for a group:

```
attr = group.customattributes.set(attr_key, attr_value)
```

Delete a custom attribute for a group:

```
attr.delete()
# or
group.customattributes.delete(attr_key)
```

Search groups by custom attribute:

```
group.customattributes.set('role': 'admin')
gl.groups.list(custom_attributes={'role': 'admin'})
```

### 5.17.4 Group members

The following constants define the supported access levels:

- `gitlab.GUEST_ACCESS = 10`
- `gitlab.REPORTER_ACCESS = 20`
- `gitlab.DEVELOPER_ACCESS = 30`
- `gitlab.MASTER_ACCESS = 40`
- `gitlab.OWNER_ACCESS = 50`

## Reference

- v4 API:
  - `gitlab.v4.objects.GroupMember`
  - `gitlab.v4.objects.GroupMemberManager`
  - `gitlab.v4.objects.Group.members`
- GitLab API: <https://docs.gitlab.com/ce/api/groups.html>

## Examples

List group members:

```
members = group.members.list()
```

Get a group member:

```
members = group.members.get(member_id)
```

Add a member to the group:

```
member = group.members.create({'user_id': user_id,
                               'access_level': gitlab.GUEST_ACCESS})
```

Update a member (change the access level):

```
member.access_level = gitlab.DEVELOPER_ACCESS
member.save()
```

Remove a member from the group:

```
group.members.delete(member_id)
# or
member.delete()
```

### 5.17.5 LDAP group links

Add an LDAP group link to an existing GitLab group:

```
group.add_ldap_group_link(ldap_group_cn, gitlab.DEVELOPER_ACCESS, 'ldapmain')
```

Remove a link:

```
group.delete_ldap_group_link(ldap_group_cn, 'ldapmain')
```

Sync the LDAP groups:

```
group.ldap_sync()
```

You can use the `ldapgroups` manager to list available LDAP groups:

```
# listing (supports pagination)
ldap_groups = gl.ldapgroups.list()

# filter using a group name
ldap_groups = gl.ldapgroups.list(search='foo')

# list the groups for a specific LDAP provider
ldap_groups = gl.ldapgroups.list(search='foo', provider='ldapmain')
```

## 5.18 Issues

### 5.18.1 Reported issues

#### Reference

- v4 API:
  - `gitlab.v4.objects.Issue`
  - `gitlab.v4.objects.IssueManager`
  - `gitlab.Gitlab.issues`
- GitLab API: <https://docs.gitlab.com/ce/api/issues.html>

#### Examples

List the issues:

```
issues = gl.issues.list()
```

Use the `state` and `label` parameters to filter the results. Use the `order_by` and `sort` attributes to sort the results:

```
open_issues = gl.issues.list(state='opened')
closed_issues = gl.issues.list(state='closed')
tagged_issues = gl.issues.list(labels=['foo', 'bar'])
```

### 5.18.2 Group issues

#### Reference

- v4 API:
  - `gitlab.v4.objects.GroupIssue`



- `gitlab.v4.objects.GroupIssueManager`
- `gitlab.v4.objects.Group.issues`
- GitLab API: <https://docs.gitlab.com/ce/api/issues.html>

## Examples

List the group issues:

```
issues = group.issues.list()
# Filter using the state, labels and milestone parameters
issues = group.issues.list(milestone='1.0', state='opened')
# Order using the order_by and sort parameters
issues = group.issues.list(order_by='created_at', sort='desc')
```

### 5.18.3 Project issues

#### Reference

- v4 API:
  - `gitlab.v4.objects.ProjectIssue`
  - `gitlab.v4.objects.ProjectIssueManager`
  - `gitlab.v4.objects.Project.issues`
- GitLab API: <https://docs.gitlab.com/ce/api/issues.html>

## Examples

List the project issues:

```
issues = project.issues.list()
# Filter using the state, labels and milestone parameters
issues = project.issues.list(milestone='1.0', state='opened')
# Order using the order_by and sort parameters
issues = project.issues.list(order_by='created_at', sort='desc')
```

Get a project issue:

```
issue = project.issues.get(issue_iid)
```

Create a new issue:

```
issue = project.issues.create({'title': 'I have a bug',
                              'description': 'Something useful here.'})
```

Update an issue:

```
issue.labels = ['foo', 'bar']
issue.save()
```

Close / reopen an issue:

```
# close an issue
issue.state_event = 'close'
issue.save()
# reopen it
issue.state_event = 'reopen'
issue.save()
```

Delete an issue:

```
project.issues.delete(issue_id)
# pr
issue.delete()
```

Subscribe / unsubscribe from an issue:

```
issue.subscribe()
issue.unsubscribe()
```

Move an issue to another project:

```
issue.move(other_project_id)
```

Make an issue as todo:

```
issue.todo()
```

Get time tracking stats:

```
issue.time_stats()
```

On recent versions of Gitlab the time stats are also returned as an issue object attribute:

```
issue = project.issue.get(iid)
print(issue.attributes['time_stats'])
```

Set a time estimate for an issue:

```
issue.time_estimate('3h30m')
```

Reset a time estimate for an issue:

```
issue.reset_time_estimate()
```

Add spent time for an issue:

```
issue.add_spent_time('3h30m')
```

Reset spent time for an issue:

```
issue.reset_spent_time()
```

Get user agent detail for the issue (admin only):

```
detail = issue.user_agent_detail()
```

Get the list of merge requests that will close an issue when merged:

```
mrs = issue.closed_by()
```

Get the list of participants:

```
users = issue.participants()
```

## 5.18.4 Issue links

### Reference

- v4 API:
  - `gitlab.v4.objects.ProjectIssueLink`
  - `gitlab.v4.objects.ProjectIssueLinkManager`
  - `gitlab.v4.objects.ProjectIssue.links`
- GitLab API: [https://docs.gitlab.com/ee/api/issue\\_links.html](https://docs.gitlab.com/ee/api/issue_links.html) (EE feature)

### Examples

List the issues linked to `i1`:

```
links = i1.links.list()
```

Link issue `i1` to issue `i2`:

```
data = {
    'target_project_id': i2.project_id,
    'target_issue_iid': i2.iid
}
src_issue, dest_issue = i1.links.create(data)
```

---

**Note:** The `create()` method returns the source and destination `ProjectIssue` objects, not a `ProjectIssueLink` object.

---

Delete a link:

```
i1.links.delete(issue_link_id)
```

## 5.19 Issue boards

### 5.19.1 Boards

Boards are a visual representation of existing issues for a project or a group. Issues can be moved from one list to the other to track progress and help with priorities.

## Reference

- v4 API:
  - `gitlab.v4.objects.ProjectBoard`
  - `gitlab.v4.objects.ProjectBoardManager`
  - `gitlab.v4.objects.Project.boards`
  - `gitlab.v4.objects.GroupBoard`
  - `gitlab.v4.objects.GroupBoardManager`
  - `gitlab.v4.objects.Group.boards`
- GitLab API:
  - <https://docs.gitlab.com/ce/api/boards.html>
  - [https://docs.gitlab.com/ce/api/group\\_boards.html](https://docs.gitlab.com/ce/api/group_boards.html)

## Examples

Get the list of existing boards for a project or a group:

```
# item is a Project or a Group
boards = project_or_group.boards.list()
```

Get a single board for a project or a group:

```
board = project_or_group.boards.get(board_id)
```

Create a board:

```
board = project_or_group.boards.create({'name': 'new-board'})
```

---

**Note:** Board creation is not supported in the GitLab CE edition.

---

Delete a board:

```
board.delete()
# or
project_or_group.boards.delete(board_id)
```

---

**Note:** Board deletion is not supported in the GitLab CE edition.

---

### 5.19.2 Board lists

Boards are made of lists of issues. Each list is associated to a label, and issues tagged with this label automatically belong to the list.

## Reference

- v4 API:
  - `gitlab.v4.objects.ProjectBoardList`
  - `gitlab.v4.objects.ProjectBoardListManager`
  - `gitlab.v4.objects.ProjectBoard.lists`
  - `gitlab.v4.objects.GroupBoardList`
  - `gitlab.v4.objects.GroupBoardListManager`
  - `gitlab.v4.objects.GroupBoard.lists`
- GitLab API:
  - <https://docs.gitlab.com/ce/api/boards.html>
  - [https://docs.gitlab.com/ce/api/group\\_boards.html](https://docs.gitlab.com/ce/api/group_boards.html)

## Examples

List the issue lists for a board:

```
b_lists = board.lists.list()
```

Get a single list:

```
b_list = board.lists.get(list_id)
```

Create a new list:

```
# First get a ProjectLabel
label = get_or_create_label()
# Then use its ID to create the new board list
b_list = board.lists.create({'label_id': label.id})
```

Change a list position. The first list is at position 0. Moving a list will set it at the given position and move the following lists up a position:

```
b_list.position = 2
b_list.save()
```

Delete a list:

```
b_list.delete()
```

## 5.20 Labels

### 5.20.1 Reference

- v4 API:
  - `gitlab.v4.objects.ProjectLabel`
  - `gitlab.v4.objects.ProjectLabelManager`

- `gitlab.v4.objects.Project.labels`

- GitLab API: <https://docs.gitlab.com/ce/api/labels.html>

## 5.20.2 Examples

List labels for a project:

```
labels = project.labels.list()
```

Create a label for a project:

```
label = project.labels.create({'name': 'foo', 'color': '#8899aa'})
```

Update a label for a project:

```
# change the name of the label:
label.new_name = 'bar'
label.save()
# change its color:
label.color = '#112233'
label.save()
```

Delete a label for a project:

```
project.labels.delete(label_id)
# or
label.delete()
```

Manage labels in issues and merge requests:

```
# Labels are defined as lists in issues and merge requests. The labels must
# exist.
issue = p.issues.create({'title': 'issue title',
                        'description': 'issue description',
                        'labels': ['foo']})
issue.labels.append('bar')
issue.save()
```

## 5.21 Notification settings

You can define notification settings globally, for groups and for projects. Valid levels are defined as constants:

- `gitlab.NOTIFICATION_LEVEL_DISABLED`
- `gitlab.NOTIFICATION_LEVEL_PARTICIPATING`
- `gitlab.NOTIFICATION_LEVEL_WATCH`
- `gitlab.NOTIFICATION_LEVEL_GLOBAL`
- `gitlab.NOTIFICATION_LEVEL_MENTION`
- `gitlab.NOTIFICATION_LEVEL_CUSTOM`

You get access to fine-grained settings if you use the `NOTIFICATION_LEVEL_CUSTOM` level.

### 5.21.1 Reference

- v4 API:
  - `gitlab.v4.objects.NotificationSettings`
  - `gitlab.v4.objects.NotificationSettingsManager`
  - `gitlab.Gitlab.notificationsettings`
  - `gitlab.v4.objects.GroupNotificationSettings`
  - `gitlab.v4.objects.GroupNotificationSettingsManager`
  - `gitlab.v4.objects.Group.notificationsettings`
  - `gitlab.v4.objects.ProjectNotificationSettings`
  - `gitlab.v4.objects.ProjectNotificationSettingsManager`
  - `gitlab.v4.objects.Project.notificationsettings`
- GitLab API: [https://docs.gitlab.com/ce/api/notification\\_settings.html](https://docs.gitlab.com/ce/api/notification_settings.html)

### 5.21.2 Examples

Get the notifications settings:

```
# global settings
settings = gl.notificationsettings.get()
# for a group
settings = gl.groups.get(group_id).notificationsettings.get()
# for a project
settings = gl.projects.get(project_id).notificationsettings.get()
```

Update the notifications settings:

```
# use a predefined level
settings.level = gitlab.NOTIFICATION_LEVEL_WATCH

# create a custom setup
settings.level = gitlab.NOTIFICATION_LEVEL_CUSTOM
settings.save() # will create additional attributes, but not mandatory

settings.new_merge_request = True
settings.new_issue = True
settings.new_note = True
settings.save()
```

## 5.22 Merge requests

You can use merge requests to notify a project that a branch is ready for merging. The owner of the target project can accept the merge request.

## 5.22.1 Reference

- v4 API:
  - `gitlab.v4.objects.ProjectMergeRequest`
  - `gitlab.v4.objects.ProjectMergeRequestManager`
  - `gitlab.v4.objects.Project.mergerequests`
- GitLab API: [https://docs.gitlab.com/ce/api/merge\\_requests.html](https://docs.gitlab.com/ce/api/merge_requests.html)

## 5.22.2 Examples

List MRs for a project:

```
mrs = project.mergerequests.list()
```

You can filter and sort the returned list with the following parameters:

- `state`: state of the MR. It can be one of `all`, `merged`, `opened` or `closed`
- `order_by`: sort by `created_at` or `updated_at`
- `sort`: sort order (`asc` or `desc`)

For example:

```
mrs = project.mergerequests.list(state='merged', order_by='updated_at')
```

Get a single MR:

```
mr = project.mergerequests.get(mr_id)
```

Create a MR:

```
mr = project.mergerequests.create({'source_branch': 'cool_feature',  
                                  'target_branch': 'master',  
                                  'title': 'merge cool feature',  
                                  'labels': ['label1', 'label2']})
```

Update a MR:

```
mr.description = 'New description'  
mr.labels = ['foo', 'bar']  
mr.save()
```

Change the state of a MR (close or reopen):

```
mr.state_event = 'close' # or 'reopen'  
mr.save()
```

Delete a MR:

```
project.mergerequests.delete(mr_id)  
# or  
mr.delete()
```

Accept a MR:



```
mr.merge()
```

Cancel a MR when the build succeeds:

```
mr.cancel_merge_when_pipeline_succeeds()
```

List commits of a MR:

```
commits = mr.commits()
```

List issues that will close on merge:

```
mr.closes_issues()
```

Subscribe to / unsubscribe from a MR:

```
mr.subscribe()  
mr.unsubscribe()
```

Mark a MR as todo:

```
mr.todo()
```

List the diffs for a merge request:

```
diffs = mr.diffs.list()
```

Get a diff for a merge request:

```
diff = mr.diffs.get(diff_id)
```

Get time tracking stats:

```
merge_request.time_stats()
```

On recent versions of Gitlab the time stats are also returned as a merge request object attribute:

```
mr = project.mergerequests.get(id)  
print(mr.attributes['time_stats'])
```

Set a time estimate for a merge request:

```
mr.time_estimate('3h30m')
```

Reset a time estimate for a merge request:

```
mr.reset_time_estimate()
```

Add spent time for a merge request:

```
mr.add_spent_time('3h30m')
```

Reset spent time for a merge request:

```
mr.reset_spent_time()
```

Get user agent detail for the issue (admin only):

```
detail = issue.user_agent_detail()
```

## 5.23 Merge request approvals settings

Merge request approvals can be defined at the project level or at the merge request level.

### 5.23.1 References

- v4 API:
  - `gitlab.v4.objects.ProjectApproval`
  - `gitlab.v4.objects.ProjectApprovalManager`
  - `gitlab.v4.objects.Project.approvals`
  - `gitlab.v4.objects.ProjectMergeRequestApproval`
  - `gitlab.v4.objects.ProjectMergeRequestApprovalManager`
  - `gitlab.v4.objects.ProjectMergeRequest.approvals`
- GitLab API: [https://docs.gitlab.com/ee/api/merge\\_request\\_approvals.html](https://docs.gitlab.com/ee/api/merge_request_approvals.html)

### 5.23.2 Examples

Get project-level or MR-level MR approvals settings:

```
p_mras = project.approvals.get()
mr_mras = mr.approvals.get()
```

Change project-level or MR-level MR approvals settings:

```
p_mras.approvals_before_merge = 2
p_mras.save()

mr_mras.approvals_before_merge = 2
mr_mras.save()
```

Change project-level or MR-level MR allowed approvers:

```
project.approvals.set_approvers(approver_ids=[105],
                                approver_group_ids=[653, 654])

mr.approvals.set_approvers(approver_ids=[105],
                            approver_group_ids=[653, 654])
```

## 5.24 Milestones

### 5.24.1 Reference

- v4 API:

- `gitlab.v4.objects.ProjectMilestone`
- `gitlab.v4.objects.ProjectMilestoneManager`
- `gitlab.v4.objects.Project.milestones`
- `gitlab.v4.objects.GroupMilestone`
- `gitlab.v4.objects.GroupMilestoneManager`
- `gitlab.v4.objects.Group.milestones`
- GitLab API:
  - <https://docs.gitlab.com/ce/api/milestones.html>
  - [https://docs.gitlab.com/ce/api/group\\_milestones.html](https://docs.gitlab.com/ce/api/group_milestones.html)

## 5.24.2 Examples

List the milestones for a project or a group:

```
p_milestones = project.milestones.list()
g_milestones = group.milestones.list()
```

You can filter the list using the following parameters:

- `iid`: unique ID of the milestone for the project
- `state`: either `active` or `closed`
- `search`: to search using a string

```
p_milestones = project.milestones.list(state='closed')
g_milestones = group.milestones.list(state='active')
```

Get a single milestone:

```
p_milestone = project.milestones.get(milestone_id)
g_milestone = group.milestones.get(milestone_id)
```

Create a milestone:

```
milestone = project.milestones.create({'title': '1.0'})
```

Edit a milestone:

```
milestone.description = 'v 1.0 release'
milestone.save()
```

Change the state of a milestone (activate / close):

```
# close a milestone
milestone.state_event = 'close'
milestone.save()

# activate a milestone
milestone.state_event = 'activate'
milestone.save()
```

List the issues related to a milestone:

```
issues = milestone.issues()
```

List the merge requests related to a milestone:

```
merge_requests = milestone.merge_requests()
```

## 5.25 Namespaces

### 5.25.1 Reference

- v4 API:
  - `gitlab.v4.objects.Namespace`
  - `gitlab.v4.objects.NamespaceManager`
  - `gitlab.Gitlab.namespaces`
- GitLab API: <https://docs.gitlab.com/ce/api/namespaces.html>

### 5.25.2 Examples

List namespaces:

```
namespaces = gl.namespaces.list()
```

Search namespaces:

```
namespaces = gl.namespaces.list(search='foo')
```

## 5.26 Notes

You can manipulate notes (comments) on project issues, merge requests and snippets.

### 5.26.1 Reference

- v4 API:
  - Issues:
    - `gitlab.v4.objects.ProjectIssueNote`
    - `gitlab.v4.objects.ProjectIssueNoteManager`
    - `gitlab.v4.objects.ProjectIssue.notes`
  - MergeRequests:
    - `gitlab.v4.objects.ProjectMergeRequestNote`
    - `gitlab.v4.objects.ProjectMergeRequestNoteManager`
    - `gitlab.v4.objects.ProjectMergeRequest.notes`

Snippets:

- `gitlab.v4.objects.ProjectSnippetNote`
- `gitlab.v4.objects.ProjectSnippetNoteManager`
- `gitlab.v4.objects.ProjectSnippet.notes`

- GitLab API: <https://docs.gitlab.com/ce/api/notes.html>

## 5.26.2 Examples

List the notes for a resource:

```
i_notes = issue.notes.list()
mr_notes = mr.notes.list()
s_notes = snippet.notes.list()
```

Get a note for a resource:

```
i_note = issue.notes.get(note_id)
mr_note = mr.notes.get(note_id)
s_note = snippet.notes.get(note_id)
```

Create a note for a resource:

```
i_note = issue.notes.create({'body': 'note content'})
mr_note = mr.notes.create({'body': 'note content'})
s_note = snippet.notes.create({'body': 'note content'})
```

Update a note for a resource:

```
note.body = 'updated note content'
note.save()
```

Delete a note for a resource:

```
note.delete()
```

## 5.27 Pages domains

### 5.27.1 Admin

#### References

- v4 API:
  - `gitlab.v4.objects.PagesDomain`
  - `gitlab.v4.objects.PagesDomainManager`
  - `gitlab.Gitlab.pagesdomains`
- GitLab API: [https://docs.gitlab.com/ce/api/pages\\_domains.html#list-all-pages-domains](https://docs.gitlab.com/ce/api/pages_domains.html#list-all-pages-domains)

## Examples

List all the existing domains (admin only):

```
domains = gl.pagesdomains.list()
```

## 5.27.2 Project pages domain

### References

- v4 API:
  - *gitlab.v4.objects.ProjectPagesDomain*
  - *gitlab.v4.objects.ProjectPagesDomainManager*
  - `gitlab.v4.objects.Project.pagesdomains`
- GitLab API: [https://docs.gitlab.com/ce/api/pages\\_domains.html#list-pages-domains](https://docs.gitlab.com/ce/api/pages_domains.html#list-pages-domains)

### Examples

List domains for a project:

```
domains = project.pagesdomains.list()
```

Get a single domain:

```
domain = project.pagesdomains.get('d1.example.com')
```

Create a new domain:

```
domain = project.pagesdomains.create({'domain': 'd2.example.com'})
```

Update an existing domain:

```
domain.certificate = open('d2.crt').read()
domain.key = open('d2.key').read()
domain.save()
```

Delete an existing domain:

```
domain.delete
# or
project.pagesdomains.delete('d2.example.com')
```

## 5.28 Projects

### 5.28.1 Projects

#### Reference

- v4 API:

- `gitlab.v4.objects.Project`
- `gitlab.v4.objects.ProjectManager`
- `gitlab.Gitlab.projects`

- GitLab API: <https://docs.gitlab.com/ce/api/projects.html>

## Examples

List projects:

```
projects = gl.projects.list()
```

The API provides several filtering parameters for the listing methods:

- `archived`: if `True` only archived projects will be returned
- `visibility`: returns only projects with the specified visibility (can be `public`, `internal` or `private`)
- `search`: returns project matching the given pattern

Results can also be sorted using the following parameters:

- `order_by`: sort using the given argument. Valid values are `id`, `name`, `path`, `created_at`, `updated_at` and `last_activity_at`. The default is to sort by `created_at`
- `sort`: sort order (`asc` or `desc`)

```
# Archived projects
projects = gl.projects.list(archived=1)
# Limit to projects with a defined visibility
projects = gl.projects.list(visibility='public')

# List owned projects
projects = gl.projects.owned()

# List starred projects
projects = gl.projects.starred()

# Search projects
projects = gl.projects.list(search='keyword')
```

Get a single project:

```
# Get a project by ID
project = gl.projects.get(10)
# Get a project by userspace/name
project = gl.projects.get('myteam/myproject')
```

Create a project:

```
project = gl.projects.create({'name': 'project1'})
```

Create a project for a user (admin only):

```
alice = gl.users.list(username='alice')[0]
user_project = alice.projects.create({'name': 'project'})
user_projects = alice.projects.list()
```

Create a project in a group:

```
# You need to get the id of the group, then use the namespace_id attribute  
# to create the group  
group_id = gl.groups.search('my-group')[0].id  
project = gl.projects.create({'name': 'myrepo', 'namespace_id': group_id})
```

Update a project:

```
project.snippets_enabled = 1  
project.save()
```

Delete a project:

```
gl.projects.delete(1)  
# or  
project.delete()
```

Fork a project:

```
fork = project.forks.create({})  
  
# fork to a specific namespace  
fork = project.forks.create({'namespace': 'myteam'})
```

Create/delete a fork relation between projects (requires admin permissions):

```
project.create_fork_relation(source_project.id)  
project.delete_fork_relation()
```

Get languages used in the project with percentage value:

```
languages = project.languages()
```

Star/unstar a project:

```
project.star()  
project.unstar()
```

Archive/unarchive a project:

```
project.archive()  
project.unarchive()
```

Start the housekeeping job:

```
project.housekeeping()
```

List the repository tree:

```
# list the content of the root directory for the default branch  
items = project.repository_tree()  
  
# list the content of a subdirectory on a specific branch  
items = project.repository_tree(path='docs', ref='branch1')
```

Get the content and metadata of a file for a commit, using a blob sha:



```
items = project.repository_tree(path='docs', ref='branch1')
file_info = p.repository_blob(items[0]['id'])
content = base64.b64decode(file_info['content'])
size = file_info['size']
```

Get the repository archive:

```
tgz = project.repository_archive()

# get the archive for a branch/tag/commit
tgz = project.repository_archive(sha='4567abc')
```

**Warning:** Archives are entirely stored in memory unless you use the streaming feature. See *the artifacts example*.

Get the content of a file using the blob id:

```
# find the id for the blob (simple search)
id = [d['id'] for d in p.repository_tree() if d['name'] == 'README.rst'][0]

# get the content
file_content = p.repository_raw_blob(id)
```

**Warning:** Blobs are entirely stored in memory unless you use the streaming feature. See *the artifacts example*.

Get a snapshot of the repository:

```
tar_file = project.snapshot()
```

**Warning:** Snapshots are entirely stored in memory unless you use the streaming feature. See *the artifacts example*.

Compare two branches, tags or commits:

```
result = project.repository_compare('master', 'branch1')

# get the commits
for commit in result['commits']:
    print(commit)

# get the diffs
for file_diff in result['diffs']:
    print(file_diff)
```

Get a list of contributors for the repository:

```
contributors = project.repository_contributors()
```

Get a list of users for the repository:

```
users = p.users.list()

# search for users
users = p.users.list(search='pattern')
```

Start the pull mirroring process (EE edition):

```
project.mirror_pull()
```

## 5.28.2 Import / Export

You can export projects from gitlab, and re-import them to create new projects or overwrite existing ones.

### Reference

- v4 API:
  - `gitlab.v4.objects.ProjectExport`
  - `gitlab.v4.objects.ProjectExportManager`
  - `gitlab.v4.objects.Project.exports`
  - `gitlab.v4.objects.ProjectImport`
  - `gitlab.v4.objects.ProjectImportManager`
  - `gitlab.v4.objects.Project.imports`
  - `gitlab.v4.objects.ProjectManager.import_project`
- GitLab API: [https://docs.gitlab.com/ce/api/project\\_import\\_export.html](https://docs.gitlab.com/ce/api/project_import_export.html)

### Examples

A project export is an asynchronous operation. To retrieve the archive generated by GitLab you need to:

1. Create an export using the API
2. Wait for the export to be done
3. Download the result

```
# Create the export
p = gl.projects.get(my_project)
export = p.exports.create({})

# Wait for the 'finished' status
export.refresh()
while export.export_status != 'finished':
    time.sleep(1)
    export.refresh()

# Download the result
with open('/tmp/export.tgz', 'wb') as f:
    export.download(streamed=True, action=f.write)
```

Import the project:

```

gl.projects.import_project(open('/tmp/export.tgz', 'rb'), 'my_new_project')
# Get a ProjectImport object to track the import status
project_import = gl.projects.get(output['id'], lazy=True).imports.get()
while project_import.import_status != 'finished':
    time.sleep(1)
    project_import.refresh()

```

### 5.28.3 Project custom attributes

#### Reference

- v4 API:
  - `gitlab.v4.objects.ProjectCustomAttribute`
  - `gitlab.v4.objects.ProjectCustomAttributeManager`
  - `gitlab.v4.objects.Project.customattributes`
- GitLab API: [https://docs.gitlab.com/ce/api/custom\\_attributes.html](https://docs.gitlab.com/ce/api/custom_attributes.html)

#### Examples

List custom attributes for a project:

```
attrs = project.customattributes.list()
```

Get a custom attribute for a project:

```
attr = project.customattributes.get(attr_key)
```

Set (create or update) a custom attribute for a project:

```
attr = project.customattributes.set(attr_key, attr_value)
```

Delete a custom attribute for a project:

```

attr.delete()
# or
project.customattributes.delete(attr_key)

```

Search projects by custom attribute:

```

project.customattributes.set('type': 'internal')
gl.projects.list(custom_attributes={'type': 'internal'})

```

### 5.28.4 Project files

#### Reference

- v4 API:
  - `gitlab.v4.objects.ProjectFile`
  - `gitlab.v4.objects.ProjectFileManager`

- `gitlab.v4.objects.Project.files`

- GitLab API: [https://docs.gitlab.com/ce/api/repository\\_files.html](https://docs.gitlab.com/ce/api/repository_files.html)

## Examples

Get a file:

```
f = project.files.get(file_path='README.rst', ref='master')

# get the base64 encoded content
print(f.content)

# get the decoded content
print(f.decode())
```

Create a new file:

```
f = project.files.create({'file_path': 'testfile.txt',
                          'branch': 'master',
                          'content': file_content,
                          'author_email': 'test@example.com',
                          'author_name': 'yourname',
                          'encoding': 'text',
                          'commit_message': 'Create testfile'})
```

Update a file. The entire content must be uploaded, as plain text or as base64 encoded text:

```
f.content = 'new content'
f.save(branch='master', commit_message='Update testfile')

# or for binary data
# Note: decode() is required with python 3 for data serialization. You can omit
# it with python 2
f.content = base64.b64encode(open('image.png').read()).decode()
f.save(branch='master', commit_message='Update testfile', encoding='base64')
```

Delete a file:

```
f.delete(commit_message='Delete testfile')
```

## 5.28.5 Project tags

### Reference

- v4 API:
  - `gitlab.v4.objects.ProjectTag`
  - `gitlab.v4.objects.ProjectTagManager`
  - `gitlab.v4.objects.Project.tags`
- GitLab API: <https://docs.gitlab.com/ce/api/tags.html>

## Examples

List the project tags:

```
tags = project.tags.list()
```

Get a tag:

```
tag = project.tags.get('1.0')
```

Create a tag:

```
tag = project.tags.create({'tag_name': '1.0', 'ref': 'master'})
```

Set or update the release note for a tag:

```
tag.set_release_description('awesome v1.0 release')
```

Delete a tag:

```
project.tags.delete('1.0')
# or
tag.delete()
```

## 5.28.6 Project snippets

The snippet visibility can be defined using the following constants:

- `gitlab.VISIBILITY_PRIVATE`
- `gitlab.VISIBILITY_INTERNAL`
- `gitlab.VISIBILITY_PUBLIC`

## Reference

- v4 API:
  - `gitlab.v4.objects.ProjectSnippet`
  - `gitlab.v4.objects.ProjectSnippetManager`
  - `gitlab.v4.objects.Project.files`
- GitLab API: [https://docs.gitlab.com/ce/api/project\\_snippets.html](https://docs.gitlab.com/ce/api/project_snippets.html)

## Examples

List the project snippets:

```
snippets = project.snippets.list()
```

Get a snippet:

```
snippets = project.snippets.list(snippet_id)
```

Get the content of a snippet:

```
print(snippet.content())
```

**Warning:** The snippet content is entirely stored in memory unless you use the streaming feature. See *the artifacts example*.

Create a snippet:

```
snippet = project.snippets.create({'title': 'sample 1',
                                  'file_name': 'foo.py',
                                  'code': 'import gitlab',
                                  'visibility_level':
gitlab.VISIBILITY_PRIVATE})
```

Update a snippet:

```
snippet.code = 'import gitlab\nimport whatever'
snippet.save
```

Delete a snippet:

```
project.snippets.delete(snippet_id)
# or
snippet.delete()
```

Get user agent detail (admin only):

```
detail = snippet.user_agent_detail()
```

## 5.28.7 Notes

See *Notes*.

## 5.28.8 Project members

### Reference

- v4 API:
  - `gitlab.v4.objects.ProjectMember`
  - `gitlab.v4.objects.ProjectMemberManager`
  - `gitlab.v4.objects.Project.members`
- GitLab API: <https://docs.gitlab.com/ce/api/members.html>

### Examples

List the project members:

```
members = project.members.list()
```

Search project members matching a query string:

```
members = project.members.list(query='bar')
```

Get a single project member:

```
member = project.members.get(1)
```

Add a project member:

```
member = project.members.create({'user_id': user.id, 'access_level':
                                gitlab.DEVELOPER_ACCESS})
```

Modify a project member (change the access level):

```
member.access_level = gitlab.MASTER_ACCESS
member.save()
```

Remove a member from the project team:

```
project.members.delete(user.id)
# or
member.delete()
```

Share/unshare the project with a group:

```
project.share(group.id, gitlab.DEVELOPER_ACCESS)
project.unshare(group.id)
```

## 5.28.9 Project hooks

### Reference

- v4 API:
  - `gitlab.v4.objects.ProjectHook`
  - `gitlab.v4.objects.ProjectHookManager`
  - `gitlab.v4.objects.Project.hooks`
- GitLab API: <https://docs.gitlab.com/ce/api/projects.html#hooks>

### Examples

List the project hooks:

```
hooks = project.hooks.list()
```

Get a project hook:

```
hook = project.hooks.get(1)
```

Create a project hook:

```
hook = project.hooks.create({'url': 'http://my/action/url', 'push_events': 1})
```

Update a project hook:

```
hook.push_events = 0
hook.save()
```

Delete a project hook:

```
project.hooks.delete(1)
# or
hook.delete()
```

## 5.28.10 Project Services

### Reference

- v4 API:
  - `gitlab.v4.objects.ProjectService`
  - `gitlab.v4.objects.ProjectServiceManager`
  - `gitlab.v4.objects.Project.services`
- GitLab API: <https://docs.gitlab.com/ce/api/services.html>

### Examples

Get a service:

```
service = project.services.get('asana')
# display its status (enabled/disabled)
print(service.active)
```

List the code names of available services (doesn't return objects):

```
services = project.services.available()
```

Configure and enable a service:

```
service.api_key = 'randomkey'
service.save()
```

Disable a service:

```
service.delete()
```

## 5.28.11 File uploads

### Reference

- v4 API:
  - `gitlab.v4.objects.Project.upload`
- Gitlab API: <https://docs.gitlab.com/ce/api/projects.html#upload-a-file>



## Examples

Upload a file into a project using a filesystem path:

```
project.upload("filename.txt", filepath="/some/path/filename.txt")
```

Upload a file into a project without a filesystem path:

```
project.upload("filename.txt", filedata="Raw data")
```

Upload a file and comment on an issue using the uploaded file's markdown:

```
uploaded_file = project.upload("filename.txt", filedata="data")
issue = project.issues.get(issue_id)
issue.notes.create({
    "body": "See the attached file: {}".format(uploaded_file["markdown"])
})
```

Upload a file and comment on an issue while using custom markdown to reference the uploaded file:

```
uploaded_file = project.upload("filename.txt", filedata="data")
issue = project.issues.get(issue_id)
issue.notes.create({
    "body": "See the [attached file]({})".format(uploaded_file["url"])
})
```

## 5.28.12 Project push rules

### Reference

- v4 API:
  - `gitlab.v4.objects.ProjectPushRules`
  - `gitlab.v4.objects.ProjectPushRulesManager`
  - `gitlab.v4.objects.Project.pushrules`
- GitLab API: <https://docs.gitlab.com/ee/api/projects.html#push-rules>

### Examples

Create project push rules (at least one rule is necessary):

```
project.pushrules.create({'deny_delete_tag': True})
```

Get project push rules (returns None if there are no push rules):

```
pr = project.pushrules.get()
```

Edit project push rules:

```
pr.branch_name_regex = '^((master|develop|support-\d+|release-\d+\.\.+|hotfix-\d+|feature-\d+)$)'
pr.save()
```

Delete project push rules:

```
pr.delete()
```

## 5.29 Runners

Runners are external processes used to run CI jobs. They are deployed by the administrator and registered to the GitLab instance.

Shared runners are available for all projects. Specific runners are enabled for a list of projects.

### 5.29.1 Global runners (admin)

#### Reference

- v4 API:
  - `gitlab.v4.objects.Runner`
  - `gitlab.v4.objects.RunnerManager`
  - `gitlab.Gitlab.runners`
- GitLab API: <https://docs.gitlab.com/ce/api/runners.html>

#### Examples

Use the `list()` and `all()` methods to list runners.

Both methods accept a `scope` parameter to filter the list. Allowed values for this parameter are:

- `active`
- `paused`
- `online`
- `specific(all() only)`
- `shared(all() only)`

---

**Note:** The returned objects hold minimal information about the runners. Use the `get()` method to retrieve detail about a runner.

---

```
# List owned runners
runners = gl.runners.list()
# With a filter
runners = gl.runners.list(scope='active')
# List all runners, using a filter
runners = gl.runners.all(scope='paused')
```

Get a runner's detail:

```
runner = gl.runners.get(runner_id)
```

Register a new runner:

```
runner = gl.runners.create({'token': secret_token})
```

Update a runner:

```
runner = gl.runners.get(runner_id)
runner.tag_list.append('new_tag')
runner.save()
```

Remove a runner:

```
gl.runners.delete(runner_id)
# or
runner.delete()
```

Verify a registered runner token:

```
try:
    gl.runners.verify(runner_token)
    print("Valid token")
except GitlabVerifyError:
    print("Invalid token")
```

## 5.29.2 Project runners

### Reference

- v4 API:
  - `gitlab.v4.objects.ProjectRunner`
  - `gitlab.v4.objects.ProjectRunnerManager`
  - `gitlab.v4.objects.Project.runners`
- GitLab API: <https://docs.gitlab.com/ce/api/runners.html>

### Examples

List the runners for a project:

```
runners = project.runners.list()
```

Enable a specific runner for a project:

```
p_runner = project.runners.create({'runner_id': runner.id})
```

Disable a specific runner for a project:

```
project.runners.delete(runner.id)
```

## 5.29.3 Runner jobs

### Reference

- v4 API:

- `gitlab.v4.objects.RunnerJob`
- `gitlab.v4.objects.RunnerJobManager`
- `gitlab.v4.objects.Runner.jobs`
- GitLab API: <https://docs.gitlab.com/ce/api/runners.html>

## Examples

List for jobs for a runner:

```
jobs = runner.jobs.list()
```

Filter the list using the jobs status:

```
# status can be 'running', 'success', 'failed' or 'canceled'  
active_jobs = runner.jobs.list(status='running')
```

## 5.30 Search API

You can search for resources at the top level, in a project or in a group. Searches are based on a scope (issues, merge requests, and so on) and a search string.

### 5.30.1 Reference

- v4 API:
  - `gitlab.Gitlab.search`
  - `gitlab.v4.objects.Group.search`
  - `gitlab.v4.objects.Project.search`
- GitLab API: <https://docs.gitlab.com/ce/api/search.html>

### 5.30.2 Examples

Search for issues matching a specific string:

```
# global search  
gl.search('issues', 'regression')  
  
# group search  
group = gl.groups.get('mygroup')  
group.search('issues', 'regression')  
  
# project search  
project = gl.projects.get('myproject')  
project.search('issues', 'regression')
```

The `search()` methods implement the pagination support:

```
# get lists of 10 items, and start at page 2
gl.search('issues', search_str, page=2, per_page=10)

# get a generator that will automatically make required API calls for
# pagination
for item in gl.search('issues', search_str, as_list=False):
    do_something(item)
```

The search API doesn't return objects, but dicts. If you need to act on objects, you need to create them explicitly:

```
for item in gl.search('issues', search_str, as_list=False):
    issue_project = gl.projects.get(item['project_id'], lazy=True)
    issue = issue_project.issues.get(item['iid'])
    issue.state = 'closed'
    issue.save()
```

## 5.31 Settings

### 5.31.1 Reference

- v4 API:
  - `gitlab.v4.objects.ApplicationSettings`
  - `gitlab.v4.objects.ApplicationSettingsManager`
  - `gitlab.Gitlab.settings`
- GitLab API: <https://docs.gitlab.com/ce/api/settings.html>

### 5.31.2 Examples

Get the settings:

```
settings = gl.settings.get()
```

Update the settings:

```
settings.signin_enabled = False
settings.save()
```

## 5.32 Snippets

### 5.32.1 Reference

- v4 API:
  - `gitlab.v4.objects.Snippet`
  - `gitlab.v4.objects.SnippetManager`
  - `gitlab.Gitlab.snippets`
- GitLab API: <https://docs.gitlab.com/ce/api/snippets.html>

## 5.32.2 Examples

List snippets owned by the current user:

```
snippets = gl.snippets.list()
```

List the public snippets:

```
public_snippets = gl.snippets.public()
```

Get a snippet:

```
snippet = gl.snippets.get(snippet_id)
# get the content
content = snippet.content()
```

**Warning:** Blobs are entirely stored in memory unless you use the streaming feature. See *the artifacts example*.

Create a snippet:

```
snippet = gl.snippets.create({'title': 'snippet1',
                              'file_name': 'snippet1.py',
                              'content': open('snippet1.py').read()})
```

Update a snippet:

```
snippet.visibility_level = gitlab.Project.VISIBILITY_PUBLIC
snippet.save()
```

Delete a snippet:

```
gl.snippets.delete(snippet_id)
# or
snippet.delete()
```

Get user agent detail (admin only):

```
detail = snippet.user_agent_detail()
```

## 5.33 System hooks

### 5.33.1 Reference

- v4 API:
  - `gitlab.v4.objects.Hook`
  - `gitlab.v4.objects.HookManager`
  - `gitlab.Gitlab.hooks`
- GitLab API: [https://docs.gitlab.com/ce/api/system\\_hooks.html](https://docs.gitlab.com/ce/api/system_hooks.html)

### 5.33.2 Examples

List the system hooks:

```
hooks = gl.hooks.list()
```

Create a system hook:

```
gl.hooks.get(hook_id)
```

Test a system hook. The returned object is not usable (it misses the hook ID):

```
hook = gl.hooks.create({'url': 'http://your.target.url'})
```

Delete a system hook:

```
gl.hooks.delete(hook_id)
# or
hook.delete()
```

## 5.34 Templates

You can request templates for different type of files:

- License files
- .gitignore files
- GitLab CI configuration files
- Dockerfiles

### 5.34.1 License templates

#### Reference

- v4 API:
  - *gitlab.v4.objects.License*
  - *gitlab.v4.objects.LicenseManager*
  - `gitlab.Gitlab.licenses`
- GitLab API: <https://docs.gitlab.com/ce/api/templates/licenses.html>

#### Examples

List known license templates:

```
licenses = gl.licenses.list()
```

Generate a license content for a project:

```
license = gl.licenses.get('apache-2.0', project='foobar', fullname='John Doe')
print(license.content)
```

## 5.34.2 .gitignore templates

### Reference

- v4 API:
  - `gitlab.v4.objects.Gitignore`
  - `gitlab.v4.objects.GitignoreManager`
  - `gitlab.Gitlab.gitignores`
- GitLab API: <https://docs.gitlab.com/ce/api/templates/gitignores.html>

### Examples

List known gitignore templates:

```
gitignores = gl.gitignores.list()
```

Get a gitignore template:

```
gitignore = gl.gitignores.get('Python')
print(gitignore.content)
```

## 5.34.3 GitLab CI templates

### Reference

- v4 API:
  - `gitlab.v4.objects.Gitlabciyaml`
  - `gitlab.v4.objects.GitlabciyamlManager`
  - `gitlab.Gitlab.gitlabciyaml`
- GitLab API: [https://docs.gitlab.com/ce/api/templates/gitlab\\_ci\\_ymls.html](https://docs.gitlab.com/ce/api/templates/gitlab_ci_ymls.html)

### Examples

List known GitLab CI templates:

```
gitlabciyaml = gl.gitlabciyaml.list()
```

Get a GitLab CI template:

```
gitlabciyaml = gl.gitlabciyaml.get('Pelican')
print(gitlabciyaml.content)
```

## 5.34.4 Dockerfile templates

### Reference

- v4 API:



- `gitlab.v4.objects.Dockerfile`
- `gitlab.v4.objects.DockerfileManager`
- `gitlab.Gitlab.gitlabciymls`
- GitLab API: Not documented.

## Examples

List known Dockerfile templates:

```
dockerfiles = gl.dockerfiles.list()
```

Get a Dockerfile template:

```
dockerfile = gl.dockerfiles.get('Python')
print(dockerfile.content)
```

## 5.35 Todos

### 5.35.1 Reference

- v4 API:
  - `Todo`
  - `TodoManager`
  - `gitlab.Gitlab.todos`
- GitLab API: <https://docs.gitlab.com/ce/api/todos.html>

### 5.35.2 Examples

List active todos:

```
todos = gl.todos.list()
```

You can filter the list using the following parameters:

- `action`: can be assigned, mentioned, build\_failed, marked, or approval\_required
- `author_id`
- `project_id`
- `state`: can be pending or done
- `type`: can be Issue or MergeRequest

For example:

```
todos = gl.todos.list(project_id=1)
todos = gl.todos.list(state='done', type='Issue')
```

Mark a todo as done:

```
gl.todos.delete(todo_id)
# or
todo.delete()
```

Mark all the todos as done:

```
nb_of_closed_todos = gl.todos.delete_all()
```

## 5.36 Users and current user

The Gitlab API exposes user-related method that can be manipulated by admins only.

The currently logged-in user is also exposed.

### 5.36.1 Users

#### References

- v4 API:
  - `gitlab.v4.objects.User`
  - `gitlab.v4.objects.UserManager`
  - `gitlab.Gitlab.users`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html>

#### Examples

Get the list of users:

```
users = gl.users.list()
```

Search users whose username match a given string:

```
users = gl.users.list(search='foo')
```

Get a single user:

```
# by ID
user = gl.users.get(2)
# by username
user = gl.users.list(username='root')[0]
```

Create a user:

```
user = gl.users.create({'email': 'john@doe.com',
                       'password': 's3cur3s3cr3T',
                       'username': 'jdoe',
                       'name': 'John Doe'})
```

Update a user:

```
user.name = 'Real Name'
user.save()
```

Delete a user:

```
gl.users.delete(2)
user.delete()
```

Block/Unblock a user:

```
user.block()
user.unblock()
```

Set the avatar image for a user:

```
# the avatar image can be passed as data (content of the file) or as a file
# object opened in binary mode
user.avatar = open('path/to/file.png', 'rb')
user.save()
```

Set an external identity for a user:

```
user.provider = 'oauth2_generic'
user.extern_uid = '3'
user.save()
```

## 5.36.2 User custom attributes

### References

- v4 API:
  - `gitlab.v4.objects.UserCustomAttribute`
  - `gitlab.v4.objects.UserCustomAttributeManager`
  - `gitlab.v4.objects.User.customattributes`
- GitLab API: [https://docs.gitlab.com/ce/api/custom\\_attributes.html](https://docs.gitlab.com/ce/api/custom_attributes.html)

### Examples

List custom attributes for a user:

```
attrs = user.customattributes.list()
```

Get a custom attribute for a user:

```
attr = user.customattributes.get(attr_key)
```

Set (create or update) a custom attribute for a user:

```
attr = user.customattributes.set(attr_key, attr_value)
```

Delete a custom attribute for a user:

```
attr.delete()
# or
user.customattributes.delete(attr_key)
```

Search users by custom attribute:

```
user.customattributes.set('role': 'QA')
gl.users.list(custom_attributes={'role': 'QA'})
```

### 5.36.3 User impersonation tokens

#### References

- v4 API:
  - `gitlab.v4.objects.UserImpersonationToken`
  - `gitlab.v4.objects.UserImpersonationTokenManager`
  - `gitlab.v4.objects.User.impersonationtokens`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#get-all-impersonation-tokens-of-a-user>

List impersonation tokens for a user:

```
i_t = user.impersonationtokens.list(state='active')
i_t = user.impersonationtokens.list(state='inactive')
```

Get an impersonation token for a user:

```
i_t = user.impersonationtokens.get(i_t_id)
```

Create and use an impersonation token for a user:

```
i_t = user.impersonationtokens.create({'name': 'token1', 'scopes': ['api']})
# use the token to create a new gitlab connection
user_gl = gitlab.Gitlab(gitlab_url, private_token=i_t.token)
```

Revoke (delete) an impersonation token for a user:

```
i_t.delete()
```

### 5.36.4 Current User

#### References

- v4 API:
  - `gitlab.v4.objects.CurrentUser`
  - `gitlab.v4.objects.CurrentUserManager`
  - `gitlab.Gitlab.user`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html>

## Examples

Get the current user:

```
gl.auth()
current_user = gl.user
```

### 5.36.5 GPG keys

#### References

You can manipulate GPG keys for the current user and for the other users if you are admin.

- v4 API:
  - `gitlab.v4.objects.CurrentUserGPGKey`
  - `gitlab.v4.objects.CurrentUserGPGKeyManager`
  - `gitlab.v4.objects.CurrentUser.gpgkeys`
  - `gitlab.v4.objects.UserGPGKey`
  - `gitlab.v4.objects.UserGPGKeyManager`
  - `gitlab.v4.objects.User.gpgkeys`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#list-all-gpg-keys>

#### Exemples

List GPG keys for a user:

```
gpgkeys = user.gpgkeys.list()
```

Get a GPG gpgkey for a user:

```
gpgkey = user.gpgkeys.get(1)
```

Create a GPG gpgkey for a user:

```
# get the key with `gpg --export -a GPG_KEY_ID`
k = user.gpgkeys.create({'key': public_key_content})
```

Delete a GPG gpgkey for a user:

```
user.gpgkeys.delete(1)
# or
gpgkey.delete()
```

### 5.36.6 SSH keys

#### References

You can manipulate SSH keys for the current user and for the other users if you are admin.

- v4 API:
  - `gitlab.v4.objects.CurrentUserKey`
  - `gitlab.v4.objects.CurrentUserKeyManager`
  - `gitlab.v4.objects.CurrentUser.keys`
  - `gitlab.v4.objects.UserKey`
  - `gitlab.v4.objects.UserKeyManager`
  - `gitlab.v4.objects.User.keys`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#list-ssh-keys>

## Examples

List SSH keys for a user:

```
keys = user.keys.list()
```

Create an SSH key for a user:

```
k = user.keys.create({'title': 'my_key',  
                    'key': open('/home/me/.ssh/id_rsa.pub').read()})
```

Delete an SSH key for a user:

```
user.keys.delete(1)  
# or  
key.delete()
```

## 5.36.7 Emails

### References

You can manipulate emails for the current user and for the other users if you are admin.

- v4 API:
  - `gitlab.v4.objects.CurrentUserEmail`
  - `gitlab.v4.objects.CurrentUserEmailManager`
  - `gitlab.v4.objects.CurrentUser.emails`
  - `gitlab.v4.objects.UserEmail`
  - `gitlab.v4.objects.UserEmailManager`
  - `gitlab.v4.objects.User.emails`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#list-emails>

## Exemples

List emails for a user:

```
emails = user.emails.list()
```

Get an email for a user:

```
email = gl.user_emails.list(1, user_id=1)
# or
email = user.emails.get(1)
```

Create an email for a user:

```
k = user.emails.create({'email': 'foo@bar.com'})
```

Delete an email for a user:

```
user.emails.delete(1)
# or
email.delete()
```

## 5.36.8 Users activities

### References

- admin only
- v4 API:
  - *gitlab.v4.objects.UserActivities*
  - *gitlab.v4.objects.UserActivitiesManager*
  - `gitlab.Gitlab.user_activities`
- GitLab API: <https://docs.gitlab.com/ce/api/users.html#get-user-activities-admin-only>

### Examples

Get the users activities:

```
activities = gl.user_activities.list(all=True, as_list=False)
```

## 5.37 Sidekiq metrics

### 5.37.1 Reference

- v4 API:
  - *gitlab.v4.objects.SidekiqManager*
  - `gitlab.Gitlab.sidekiq`
- GitLab API: [https://docs.gitlab.com/ce/api/sidekiq\\_metrics.html](https://docs.gitlab.com/ce/api/sidekiq_metrics.html)

## 5.37.2 Examples

```
gl.sidekiq.queue_metrics()
gl.sidekiq.process_metrics()
gl.sidekiq.job_stats()
gl.sidekiq.compound_metrics()
```

## 5.38 Wiki pages

### 5.38.1 References

- v4 API:
  - `gitlab.v4.objects.ProjectWiki`
  - `gitlab.v4.objects.ProjectWikiManager`
  - `gitlab.v4.objects.Project.wikis`
- GitLab API: <https://docs.gitlab.com/ce/api/wikis.html>

### Examples

Get the list of wiki pages for a project:

```
pages = project.wikis.list()
```

Get a single wiki page:

```
page = project.wikis.get(page_slug)
```

Create a wiki page:

```
page = project.wikis.create({'title': 'Wiki Page 1',
                             'content': open(a_file).read()})
```

Update a wiki page:

```
page.content = 'My new content'
page.save()
```

Delete a wiki page:

```
page.delete()
```



## 6.1 Subpackages

### 6.1.1 gitlab.v4 package

#### Submodules

#### gitlab.v4.objects module

**class** `gitlab.v4.objects.ApplicationSettings` (*manager, attrs*)  
Bases: `gitlab.mixins.SaveMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.ApplicationSettingsManager` (*gl, parent=None*)  
Bases: `gitlab.mixins.GetWithoutIdMixin`, `gitlab.mixins.UpdateMixin`, `gitlab.base.RESTManager`

#### Object update

Optional attributes for object update:

- `admin_notification_email`
- `after_sign_out_path`
- `after_sign_up_text`
- `akismet_api_key`
- `akismet_enabled`
- `circuitbreaker_access_retries`
- `circuitbreaker_check_interval`
- `circuitbreaker_failure_count_threshold`
- `circuitbreaker_failure_reset_time`

- `circuitbreaker_storage_timeout`
- `clientside_sentry_dsn`
- `clientside_sentry_enabled`
- `container_registry_token_expire_delay`
- `default_artifacts_expire_in`
- `default_branch_protection`
- `default_group_visibility`
- `default_project_visibility`
- `default_projects_limit`
- `default_snippet_visibility`
- `disabled_oauth_sign_in_sources`
- `domain_blacklist_enabled`
- `domain_blacklist`
- `domain_whitelist`
- `dsa_key_restriction`
- `ecdsa_key_restriction`
- `ed25519_key_restriction`
- `email_author_in_body`
- `enabled_git_access_protocol`
- `gravatar_enabled`
- `help_page_hide_commercial_content`
- `help_page_support_url`
- `home_page_url`
- `housekeeping_bitmaps_enabled`
- `housekeeping_enabled`
- `housekeeping_full_repack_period`
- `housekeeping_gc_period`
- `housekeeping_incremental_repack_period`
- `html_emails_enabled`
- `import_sources`
- `koding_enabled`
- `koding_url`
- `max_artifacts_size`
- `max_attachment_size`
- `max_pages_size`
- `metrics_enabled`

- `metrics_host`
- `metrics_method_call_threshold`
- `metrics_packet_size`
- `metrics_pool_size`
- `metrics_port`
- `metrics_sample_interval`
- `metrics_timeout`
- `password_authentication_enabled_for_web`
- `password_authentication_enabled_for_git`
- `performance_bar_allowed_group_id`
- `performance_bar_enabled`
- `plantuml_enabled`
- `plantuml_url`
- `polling_interval_multiplier`
- `project_export_enabled`
- `prometheus_metrics_enabled`
- `recaptcha_enabled`
- `recaptcha_private_key`
- `recaptcha_site_key`
- `repository_checks_enabled`
- `repository_storages`
- `require_two_factor_authentication`
- `restricted_visibility_levels`
- `rsa_key_restriction`
- `send_user_confirmation_email`
- `sentry_dsn`
- `sentry_enabled`
- `session_expire_delay`
- `shared_runners_enabled`
- `shared_runners_text`
- `sidekiq_throttling_enabled`
- `sidekiq_throttling_factor`
- `sidekiq_throttling_queues`
- `sign_in_text`
- `signup_enabled`
- `terminal_max_session_time`

- `two_factor_grace_period`
- `unique_ips_limit_enabled`
- `unique_ips_limit_per_user`
- `unique_ips_limit_time_window`
- `usage_ping_enabled`
- `user_default_external`
- `user_oauth_applications`
- `version_check_enabled`
- `enforce_terms`
- `terms`

**update** (*\*\*kwargs*)

Update an object on the server.

**Parameters**

- **id** – ID of the object to update (can be None if not required)
- **new\_data** – the update data for the object
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Returns** The new object data (*not* a RESTObject)

**Return type** dict

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabUpdateError` – If the server cannot perform the request

**class** `gitlab.v4.objects.BroadcastMessage` (*manager, attrs*)

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.BroadcastMessageManager` (*gl, parent=None*)

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

**Object Creation**

Mandatory attributes:

- `message`

Optional attributes:

- `starts_at`
- `ends_at`
- `color`
- `font`

**Object update**

Optional attributes for object update:

- `message`

- starts\_at
- ends\_at
- color
- font

```
class gitlab.v4.objects.CurrentUser (manager, attrs)
    Bases: gitlab.base.RESTObject
```

```
class gitlab.v4.objects.CurrentUserEmail (manager, attrs)
    Bases: gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject
```

```
class gitlab.v4.objects.CurrentUserEmailManager (gl, parent=None)
    Bases: gitlab.mixins.RetrieveMixin, gitlab.mixins.CreateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager
```

### Object Creation

Mandatory attributes:

- email

```
class gitlab.v4.objects.CurrentUserGPGKey (manager, attrs)
    Bases: gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject
```

```
class gitlab.v4.objects.CurrentUserGPGKeyManager (gl, parent=None)
    Bases: gitlab.mixins.RetrieveMixin, gitlab.mixins.CreateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager
```

### Object Creation

Mandatory attributes:

- key

```
class gitlab.v4.objects.CurrentUserKey (manager, attrs)
    Bases: gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject
```

```
class gitlab.v4.objects.CurrentUserKeyManager (gl, parent=None)
    Bases: gitlab.mixins.RetrieveMixin, gitlab.mixins.CreateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager
```

### Object Creation

Mandatory attributes:

- title
- key

```
class gitlab.v4.objects.CurrentUserManager (gl, parent=None)
    Bases: gitlab.mixins.GetWithoutIdMixin, gitlab.base.RESTManager
```

```
class gitlab.v4.objects.DeployKey (manager, attrs)
    Bases: gitlab.base.RESTObject
```

```
class gitlab.v4.objects.DeployKeyManager (gl, parent=None)
    Bases: gitlab.mixins.ListMixin, gitlab.base.RESTManager
```

```
class gitlab.v4.objects.Dockerfile (manager, attrs)
    Bases: gitlab.base.RESTObject
```

```
class gitlab.v4.objects.DockerfileManager (gl, parent=None)
    Bases: gitlab.mixins.RetrieveMixin, gitlab.base.RESTManager
```

**class** gitlab.v4.objects.**Event** (*manager, attrs*)

Bases: *gitlab.base.RESTObject*

**class** gitlab.v4.objects.**EventManager** (*gl, parent=None*)

Bases: *gitlab.mixins.ListMixin, gitlab.base.RESTManager*

#### Object listing filters

- `action`
- `target_type`
- `before`
- `after`
- `sort`

**class** gitlab.v4.objects.**Feature** (*manager, attrs*)

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**class** gitlab.v4.objects.**FeatureManager** (*gl, parent=None*)

Bases: *gitlab.mixins.ListMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager*

**set** (*\*\*kwargs*)

Create or update the object.

#### Parameters

- **name** (*str*) – The value to set for the object
- **value** (*bool/int*) – The value to set for the object
- **feature\_group** (*str*) – A feature group name
- **user** (*str*) – A GitLab username
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabSetError` – If an error occurred

**Returns** The created/updated attribute

**Return type** `obj`

**class** gitlab.v4.objects.**GeoNode** (*manager, attrs*)

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**repair** (*\*\*kwargs*)

Repair the OAuth authentication of the geo node.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabRepairError` – If the server failed to perform the request

**status** (*\*\*kwargs*)

Get the status of the geo node.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server failed to perform the request

**Returns** The status of the geo node

**Return type** dict

**class** `gitlab.v4.objects.GeoNodeManager` (*gl, parent=None*)

Bases: `gitlab.mixins.RetrieveMixin`, `gitlab.mixins.UpdateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

**Object update**

Optional attributes for object update:

- `enabled`
- `url`
- `files_max_capacity`
- `repos_max_capacity`

**current\_failures** (*\*\*kwargs*)

Get the list of failures on the current geo node.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server failed to perform the request

**Returns** The list of failures

**Return type** list

**status** (*\*\*kwargs*)

Get the status of all the geo nodes.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server failed to perform the request

**Returns** The status of all the geo nodes

**Return type** list

**class** `gitlab.v4.objects.Gitignore` (*manager, attrs*)

Bases: `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.GitignoreManager` (*gl, parent=None*)

Bases: `gitlab.mixins.RetrieveMixin`, `gitlab.base.RESTManager`

**class** `gitlab.v4.objects.Gitlabciyaml` (*manager, attrs*)

Bases: `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.GitlabciyamlManager` (*gl, parent=None*)

Bases: `gitlab.mixins.RetrieveMixin`, `gitlab.base.RESTManager`

**class** gitlab.v4.objects.**Group** (*manager, attrs*)

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**add\_ldap\_group\_link** (*\*\*kwargs*)

Add an LDAP group link.

**Parameters**

- **cn** (*str*) – CN of the LDAP group
- **group\_access** (*int*) – Minimum access level for members of the LDAP group
- **provider** (*str*) – LDAP provider for the LDAP group
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

**delete\_ldap\_group\_link** (*\*\*kwargs*)

Delete an LDAP group link.

**Parameters**

- **cn** (*str*) – CN of the LDAP group
- **provider** (*str*) – LDAP provider for the LDAP group
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabDeleteError` – If the server cannot perform the request

**ldap\_sync** (*\*\*kwargs*)

Sync LDAP groups.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

**search** (*\*\*kwargs*)

Search the group resources matching the provided string.

**Parameters**

- **scope** (*str*) – Scope of the search
- **search** (*str*) – Search string
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabSearchError` – If the server failed to perform the request

**Returns** A list of dicts describing the resources found.



**Return type** *GitlabList*

**transfer\_project** (\*\*kwargs)

Transfer a project to this group.

**Parameters**

- **to\_project\_id** (*int*) – ID of the project to transfer
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabTransferProjectError` – If the project could not be transferred

**class** `gitlab.v4.objects.GroupAccessRequest` (*manager, attrs*)

Bases: `gitlab.mixins.AccessRequestMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.GroupAccessRequestManager` (*gl, parent=None*)

Bases: `gitlab.mixins.ListMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

**class** `gitlab.v4.objects.GroupBadge` (*manager, attrs*)

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.GroupBadgeManager` (*gl, parent=None*)

Bases: `gitlab.mixins.BadgeRenderMixin`, `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

**Object Creation**

Mandatory attributes:

- `link_url`
- `image_url`

**Object update**

Optional attributes for object update:

- `link_url`
- `image_url`

**class** `gitlab.v4.objects.GroupBoard` (*manager, attrs*)

Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.GroupBoardList` (*manager, attrs*)

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.GroupBoardListManager` (*gl, parent=None*)

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

**Object Creation**

Mandatory attributes:

- `label_id`

### Object update

Mandatory attributes for object update:

- `position`

```
class gitlab.v4.objects.GroupBoardManager (gl, parent=None)
```

```
Bases: gitlab.mixins.NoUpdateMixin, gitlab.base.RESTManager
```

### Object Creation

Mandatory attributes:

- `name`

```
class gitlab.v4.objects.GroupCustomAttribute (manager, attrs)
```

```
Bases: gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject
```

```
class gitlab.v4.objects.GroupCustomAttributeManager (gl, parent=None)
```

```
Bases: gitlab.mixins.RetrieveMixin, gitlab.mixins.SetMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager
```

```
class gitlab.v4.objects.GroupEpic (manager, attrs)
```

```
Bases: gitlab.mixins.ObjectDeleteMixin, gitlab.mixins.SaveMixin, gitlab.base.RESTObject
```

```
class gitlab.v4.objects.GroupEpicIssue (manager, attrs)
```

```
Bases: gitlab.mixins.ObjectDeleteMixin, gitlab.mixins.SaveMixin, gitlab.base.RESTObject
```

```
save (**kwargs)
```

Save the changes made to the object to the server.

The object is updated to match what the server returns.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

**Raise:** `GitlabAuthenticationError`: If authentication is not correct `GitlabUpdateError`: If the server cannot perform the request

```
class gitlab.v4.objects.GroupEpicIssueManager (gl, parent=None)
```

```
Bases: gitlab.mixins.ListMixin, gitlab.mixins.CreateMixin, gitlab.mixins.UpdateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager
```

### Object Creation

Mandatory attributes:

- `issue_id`

### Object update

Optional attributes for object update:

- `move_before_id`
- `move_after_id`

```
create (**kwargs)
```

Create a new object.

**Parameters**

- **data** (*dict*) – Parameters to send to the server to create the resource
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

**Returns**

A new instance of the manage object class build with the data sent by the server

Return type *RESTObject*

```
class gitlab.v4.objects.GroupEpicManager (gl, parent=None)
    Bases: gitlab.mixins.CRUDMixin, gitlab.base.RESTManager
```

**Object listing filters**

- `author_id`
- `labels`
- `order_by`
- `sort`
- `search`

**Object Creation**

Mandatory attributes:

- `title`

Optional attributes:

- `labels`
- `description`
- `start_date`
- `end_date`

**Object update**

Optional attributes for object update:

- `title`
- `labels`
- `description`
- `start_date`
- `end_date`

```
class gitlab.v4.objects.GroupIssue (manager, attrs)
    Bases: gitlab.base.RESTObject
```

```
class gitlab.v4.objects.GroupIssueManager (gl, parent=None)
    Bases: gitlab.mixins.ListMixin, gitlab.base.RESTManager
```

**Object listing filters**

- `state`
- `labels`
- `milestone`

- `order_by`
- `sort`
- `iids`
- `author_id`
- `assignee_id`
- `my_reaction_emoji`
- `search`
- `created_after`
- `created_before`
- `updated_after`
- `updated_before`

**class** `gitlab.v4.objects.GroupManager` (*gl*, *parent=None*)  
Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

#### Object listing filters

- `skip_groups`
- `all_available`
- `search`
- `order_by`
- `sort`
- `statistics`
- `owned`
- `with_custom_attributes`

#### Object Creation

Mandatory attributes:

- `name`
- `path`

Optional attributes:

- `description`
- `visibility`
- `parent_id`
- `lfs_enabled`
- `request_access_enabled`

#### Object update

Optional attributes for object update:

- `name`
- `path`

- `description`
- `visibility`
- `lfs_enabled`
- `request_access_enabled`

**class** `gitlab.v4.objects.GroupMember` (*manager, attrs*)

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.GroupMemberManager` (*gl, parent=None*)

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

### Object Creation

Mandatory attributes:

- `access_level`
- `user_id`

Optional attributes:

- `expires_at`

### Object update

Mandatory attributes for object update:

- `access_level`

Optional attributes for object update:

- `expires_at`

**class** `gitlab.v4.objects.GroupMergeRequest` (*manager, attrs*)

Bases: `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.GroupMergeRequestManager` (*gl, parent=None*)

Bases: `gitlab.base.RESTManager`

**class** `gitlab.v4.objects.GroupMilestone` (*manager, attrs*)

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**issues** (*\*\*kwargs*)

List issues related to this milestone.

#### Parameters

- **all** (*bool*) – If True, return all the items, without pagination
- **per\_page** (*int*) – Number of items to retrieve per request
- **page** (*int*) – ID of the page to return (starts with page 1)
- **as\_list** (*bool*) – If set to False and no pagination option is defined, return a generator instead of a list
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabListError` – If the list could not be retrieved

**Returns** The list of issues

**Return type** *RESTObjectList*

**merge\_requests** (*\*\*kwargs*)

List the merge requests related to this milestone.

#### Parameters

- **all** (*bool*) – If True, return all the items, without pagination
- **per\_page** (*int*) – Number of items to retrieve per request
- **page** (*int*) – ID of the page to return (starts with page 1)
- **as\_list** (*bool*) – If set to False and no pagination option is defined, return a generator instead of a list
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabListError` – If the list could not be retrieved

**Returns** The list of merge requests

**Return type** *RESTObjectList*

**class** `gitlab.v4.objects.GroupMilestoneManager` (*gl, parent=None*)

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

#### Object listing filters

- `iids`
- `state`
- `search`

#### Object Creation

Mandatory attributes:

- `title`

Optional attributes:

- `description`
- `due_date`
- `start_date`

#### Object update

Optional attributes for object update:

- `title`
- `description`
- `due_date`
- `start_date`
- `state_event`

**class** gitlab.v4.objects.**GroupNotificationSettings** (*manager, attrs*)  
Bases: *gitlab.v4.objects.NotificationSettings*

**class** gitlab.v4.objects.**GroupNotificationSettingsManager** (*gl, parent=None*)  
Bases: *gitlab.v4.objects.NotificationSettingsManager*

#### Object update

Optional attributes for object update:

- level
- notification\_email
- new\_note
- new\_issue
- reopen\_issue
- close\_issue
- reassign\_issue
- new\_merge\_request
- reopen\_merge\_request
- close\_merge\_request
- reassign\_merge\_request
- merge\_merge\_request

**class** gitlab.v4.objects.**GroupProject** (*manager, attrs*)  
Bases: *gitlab.base.RESTObject*

**class** gitlab.v4.objects.**GroupProjectManager** (*gl, parent=None*)  
Bases: *gitlab.mixins.ListMixin, gitlab.base.RESTManager*

#### Object listing filters

- archived
- visibility
- order\_by
- sort
- search
- ci\_enabled\_first
- simple
- owned
- starred
- with\_custom\_attributes

**class** gitlab.v4.objects.**GroupSubgroup** (*manager, attrs*)  
Bases: *gitlab.base.RESTObject*

**class** gitlab.v4.objects.**GroupSubgroupManager** (*gl, parent=None*)  
Bases: *gitlab.mixins.ListMixin, gitlab.base.RESTManager*

#### Object listing filters

- skip\_groups
- all\_available
- search
- order\_by
- sort
- statistics
- owned
- with\_custom\_attributes

**class** gitlab.v4.objects.**GroupVariable** (*manager, attrs*)  
Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**class** gitlab.v4.objects.**GroupVariableManager** (*gl, parent=None*)  
Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

#### Object Creation

Mandatory attributes:

- key
- value

Optional attributes:

- protected

#### Object update

Mandatory attributes for object update:

- key
- value

Optional attributes for object update:

- protected

**class** gitlab.v4.objects.**Hook** (*manager, attrs*)  
Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**class** gitlab.v4.objects.**HookManager** (*gl, parent=None*)  
Bases: *gitlab.mixins.NoUpdateMixin, gitlab.base.RESTManager*

#### Object Creation

Mandatory attributes:

- url

**class** gitlab.v4.objects.**Issue** (*manager, attrs*)  
Bases: *gitlab.base.RESTObject*

**class** gitlab.v4.objects.**IssueManager** (*gl, parent=None*)  
Bases: *gitlab.mixins.ListMixin, gitlab.base.RESTManager*

#### Object listing filters

- state



- labels
- milestone
- scope
- author\_id
- assignee\_id
- my\_reaction\_emoji
- iids
- order\_by
- sort
- search
- created\_after
- created\_before
- updated\_after
- updated\_before

**class** gitlab.v4.objects.**LDAPGroup** (*manager, attrs*)

Bases: *gitlab.base.RESTObject*

**class** gitlab.v4.objects.**LDAPGroupManager** (*gl, parent=None*)

Bases: *gitlab.base.RESTManager*

#### Object listing filters

- search
- provider

**list** (*\*\*kwargs*)

Retrieve a list of objects.

#### Parameters

- **all** (*bool*) – If True, return all the items, without pagination
- **per\_page** (*int*) – Number of items to retrieve per request
- **page** (*int*) – ID of the page to return (starts with page 1)
- **as\_list** (*bool*) – If set to False and no pagination option is defined, return a generator instead of a list
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Returns** The list of objects, or a generator if *as\_list* is False

**Return type** list

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabListError` – If the server cannot perform the request

**class** gitlab.v4.objects.**License** (*manager, attrs*)

Bases: *gitlab.base.RESTObject*

```
class gitlab.v4.objects.LicenseManager (gl, parent=None)
    Bases: gitlab.mixins.RetrieveMixin, gitlab.base.RESTManager
```

#### Object listing filters

- popular

```
class gitlab.v4.objects.Namespace (manager, attrs)
    Bases: gitlab.base.RESTObject
```

```
class gitlab.v4.objects.NamespaceManager (gl, parent=None)
    Bases: gitlab.mixins.RetrieveMixin, gitlab.base.RESTManager
```

#### Object listing filters

- search

```
class gitlab.v4.objects.NotificationSettings (manager, attrs)
    Bases: gitlab.mixins.SaveMixin, gitlab.base.RESTObject
```

```
class gitlab.v4.objects.NotificationSettingsManager (gl, parent=None)
    Bases: gitlab.mixins.GetWithoutIdMixin, gitlab.mixins.UpdateMixin, gitlab.base.RESTManager
```

#### Object update

Optional attributes for object update:

- level
- notification\_email
- new\_note
- new\_issue
- reopen\_issue
- close\_issue
- reassign\_issue
- new\_merge\_request
- reopen\_merge\_request
- close\_merge\_request
- reassign\_merge\_request
- merge\_merge\_request

```
class gitlab.v4.objects.PagesDomain (manager, attrs)
    Bases: gitlab.base.RESTObject
```

```
class gitlab.v4.objects.PagesDomainManager (gl, parent=None)
    Bases: gitlab.mixins.ListMixin, gitlab.base.RESTManager
```

```
class gitlab.v4.objects.Project (manager, attrs)
    Bases: gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject
```

```
archive (**kwargs)
    Archive a project.
```

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server failed to perform the request

**create\_fork\_relation** (\*\*kwargs)

Create a forked from/to relation between existing projects.

**Parameters**

- **forked\_from\_id** (*int*) – The ID of the project that was forked from
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the relation could not be created

**delete\_fork\_relation** (\*\*kwargs)

Delete a forked relation between existing projects.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabDeleteError` – If the server failed to perform the request

**delete\_merged\_branches** (\*\*kwargs)

Delete merged branches.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabDeleteError` – If the server failed to perform the request

**housekeeping** (\*\*kwargs)

Start the housekeeping task.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabHousekeepingError` – If the server failed to perform the request

**languages** (\*\*kwargs)

Get languages used in the project with percentage value.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server failed to perform the request

**mirror\_pull** (\*\*kwargs)

Start the pull mirroring process for the project.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server failed to perform the request

**repository\_archive** (*\*\*kwargs*)

Return a tarball of the repository.

**Parameters**

- **sha** (*str*) – ID of the commit (default branch by default)
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk\_size* and each chunk is passed to *action* for treatment
- **action** (*callable*) – Callable responsible of dealing with chunk of data
- **chunk\_size** (*int*) – Size of each chunk
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabListError` – If the server failed to perform the request

**Returns** The binary data of the archive

**Return type** `str`

**repository\_blob** (*\*\*kwargs*)

Return a file by blob SHA.

**Parameters**

- **sha** (*str*) – ID of the blob
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server failed to perform the request

**Returns** The blob content and metadata

**Return type** `dict`

**repository\_compare** (*\*\*kwargs*)

Return a diff between two branches/commits.

**Parameters**

- **from** (*str*) – Source branch/SHA
- **to** (*str*) – Destination branch/SHA
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server failed to perform the request

**Returns** The diff

**Return type** `str`

**repository\_contributors** (\*\*kwargs)

Return a list of contributors for the project.

**Parameters**

- **all** (*bool*) – If True, return all the items, without pagination
- **per\_page** (*int*) – Number of items to retrieve per request
- **page** (*int*) – ID of the page to return (starts with page 1)
- **as\_list** (*bool*) – If set to False and no pagination option is defined, return a generator instead of a list
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server failed to perform the request

**Returns** The contributors

**Return type** list

**repository\_raw\_blob** (\*\*kwargs)

Return the raw file contents for a blob.

**Parameters**

- **sha** (*str*) – ID of the blob
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk\_size* and each chunk is passed to *action* for treatment
- **action** (*callable*) – Callable responsible of dealing with chunk of data
- **chunk\_size** (*int*) – Size of each chunk
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server failed to perform the request

**Returns** The blob content if streamed is False, None otherwise

**Return type** str

**repository\_tree** (\*\*kwargs)

Return a list of files in the repository.

**Parameters**

- **path** (*str*) – Path of the top folder (/ by default)
- **ref** (*str*) – Reference to a commit or branch
- **recursive** (*bool*) – Whether to get the tree recursively
- **all** (*bool*) – If True, return all the items, without pagination
- **per\_page** (*int*) – Number of items to retrieve per request
- **page** (*int*) – ID of the page to return (starts with page 1)

- **as\_list** (*bool*) – If set to False and no pagination option is defined, return a generator instead of a list
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server failed to perform the request

**Returns** The representation of the tree

**Return type** list

**search** (*\*\*kwargs*)

Search the project resources matching the provided string.

**Parameters**

- **scope** (*str*) – Scope of the search
- **search** (*str*) – Search string
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabSearchError` – If the server failed to perform the request

**Returns** A list of dicts describing the resources found.

**Return type** *GitlabList*

**share** (*\*\*kwargs*)

Share the project with a group.

**Parameters**

- **group\_id** (*int*) – ID of the group.
- **group\_access** (*int*) – Access level for the group.
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server failed to perform the request

**snapshot** (*\*\*kwargs*)

Return a snapshot of the repository.

**Parameters**

- **wiki** (*bool*) – If True return the wiki repository
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk\_size* and each chunk is passed to *action* for treatment.
- **action** (*callable*) – Callable responsible of dealing with chunk of data
- **chunk\_size** (*int*) – Size of each chunk
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the content could not be retrieved

**Returns** The uncompressed tar archive of the repository

**Return type** `str`

**star** (*\*\*kwargs*)

Star a project.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server failed to perform the request

**trigger\_pipeline** (*\*\*kwargs*)

Trigger a CI build.

See <https://gitlab.com/help/ci/triggers/README.md#trigger-a-build>

**Parameters**

- **ref** (*str*) – Commit to build; can be a branch name or a tag
- **token** (*str*) – The trigger token
- **variables** (*dict*) – Variables passed to the build script
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server failed to perform the request

**unarchive** (*\*\*kwargs*)

Unarchive a project.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabDeleteError` – If the server failed to perform the request

**unshare** (*\*\*kwargs*)

Delete a shared project link within a group.

**Parameters**

- **group\_id** (*int*) – ID of the group.
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabDeleteError` – If the server failed to perform the request

**unstar** (*\*\*kwargs*)

Unstar a project.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabDeleteError` – If the server failed to perform the request

**upload** (*\*\*kwargs*)

Upload the specified file into the project.

---

**Note:** Either `filedata` or `filepath` *MUST* be specified.

---

**Parameters**

- **filename** (*str*) – The name of the file being uploaded
- **filedata** (*bytes*) – The raw data of the file being uploaded
- **filepath** (*str*) – The path to a local file to upload (optional)

**Raises**

- `GitlabConnectionError` – If the server cannot be reached
- `GitlabUploadError` – If the file upload fails
- `GitlabUploadError` – If `filedata` and `filepath` are not specified
- `GitlabUploadError` – If both `filedata` and `filepath` are specified

**Returns****A dict with the keys:**

- `alt` - The alternate text for the upload
- `url` - The direct url to the uploaded file
- `markdown` - Markdown for the uploaded file

**Return type** dict**class** `gitlab.v4.objects.ProjectAccessRequest` (*manager, attrs*)Bases: `gitlab.mixins.AccessRequestMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`**class** `gitlab.v4.objects.ProjectAccessRequestManager` (*gl, parent=None*)Bases: `gitlab.mixins.ListMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`**class** `gitlab.v4.objects.ProjectApproval` (*manager, attrs*)Bases: `gitlab.mixins.SaveMixin`, `gitlab.base.RESTObject`**class** `gitlab.v4.objects.ProjectApprovalManager` (*gl, parent=None*)Bases: `gitlab.mixins.GetWithoutIdMixin`, `gitlab.mixins.UpdateMixin`, `gitlab.base.RESTManager`**Object update**

Optional attributes for object update:

- `approvals_before_merge`
- `reset_approvals_on_push`
- `disable_overriding_approvers_per_merge_request`



**set\_approvers** (\*\*kwargs)

Change project-level allowed approvers and approver groups.

#### Parameters

- **approver\_ids** (*list*) – User IDs that can approve MRs
- **approver\_group\_ids** (*list*) – Group IDs whose members can approve MRs

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabUpdateError` – If the server failed to perform the request

**class** `gitlab.v4.objects.ProjectBadge` (*manager, attrs*)

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.ProjectBadgeManager` (*gl, parent=None*)

Bases: `gitlab.mixins.BadgeRenderMixin`, `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

#### Object Creation

Mandatory attributes:

- `link_url`
- `image_url`

#### Object update

Optional attributes for object update:

- `link_url`
- `image_url`

**class** `gitlab.v4.objects.ProjectBoard` (*manager, attrs*)

Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.ProjectBoardList` (*manager, attrs*)

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.ProjectBoardListManager` (*gl, parent=None*)

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

#### Object Creation

Mandatory attributes:

- `label_id`

#### Object update

Mandatory attributes for object update:

- `position`

**class** `gitlab.v4.objects.ProjectBoardManager` (*gl, parent=None*)

Bases: `gitlab.mixins.NoUpdateMixin`, `gitlab.base.RESTManager`

#### Object Creation

Mandatory attributes:

- name

**class** gitlab.v4.objects.**ProjectBranch** (*manager, attrs*)

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**protect** (*\*\*kwargs*)

Protect the branch.

#### Parameters

- **developers\_can\_push** (*bool*) – Set to True if developers are allowed to push to the branch
- **developers\_can\_merge** (*bool*) – Set to True if developers are allowed to merge to the branch
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabProtectError` – If the branch could not be protected

**unprotect** (*\*\*kwargs*)

Unprotect the branch.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabProtectError` – If the branch could not be unprotected

**class** gitlab.v4.objects.**ProjectBranchManager** (*gl, parent=None*)

Bases: *gitlab.mixins.NoUpdateMixin, gitlab.base.RESTManager*

#### Object Creation

Mandatory attributes:

- branch
- ref

**class** gitlab.v4.objects.**ProjectCommit** (*manager, attrs*)

Bases: *gitlab.base.RESTObject*

**cherry\_pick** (*\*\*kwargs*)

Cherry-pick a commit into a branch.

#### Parameters

- **branch** (*str*) – Name of target branch
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCherryPickError` – If the cherry-pick could not be performed

**diff** (*\*\*kwargs*)

Generate the commit diff.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the diff could not be retrieved

**Returns** The changes done in this commit

**Return type** list

**merge\_requests** (*\*\*kwargs*)

List the merge requests related to the commit.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the references could not be retrieved

**Returns** The merge requests related to the commit.

**Return type** list

**refs** (*\*\*kwargs*)

List the references the commit is pushed to.

**Parameters**

- **type** (*str*) – The scope of references ('branch', 'tag' or 'all')
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the references could not be retrieved

**Returns** The references the commit is pushed to.

**Return type** list

**class** `gitlab.v4.objects.ProjectCommitComment` (*manager, attrs*)

Bases: `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.ProjectCommitCommentManager` (*gl, parent=None*)

Bases: `gitlab.mixins.ListMixin`, `gitlab.mixins.CreateMixin`, `gitlab.base.RESTManager`

**Object Creation**

Mandatory attributes:

- `note`

Optional attributes:

- `path`
- `line`
- `line_type`

**class** `gitlab.v4.objects.ProjectCommitDiscussion` (*manager, attrs*)

Bases: `gitlab.base.RESTObject`

```
class gitlab.v4.objects.ProjectCommitDiscussionManager (gl, parent=None)
    Bases: gitlab.mixins.RetrieveMixin, gitlab.mixins.CreateMixin, gitlab.base.RESTManager
```

#### Object Creation

Mandatory attributes:

- body

Optional attributes:

- created\_at

```
class gitlab.v4.objects.ProjectCommitDiscussionNote (manager, attrs)
    Bases: gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject
```

```
class gitlab.v4.objects.ProjectCommitDiscussionNoteManager (gl, parent=None)
```

```
    Bases: gitlab.mixins.GetMixin, gitlab.mixins.CreateMixin, gitlab.mixins.UpdateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager
```

#### Object Creation

Mandatory attributes:

- body

Optional attributes:

- created\_at
- position

#### Object update

Mandatory attributes for object update:

- body

```
class gitlab.v4.objects.ProjectCommitManager (gl, parent=None)
    Bases: gitlab.mixins.RetrieveMixin, gitlab.mixins.CreateMixin, gitlab.base.RESTManager
```

#### Object Creation

Mandatory attributes:

- branch
- commit\_message
- actions

Optional attributes:

- author\_email
- author\_name

```
class gitlab.v4.objects.ProjectCommitStatus (manager, attrs)
    Bases: gitlab.base.RESTObject, gitlab.mixins.RefreshMixin
```

```
class gitlab.v4.objects.ProjectCommitStatusManager (gl, parent=None)
    Bases: gitlab.mixins.ListMixin, gitlab.mixins.CreateMixin, gitlab.base.RESTManager
```

#### Object Creation

Mandatory attributes:

- `state`

Optional attributes:

- `description`
- `name`
- `context`
- `ref`
- `target_url`
- `coverage`

**create** (*\*\*kwargs*)  
Create a new object.

#### Parameters

- **data** (*dict*) – Parameters to send to the server to create the resource
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo` or `'ref_name'`, `'stage'`, `'name'`, `'all'`)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

#### Returns

A new instance of the manage object class build with the data sent by the server

Return type *RESTObject*

```
class gitlab.v4.objects.ProjectCustomAttribute (manager, attrs)
```

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

```
class gitlab.v4.objects.ProjectCustomAttributeManager (gl, parent=None)
```

Bases: *gitlab.mixins.RetrieveMixin, gitlab.mixins.SetMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager*

```
class gitlab.v4.objects.ProjectDeployment (manager, attrs)
```

Bases: *gitlab.base.RESTObject*

```
class gitlab.v4.objects.ProjectDeploymentManager (gl, parent=None)
```

Bases: *gitlab.mixins.RetrieveMixin, gitlab.base.RESTManager*

#### Object listing filters

- `order_by`
- `sort`

```
class gitlab.v4.objects.ProjectEnvironment (manager, attrs)
```

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**stop** (*\*\*kwargs*)

Stop the environment.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabStopError` – If the operation failed

**class** `gitlab.v4.objects.ProjectEnvironmentManager` (*gl, parent=None*)

Bases: `gitlab.mixins.ListMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.UpdateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

**Object Creation**

Mandatory attributes:

- `name`

Optional attributes:

- `external_url`

**Object update**

Optional attributes for object update:

- `name`
- `external_url`

**class** `gitlab.v4.objects.ProjectEvent` (*manager, attrs*)

Bases: `gitlab.v4.objects.Event`

**class** `gitlab.v4.objects.ProjectEventManager` (*gl, parent=None*)

Bases: `gitlab.v4.objects.EventManager`

**Object listing filters**

- `action`
- `target_type`
- `before`
- `after`
- `sort`

**class** `gitlab.v4.objects.ProjectExport` (*manager, attrs*)

Bases: `gitlab.mixins.RefreshMixin`, `gitlab.base.RESTObject`

**download** (*\*\*kwargs*)

Download the archive of a project export.

**Parameters**

- **streamed** (*bool*) – If True the data will be processed by chunks of `chunk_size` and each chunk is passed to `action` for treatment
- **action** (*callable*) – Callable responsible of dealing with chunk of data
- **chunk\_size** (*int*) – Size of each chunk
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server failed to perform the request

**Returns** The blob content if streamed is False, None otherwise

**Return type** str

**class** gitlab.v4.objects.**ProjectExportManager** (*gl, parent=None*)

Bases: *gitlab.mixins.GetWithoutIdMixin, gitlab.mixins.CreateMixin, gitlab.base.RESTManager*

#### Object Creation

Optional attributes:

- description

**class** gitlab.v4.objects.**ProjectFile** (*manager, attrs*)

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**decode** ()

Returns the decoded content of the file.

**Returns** the decoded content.

**Return type** (str)

**delete** (*branch, commit\_message, \*\*kwargs*)

Delete the file from the server.

#### Parameters

- **branch** (*str*) – Branch from which the file will be removed
- **commit\_message** (*str*) – Commit message for the deletion
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabDeleteError` – If the server cannot perform the request

**save** (*branch, commit\_message, \*\*kwargs*)

Save the changes made to the file to the server.

The object is updated to match what the server returns.

#### Parameters

- **branch** (*str*) – Branch in which the file will be updated
- **commit\_message** (*str*) – Message to send with the commit
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabUpdateError` – If the server cannot perform the request

**class** gitlab.v4.objects.**ProjectFileManager** (*gl, parent=None*)

Bases: *gitlab.mixins.GetMixin, gitlab.mixins.CreateMixin, gitlab.mixins.UpdateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager*

#### Object Creation

Mandatory attributes:

- `file_path`
- `branch`
- `content`
- `commit_message`

Optional attributes:

- `encoding`
- `author_email`
- `author_name`

### Object update

Mandatory attributes for object update:

- `file_path`
- `branch`
- `content`
- `commit_message`

Optional attributes for object update:

- `encoding`
- `author_email`
- `author_name`

**create** (*\*\*kwargs*)

Create a new object.

#### Parameters

- **data** (*dict*) – parameters to send to the server to create the resource
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

#### Returns

a new instance of the managed object class built with the data sent by the server

**Return type** *RESTObject*

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

**delete** (*\*\*kwargs*)

Delete a file on the server.

#### Parameters

- **file\_path** (*str*) – Path of the file to remove
- **branch** (*str*) – Branch from which the file will be removed
- **commit\_message** (*str*) – Commit message for the deletion
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

#### Raises



- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabDeleteError` – If the server cannot perform the request

**get** (*\*\*kwargs*)

Retrieve a single file.

#### Parameters

- **file\_path** (*str*) – Path of the file to retrieve
- **ref** (*str*) – Name of the branch, tag or commit
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the file could not be retrieved

**Returns** The generated RESTObject

**Return type** object

**raw** (*\*\*kwargs*)

Return the content of a file for a commit.

#### Parameters

- **ref** (*str*) – ID of the commit
- **filepath** (*str*) – Path of the file to return
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk\_size* and each chunk is passed to *action* for treatment
- **action** (*callable*) – Callable responsible of dealing with chunk of data
- **chunk\_size** (*int*) – Size of each chunk
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the file could not be retrieved

**Returns** The file content

**Return type** str

**update** (*\*\*kwargs*)

Update an object on the server.

#### Parameters

- **id** – ID of the object to update (can be None if not required)
- **new\_data** – the update data for the object
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

**Returns** The new object data (*not* a RESTObject)

**Return type** dict

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabUpdateError` – If the server cannot perform the request

**class** `gitlab.v4.objects.ProjectFork` (*manager, attrs*)

Bases: `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.ProjectForkManager` (*gl, parent=None*)

Bases: `gitlab.mixins.CreateMixin`, `gitlab.base.RESTManager`

#### Object listing filters

- `archived`
- `visibility`
- `order_by`
- `sort`
- `search`
- `simple`
- `owned`
- `membership`
- `starred`
- `statistics`
- `with_custom_attributes`
- `with_issues_enabled`
- `with_merge_requests_enabled`

#### Object Creation

Optional attributes:

- `namespace`

**class** `gitlab.v4.objects.ProjectHook` (*manager, attrs*)

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.ProjectHookManager` (*gl, parent=None*)

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

#### Object Creation

Mandatory attributes:

- `url`

Optional attributes:

- `push_events`
- `issues_events`
- `confidential_issues_events`
- `merge_requests_events`
- `tag_push_events`
- `note_events`

- `job_events`
- `pipeline_events`
- `wiki_page_events`
- `enable_ssl_verification`
- `token`

### Object update

Mandatory attributes for object update:

- `url`

Optional attributes for object update:

- `push_events`
- `issues_events`
- `confidential_issues_events`
- `merge_requests_events`
- `tag_push_events`
- `note_events`
- `job_events`
- `pipeline_events`
- `wiki_events`
- `enable_ssl_verification`
- `token`

**class** `gitlab.v4.objects.ProjectImport` (*manager, attrs*)  
 Bases: `gitlab.mixins.RefreshMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.ProjectImportManager` (*gl, parent=None*)  
 Bases: `gitlab.mixins.GetWithoutIdMixin`, `gitlab.base.RESTManager`

**class** `gitlab.v4.objects.ProjectIssue` (*manager, attrs*)  
 Bases: `gitlab.mixins.UserAgentDetailMixin`, `gitlab.mixins.SubscribableMixin`, `gitlab.mixins.TODOMixin`, `gitlab.mixins.TimeTrackingMixin`, `gitlab.mixins.ParticipantsMixin`, `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**closed\_by** (*\*\*kwargs*)  
 List merge requests that will close the issue when merged.

**Parameters** *\*\*kwargs* – Extra options to send to the server (e.g. `sudo`)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the merge requests could not be retrieved

**Returns** The list of merge requests.

**Return type** list

**move** (*\*\*kwargs*)  
 Move the issue to another project.

**Parameters**

- `to_project_id` (*int*) – ID of the target project
- `**kwargs` – Extra options to send to the server (e.g. `sudo`)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabUpdateError` – If the issue could not be moved

```
class gitlab.v4.objects.ProjectIssueAwardEmoji (manager, attrs)  
    Bases: gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject
```

```
class gitlab.v4.objects.ProjectIssueAwardEmojiManager (gl, parent=None)  
    Bases: gitlab.mixins.NoUpdateMixin, gitlab.base.RESTManager
```

**Object Creation**

Mandatory attributes:

- `name`

```
class gitlab.v4.objects.ProjectIssueDiscussion (manager, attrs)  
    Bases: gitlab.base.RESTObject
```

```
class gitlab.v4.objects.ProjectIssueDiscussionManager (gl, parent=None)  
    Bases: gitlab.mixins.RetrieveMixin, gitlab.mixins.CreateMixin, gitlab.base.RESTManager
```

**Object Creation**

Mandatory attributes:

- `body`

Optional attributes:

- `created_at`

```
class gitlab.v4.objects.ProjectIssueDiscussionNote (manager, attrs)  
    Bases: gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject
```

```
class gitlab.v4.objects.ProjectIssueDiscussionNoteManager (gl, parent=None)  
    Bases: gitlab.mixins.GetMixin, gitlab.mixins.CreateMixin, gitlab.mixins.UpdateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager
```

**Object Creation**

Mandatory attributes:

- `body`

Optional attributes:

- `created_at`

**Object update**

Mandatory attributes for object update:

- `body`

```
class gitlab.v4.objects.ProjectIssueLink (manager, attrs)  
    Bases: gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject
```

**class** `gitlab.v4.objects.ProjectIssueLinkManager` (*gl, parent=None*)  
 Bases: `gitlab.mixins.ListMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

### Object Creation

Mandatory attributes:

- `target_project_id`
- `target_issue_iid`

**create** (*\*\*kwargs*)  
 Create a new object.

#### Parameters

- **data** (*dict*) – parameters to send to the server to create the resource
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

**Returns** The source and target issues

**Return type** `RESTObject`, `RESTObject`

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

**class** `gitlab.v4.objects.ProjectIssueManager` (*gl, parent=None*)  
 Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

### Object listing filters

- `iids`
- `state`
- `labels`
- `milestone`
- `scope`
- `author_id`
- `assignee_id`
- `my_reaction_emoji`
- `order_by`
- `sort`
- `search`
- `created_after`
- `created_before`
- `updated_after`
- `updated_before`

### Object Creation

Mandatory attributes:

- title

Optional attributes:

- description
- confidential
- assignee\_id
- assignee\_idssmilestone\_id
- labels
- created\_at
- due\_date
- merge\_request\_to\_resolve\_discussions\_of
- discussion\_to\_resolve

### Object update

Optional attributes for object update:

- title
- description
- confidential
- assignee\_ids
- assignee\_id
- milestone\_id
- labels
- state\_event
- updated\_at
- due\_date
- discussion\_locked

**class** gitlab.v4.objects.**ProjectIssueNote** (*manager, attrs*)

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**class** gitlab.v4.objects.**ProjectIssueNoteAwardEmoji** (*manager, attrs*)

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**class** gitlab.v4.objects.**ProjectIssueNoteAwardEmojiManager** (*gl, parent=None*)

Bases: *gitlab.mixins.NoUpdateMixin, gitlab.base.RESTManager*

### Object Creation

Mandatory attributes:

- name

**class** gitlab.v4.objects.**ProjectIssueNoteManager** (*gl, parent=None*)

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

### Object Creation

Mandatory attributes:

- `body`

Optional attributes:

- `created_at`

### Object update

Mandatory attributes for object update:

- `body`

**class** `gitlab.v4.objects.ProjectJob` (*manager, attrs*)

Bases: `gitlab.base.RESTObject`, `gitlab.mixins.RefreshMixin`

**artifact** (*\*\*kwargs*)

Get a single artifact file from within the job's artifacts archive.

#### Parameters

- **path** (*str*) – Path of the artifact
- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk\_size* and each chunk is passed to *action* for treatment
- **action** (*callable*) – Callable responsible of dealing with chunk of data
- **chunk\_size** (*int*) – Size of each chunk
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the artifacts could not be retrieved

**Returns** The artifacts if *streamed* is False, None otherwise.

**Return type** `str`

**artifacts** (*\*\*kwargs*)

Get the job artifacts.

#### Parameters

- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk\_size* and each chunk is passed to *action* for treatment
- **action** (*callable*) – Callable responsible of dealing with chunk of data
- **chunk\_size** (*int*) – Size of each chunk
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the artifacts could not be retrieved

**Returns** The artifacts if *streamed* is False, None otherwise.

**Return type** `str`

**cancel** (*\*\*kwargs*)

Cancel the job.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabJobCancelError` – If the job could not be canceled

**erase** (\*\*kwargs)

Erase the job (remove job artifacts and trace).

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabJobEraseError` – If the job could not be erased

**keep\_artifacts** (\*\*kwargs)

Prevent artifacts from being deleted when expiration is set.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the request could not be performed

**play** (\*\*kwargs)

Trigger a job explicitly.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabJobPlayError` – If the job could not be triggered

**retry** (\*\*kwargs)

Retry the job.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabJobRetryError` – If the job could not be retried

**trace** (\*\*kwargs)

Get the job trace.

**Parameters**

- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk\_size* and each chunk is passed to *action* for treatment
- **action** (*callable*) – Callable responsible of dealing with chunk of data
- **chunk\_size** (*int*) – Size of each chunk
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the artifacts could not be retrieved



**Returns** The trace

**Return type** str

**class** gitlab.v4.objects.**ProjectJobManager** (*gl, parent=None*)

Bases: *gitlab.mixins.RetrieveMixin, gitlab.base.RESTManager*

**class** gitlab.v4.objects.**ProjectKey** (*manager, attrs*)

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**class** gitlab.v4.objects.**ProjectKeyManager** (*gl, parent=None*)

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

### Object Creation

Mandatory attributes:

- title
- key

Optional attributes:

- can\_push

### Object update

Optional attributes for object update:

- title
- can\_push

**enable** (*\*\*kwargs*)

Enable a deploy key for a project.

#### Parameters

- **key\_id** (*int*) – The ID of the key to enable
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabProjectDeployKeyError` – If the key could not be enabled

**class** gitlab.v4.objects.**ProjectLabel** (*manager, attrs*)

Bases: *gitlab.mixins.SubscribableMixin, gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**save** (*\*\*kwargs*)

Saves the changes made to the object to the server.

The object is updated to match what the server returns.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct.
- `GitlabUpdateError` – If the server cannot perform the request.

**class** gitlab.v4.objects.**ProjectLabelManager** (*gl, parent=None*)

Bases: *gitlab.mixins.ListMixin, gitlab.mixins.CreateMixin, gitlab.mixins.UpdateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager*

### Object Creation

Mandatory attributes:

- name
- color

Optional attributes:

- description
- priority

### Object update

Mandatory attributes for object update:

- name

Optional attributes for object update:

- new\_name
- color
- description
- priority

**delete** (*\*\*kwargs*)

Delete a Label on the server.

#### Parameters

- **name** – The name of the label
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabDeleteError` – If the server cannot perform the request

**class** gitlab.v4.objects.**ProjectManager** (*gl, parent=None*)

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

### Object listing filters

- search
- owned
- starred
- archived
- visibility
- order\_by
- sort
- simple

- membership
- statistics
- with\_issues\_enabled
- with\_merge\_requests\_enabled
- with\_custom\_attributes

### Object Creation

Optional attributes:

- name
- path
- namespace\_id
- description
- issues\_enabled
- merge\_requests\_enabled
- jobs\_enabled
- wiki\_enabled
- snippets\_enabled
- resolve\_outdated\_diff\_discussions
- container\_registry\_enabled
- shared\_runners\_enabled
- visibility
- import\_url
- public\_jobs
- only\_allow\_merge\_if\_pipeline\_succeeds
- only\_allow\_merge\_if\_all\_discussions\_are\_resolved
- merge\_method
- lfs\_enabled
- request\_access\_enabled
- tag\_list
- avatar
- printing\_merge\_request\_link\_enabled
- ci\_config\_path

### Object update

Optional attributes for object update:

- name
- path
- default\_branch

- `description`
- `issues_enabled`
- `merge_requests_enabled`
- `jobs_enabled`
- `wiki_enabled`
- `snippets_enabled`
- `resolve_outdated_diff_discussions`
- `container_registry_enabled`
- `shared_runners_enabled`
- `visibility`
- `import_url`
- `public_jobs`
- `only_allow_merge_if_pipeline_succeeds`
- `only_allow_merge_if_all_discussions_are_resolved`
- `merge_method`
- `lfs_enabled`
- `request_access_enabled`
- `tag_list`
- `avatar`
- `ci_config_path`

**import\_project** (*file*, *path*, *namespace=None*, *overwrite=False*, *override\_params=None*, *\*\*kwargs*)  
Import a project from an archive file.

#### Parameters

- **file** – Data or file object containing the project
- **path** (*str*) – Name and path for the new project
- **namespace** (*str*) – The ID or path of the namespace that the project will be imported to
- **overwrite** (*bool*) – If True overwrite an existing project with the same path
- **override\_params** (*dict*) – Set the specific settings for the project
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabListError` – If the server failed to perform the request

**Returns** A representation of the import status.

**Return type** `dict`

**class** gitlab.v4.objects.**ProjectMember** (*manager, attrs*)  
 Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**class** gitlab.v4.objects.**ProjectMemberManager** (*gl, parent=None*)  
 Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

### Object Creation

Mandatory attributes:

- `access_level`
- `user_id`

Optional attributes:

- `expires_at`

### Object update

Mandatory attributes for object update:

- `access_level`

Optional attributes for object update:

- `expires_at`

**class** gitlab.v4.objects.**ProjectMergeRequest** (*manager, attrs*)  
 Bases: *gitlab.mixins.SubscribableMixin, gitlab.mixins.TODOMixin, gitlab.mixins.TimeTrackingMixin, gitlab.mixins.ParticipantsMixin, gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**cancel\_merge\_when\_pipeline\_succeeds** (*\*\*kwargs*)

Cancel merge when the pipeline succeeds.

**Parameters** *\*\*kwargs* – Extra options to send to the server (e.g. `sudo`)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabMRonBuildSuccessError` – If the server could not handle the request

**changes** (*\*\*kwargs*)

List the merge request changes.

**Parameters** *\*\*kwargs* – Extra options to send to the server (e.g. `sudo`)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabListError` – If the list could not be retrieved

**Returns** List of changes

**Return type** *RESTObjectList*

**closes\_issues** (*\*\*kwargs*)

List issues that will close on merge.”

#### Parameters

- **all** (*bool*) – If True, return all the items, without pagination
- **per\_page** (*int*) – Number of items to retrieve per request

- **page** (*int*) – ID of the page to return (starts with page 1)
- **as\_list** (*bool*) – If set to False and no pagination option is defined, return a generator instead of a list
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabListError` – If the list could not be retrieved

**Returns** List of issues**Return type** *RESTObjectList***commits** (*\*\*kwargs*)

List the merge request commits.

**Parameters**

- **all** (*bool*) – If True, return all the items, without pagination
- **per\_page** (*int*) – Number of items to retrieve per request
- **page** (*int*) – ID of the page to return (starts with page 1)
- **as\_list** (*bool*) – If set to False and no pagination option is defined, return a generator instead of a list
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabListError` – If the list could not be retrieved

**Returns** The list of commits**Return type** *RESTObjectList***merge** (*\*\*kwargs*)

Accept the merge request.

**Parameters**

- **merge\_commit\_message** (*bool*) – Commit message
- **should\_remove\_source\_branch** (*bool*) – If True, removes the source branch
- **merge\_when\_pipeline\_succeeds** (*bool*) – Wait for the build to succeed, then merge
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabMRClosedError` – If the merge failed

**class** `gitlab.v4.objects.ProjectMergeRequestApproval` (*manager, attrs*)Bases: `gitlab.mixins.SaveMixin`, `gitlab.base.RESTObject`

```
class gitlab.v4.objects.ProjectMergeRequestApprovalManager (gl, parent=None)
    Bases: gitlab.mixins.GetWithoutIdMixin, gitlab.mixins.UpdateMixin, gitlab.
base.RESTManager
```

### Object update

Mandatory attributes for object update:

- `approvals_required`

```
set_approvers (**kwargs)
```

Change MR-level allowed approvers and approver groups.

#### Parameters

- **`approver_ids`** (*list*) – User IDs that can approve MRs
- **`approver_group_ids`** (*list*) – Group IDs whose members can approve MRs

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabUpdateError` – If the server failed to perform the request

```
class gitlab.v4.objects.ProjectMergeRequestAwardEmoji (manager, attrs)
    Bases: gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject
```

```
class gitlab.v4.objects.ProjectMergeRequestAwardEmojiManager (gl, parent=None)
    Bases: gitlab.mixins.NoUpdateMixin, gitlab.base.RESTManager
```

### Object Creation

Mandatory attributes:

- `name`

```
class gitlab.v4.objects.ProjectMergeRequestDiff (manager, attrs)
    Bases: gitlab.base.RESTObject
```

```
class gitlab.v4.objects.ProjectMergeRequestDiffManager (gl, parent=None)
    Bases: gitlab.mixins.RetrieveMixin, gitlab.base.RESTManager
```

```
class gitlab.v4.objects.ProjectMergeRequestDiscussion (manager, attrs)
    Bases: gitlab.mixins.SaveMixin, gitlab.base.RESTObject
```

```
class gitlab.v4.objects.ProjectMergeRequestDiscussionManager (gl, parent=None)
    Bases: gitlab.mixins.RetrieveMixin, gitlab.mixins.CreateMixin, gitlab.mixins.
UpdateMixin, gitlab.base.RESTManager
```

### Object Creation

Mandatory attributes:

- `body`

Optional attributes:

- `created_at`
- `position`

### Object update

Mandatory attributes for object update:

- `resolved`

```
class gitlab.v4.objects.ProjectMergeRequestDiscussionNote (manager, attrs)  
    Bases: gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject
```

```
class gitlab.v4.objects.ProjectMergeRequestDiscussionNoteManager (gl, parent=None)  
    Bases: gitlab.mixins.GetMixin, gitlab.mixins.CreateMixin, gitlab.mixins.UpdateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager
```

#### Object Creation

Mandatory attributes:

- `body`

Optional attributes:

- `created_at`

#### Object update

Mandatory attributes for object update:

- `body`

```
class gitlab.v4.objects.ProjectMergeRequestManager (gl, parent=None)
```

```
    Bases: gitlab.mixins.CRUDMixin, gitlab.base.RESTManager
```

#### Object listing filters

- `state`
- `order_by`
- `sort`
- `milestone`
- `view`
- `labels`
- `created_after`
- `created_before`
- `updated_after`
- `updated_before`
- `scope`
- `author_id`
- `assignee_id`
- `my_reaction_emoji`
- `source_branch`
- `target_branch`
- `search`

#### Object Creation

Mandatory attributes:

- `source_branch`



- target\_branch
- title

Optional attributes:

- assignee\_id
- description
- target\_project\_id
- labels
- milestone\_id
- remove\_source\_branch
- allow\_maintainer\_to\_push

### Object update

Optional attributes for object update:

- target\_branch
- assignee\_id
- title
- description
- state\_event
- labels
- milestone\_id
- remove\_source\_branch
- discussion\_locked
- allow\_maintainer\_to\_push

**class** gitlab.v4.objects.**ProjectMergeRequestNote** (*manager, attrs*)  
 Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**class** gitlab.v4.objects.**ProjectMergeRequestNoteAwardEmoji** (*manager, attrs*)  
 Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**class** gitlab.v4.objects.**ProjectMergeRequestNoteAwardEmojiManager** (*gl, parent=None*)  
 Bases: *gitlab.mixins.NoUpdateMixin, gitlab.base.RESTManager*

### Object Creation

Mandatory attributes:

- name

**class** gitlab.v4.objects.**ProjectMergeRequestNoteManager** (*gl, parent=None*)  
 Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

### Object Creation

Mandatory attributes:

- body

## Object update

Mandatory attributes for object update:

- `body`

**class** `gitlab.v4.objects.ProjectMilestone` (*manager, attrs*)

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**issues** (*\*\*kwargs*)

List issues related to this milestone.

### Parameters

- **all** (*bool*) – If True, return all the items, without pagination
- **per\_page** (*int*) – Number of items to retrieve per request
- **page** (*int*) – ID of the page to return (starts with page 1)
- **as\_list** (*bool*) – If set to False and no pagination option is defined, return a generator instead of a list
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabListError` – If the list could not be retrieved

**Returns** The list of issues

**Return type** `RESTObjectList`

**merge\_requests** (*\*\*kwargs*)

List the merge requests related to this milestone.

### Parameters

- **all** (*bool*) – If True, return all the items, without pagination
- **per\_page** (*int*) – Number of items to retrieve per request
- **page** (*int*) – ID of the page to return (starts with page 1)
- **as\_list** (*bool*) – If set to False and no pagination option is defined, return a generator instead of a list
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabListError` – If the list could not be retrieved

**Returns** The list of merge requests

**Return type** `RESTObjectList`

**class** `gitlab.v4.objects.ProjectMilestoneManager` (*gl, parent=None*)

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

## Object listing filters

- `iids`

- state
- search

### Object Creation

Mandatory attributes:

- title

Optional attributes:

- description
- due\_date
- start\_date
- state\_event

### Object update

Optional attributes for object update:

- title
- description
- due\_date
- start\_date
- state\_event

```
class gitlab.v4.objects.ProjectNote (manager, attrs)
```

```
    Bases: gitlab.base.RESTObject
```

```
class gitlab.v4.objects.ProjectNoteManager (gl, parent=None)
```

```
    Bases: gitlab.mixins.RetrieveMixin, gitlab.base.RESTManager
```

### Object Creation

Mandatory attributes:

- body

```
class gitlab.v4.objects.ProjectNotificationSettings (manager, attrs)
```

```
    Bases: gitlab.v4.objects.NotificationSettings
```

```
class gitlab.v4.objects.ProjectNotificationSettingsManager (gl, parent=None)
```

```
    Bases: gitlab.v4.objects.NotificationSettingsManager
```

### Object update

Optional attributes for object update:

- level
- notification\_email
- new\_note
- new\_issue
- reopen\_issue
- close\_issue
- reassign\_issue

- `new_merge_request`
- `reopen_merge_request`
- `close_merge_request`
- `reassign_merge_request`
- `merge_merge_request`

**class** `gitlab.v4.objects.ProjectPagesDomain` (*manager, attrs*)

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.ProjectPagesDomainManager` (*gl, parent=None*)

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

### Object Creation

Mandatory attributes:

- `domain`

Optional attributes:

- `certificate`
- `key`

### Object update

Optional attributes for object update:

- `certificate`
- `key`

**class** `gitlab.v4.objects.ProjectPipeline` (*manager, attrs*)

Bases: `gitlab.base.RESTObject`, `gitlab.mixins.RefreshMixin`

**cancel** (*\*\*kwargs*)

Cancel the job.

**Parameters** *\*\*kwargs* – Extra options to send to the server (e.g. `sudo`)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabPipelineCancelError` – If the request failed

**retry** (*\*\*kwargs*)

Retry the job.

**Parameters** *\*\*kwargs* – Extra options to send to the server (e.g. `sudo`)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabPipelineRetryError` – If the request failed

**class** `gitlab.v4.objects.ProjectPipelineJob` (*manager, attrs*)

Bases: `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.ProjectPipelineJobManager` (*gl, parent=None*)

Bases: `gitlab.mixins.ListMixin`, `gitlab.base.RESTManager`

### Object listing filters

- scope

**class** gitlab.v4.objects.**ProjectPipelineManager** (*gl, parent=None*)

Bases: *gitlab.mixins.RetrieveMixin, gitlab.mixins.CreateMixin, gitlab.base.RESTManager*

#### Object listing filters

- scope
- status
- ref
- sha
- yaml\_errors
- name
- username
- order\_by
- sort

#### Object Creation

Mandatory attributes:

- ref

**create** (*data, \*\*kwargs*)

Creates a new object.

##### Parameters

- **data** (*dict*) – Parameters to send to the server to create the resource
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

##### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

##### Returns

A new instance of the managed object class build with the data sent by the server

Return type *RESTObject*

**class** gitlab.v4.objects.**ProjectPipelineSchedule** (*manager, attrs*)

Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**take\_ownership** (*\*\*kwargs*)

Update the owner of a pipeline schedule.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

##### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabOwnershipError` – If the request failed

**class** gitlab.v4.objects.**ProjectPipelineScheduleManager** (*gl, parent=None*)  
Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

### Object Creation

Mandatory attributes:

- description
- ref
- cron

Optional attributes:

- cron\_timezone
- active

### Object update

Optional attributes for object update:

- description
- ref
- cron
- cron\_timezone
- active

**class** gitlab.v4.objects.**ProjectPipelineScheduleVariable** (*manager, attrs*)  
Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**class** gitlab.v4.objects.**ProjectPipelineScheduleVariableManager** (*gl, parent=None*)  
Bases: *gitlab.mixins.CreateMixin, gitlab.mixins.UpdateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager*

### Object Creation

Mandatory attributes:

- key
- value

### Object update

Mandatory attributes for object update:

- key
- value

**class** gitlab.v4.objects.**ProjectProtectedBranch** (*manager, attrs*)  
Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**class** gitlab.v4.objects.**ProjectProtectedBranchManager** (*gl, parent=None*)  
Bases: *gitlab.mixins.NoUpdateMixin, gitlab.base.RESTManager*

### Object Creation

Mandatory attributes:

- name

Optional attributes:

- `push_access_level`
- `merge_access_level`

**class** `gitlab.v4.objects.ProjectPushRules` (*manager, attrs*)

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.ProjectPushRulesManager` (*gl, parent=None*)

Bases: `gitlab.mixins.GetWithoutIdMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.UpdateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

### Object Creation

Optional attributes:

- `deny_delete_tag`
- `member_check`
- `prevent_secrets`
- `commit_message_regex`
- `branch_name_regex`
- `author_email_regex`
- `file_name_regex`
- `max_file_size`

### Object update

Optional attributes for object update:

- `deny_delete_tag`
- `member_check`
- `prevent_secrets`
- `commit_message_regex`
- `branch_name_regex`
- `author_email_regex`
- `file_name_regex`
- `max_file_size`

**class** `gitlab.v4.objects.ProjectRunner` (*manager, attrs*)

Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.ProjectRunnerManager` (*gl, parent=None*)

Bases: `gitlab.mixins.NoUpdateMixin`, `gitlab.base.RESTManager`

### Object Creation

Mandatory attributes:

- `runner_id`

**class** `gitlab.v4.objects.ProjectService` (*manager, attrs*)

Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.ProjectServiceManager` (*gl*, *parent=None*)  
Bases: `gitlab.mixins.GetMixin`, `gitlab.mixins.UpdateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

**available** (*\*\*kwargs*)  
List the services known by python-gitlab.  
**Returns** The list of service code names.  
**Return type** list (str)

**get** (*id*, *\*\*kwargs*)  
Retrieve a single object.  
**Parameters**

- **id** (*int* or *str*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Returns** The generated RESTObject.  
**Return type** object

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

**update** (*id=None*, *new\_data={}*, *\*\*kwargs*)  
Update an object on the server.  
**Parameters**

- **id** – ID of the object to update (can be None if not required)
- **new\_data** – the update data for the object
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Returns** The new object data (*not* a RESTObject)  
**Return type** dict

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabUpdateError` – If the server cannot perform the request

**class** `gitlab.v4.objects.ProjectSnippet` (*manager*, *attrs*)  
Bases: `gitlab.mixins.UserAgentDetailMixin`, `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**content** (*\*\*kwargs*)  
Return the content of a snippet.  
**Parameters**

- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk\_size* and each chunk is passed to *action* for treatment.
- **action** (*callable*) – Callable responsible of dealing with chunk of data



- **chunk\_size** (*int*) – Size of each chunk
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the content could not be retrieved

**Returns** The snippet content

**Return type** str

```
class gitlab.v4.objects.ProjectSnippetAwardEmoji (manager, attrs)
    Bases: gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject
```

```
class gitlab.v4.objects.ProjectSnippetAwardEmojiManager (gl, parent=None)
    Bases: gitlab.mixins.NoUpdateMixin, gitlab.base.RESTManager
```

**Object Creation**

Mandatory attributes:

- name

```
class gitlab.v4.objects.ProjectSnippetDiscussion (manager, attrs)
    Bases: gitlab.base.RESTObject
```

```
class gitlab.v4.objects.ProjectSnippetDiscussionManager (gl, parent=None)
    Bases: gitlab.mixins.RetrieveMixin, gitlab.mixins.CreateMixin, gitlab.base.RESTManager
```

**Object Creation**

Mandatory attributes:

- body

Optional attributes:

- created\_at

```
class gitlab.v4.objects.ProjectSnippetDiscussionNote (manager, attrs)
    Bases: gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject
```

```
class gitlab.v4.objects.ProjectSnippetDiscussionNoteManager (gl, parent=None)
    Bases: gitlab.mixins.GetMixin, gitlab.mixins.CreateMixin, gitlab.mixins.UpdateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager
```

**Object Creation**

Mandatory attributes:

- body

Optional attributes:

- created\_at

**Object update**

Mandatory attributes for object update:

- body

**class** `gitlab.v4.objects.ProjectSnippetManager` (*gl, parent=None*)  
Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

#### Object Creation

Mandatory attributes:

- `title`
- `file_name`
- `code`

Optional attributes:

- `lifetime`
- `visibility`

#### Object update

Optional attributes for object update:

- `title`
- `file_name`
- `code`
- `visibility`

**class** `gitlab.v4.objects.ProjectSnippetNote` (*manager, attrs*)  
Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.ProjectSnippetNoteAwardEmoji` (*manager, attrs*)  
Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.ProjectSnippetNoteAwardEmojiManager` (*gl, parent=None*)  
Bases: `gitlab.mixins.NoUpdateMixin`, `gitlab.base.RESTManager`

#### Object Creation

Mandatory attributes:

- `name`

**class** `gitlab.v4.objects.ProjectSnippetNoteManager` (*gl, parent=None*)  
Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

#### Object Creation

Mandatory attributes:

- `body`

#### Object update

Mandatory attributes for object update:

- `body`

**class** `gitlab.v4.objects.ProjectTag` (*manager, attrs*)  
Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**set\_release\_description** (*\*\*kwargs*)  
Set the release notes on the tag.

If the release doesn't exist yet, it will be created. If it already exists, its description will be updated.

**Parameters**

- **description** (*str*) – Description of the release.
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server fails to create the release
- `GitlabUpdateError` – If the server fails to update the release

```
class gitlab.v4.objects.ProjectTagManager (gl, parent=None)
    Bases: gitlab.mixins.NoUpdateMixin, gitlab.base.RESTManager
```

**Object Creation**

Mandatory attributes:

- `tag_name`
- `ref`

Optional attributes:

- `message`

```
class gitlab.v4.objects.ProjectTrigger (manager, attrs)
    Bases: gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject
```

```
take_ownership (**kwargs)
    Update the owner of a trigger.
```

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabOwnershipError` – If the request failed

```
class gitlab.v4.objects.ProjectTriggerManager (gl, parent=None)
    Bases: gitlab.mixins.CRUDMixin, gitlab.base.RESTManager
```

**Object Creation**

Mandatory attributes:

- `description`

**Object update**

Mandatory attributes for object update:

- `description`

```
class gitlab.v4.objects.ProjectUser (manager, attrs)
    Bases: gitlab.base.RESTObject
```

```
class gitlab.v4.objects.ProjectUserManager (gl, parent=None)
    Bases: gitlab.mixins.ListMixin, gitlab.base.RESTManager
```

**Object listing filters**

- `search`

**class** gitlab.v4.objects.**ProjectVariable** (*manager, attrs*)  
Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**class** gitlab.v4.objects.**ProjectVariableManager** (*gl, parent=None*)  
Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

#### Object Creation

Mandatory attributes:

- key
- value

#### Object update

Mandatory attributes for object update:

- key
- value

**class** gitlab.v4.objects.**ProjectWiki** (*manager, attrs*)  
Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**class** gitlab.v4.objects.**ProjectWikiManager** (*gl, parent=None*)  
Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

#### Object listing filters

- with\_content

#### Object Creation

Mandatory attributes:

- title
- content

Optional attributes:

- format

#### Object update

Optional attributes for object update:

- title
- content
- format

**class** gitlab.v4.objects.**Runner** (*manager, attrs*)  
Bases: *gitlab.mixins.SaveMixin, gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**class** gitlab.v4.objects.**RunnerJob** (*manager, attrs*)  
Bases: *gitlab.base.RESTObject*

**class** gitlab.v4.objects.**RunnerJobManager** (*gl, parent=None*)  
Bases: *gitlab.mixins.ListMixin, gitlab.base.RESTManager*

#### Object listing filters

- status

**class** gitlab.v4.objects.**RunnerManager** (*gl, parent=None*)

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

#### Object listing filters

- scope

#### Object Creation

Mandatory attributes:

- token

Optional attributes:

- description
- info
- active
- locked
- run\_untagged
- tag\_list
- maximum\_timeout

#### Object update

Optional attributes for object update:

- description
- active
- tag\_list
- run\_untagged
- locked
- access\_level
- maximum\_timeout

**all** (*\*\*kwargs*)

List all the runners.

#### Parameters

- **scope** (*str*) – The scope of runners to show, one of: specific, shared, active, paused, online
- **all** (*bool*) – If True, return all the items, without pagination
- **per\_page** (*int*) – Number of items to retrieve per request
- **page** (*int*) – ID of the page to return (starts with page 1)
- **as\_list** (*bool*) – If set to False and no pagination option is defined, return a generator instead of a list
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabListError` – If the server failed to perform the request

**Returns** a list of runners matching the scope.

**Return type** `list(Runner)`

**verify** (*\*\*kwargs*)

Validates authentication credentials for a registered Runner.

**Parameters**

- **token** (*str*) – The runner’s authentication token
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabVerifyError` – If the server failed to verify the token

**class** `gitlab.v4.objects.SidekiqManager` (*gl, parent=None*)

Bases: `gitlab.base.RESTManager`

Manager for the Sidekiq methods.

This manager doesn’t actually manage objects but provides helper function for the sidekiq metrics API.

**compound\_metrics** (*\*\*kwargs*)

Return all available metrics and statistics.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the information couldn’t be retrieved

**Returns** All available Sidekiq metrics and statistics

**Return type** `dict`

**job\_stats** (*\*\*kwargs*)

Return statistics about the jobs performed.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the information couldn’t be retrieved

**Returns** Statistics about the Sidekiq jobs performed

**Return type** `dict`

**process\_metrics** (*\*\*kwargs*)

Return the registred sidekiq workers.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the information couldn’t be retrieved

**Returns** Information about the register Sidekiq worker

**Return type** dict

**queue\_metrics** (\*\*kwargs)

Return the registred queues information.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the information couldn't be retrieved

**Returns** Information about the Sidekiq queues

**Return type** dict

**class** `gitlab.v4.objects.Snippet` (*manager, attrs*)

Bases: `gitlab.mixins.UserAgentDetailMixin`, `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**content** (\*\*kwargs)

Return the content of a snippet.

**Parameters**

- **streamed** (*bool*) – If True the data will be processed by chunks of *chunk\_size* and each chunk is passed to *action* for treatment.
- **action** (*callable*) – Callable responsible of dealing with chunk of data
- **chunk\_size** (*int*) – Size of each chunk
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the content could not be retrieved

**Returns** The snippet content

**Return type** str

**class** `gitlab.v4.objects.SnippetManager` (*gl, parent=None*)

Bases: `gitlab.mixins.CRUDMixin`, `gitlab.base.RESTManager`

**Object Creation**

Mandatory attributes:

- title
- file\_name
- content

Optional attributes:

- lifetime
- visibility

**Object update**

Optional attributes for object update:

- title
- file\_name
- content
- visibility

**public** (\*\*kwargs)

List all the public snippets.

**Parameters**

- **all** (*bool*) – If True the returned object will be a list
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises** `GitlabListError` – If the list could not be retrieved

**Returns** A generator for the snippets list

**Return type** `RESTObjectList`

**class** `gitlab.v4.objects.TODO` (*manager, attrs*)

Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**mark\_as\_done** (\*\*kwargs)

Mark the todo as done.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabTodoError` – If the server failed to perform the request

**class** `gitlab.v4.objects.TODOManager` (*gl, parent=None*)

Bases: `gitlab.mixins.ListMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

**Object listing filters**

- action
- author\_id
- project\_id
- state
- type

**mark\_all\_as\_done** (\*\*kwargs)

Mark all the todos as done.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabTodoError` – If the server failed to perform the request

**Returns** The number of todos made done

**Return type** `int`



**class** `gitlab.v4.objects.User` (*manager, attrs*)  
 Bases: `gitlab.mixins.SaveMixin`, `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**block** (*\*\*kwargs*)  
 Block the user.

**Parameters** *\*\*kwargs* – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabBlockError` – If the user could not be blocked

**Returns** Whether the user status has been changed

**Return type** `bool`

**unblock** (*\*\*kwargs*)  
 Unblock the user.

**Parameters** *\*\*kwargs* – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabUnblockError` – If the user could not be unblocked

**Returns** Whether the user status has been changed

**Return type** `bool`

**class** `gitlab.v4.objects.UserActivities` (*manager, attrs*)  
 Bases: `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.UserActivitiesManager` (*gl, parent=None*)  
 Bases: `gitlab.mixins.ListMixin`, `gitlab.base.RESTManager`

**class** `gitlab.v4.objects.UserCustomAttribute` (*manager, attrs*)  
 Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.UserCustomAttributeManager` (*gl, parent=None*)  
 Bases: `gitlab.mixins.RetrieveMixin`, `gitlab.mixins.SetMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

**class** `gitlab.v4.objects.UserEmail` (*manager, attrs*)  
 Bases: `gitlab.mixins.ObjectDeleteMixin`, `gitlab.base.RESTObject`

**class** `gitlab.v4.objects.UserEmailManager` (*gl, parent=None*)  
 Bases: `gitlab.mixins.RetrieveMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.DeleteMixin`, `gitlab.base.RESTManager`

**Object Creation**

Mandatory attributes:

- `email`

**class** `gitlab.v4.objects.UserEvent` (*manager, attrs*)  
 Bases: `gitlab.v4.objects.Event`

**class** `gitlab.v4.objects.UserEventManager` (*gl, parent=None*)  
 Bases: `gitlab.v4.objects.EventManager`

**Object listing filters**

- action
- target\_type
- before
- after
- sort

**class** gitlab.v4.objects.**UserGPGKey** (*manager, attrs*)

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**class** gitlab.v4.objects.**UserGPGKeyManager** (*gl, parent=None*)

Bases: *gitlab.mixins.RetrieveMixin, gitlab.mixins.CreateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager*

### Object Creation

Mandatory attributes:

- key

**class** gitlab.v4.objects.**UserImpersonationToken** (*manager, attrs*)

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**class** gitlab.v4.objects.**UserImpersonationTokenManager** (*gl, parent=None*)

Bases: *gitlab.mixins.NoUpdateMixin, gitlab.base.RESTManager*

### Object listing filters

- state

### Object Creation

Mandatory attributes:

- name
- scopes

Optional attributes:

- expires\_at

**class** gitlab.v4.objects.**UserKey** (*manager, attrs*)

Bases: *gitlab.mixins.ObjectDeleteMixin, gitlab.base.RESTObject*

**class** gitlab.v4.objects.**UserKeyManager** (*gl, parent=None*)

Bases: *gitlab.mixins.ListMixin, gitlab.mixins.CreateMixin, gitlab.mixins.DeleteMixin, gitlab.base.RESTManager*

### Object Creation

Mandatory attributes:

- title
- key

**class** gitlab.v4.objects.**UserManager** (*gl, parent=None*)

Bases: *gitlab.mixins.CRUDMixin, gitlab.base.RESTManager*

### Object listing filters

- active
- blocked

- username
- extern\_uid
- provider
- external
- search
- custom\_attributes

### **Object Creation**

Optional attributes:

- email
- username
- name
- password
- reset\_password
- skype
- linkedin
- twitter
- projects\_limit
- extern\_uid
- provider
- bio
- admin
- can\_create\_group
- website\_url
- skip\_confirmation
- external
- organization
- location
- avatar

### **Object update**

Mandatory attributes for object update:

- email
- username
- name

Optional attributes for object update:

- password
- skype

- linkedin
- twitter
- projects\_limit
- extern\_uid
- provider
- bio
- admin
- can\_create\_group
- website\_url
- skip\_confirmation
- external
- organization
- location
- avatar

**class** gitlab.v4.objects.**UserProject** (*manager, attrs*)

Bases: *gitlab.base.RESTObject*

**class** gitlab.v4.objects.**UserProjectManager** (*gl, parent=None*)

Bases: *gitlab.mixins.ListMixin, gitlab.mixins.CreateMixin, gitlab.base.RESTManager*

#### Object listing filters

- archived
- visibility
- order\_by
- sort
- search
- simple
- owned
- membership
- starred
- statistics
- with\_issues\_enabled
- with\_merge\_requests\_enabled

#### Object Creation

Mandatory attributes:

- name

Optional attributes:

- default\_branch

- `issues_enabled`
- `wall_enabled`
- `merge_requests_enabled`
- `wiki_enabled`
- `snippets_enabled`
- `public`
- `visibility`
- `description`
- `builds_enabled`
- `public_builds`
- `import_url`
- `only_allow_merge_if_build_succeeds`

**list** (*\*\*kwargs*)

Retrieve a list of objects.

#### Parameters

- **all** (*bool*) – If True, return all the items, without pagination
- **per\_page** (*int*) – Number of items to retrieve per request
- **page** (*int*) – ID of the page to return (starts with page 1)
- **as\_list** (*bool*) – If set to False and no pagination option is defined, return a generator instead of a list
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Returns** The list of objects, or a generator if *as\_list* is False

**Return type** list

#### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabListError` – If the server cannot perform the request

## Module contents

## 6.2 Submodules

## 6.3 gitlab.base module

**class** `gitlab.base.RESTManager` (*gl*, *parent=None*)

Bases: `object`

Base class for CRUD operations on objects.

Derivated class must define `_path` and `_obj_cls`.

`_path`: Base URL path on which requests will be sent (e.g. `‘/projects’`) `_obj_cls`: The class of objects that will be created

**parent\_attrs**

**path**

**class** `gitlab.base.RESTObject` (*manager, attrs*)

Bases: `object`

Represents an object built from server data.

It holds the attributes know from the server, and the updated attributes in another. This allows smart updates, if the object allows it.

You can redefine `_id_attr` in child classes to specify which attribute must be used as uniq ID. `None` means that the object can be updated without ID in the url.

**attributes**

**get\_id()**

Returns the id of the resource.

**class** `gitlab.base.RESTObjectList` (*manager, obj\_cls, \_list*)

Bases: `object`

Generator object representing a list of `RESTObject`’s.

This generator uses the Gitlab pagination system to fetch new data when required.

Note: you should not instanciate such objects, they are returned by calls to `RESTManager.list()`

**Parameters**

- **manager** – Manager to attach to the created objects
- **obj\_cls** – Type of objects to create from the json data
- **\_list** – A `GitlabList` object

**current\_page**

The current page number.

**next()**

**next\_page**

The next page number.

If `None`, the current page is the last.

**per\_page**

The number of items per page.

**prev\_page**

The next page number.

If `None`, the current page is the last.

**total**

The total number of items.

**total\_pages**

The total number of pages.

## 6.4 gitlab.cli module

```
gitlab.cli.cls_to_what(cls)
gitlab.cli.die(msg, e=None)
gitlab.cli.main()
gitlab.cli.register_custom_action(cls_names, mandatory=(), optional=())
gitlab.cli.what_to_cls(what)
```

## 6.5 gitlab.config module

```
exception gitlab.config.ConfigError
    Bases: exceptions.Exception

class gitlab.config.GitlabConfigParser(gitlab_id=None, config_files=None)
    Bases: object

exception gitlab.config.GitlabDataError
    Bases: gitlab.config.ConfigError

exception gitlab.config.GitlabIDError
    Bases: gitlab.config.ConfigError
```

## 6.6 gitlab.const module

## 6.7 gitlab.exceptions module

```
exception gitlab.exceptions.GitlabAttachFileError(error_message="", response_code=None, response_body=None)
    Bases: gitlab.exceptions.GitlabOperationError

exception gitlab.exceptions.GitlabAuthenticationError(error_message="", response_code=None, response_body=None)
    Bases: gitlab.exceptions.GitlabError

exception gitlab.exceptions.GitlabBlockError(error_message="", response_code=None, response_body=None)
    Bases: gitlab.exceptions.GitlabOperationError

exception gitlab.exceptions.GitlabBuildCancelError(error_message="", response_code=None, response_body=None)
    Bases: gitlab.exceptions.GitlabCancelError

exception gitlab.exceptions.GitlabBuildEraseError(error_message="", response_code=None, response_body=None)
    Bases: gitlab.exceptions.GitlabRetryError
```

**exception** `gitlab.exceptions.GitlabBuildPlayError` (`error_message=""`, `response_code=None`, `response_body=None`) re-  
re-  
Bases: `gitlab.exceptions.GitlabRetryError`

**exception** `gitlab.exceptions.GitlabBuildRetryError` (`error_message=""`, `response_code=None`, `response_body=None`) re-  
re-  
Bases: `gitlab.exceptions.GitlabRetryError`

**exception** `gitlab.exceptions.GitlabCancelError` (`error_message=""`, `response_code=None`, `response_body=None`)  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabCherryPickError` (`error_message=""`, `response_code=None`, `response_body=None`) re-  
re-  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabConnectionError` (`error_message=""`, `response_code=None`, `response_body=None`) re-  
re-  
Bases: `gitlab.exceptions.GitlabError`

**exception** `gitlab.exceptions.GitlabCreateError` (`error_message=""`, `response_code=None`, `response_body=None`)  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabDeleteError` (`error_message=""`, `response_code=None`, `response_body=None`)  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabError` (`error_message=""`, `response_code=None`, `response_body=None`)  
Bases: `exceptions.Exception`

**exception** `gitlab.exceptions.GitlabGetError` (`error_message=""`, `response_code=None`, `response_body=None`)  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabHousekeepingError` (`error_message=""`, `response_code=None`, `response_body=None`) re-  
re-  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabHttpError` (`error_message=""`, `response_code=None`, `response_body=None`)  
Bases: `gitlab.exceptions.GitlabError`

**exception** `gitlab.exceptions.GitlabJobCancelError` (`error_message=""`, `response_code=None`, `response_body=None`) re-  
re-  
Bases: `gitlab.exceptions.GitlabCancelError`

**exception** `gitlab.exceptions.GitlabJobEraseError` (`error_message=""`, `response_code=None`, `response_body=None`) re-  
re-  
Bases: `gitlab.exceptions.GitlabRetryError`

**exception** `gitlab.exceptions.GitlabJobPlayError` (`error_message=""`, `response_code=None`, `response_body=None`) re-  
re-  
Bases: `gitlab.exceptions.GitlabRetryError`



---

```

exception gitlab.exceptions.GitlabJobRetryError (error_message="",          re-
                                                sponse_code=None,          re-
                                                sponse_body=None)

    Bases: gitlab.exceptions.GitlabRetryError

exception gitlab.exceptions.GitlabLicenseError (error_message="",          re-
                                                sponse_code=None,          re-
                                                sponse_body=None)

    Bases: gitlab.exceptions.GitlabOperationError

exception gitlab.exceptions.GitlabListError (error_message="", response_code=None, re-
                                                sponse_body=None)

    Bases: gitlab.exceptions.GitlabOperationError

exception gitlab.exceptions.GitlabMRClosedError (error_message="",          re-
                                                sponse_code=None,          re-
                                                sponse_body=None)

    Bases: gitlab.exceptions.GitlabOperationError

exception gitlab.exceptions.GitlabMRForbiddenError (error_message="",          re-
                                                sponse_code=None,          re-
                                                sponse_body=None)

    Bases: gitlab.exceptions.GitlabOperationError

exception gitlab.exceptions.GitlabMROnBuildSuccessError (error_message="",          re-
                                                sponse_code=None,
                                                response_body=None)

    Bases: gitlab.exceptions.GitlabOperationError

exception gitlab.exceptions.GitlabMarkdownError (error_message="",          re-
                                                sponse_code=None,          re-
                                                sponse_body=None)

    Bases: gitlab.exceptions.GitlabOperationError

exception gitlab.exceptions.GitlabOperationError (error_message="",          re-
                                                sponse_code=None,          re-
                                                sponse_body=None)

    Bases: gitlab.exceptions.GitlabError

exception gitlab.exceptions.GitlabOwnershipError (error_message="",          re-
                                                sponse_code=None,          re-
                                                sponse_body=None)

    Bases: gitlab.exceptions.GitlabOperationError

exception gitlab.exceptions.GitlabParsingError (error_message="",          re-
                                                sponse_code=None,          re-
                                                sponse_body=None)

    Bases: gitlab.exceptions.GitlabError

exception gitlab.exceptions.GitlabPipelineCancelError (error_message="",          re-
                                                sponse_code=None,          re-
                                                sponse_body=None)

    Bases: gitlab.exceptions.GitlabCancelError

exception gitlab.exceptions.GitlabPipelineRetryError (error_message="",          re-
                                                sponse_code=None,          re-
                                                sponse_body=None)

    Bases: gitlab.exceptions.GitlabRetryError

exception gitlab.exceptions.GitlabProjectDeployKeyError (error_message="",          re-
                                                sponse_code=None,
                                                response_body=None)

    Bases: gitlab.exceptions.GitlabOperationError

```

**exception** `gitlab.exceptions.GitlabProtectError` (`error_message=""`, `response_code=None`, `response_body=None`) re-re  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabRenderError` (`error_message=""`, `response_code=None`, `response_body=None`)  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabRepairError` (`error_message=""`, `response_code=None`, `response_body=None`)  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabRetryError` (`error_message=""`, `response_code=None`, `response_body=None`)  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabSearchError` (`error_message=""`, `response_code=None`, `response_body=None`)  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabSetError` (`error_message=""`, `response_code=None`, `response_body=None`)  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabStopError` (`error_message=""`, `response_code=None`, `response_body=None`)  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabSubscribeError` (`error_message=""`, `response_code=None`, `response_body=None`) re-re  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabTimeTrackingError` (`error_message=""`, `response_code=None`, `response_body=None`) re-re  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabTodoError` (`error_message=""`, `response_code=None`, `response_body=None`)  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabTransferProjectError` (`error_message=""`, `response_code=None`, `response_body=None`) re-re  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabUnblockError` (`error_message=""`, `response_code=None`, `response_body=None`) re-re  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabUnsubscribeError` (`error_message=""`, `response_code=None`, `response_body=None`) re-re  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabUpdateError` (`error_message=""`, `response_code=None`, `response_body=None`)  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabUploadError` (*error\_message=""*, *response\_code=None*,  
*response\_body=None*)  
Bases: `gitlab.exceptions.GitlabOperationError`

**exception** `gitlab.exceptions.GitlabVerifyError` (*error\_message=""*, *response\_code=None*,  
*response\_body=None*)  
Bases: `gitlab.exceptions.GitlabOperationError`

`gitlab.exceptions.on_http_error` (*error*)  
Manage GitlabHttpError exceptions.

This decorator function can be used to catch GitlabHttpError exceptions raise specialized exceptions instead.

**Parameters** `error` (*Exception*) – The exception type to raise – must inherit from GitlabError

## 6.8 gitlab.mixins module

**class** `gitlab.mixins.AccessRequestMixin`  
Bases: `object`

**approve** (*\*\*kwargs*)  
Approve an access request.

### Parameters

- **access\_level** (*int*) – The access level for the user
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabUpdateError` – If the server fails to perform the request

**class** `gitlab.mixins.BadgeRenderMixin`  
Bases: `object`

**render** (*\*\*kwargs*)  
Preview `link_url` and `image_url` after interpolation.

### Parameters

- **link\_url** (*str*) – URL of the badge link
- **image\_url** (*str*) – URL of the badge image
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

### Raises

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabRenderError` – If the rendering failed

**Returns** The rendering properties

**Return type** `dict`

**class** `gitlab.mixins.CRUDMixin`  
Bases: `gitlab.mixins.GetMixin`, `gitlab.mixins.ListMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.UpdateMixin`, `gitlab.mixins.DeleteMixin`

**class** `gitlab.mixins.CreateMixin`  
Bases: `object`

**create** (\*\*kwargs)

Create a new object.

**Parameters**

- **data** (*dict*) – parameters to send to the server to create the resource
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Returns**

a new instance of the managed object class built with the data sent by the server

**Return type** *RESTObject*

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabCreateError` – If the server cannot perform the request

**get\_create\_attrs** ()

Return the required and optional arguments.

**Returns**

2 items: list of required arguments and list of optional arguments for creation (in that order)

**Return type** tuple

**class** `gitlab.mixins.DeleteMixin`

Bases: `object`

**delete** (\*\*kwargs)

Delete an object on the server.

**Parameters**

- **id** – ID of the object to delete
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabDeleteError` – If the server cannot perform the request

**class** `gitlab.mixins.GetMixin`

Bases: `object`

**get** (\*\*kwargs)

Retrieve a single object.

**Parameters**

- **id** (*int or str*) – ID of the object to retrieve
- **lazy** (*bool*) – If True, don't request the server, but create a shallow object giving access to the managers. This is useful if you want to avoid useless calls to the API.
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Returns** The generated `RESTObject`.

**Return type** `object`

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

**class** `gitlab.mixins.GetWithoutIdMixin`

Bases: `object`

**get** (*\*\*kwargs*)

Retrieve a single object.

**Parameters** *\*\*kwargs* – Extra options to send to the server (e.g. `sudo`)

**Returns** The generated `RESTObject`

**Return type** `object`

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

**class** `gitlab.mixins.ListMixin`

Bases: `object`

**list** (*\*\*kwargs*)

Retrieve a list of objects.

**Parameters**

- **all** (*bool*) – If True, return all the items, without pagination
- **per\_page** (*int*) – Number of items to retrieve per request
- **page** (*int*) – ID of the page to return (starts with page 1)
- **as\_list** (*bool*) – If set to False and no pagination option is defined, return a generator instead of a list
- *\*\*kwargs* – Extra options to send to the server (e.g. `sudo`)

**Returns** The list of objects, or a generator if *as\_list* is False

**Return type** `list`

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabListError` – If the server cannot perform the request

**class** `gitlab.mixins.NoUpdateMixin`

Bases: `gitlab.mixins.GetMixin`, `gitlab.mixins.ListMixin`, `gitlab.mixins.CreateMixin`, `gitlab.mixins.DeleteMixin`

**class** `gitlab.mixins.ObjectDeleteMixin`

Bases: `object`

Mixin for `RESTObject`'s that can be deleted.

**delete** (*\*\*kwargs*)

Delete the object from the server.

**Parameters** *\*\*kwargs* – Extra options to send to the server (e.g. `sudo`)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct

- `GitlabDeleteError` – If the server cannot perform the request

**class** `gitlab.mixins.ParticipantsMixin`

Bases: `object`

**participants** (*\*\*kwargs*)

List the participants.

**Parameters**

- **all** (*bool*) – If True, return all the items, without pagination
- **per\_page** (*int*) – Number of items to retrieve per request
- **page** (*int*) – ID of the page to return (starts with page 1)
- **as\_list** (*bool*) – If set to False and no pagination option is defined, return a generator instead of a list
- **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabListError` – If the list could not be retrieved

**Returns** The list of participants

**Return type** *RESTObjectList*

**class** `gitlab.mixins.RefreshMixin`

Bases: `object`

**refresh** (*\*\*kwargs*)

Refresh a single object from server.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

Returns `None` (updates the object)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

**class** `gitlab.mixins.RetrieveMixin`

Bases: *gitlab.mixins.ListMixin*, *gitlab.mixins.GetMixin*

**class** `gitlab.mixins.SaveMixin`

Bases: `object`

Mixin for `RESTObject`'s that can be updated.

**save** (*\*\*kwargs*)

Save the changes made to the object to the server.

The object is updated to match what the server returns.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. `sudo`)

**Raise:** `GitlabAuthenticationError`: If authentication is not correct `GitlabUpdateError`: If the server cannot perform the request

**class** `gitlab.mixins.SetMixin`

Bases: `object`

**set** (\*\*kwargs)

Create or update the object.

**Parameters**

- **key** (*str*) – The key of the object to create/update
- **value** (*str*) – The value to set for the object
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabSetError` – If an error occurred

**Returns** The created/updated attribute

**Return type** `obj`

**class** `gitlab.mixins.SubscribableMixin`

Bases: `object`

**subscribe** (\*\*kwargs)

Subscribe to the object notifications.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabSubscribeError` – If the subscription cannot be done

**unsubscribe** (\*\*kwargs)

Unsubscribe from the object notifications.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabUnsubscribeError` – If the unsubscription cannot be done

**class** `gitlab.mixins.TimeTrackingMixin`

Bases: `object`

**add\_spent\_time** (\*\*kwargs)

Add time spent working on the object.

**Parameters**

- **duration** (*str*) – Duration in human format (e.g. 3h30)
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabTimeTrackingError` – If the time tracking update cannot be done

**reset\_spent\_time** (\*\*kwargs)

Resets the time spent working on the object.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabTimeTrackingError` – If the time tracking update cannot be done

`reset_time_estimate (**kwargs)`

Resets estimated time for the object to 0 seconds.

**Parameters** `**kwargs` – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabTimeTrackingError` – If the time tracking update cannot be done

`time_estimate (**kwargs)`

Set an estimated time of work for the object.

**Parameters**

- `duration (str)` – Duration in human format (e.g. 3h30)
- `**kwargs` – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabTimeTrackingError` – If the time tracking update cannot be done

`time_stats (**kwargs)`

Get time stats for the object.

**Parameters** `**kwargs` – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabTimeTrackingError` – If the time tracking update cannot be done

`class gitlab.mixins.TODOMixin`

Bases: object

`todo (**kwargs)`

Create a todo associated to the object.

**Parameters** `**kwargs` – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabTodoError` – If the todo cannot be set

`class gitlab.mixins.UpdateMixin`

Bases: object

`get_update_attrs ()`

Return the required and optional arguments.

**Returns**

**2 items: list of required arguments and list of optional arguments** for update (in that order)

**Return type** tuple



**update** (\*\*kwargs)

Update an object on the server.

**Parameters**

- **id** – ID of the object to update (can be None if not required)
- **new\_data** – the update data for the object
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Returns** The new object data (*not* a RESTObject)

**Return type** dict

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabUpdateError` – If the server cannot perform the request

**class** gitlab.mixins.**UserAgentDetailMixin**

Bases: object

**user\_agent\_detail** (\*\*kwargs)

Get the user agent detail.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabGetError` – If the server cannot perform the request

## 6.9 gitlab.utils module

gitlab.utils.**response\_content** (*response, streamed, action, chunk\_size*)

## 6.10 Module contents

Wrapper for the GitLab API.

**class** gitlab.**Gitlab** (*url, private\_token=None, oauth\_token=None, email=None, password=None, ssl\_verify=True, http\_username=None, http\_password=None, timeout=None, api\_version='4', session=None, per\_page=None*)

Bases: object

Represents a GitLab server connection.

**Parameters**

- **url** (*str*) – The URL of the GitLab server.
- **private\_token** (*str*) – The user private token
- **oauth\_token** (*str*) – An oauth token
- **email** (*str*) – The user email or login.
- **password** (*str*) – The user password (associated with email).

- **ssl\_verify** (*bool/str*) – Whether SSL certificates should be validated. If the value is a string, it is the path to a CA file used for certificate validation.
- **timeout** (*float*) – Timeout to use for requests to the GitLab server.
- **http\_username** (*str*) – Username for HTTP authentication
- **http\_password** (*str*) – Password for HTTP authentication
- **api\_version** (*str*) – Gitlab API version to use (support for 4 only)

**api\_url**

The computed API base URL.

**api\_version**

The API version used (4 only).

**auth()**

Performs an authentication.

Uses either the private token, or the email/password pair.

The *user* attribute will hold a *gitlab.objects.CurrentUser* object on success.

**email = None**

The user email

**enable\_debug()****static from\_config** (*gitlab\_id=None, config\_files=None*)

Create a Gitlab connection from configuration files.

**Parameters**

- **gitlab\_id** (*str*) – ID of the configuration section.
- **list [str]** (*config\_files*) – List of paths to configuration files.

**Returns** A Gitlab connection.

**Return type** (*gitlab.Gitlab*)

**Raises** *gitlab.config.GitlabDataError* – If the configuration is not correct.

**get\_license** (*\*\*kwargs*)

Retrieve information about the current license.

**Parameters** **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- *GitlabAuthenticationError* – If authentication is not correct
- *GitlabGetError* – If the server cannot perform the request

**Returns** The current license information

**Return type** dict

**headers = None**

Headers that will be used in request to GitLab

**http\_delete** (*path, \*\*kwargs*)

Make a PUT request to the Gitlab server.

**Parameters**

- **path** (*str*) – Path or full URL to query ('/projects' or 'http://whatever/v4/api/projects')

- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Returns** The requests object.

**Raises** `GitlabHttpError` – When the return code is not 2xx

**http\_get** (*path*, *query\_data*={}, *streamed*=False, *\*\*kwargs*)

Make a GET request to the Gitlab server.

#### Parameters

- **path** (*str*) – Path or full URL to query (‘/projects’ or ‘<http://whatever/v4/api/projects>’)
- **query\_data** (*dict*) – Data to send as query parameters
- **streamed** (*bool*) – Whether the data should be streamed
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Returns** A requests result object is streamed is True or the content type is not json. The parsed json data otherwise.

#### Raises

- `GitlabHttpError` – When the return code is not 2xx
- `GitlabParsingError` – If the json data could not be parsed

**http\_list** (*path*, *query\_data*={}, *as\_list*=None, *\*\*kwargs*)

Make a GET request to the Gitlab server for list-oriented queries.

#### Parameters

- **path** (*str*) – Path or full URL to query (‘/projects’ or ‘<http://whatever/v4/api/projects>’)
- **query\_data** (*dict*) – Data to send as query parameters
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo, page, per\_page)

**Returns** A list of the objects returned by the server. If *as\_list* is False and no pagination-related arguments (*page*, *per\_page*, *all*) are defined then a `GitlabList` object (generator) is returned instead. This object will make API calls when needed to fetch the next items from the server.

**Return type** list

#### Raises

- `GitlabHttpError` – When the return code is not 2xx
- `GitlabParsingError` – If the json data could not be parsed

**http\_post** (*path*, *query\_data*={}, *post\_data*={}, *files*=None, *\*\*kwargs*)

Make a POST request to the Gitlab server.

#### Parameters

- **path** (*str*) – Path or full URL to query (‘/projects’ or ‘<http://whatever/v4/api/projects>’)
- **query\_data** (*dict*) – Data to send as query parameters
- **post\_data** (*dict*) – Data to send in the body (will be converted to json)
- **files** (*dict*) – The files to send to the server
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Returns** The parsed json returned by the server if json is return, else the raw content

#### Raises

- `GitlabHttpError` – When the return code is not 2xx
- `GitlabParsingError` – If the json data could not be parsed

**http\_put** (*path*, *query\_data*={}, *post\_data*={}, *files*=None, *\*\*kwargs*)

Make a PUT request to the Gitlab server.

**Parameters**

- **path** (*str*) – Path or full URL to query (‘/projects’ or ‘<http://whatever/v4/api/projects>’)
- **query\_data** (*dict*) – Data to send as query parameters
- **post\_data** (*dict*) – Data to send in the body (will be converted to json)
- **files** (*dict*) – The files to send to the server
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Returns** The parsed json returned by the server.

**Raises**

- `GitlabHttpError` – When the return code is not 2xx
- `GitlabParsingError` – If the json data could not be parsed

**http\_request** (*verb*, *path*, *query\_data*={}, *post\_data*=None, *streamed*=False, *files*=None, *\*\*kwargs*)

Make an HTTP request to the Gitlab server.

**Parameters**

- **verb** (*str*) – The HTTP method to call (‘get’, ‘post’, ‘put’, ‘delete’)
- **path** (*str*) – Path or full URL to query (‘/projects’ or ‘<http://whatever/v4/api/projects>’)
- **query\_data** (*dict*) – Data to send as query parameters
- **post\_data** (*dict*) – Data to send in the body (will be converted to json)
- **streamed** (*bool*) – Whether the data should be streamed
- **files** (*dict*) – The files to send to the server
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Returns** A requests result object.

**Raises** `GitlabHttpError` – When the return code is not 2xx

**lint** (*\*\*kwargs*)

Validate a gitlab CI configuration.

**Parameters**

- **content** (*txt*) – The .gitlab-ci.yml content
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabVerifyError` – If the validation could not be done

**Returns**

(**True**, []) if the file is valid, (**False**, **errors(list)**) otherwise

**Return type** tuple

**markdown** (\*\*kwargs)

Render an arbitrary Markdown document.

**Parameters**

- **text** (*str*) – The markdown text to render
- **gfm** (*bool*) – Render text using GitLab Flavored Markdown. Default is False
- **project** (*str*) – Full path of a project used a context when *gfm* is True
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabMarkdownError` – If the server cannot perform the request

**Returns** The HTML rendering of the markdown text.

**Return type** `str`

**password = None**

The user password (associated with email)

**search** (\*\*kwargs)

Search GitLab resources matching the provided string.

**Parameters**

- **scope** (*str*) – Scope of the search
- **search** (*str*) – Search string
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabSearchError` – If the server failed to perform the request

**Returns** A list of dicts describing the resources found.

**Return type** `GitlabList`

**session = None**

Create a session object for requests

**set\_license** (\*\*kwargs)

Add a new license.

**Parameters**

- **license** (*str*) – The license string
- **\*\*kwargs** – Extra options to send to the server (e.g. sudo)

**Raises**

- `GitlabAuthenticationError` – If authentication is not correct
- `GitlabPostError` – If the server cannot perform the request

**Returns** The new license information

**Return type** `dict`

**ssl\_verify = None**

Whether SSL certificates should be validated

**timeout = None**

Timeout to use for requests to gitlab server

**url**

The user-provided server URL.

**version ()**

Returns the version and revision of the gitlab server.

Note that self.version and self.revision will be set on the gitlab object.

**Returns**

**The server version and server revision.** ('unknown', 'unknown') if the server doesn't perform as expected.

**Return type** tuple (str, str)

**class** gitlab.**GitlabList** (*gl, url, query\_data, get\_next=True, \*\*kwargs*)

Bases: object

Generator representing a list of remote objects.

The object handles the links returned by a query to the API, and will call the API again when needed.

**current\_page**

The current page number.

**next ()**

**next\_page**

The next page number.

If None, the current page is the last.

**per\_page**

The number of items per page.

**prev\_page**

The next page number.

If None, the current page is the last.

**total**

The total number of items.

**total\_pages**

The total number of pages.

This page describes important changes between python-gitlab releases.

### 7.1 Changes from 1.4 to 1.5

- APIv3 support has been removed. Use the 1.4 release/branch if you need v3 support.
- GitLab EE features are now supported: Geo nodes, issue links, LDAP groups, project/group boards, project mirror pulling, project push rules, EE license configuration, epics.
- The `GetFromListMixin` class has been removed. The `get()` method is not available anymore for the following managers: - `UserKeyManager` - `DeployKeyManager` - `GroupAccessRequestManager` - `GroupIssueManager` - `GroupProjectManager` - `GroupSubgroupManager` - `IssueManager` - `ProjectCommitStatusManager` - `ProjectEnvironmentManager` - `ProjectLabelManager` - `ProjectPipelineJobManager` - `ProjectAccessRequestManager` - `TodoManager`
- `ProjectPipelineJob` do not heritate from `ProjectJob` anymore and thus can only be listed.

### 7.2 Changes from 1.3 to 1.4

- 1.4 is the last release supporting the v3 API, and the related code will be removed in the 1.5 version.

If you are using a Gitlab server version that does not support the v4 API you can:

- upgrade the server (recommended)
- make sure to use version 1.4 of python-gitlab (`pip install python-gitlab==1.4`)

See also the [Switching to GitLab API v4 documentation](#).

- python-gitlab now handles the server rate limiting feature. It will pause for the required time when reaching the limit ([documentation](#))

- The `GetFromListMixin.get()` method is deprecated and will be removed in the next python-gitlab version. The goal of this mixin/method is to provide a way to get an object by looping through a list for GitLab objects that don't support the GET method. The method is broken and conflicts with the GET method now supported by some GitLab objects.

You can implement your own method with something like:

```
def get_from_list(self, id):
    for obj in self.list(as_list=False):
        if obj.get_id() == id:
            return obj
```

- The `GroupMemberManager`, `NamespaceManager` and `ProjectBoardManager` managers now use the GET API from GitLab instead of the `GetFromListMixin.get()` method.

## 7.3 Changes from 1.2 to 1.3

- `gitlab.Gitlab` objects can be used as context managers in a `with` block.

## 7.4 Changes from 1.1 to 1.2

- python-gitlab now respects the `*_proxy`, `REQUESTS_CA_BUNDLE` and `CURL_CA_BUNDLE` environment variables (#352)
- The following deprecated methods and objects have been removed:
  - `gitlab.v3.object.Key` and `KeyManager` objects: use `DeployKey` and `DeployKeyManager` instead
  - `gitlab.v3.objects.Project.archive_` and `unarchive_` methods
  - `gitlab.Gitlab.credentials_auth`, `token_auth`, `set_url`, `set_token` and `set_credentials` methods. Once a Gitlab object has been created its URL and authentication information cannot be updated: create a new Gitlab object if you need to use new information
- The `todo()` method raises a `GitlabTodoError` exception on error

## 7.5 Changes from 1.0.2 to 1.1

- The `ProjectUser` class doesn't inherit from `User` anymore, and the `GroupProject` class doesn't inherit from `Project` anymore. The Gitlab API doesn't provide the same set of features for these objects, so python-gitlab objects shouldn't try to workaround that.

You can create `User` or `Project` objects from `ProjectUser` and `GroupProject` objects using the `id` attribute:

```
for gr_project in group.projects.list():
    # lazy object creation avoids a Gitlab API request
    project = gl.projects.get(gr_project.id, lazy=True)
    project.default_branch = 'develop'
    project.save()
```



## 7.6 Changes from 0.21 to 1.0.0

1.0.0 brings a stable python-gitlab API for the v4 Gitlab API. v3 is still used by default.

v4 is mostly compatible with the v3, but some important changes have been introduced. Make sure to read [Switching to GitLab API v4](#).

The development focus will be v4 from now on. v3 has been deprecated by GitLab and will disappear from python-gitlab at some point.

## 7.7 Changes from 0.20 to 0.21

- Initial support for the v4 API (experimental)

The support for v4 is stable enough to be tested, but some features might be broken. Please report issues to <https://github.com/python-gitlab/python-gitlab/issues/>

Be aware that the python-gitlab API for v4 objects might change in the next releases.

**Warning:** Consider defining explicitly which API version you want to use in the configuration files or in your `gitlab.Gitlab` instances. The default will change from v3 to v4 soon.

- Several methods have been deprecated in the `gitlab.Gitlab` class:
  - `credentials_auth()` is deprecated and will be removed. Call `auth()`.
  - `token_auth()` is deprecated and will be removed. Call `auth()`.
  - `set_url()` is deprecated, create a new `Gitlab` instance if you need an updated URL.
  - `set_token()` is deprecated, use the `private_token` argument of the `Gitlab` constructor.
  - `set_credentials()` is deprecated, use the `email` and `password` arguments of the `Gitlab` constructor.
- The service listing method (`ProjectServiceManager.list()`) now returns a python list instead of a JSON string.

## 7.8 Changes from 0.19 to 0.20

- The `projects` attribute of `Group` objects is not a list of `Project` objects anymore. It is a `Manager` object giving access to `GroupProject` objects. To get the list of projects use:

```
group.projects.list()
```

Documentation: [http://python-gitlab.readthedocs.io/en/stable/gl\\_objects/groups.html#examples](http://python-gitlab.readthedocs.io/en/stable/gl_objects/groups.html#examples)

Related issue: <https://github.com/python-gitlab/python-gitlab/issues/209>

- The `Key` objects are deprecated in favor of the new `DeployKey` objects. They are exactly the same but the name makes more sense.

Documentation: [http://python-gitlab.readthedocs.io/en/stable/gl\\_objects/deploy\\_keys.html](http://python-gitlab.readthedocs.io/en/stable/gl_objects/deploy_keys.html)

Related issue: <https://github.com/python-gitlab/python-gitlab/issues/212>



### 8.1 Version 1.5.1 - 2018-06-23

- Fix the ProjectPipelineJob base class (regression)

### 8.2 Version 1.5.0 - 2018-06-22

- Drop API v3 support
- Drop GetFromListMixin
- Update the sphinx extension for v4 objects
- Add support for user avatar upload
- Add support for project import/export
- Add support for the search API
- Add a global per\_page config option
- Add support for the discussions API
- Add support for merged branches deletion
- Add support for Project badges
- Implement user\_agent\_detail for snippets
- Implement commit.refs()
- Add commit.merge\_requests() support
- Deployment: add list filters
- Deploy key: add missing attributes
- Add support for environment stop()

- Add feature flags deletion support
- Update some group attributes
- Issues: add missing attributes and methods
- Fix the participants() decorator
- Add support for group boards
- Implement the markdown rendering API
- Update MR attributes
- Add pipeline listing filters
- Add missing project attributes
- Implement runner jobs listing
- Runners can be created (registered)
- Implement runner token validation
- Update the settings attributes
- Add support for the gitlab CI lint API
- Add support for group badges
- Fix the IssueManager path to avoid redirections
- time\_stats(): use an existing attribute if available
- Make ProjectCommitStatus.create work with CLI
- Tests: default to python 3
- ProjectPipelineJob was defined twice
- Silence logs/warnings in unittests
- Add support for MR approval configuration (EE)
- Change post\_data default value to None
- Add geo nodes API support (EE)
- Add support for issue links (EE)
- Add support for LDAP groups (EE)
- Add support for board creation/deletion (EE)
- Add support for Project.pull\_mirror (EE)
- Add project push rules configuration (EE)
- Add support for the EE license API
- Add support for the LDAP groups API (EE)
- Add support for epics API (EE)
- Fix the non-verbose output of ProjectCommitComment

## 8.3 Version 1.4.0 - 2018-05-19

- Require requests $\geq$ 2.4.2
- ProjectKeys can be updated
- Add support for unsharing projects (v3/v4)
- [cli] fix listing for json and yaml output
- Fix typos in documentation
- Introduce RefreshMixin
- [docs] Fix the time tracking examples
- [docs] Commits: add an example of binary file creation
- [cli] Allow to read args from files
- Add support for recursive tree listing
- [cli] Restore the `-help` option behavior
- Add basic unit tests for v4 CLI
- [cli] Fix listing of strings
- Support downloading a single artifact file
- Update docs copyright years
- Implement attribute types to handle special cases
- [docs] fix GitLab reference for notes
- Expose additional properties for Gitlab objects
- Fix the impersonation token deletion example
- feat: obey the rate limit
- Fix URL encoding on branch methods
- [docs] add a code example for listing commits of a MR
- [docs] update `service.available()` example for API v4
- [tests] fix functional tests for python3
- api-usage: bit more detail for listing with *all*
- More efficient `.get()` for group members
- Add docs for the *files* arg in `http_*`
- Deprecate GetFromListMixin

## 8.4 Version 1.3.0 - 2018-02-18

- Add support for pipeline schedules and schedule variables
- Clarify information about supported python version
- Add manager for jobs within a pipeline
- Fix wrong tag example

- Update the groups documentation
- Add support for MR participants API
- Add support for getting list of user projects
- Add Gitlab and User events support
- Make trigger\_pipeline return the pipeline
- Config: support api\_version in the global section
- Gitlab can be used as context manager
- Default to API v4
- Add a simplified example for streamed artifacts
- Add documentation about labels update

## 8.5 Version 1.2.0 - 2018-01-01

- Add mattermost service support
- Add users custom attributes support
- [doc] Fix project.triggers.create example with v4 API
- OAuth token support
- Remove deprecated objects/methods
- Rework authentication args handling
- Add support for oauth and anonymous auth in config/CLI
- Add support for impersonation tokens API
- Add support for user activities
- Update user docs with gitlab URLs
- [docs] Bad arguments in projects file documentation
- Add support for user\_agent\_detail (issues)
- Add a SetMixin
- Add support for project housekeeping
- Expected HTTP response for subscribe is 201
- Update pagination docs for ProjectCommit
- Add doc to get issue from iid
- Make todo() raise GitlabTodoError on error
- Add support for award emojis
- Update project services docs for v4
- Avoid sending empty update data to issue.save
- [docstrings] Explicitly document pagination arguments
- [docs] Add a note about password auth being removed from GitLab

- Submanagers: allow having undefined parameters
- ProjectFile.create(): don't modify the input data
- Update testing tools for /session removal
- Update groups tests
- Allow per\_page to be used with generators
- Add groups listing attributes
- Add support for subgroups listing
- Add supported python versions in setup.py
- Add support for pagesdomains
- Add support for features flags
- Add support for project and group custom variables
- Add support for user/group/project filter by custom attribute
- Respect content of REQUESTS\_CA\_BUNDLE and \*\_proxy envvars

## 8.6 Version 1.1.0 - 2017-11-03

- Fix trigger variables in v4 API
- Make the delete() method handle / in ids
- [docs] update the file upload samples
- Tags release description: support / in tag names
- [docs] improve the labels usage documentation
- Add support for listing project users
- ProjectFileManager.create: handle / in file paths
- Change ProjectUser and GroupProject base class
- [docs] document *get\_create\_attrs* in the API tutorial
- Document the Gitlab session parameter
- ProjectFileManager: custom update() method
- Project: add support for printing\_merge\_request\_link\_enabled attr
- Update the ssl\_verify docstring
- Add support for group milestones
- Add support for GPG keys
- Add support for wiki pages
- Update the repository\_blob documentation
- Fix the CLI for objects without ID (API v4)
- Add a contributed Dockerfile
- Pagination generators: expose more information

- Module's base objects serialization
- [doc] Add sample code for client-side certificates

## 8.7 Version 1.0.2 - 2017-09-29

- [docs] remove example usage of submanagers
- Properly handle the labels attribute in ProjectMergeRequest
- ProjectFile: handle / in path for delete() and save()

## 8.8 Version 1.0.1 - 2017-09-21

- Tags can be retrieved by ID
- Add the server response in GitlabError exceptions
- Add support for project file upload
- Minor typo fix in "Switching to v4" documentation
- Fix password authentication for v4
- Fix the labels attrs on MR and issues
- Exceptions: use a proper error message
- Fix http\_get method in get artifacts and job trace
- CommitStatus: *sha* is parent attribute
- Fix a couple listing calls to allow proper pagination
- Add missing doc file

## 8.9 Version 1.0.0 - 2017-09-08

- Support for API v4. See <http://python-gitlab.readthedocs.io/en/master/switching-to-v4.html>
- Support SSL verification via internal CA bundle
- Docs: Add link to gitlab docs on obtaining a token
- Added dependency injection support for Session
- Fixed repository\_compare examples
- Fix changelog and release notes inclusion in sdist
- Missing expires\_at in GroupMembers update
- Add lower-level methods for Gitlab()



## 8.10 Version 0.21.2 - 2017-06-11

- Install doc: use sudo for system commands
- [v4] Make MR work properly
- Remove extra\_attrs argument from \_raw\_list
- [v4] Make project issues work properly
- Fix urlencode() usage (python 2/3) (#268)
- Fixed spelling mistake (#269)
- Add new event types to ProjectHook

## 8.11 Version 0.21.1 - 2017-05-25

- Fix the manager name for jobs in the Project class
- Fix the docs

## 8.12 Version 0.21 - 2017-05-24

- Add time\_stats to ProjectMergeRequest
- Update User options for creation and update (#246)
- Add milestone.merge\_requests() API
- Fix docs typo (s/correspding/corresponding/)
- Support milestone start date (#251)
- Add support for priority attribute in labels (#256)
- Add support for nested groups (#257)
- Make GroupProjectManager a subclass of ProjectManager (#255)
- Available services: return a list instead of JSON (#258)
- MR: add support for time tracking features (#248)
- Fixed repository\_tree and repository\_blob path encoding (#265)
- Add 'search' attribute to projects.list()
- Initial gitlab API v4 support
- Reorganise the code to handle v3 and v4 objects
- Allow 202 as delete return code
- Deprecate parameter related methods in gitlab.Gitlab

## 8.13 Version 0.20 - 2017-03-25

- Add time tracking support (#222)
- Improve changelog (#229, #230)
- Make sure that manager objects are never overwritten (#209)
- Include chanlog and release notes in docs
- Add DeployKey{,Manager} classes (#212)
- Add support for merge request notes deletion (#227)
- Properly handle extra args when listing with all=True (#233)
- Implement pipeline creation API (#237)
- Fix spent\_time methods
- Add 'delete source branch' option when creating MR (#241)
- Provide API wrapper for cherry picking commits (#236)
- Stop listing if recursion limit is hit (#234)

## 8.14 Version 0.19 - 2017-02-21

- Update project.archive() docs
- Support the scope attribute in runners.list()
- Add support for project runners
- Add support for commit creation
- Fix install doc
- Add builds-email and pipelines-email services
- Deploy keys: rework enable/disable
- Document the dynamic aspect of objects
- Add pipeline\_events to ProjectHook attrs
- Add due\_date attribute to ProjectIssue
- Handle settings.domain\_whitelist, partly
- {Project,Group}Member: support expires\_at attribute

## 8.15 Version 0.18 - 2016-12-27

- Fix JIRA service editing for GitLab 8.14+
- Add jira\_issue\_transition\_id to the JIRA service optional fields
- Added support for Snippets (new API in Gitlab 8.15)
- [docs] update pagination section
- [docs] artifacts example: open file in wb mode

- [CLI] ignore empty arguments
- [CLI] Fix wrong use of arguments
- [docs] Add doc for snippets
- Fix duplicated data in API docs
- Update known attributes for projects
- sudo: always use strings

## 8.16 Version 0.17 - 2016-12-02

- README: add badges for pypi and RTD
- Fix ProjectBuild.play (raised error on success)
- Pass kwargs to the object factory
- Add .tox to ignore to respect default tox settings
- Convert response list to single data source for iid requests
- Add support for boards API
- Add support for Gitlab.version()
- Add support for broadcast messages API
- Add support for the notification settings API
- Don't overwrite attributes returned by the server
- Fix bug when retrieving changes for merge request
- Feature: enable / disable the deploy key in a project
- Docs: add a note for python 3.5 for file content update
- ProjectHook: support the token attribute
- Rework the API documentation
- Fix docstring for http\_{username,password}
- Build managers on demand on GitlabObject's
- API docs: add managers doc in GitlabObject's
- Sphinx ext: factorize the build methods
- Implement \_\_repr\_\_ for gitlab objects
- Add a 'report a bug' link on doc
- Remove deprecated methods
- Implement merge requests diff support
- Make the manager objects creation more dynamic
- Add support for templates API
- Add attr 'created\_at' to ProjectIssueNote
- Add attr 'updated\_at' to ProjectIssue

- CLI: add support for project all `--all`
- Add support for triggering a new build
- Rework requests arguments (support latest requests release)
- Fix `should_remove_source_branch`

## 8.17 Version 0.16 - 2016-10-16

- Add the ability to fork to a specific namespace
- JIRA service - add `api_url` to optional attributes
- Fix bug: Missing comma concatenates array values
- docs: branch protection notes
- Create a project in a group
- Add `only_allow_merge_if_build_succeeds` option to project objects
- Add support for `--all` in CLI
- Fix examples for file modification
- Use the plural `merge_requests` URL everywhere
- Rework travis and tox setup
- Workaround gitlab setup failure in tests
- Add `ProjectBuild.erase()`
- Implement `ProjectBuild.play()`

## 8.18 Version 0.15.1 - 2016-10-16

- docs: improve the pagination section
- Fix and test pagination
- `'path'` is an existing gitlab attr, don't use it as method argument

## 8.19 Version 0.15 - 2016-08-28

- Add a basic HTTP debug method
- Run more tests in travis
- Fix fork creation documentation
- Add more API examples in docs
- Update the `ApplicationSettings` attributes
- Implement the todo API
- Add sidekiq metrics support
- Move the constants at the gitlab root level

- Remove methods marked as deprecated 7 months ago
- Refactor the Gitlab class
- Remove `_get_list_or_object()` and its tests
- Fix `canGet` attribute (typo)
- Remove unused `ProjectTagReleaseManager` class
- Add support for project services API
- Add support for project pipelines
- Add support for access requests
- Add support for project deployments

## 8.20 Version 0.14 - 2016-08-07

- Remove `'next_url'` from kwargs before passing it to the cls constructor.
- List projects under group
- Add support for subscribe and unsubscribe in issues
- Project issue: doc and CLI for (un)subscribe
- Added support for HTTP basic authentication
- Add support for build artifacts and trace
- `-title` is a required argument for `ProjectMilestone`
- Commit status: add optional context url
- Commit status: optional get attrs
- Add support for commit comments
- Issues: add optional listing parameters
- Issues: add missing optional listing parameters
- Project issue: proper update attributes
- Add support for project-issue move
- Update `ProjectLabel` attributes
- Milestone: optional listing attrs
- Add support for namespaces
- Add support for label (un)subscribe
- MR: add (un)subscribe support
- Add `note_events` to project hooks attributes
- Add code examples for a bunch of resources
- Implement user emails support
- Project: add `VISIBILITY_*` constants
- Fix the `Project.archive` call

- Implement archive/unarchive for a projet
- Update ProjectSnippet attributes
- Fix ProjectMember update
- Implement sharing project with a group
- Implement CLI for project archive/unarchive/share
- Implement runners global API
- Gitlab: add managers for build-related resources
- Implement ProjectBuild.keep\_artifacts
- Allow to stream the downloads when appropriate
- Groups can be updated
- Replace Snippet.Content() with a new content() method
- CLI: refactor \_die()
- Improve commit statuses and comments
- Add support from listing group issues
- Added a new project attribute to enable the container registry.
- Add a contributing section in README
- Add support for global deploy key listing
- Add support for project environments
- MR: get list of changes and commits
- Fix the listing of some resources
- MR: fix updates
- Handle empty messages from server in exceptions
- MR (un)subscribe: don't fail if state doesn't change
- MR merge(): update the object

## 8.21 Version 0.13 - 2016-05-16

- Add support for MergeRequest validation
- MR: add support for cancel\_merge\_when\_build\_succeeds
- MR: add support for closes\_issues
- Add “external” parameter for users
- Add deletion support for issues and MR
- Add missing group creation parameters
- Add a Session instance for all HTTP requests
- Enable updates on ProjectIssueNotes
- Add support for Project raw\_blob

- Implement project compare
- Implement project contributors
- Drop the next\_url attribute when listing
- Remove unnecessary canUpdate property from ProjectIssuesNote
- Add new optional attributes for projects
- Enable deprecation warnings for gitlab only
- Rework merge requests update
- Rework the Gitlab.delete method
- ProjectFile: file\_path is required for deletion
- Rename some methods to better match the API URLs
- Deprecate the file\_\* methods in favor of the files manager
- Implement star/unstar for projects
- Implement list/get licenses
- Manage optional parameters for list() and get()

## 8.22 Version 0.12.2 - 2016-03-19

- Add new *ProjectHook* attributes
- Add support for user block/unblock
- Fix GitlabObject creation in \_custom\_list
- Add support for more CLI subcommands
- Add some unit tests for CLI
- Add a coverage tox env
- Define GitlabObject.as\_dict() to dump object as a dict
- Define GitlabObject.\_\_eq\_\_() and \_\_ne\_\_() equivalence methods
- Define UserManager.search() to search for users
- Define UserManager.get\_by\_username() to get a user by username
- Implement “user search” CLI
- Improve the doc for UserManager
- CLI: implement user get-by-username
- Re-implement \_custom\_list in the Gitlab class
- Fix the ‘invalid syntax’ error on Python 3.2
- Gitlab.update(): use the proper attributes if defined

## 8.23 Version 0.12.1 - 2016-02-03

- Fix a broken upload to pypi

## 8.24 Version 0.12 - 2016-02-03

- Improve documentation
- Improve unit tests
- Improve test scripts
- Skip BaseManager attributes when encoding to JSON
- Fix the json() method for python 3
- Add Travis CI support
- Add a decode method for ProjectFile
- Make connection exceptions more explicit
- Fix ProjectLabel get and delete
- Implement ProjectMilestone.issues()
- ProjectTag supports deletion
- Implement setting release info on a tag
- Implement project triggers support
- Implement project variables support
- Add support for application settings
- Fix the 'password' requirement for User creation
- Add sudo support
- Fix project update
- Fix Project.tree()
- Add support for project builds

## 8.25 Version 0.11.1 - 2016-01-17

- Fix discovery of parents object attrs for managers
- Support setting commit status
- Support deletion without getting the object first
- Improve the documentation



## 8.26 Version 0.11 - 2016-01-09

- functional\_tests.sh: support python 2 and 3
- Add a get method for GitlabObject
- CLI: Add the -g short option for -gitlab
- Provide a create method for GitlabObject's
- Rename the \_created attribute \_from\_api
- More unit tests
- CLI: fix error when arguments are missing (python 3)
- Remove deprecated methods
- Implement managers to get access to resources
- Documentation improvements
- Add fork project support
- Deprecate the "old" Gitlab methods
- Add support for groups search

## 8.27 Version 0.10 - 2015-12-29

- Implement pagination for list() (#63)
- Fix url when fetching a single MergeRequest
- Add support to update MergeRequestNotes
- API: Provide a Gitlab.from\_config method
- setup.py: require requests>=1 (#69)
- Fix deletion of object not using 'id' as ID (#68)
- Fix GET/POST for project files
- Make 'confirm' an optional attribute for user creation
- Python 3 compatibility fixes
- Add support for group members update (#73)

## 8.28 Version 0.9.2 - 2015-07-11

- CLI: fix the update and delete subcommands (#62)

## 8.29 Version 0.9.1 - 2015-05-15

- Fix the setup.py script

## 8.30 Version 0.9 - 2015-05-15

- Implement argparse library for parsing argument on CLI
- Provide unit tests and (a few) functional tests
- Provide PEP8 tests
- Use tox to run the tests
- CLI: provide a `--config-file` option
- Turn the gitlab module into a proper package
- Allow projects to be updated
- Use more pythonic names for some methods
- **Deprecate some Gitlab object methods:**
  - `raw*` methods should never have been exposed; replace them with `_raw_*` methods
  - `setCredentials` and `setToken` are replaced with `set_credentials` and `set_token`
- Sphinx: don't hardcode the version in `conf.py`

## 8.31 Version 0.8 - 2014-10-26

- Better python 2.6 and python 3 support
- Timeout support in HTTP requests
- `Gitlab.get()` raised `GitlabListError` instead of `GitlabGetError`
- Support api-objects which don't have id in api response
- Add `ProjectLabel` and `ProjectFile` classes
- Moved url attributes to separate list
- Added list for delete attributes

## 8.32 Version 0.7 - 2014-08-21

- Fix license classifier in `setup.py`
- Fix encoding error when printing to redirected output
- Fix encoding error when updating with redirected output
- Add support for `UserKey` listing and deletion
- Add support for branches creation and deletion
- Support `state_event` in `ProjectMilestone` (#30)
- Support `namespace/name` for project id (#28)
- Fix handling of boolean values (#22)

### 8.33 Version 0.6 - 2014-01-16

- IDs can be unicode (#15)
- ProjectMember: constructor should not create a User object
- Add support for extra parameters when listing all projects (#12)
- Projects listing: explicitly define arguments for pagination

### 8.34 Version 0.5 - 2013-12-26

- Add SSH key for user
- Fix comments
- Add support for project events
- Support creation of projects for users
- Project: add methods for create/update/delete files
- Support projects listing: search, all, owned
- System hooks can't be updated
- Project.archive(): download tarball of the project
- Define new optional attributes for user creation
- Provide constants for access permissions in groups

### 8.35 Version 0.4 - 2013-09-26

- Fix strings encoding (Closes #6)
- Allow to get a project commit (GitLab 6.1)
- ProjectMergeRequest: fix Note() method
- Gitlab 6.1 methods: diff, blob (commit), tree, blob (project)
- Add support for Gitlab 6.1 group members

### 8.36 Version 0.3 - 2013-08-27

- Use PRIVATE-TOKEN header for passing the auth token
- provide an AUTHORS file
- cli: support ssl\_verify config option
- Add ssl\_verify option to Gitlab object. Defaults to True
- Correct url for merge requests API.

### 8.37 Version 0.2 - 2013-08-08

- provide a pip requirements.txt
- drop some debug statements

### 8.38 Version 0.1 - 2013-07-08

- Initial release

## CHAPTER 9

---

### Indices and tables

---

- `genindex`
- `modindex`
- `search`



## g

gitlab, 163  
gitlab.base, 151  
gitlab.cli, 153  
gitlab.config, 153  
gitlab.const, 153  
gitlab.exceptions, 153  
gitlab.mixins, 157  
gitlab.utils, 163  
gitlab.v4, 151  
gitlab.v4.objects, 83





**A**

AccessRequestMixin (class in gitlab.mixins), 157  
add\_ldap\_group\_link() (gitlab.v4.objects.Group method), 90  
add\_spent\_time() (gitlab.mixins.TimeTrackingMixin method), 161  
all() (gitlab.v4.objects.RunnerManager method), 143  
api\_url (gitlab.Gitlab attribute), 164  
api\_version (gitlab.Gitlab attribute), 164  
ApplicationSettings (class in gitlab.v4.objects), 83  
ApplicationSettingsManager (class in gitlab.v4.objects), 83  
approve() (gitlab.mixins.AccessRequestMixin method), 157  
archive() (gitlab.v4.objects.Project method), 100  
artifact() (gitlab.v4.objects.ProjectJob method), 121  
artifacts() (gitlab.v4.objects.ProjectJob method), 121  
attributes (gitlab.base.RESTObject attribute), 152  
auth() (gitlab.Gitlab method), 164  
available() (gitlab.v4.objects.ProjectServiceManager method), 138

**B**

BadgeRenderMixin (class in gitlab.mixins), 157  
block() (gitlab.v4.objects.User method), 147  
BroadcastMessage (class in gitlab.v4.objects), 86  
BroadcastMessageManager (class in gitlab.v4.objects), 86

**C**

cancel() (gitlab.v4.objects.ProjectJob method), 121  
cancel() (gitlab.v4.objects.ProjectPipeline method), 134  
cancel\_merge\_when\_pipeline\_succeeds() (gitlab.v4.objects.ProjectMergeRequest method), 127  
changes() (gitlab.v4.objects.ProjectMergeRequest method), 127  
cherry\_pick() (gitlab.v4.objects.ProjectCommit method), 108

closed\_by() (gitlab.v4.objects.ProjectIssue method), 117  
closes\_issues() (gitlab.v4.objects.ProjectMergeRequest method), 127  
cls\_to\_what() (in module gitlab.cli), 153  
commits() (gitlab.v4.objects.ProjectMergeRequest method), 128  
compound\_metrics() (gitlab.v4.objects.SidekiqManager method), 144  
ConfigError, 153  
content() (gitlab.v4.objects.ProjectSnippet method), 138  
content() (gitlab.v4.objects.Snippet method), 145  
create() (gitlab.mixins.CreateMixin method), 157  
create() (gitlab.v4.objects.GroupEpicIssueManager method), 92  
create() (gitlab.v4.objects.ProjectCommitStatusManager method), 111  
create() (gitlab.v4.objects.ProjectFileManager method), 114  
create() (gitlab.v4.objects.ProjectIssueLinkManager method), 119  
create() (gitlab.v4.objects.ProjectPipelineManager method), 135  
create\_fork\_relation() (gitlab.v4.objects.Project method), 101  
CreateMixin (class in gitlab.mixins), 157  
CRUDMixin (class in gitlab.mixins), 157  
current\_failures() (gitlab.v4.objects.GeoNodeManager method), 89  
current\_page (gitlab.base.RESTObjectList attribute), 152  
current\_page (gitlab.GitlabList attribute), 168  
CurrentUser (class in gitlab.v4.objects), 87  
CurrentUserEmail (class in gitlab.v4.objects), 87  
CurrentUserEmailManager (class in gitlab.v4.objects), 87  
CurrentUserGPGKey (class in gitlab.v4.objects), 87  
CurrentUserGPGKeyManager (class in gitlab.v4.objects), 87  
CurrentUserKey (class in gitlab.v4.objects), 87  
CurrentUserKeyManager (class in gitlab.v4.objects), 87  
CurrentUserManager (class in gitlab.v4.objects), 87

## D

`decode()` (gitlab.v4.objects.ProjectFile method), 113  
`delete()` (gitlab.mixins.DeleteMixin method), 158  
`delete()` (gitlab.mixins.ObjectDeleteMixin method), 159  
`delete()` (gitlab.v4.objects.ProjectFile method), 113  
`delete()` (gitlab.v4.objects.ProjectFileManager method), 114  
`delete()` (gitlab.v4.objects.ProjectLabelManager method), 124  
`delete_fork_relation()` (gitlab.v4.objects.Project method), 101  
`delete_ldap_group_link()` (gitlab.v4.objects.Group method), 90  
`delete_merged_branches()` (gitlab.v4.objects.Project method), 101  
`DeleteMixin` (class in gitlab.mixins), 158  
`DeployKey` (class in gitlab.v4.objects), 87  
`DeployKeyManager` (class in gitlab.v4.objects), 87  
`die()` (in module gitlab.cli), 153  
`diff()` (gitlab.v4.objects.ProjectCommit method), 108  
`Dockerfile` (class in gitlab.v4.objects), 87  
`DockerfileManager` (class in gitlab.v4.objects), 87  
`download()` (gitlab.v4.objects.ProjectExport method), 112

## E

`email` (gitlab.Gitlab attribute), 164  
`enable()` (gitlab.v4.objects.ProjectKeyManager method), 123  
`enable_debug()` (gitlab.Gitlab method), 164  
`erase()` (gitlab.v4.objects.ProjectJob method), 122  
`Event` (class in gitlab.v4.objects), 87  
`EventManager` (class in gitlab.v4.objects), 88

## F

`Feature` (class in gitlab.v4.objects), 88  
`FeatureManager` (class in gitlab.v4.objects), 88  
`from_config()` (gitlab.Gitlab static method), 164

## G

`GeoNode` (class in gitlab.v4.objects), 88  
`GeoNodeManager` (class in gitlab.v4.objects), 89  
`get()` (gitlab.mixins.GetMixin method), 158  
`get()` (gitlab.mixins.GetWithoutIdMixin method), 159  
`get()` (gitlab.v4.objects.ProjectFileManager method), 115  
`get()` (gitlab.v4.objects.ProjectServiceManager method), 138  
`get_create_attrs()` (gitlab.mixins.CreateMixin method), 158  
`get_id()` (gitlab.base.RESTObject method), 152  
`get_license()` (gitlab.Gitlab method), 164  
`get_update_attrs()` (gitlab.mixins.UpdateMixin method), 162  
`GetMixin` (class in gitlab.mixins), 158

`GetWithoutIdMixin` (class in gitlab.mixins), 159  
`Gitignore` (class in gitlab.v4.objects), 89  
`GitignoreManager` (class in gitlab.v4.objects), 89  
`Gitlab` (class in gitlab), 163  
`gitlab` (module), 163  
`gitlab.base` (module), 151  
`gitlab.cli` (module), 153  
`gitlab.config` (module), 153  
`gitlab.const` (module), 153  
`gitlab.exceptions` (module), 153  
`gitlab.mixins` (module), 157  
`gitlab.utils` (module), 163  
`gitlab.v4` (module), 151  
`gitlab.v4.objects` (module), 83  
`GitlabAttachFileError`, 153  
`GitlabAuthenticationError`, 153  
`GitlabBlockError`, 153  
`GitlabBuildCancelError`, 153  
`GitlabBuildEraseError`, 153  
`GitlabBuildPlayError`, 153  
`GitlabBuildRetryError`, 154  
`GitlabCancelError`, 154  
`GitlabCherryPickError`, 154  
`Gitlabciyaml` (class in gitlab.v4.objects), 89  
`GitlabciyamlManager` (class in gitlab.v4.objects), 89  
`GitlabConfigParser` (class in gitlab.config), 153  
`GitlabConnectionError`, 154  
`GitlabCreateError`, 154  
`GitlabDataError`, 153  
`GitlabDeleteError`, 154  
`GitlabError`, 154  
`GitlabGetError`, 154  
`GitlabHousekeepingError`, 154  
`GitlabHttpError`, 154  
`GitlabIDError`, 153  
`GitlabJobCancelError`, 154  
`GitlabJobEraseError`, 154  
`GitlabJobPlayError`, 154  
`GitlabJobRetryError`, 154  
`GitlabLicenseError`, 155  
`GitlabList` (class in gitlab), 168  
`GitlabListError`, 155  
`GitlabMarkdownError`, 155  
`GitlabMRClosedError`, 155  
`GitlabMRForbiddenError`, 155  
`GitlabMROnBuildSuccessError`, 155  
`GitlabOperationError`, 155  
`GitlabOwnershipError`, 155  
`GitlabParsingError`, 155  
`GitlabPipelineCancelError`, 155  
`GitlabPipelineRetryError`, 155  
`GitlabProjectDeployKeyError`, 155  
`GitlabProtectError`, 156  
`GitlabRenderError`, 156

- GitlabRepairError, 156
  - GitlabRetryError, 156
  - GitlabSearchError, 156
  - GitlabSetError, 156
  - GitlabStopError, 156
  - GitlabSubscribeError, 156
  - GitlabTimeTrackingError, 156
  - GitlabTodoError, 156
  - GitlabTransferProjectError, 156
  - GitlabUnblockError, 156
  - GitlabUnsubscribeError, 156
  - GitlabUpdateError, 156
  - GitlabUploadError, 156
  - GitlabVerifyError, 157
  - Group (class in gitlab.v4.objects), 89
  - GroupAccessRequest (class in gitlab.v4.objects), 91
  - GroupAccessRequestManager (class in gitlab.v4.objects), 91
  - GroupBadge (class in gitlab.v4.objects), 91
  - GroupBadgeManager (class in gitlab.v4.objects), 91
  - GroupBoard (class in gitlab.v4.objects), 91
  - GroupBoardList (class in gitlab.v4.objects), 91
  - GroupBoardListManager (class in gitlab.v4.objects), 91
  - GroupBoardManager (class in gitlab.v4.objects), 92
  - GroupCustomAttribute (class in gitlab.v4.objects), 92
  - GroupCustomAttributeManager (class in gitlab.v4.objects), 92
  - GroupEpic (class in gitlab.v4.objects), 92
  - GroupEpicIssue (class in gitlab.v4.objects), 92
  - GroupEpicIssueManager (class in gitlab.v4.objects), 92
  - GroupEpicManager (class in gitlab.v4.objects), 93
  - GroupIssue (class in gitlab.v4.objects), 93
  - GroupIssueManager (class in gitlab.v4.objects), 93
  - GroupManager (class in gitlab.v4.objects), 94
  - GroupMember (class in gitlab.v4.objects), 95
  - GroupMemberManager (class in gitlab.v4.objects), 95
  - GroupMergeRequest (class in gitlab.v4.objects), 95
  - GroupMergeRequestManager (class in gitlab.v4.objects), 95
  - GroupMilestone (class in gitlab.v4.objects), 95
  - GroupMilestoneManager (class in gitlab.v4.objects), 96
  - GroupNotificationSettings (class in gitlab.v4.objects), 96
  - GroupNotificationSettingsManager (class in gitlab.v4.objects), 97
  - GroupProject (class in gitlab.v4.objects), 97
  - GroupProjectManager (class in gitlab.v4.objects), 97
  - GroupSubgroup (class in gitlab.v4.objects), 97
  - GroupSubgroupManager (class in gitlab.v4.objects), 97
  - GroupVariable (class in gitlab.v4.objects), 98
  - GroupVariableManager (class in gitlab.v4.objects), 98
- ## H
- headers (gitlab.Gitlab attribute), 164
  - Hook (class in gitlab.v4.objects), 98
  - HookManager (class in gitlab.v4.objects), 98
  - housekeeping() (gitlab.v4.objects.Project method), 101
  - http\_delete() (gitlab.Gitlab method), 164
  - http\_get() (gitlab.Gitlab method), 165
  - http\_list() (gitlab.Gitlab method), 165
  - http\_post() (gitlab.Gitlab method), 165
  - http\_put() (gitlab.Gitlab method), 166
  - http\_request() (gitlab.Gitlab method), 166
- ## I
- import\_project() (gitlab.v4.objects.ProjectManager method), 126
  - Issue (class in gitlab.v4.objects), 98
  - IssueManager (class in gitlab.v4.objects), 98
  - issues() (gitlab.v4.objects.GroupMilestone method), 95
  - issues() (gitlab.v4.objects.ProjectMilestone method), 132
- ## J
- job\_stats() (gitlab.v4.objects.SidekiqManager method), 144
- ## K
- keep\_artifacts() (gitlab.v4.objects.ProjectJob method), 122
- ## L
- languages() (gitlab.v4.objects.Project method), 101
  - ldap\_sync() (gitlab.v4.objects.Group method), 90
  - LDAPGroup (class in gitlab.v4.objects), 99
  - LDAPGroupManager (class in gitlab.v4.objects), 99
  - License (class in gitlab.v4.objects), 99
  - LicenseManager (class in gitlab.v4.objects), 99
  - lint() (gitlab.Gitlab method), 166
  - list() (gitlab.mixins.ListMixin method), 159
  - list() (gitlab.v4.objects.LDAPGroupManager method), 99
  - list() (gitlab.v4.objects.UserProjectManager method), 151
  - ListMixin (class in gitlab.mixins), 159
- ## M
- main() (in module gitlab.cli), 153
  - mark\_all\_as\_done() (gitlab.v4.objects.TODOManager method), 146
  - mark\_as\_done() (gitlab.v4.objects.TODO method), 146
  - markdown() (gitlab.Gitlab method), 166
  - merge() (gitlab.v4.objects.ProjectMergeRequest method), 128
  - merge\_requests() (gitlab.v4.objects.GroupMilestone method), 96
  - merge\_requests() (gitlab.v4.objects.ProjectCommit method), 109
  - merge\_requests() (gitlab.v4.objects.ProjectMilestone method), 132
  - mirror\_pull() (gitlab.v4.objects.Project method), 101

move() (gitlab.v4.objects.ProjectIssue method), 117

## N

Namespace (class in gitlab.v4.objects), 100

NamespaceManager (class in gitlab.v4.objects), 100

next() (gitlab.base.RESTObjectList method), 152

next() (gitlab.GitlabList method), 168

next\_page (gitlab.base.RESTObjectList attribute), 152

next\_page (gitlab.GitlabList attribute), 168

NotificationSettings (class in gitlab.v4.objects), 100

NotificationSettingsManager (class in gitlab.v4.objects), 100

NoUpdateMixin (class in gitlab.mixins), 159

## O

ObjectDeleteMixin (class in gitlab.mixins), 159

on\_http\_error() (in module gitlab.exceptions), 157

## P

PagesDomain (class in gitlab.v4.objects), 100

PagesDomainManager (class in gitlab.v4.objects), 100

parent\_attrs (gitlab.base.RESTManager attribute), 152

participants() (gitlab.mixins.ParticipantsMixin method), 160

ParticipantsMixin (class in gitlab.mixins), 160

password (gitlab.Gitlab attribute), 167

path (gitlab.base.RESTManager attribute), 152

per\_page (gitlab.base.RESTObjectList attribute), 152

per\_page (gitlab.GitlabList attribute), 168

play() (gitlab.v4.objects.ProjectJob method), 122

prev\_page (gitlab.base.RESTObjectList attribute), 152

prev\_page (gitlab.GitlabList attribute), 168

process\_metrics() (gitlab.v4.objects.SidekiqManager method), 144

Project (class in gitlab.v4.objects), 100

ProjectAccessRequest (class in gitlab.v4.objects), 106

ProjectAccessRequestManager (class in gitlab.v4.objects), 106

ProjectApproval (class in gitlab.v4.objects), 106

ProjectApprovalManager (class in gitlab.v4.objects), 106

ProjectBadge (class in gitlab.v4.objects), 107

ProjectBadgeManager (class in gitlab.v4.objects), 107

ProjectBoard (class in gitlab.v4.objects), 107

ProjectBoardList (class in gitlab.v4.objects), 107

ProjectBoardListManager (class in gitlab.v4.objects), 107

ProjectBoardManager (class in gitlab.v4.objects), 107

ProjectBranch (class in gitlab.v4.objects), 108

ProjectBranchManager (class in gitlab.v4.objects), 108

ProjectCommit (class in gitlab.v4.objects), 108

ProjectCommitComment (class in gitlab.v4.objects), 109

ProjectCommitCommentManager (class in gitlab.v4.objects), 109

ProjectCommitDiscussion (class in gitlab.v4.objects), 109

ProjectCommitDiscussionManager (class in gitlab.v4.objects), 109

ProjectCommitDiscussionNote (class in gitlab.v4.objects), 110

ProjectCommitDiscussionNoteManager (class in gitlab.v4.objects), 110

ProjectCommitManager (class in gitlab.v4.objects), 110

ProjectCommitStatus (class in gitlab.v4.objects), 110

ProjectCommitStatusManager (class in gitlab.v4.objects), 110

ProjectCustomAttribute (class in gitlab.v4.objects), 111

ProjectCustomAttributeManager (class in gitlab.v4.objects), 111

ProjectDeployment (class in gitlab.v4.objects), 111

ProjectDeploymentManager (class in gitlab.v4.objects), 111

ProjectEnvironment (class in gitlab.v4.objects), 111

ProjectEnvironmentManager (class in gitlab.v4.objects), 112

ProjectEvent (class in gitlab.v4.objects), 112

ProjectEventManager (class in gitlab.v4.objects), 112

ProjectExport (class in gitlab.v4.objects), 112

ProjectExportManager (class in gitlab.v4.objects), 113

ProjectFile (class in gitlab.v4.objects), 113

ProjectFileManager (class in gitlab.v4.objects), 113

ProjectFork (class in gitlab.v4.objects), 116

ProjectForkManager (class in gitlab.v4.objects), 116

ProjectHook (class in gitlab.v4.objects), 116

ProjectHookManager (class in gitlab.v4.objects), 116

ProjectImport (class in gitlab.v4.objects), 117

ProjectImportManager (class in gitlab.v4.objects), 117

ProjectIssue (class in gitlab.v4.objects), 117

ProjectIssueAwardEmoji (class in gitlab.v4.objects), 118

ProjectIssueAwardEmojiManager (class in gitlab.v4.objects), 118

ProjectIssueDiscussion (class in gitlab.v4.objects), 118

ProjectIssueDiscussionManager (class in gitlab.v4.objects), 118

ProjectIssueDiscussionNote (class in gitlab.v4.objects), 118

ProjectIssueDiscussionNoteManager (class in gitlab.v4.objects), 118

ProjectIssueLink (class in gitlab.v4.objects), 118

ProjectIssueLinkManager (class in gitlab.v4.objects), 118

ProjectIssueManager (class in gitlab.v4.objects), 119

ProjectIssueNote (class in gitlab.v4.objects), 120

ProjectIssueNoteAwardEmoji (class in gitlab.v4.objects), 120

ProjectIssueNoteAwardEmojiManager (class in gitlab.v4.objects), 120

ProjectIssueNoteManager (class in gitlab.v4.objects), 120

ProjectJob (class in gitlab.v4.objects), 121

ProjectJobManager (class in gitlab.v4.objects), 123

ProjectKey (class in gitlab.v4.objects), 123

- ProjectKeyManager (class in gitlab.v4.objects), 123
- ProjectLabel (class in gitlab.v4.objects), 123
- ProjectLabelManager (class in gitlab.v4.objects), 123
- ProjectManager (class in gitlab.v4.objects), 124
- ProjectMember (class in gitlab.v4.objects), 126
- ProjectMemberManager (class in gitlab.v4.objects), 127
- ProjectMergeRequest (class in gitlab.v4.objects), 127
- ProjectMergeRequestApproval (class in gitlab.v4.objects), 128
- ProjectMergeRequestApprovalManager (class in gitlab.v4.objects), 128
- ProjectMergeRequestAwardEmoji (class in gitlab.v4.objects), 129
- ProjectMergeRequestAwardEmojiManager (class in gitlab.v4.objects), 129
- ProjectMergeRequestDiff (class in gitlab.v4.objects), 129
- ProjectMergeRequestDiffManager (class in gitlab.v4.objects), 129
- ProjectMergeRequestDiscussion (class in gitlab.v4.objects), 129
- ProjectMergeRequestDiscussionManager (class in gitlab.v4.objects), 129
- ProjectMergeRequestDiscussionNote (class in gitlab.v4.objects), 129
- ProjectMergeRequestDiscussionNoteManager (class in gitlab.v4.objects), 130
- ProjectMergeRequestManager (class in gitlab.v4.objects), 130
- ProjectMergeRequestNote (class in gitlab.v4.objects), 131
- ProjectMergeRequestNoteAwardEmoji (class in gitlab.v4.objects), 131
- ProjectMergeRequestNoteAwardEmojiManager (class in gitlab.v4.objects), 131
- ProjectMergeRequestNoteManager (class in gitlab.v4.objects), 131
- ProjectMilestone (class in gitlab.v4.objects), 132
- ProjectMilestoneManager (class in gitlab.v4.objects), 132
- ProjectNote (class in gitlab.v4.objects), 133
- ProjectNoteManager (class in gitlab.v4.objects), 133
- ProjectNotificationSettings (class in gitlab.v4.objects), 133
- ProjectNotificationSettingsManager (class in gitlab.v4.objects), 133
- ProjectPagesDomain (class in gitlab.v4.objects), 134
- ProjectPagesDomainManager (class in gitlab.v4.objects), 134
- ProjectPipeline (class in gitlab.v4.objects), 134
- ProjectPipelineJob (class in gitlab.v4.objects), 134
- ProjectPipelineJobManager (class in gitlab.v4.objects), 134
- ProjectPipelineManager (class in gitlab.v4.objects), 135
- ProjectPipelineSchedule (class in gitlab.v4.objects), 135
- ProjectPipelineScheduleManager (class in gitlab.v4.objects), 135
- ProjectPipelineScheduleVariable (class in gitlab.v4.objects), 136
- ProjectPipelineScheduleVariableManager (class in gitlab.v4.objects), 136
- ProjectProtectedBranch (class in gitlab.v4.objects), 136
- ProjectProtectedBranchManager (class in gitlab.v4.objects), 136
- ProjectPushRules (class in gitlab.v4.objects), 137
- ProjectPushRulesManager (class in gitlab.v4.objects), 137
- ProjectRunner (class in gitlab.v4.objects), 137
- ProjectRunnerManager (class in gitlab.v4.objects), 137
- ProjectService (class in gitlab.v4.objects), 137
- ProjectServiceManager (class in gitlab.v4.objects), 137
- ProjectSnippet (class in gitlab.v4.objects), 138
- ProjectSnippetAwardEmoji (class in gitlab.v4.objects), 139
- ProjectSnippetAwardEmojiManager (class in gitlab.v4.objects), 139
- ProjectSnippetDiscussion (class in gitlab.v4.objects), 139
- ProjectSnippetDiscussionManager (class in gitlab.v4.objects), 139
- ProjectSnippetDiscussionNote (class in gitlab.v4.objects), 139
- ProjectSnippetDiscussionNoteManager (class in gitlab.v4.objects), 139
- ProjectSnippetManager (class in gitlab.v4.objects), 139
- ProjectSnippetNote (class in gitlab.v4.objects), 140
- ProjectSnippetNoteAwardEmoji (class in gitlab.v4.objects), 140
- ProjectSnippetNoteAwardEmojiManager (class in gitlab.v4.objects), 140
- ProjectSnippetNoteManager (class in gitlab.v4.objects), 140
- ProjectTag (class in gitlab.v4.objects), 140
- ProjectTagManager (class in gitlab.v4.objects), 141
- ProjectTrigger (class in gitlab.v4.objects), 141
- ProjectTriggerManager (class in gitlab.v4.objects), 141
- ProjectUser (class in gitlab.v4.objects), 141
- ProjectUserManager (class in gitlab.v4.objects), 141
- ProjectVariable (class in gitlab.v4.objects), 141
- ProjectVariableManager (class in gitlab.v4.objects), 142
- ProjectWiki (class in gitlab.v4.objects), 142
- ProjectWikiManager (class in gitlab.v4.objects), 142
- protect() (gitlab.v4.objects.ProjectBranch method), 108
- public() (gitlab.v4.objects.SnippetManager method), 146
- ## Q
- queue\_metrics() (gitlab.v4.objects.SidekiqManager method), 145
- ## R
- raw() (gitlab.v4.objects.ProjectFileManager method), 115

refresh() (gitlab.mixins.RefreshMixin method), 160  
RefreshMixin (class in gitlab.mixins), 160  
refs() (gitlab.v4.objects.ProjectCommit method), 109  
register\_custom\_action() (in module gitlab.cli), 153  
render() (gitlab.mixins.BadgeRenderMixin method), 157  
repair() (gitlab.v4.objects.GeoNode method), 88  
repository\_archive() (gitlab.v4.objects.Project method), 102  
repository\_blob() (gitlab.v4.objects.Project method), 102  
repository\_compare() (gitlab.v4.objects.Project method), 102  
repository\_contributors() (gitlab.v4.objects.Project method), 102  
repository\_raw\_blob() (gitlab.v4.objects.Project method), 103  
repository\_tree() (gitlab.v4.objects.Project method), 103  
reset\_spent\_time() (gitlab.mixins.TimeTrackingMixin method), 161  
reset\_time\_estimate() (gitlab.mixins.TimeTrackingMixin method), 162  
response\_content() (in module gitlab.utils), 163  
RESTManager (class in gitlab.base), 151  
RESTObject (class in gitlab.base), 152  
RESTObjectList (class in gitlab.base), 152  
RetrieveMixin (class in gitlab.mixins), 160  
retry() (gitlab.v4.objects.ProjectJob method), 122  
retry() (gitlab.v4.objects.ProjectPipeline method), 134  
Runner (class in gitlab.v4.objects), 142  
RunnerJob (class in gitlab.v4.objects), 142  
RunnerJobManager (class in gitlab.v4.objects), 142  
RunnerManager (class in gitlab.v4.objects), 143

## S

save() (gitlab.mixins.SaveMixin method), 160  
save() (gitlab.v4.objects.GroupEpicIssue method), 92  
save() (gitlab.v4.objects.ProjectFile method), 113  
save() (gitlab.v4.objects.ProjectLabel method), 123  
SaveMixin (class in gitlab.mixins), 160  
search() (gitlab.Gitlab method), 167  
search() (gitlab.v4.objects.Group method), 90  
search() (gitlab.v4.objects.Project method), 104  
session (gitlab.Gitlab attribute), 167  
set() (gitlab.mixins.SetMixin method), 160  
set() (gitlab.v4.objects.FeatureManager method), 88  
set\_approvers() (gitlab.v4.objects.ProjectApprovalManager method), 106  
set\_approvers() (gitlab.v4.objects.ProjectMergeRequestApprovalManager method), 129  
set\_license() (gitlab.Gitlab method), 167  
set\_release\_description() (gitlab.v4.objects.ProjectTag method), 140  
SetMixin (class in gitlab.mixins), 160  
share() (gitlab.v4.objects.Project method), 104  
SidekiqManager (class in gitlab.v4.objects), 144

snapshot() (gitlab.v4.objects.Project method), 104  
Snippet (class in gitlab.v4.objects), 145  
SnippetManager (class in gitlab.v4.objects), 145  
ssl\_verify (gitlab.Gitlab attribute), 167  
star() (gitlab.v4.objects.Project method), 105  
status() (gitlab.v4.objects.GeoNode method), 88  
status() (gitlab.v4.objects.GeoNodeManager method), 89  
stop() (gitlab.v4.objects.ProjectEnvironment method), 111  
SubscribableMixin (class in gitlab.mixins), 161  
subscribe() (gitlab.mixins.SubscribableMixin method), 161

## T

take\_ownership() (gitlab.v4.objects.ProjectPipelineSchedule method), 135  
take\_ownership() (gitlab.v4.objects.ProjectTrigger method), 141  
time\_estimate() (gitlab.mixins.TimeTrackingMixin method), 162  
time\_stats() (gitlab.mixins.TimeTrackingMixin method), 162  
timeout (gitlab.Gitlab attribute), 168  
TimeTrackingMixin (class in gitlab.mixins), 161  
Todo (class in gitlab.v4.objects), 146  
todo() (gitlab.mixins.TODOMixin method), 162  
TodoManager (class in gitlab.v4.objects), 146  
TODOMixin (class in gitlab.mixins), 162  
total (gitlab.base.RESTObjectList attribute), 152  
total (gitlab.GitlabList attribute), 168  
total\_pages (gitlab.base.RESTObjectList attribute), 152  
total\_pages (gitlab.GitlabList attribute), 168  
trace() (gitlab.v4.objects.ProjectJob method), 122  
transfer\_project() (gitlab.v4.objects.Group method), 91  
trigger\_pipeline() (gitlab.v4.objects.Project method), 105

## U

unarchive() (gitlab.v4.objects.Project method), 105  
unblock() (gitlab.v4.objects.User method), 147  
unprotect() (gitlab.v4.objects.ProjectBranch method), 108  
unshare() (gitlab.v4.objects.Project method), 105  
unstar() (gitlab.v4.objects.Project method), 105  
unsubscribe() (gitlab.mixins.SubscribableMixin method), 161  
update() (gitlab.mixins.UpdateMixin method), 162  
update() (gitlab.v4.objects.ApplicationSettingsManager method), 86  
update() (gitlab.v4.objects.ProjectFileManager method), 115  
update() (gitlab.v4.objects.ProjectServiceManager method), 138  
UpdateMixin (class in gitlab.mixins), 162  
upload() (gitlab.v4.objects.Project method), 106  
url (gitlab.Gitlab attribute), 168

User (class in gitlab.v4.objects), 146  
user\_agent\_detail() (gitlab.mixins.UserAgentDetailMixin method), 163  
UserActivities (class in gitlab.v4.objects), 147  
UserActivitiesManager (class in gitlab.v4.objects), 147  
UserAgentDetailMixin (class in gitlab.mixins), 163  
UserCustomAttribute (class in gitlab.v4.objects), 147  
UserCustomAttributeManager (class in gitlab.v4.objects), 147  
UserEmail (class in gitlab.v4.objects), 147  
UserEmailManager (class in gitlab.v4.objects), 147  
UserEvent (class in gitlab.v4.objects), 147  
UserEventManager (class in gitlab.v4.objects), 147  
UserGPGKey (class in gitlab.v4.objects), 148  
UserGPGKeyManager (class in gitlab.v4.objects), 148  
UserImpersonationToken (class in gitlab.v4.objects), 148  
UserImpersonationTokenManager (class in gitlab.v4.objects), 148  
UserKey (class in gitlab.v4.objects), 148  
UserKeyManager (class in gitlab.v4.objects), 148  
UserManager (class in gitlab.v4.objects), 148  
UserProject (class in gitlab.v4.objects), 150  
UserProjectManager (class in gitlab.v4.objects), 150

## V

verify() (gitlab.v4.objects.RunnerManager method), 144  
version() (gitlab.Gitlab method), 168

## W

what\_to\_cls() (in module gitlab.cli), 153