
sexpdata Documentation

Release 0.0.4.dev1

Takafumi Arakaki

March 08, 2014

sexpdata is a simple S-expression parser/serializer. It has simple *load* and *dump* functions like *pickle*, *json* or *PyYAML* module.

```
>>> from sexpdata import loads, dumps
>>> loads('("a" "b")')
['a', 'b']
>>> print(dumps(['a', 'b']))
("a" "b")
```

You can install *sexpdata* from PyPI:

```
pip install sexpdata
```

Links:

- [Documentation \(at Read the Docs\)](#)
- [Repository \(at GitHub\)](#)
- [Issue tracker \(at GitHub\)](#)
- [PyPI](#)
- [Travis CI](#)

sexprdata is licensed under the terms of the BSD 2-Clause License. See the source code for more information.

`sexprdata.load(filelike, **kwds)`

Load object from S-expression stored in *filelike*.

Parameters *filelike* – A text stream object.

See `loads()` for valid keyword arguments.

```
>>> import io
>>> fp = io.StringIO()
>>> sexp = [Symbol('a'), Symbol('b')] # let's dump and load this object
>>> dump(sexp, fp)
>>> _ = fp.seek(0)
>>> load(fp) == sexp
True
```

`sexprdata.loads(string, **kwds)`

Load object from S-expression *string*.

Parameters

- **string** – String containing an S-expression.
- **nil** (*str or None*) – A symbol interpreted as an empty list. Default is 'nil'.
- **true** (*str or None*) – A symbol interpreted as True. Default is 't'.
- **false** (*str or None*) – A symbol interpreted as False. Default is None.
- **line_comment** (*str*) – Beginning of line comment. Default is ';'.

```
>>> loads("(a b)")
[Symbol('a'), Symbol('b')]
>>> loads("a")
Symbol('a')
>>> loads("(a 'b)")
[Symbol('a'), Quoted(Symbol('b'))]
>>> loads("(a '(b))")
[Symbol('a'), Quoted([Symbol('b')])]
>>> loads("""
... ;; This is a line comment.
... ("a "b") ; this is also a comment.
... """)
['a', 'b']
>>> loads("""
```

```
... # This is a line comment.
... ("a" "b") # this is also a comment.
... ''' , line_comment='#')
['a', 'b']
```

`nil` is converted to an empty list by default. You can use keyword argument `nil` to change what symbol must be interpreted as `nil`:

```
>>> loads("nil")
[]
>>> loads("null", nil='null')
[]
>>> loads("nil", nil=None)
Symbol('nil')
```

`t` is converted to `True` by default. You can use keyword argument `true` to change what symbol must be converted to `True`:

```
>>> loads("t")
True
>>> loads("#t", true='#t')
True
>>> loads("t", true=None)
Symbol('t')
```

No symbol is converted to `False` by default. You can use keyword argument `false` to convert a symbol to `False`.

```
>>> loads("#f")
Symbol('#f')
>>> loads("#f", false='#f')
False
>>> loads("nil", false='nil', nil=None)
False
```

`sexpdata.dump(obj, filelike, **kwds)`

Write `obj` as an S-expression into given stream `filelike`.

Parameters

- **obj** – A Python object.
- **filelike** – A text stream object.

See `dumps()` for valid keyword arguments.

```
>>> import io
>>> fp = io.StringIO()
>>> dump([Symbol('a'), Symbol('b')], fp)
>>> print(fp.getvalue())
(a b)
```

`sexpdata.dumps(obj, **kwds)`

Convert python object into an S-expression.

Parameters

- **obj** – A Python object.
- **str_as** (`'symbol'` or `'string'`) – How string should be interpreted. Default is `'string'`.
- **tuple_as** (`'list'` or `'array'`) – How tuple should be interpreted. Default is `'list'`.

- **true_as** (*str*) – How True should be interpreted. Default is 't'
- **false_as** (*str*) – How False should be interpreted. Default is '()''
- **none_as** (*str*) – How None should be interpreted. Default is '()''

Basic usage:

```
>>> print (dumps(['a', 'b']))
("a" "b")
>>> print (dumps(['a', 'b'], str_as='symbol'))
(a b)
>>> print (dumps(dict(a=1)))
(:a 1)
>>> print (dumps([None, True, False, ()]))
(() t () ())
>>> print (dumps([None, True, False, ()],
...             none_as='null', true_as='#t', false_as='#f'))
(null #t #f ())
>>> print (dumps(('a', 'b')))
("a" "b")
>>> print (dumps(('a', 'b'), tuple_as='array'))
["a" "b"]
```

More verbose usage:

```
>>> print (dumps([Symbol('a'), Symbol('b')]))
(a b)
>>> print (dumps(Symbol('a')))
a
>>> print (dumps([Symbol('a'), Quoted(Symbol('b'))]))
(a 'b)
>>> print (dumps([Symbol('a'), Quoted([Symbol('b')]))])
(a '(b))
```

sexpdata.**car** (*obj*)

Alias of `obj[0]`.

```
>>> car(loads(' (a . b) '))
Symbol('a')
>>> car(loads(' (a b) '))
Symbol('a')
```

sexpdata.**cdr** (*obj*)

cdr-like function.

```
>>> cdr(loads(' (a . b) '))
Symbol('b')
>>> cdr(loads(' (a b) '))
[Symbol('b')]
>>> cdr(loads(' (a . (b)) '))
[Symbol('b')]
>>> cdr(loads(' (a) '))
[]
>>> cdr(loads(' (a . nil) '))
[]
```

Changelog

2.1 v0.0.3

- Encoded raw string can be dumped to S-expression, assuming that the encoding is UTF-8. See also [tkf/emacs-jedi/#43](#).

2.2 v0.0.2

- Performance improvement. Especially for long string literal.

2.3 v0.0.1

- Initial release.

Indices and tables

- *genindex*
- *modindex*
- *search*

S

sexpdata, ??