

---

# **python-stix Documentation**

*Release 1.2.0.5.dev0*

**The MITRE Corporation**

May 02, 2017



<b>1</b>	<b>Versions</b>	<b>3</b>
<b>2</b>	<b>Contents</b>	<b>5</b>
2.1	Installation . . . . .	5
2.2	Getting Started . . . . .	6
2.3	Overview . . . . .	8
2.4	Examples . . . . .	13
2.5	APIs or bindings? . . . . .	14
<b>3</b>	<b>API Reference</b>	<b>17</b>
3.1	API Reference . . . . .	17
3.2	API Coverage . . . . .	96
<b>4</b>	<b>Contributing</b>	<b>99</b>
<b>5</b>	<b>Indices and tables</b>	<b>101</b>
	<b>Python Module Index</b>	<b>103</b>



**Version:** 1.2.0.5.dev0

The **python-stix** library provides an API for developing and consuming *Structured Threat Information eXpression* (**STIX**) content. Developers can leverage the API to develop applications that create, consume, translate, or otherwise process STIX content. This page should help new developers get started with using this library. For more information about STIX, please refer to the [STIX website](#).

---

**Note:** These docs provide standard reference for this Python library. For documentation on *idiomatic* usage and *common patterns*, as well as various STIX-related information and utilities, please visit the [STIXProject at GitHub](#).

---



---

## Versions

---

Each version of `python-stix` is designed to work with a single version of the STIX Language. The table below shows the latest version the library for each version of STIX.

STIX Version	python-stix Version
1.2	1.2.0.4 ( <a href="#">PyPI</a> ) ( <a href="#">GitHub</a> )
1.1.1	1.1.1.8 ( <a href="#">PyPI</a> ) ( <a href="#">GitHub</a> )
1.1.0	1.1.0.6 ( <a href="#">PyPI</a> ) ( <a href="#">GitHub</a> )
1.0.1	1.0.1.1 ( <a href="#">PyPI</a> ) ( <a href="#">GitHub</a> )
1.0	1.0.0a7 ( <a href="#">PyPI</a> ) ( <a href="#">GitHub</a> )

Users and developers working with multiple versions of STIX content may want to take a look at [stix-ramrod](#), which is a library designed to update STIX and CybOX content.

Check out the [Working with python-stix](#) section for examples on how to integrate **stix-ramrod** and **python-stix**.





**Version:** 1.2.0.5.dev0

## Installation

The installation of python-stix can be accomplished through a few different workflows.

### Recommended Installation

Use `pypi` and `pip`:

```
$ pip install stix
```

You might also want to consider using a `virtualenv`. Please refer to the [pip installation instructions](#) for details regarding the installation of `pip`.

### Dependencies

The python-stix library relies on some non-standard Python libraries for the processing of STIX content. Revisions of python-stix may depend on particular versions of dependencies to function correctly. These versions are detailed within the `distutils setup.py` installation script.

The following libraries are required to use python-stix:

- `lxml` - A Pythonic binding for the C libraries `libxml2` and `libxslt`.
- `python-cybox` - A library for consuming and producing CybOX content.
- `python-dateutil` - A library for parsing datetime information.

Each of these can be installed with `pip` or by manually downloading packages from PyPI. On Windows, you will probably have the most luck using [pre-compiled binaries](#) for `lxml`. On Ubuntu (12.04 or 14.04), you should make sure the following packages are installed before attempting to compile `lxml` from source:

- `libxml2-dev`
- `libxslt1-dev`
- `zlib1g-dev`

**Warning:** Users have encountered errors with versions of libxml2 (a dependency of lxml) prior to version 2.9.1. The default version of libxml2 provided on Ubuntu 12.04 is currently 2.7.8. Users are encouraged to upgrade libxml2 manually if they have any issues. Ubuntu 14.04 provides libxml2 version 2.9.1.

## Manual Installation

If you are unable to use pip, you can also install python-stix with [setuptools](#). If you don't already have setuptools installed, please install it before continuing.

1. Download and install the *dependencies* above. Although setuptools will generally install dependencies automatically, installing the dependencies manually beforehand helps distinguish errors in dependency installation from errors in stix installation. Make sure you check to ensure the versions you install are compatible with the version of stix you plan to install.
2. Download the desired version of stix from [PyPI](#) or the [GitHub releases](#) page. The steps below assume you are using the 1.2.0.5.dev0 release.
3. Extract the downloaded file. This will leave you with a directory named stix-1.2.0.5.dev0.

```
$ tar -zxf stix-1.2.0.5.dev0.tar.gz
$ ls
stix-1.2.0.5.dev0 stix-1.2.0.5.dev0.tar.gz
```

OR

```
$ unzip stix-1.2.0.5.dev0.zip
$ ls
stix-1.2.0.5.dev0 stix-1.2.0.5.dev0.zip
```

4. Run the installation script.

```
$ cd stix-1.2.0.5.dev0
$ python setup.py install
```

5. Test the installation.

```
$ python
Python 2.7.6 (default, Mar 22 2014, 22:59:56)
[GCC 4.8.2] on linux2
Type "help", "copyright", "credits" or "license" for more information.
>>> import stix
>>>
```

If you don't see an `ImportError`, the installation was successful.

## Further Information

If you're new to installing Python packages, you can learn more at the [Python Packaging User Guide](#), specifically the [Installing Python Packages](#) section.

**Version:** 1.2.0.5.dev0

## Getting Started

This page gives an introduction to **python-stix** and how to use it.

---

**Note:** This page is being actively worked on; feedback is always welcome.

---

## Prerequisites

The python-stix library provides an API for creating or processing STIX content. As such, it is a developer tool that can be leveraged by those who know Python 2.6/2.7 and are familiar with object-oriented programming practices, Python package layouts, and are comfortable with the installation of Python libraries. To contribute code to the python-stix repository, users must be familiar with [git](#) and [GitHub pull request](#) methodologies. Understanding XML, XML Schema, and the STIX language is also incredibly helpful when using python-stix in an application.

## Your First STIX Application

Once you have installed python-stix, you can begin writing Python applications that consume or create STIX content!

---

**Note:** The *python-stix* library provides **bindings** and **APIs**, both of which can be used to parse and write STIX XML files. For in-depth description of the *APIs*, *bindings*, and *the differences between the two*, please refer to [APIs or bindings?](#)

---

## Creating a STIX Package

```

from stix.core import STIXPackage           # Import the STIX Package API
from stix.report import Report              # Import the STIX Report API
from stix.report.header import Header       # Import the STIX Report Header API

stix_package = STIXPackage()                # Create an instance of STIXPackage
stix_report = Report()                     # Create a Report instance
stix_report.header = Header()              # Create a header for the report
stix_report.header.description = "Getting Started!" # Set the description
stix_package.add(stix_report)              # Add the report to our STIX Package

print(stix_package.to_xml())                # Print the XML for this STIX Package

```

## Parsing STIX XML

```

from stix.core import STIXPackage          # Import the STIX Package API

fn = 'stix_content.xml'                    # The STIX content filename
stix_package = STIXPackage.from_xml(fn)     # Parse using the from_xml() method

```

## Examples

The python-stix GitHub repository contains several example scripts that help illustrate the capabilities of the APIs. These examples can be found [here](#). Accompanying walkthrough [slides](#) are available. These scripts are simple command line utilities that can be executed by passing the name of the script to a Python interpreter.

```

Example:
$ python ex_01.py

```

---

**Note:** You must install python-stix before running these example scripts.

---

**Version:** 1.2.0.5.dev0

## Overview

This page provides a quick overview needed to understand the inner workings of the **python-stix** library. If you prefer a more hands-on approach, browse the [Examples](#).

**Version:** 1.2.0.5.dev0

## ID Namespaces

By default, **python-stix** sets the default ID namespace to `http://example.com` with an alias of `example`. This results in STIX id declarations that look like `id="example:Package-2813128d-f45e-41f7-b10a-20a5656e3785"`.

To change this, use the `mixbox.idgen.set_id_namespace()` method which takes a dictionary as a parameter.

```
from stix.core import STIXPackage
from mixbox.idgen import set_id_namespace
from mixbox.namespaces import Namespace

NAMESPACE = Namespace("http://MY-NAMESPACE.com", "myNS")
set_id_namespace(NAMESPACE) # new ids will be prefixed by "myNS"

stix_package = STIXPackage() # id will be created automatically
print stix_package.to_xml()
```

Which outputs:

```
<stix:STIX_Package
  xmlns:ds="http://www.w3.org/2000/09/xmldsig#"
  xmlns:myNS="http://MY-NAMESPACE.com"
  xmlns:stix="http://stix.mitre.org/stix-1"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xlink="http://www.w3.org/1999/xlink"
  id="myNS:Package-b2039368-9476-4a5b-8c1d-0ef5d1b37e06" version="1.2"/>
```

Success! The `xmlns:myNS="http://MY-NAMESPACE.com"` matches our `NAMESPACE` dictionary and the `id` attribute includes the `myNS` namespace alias.

## Working With CybOX

When setting the ID namespace in **python-stix**, the ID namespace will also be set in **python-cybox**.

**Version:** 1.2.0.5.dev0

## Controlled Vocabularies

Many fields in STIX leverage the `stixCommon:ControlledVocabularyStringType`, which acts as a base type for controlled vocabulary implementations. The STIX language defines a set of default controlled vocabularies which are found in the `stix_default_vocabs.xsd` XML Schema file.

The **python-stix** library contains a `stix.common.vocabs` module, which defines the `VocabString` class implementation of the schema `ControlledVocabularyStringType` as well as `VocabString` implementations which correspond to default controlled vocabularies.

For example, the `stix_default_vocabularies.xsd` schema defines a controlled vocabulary for STIX Package Intents: `PackageIntentVocab-1.0`. The `stix.common.vocabs` module contains an analogous `PackageIntent` class, which acts as a derivation of `VocabString`.

Each `VocabString` implementation contains:

- A static list of class-level term attributes, each beginning with `TERM_`` (e.g., ```TERM_INDICATORS`)
- A tuple containing all allowed vocabulary terms: `_ALLOWED_VALUES`, which is use for input validation. This is generated via the `vocabs.register_vocab()` class decorator.
- Methods found on `stix.Entity`, such as `to_xml()`, `to_dict()`, `from_dict()`, etc.

## Interacting With VocabString Fields

The following sections define ways of interacting with `VocabString` fields.

### Default Vocabulary Terms

The STIX Language often suggested a default controlled vocabulary type for a given controlled vocabulary field. Each controlled vocabulary contains an enumeration of allowed terms.

Each `VocabString` implementation found in the `stix.common.vocabs` module contains static class-level attributes for each vocabulary term. When setting controlled vocabulary field values, it is recommended that users take advantage of these class-level attributes.

The following demonstrates setting the `Package_Intent` field with a default vocabulary term. Note that the `STIXHeader.package_intents` property returns a list. As such, we use the `append()` method to add terms. Other STIX controlled vocabulary fields may only allow one value rather than a list of values.

```
from stix.core import STIXHeader
from stix.common.vocabs import PackageIntent

header = STIXHeader()
header.package_intents.append(PackageIntent.TERM_INDICATORS)

print(header.to_xml())
```

Which outputs:

```
<stix:STIXHeaderType>
  <stix:Package_Intent xsi:type="stixVocabs:PackageIntentVocab-1.0">Indicators</stix:Package_Intent
</stix:STIXHeaderType>
```

## Non-Default Vocabulary Terms

Though it is suggested, STIX content authors are not required to use the default controlled vocabulary for a given field. As such, **python-stix** allows users to pass in non-default values for controlled vocabulary fields.

To set a controlled vocabulary to a non-default vocabulary term, pass a *VocabString* instance into a controlled vocabulary field.

A raw *VocabString* field will contain no `xsi:type` information or `_ALLOWED_VALUES` members, which removes the input and schema validation requirements.

```
from stix.core import STIXHeader
from stix.common.vocabs import VocabString, PackageIntent

header = STIXHeader()
non_default_term = VocabString("NON-DEFAULT VOCABULARY TERM")
header.package_intents.append(non_default_term)

print(header.to_xml())
```

Which outputs:

```
<stix:STIXHeaderType>
  <stix:Package_Intent>NON-DEFAULT VOCABULARY TERM</stix:Package_Intent>
</stix:STIXHeaderType>
```

Notice that the `<stix:Package_Intent>` field does not have an `xsi:type` attribute. As such, this field can contain any string value and is not bound by a controlled vocabulary enumeration of terms.

## Working With Custom Controlled Vocabularies

STIX allows content authors and developers to extend the `ControlledVocabularyStringType` schema type for the definition of new controlled vocabularies. The **python-stix** library allows developers to create and register Python types which mirror the custom XML Schema vocabulary types.

**XSD Example** The following XML Schema example shows the definition of a new custom controlled vocabulary schema type. Instances of this schema type could be used wherever a `ControlledVocabularyStringType` instance is expected (e.g., the `STIX_Header/Package_Intent` field).

```
Filename: customVocabs.xsd

<xs:schema
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:customVocabs="http://customvocabs.com/vocabs-1"
  xmlns:stixVocabs="http://stix.mitre.org/default_vocabularies-1"
  xmlns:stixCommon="http://stix.mitre.org/common-1"
  targetNamespace="http://customvocabs.com/vocabs-1"
  elementFormDefault="qualified"
  version="1.2"
  xml:lang="English">
  <xs:import namespace="http://stix.mitre.org/common-1" schemaLocation="http://stix.mitre.org/XMLS
  <xs:complexType name="CustomVocab-1.0">
    <xs:simpleContent>
      <xs:restriction base="stixCommon:ControlledVocabularyStringType">
        <xs:simpleType>
          <xs:union memberTypes="customVocabs:CustomEnum-1.0"/>
        </xs:simpleType>
      </xs:restriction>
    </xs:simpleContent>
  </xs:complexType>
```

```

        <xs:attribute name="vocab_name" type="xs:string" use="optional" fixed="Test Vocab"/>
        <xs:attribute name="vocab_reference" type="xs:anyURI" use="optional" fixed="http://ex
    </xs:restriction>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="CustomEnum-1.0">
  <xs:restriction base="xs:string">
    <xs:enumeration value="FOO"/>
    <xs:enumeration value="BAR"/>
  </xs:restriction>
</xs:simpleType>
</xs:schema>

```

**XML Instance Sample** The following STIX XML instance document shows a potential use of this field. Note the `xsi:type=customVocabs:CustomVocab-1.0` on the `Package_Intent` field.

```

Filename: customVocabs.xml

<stix:STIX_Package
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:stixExample="http://stix.mitre.org/example"
  xmlns:stix="http://stix.mitre.org/stix-1"
  xmlns:customVocabs="http://customvocabs.com/vocabs-1"
  xsi:schemaLocation="
    http://stix.mitre.org/stix-1 /path/to/stix_core.xsd
    http://customvocabs.com/vocabs-1 /path/to/customVocabs.xsd"
  id="stixExample:STIXPackage-33fe3b22-0201-47cf-85d0-97c02164528d"
  version="1.2">
  <stix:STIX_Header>
    <stix:Package_Intent xsi:type="customVocabs:CustomVocab-1.0">FOO</stix:Package_Intent>
  </stix:STIX_Header>
</stix:STIX_Package>

```

**Python Code** To parse content which uses custom controlled vocabularies, Python developers don't have to do anything special—you just call `STIXPackage.from_xml()` on the input and all the namespaces, `xsi:types`, etc. are attached to each instance of `VocabString`. When serializing the document, the input namespaces and `xsi:type` attributes are retained!

However, to *create* new content which utilizes a schema defined and enforced custom controlled vocabulary, developers must create a `VocabString` implementation which mirrors the schema definition.

For our `CustomVocab-1.0` schema type, the Python would look like this:

```

from stix.common import vocabs

# Create a custom vocabulary type
@vocabs.register_vocab
class CustomVocab(vocabs.VocabString):
    _namespace = 'http://customvocabs.com/vocabs-1'
    _XSI_TYPE = 'customVocabs:CustomVocab-1.0'

    # Valid terms
    TERM_FOO = 'FOO'
    TERM_BAR = 'BAR'

```

As you can see, we can express a lot of the same information found in the XML Schema definition, but in Python!

- `_namespace`: The `targetNamespace` for our custom vocabulary
- `_XSI_TYPE`: The `xsi:type` attribute value to write out for instances of this vocabulary.
- `TERM_FOO|BAR`: Allowable terms for the vocabulary. These terms are collected for input validation.

**Note:** The `@register_vocab` class decorator registers the class and its `xsi:type` as a `VocabString` implementation so **python-stix** will know to build instances of `CustomVocab` when parsed content contains `CustomVocab-1.0` content.

This also inspects the class attributes for any that begin with `TERM_` and collects their values for the purpose of input validation.

**Warning:** Before **python-stix** 1.2.0.0, users registered custom `VocabString` implementations via the `stix.common.vocabs.add_vocab()` method. This method still exists but is considered **DEPRECATED** in favor of the `stix.common.vocabs.register_vocab()` class decorator.

```
# builtin
from StringIO import StringIO

# python-stix modules
from stix.core import STIXPackage
from stix.common.vocabs import VocabString, register_vocab
from mixbox.namespaces import register_namespace, Namespace

XML = \
"""
<stix:STIX_Package
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:stix="http://stix.mitre.org/stix-1"
  xmlns:customVocabs="http://customvocabs.com/vocabs-1"
  xmlns:example="http://example.com/"
  xsi:schemaLocation="
    http://stix.mitre.org/stix-1 /path/to/stix_core.xsd
    http://customvocabs.com/vocabs-1 /path/to/customVocabs.xsd"
  id="example:STIXPackage-33fe3b22-0201-47cf-85d0-97c02164528d"
  version="1.2">
  <stix:STIX_Header>
    <stix:Package_Intent xsi:type="customVocabs:CustomVocab-1.0">FOO</stix:Package_Intent>
  </stix:STIX_Header>
</stix:STIX_Package>
"""

# Create a VocabString class for our CustomVocab-1.0 vocabulary which
@register_vocab
class CustomVocab(VocabString):
    _namespace = 'http://customvocabs.com/vocabs-1'
    _XSI_TYPE = 'customVocabs:CustomVocab-1.0'
    TERM_FOO = 'FOO'
    TERM_BAR = 'BAR'

register_namespace(Namespace(CustomVocab._namespace, "customVocabNS"))

# Parse the input document
sio = StringIO(XML)
package = STIXPackage.from_xml(sio)

# Retrieve the first (and only) Package_Intent entry
```



```

package_intent = package.stix_header.package_intents[0]

# Print information about the input Package_Intent
print('%s %s %s' % (type(package_intent), package_intent.xsi_type, package_intent))

# Add another Package Intent
bar = CustomVocab('BAR')
package.stix_header.add_package_intent(bar)

# This will include the 'BAR' CustomVocab entry
print(package.to_xml())

```

Version: 1.2.0.5.dev0

## Examples

This page includes some basic examples of creating and parsing STIX content.

There are a couple things we do in these examples for purposes of demonstration that shouldn't be done in production code:

- In some examples, we use `set_id_method(IDGenerator.METHOD_INT)` to make IDs for STIX constructs easier to read and cross-reference within the XML document. In production code, you should omit this statement, which causes random UUIDs to be created instead, or create explicit IDs yourself for STIX constructs.

See the [STIX Idioms](#) documentation for more great examples of how to use **python-stix**.

## Creating a STIX Package

```

from stix.core import STIXPackage
from stix.report import Report
from stix.report.header import Header
from stix.utils import IDGenerator, set_id_method

set_id_method(IDGenerator.METHOD_INT) # For testing and demonstration only!

stix_package = STIXPackage()
stix_report = Report()
stix_report.header = Header()
stix_report.header.description = "Getting Started!"
stix_package.add(stix_report)

print(stix_package.to_xml())

```

Which outputs:

```

<stix:STIX_Package
  xmlns:cybox="http://cybox.mitre.org/cybox-2"
  xmlns:cyboxCommon="http://cybox.mitre.org/common-2"
  xmlns:cyboxVocabs="http://cybox.mitre.org/default_vocabularies-2"
  xmlns:example="http://example.com"
  xmlns:report="http://stix.mitre.org/Report-1"
  xmlns:stix="http://stix.mitre.org/stix-1"
  xmlns:stixCommon="http://stix.mitre.org/common-1"
  xmlns:stixVocabs="http://stix.mitre.org/default_vocabularies-1"

```

```
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" id="example:Package-1" version="1.2">
<stix:Reports>
  <stix:Report timestamp="2016-07-15T15:27:43.847000+00:00" id="example:Report-2" xsi:type='rep
    <report:Header>
      <report:Description>Getting Started!</report:Description>
    </report:Header>
  </stix:Report>
</stix:Reports>
</stix:STIX_Package>
```

## Controlled Vocabularies: VocabString

This section has moved! Head over to [Controlled Vocabularies](#) for the documentation.

## ID Namespaces

This section has moved! Head over to [ID Namespaces](#) for the documentation.

**Version:** 1.2.0.5.dev0

## APIs or bindings?

This page describes both the **APIs** and the **bindings** provided by the *python-stix* library.

### Overview

The python-stix library provides APIs and utilities that aid in the creation, consumption, and processing of Structured Threat Information eXpression (STIX) content. The APIs that drive much of the functionality of python-stix sit on top of a binding layer that acts as a direct connection between Python and the STIX XML. Because both the APIs and the bindings allow for the creation and development of STIX content, developers that are new to python-stix may not understand the differences between the two. This document aims to identify the purpose and uses of the APIs and bindings.

### Bindings

The python-stix library leverages machine generated XML-to-Python bindings for the creation and processing of STIX content. These bindings are created using the [generateDS](#) utility and can be found under `stix.bindings` within the package hierarchy.

The STIX bindings allow for a direct, complete mapping between Python classes and STIX XML Schema data structures. That being said, it is possible (though not advised) to use only the STIX bindings to create STIX documents. However, because the code is generated from XML Schema without contextual knowledge of relationships or broader organizational/developmental schemes, it is often a cumbersome and laborious task to create even the simplest of STIX documents.

Developers within the python-stix team felt that the binding code did not lend itself to rapid development or natural navigation of data, and so it was decided that a higher-level API should be created.

## APIs

The python-stix APIs are classes and utilities that leverage the STIX bindings for the creation and processing of STIX content. The APIs are designed to behave more naturally when working with STIX content, allowing developers to conceptualize and interact with STIX documents as pure Python objects and not XML Schema objects.

The APIs provide validation of inputs, multiple input and output formats, more Pythonic access of data structure internals and interaction with classes, and better interpretation of a developers intent through datatype coercion and implicit instantiation.

---

**Note:** The python-stix APIs are under constant development. Our goal is to provide full API coverage of the STIX data structures, but not all structures are exposed via the APIs yet. Please refer to the [API Reference](#) for API coverage details.

---

## Brevity Wins

The two code examples show the difference in creating and printing a simple STIX document consisting of only a STIX Package and a STIX Header with a description and produced time using the python-stix and python-cybox bindings. Both examples will produce the same STIX XML!

### API Example

```
from datetime import datetime
from stix.core import STIXPackage, STIXHeader
from stix.common import InformationSource
from cybox.common import Time

# Create the STIX Package and STIX Header objects
stix_package = STIXPackage()
stix_header = STIXHeader()

# Set the description
stix_header.description = 'APIs vs. Bindings Wiki Example'

# Set the produced time to now
stix_header.information_source = InformationSource()
stix_header.information_source.time = Time()
stix_header.information_source.time.produced_time = datetime.now()

# Build document
stix_package.stix_header = stix_header

# Print the document to stdout
print(stix_package.to_xml())
```

### Binding Example

```
import sys
from datetime import datetime

import stix.bindings.stix_core as stix_core_binding
import stix.bindings.stix_common as stix_common_binding
import cybox.bindings.cybox_common as cybox_common_binding

# Create the STIX Package and STIX Header objects
stix_package = stix_core_binding.STIXType()
```

```
stix_header = stix_core_binding.STIXHeaderType()

# Set the description
stix_header_description = stix_common_binding.StructuredTextType()
stix_header_description.set_valueOf_('APIs vs. Bindings Wiki Example')

# Set the produced time to now
stix_header_time = cybox_common_binding.TimeType()
stix_header_time.set_Produced_Time(datetime.now())

# Bind the time to the STIX Header's Information Source element
stix_header_info_source = stix_common_binding.InformationSourceType()
stix_header_info_source.set_Time(stix_header_time)

# Build the document
stix_header.set_Description(stix_header_description)
stix_header.set_Information_Source(stix_header_info_source)
stix_package.set_STIX_Header(stix_header)

# Print the document to stdout
stix_package.export(sys.stdout, 0, stix_core_binding.DEFAULT_XML_NS_MAP)
```

## Feedback

If there is a problem with the APIs or bindings, or if there is functionality missing from the APIs that forces the use of the bindings, let us know in the [python-stix issue tracker](#)

---

## API Reference

---

**Version:** 1.2.0.5.dev0

### API Reference

The *python-stix* APIs are the recommended tools for reading, writing, and manipulating STIX XML documents.

---

**Note:** The *python-stix* APIs are currently under development. As such, API coverage of STIX data constructs is incomplete; please bear with us as we work toward complete coverage. This documentation also serves to outline current API coverage.

---

### STIX

Modules located in the base *stix* package

**Version:** 1.2.0.5.dev0

#### *stix*.base Module

##### Classes

**class** *stix*.base.**Entity**

Base class for all classes in the STIX API.

**find** (*id\_*)

Searches the children of a *Entity* implementation for an object with an *id\_* property that matches *id\_*.

**to\_xml** (*include\_namespaces=True, include\_schemalocs=False, ns\_dict=None, schemaloc\_dict=None, pretty=True, auto\_namespace=True, encoding='utf-8'*)

Serializes a *Entity* instance to an XML string.

The default character encoding is `utf-8` and can be set via the *encoding* parameter. If *encoding* is `None`, a string (unicode in Python 2, str in Python 3) is returned.

##### Parameters

- **auto\_namespace** – Automatically discover and export XML namespaces for a STIX *Entity* instance.

- **include\_namespaces** – Export namespace definitions in the output XML. Default is `True`.
- **include\_schemalocs** – Export `xsi:schemaLocation` attribute in the output document. This will attempt to associate namespaces declared in the STIX document with schema locations. If a namespace cannot be resolved to a `schemaLocation`, a Python warning will be raised. Schemalocations will only be exported if `include_namespaces` is also `True`.
- **ns\_dict** – Dictionary of XML definitions (namespace is key, alias is value) to include in the exported document. This must be passed in if `auto_namespace` is `False`.
- **schemaloc\_dict** – Dictionary of XML namespace: schema location mappings to include in the exported document. These will only be included if `auto_namespace` is `False`.
- **pretty** – Pretty-print the XML.
- **encoding** – The output character encoding. Default is `utf-8`. If `encoding` is set to `None`, a string (unicode in Python 2, str in Python 3) is returned.

**Returns** An XML string for this `Entity` instance. Default character encoding is `utf-8`.

```
class stix.base.EntityList(*args)
    Bases: mixbox.entities.EntityList, stix.base.Entity
```

**Version:** 1.2.0.5.dev0

## stix.data\_marking Module

### Classes

```
class stix.data_marking.Marking(markings=None)
    Bases: stix.base.EntityList
```

```
class stix.data_marking.MarkingSpecification(controlled_structure=None, marking_structures=None)
    Bases: stix.base.Entity
```

```
class stix.data_marking.MarkingStructure
    Bases: stix.base.Entity
```

### Functions

```
stix.data_marking.add_extension(cls)
    Registers a stix.Entity class as an implementation of an xml type.
```

Classes must have an `_XSI_TYPE` class attributes to be registered. The value of this attribute must be a valid `xsi:type`.

---

**Note:** This was designed for internal use.

---

## STIX Campaign

Modules located in the `stix.campaign` package

Version: 1.2.0.5.dev0

## stix.campaign Module

### Overview

The `stix.campaign` module implements `Campaign`.

Campaigns are instances of ThreatActors pursuing an intent, as observed through sets of Incidents and/or TTP, potentially across organizations.

### Documentation Resources

- [Campaign Data Model](#)

### Classes

**class** `stix.campaign.Campaign` (*id=None, idref=None, timestamp=None, title=None, description=None, short\_description=None*)

Bases: `stix.base.BaseCoreComponent`

Implementation of the STIX Campaign.

#### Parameters

- **id** (*optional*) – An identifier. If `None`, a value will be generated via `mixbox.idgen.create_id()`. If set, this will unset the `idref` property.
- **idref** (*optional*) – An identifier reference. If set this will unset the `id_` property.
- **timestamp** (*optional*) – A timestamp value. Can be an instance of `datetime.datetime` or `str`.
- **description** – A description of the purpose or intent of this object.
- **short\_description** – A short description of the intent or purpose of this object.
- **title** – The title of this object.

**add\_activity** (*value*)

Adds an `Activity` object to the activity collection.

**add\_description** (*description*)

Adds a description to the descriptions collection.

This is the same as calling “`foo.descriptions.add(bar)`”.

**add\_short\_description** (*description*)

Adds a description to the short\_descriptions collection.

This is the same as calling “`foo.short_descriptions.add(bar)`”.

**description**

A single description about the contents or purpose of this object.

Default Value: `None`

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**find** (*id\_*)

Searches the children of a *Entity* implementation for an object with an *id\_* property that matches *id\_*.

**short\_description**

A single short description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one short description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**to\_dict** ()

Convert to a dict

Subclasses can override this function.

**Returns** Python dict with keys set from this *Entity*.

**to\_json** ()

Export an object as a JSON String.

**to\_obj** (*ns\_info=None*)

Convert to a GenerateDS binding object.

Subclasses can override this function.

**Returns** An instance of this *Entity*'s *\_binding\_class* with properties set from this *Entity*.

**class** *stix.campaign.AssociatedCampaigns* (*scope=None, \*args*)  
Bases: *stix.common.related.GenericRelationshipList*

**class** *stix.campaign.Attribution* (*scope=None, \*args*)  
Bases: *stix.common.related.GenericRelationshipList*

**class** *stix.campaign.Names* (*\*args*)  
Bases: *stix.base.EntityList*

**class** *stix.campaign.RelatedIncidents* (*scope=None, \*args*)  
Bases: *stix.common.related.GenericRelationshipList*

**class** *stix.campaign.RelatedIndicators* (*scope=None, \*args*)  
Bases: *stix.common.related.GenericRelationshipList*

**class** *stix.campaign.RelatedTTPs* (*scope=None, \*args*)  
Bases: *stix.common.related.GenericRelationshipList*

## STIX Common

Modules located in the *stix.common* package

Version: 1.2.0.5.dev0



## stix.common Module

### Classes

**class** stix.common.**EncodedCDATA** (*value=None, encoded=None*)  
Bases: *stix.base.Entity*

Version: 1.2.0.5.dev0

## stix.common.activity Module

### Classes

**class** stix.common.activity.**Activity**  
Bases: *stix.base.Entity*

**add\_description** (*description*)  
Adds a description to the descriptions collection.  
This is the same as calling “foo.descriptions.add(bar)”.

**description**  
A single description about the contents or purpose of this object.  
Default Value: None

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

Version: 1.2.0.5.dev0

## stix.common.confidence Module

### Classes

**class** stix.common.confidence.**Confidence** (*value=None, timestamp=None, description=None, source=None*)  
Bases: *stix.base.Entity*

**add\_description** (*description*)  
Adds a description to the descriptions collection.  
This is the same as calling “foo.descriptions.add(bar)”.

**description**  
A single description about the contents or purpose of this object.  
Default Value: None

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**Version:** 1.2.0.5.dev0

## **stix.common.datetimewithprecision Module**

### **Classes**

**class** stix.common.datetimewithprecision.**DateTimeWithPrecision** (*value=None, precision='second'*)  
Bases: *stix.base.Entity*

### **Constants**

stix.common.datetimewithprecision.**DATE\_PRECISION\_VALUES** = ('year', 'month', 'day')  
tuple() -> empty tuple  
tuple(iterable) -> tuple initialized from iterable's items

If the argument is a tuple, the return value is the same object.

stix.common.datetimewithprecision.**TIME\_PRECISION\_VALUES** = ('hour', 'minute', 'second')  
tuple() -> empty tuple  
tuple(iterable) -> tuple initialized from iterable's items

If the argument is a tuple, the return value is the same object.

stix.common.datetimewithprecision.**DATETIME\_PRECISION\_VALUES** = ('year', 'month', 'day', 'hour', 'minute', 'second')  
tuple() -> empty tuple  
tuple(iterable) -> tuple initialized from iterable's items

If the argument is a tuple, the return value is the same object.

**Version:** 1.2.0.5.dev0

## **stix.common.identity Module**

### **Classes**

**class** stix.common.identity.**Identity** (*id=None, idref=None, name=None, related\_identities=None*)  
Bases: *stix.base.Entity*

**class** stix.common.identity.**RelatedIdentities** (*\*args*)  
Bases: *stix.base.EntityList*

### **Functions**

stix.common.identity.**add\_extension** (*cls*)  
Registers a stix.Entity class as an implementation of an xml type.

Classes must have an `_XSI_TYPE` class attributes to be registered. The value of this attribute must be a valid xsi:type.

---

**Note:** This was designed for internal use.

---

**Version:** 1.2.0.5.dev0

**stix.common.information\_source Module****Classes**

**class** stix.common.information\_source.**InformationSource** (*description=None, identity=None, time=None, tools=None, contributing\_sources=None, references=None*)

Bases: *stix.base.Entity*

**add\_description** (*description*)

Adds a description to the descriptions collection.

This is the same as calling “foo.descriptions.add(bar)”.

**description**

A single description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**class** stix.common.information\_source.**ContributingSources** (*\*args*)

Bases: *stix.base.EntityList*

**Version:** 1.2.0.5.dev0

**stix.common.kill\_chains Module****Classes**

**class** stix.common.kill\_chains.**KillChain** (*id=None, name=None, definer=None, reference=None*)

Bases: *stix.base.Entity*

**class** stix.common.kill\_chains.**KillChains** (*\*args*)

Bases: *stix.base.EntityList*

**class** stix.common.kill\_chains.**KillChainPhase** (*phase\_id=None, name=None, ordinality=None*)

Bases: *stix.base.Entity*

**class** stix.common.kill\_chains.**KillChainPhaseReference** (*phase\_id=None, name=None, ordinality=None, kill\_chain\_id=None, kill\_chain\_name=None*)

Bases: *stix.common.kill\_chains.KillChainPhase*

**class** stix.common.kill\_chains.**KillChainPhasesReference** (*\*args*)

Bases: *stix.base.EntityList*

## Lockheed Martin Kill Chain

There is a shortcuts for adding kill chain phases from the [Lockheed Martin Cyber Kill Chain](#) to indicators:

```
from stix.common.kill_chains.lmco import PHASE_RECONNAISSANCE
from stix.indicator import Indicator
i = Indicator()
i.add_kill_chain_phase(PHASE_RECONNAISSANCE)
print i.to_xml(include_namespaces=False)
```

```
<indicator:Indicator id="example:indicator-2bb1c0ea-7dd8-40fb-af64-7199f00719c1"
  timestamp="2015-03-17T19:14:22.797675+00:00" xsi:type='indicator:IndicatorType'>
  <indicator:Kill_Chain_Phases>
    <stixCommon:Kill_Chain_Phase phase_id="stix:TTP-af1016d6-a744-4ed7-ac91-00fe2272185a"/>
  </indicator:Kill_Chain_Phases>
</indicator:Indicator>
```

Version: 1.2.0.5.dev0

## stix.common.related Module

### Classes

**class** stix.common.related.**GenericRelationship** (*confidence=None, information\_source=None, relationship=None*)

Bases: *stix.base.Entity*

**class** stix.common.related.**GenericRelationshipList** (*scope=None, \*args*)

Bases: *stix.base.EntityList*

Base class for concrete GenericRelationshipList types.

---

**Note:** Subclasses must supply exactly one multiple TypedField.

---

**class** stix.common.related.**RelatedPackageRef** (*idref=None, timestamp=None, confidence=None, information\_source=None, relationship=None*)

Bases: *stix.common.related.GenericRelationship*

**class** stix.common.related.**RelatedPackageRefs** (*\*args*)

Bases: *stix.base.EntityList*

**class** stix.common.related.**BaseRelated** (*item=None, confidence=None, information\_source=None, relationship=None*)

Bases: *stix.common.related.GenericRelationship*

A base class for related types.

This class is not a real STIX type and should not be directly instantiated.

---

**Note:** Subclasses must supply a TypedField named *item*!

---

**class** stix.common.related.**RelatedCampaign** (*item=None, confidence=None, information\_source=None, relationship=None*)

Bases: *stix.common.related.BaseRelated*

```

class stix.common.related.RelatedCOA (item=None, confidence=None, information_source=None,
                                         relationship=None)
    Bases: stix.common.related._BaseRelated

class stix.common.related.RelatedExploitTarget (item=None, confidence=None, informa-
                                                tion_source=None, relationship=None)
    Bases: stix.common.related._BaseRelated

class stix.common.related.RelatedIdentity (item=None, confidence=None, informa-
                                                tion_source=None, relationship=None)
    Bases: stix.common.related._BaseRelated

class stix.common.related.RelatedIncident (item=None, confidence=None, informa-
                                                tion_source=None, relationship=None)
    Bases: stix.common.related._BaseRelated

class stix.common.related.RelatedIndicator (item=None, confidence=None, informa-
                                                tion_source=None, relationship=None)
    Bases: stix.common.related._BaseRelated

class stix.common.related.RelatedObservable (item=None, confidence=None, informa-
                                                tion_source=None, relationship=None)
    Bases: stix.common.related._BaseRelated

class stix.common.related.RelatedThreatActor (item=None, confidence=None, informa-
                                                tion_source=None, relationship=None)
    Bases: stix.common.related._BaseRelated

class stix.common.related.RelatedTTP (item=None, confidence=None, information_source=None,
                                         relationship=None)
    Bases: stix.common.related._BaseRelated

class stix.common.related.RelatedReports (scope=None, *args)
    Bases: stix.common.related.GenericRelationshipList

class stix.common.related.RelatedReport (item=None, confidence=None, informa-
                                                tion_source=None, relationship=None)
    Bases: stix.common.related._BaseRelated

```

Version: 1.2.0.5.dev0

## stix.common.statement Module

### Classes

```

class stix.common.statement.Statement (value=None, timestamp=None, description=None,
                                         source=None)
    Bases: stix.base.Entity

add_description (description)
    Adds a description to the descriptions collection.
    This is the same as calling “foo.descriptions.add(bar)”.

description
    A single description about the contents or purpose of this object.
    Default Value: None

```

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**Version:** 1.2.0.5.dev0

## `stix.common.structured_text` Module

### Classes

**class** `stix.common.structured_text.StructuredText` (*value=None, ordinality=None*)  
Bases: `stix.base.Entity`

Used for storing descriptive text elements.

**id\_**

An id for the text element, typically used for controlled structure xpath selectors.

**value**

The text value of this object.

**structuring\_format**

The format of the text. For example, `html5`.

**\_\_str\_\_** ()

Returns a UTF-8 encoded string representation of the `value`.

**\_\_unicode\_\_** ()

Returns a `unicode` string representation of the `value`.

**to\_dict** ()

Converts this object into a dictionary representation.

---

**Note:** If no properties or attributes are set other than `value`, this will return a string.

---

**to\_obj** (*ns\_info=None*)

Convert to a GenerateDS binding object.

Subclasses can override this function.

**Returns** An instance of this Entity's `_binding_class` with properties set from this Entity.

**class** `stix.common.structured_text.StructuredTextList` (*\*args*)  
Bases: `stix.base.TypedCollection, _abcoll.Sequence`

A sequence type used to store `StructureText` objects.

**Parameters** *\*args* – A variable-length argument list which can contain single *StructuredText* objects or sequences of objects.

**\_\_delitem\_\_** (*key*)

Removes the item with a given ordinality.

**Parameters** *key* – An ordinality value.

**Raises** `KeyError` – If the *key* does not match the ordinality for any object in the collection.

`__getitem__ (key)`

Returns the *StructuredText* object with a matching ordinality.

**Parameters** `key` – An ordinality value.

**Raises** `KeyError` – If `key` does not match the ordinality of any *StructuredText* object.

`__iter__ ()`

Returns an iterator for the collection sorted by ordinality.

`add (value)`

Adds the *StructuredText* `value` to the collection.

If `value` is not a *StructuredText* object, an attempt will be made to convert it to one.

---

**Note:** If `value` does not have an `ordinality` set, one will be assigned. If `value` has an ordinality which matches one already in the collection, `value` will replace the existing item.

---

**Parameters** `value` – A *StructuredText* object.

`insert (value)`

Inserts `value` into the collection.

If `value` has an ordinality which conflicts with an existing value, the existing value (and any contiguous values) will have their ordinality values incremented by one.

`next_ordinality`

Returns the “+1” of the highest ordinality in the collection.

`remove (value)`

Removes the value from the collection.

`reset ()`

Assigns sequential ordinality values to each of the sorted *StructuredText* objects, starting with 1 and ending at `len (self)`.

`sorted`

Returns a copy of the collection of internal *StructuredText* objects, sorted by their `ordinality`.

`to_dict ()`

Returns a list of dictionary representations of the contained objects.

An attempt is made to flatten out the returned list when there is only one item in the collection. This is to support backwards compatibility with previous versions of python-stix.

- If the list repr has more than one item, return the list.
- If there is only one item, inspect it.
  - If the item is not a dictionary, return it.
  - If its `ordinality` key has a corresponding value of 1, remove it from the dictionary since it’s assumed if there is only one item.
  - After removing `ordinality`, if the only key left is `value`, just return the value of `value` (a string).

`to_obj (ns_info=None)`

Returns a binding object list for the *StructuredTextList*.

If the list has a length of 1, and its member has an ordinality of 1, the ordinality will be unset.

**update** (*iterable*)

Adds each item of *iterable* to the collection.

---

**Note:** Any existing objects with conflicting ordinality values will be overwritten.

---

**Parameters** *iterable* – An iterable collection of *StructuredText* objects to add to this collection.

**Version:** 1.2.0.5.dev0

## **stix.common.tools Module**

### **Classes**

**class** `stix.common.tools.ToolInformation` (*title=None*, *short\_description=None*,  
*tool\_name=None*, *tool\_vendor=None*)

Bases: *stix.base.Entity*, `cybox.common.tools.ToolInformation`

**add\_short\_description** (*description*)

Adds a description to the `short_descriptions` collection.

This is the same as calling “`foo.short_descriptions.add(bar)`”.

**short\_description**

A single short description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one short description set, this will return the short description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**Version:** 1.2.0.5.dev0

## **stix.common.vocabs Module**

### **Classes**

**class** `stix.common.vocabs.AssetType_1_0` (*value=None*)

Bases: *stix.common.vocabs.VocabString*

**TERM\_ACCESS\_READER** = ‘Access reader’

**TERM\_ADMINISTRATOR** = ‘Administrator’

**TERM\_ATM** = ‘ATM’

**TERM\_AUDITOR** = ‘Auditor’

**TERM\_AUTH\_TOKEN** = ‘Auth token’

**TERM\_BACKUP** = ‘Backup’

**TERM\_BROADBAND** = ‘Broadband’



TERM\_CALL\_CENTER = 'Call center'  
TERM\_CAMERA = 'Camera'  
TERM\_CASHIER = 'Cashier'  
TERM\_CUSTOMER = 'Customer'  
TERM\_DATABASE = 'Database'  
TERM\_DCS = 'DCS'  
TERM\_DESKTOP = 'Desktop'  
TERM\_DEVELOPER = 'Developer'  
TERM\_DHCP = 'DHCP'  
TERM\_DIRECTORY = 'Directory'  
TERM\_DISK\_DRIVE = 'Disk drive'  
TERM\_DISK\_MEDIA = 'Disk media'  
TERM\_DNS = 'DNS'  
TERM\_DOCUMENTS = 'Documents'  
TERM\_ENDUSER = 'End-user'  
TERM\_EXECUTIVE = 'Executive'  
TERM\_FILE = 'File'  
TERM\_FINANCE = 'Finance'  
TERM\_FIREWALL = 'Firewall'  
TERM\_FLASH\_DRIVE = 'Flash drive'  
TERM\_FORMER\_EMPLOYEE = 'Former employee'  
TERM\_GAS\_TERMINAL = 'Gas terminal'  
TERM\_GUARD = 'Guard'  
TERM\_HELPDESK = 'Helpdesk'  
TERM\_HSM = 'HSM'  
TERM\_HUMAN\_RESOURCES = 'Human resources'  
TERM\_IDS = 'IDS'  
TERM\_KIOSK = 'Kiosk'  
TERM\_LAN = 'LAN'  
TERM\_LAPTOP = 'Laptop'  
TERM\_LOG = 'Log'  
TERM\_MAIL = 'Mail'  
TERM\_MAINFRAME = 'Mainframe'  
TERM\_MAINTENANCE = 'Maintenance'  
TERM\_MANAGER = 'Manager'  
TERM\_MEDIA = 'Media'

```
TERM_MOBILE_PHONE = 'Mobile phone'  
TERM_NETWORK = 'Network'  
TERM_PARTNER = 'Partner'  
TERM_PAYMENT_CARD = 'Payment card'  
TERM_PAYMENT_SWITCH = 'Payment switch'  
TERM_PBX = 'PBX'  
TERM_PED_PAD = 'PED pad'  
TERM_PERIPHERAL = 'Peripheral'  
TERM_PERSON = 'Person'  
TERM_PLC = 'PLC'  
TERM_POS_CONTROLLER = 'POS controller'  
TERM_POS_TERMINAL = 'POS terminal'  
TERM_PRINT = 'Print'  
TERM_PRIVATE_WAN = 'Private WAN'  
TERM_PROXY = 'Proxy'  
TERM_PUBLIC_WAN = 'Public WAN'  
TERM_REMOTE_ACCESS = 'Remote access'  
TERM_ROUTER_OR_SWITCH = 'Router or switch'  
TERM_RTU = 'RTU'  
TERM_SAN = 'SAN'  
TERM_SCADA = 'SCADA'  
TERM_SERVER = 'Server'  
TERM_SMART_CARD = 'Smart card'  
TERM_TABLET = 'Tablet'  
TERM_TAPES = 'Tapes'  
TERM_TELEPHONE = 'Telephone'  
TERM_UNKNOWN = 'Unknown'  
TERM_USER_DEVICE = 'User Device'  
TERM_VOIP_ADAPTER = 'VoIP adapter'  
TERM_VOIP_PHONE = 'VoIP phone'  
TERM_WEB_APPLICATION = 'Web application'  
TERM_WLAN = 'WLAN'
```

```
class stix.common.vocabs.AttackerInfrastructureType_1_0 (value=None)  
    Bases: stix.common.vocabs.VocabString
```

```
TERM_ANONYMIZATION = 'Anonymization'  
TERM_ANONYMIZATION_PROXY = 'Anonymization - Proxy'
```

```

TERM_ANONYMIZATION_TOR_NETWORK = 'Anonymization - TOR Network'
TERM_ANONYMIZATION_VPN = 'Anonymization - VPN'
TERM_COMMUNICATIONS = 'Communications'
TERM_COMMUNICATIONS_BLOGS = 'Communications - Blogs'
TERM_COMMUNICATIONS_FORUMS = 'Communications - Forums'
TERM_COMMUNICATIONS_INTERNET_RELAY_CHAT = 'Communications - Internet Relay Chat'
TERM_COMMUNICATIONS_MICROBLOGS = 'Communications - Micro-Blogs'
TERM_COMMUNICATIONS_MOBILE_COMMUNICATIONS = 'Communications - Mobile Communications'
TERM_COMMUNICATIONS_SOCIAL_NETWORKS = 'Communications - Social Networks'
TERM_COMMUNICATIONS_USERGENERATED_CONTENT_WEBSITES = 'Communications - User-Generated Content We
TERM_DOMAIN_REGISTRATION = 'Domain Registration'
TERM_DOMAIN_REGISTRATION_DYNAMIC_DNS_SERVICES = 'Domain Registration - Dynamic DNS Services'
TERM_DOMAIN_REGISTRATION_LEGITIMATE_DOMAIN_REGISTRATION_SERVICES = 'Domain Registration - Legit
TERM_DOMAIN_REGISTRATION_MALICIOUS_DOMAIN_REGISTRARS = 'Domain Registration - Malicious Domain Re
TERM_DOMAIN_REGISTRATION_TOPLLEVEL_DOMAIN_REGISTRARS = 'Domain Registration - Top-Level Domain Regi
TERM_ELECTRONIC_PAYMENT_METHODS = 'Electronic Payment Methods'
TERM_HOSTING = 'Hosting'
TERM_HOSTING_BULLETPROOF_OR_ROGUE_HOSTING = 'Hosting - Bulletproof / Rogue Hosting'
TERM_HOSTING_CLOUD_HOSTING = 'Hosting - Cloud Hosting'
TERM_HOSTING_COMPROMISED_SERVER = 'Hosting - Compromised Server'
TERM_HOSTING_FAST_FLUX_BOTNET_HOSTING = 'Hosting - Fast Flux Botnet Hosting'
TERM_HOSTING_LEGITIMATE_HOSTING = 'Hosting - Legitimate Hosting'
class stix.common.vocabs.AttackerToolType_1_0 (value=None)
  Bases: stix.common.vocabs.VocabString
  TERM_APPLICATION_SCANNER = 'Application Scanner'
  TERM_MALWARE = 'Malware'
  TERM_PASSWORD_CRACKING = 'Password Cracking'
  TERM_PENETRATION_TESTING = 'Penetration Testing'
  TERM_PORT_SCANNER = 'Port Scanner'
  TERM_TRAFFIC_SCANNER = 'Traffic Scanner'
  TERM_VULNERABILITY_SCANNER = 'Vulnerability Scanner'
class stix.common.vocabs.AvailabilityLossType_1_0 (value=None)
  Bases: stix.common.vocabs.VocabString
  TERM_ACCELERATION = 'Acceleration'
  TERM_DEGREDDATION = 'Degredation'
  TERM_DESTRUCTION = 'Destruction'
  TERM_INTERRUPTION = 'Interruption'

```

```
TERM_LOSS = 'Loss'
TERM_OBSCURATION = 'Obscuration'
TERM_UNKNOWN = 'Unknown'
class stix.common.vocabs.AvailabilityLossType_1_1_1 (value=None)
    Bases: stix.common.vocabs.VocabString
    TERM_ACCELERATION = 'Acceleration'
    TERM_DEGRADATION = 'Degradation'
    TERM_DESTRUCTION = 'Destruction'
    TERM_INTERRUPTION = 'Interruption'
    TERM_LOSS = 'Loss'
    TERM_OBSCURATION = 'Obscuration'
    TERM_UNKNOWN = 'Unknown'
class stix.common.vocabs.COASTage_1_0 (value=None)
    Bases: stix.common.vocabs.VocabString
    TERM_REMEDY = 'Remedy'
    TERM_RESPONSE = 'Response'
class stix.common.vocabs.CampaignStatus_1_0 (value=None)
    Bases: stix.common.vocabs.VocabString
    TERM_FUTURE = 'Future'
    TERM_HISTORIC = 'Historic'
    TERM_ONGOING = 'Ongoing'
class stix.common.vocabs.CourseOfActionType_1_0 (value=None)
    Bases: stix.common.vocabs.VocabString
    TERM_DIPLOMATIC_ACTIONS = 'Diplomatic Actions'
    TERM_ERADICATION = 'Eradication'
    TERM_HARDENING = 'Hardening'
    TERM_INTERNAL_BLOCKING = 'Internal Blocking'
    TERM_LOGICAL_ACCESS_RESTRICTIONS = 'Logical Access Restrictions'
    TERM_MONITORING = 'Monitoring'
    TERM_OTHER = 'Other'
    TERM_PATCHING = 'Patching'
    TERM_PERIMETER_BLOCKING = 'Perimeter Blocking'
    TERM_PHYSICAL_ACCESS_RESTRICTIONS = 'Physical Access Restrictions'
    TERM_POLICY_ACTIONS = 'Policy Actions'
    TERM_PUBLIC_DISCLOSURE = 'Public Disclosure'
    TERM_REBUILDING = 'Rebuilding'
    TERM_REDIRECTION = 'Redirection'
```

```

TERM_REDIRECTION_HONEY_POT = 'Redirection (Honey Pot)'
TERM_TRAINING = 'Training'
class stix.common.vocabs.DiscoveryMethod_1_0 (value=None)
  Bases: stix.common.vocabs.VocabString
TERM_AGENT_DISCLOSURE = 'Agent Disclosure'
TERM_ANTIVIRUS = 'Antivirus'
TERM_AUDIT = 'Audit'
TERM_CUSTOMER = 'Customer'
TERM_FINANCIAL_AUDIT = 'Financial Audit'
TERM_FRAUD_DETECTION = 'Fraud Detection'
TERM_HIPS = 'HIPS'
TERM_INCIDENT_RESPONSE = 'Incident Response'
TERM_IT_AUDIT = 'IT Audit'
TERM_LAW_ENFORCEMENT = 'Law Enforcement'
TERM_LOG_REVIEW = 'Log Review'
TERM_MONITORING_SERVICE = 'Monitoring Service'
TERM_NIDS = 'NIDS'
TERM_SECURITY_ALARM = 'Security Alarm'
TERM_UNKNOWN = 'Unknown'
TERM_UNRELATED_PARTY = 'Unrelated Party'
TERM_USER = 'User'
class stix.common.vocabs.DiscoveryMethod_2_0 (value=None)
  Bases: stix.common.vocabs.VocabString
TERM_AGENT_DISCLOSURE = 'Agent Disclosure'
TERM_ANTIVIRUS = 'Antivirus'
TERM_AUDIT = 'Audit'
TERM_CUSTOMER = 'Customer'
TERM_EXTERNAL_FRAUD_DETECTION = 'External - Fraud Detection'
TERM_FINANCIAL_AUDIT = 'Financial Audit'
TERM_HIPS = 'HIPS'
TERM_INCIDENT_RESPONSE = 'Incident Response'
TERM_INTERNAL_FRAUD_DETECTION = 'Internal - Fraud Detection'
TERM_IT_AUDIT = 'IT Audit'
TERM_LAW_ENFORCEMENT = 'Law Enforcement'
TERM_LOG_REVIEW = 'Log Review'
TERM_MONITORING_SERVICE = 'Monitoring Service'
TERM_NIDS = 'NIDS'

```

```
TERM_SECURITY_ALARM = 'Security Alarm'
TERM_UNKNOWN = 'Unknown'
TERM_UNRELATED_PARTY = 'Unrelated Party'
TERM_USER = 'User'
class stix.common.vocabs.HighMediumLow_1_0 (value=None)
  Bases: stix.common.vocabs.VocabString
  TERM_HIGH = 'High'
  TERM_LOW = 'Low'
  TERM_MEDIUM = 'Medium'
  TERM_NONE = 'None'
  TERM_UNKNOWN = 'Unknown'
class stix.common.vocabs.ImpactQualification_1_0 (value=None)
  Bases: stix.common.vocabs.VocabString
  TERM_CATASTROPHIC = 'Catastrophic'
  TERM_DAMAGING = 'Damaging'
  TERM_DISTRACTING = 'Distracting'
  TERM_INSIGNIFICANT = 'Insignificant'
  TERM_PAINFUL = 'Painful'
  TERM_UNKNOWN = 'Unknown'
class stix.common.vocabs.ImpactRating_1_0 (value=None)
  Bases: stix.common.vocabs.VocabString
  TERM_MAJOR = 'Major'
  TERM_MINOR = 'Minor'
  TERM_MODERATE = 'Moderate'
  TERM_NONE = 'None'
  TERM_UNKNOWN = 'Unknown'
class stix.common.vocabs.IncidentCategory_1_0 (value=None)
  Bases: stix.common.vocabs.VocabString
  TERM_DENIAL_OF_SERVICE = 'Denial of Service'
  TERM_EXERCISEORNETWORK_DEFENSE_TESTING = 'Exercise/Network Defense Testing'
  TERM_IMPROPER_USAGE = 'Improper Usage'
  TERM_INVESTIGATION = 'Investigation'
  TERM_MALICIOUS_CODE = 'Malicious Code'
  TERM_SCANSORPROBESORATTEMPTED_ACCESS = 'Scans/Probes/Attempted Access'
  TERM_UNAUTHORIZED_ACCESS = 'Unauthorized Access'
class stix.common.vocabs.IncidentEffect_1_0 (value=None)
  Bases: stix.common.vocabs.VocabString
  TERM_BRAND_OR_IMAGE_DEGRADATION = 'Brand or Image Degradation'
```

```

TERM_DATA_BREACH_OR_COMPROMISE = 'Data Breach or Compromise'
TERM_DEGRADATION_OF_SERVICE = 'Degradation of Service'
TERM_DESTRUCTION = 'Destruction'
TERM_DISRUPTION_OF_SERVICE_OR_OPERATIONS = 'Disruption of Service / Operations'
TERM_FINANCIAL_LOSS = 'Financial Loss'
TERM_LOSS_OF_COMPETITIVE_ADVANTAGE = 'Loss of Competitive Advantage'
TERM_LOSS_OF_COMPETITIVE_ADVANTAGE_ECONOMIC = 'Loss of Competitive Advantage - Economic'
TERM_LOSS_OF_COMPETITIVE_ADVANTAGE_MILITARY = 'Loss of Competitive Advantage - Military'
TERM_LOSS_OF_COMPETITIVE_ADVANTAGE_POLITICAL = 'Loss of Competitive Advantage - Political'
TERM_LOSS_OF_CONFIDENTIAL_OR_PROPRIETARY_INFORMATION_OR_INTELLECTUAL_PROPERTY = 'Loss of C
TERM_REGULATORY_COMPLIANCE_OR_LEGAL_IMPACT = 'Regulatory, Compliance or Legal Impact'
TERM_UNINTENDED_ACCESS = 'Unintended Access'
TERM_USER_DATA_LOSS = 'User Data Loss'

class stix.common.vocabs.IncidentStatus_1_0 (value=None)
    Bases: stix.common.vocabs.VocabString
TERM_CLOSED = 'Closed'
TERM_CONTAINMENT_ACHIEVED = 'Containment Achieved'
TERM_DELETED = 'Deleted'
TERM_INCIDENT_REPORTED = 'Incident Reported'
TERM_NEW = 'New'
TERM_OPEN = 'Open'
TERM_REJECTED = 'Rejected'
TERM_RESTITUTION_ACHIEVED = 'Restoration Achieved'
TERM_STALLED = 'Stalled'

class stix.common.vocabs.IndicatorType_1_0 (value=None)
    Bases: stix.common.vocabs.VocabString
TERM_ANONYMIZATION = 'Anonymization'
TERM_C2 = 'C2'
TERM_DOMAIN_WATCHLIST = 'Domain Watchlist'
TERM_EXFILTRATION = 'Exfiltration'
TERM_FILE_HASH_WATCHLIST = 'File Hash Watchlist'
TERM_HOST_CHARACTERISTICS = 'Host Characteristics'
TERM_IP_WATCHLIST = 'IP Watchlist'
TERM_MALICIOUS_EMAIL = 'Malicious E-mail'
TERM_MALWARE_ARTIFACTS = 'Malware Artifacts'
TERM_URL_WATCHLIST = 'URL Watchlist'

```

```
class stix.common.vocabs.IndicatorType_1_1 (value=None)
    Bases: stix.common.vocabs.VocabString
```

```
    TERM_ANONYMIZATION = 'Anonymization'
```

```
    TERM_C2 = 'C2'
```

```
    TERM_COMPROMISED_PKI_CERTIFICATE = 'Compromised PKI Certificate'
```

```
    TERM_DOMAIN_WATCHLIST = 'Domain Watchlist'
```

```
    TERM_EXFILTRATION = 'Exfiltration'
```

```
    TERM_FILE_HASH_WATCHLIST = 'File Hash Watchlist'
```

```
    TERM_HOST_CHARACTERISTICS = 'Host Characteristics'
```

```
    TERM_IMEI_WATCHLIST = 'IMEI Watchlist'
```

```
    TERM_IMSI_WATCHLIST = 'IMSI Watchlist'
```

```
    TERM_IP_WATCHLIST = 'IP Watchlist'
```

```
    TERM_LOGIN_NAME = 'Login Name'
```

```
    TERM_MALICIOUS_EMAIL = 'Malicious E-mail'
```

```
    TERM_MALWARE_ARTIFACTS = 'Malware Artifacts'
```

```
    TERM_URL_WATCHLIST = 'URL Watchlist'
```

```
class stix.common.vocabs.InformationSourceRole_1_0 (value=None)
    Bases: stix.common.vocabs.VocabString
```

```
    TERM_AGGREGATOR = 'Aggregator'
```

```
    TERM_CONTENT_ENHANCERORREFINER = 'Content Enhancer/Refiner'
```

```
    TERM_INITIAL_AUTHOR = 'Initial Author'
```

```
    TERM_TRANSFORMERORTRANSLATOR = 'Transformer/Translator'
```

```
class stix.common.vocabs.InformationType_1_0 (value=None)
    Bases: stix.common.vocabs.VocabString
```

```
    TERM_AUTHENTICATION_COOKIES = 'Authentication Cookies'
```

```
    TERM_INFORMATION_ASSETS = 'Information Assets'
```

```
    TERM_INFORMATION_ASSETS_CORPORATE_EMPLOYEE_INFORMATION = 'Information Assets - Corporate Employee Information'
```

```
    TERM_INFORMATION_ASSETS_CUSTOMER_PII = 'Information Assets - Customer PII'
```

```
    TERM_INFORMATION_ASSETS_EMAIL_LISTS_OR_ARCHIVES = 'Information Assets - Email Lists / Archives'
```

```
    TERM_INFORMATION_ASSETS_FINANCIAL_DATA = 'Information Assets - Financial Data'
```

```
    TERM_INFORMATION_ASSETS_INTELLECTUAL_PROPERTY = 'Information Assets - Intellectual Property'
```

```
    TERM_INFORMATION_ASSETS_MOBILE_PHONE_CONTACTS = 'Information Assets - Mobile Phone Contacts'
```

```
    TERM_INFORMATION_ASSETS_USER_CREDENTIALS = 'Information Assets - User Credentials'
```

```
class stix.common.vocabs.IntendedEffect_1_0 (value=None)
    Bases: stix.common.vocabs.VocabString
```

```
    TERM_ACCOUNT_TAKEOVER = 'Account Takeover'
```

```
    TERM_ADVANTAGE = 'Advantage'
```



```

TERM_ADVANTAGE_ECONOMIC = 'Advantage - Economic'
TERM_ADVANTAGE_MILITARY = 'Advantage - Military'
TERM_ADVANTAGE_POLITICAL = 'Advantage - Political'
TERM_BRAND_DAMAGE = 'Brand Damage'
TERM_COMPETITIVE_ADVANTAGE = 'Competitive Advantage'
TERM_DEGRADATION_OF_SERVICE = 'Degradation of Service'
TERM_DENIAL_AND_DECEPTION = 'Denial and Deception'
TERM_DESTRUCTION = 'Destruction'
TERM_DISRUPTION = 'Disruption'
TERM_EMBARRASSMENT = 'Embarrassment'
TERM_EXPOSURE = 'Exposure'
TERM_EXTORTION = 'Extortion'
TERM_FRAUD = 'Fraud'
TERM_HARASSMENT = 'Harassment'
TERM_ICS_CONTROL = 'ICS Control'
TERM_THEFT = 'Theft'
TERM_THEFT_CREDENTIAL_THEFT = 'Theft - Credential Theft'
TERM_THEFT_IDENTITY_THEFT = 'Theft - Identity Theft'
TERM_THEFT_INTELLECTUAL_PROPERTY = 'Theft - Intellectual Property'
TERM_THEFT_THEFT_OF_PROPRIETARY_INFORMATION = 'Theft - Theft of Proprietary Information'
TERM_TRAFFIC_DIVERSION = 'Traffic Diversion'
TERM_UNAUTHORIZED_ACCESS = 'Unauthorized Access'
class stix.common.vocabs.LocationClass_1_0 (value=None)
  Bases: stix.common.vocabs.VocabString
TERM_COLOCATED = 'Co-Located'
TERM_EXTERNALLYLOCATED = 'Externally-Located'
TERM_INTERNALLYLOCATED = 'Internally-Located'
TERM_MOBILE = 'Mobile'
TERM_UNKNOWN = 'Unknown'
class stix.common.vocabs.LossDuration_1_0 (value=None)
  Bases: stix.common.vocabs.VocabString
TERM_DAYS = 'Days'
TERM_HOURS = 'Hours'
TERM_MINUTES = 'Minutes'
TERM_PERMANENT = 'Permanent'
TERM_SECONDS = 'Seconds'
TERM_UNKNOWN = 'Unknown'

```

```
    TERM_WEEKS = 'Weeks'

class stix.common.vocabs.LossProperty_1_0 (value=None)
    Bases: stix.common.vocabs.VocabString

    TERM_ACCOUNTABILITY = 'Accountability'

    TERM_AVAILABILITY = 'Availability'

    TERM_CONFIDENTIALITY = 'Confidentiality'

    TERM_INTEGRITY = 'Integrity'

    TERM_NONREPUDIATION = 'Non-Repudiation'

class stix.common.vocabs.MalwareType_1_0 (value=None)
    Bases: stix.common.vocabs.VocabString

    TERM_ADWARE = 'Adware'

    TERM_AUTOMATED_TRANSFER_SCRIPTS = 'Automated Transfer Scripts'

    TERM_BOT = 'Bot'

    TERM_BOT_CREDENTIAL_THEFT = 'Bot - Credential Theft'

    TERM_BOT_DDOS = 'Bot - DDoS'

    TERM_BOT_LOADER = 'Bot - Loader'

    TERM_BOT_SPAM = 'Bot - Spam'

    TERM_DIALER = 'Dialer'

    TERM_DOS_OR_DDOS = 'DoS / DDoS'

    TERM_DOS_OR_DDOS_PARTICIPATORY = 'DoS / DDoS - Participatory'

    TERM_DOS_OR_DDOS_SCRIPT = 'DoS / DDoS - Script'

    TERM_DOS_OR_DDOS_STRESS_TEST_TOOLS = 'DoS / DDoS - Stress Test Tools'

    TERM_EXPLOIT_KITS = 'Exploit Kits'

    TERM_POS_OR_ATM_MALWARE = 'POS / ATM Malware'

    TERM_RANSOMWARE = 'Ransomware'

    TERM_REMOTE_ACCESS_TROJAN = 'Remote Access Trojan'

    TERM_ROGUE_ANTIVIRUS = 'Rogue Antivirus'

    TERM_ROOTKIT = 'Rootkit'

class stix.common.vocabs.ManagementClass_1_0 (value=None)
    Bases: stix.common.vocabs.VocabString

    TERM_COMANAGEMENT = 'Co-Management'

    TERM_EXTERNALLYMANAGEMENT = 'Externally-Management'

    TERM_INTERNALLYMANAGED = 'Internally-Managed'

    TERM_UNKNOWN = 'Unknown'

class stix.common.vocabs.Motivation_1_0 (value=None)
    Bases: stix.common.vocabs.VocabString

    TERM_EGO = 'Ego'
```

```

TERM_FINANCIAL_OR_ECONOMIC = 'Financial or Economic'
TERM_IDEOLOGICAL = 'Ideological'
TERM_IDEOLOGICAL_ANTICORRUPTION = 'Ideological - Anti-Corruption'
TERM_IDEOLOGICAL_ANTIESTABLISHMENT = 'Ideological - Anti-Establishment'
TERM_IDEOLOGICAL_ENVIRONMENTAL = 'Ideological - Environmental'
TERM_IDEOLOGICAL_ETHNIC_NATIONALIST = 'Ideological - Ethnic / Nationalist'
TERM_IDEOLOGICAL_HUMAN_RIGHTS = 'Ideological - Human Rights'
TERM_IDEOLOGICAL_INFORMATION_FREEDOM = 'Ideological - Information Freedom'
TERM_IDEOLOGICAL_RELIGIOUS = 'Ideological - Religious'
TERM_IDEOLOGICAL_SECURITY_AWARENESS = 'Ideological - Security Awareness'
TERM_MILITARY = 'Military'
TERM_OPPORTUNISTIC = 'Opportunistic'
TERM_POLICITAL = 'Policital'
class stix.common.vocabs.Motivation_1_0_1 (value=None)
  Bases: stix.common.vocabs.VocabString
TERM_EGO = 'Ego'
TERM_FINANCIAL_OR_ECONOMIC = 'Financial or Economic'
TERM_IDEOLOGICAL = 'Ideological'
TERM_IDEOLOGICAL_ANTI_CORRUPTION = 'Ideological - Anti-Corruption'
TERM_IDEOLOGICAL_ANTI_ESTABLISHMENT = 'Ideological - Anti-Establishment'
TERM_IDEOLOGICAL_ENVIRONMENTAL = 'Ideological - Environmental'
TERM_IDEOLOGICAL_ETHNIC_NATIONALIST = 'Ideological - Ethnic / Nationalist'
TERM_IDEOLOGICAL_HUMAN_RIGHTS = 'Ideological - Human Rights'
TERM_IDEOLOGICAL_INFORMATION_FREEDOM = 'Ideological - Information Freedom'
TERM_IDEOLOGICAL_SECURITY_AWARENESS = 'Ideological - Security Awareness'
TERM_IDEOLOGICAL_RELIGIOUS = 'Ideological - Religious'
TERM_MILITARY = 'Military'
TERM_OPPORTUNISTIC = 'Opportunistic'
TERM_POLICITAL = 'Policital'
class stix.common.vocabs.Motivation_1_1 (value=None)
  Bases: stix.common.vocabs.VocabString
TERM_EGO = 'Ego'
TERM_FINANCIAL_OR_ECONOMIC = 'Financial or Economic'
TERM_IDEOLOGICAL = 'Ideological'
TERM_IDEOLOGICAL_ANTICORRUPTION = 'Ideological - Anti-Corruption'
TERM_IDEOLOGICAL_ANTIESTABLISHMENT = 'Ideological - Anti-Establishment'
TERM_IDEOLOGICAL_ENVIRONMENTAL = 'Ideological - Environmental'

```

```
TERM_IDEOLOGICAL_ETHNIC_NATIONALIST = 'Ideological - Ethnic / Nationalist'  
TERM_IDEOLOGICAL_HUMAN_RIGHTS = 'Ideological - Human Rights'  
TERM_IDEOLOGICAL_INFORMATION_FREEDOM = 'Ideological - Information Freedom'  
TERM_IDEOLOGICAL_RELIGIOUS = 'Ideological - Religious'  
TERM_IDEOLOGICAL_SECURITY_AWARENESS = 'Ideological - Security Awareness'  
TERM_MILITARY = 'Military'  
TERM_OPPORTUNISTIC = 'Opportunistic'  
TERM_POLITICAL = 'Political'
```

```
class stix.common.vocabs.OwnershipClass_1_0 (value=None)  
    Bases: stix.common.vocabs.VocabString
```

```
TERM_CUSTOMEROWNED = 'Customer-Owned'  
TERM_EMPLOYEEOWNED = 'Employee-Owned'  
TERM_INTERNALLYOWNED = 'Internally-Owned'  
TERM_PARTNEROWNED = 'Partner-Owned'  
TERM_UNKNOWN = 'Unknown'
```

```
class stix.common.vocabs.PackageIntent_1_0 (value=None)  
    Bases: stix.common.vocabs.VocabString
```

```
TERM_ATTACK_PATTERN_CHARACTERIZATION = 'Attack Pattern Characterization'  
TERM_CAMPAIGN_CHARACTERIZATION = 'Campaign Characterization'  
TERM_COLLECTIVE_THREAT_INTELLIGENCE = 'Collective Threat Intelligence'  
TERM_COURSES_OF_ACTION = 'Courses of Action'  
TERM_EXPLOIT_CHARACTERIZATION = 'Exploit Characterization'  
TERM_INCIDENT = 'Incident'  
TERM_INDICATORS = 'Indicators'  
TERM_INDICATORS_ENDPOINT_CHARACTERISTICS = 'Indicators - Endpoint Characteristics'  
TERM_INDICATORS_MALWARE_ARTIFACTS = 'Indicators - Malware Artifacts'  
TERM_INDICATORS_NETWORK_ACTIVITY = 'Indicators - Network Activity'  
TERM_INDICATORS_PHISHING = 'Indicators - Phishing'  
TERM_INDICATORS_WATCHLIST = 'Indicators - Watchlist'  
TERM_MALWARE_CHARACTERIZATION = 'Malware Characterization'  
TERM_MALWARE_SAMPLES = 'Malware Samples'  
TERM_OBSERVATIONS = 'Observations'  
TERM_OBSERVATIONS_EMAIL = 'Observations - Email'  
TERM_THREAT_ACTOR_CHARACTERIZATION = 'Threat Actor Characterization'  
TERM_THREAT_REPORT = 'Threat Report'  
TERM_TTP_INFRASTRUCTURE = 'TTP - Infrastructure'  
TERM_TTP_TOOLS = 'TTP - Tools'
```

```
class stix.common.vocabs.PlanningAndOperationalSupport_1_0 (value=None)
```

```
    Bases: stix.common.vocabs.VocabString
```

```
    TERM_DATA_EXPLOITATION = 'Data Exploitation'
```

```
    TERM_DATA_EXPLOITATION_ANALYTIC_SUPPORT = 'Data Exploitation - Analytic Support'
```

```
    TERM_DATA_EXPLOITATION_TRANSLATION_SUPPORT = 'Data Exploitation - Translation Support'
```

```
    TERM_FINANCIAL_RESOURCES = 'Financial Resources'
```

```
    TERM_FINANCIAL_RESOURCES_ACADEMIC = 'Financial Resources - Academic'
```

```
    TERM_FINANCIAL_RESOURCES_COMMERCIAL = 'Financial Resources - Commercial'
```

```
    TERM_FINANCIAL_RESOURCES_GOVERNMENT = 'Financial Resources - Government'
```

```
    TERM_FINANCIAL_RESOURCES_HACKTIVIST_OR_GRASSROOT = 'Financial Resources - Hactivist or Grassroot'
```

```
    TERM_FINANCIAL_RESOURCES_NONATTRIBUTABLE_FINANCE = 'Financial Resources - Non-Attributable Finance'
```

```
    TERM_PLANNING = 'Planning'
```

```
    TERM_PLANNING_OPEN_SOURCE_INTELLIGENCE_OSINT_GATHERING = 'Planning - Open-Source Intelligence (OSINT)'
```

```
    TERM_PLANNING_OPERATIONAL_COVER_PLAN = 'Planning - Operational Cover Plan'
```

```
    TERM_PLANNING_PRE_OPERATIONAL_SURVEILLANCE_AND_RECONNAISSANCE = 'Planning - Pre-Operational Surveillance and Reconnaissance'
```

```
    TERM_PLANNING_TARGET_SELECTION = 'Planning - Target Selection'
```

```
    TERM_SKILL_DEVELOPMENT_RECRUITMENT = 'Skill Development / Recruitment'
```

```
    TERM_SKILL_DEVELOPMENT_RECRUITMENT_CONTRACTING_AND_HIRING = 'Skill Development / Recruitment - Contracting and Hiring'
```

```
    TERM_SKILL_DEVELOPMENT_RECRUITMENT_DOCUMENT_EXPLOITATION_DOCEX_TRAINING = 'Skill Development / Recruitment - Document Exploitation DoCEX Training'
```

```
    TERM_SKILL_DEVELOPMENT_RECRUITMENT_INTERNAL_TRAINING = 'Skill Development / Recruitment - Internal Training'
```

```
    TERM_SKILL_DEVELOPMENT_RECRUITMENT_MILITARY_PROGRAMS = 'Skill Development / Recruitment - Military Programs'
```

```
    TERM_SKILL_DEVELOPMENT_RECRUITMENT_SECURITY_HACKER_CONFERENCES = 'Skill Development / Recruitment - Security Hacker Conferences'
```

```
    TERM_SKILL_DEVELOPMENT_RECRUITMENT_UNDERGROUND_FORUMS = 'Skill Development / Recruitment - Underground Forums'
```

```
    TERM_SKILL_DEVELOPMENT_RECRUITMENT_UNIVERSITY_PROGRAMS = 'Skill Development / Recruitment - University Programs'
```

```
class stix.common.vocabs.PlanningAndOperationalSupport_1_0_1 (value=None)
```

```
    Bases: stix.common.vocabs.VocabString
```

```
    TERM_DATA_EXPLOITATION = 'Data Exploitation'
```

```
    TERM_DATA_EXPLOITATION_ANALYTIC_SUPPORT = 'Data Exploitation - Analytic Support'
```

```
    TERM_DATA_EXPLOITATION_TRANSLATION_SUPPORT = 'Data Exploitation - Translation Support'
```

```
    TERM_FINANCIAL_RESOURCES = 'Financial Resources'
```

```
    TERM_FINANCIAL_RESOURCES_ACADEMIC = 'Financial Resources - Academic'
```

```
    TERM_FINANCIAL_RESOURCES_COMMERCIAL = 'Financial Resources - Commercial'
```

```
    TERM_FINANCIAL_RESOURCES_GOVERNMENT = 'Financial Resources - Government'
```

```
    TERM_FINANCIAL_RESOURCES_HACKTIVIST_OR_GRASSROOT = 'Financial Resources - Hactivist or Grassroot'
```

```
    TERM_FINANCIAL_RESOURCES_NONATTRIBUTABLE_FINANCE = 'Financial Resources - Non-Attributable Finance'
```

```
    TERM_PLANNING = 'Planning'
```

```
    TERM_PLANNING_OPENSOURCE_INTELLIGENCE_OSINT_GATHERING = 'Planning - Open-Source Intelligence (OSINT)'
```

```
TERM_PLANNING_OPERATIONAL_COVER_PLAN = 'Planning - Operational Cover Plan'  
TERM_PLANNING_PREOPERATIONAL_SURVEILLANCE_AND_RECONNAISSANCE = 'Planning - Pre-Operational Surve  
TERM_PLANNING_TARGET_SELECTION = 'Planning - Target Selection'  
TERM_SKILL_DEVELOPMENT_OR_RECRUITMENT = 'Skill Development / Recruitment'  
TERM_SKILL_DEVELOPMENT_OR_RECRUITMENT_CONTRACTING_AND_HIRING = 'Skill Development / Recruitment  
TERM_SKILL_DEVELOPMENT_OR_RECRUITMENT_DOCUMENT_EXPLOITATION_DOCEX_TRAINING = 'Skill Develop  
TERM_SKILL_DEVELOPMENT_OR_RECRUITMENT_INTERNAL_TRAINING = 'Skill Development / Recruitment - Intern  
TERM_SKILL_DEVELOPMENT_OR_RECRUITMENT_MILITARY_PROGRAMS = 'Skill Development / Recruitment - Milita  
TERM_SKILL_DEVELOPMENT_OR_RECRUITMENT_SECURITY_OR_HACKER_CONFERENCES = 'Skill Development / Re  
TERM_SKILL_DEVELOPMENT_OR_RECRUITMENT_UNDERGROUND_FORUMS = 'Skill Development / Recruitment - Und  
TERM_SKILL_DEVELOPMENT_OR_RECRUITMENT_UNIVERSITY_PROGRAMS = 'Skill Development / Recruitment - Un
```

```
class stix.common.vocabs.ReportIntent_1_0 (value=None)
```

```
  Bases: stix.common.vocabs.VocabString
```

```
TERM_ATTACK_PATTERN_CHARACTERIZATION = 'Attack Pattern Characterization'  
TERM_CAMPAIGN_CHARACTERIZATION = 'Campaign Characterization'  
TERM_COLLECTIVE_THREAT_INTELLIGENCE = 'Collective Threat Intelligence'  
TERM_COURSES_OF_ACTION = 'Courses of Action'  
TERM_EXPLOIT_CHARACTERIZATION = 'Exploit Characterization'  
TERM_INCIDENT = 'Incident'  
TERM_INDICATORS = 'Indicators'  
TERM_INDICATORS_ENDPOINT_CHARACTERISTICS = 'Indicators - Endpoint Characteristics'  
TERM_INDICATORS_MALWARE_ARTIFACTS = 'Indicators - Malware Artifacts'  
TERM_INDICATORS_NETWORK_ACTIVITY = 'Indicators - Network Activity'  
TERM_INDICATORS_PHISHING = 'Indicators - Phishing'  
TERM_INDICATORS_WATCHLIST = 'Indicators - Watchlist'  
TERM_MALWARE_CHARACTERIZATION = 'Malware Characterization'  
TERM_MALWARE_SAMPLES = 'Malware Samples'  
TERM_OBSERVATIONS = 'Observations'  
TERM_OBSERVATIONS_EMAIL = 'Observations - Email'  
TERM_THREAT_ACTOR_CHARACTERIZATION = 'Threat Actor Characterization'  
TERM_THREAT_REPORT = 'Threat Report'  
TERM_TTP_INFRASTRUCTURE = 'TTP - Infrastructure'  
TERM_TTP_TOOLS = 'TTP - Tools'
```

```
class stix.common.vocabs.SecurityCompromise_1_0 (value=None)
```

```
  Bases: stix.common.vocabs.VocabString
```

```
TERM_NO = 'No'  
TERM_SUSPECTED = 'Suspected'
```

```

TERM_UNKNOWN = 'Unknown'

TERM_YES = 'Yes'

class stix.common.vocabs.SystemType_1_0 (value=None)
    Bases: stix.common.vocabs.VocabString

TERM_ENTERPRISE_SYSTEMS = 'Enterprise Systems'

TERM_ENTERPRISE_SYSTEMS_APPLICATION_LAYER = 'Enterprise Systems - Application Layer'

TERM_ENTERPRISE_SYSTEMS_DATABASE_LAYER = 'Enterprise Systems - Database Layer'

TERM_ENTERPRISE_SYSTEMS_ENTERPRISE_TECHNOLOGIES_AND_SUPPORT_INFRASTRUCTURE = 'Enterprise Systems - Enterprise Technologies and Support Infrastructure'

TERM_ENTERPRISE_SYSTEMS_NETWORKING_DEVICES = 'Enterprise Systems - Networking Devices'

TERM_ENTERPRISE_SYSTEMS_NETWORK_SYSTEMS = 'Enterprise Systems - Network Systems'

TERM_ENTERPRISE_SYSTEMS_VOIP = 'Enterprise Systems - VoIP'

TERM_ENTERPRISE_SYSTEMS_WEB_LAYER = 'Enterprise Systems - Web Layer'

TERM_INDUSTRIAL_CONTROL_SYSTEMS = 'Industrial Control Systems'

TERM_INDUSTRIAL_CONTROL_SYSTEMS_EQUIPMENT_UNDER_CONTROL = 'Industrial Control Systems - Equipment Under Control'

TERM_INDUSTRIAL_CONTROL_SYSTEMS_OPERATIONS_MANAGEMENT = 'Industrial Control Systems - Operations Management'

TERM_INDUSTRIAL_CONTROL_SYSTEMS_SAFETY_PROTECTION_AND_LOCAL_CONTROL = 'Industrial Control Systems - Safety Protection and Local Control'

TERM_INDUSTRIAL_CONTROL_SYSTEMS_SUPERVISORY_CONTROL = 'Industrial Control Systems - Supervisory Control'

TERM_MOBILE_SYSTEMS = 'Mobile Systems'

TERM_MOBILE_SYSTEMS_MOBILE_DEVICES = 'Mobile Systems - Mobile Devices'

TERM_MOBILE_SYSTEMS_MOBILE_OPERATING_SYSTEMS = 'Mobile Systems - Mobile Operating Systems'

TERM_MOBILE_SYSTEMS_NEAR_FIELD_COMMUNICATIONS = 'Mobile Systems - Near Field Communications'

TERM_THIRDPARTY_SERVICES = 'Third-Party Services'

TERM_THIRDPARTY_SERVICES_APPLICATION_STORES = 'Third-Party Services - Application Stores'

TERM_THIRDPARTY_SERVICES_CLOUD_SERVICES = 'Third-Party Services - Cloud Services'

TERM_THIRDPARTY_SERVICES_SECURITY_VENDORS = 'Third-Party Services - Security Vendors'

TERM_THIRDPARTY_SERVICES_SOCIAL_MEDIA = 'Third-Party Services - Social Media'

TERM_THIRDPARTY_SERVICES_SOFTWARE_UPDATE = 'Third-Party Services - Software Update'

TERM_USERS = 'Users'

TERM_USERS_APPLICATION_AND_SOFTWARE = 'Users - Application And Software'

TERM_USERS_REMOVABLE_MEDIA = 'Users - Removable Media'

TERM_USERS_WORKSTATION = 'Users - Workstation'

class stix.common.vocabs.ThreatActorSophistication_1_0 (value=None)
    Bases: stix.common.vocabs.VocabString

TERM_ASPIRANT = 'Aspirant'

TERM_EXPERT = 'Expert'

TERM_INNOVATOR = 'Innovator'

TERM_NOVICE = 'Novice'

```

```
TERM_PRACTITIONER = 'Practitioner'

class stix.common.vocabs.ThreatActorType_1_0 (value=None)
    Bases: stix.common.vocabs.VocabString

    TERM_CYBER_ESPIONAGE_OPERATIONS = 'Cyber Espionage Operations'
    TERM_DISGRUNTLED_CUSTOMER_OR_USER = 'Disgruntled Customer / User'
    TERM_ECRIME_ACTOR_CREDENTIAL_THEFT_BOTNET_OPERATOR = 'eCrime Actor - Credential Theft Botnet Operator'
    TERM_ECRIME_ACTOR_CREDENTIAL_THEFT_BOTNET_SERVICE = 'eCrime Actor - Credential Theft Botnet Service'
    TERM_ECRIME_ACTOR_MALWARE_DEVELOPER = 'eCrime Actor - Malware Developer'
    TERM_ECRIME_ACTOR_MONEY_LAUNDERING_NETWORK = 'eCrime Actor - Money Laundering Network'
    TERM_ECRIME_ACTOR_ORGANIZED_CRIME_ACTOR = 'eCrime Actor - Organized Crime Actor'
    TERM_ECRIME_ACTOR_SPAM_SERVICE = 'eCrime Actor - Spam Service'
    TERM_ECRIME_ACTOR_TRAFFIC_SERVICE = 'eCrime Actor - Traffic Service'
    TERM_ECRIME_ACTOR_UNDERGROUND_CALL_SERVICE = 'eCrime Actor - Underground Call Service'
    TERM_HACKER = 'Hacker'
    TERM_HACKER_BLACK_HAT = 'Hacker - Black hat'
    TERM_HACKER_GRAY_HAT = 'Hacker - Gray hat'
    TERM_HACKER_WHITE_HAT = 'Hacker - White hat'
    TERM_HACKTIVIST = 'Hacktivist'
    TERM_INSIDER_THREAT = 'Insider Threat'
    TERM_STATE_ACTOR_OR_AGENCY = 'State Actor / Agency'

class stix.common.vocabs.Versioning_1_0 (value=None)
    Bases: stix.common.vocabs.VocabString

    TERM_REVOKES = 'Revokes'
    TERM_UPDATES_REVISES = 'Updates - Revises'
    TERM_UPDATE_CORRECTS = 'Updates - Corrects'

class stix.common.vocabs.VocabString (value=None)
    Bases: stix.base.Entity

    is_plain ()
        Whether the VocabString can be represented as a single value.

stix.common.vocabs.AssetType
    alias of AssetType_1_0

stix.common.vocabs.AttackerInfrastructureType
    alias of AttackerInfrastructureType_1_0

stix.common.vocabs.AttackerToolType
    alias of AttackerToolType_1_0

stix.common.vocabs.AvailabilityLossType
    alias of AvailabilityLossType_1_1_1

stix.common.vocabs.CampaignStatus
    alias of CampaignStatus_1_0
```



`stix.common.vocabs.COASStage`  
alias of `COASStage_1_0`

`stix.common.vocabs.CourseOfActionType`  
alias of `CourseOfActionType_1_0`

`stix.common.vocabs.DiscoveryMethod`  
alias of `DiscoveryMethod_2_0`

`stix.common.vocabs.HighMediumLow`  
alias of `HighMediumLow_1_0`

`stix.common.vocabs.ImpactQualification`  
alias of `ImpactQualification_1_0`

`stix.common.vocabs.ImpactRating`  
alias of `ImpactRating_1_0`

`stix.common.vocabs.IncidentCategory`  
alias of `IncidentCategory_1_0`

`stix.common.vocabs.IncidentEffect`  
alias of `IncidentEffect_1_0`

`stix.common.vocabs.IncidentStatus`  
alias of `IncidentStatus_1_0`

`stix.common.vocabs.IndicatorType`  
alias of `IndicatorType_1_1`

`stix.common.vocabs.InformationSourceRole`  
alias of `InformationSourceRole_1_0`

`stix.common.vocabs.InformationType`  
alias of `InformationType_1_0`

`stix.common.vocabs.IntendedEffect`  
alias of `IntendedEffect_1_0`

`stix.common.vocabs.LocationClass`  
alias of `LocationClass_1_0`

`stix.common.vocabs.LossDuration`  
alias of `LossDuration_1_0`

`stix.common.vocabs.LossProperty`  
alias of `LossProperty_1_0`

`stix.common.vocabs.MalwareType`  
alias of `MalwareType_1_0`

`stix.common.vocabs.ManagementClass`  
alias of `ManagementClass_1_0`

`stix.common.vocabs.Motivation`  
alias of `Motivation_1_1`

`stix.common.vocabs.OwnershipClass`  
alias of `OwnershipClass_1_0`

`stix.common.vocabs.PackageIntent`  
alias of `PackageIntent_1_0`

`stix.common.vocabs.PlanningAndOperationalSupport`  
alias of `PlanningAndOperationalSupport_1_0_1`

`stix.common.vocabs.SecurityCompromise`  
alias of `SecurityCompromise_1_0`

`stix.common.vocabs.SystemType`  
alias of `SystemType_1_0`

`stix.common.vocabs.ThreatActorSophistication`  
alias of `ThreatActorSophistication_1_0`

`stix.common.vocabs.ThreatActorType`  
alias of `ThreatActorType_1_0`

## Functions

`stix.common.vocabs.add_vocab(cls)`  
Registers a VocabString subclass.

---

**Note:** The `register_vocab()` class decorator has replaced this method.

---

`stix.common.vocabs.register_vocab(cls)`  
Class decorator that registers a VocabString subclass.

Also, calculate all the permitted values for class being decorated by adding an `_ALLOWED_VALUES` tuple of all the values of class members beginning with `TERM_`.

## STIX Core

Modules located in the `stix.core` package

**Version:** 1.2.0.5.dev0

### `stix.core.stix_header` Module

#### Classes

`class stix.core.stix_header.STIXHeader` (`package_intents=None`, `description=None`, `handling=None`, `information_source=None`, `title=None`, `short_description=None`)

Bases: `stix.base.Entity`

The STIX Package Header.

#### Parameters

- **handling** – The data marking section of the Header.
- **information\_source** – The `InformationSource` section of the Header.
- **package\_intents** – **DEPRECATED**. A collection of `VocabString` defining the intent of the parent `STIXPackage`.
- **description** – **DEPRECATED**. A description of the intent or purpose of the parent `STIXPackage`.

- **short\_description** – **DEPRECATED**. A short description of the intent or purpose of the parent *STIXPackage*.
- **title** – **DEPRECATED**. The title of the *STIXPackage*.

**profiles**

A collection of STIX Profiles the parent *STIXPackage* conforms to.

**title**

**DEPRECATED**. The title of the parent *STIXPackage*.

**add\_description** (*description*)

**DEPRECATED**. Adds a description to the `descriptions` collection.

This is the same as calling “foo.descriptions.add(bar)”.

**add\_package\_intent** (*package\_intent*)

**DEPRECATED**. Adds *VocabString* object to the `package_intents` collection.

If the input is not an instance of *VocabString*, an effort will be made to convert it into an instance of *PackageIntent*.

**add\_profile** (*profile*)

Adds a profile to the STIX Header. A Profile is represented by a string URI.

**add\_short\_description** (*description*)

**DEPRECATED**. Adds a description to the `short_descriptions` collection.

This is the same as calling “foo.short\_descriptions.add(bar)”.

**description**

**DEPRECATED**. A single description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**short\_description**

**DEPRECATED**. A single short description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one short description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

Version: 1.2.0.5.dev0

**stix.core.stix\_package Module**

## Overview

The `stix.core.stix_package` module implements `STIXPackage`.

STIXType defines a bundle of information characterized in the Structured Threat Information eXpression (STIX) language.

## Documentation Resources

- [STIX Package Data Model](#)

## Classes

```
class stix.core.stix_package.STIXPackage (id=None, idref=None, timestamp=None,
                                          stix_header=None, courses_of_action=None,
                                          exploit_targets=None, indicators=None,
                                          observables=None, incidents=None,
                                          threat_actors=None, ttps=None, campaigns=None,
                                          related_packages=None, reports=None)
```

Bases: `stix.base.Entity`

A STIX Package object.

### Parameters

- **id** (*optional*) – An identifier. If None, a value will be generated via `mixbox.idgen.create_id()`. If set, this will unset the `idref` property.
- **idref** – **DEPRECATED** An identifier reference. If set this will unset the `id_` property.
- **timestamp** – **DEPRECATED** A timestamp value. Can be an instance of `datetime.datetime` or `str`.
- **header** – A Report `Header` object.
- **campaigns** – A collection of `Campaign` objects.
- **course\_of\_action** – A collection of `CourseOfAction` objects.
- **exploit\_targets** – A collection of `ExploitTarget` objects.
- **incidents** – A collection of `Incident` objects.
- **indicators** – A collection of `Indicator` objects.
- **threat\_actors** – A collection of `ThreatActor` objects.
- **ttps** – A collection of `TTP` objects.
- **related\_packages** – **DEPRECATED**. A collection of `RelatedPackage` objects.
- **reports** – A collection of `Report` objects.

**add** (*entity*)

Adds *entity* to a top-level collection. For example, if *entity* is an `Indicator` object, the *entity* will be added to the `indicators` top-level collection.

**add\_campaign** (*campaign*)

Adds a `Campaign` object to the `campaigns` collection.

**add\_course\_of\_action** (*course\_of\_action*)

Adds an `CourseOfAction` object to the `courses_of_action` collection.

**add\_exploit\_target** (*exploit\_target*)

Adds an *ExploitTarget* object to the `exploit_targets` collection.

**add\_incident** (*incident*)

Adds an *Incident* object to the `incidents` collection.

**add\_indicator** (*indicator*)

Adds an *Indicator* object to the `indicators` collection.

**add\_observable** (*observable*)

Adds an *Observable* object to the `observables` collection.

If *observable* is not an *Observable* instance, an effort will be made to convert it to one.

**add\_related\_package** (*related\_package*)

Adds a *RelatedPackage* object to the `related_packages` collection.

**add\_report** (*report*)

Adds a *Report* object to the `reports` collection.

**add\_threat\_actor** (*threat\_actor*)

Adds an *ThreatActor* object to the `threat_actors` collection.

**add\_ttp** (*ttp*)

Adds an *TTP* object to the `ttps` collection.

**find** (*id\_*)

Searches the children of a *Entity* implementation for an object with an `id_` property that matches *id\_*.

**classmethod from\_xml** (*xml\_file*, *encoding=None*)

Parses the *xml\_file* file-like object and returns a *STIXPackage* instance.

#### Parameters

- **xml\_file** – A file, file-like object, *etree.\_Element*, or *etree.\_ElementTree* instance.
- **encoding** – The character encoding of the *xml\_file* input. If *None*, an attempt will be made to determine the input character encoding. Default is *None*.

**Returns** An instance of *STIXPackage*.

**to\_dict** ()

Convert to a dict

Subclasses can override this function.

**Returns** Python dict with keys set from this *Entity*.

**to\_dict** ()

Convert to a dict

Subclasses can override this function.

**Returns** Python dict with keys set from this *Entity*.

**to\_json** ()

Export an object as a JSON String.

**to\_obj** (*ns\_info=None*)

Convert to a *GenerateDS* binding object.

Subclasses can override this function.

**Returns** An instance of this *Entity*'s `_binding_class` with properties set from this *Entity*.

**to\_obj** (*ns\_info=None*)

Convert to a GenerateDS binding object.

Subclasses can override this function.

**Returns** An instance of this Entity's `_binding_class` with properties set from this Entity.

**to\_xml** (*include\_namespaces=True, include\_schemalocs=False, ns\_dict=None, schemaloc\_dict=None, pretty=True, auto\_namespace=True, encoding='utf-8'*)  
Serializes a Entity instance to an XML string.

The default character encoding is `utf-8` and can be set via the `encoding` parameter. If `encoding` is `None`, a string (unicode in Python 2, str in Python 3) is returned.

#### Parameters

- **auto\_namespace** – Automatically discover and export XML namespaces for a STIX Entity instance.
- **include\_namespaces** – Export namespace definitions in the output XML. Default is `True`.
- **include\_schemalocs** – Export `xsi:schemaLocation` attribute in the output document. This will attempt to associate namespaces declared in the STIX document with schema locations. If a namespace cannot be resolved to a `schemaLocation`, a Python warning will be raised. Schemalocations will only be exported if `include_namespaces` is also `True`.
- **ns\_dict** – Dictionary of XML definitions (namespace is key, alias is value) to include in the exported document. This must be passed in if `auto_namespace` is `False`.
- **schemaloc\_dict** – Dictionary of XML namespace: schema location mappings to include in the exported document. These will only be included if `auto_namespace` is `False`.
- **pretty** – Pretty-print the XML.
- **encoding** – The output character encoding. Default is `utf-8`. If `encoding` is set to `None`, a string (unicode in Python 2, str in Python 3) is returned.

**Returns** An XML string for this Entity instance. Default character encoding is `utf-8`.

**class** `stix.core.stix_package.RelatedPackages` (*scope=None, \*args*)

Bases: `stix.common.related.GenericRelationshipList`

**Version:** 1.2.0.5.dev0

## `stix.core.ttps` Module

### Classes

**class** `stix.core.ttps.TTPs` (*ttps=None*)

Bases: `stix.base.EntityList`

## STIX Course of Action (COA)

Modules located in the `stix.coa` package

**Version:** 1.2.0.5.dev0

## stix.coa Module

### Overview

The `stix.coa` module implements `CourseOfAction`.

CoursesOfAction are specific measures to be taken to address threat whether they are corrective or preventative to address ExploitTargets, or responsive to counter or mitigate the potential impacts of Incidents

### Documentation Resources

- [Course Of Action Data Model](#)

### Classes

**class** `stix.coa.CourseOfAction` (*id\_=None, idref=None, timestamp=None, title=None, description=None, short\_description=None*)

Bases: `stix.base.BaseCoreComponent`

Implementation of the STIX Course of Action.

#### Parameters

- **id** (*optional*) – An identifier. If None, a value will be generated via `mixbox.idgen.create_id()`. If set, this will unset the `idref` property.
- **idref** (*optional*) – An identifier reference. If set this will unset the `id_` property.
- **timestamp** (*optional*) – A timestamp value. Can be an instance of `datetime.datetime` or `str`.
- **description** – A description of the purpose or intent of this object.
- **short\_description** – A short description of the intent or purpose of this object.
- **title** – The title of this object.

**add\_description** (*description*)

Adds a description to the `descriptions` collection.

This is the same as calling “`foo.descriptions.add(bar)`”.

**add\_short\_description** (*description*)

Adds a description to the `short_descriptions` collection.

This is the same as calling “`foo.short_descriptions.add(bar)`”.

**description**

A single description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of `StructuredText`

**find** (*id\_*)

Searches the children of a `Entity` implementation for an object with an `id_` property that matches *id\_*.

**short\_description**

A single short description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one short description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**to\_dict ()**

Convert to a dict

Subclasses can override this function.

**Returns** Python dict with keys set from this Entity.

**to\_json ()**

Export an object as a JSON String.

**to\_obj (ns\_info=None)**

Convert to a GenerateDS binding object.

Subclasses can override this function.

**Returns** An instance of this Entity's `_binding_class` with properties set from this Entity.

**class** `stix.coa.RelatedCOAs (scope=None, *args)`

Bases: `stix.common.related.GenericRelationshipList`

**Version:** 1.2.0.5.dev0

## **stix.coa.objective Module**

### **Classes**

**class** `stix.coa.objective.Objective (description=None, short_description=None)`

Bases: `stix.base.Entity`

**add\_description (description)**

Adds a description to the descriptions collection.

This is the same as calling "foo.descriptions.add(bar)".

**add\_short\_description (description)**

Adds a description to the short\_descriptions collection.

This is the same as calling "foo.short\_descriptions.add(bar)".

**description**

A single description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---



**Returns** An instance of *StructuredText*

**short\_description**

A single short description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one short description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

## STIX Exploit Target

Modules located in the `stix.exploit_target` package

**Version:** 1.2.0.5.dev0

### `stix.exploit_target` Module

#### Overview

The `stix.exploit_target` module implements *ExploitTarget*.

This denotes the specific vulnerability, weakness, or software configuration that creates a security risk.

#### Documentation Resources

- [Exploit Target Data Model](#)
- [Exploit Target Idioms](#)

#### Classes

**class** `stix.exploit_target.ExploitTarget` (*id\_=None, idref=None, timestamp=None, title=None, description=None, short\_description=None*)

Bases: `stix.base.BaseCoreComponent`

Implementation of STIX Exploit Target.

#### Parameters

- **id** (*optional*) – An identifier. If None, a value will be generated via `mixbox.idgen.create_id()`. If set, this will unset the `idref` property.
- **idref** (*optional*) – An identifier reference. If set this will unset the `id_` property.
- **title** (*optional*) – A string title.
- **timestamp** (*optional*) – A timestamp value. Can be an instance of `datetime.datetime` or `str`.
- **description** (*optional*) – A string description.
- **short\_description** (*optional*) – A string short description.

**add\_configuration** (*value*)

Adds a configuration to the `configurations` list property.

---

**Note:** If `None` is passed in no value is added

---

**Parameters** *value* – A configuration value.

**Raises** `ValueError` – If the *value* param is of type `Configuration`

**add\_description** (*description*)

Adds a description to the `descriptions` collection.

This is the same as calling “`foo.descriptions.add(bar)`”.

**add\_short\_description** (*description*)

Adds a description to the `short_descriptions` collection.

This is the same as calling “`foo.short_descriptions.add(bar)`”.

**add\_vulnerability** (*value*)

Adds a vulnerability to the `vulnerabilities` list property.

---

**Note:** If `None` is passed in no value is added

---

**Parameters** *value* – A `Vulnerability` object..

**Raises** `ValueError` – if the *value* param is of type `Vulnerability`

**add\_weakness** (*value*)

Adds a weakness to the `weaknesses` list property.

---

**Note:** If `None` is passed in no value is added

---

**Parameters** *value* – A `Weakness` object.

Raises: `ValueError` if the *value* param is of type `Weakness`

**description**

A single description about the contents or purpose of this object.

Default Value: `None`

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of `StructuredText`

**find** (*id\_*)

Searches the children of a `Entity` implementation for an object with an `id_` property that matches *id\_*.

**short\_description**

A single short description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one short description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**to\_dict ()**

Convert to a dict

Subclasses can override this function.

**Returns** Python dict with keys set from this Entity.

**to\_json ()**

Export an object as a JSON String.

**to\_obj (ns\_info=None)**

Convert to a GenerateDS binding object.

Subclasses can override this function.

**Returns** An instance of this Entity's `_binding_class` with properties set from this Entity.

**class** `stix.exploit_target.PotentialCOAs` (*coas=None, scope=None*)

Bases: *stix.common.related.GenericRelationshipList*

A list of Potential\_COA objects, defaults to empty array

**class** `stix.exploit_target.RelatedExploitTargets` (*related\_exploit\_targets=None, scope=None*)

Bases: *stix.common.related.GenericRelationshipList*

A list of RelatedExploitTargets objects, defaults to empty array

**Version:** 1.2.0.5.dev0

**stix.exploit\_target.configuration Module****Overview**

The *stix.exploit\_target.configuration* module captures the software configuration that causes a vulnerability in a system.

**Classes**

**class** `stix.exploit_target.configuration.Configuration` (*description=None, short\_description=None, cce\_id=None*)

Bases: *stix.base.Entity*

Implementation of STIX Configuration.

**Parameters**

- **cce\_id** (*optional*) – Common Configuration Enumeration value as a string
- **description** (*optional*) – A string description.
- **short\_description** (*optional*) – A string short description.

**add\_description** (*description*)

Adds a description to the `descriptions` collection.

This is the same as calling “`foo.descriptions.add(bar)`”.

**add\_short\_description** (*description*)

Adds a description to the `short_descriptions` collection.

This is the same as calling “`foo.short_descriptions.add(bar)`”.

**description**

A single description about the contents or purpose of this object.

Default Value: `None`

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**short\_description**

A single short description about the contents or purpose of this object.

Default Value: `None`

---

**Note:** If this object has more than one short description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**Version:** 1.2.0.5.dev0

## **stix.exploit\_target.vulnerability Module**

### **Overview**

The `stix.exploit_target.vulnerability` module captures the software version and specific bug that causes an exploitable condition.

### **Classes**

**class** `stix.exploit_target.vulnerability.Vulnerability` (*title=None, description=None, short\_description=None*)

Bases: `stix.base.Entity`

Implementation of STIX Vulnerability.

#### **Parameters**

- **title** (*optional*) – A string title.
- **description** (*optional*) – A string description.
- **short\_description** (*optional*) – A string short description.

**add\_description** (*description*)

Adds a description to the `descriptions` collection.

This is the same as calling “`foo.descriptions.add(bar)`”.

**add\_short\_description** (*description*)

Adds a description to the `short_descriptions` collection.

This is the same as calling “`foo.short_descriptions.add(bar)`”.

**description**

A single description about the contents or purpose of this object.

Default Value: `None`

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**short\_description**

A single short description about the contents or purpose of this object.

Default Value: `None`

---

**Note:** If this object has more than one short description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**class** `stix.exploit_target.vulnerability.CVSSVector`

Bases: *stix.base.Entity*

Common Vulnerability Scoring System object, representing its component measures

**class** `stix.exploit_target.vulnerability.AffectedSoftware` (*scope=None, \*args*)

Bases: *stix.common.related.GenericRelationshipList*

**Version:** 1.2.0.5.dev0

## `stix.exploit_target.weakness` Module

### Overview

The `stix.exploit_target.weakness` module captures a given software weakness as enumerated by CWE

## Classes

**class** `stix.exploit_target.weakness.Weakness` (*description=None, cwe\_id=None*)

Bases: `stix.base.Entity`

Implementation of STIX Weakness.

### Parameters

- **cwe\_id** (*optional*) – Common Weakness Enumeration value as a string
- **description** (*optional*) – A string description.

**add\_description** (*description*)

Adds a description to the `descriptions` collection.

This is the same as calling “`foo.descriptions.add(bar)`”.

**description**

A single description about the contents or purpose of this object.

Default Value: `None`

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of `StructuredText`

## STIX Extensions

Modules located in the `stix.extensions` package

**Version:** 1.2.0.5.dev0

### `stix.extensions.identity.ciq_identity_3_0` Module

#### Classes

**class** `stix.extensions.identity.ciq_identity_3_0.CIQIdentity3_0Instance` (*roles=None,*

*spec-  
ifica-  
tion=None*)

Bases: `stix.common.identity.Identity`

---

```

class stix.extensions.identity.ciq_identity_3_0.STIXCIQIdentity3_0 (party_name=None,
                                                                    lan-
                                                                    guages=None,
                                                                    ad-
                                                                    dresses=None,
                                                                    organisa-
                                                                    tion_info=None,
                                                                    elec-
                                                                    tronic_address_identifiers=None,
                                                                    free_text_lines=None,
                                                                    con-
                                                                    tact_numbers=None,
                                                                    nationali-
                                                                    ties=None)

    Bases: stix.base.Entity

class stix.extensions.identity.ciq_identity_3_0.Address (free_text_address=None,
                                                         country=None,  administra-
                                                         tive_area=None)

    Bases: stix.base.Entity

class stix.extensions.identity.ciq_identity_3_0.AdministrativeArea (name_elements=None)
    Bases: stix.base.Entity

class stix.extensions.identity.ciq_identity_3_0.BaseNameElement (value=None)
    Bases: stix.base.Entity

    Do not instantiate directly: use PersonNameElement or OrganisationNameElement

class stix.extensions.identity.ciq_identity_3_0.ContactNumber (contact_number_elements=None,
                                                                communica-
                                                                tion_media_type=None)

    Bases: stix.base.Entity

class stix.extensions.identity.ciq_identity_3_0.ContactNumberElement (value=None,
                                                                    type_=None)

    Bases: stix.base.Entity

class stix.extensions.identity.ciq_identity_3_0.Country (name_elements=None)
    Bases: stix.base.Entity

class stix.extensions.identity.ciq_identity_3_0.ElectronicAddressIdentifier (value=None,
                                                                    type_=None)

    Bases: stix.base.Entity

class stix.extensions.identity.ciq_identity_3_0.FreeTextAddress (address_lines=None)
    Bases: stix.base.Entity

class stix.extensions.identity.ciq_identity_3_0.FreeTextLine (value=None,
                                                                    type_=None)

    Bases: stix.base.Entity

class stix.extensions.identity.ciq_identity_3_0.Language (value=None)
    Bases: stix.base.Entity

class stix.extensions.identity.ciq_identity_3_0.NameElement (value=None,
                                                                name_type=None,
                                                                name_code=None,
                                                                name_code_type=None)

    Bases: stix.base.Entity

```

```
class stix.extensions.identity.ciq_identity_3_0.NameLine (value=None, type_=None)
    Bases: stix.base.Entity

class stix.extensions.identity.ciq_identity_3_0.OrganisationInfo (industry_type=None)
    Bases: stix.base.Entity

class stix.extensions.identity.ciq_identity_3_0.OrganisationName (name_elements=None,
                                                                    subdivi-
                                                                    sion_names=None,
                                                                    type_=None)
    Bases: stix.base.Entity

class stix.extensions.identity.ciq_identity_3_0.OrganisationNameElement (value=None,
                                                                    ele-
                                                                    ment_type=None)
    Bases: stix.extensions.identity.ciq_identity_3_0._BaseNameElement

class stix.extensions.identity.ciq_identity_3_0.PartyName (name_lines=None,    per-
                                                                    son_names=None, organi-
                                                                    sation_names=None)
    Bases: stix.base.Entity

class stix.extensions.identity.ciq_identity_3_0.PersonName (name_elements=None)
    Bases: stix.base.Entity

class stix.extensions.identity.ciq_identity_3_0.PersonNameElement (value=None,
                                                                    ele-
                                                                    ment_type=None)
    Bases: stix.extensions.identity.ciq_identity_3_0._BaseNameElement

class stix.extensions.identity.ciq_identity_3_0.SubDivisionName (value=None,
                                                                    type_=None)
    Bases: stix.base.Entity
```

## Constants

```
stix.extensions.identity.ciq_identity_3_0.XML_NS_XPIL = 'urn:oasis:names:tc:ciq:xpil:3'
    str(object='') -> string
```

Return a nice string representation of the object. If the argument is a string, the return value is the same object.

```
stix.extensions.identity.ciq_identity_3_0.XML_NS_XNL = 'urn:oasis:names:tc:ciq:xnl:3'
    str(object='') -> string
```

Return a nice string representation of the object. If the argument is a string, the return value is the same object.

```
stix.extensions.identity.ciq_identity_3_0.XML_NS_XAL = 'urn:oasis:names:tc:ciq:xal:3'
    str(object='') -> string
```

Return a nice string representation of the object. If the argument is a string, the return value is the same object.

```
stix.extensions.identity.ciq_identity_3_0.XML_NS_STIX_EXT = 'http://stix.mitre.org/extensions/Identity#CIQ'
    str(object='') -> string
```

Return a nice string representation of the object. If the argument is a string, the return value is the same object.

**Version:** 1.2.0.5.dev0

**stix.extensions.malware.maec\_4\_1\_malware Module**



## Classes

**class** `stix.extensions.malware.maec_4_1_malware.MAECInstance` (*maec=None*)  
Bases: `stix.ttp.malware_instance.MalwareInstance`

Version: 1.2.0.5.dev0

## `stix.extensions.marking.simple_marking` Module

### Classes

**class** `stix.extensions.marking.simple_marking.SimpleMarkingStructure` (*statement=None*)  
Bases: `stix.data_marking.MarkingStructure`

Version: 1.2.0.5.dev0

## `stix.extensions.marking.terms_of_use_marking` Module

### Classes

**class** `stix.extensions.marking.terms_of_use_marking.TermsOfUseMarkingStructure` (*terms\_of\_use=None*)  
Bases: `stix.data_marking.MarkingStructure`

Version: 1.2.0.5.dev0

## `stix.extensions.marking.tlp` Module

### Classes

**class** `stix.extensions.marking.tlp.TLPMarkingStructure` (*color=None*)  
Bases: `stix.data_marking.MarkingStructure`

Version: 1.2.0.5.dev0

## `stix.extensions.structured_coa.generic_structured_coa` Module

### Classes

**class** `stix.extensions.structured_coa.generic_structured_coa.GenericStructuredCOA` (*id\_=None, idref=None*)  
Bases: `stix.coa.structured_coa._BaseStructuredCOA`

**add\_description** (*description*)

Adds a description to the descriptions collection.

This is the same as calling “foo.descriptions.add(bar)”.

**description**

A single description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**Version:** 1.2.0.5.dev0

### **stix.extensions.test\_mechanism.generic\_test\_mechanism** Module

#### **Classes**

**class** stix.extensions.test\_mechanism.generic\_test\_mechanism.**GenericTestMechanism** (*id\_=None, idref=None*)

Bases: *stix.indicator.test\_mechanism.\_BaseTestMechanism*

**add\_description** (*description*)

Adds a description to the descriptions collection.

This is the same as calling “foo.descriptions.add(bar)”.

**description**

A single description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**Version:** 1.2.0.5.dev0

### **stix.extensions.test\_mechanism.open\_ioc\_2010\_test\_mechanism** Module

#### **Classes**

**class** stix.extensions.test\_mechanism.open\_ioc\_2010\_test\_mechanism.**OpenIOCTestMechanism** (*id\_=None, idref=None*)

Bases: *stix.indicator.test\_mechanism.\_BaseTestMechanism*

**Version:** 1.2.0.5.dev0

### **stix.extensions.test\_mechanism.snort\_test\_mechanism** Module

#### **Classes**

**class** stix.extensions.test\_mechanism.snort\_test\_mechanism.**SnortTestMechanism** (*id\_=None, idref=None*)

Bases: *stix.indicator.test\_mechanism.\_BaseTestMechanism*

**Version:** 1.2.0.5.dev0

**stix.extensions.test\_mechanism.yara\_test\_mechanism Module****Classes**

**class** stix.extensions.test\_mechanism.yara\_test\_mechanism.**YaraTestMechanism** (*id\_=None, idref=None*)  
 Bases: *stix.indicator.test\_mechanism.\_BaseTestMechanism*

**STIX Incident**

Modules located in the `stix.incident` package

**Version:** 1.2.0.5.dev0

**stix.incident Module****Overview**

The `stix.incident` module implements *Incident*.

Incidents are discrete instances of Indicators affecting an organization along with information discovered or decided during an incident response investigation.

**Documentation Resources**

- [Incident Data Model](#)

**Classes**

**class** stix.incident.**Incident** (*id\_=None, idref=None, timestamp=None, title=None, description=None, short\_description=None*)  
 Bases: *stix.base.BaseCoreComponent*

Implementation of the STIX Incident.

**Parameters**

- **id** (*optional*) – An identifier. If `None`, a value will be generated via `mixbox.idgen.create_id()`. If set, this will unset the `idref` property.
- **idref** (*optional*) – An identifier reference. If set this will unset the `id_` property.
- **timestamp** (*optional*) – A timestamp value. Can be an instance of `datetime.datetime` or `str`.
- **description** – A description of the purpose or intent of this object.
- **short\_description** – A short description of the intent or purpose of this object.
- **title** – The title of this object.

**add\_affected\_asset** (*v*)

Adds a *AffectedAsset* object to the `affected_assets` collection.

**add\_category** (*category*)

Adds a *VocabString* object to the `categories` collection.

If *category* is a string, an attempt will be made to convert it into an instance of *IncidentCategory*.

**add\_coa\_requested** (*value*)

Adds a *COARequested* object to the `coas_requested` collection.

**add\_coa\_taken** (*value*)

Adds a *COATaken* object to the `coas_taken` collection.

**add\_coordinator** (*value*)

Adds a *InformationSource* object to the `coordinators` collection.

**add\_description** (*description*)

Adds a description to the `descriptions` collection.

This is the same as calling “`foo.descriptions.add(bar)`”.

**add\_discovery\_method** (*value*)

Adds a *VocabString* object to the `discovery_methods` collection.

If *value* is a string, an attempt will be made to convert it to an instance of *DiscoveryMethod*.

**add\_external\_id** (*value*)

Adds a *ExternalID* object to the `external_ids` collection.

**add\_intended\_effect** (*value*)

Adds a *Statement* object to the `intended_effects` collection.

If *value* is a string, an attempt will be made to convert it into an instance of *Statement*.

**add\_related\_indicator** (*value*)

Adds an Related Indicator to the `related_indicators` list property of this *Incident*.

The *indicator* parameter must be an instance of *RelatedIndicator* or *Indicator*.

If the *indicator* parameter is `None`, no item will be added to the `related_indicators` list property.

Calling this method is the same as calling `append()` on the `related_indicators` property.

**See also:**

The *RelatedIndicators* documentation.

---

**Note:** If the *indicator* parameter is not an instance of *RelatedIndicator* an attempt will be made to convert it to one.

---

**Parameters** *indicator* – An instance of *Indicator* or *RelatedIndicator*.

**Raises** *ValueError* – If the *indicator* parameter cannot be converted into an instance of *RelatedIndicator*

**add\_related\_observable** (*value*)

Adds a Related Observable to the `related_observables` list property of this *Incident*.

The *observable* parameter must be an instance of *RelatedObservable* or *Observable*.

If the *observable* parameter is `None`, no item will be added to the `related_observables` list property.

Calling this method is the same as calling `append()` on the `related_observables` property.

**See also:**

The *RelatedObservables* documentation.

---

**Note:** If the *observable* parameter is not an instance of *RelatedObservable* an attempt will be made to convert it to one.

---

**Parameters** *observable* – An instance of *Observable* or *RelatedObservable*.

**Raises** *ValueError* – If the *value* parameter cannot be converted into an instance of *RelatedObservable*

**add\_responder** (*value*)

Adds a *InformationSource* object to the responders collection.

**add\_short\_description** (*description*)

Adds a description to the short\_descriptions collection.

This is the same as calling “foo.short\_descriptions.add(bar)”.

**add\_victim** (*victim*)

Adds a *IdentityType* value to the victims collection.

**description**

A single description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**find** (*id\_*)

Searches the children of a *Entity* implementation for an object with an *id\_* property that matches *id\_*.

**short\_description**

A single short description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one short description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**to\_dict** ()

Convert to a dict

Subclasses can override this function.

**Returns** Python dict with keys set from this Entity.

**to\_json** ()

Export an object as a JSON String.

**to\_obj** (*ns\_info=None*)

Convert to a GenerateDS binding object.

Subclasses can override this function.

**Returns** An instance of this Entity’s `_binding_class` with properties set from this Entity.

**class** `stix.incident.AttributedThreatActors` (*scope=None, \*args*)

Bases: `stix.common.related.GenericRelationshipList`

**class** `stix.incident.LeveragedTTPs` (*scope=None, \*args*)

Bases: `stix.common.related.GenericRelationshipList`

**class** `stix.incident.RelatedIndicators` (*scope=None, \*args*)

Bases: `stix.common.related.GenericRelationshipList`

**class** `stix.incident.RelatedObservables` (*scope=None, \*args*)

Bases: `stix.common.related.GenericRelationshipList`

**class** `stix.incident.RelatedIncidents` (*scope=None, \*args*)

Bases: `stix.common.related.GenericRelationshipList`

Version: 1.2.0.5.dev0

## `stix.incident.affected_asset` Module

### Classes

**class** `stix.incident.affected_asset.AffectedAsset`

Bases: `stix.base.Entity`

**add\_description** (*description*)

Adds a description to the descriptions collection.

This is the same as calling “`foo.descriptions.add(bar)`”.

**description**

A single description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of `StructuredText`

**class** `stix.incident.affected_asset.AssetType` (*value=None, count\_affected=None*)

Bases: `stix.common.vocabs.VocabString`

**is\_plain** ()

Override `VocabString.is_plain()`

Version: 1.2.0.5.dev0

## `stix.incident.coa` Module

### Classes

**class** `stix.incident.coa.COATaken` (*course\_of\_action=None*)

Bases: `stix.base.Entity`

**class** `stix.incident.coa.COARequested` (*course\_of\_action=None*)  
Bases: `stix.incident.coa.COATaken`

**class** `stix.incident.coa.COATime` (*start=None, end=None*)  
Bases: `stix.base.Entity`

Version: 1.2.0.5.dev0

### `stix.incident.contributors` Module

#### Classes

**class** `stix.incident.contributors.Contributors` (*\*args*)  
Bases: `stix.base.EntityList`

Version: 1.2.0.5.dev0

### `stix.incident.direct_impact_summary` Module

#### Classes

**class** `stix.incident.direct_impact_summary.DirectImpactSummary`  
Bases: `stix.base.Entity`

Version: 1.2.0.5.dev0

### `stix.incident.external_id` Module

#### Classes

**class** `stix.incident.external_id.ExternalID` (*value=None, source=None*)  
Bases: `stix.base.Entity`

Version: 1.2.0.5.dev0

### `stix.incident.history` Module

#### Classes

**class** `stix.incident.history.History` (*\*args*)  
Bases: `stix.base.EntityList`

**class** `stix.incident.history.HistoryItem`  
Bases: `stix.base.Entity`

**class** `stix.incident.history.JournalEntry` (*value=None*)  
Bases: `stix.base.Entity`

Version: 1.2.0.5.dev0

### `stix.incident.impact_assessment` Module

#### Classes

**class** `stix.incident.impact_assessment.ImpactAssessment`  
Bases: `stix.base.Entity`

Version: 1.2.0.5.dev0

### `stix.incident.indirect_impact_summary` Module

#### Classes

**class** `stix.incident.indirect_impact_summary.IndirectImpactSummary`  
Bases: `stix.base.Entity`

Version: 1.2.0.5.dev0

### `stix.incident.loss_estimation` Module

#### Classes

**class** `stix.incident.loss_estimation.LossEstimation`  
Bases: `stix.base.Entity`

Version: 1.2.0.5.dev0

### `stix.incident.property_affected` Module

#### Classes

**class** `stix.incident.property_affected.PropertyAffected`  
Bases: `stix.base.Entity`

#### **description\_of\_effect**

A *StructuredTextList* object, containing descriptions about the purpose or intent of this object.

Iterating over this object will yield its contents sorted by their ordinality value.

Default Value: Empty *StructuredTextList* object.

---

**Note:** IF this is set to a value that is not an instance of *StructuredText*, an effort will ne made to convert it. If this is set to an iterable, any values contained that are not an instance of *StructuredText* will be be converted.

---

**Returns** An instance of *StructuredTextList*

**class** `stix.incident.property_affected.NonPublicDataCompromised` (*value=None*,  
*data\_encrypted=None*)  
Bases: `stix.common.vocabs.VocabString`

Version: 1.2.0.5.dev0



## stix.incident.time Module

### Classes

```
class stix.incident.time.Time (first_malicious_action=None,          initial_compromise=None,
                             first_data_exfiltration=None,        incident_discovery=None,
                             incident_opened=None,                containment_achieved=None,
                             restoration_achieved=None,            incident_reported=None,    inci-
                             dent_closed=None)
```

Bases: *stix.base.Entity*

Version: 1.2.0.5.dev0

## stix.incident.total\_loss\_estimation Module

### Classes

```
class stix.incident.total_loss_estimation.TotalLossEstimation
    Bases: stix.base.Entity
```

## STIX Indicator

Modules located in the `stix.indicator` package

Version: 1.2.0.5.dev0

## stix.indicator.indicator Module

### Overview

The `stix.indicator.indicator` module implements `IndicatorType` STIX Language construct. The `IndicatorType` characterizes a cyber threat indicator made up of a pattern identifying certain observable conditions as well as contextual information about the patterns meaning, how and when it should be acted on, etc.

### Documentation Resources

- [Indicator Data Model](#)
- [Indicator Idioms](#)

### Classes

```
class stix.indicator.indicator.Indicator (id=None,                idref=None,                times-
                                         tamp=None,                title=None,                description=None,
                                         short_description=None)
```

Bases: `stix.base.BaseCoreComponent`

Implementation of the STIX Indicator.

#### Parameters

- **id** (*optional*) – An identifier. If `None`, a value will be generated via `mixbox.idgen.create_id()`. If set, this will unset the `idref` property.

- **idref** (*optional*) – An identifier reference. If set this will unset the `id_` property.
- **title** (*optional*) – A string title.
- **timestamp** (*optional*) – A timestamp value. Can be an instance of `datetime.datetime` or `str`.
- **description** (*optional*) – A string description.
- **short\_description** (*optional*) – A string short description.

**add\_alternative\_id** (*value*)

Adds an alternative id to the `alternative_id` list property.

---

**Note:** If `None` is passed in no value is added to the `alternative_id` list property.

---

**Parameters** **value** – An identifier value.

**add\_description** (*description*)

Adds a description to the `descriptions` collection.

This is the same as calling “`foo.descriptions.add(bar)`”.

**add\_indicated\_ttp** (*v*)

Adds an Indicated TTP to the `indicated_ttps` list property of this *Indicator*.

The *v* parameter must be an instance of `stix.common.related.RelatedTTP` or `stix.ttp.TTP`.

If the *v* parameter is `None`, no item will be added to the `indicated_ttps` list property.

---

**Note:** If the *v* parameter is not an instance of `stix.common.related.RelatedTTP` an attempt will be made to convert it to one.

---

**Parameters** **v** – An instance of `stix.common.related.RelatedTTP` or `stix.ttp.TTP`.

**Raises** `ValueError` – If the *v* parameter cannot be converted into an instance of `stix.common.related.RelatedTTP`

**add\_indicator\_type** (*value*)

Adds a value to the `indicator_types` list property.

The *value* parameter can be a `str` or an instance of `stix.common.vocabs.VocabString`.

---

**Note:** If the *value* parameter is a `str` instance, an attempt will be made to convert it into an instance of `stix.common.vocabs.IndicatorType`

---

**Parameters** **value** – An instance of `stix.common.vocabs.VocabString` or `str`.

**Raises** `ValueError` – If the *value* param is a `str` instance that cannot be converted into an instance of `stix.common.vocabs.IndicatorType`.

**add\_kill\_chain\_phase** (*value*)

Add a new Kill Chain Phase reference to this Indicator.

**Parameters value** – a `stix.common.kill_chains.KillChainPhase` or a `str` representing the `phase_id` of. Note that you if you are defining a custom Kill Chain, you need to add it to the STIX package separately.

**add\_object** (*object\_*)

Adds a python-cybox Object instance to the `observables` list property.

This is the same as calling `indicator.add_observable(object_)`.

---

**Note:** If the `object` param is not an instance of `cybox.core.Object` an attempt will be made to convert it into one before wrapping it in an `cybox.core.Observable` layer.

---

**Parameters object** – An instance of `cybox.core.Object` or an object that can be converted into an instance of `cybox.core.Observable`

**Raises** `ValueError` – if the `object_` param cannot be converted to an instance of `cybox.core.Observable`.

**add\_observable** (*observable*)

Adds an observable to the `observable` property of the `Indicator`.

If the `observable` parameter is `None`, no item will be added to the `observable` property.

---

**Note:** The STIX Language dictates that an `Indicator` can have only one `Observable` under it. Because of this, when a user adds another `Observable` a new, empty `Observable` will be crated and append the existing and new observable using the `ObservableComposition` property. To access the top level `Observable` can be achieved by the `observable` property .By default, the operator of the composition layer will be set to "OR". The operator value can be changed via the `observable_composition_operator` property.

Setting `observable` or `observables` with re-initialize the property and lose all `Observable` in the composition layer.

---

**Parameters observable** – An instance of `cybox.core.Observable` or an object type that can be converted into one.

**Raises** `ValueError` – If the `observable` param cannot be converted into an instance of `cybox.core.Observable`.

**add\_related\_campaign** (*value*)

Adds a Related Campaign to this Indicator.

The `value` parameter must be an instance of `RelatedCampaignRef` or `CampaignRef`.

If the `value` parameter is `None`, no item will be added to the `related_campaigns` collection.

Calling this method is the same as calling `append()` on the `related_campaigns` property.

**See also:**

The `RelatedCampaignRef` documentation.

---

**Note:** If the `value` parameter is not an instance of `RelatedCampaignRef` an attempt will be made to convert it to one.

---

**Parameters** *value* – An instance of `RelatedCampaignRef` or `Campaign`.

**Raises** `ValueError` – If the *value* parameter cannot be converted into an instance of `RelatedCampaignRef`

**add\_related\_indicator** (*indicator*)

Adds an `RelatedIndicator` to the `related_indicators` list property of this `Indicator`.

The *indicator* parameter must be an instance of `stix.common.related.RelatedIndicator` or `Indicator`.

If the *indicator* parameter is `None`, no item will be added to the `related_indicators` list property.

Calling this method is the same as calling `append()` on the `related_indicators` property.

**See also:**

The `RelatedIndicators` documentation.

---

**Note:** If the *tm* parameter is not an instance of `stix.common.related.RelatedIndicator` an attempt will be made to convert it to one.

---

**Parameters** *indicator* – An instance of `Indicator` or `stix.common.related.RelatedIndicator`.

**Raises** `ValueError` – If the *indicator* parameter cannot be converted into an instance of `stix.common.related.RelatedIndicator`

**add\_short\_description** (*description*)

Adds a description to the `short_descriptions` collection.

This is the same as calling “`foo.short_descriptions.add(bar)`”.

**add\_test\_mechanism** (*tm*)

Adds an `Test Mechanism` to the `test_mechanisms` list property of this `Indicator`.

The *tm* parameter must be an instance of a `stix.indicator.test_mechanism._BaseTestMechanism` implementation.

If the *tm* parameter is `None`, no item will be added to the `test_mechanisms` list property.

**See also:**

`Test Mechanism` implementations are found under the `stix.extensions.test_mechanism` package.

**Parameters** *tm* – An instance of a `stix.indicator.test_mechanism._BaseTestMechanism` implementation.

**Raises** `ValueError` – If the *tm* parameter is not an instance of `stix.indicator.test_mechanism._BaseTestMechanism`

**add\_valid\_time\_position** (*value*)

Adds an valid time position to the `valid_time_positions` property list.

If *value* is `None`, no item is added to the `value_time_positions` list.

**Parameters** *value* – An instance of `stix.indicator.valid_time.ValidTime`.

**Raises** `ValueError` – If the *value* argument is not an instance of `stix.indicator.valid_time.ValidTime`.

**description**

A single description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**find** (*id\_*)

Searches the children of a *Entity* implementation for an object with an *id\_* property that matches *id\_*.

**get\_produced\_time** ()

Gets the produced time for this *Indicator*.

This is the same as calling `produced_time = indicator.producer.time.produced_time`.

**Returns** None or an instance of `cybox.common.DateTimeWithPrecision`.

**get\_received\_time** ()

Gets the received time for this *Indicator*.

This is the same as calling `received_time = indicator.producer.time.received_time`.

**Returns** None or an instance of `cybox.common.DateTimeWithPrecision`.

**observables**

A list of `cybox.core.Observable` instances. This can be set to a single object instance or a list of objects.

---

**Note:** If only one *Observable* is set, this property will return a list with the `observable` property.

If multiple `cybox.core.Observable` this property will return *Observables* under the `cybox.core.ObservableComposition`.

Access to the top level `cybox.core.Observable` is made via `observable` property.

---

**Default Value:** Empty list.

**Returns** A list of `cybox.core.Observable` instances.

**set\_produced\_time** (*produced\_time*)

Sets the `produced_time` property of the `producer` property instance to *produced\_time*.

This is the same as calling `indicator.producer.time.produced_time = produced_time`.

The *produced\_time* parameter must be an instance of `str`, `datetime.datetime`, or `cybox.common.DateTimeWithPrecision`.

---

**Note:** If *produced\_time* is a `str` or `datetime.datetime` instance an attempt will be made to convert it into an instance of `cybox.common.DateTimeWithPrecision`.

---

**Parameters produced\_time** – An instance of `str`, `datetime.datetime`, or `cybox.common.DateTimeWithPrecision`.

**set\_producer\_identity** (*identity*)

Sets the name of the producer of this indicator.

This is the same as calling `indicator.producer.identity.name = identity`.

If the `producer` property is `None`, it will be initialized to an instance of `stix.common.information_source.InformationSource`.

If the `identity` property of the `producer` instance is `None`, it will be initialized to an instance of `stix.common.identity.Identity`.

---

**Note:** if the *identity* parameter is not an instance `stix.common.identity.Identity` an attempt will be made to convert it to one.

---

**Parameters identity** – An instance of `str` or `stix.common.identity.Identity`.

**set\_received\_time** (*received\_time*)

Sets the received time for this *Indicator*.

This is the same as calling `indicator.producer.time.produced_time = produced_time`.

The *received\_time* parameter must be an instance of `str`, `datetime.datetime`, or `cybox.common.DateTimeWithPrecision`.

**Parameters received\_time** – An instance of `str`, `datetime.datetime`, or `cybox.common.DateTimeWithPrecision`.

---

**Note:** If *received\_time* is a `str` or `datetime.datetime` instance an attempt will be made to convert it into an instance of `cybox.common.DateTimeWithPrecision`.

---

**short\_description**

A single short description about the contents or purpose of this object.

Default Value: `None`

---

**Note:** If this object has more than one short description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**to\_dict** ()

Convert to a dict

Subclasses can override this function.

**Returns** Python dict with keys set from this Entity.

**to\_json** ()

Export an object as a JSON String.

**to\_obj** (*ns\_info=None*)  
 Convert to a GenerateDS binding object.  
 Subclasses can override this function.

**Returns** An instance of this Entity's `_binding_class` with properties set from this Entity.

**class** `stix.indicator.indicator.CompositeIndicatorExpression` (*operator='OR', \*args*)  
 Bases: `mixbox.entities.EntityList`

Implementation of the STIX `CompositeIndicatorExpressionType`.

The `CompositeIndicatorExpression` class implements methods found on `collections.MutableSequence` and as such can be interacted with as a list (e.g., `append()`).

---

**Note:** The `append()` method can only accept instances of `Indicator`.

---

## Examples

Add a `Indicator` instance to an instance of `CompositeIndicatorExpression`:

```
>>> i = Indicator()
>>> comp = CompositeIndicatorExpression()
>>> comp.append(i)
```

Create a `CompositeIndicatorExpression` from a list of `Indicator` instances using `*args` argument list:

```
>>> list_indicators = [Indicator() for i in xrange(10)]
>>> comp = CompositeIndicatorExpression(CompositeIndicatorExpression.OP_OR, *list_indicators)
>>> len(comp)
10
```

## Parameters

- **operator** (*str, optional*) – The logical composition operator. Must be "AND" or "OR".
- **\*args** – Variable length argument list of `Indicator` instances.

### OP\_AND

*str*

String "AND"

### OP\_OR

*str*

String "OR"

### OPERATORS

*tuple*

Tuple of allowed operator values.

### operator

*str*

The logical composition operator. Must be "AND" or "OR".

**to\_obj** (*ns\_info=None*)

Convert to a GenerateDS binding object.

Subclasses can override this function.

**Returns** An instance of this Entity's `_binding_class` with properties set from this Entity.

**class** `stix.indicator.indicator.RelatedIndicators` (*related\_indicators=None, scope=None*)

Bases: `stix.common.related.GenericRelationshipList`

The `RelatedIndicators` class provides functionality for adding `stix.common.related.RelatedIndicator` instances to an `Indicator` instance.

The `RelatedIndicators` class implements methods found on `collections.MutableSequence` and as such can be interacted with as a list (e.g., `append()`).

The `append()` method can accept instances of `stix.common.related.RelatedIndicator` or `Indicator` as an argument.

---

**Note:** Calling `append()` with an instance of `stix.coa.CourseOfAction` will wrap that instance in a `stix.common.related.RelatedIndicator` layer, with `item` set to the `Indicator` instance.

---

## Examples

Append an instance of `Indicator` to the `Indicator.related_indicators` property. The instance of `Indicator` will be wrapped in an instance of `stix.common.related.RelatedIndicator`:

```
>>> related = Indicator()
>>> parent_indicator = Indicator()
>>> parent_indicator.related_indicators.append(related)
>>> print(type(indicator.related_indicators[0]))
<class 'stix.common.related.RelatedIndicator'>
```

Iterate over the `related_indicators` property of an `Indicator` instance and print the ids of each underlying `Indicator` instance:

```
>>> for related in indicator.related_indicators:
>>>     print(related.item.id_)
```

## Parameters

- **related\_indicators** (*list, optional*) – A list of `Indicator` or `stix.common.related.RelatedIndicator` instances.
- **scope** (*str, optional*) – The scope of the items. Can be set to "inclusive" or "exclusive". See `stix.common.related.GenericRelationshipList` documentation for more information.

## scope

*str*

The scope of the items. Can be set to "inclusive" or "exclusive". See `stix.common.related.GenericRelationshipList` documentation for more information.

**to\_obj** (*ns\_info=None*)

Convert to a GenerateDS binding object.

Subclasses can override this function.



**Returns** An instance of this Entity's `_binding_class` with properties set from this Entity.

**class** `stix.indicator.indicator.RelatedCampaignRefs` (*related\_campaign\_refs=None*,  
*scope=None*)

Bases: `stix.common.related.GenericRelationshipList`

**to\_obj** (*ns\_info=None*)

Convert to a GenerateDS binding object.

Subclasses can override this function.

**Returns** An instance of this Entity's `_binding_class` with properties set from this Entity.

**class** `stix.indicator.indicator.SuggestedCOAs` (*suggested\_coas=None*, *scope=None*)

Bases: `stix.common.related.GenericRelationshipList`

The SuggestedCOAs class provides functionality for adding `stix.common.related.RelatedCOA` instances to an `Indicator` instance.

The SuggestedCOAs class implements methods found on `collections.MutableSequence` and as such can be interacted with as a list (e.g., `append()`).

The `append()` method can accept instances of `stix.common.related.RelatedCOA` or `stix.coa.CourseOfAction` as an argument.

---

**Note:** Calling `append()` with an instance of `stix.coa.CourseOfAction` will wrap that instance in a `stix.common.related.RelatedCOA` layer, with the `item` set to the `stix.coa.CourseOfAction` instance.

---

## Examples

Append an instance of `stix.coa.CourseOfAction` to the `Indicator.suggested_coas` property. The instance of `stix.coa.CourseOfAction` will be wrapped in an instance of `stix.common.related.RelatedCOA`.

```
>>> coa = CourseOfAction()
>>> indicator = Indicator()
>>> indicator.suggested_coas.append(coa)
>>> print(type(indicator.suggested_coas[0]))
<class 'stix.common.related.RelatedCOA'>
```

Iterate over the `suggested_coas` property of an `Indicator` instance and print the ids of each underlying `stix.coa.CourseOfAction` instance.

```
>>> for related_coa in indicator.suggested_coas:
>>>     print(related_coa.item.id_)
```

## Parameters

- **suggested\_coas** (*list*) – A list of `stix.coa.CourseOfAction` or `stix.common.related.RelatedCOA` instances.
- **scope** (*str*) – The scope of the items. Can be set to "inclusive" or "exclusive". See `stix.common.related.GenericRelationshipList` documentation for more information.

**scope**  
*str*

The scope of the items. Can be set to "inclusive" or "exclusive". See [stix.common.related.GenericRelationshipList](#) documentation for more information.

**to\_obj** (*ns\_info=None*)

Convert to a GenerateDS binding object.

Subclasses can override this function.

**Returns** An instance of this Entity's `_binding_class` with properties set from this Entity.

**class** `stix.indicator.indicator.IndicatorTypes` (\*args)

Bases: `stix.base.TypedList`

A `stix.common.vocabs.VocabString` collection which defaults to `stix.common.vocabs.IndicatorType`. This class implements methods found on `collections.MutableSequence` and as such can be interacted with like a list.

---

**Note:** The `append()` method can accept `str` or `stix.common.vocabs.VocabString` instances. If a `str` instance is passed in, an attempt will be made to convert it to an instance of `stix.common.vocabs.IndicatorType`.

---

## Examples

Add an instance of `stix.common.vocabs.IndicatorType`:

```
>>> from stix.common.vocabs import IndicatorType
>>> itypes = IndicatorTypes()
>>> type_ = IndicatorType(IndicatorType.TERM_IP_WATCHLIST)
>>> itypes.append(type_)
>>> print(len(itypes))
1
```

Add a string value:

```
>>> from stix.common.vocabs import IndicatorType
>>> itypes = IndicatorTypes()
>>> type(IndicatorType.TERM_IP_WATCHLIST)
<type 'str'>
>>> itypes.append(IndicatorType.TERM_IP_WATCHLIST)
>>> print(len(itypes))
1
```

**Parameters** \*args – Variable length argument list of strings or `stix.common.vocabs.VocabString` instances.

**Version:** 1.2.0.5.dev0

## stix.indicator.sightings Module

### Classes

**class** `stix.indicator.sightings.Sighting` (*timestamp=None, timestamp\_precision=None, description=None*)

Bases: `stix.base.Entity`

**add\_description** (*description*)

Adds a description to the descriptions collection.

This is the same as calling “foo.descriptions.add(bar)”.

**description**

A single description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**class** `stix.indicator.sightings.Sightings` (*sightings\_count=None, \*args*)

Bases: *stix.base.EntityList*

**class** `stix.indicator.sightings.RelatedObservables` (*scope=None, \*args*)

Bases: *stix.common.related.GenericRelationshipList*

**Version:** 1.2.0.5.dev0

**stix.indicator.test\_mechanism Module****Classes**

**class** `stix.indicator.test_mechanism._BaseTestMechanism` (*id\_=None, idref=None*)

Bases: *stix.base.Entity*

**Functions**

`stix.indicator.test_mechanism.add_extension` (*cls*)

Registers a `stix.Entity` class as an implementation of an xml type.

Classes must have an `_XSI_TYPE` class attributes to be registered. The value of this attribute must be a valid `xsi:type`.

---

**Note:** This was designed for internal use.

---

**Version:** 1.2.0.5.dev0

**stix.indicator.valid\_time Module****Classes**

**class** `stix.indicator.valid_time.ValidTime` (*start\_time=None, end\_time=None*)

Bases: `mixbox.entities.Entity`

## STIX Report

Modules located in the `stix.report` package

**Version:** 1.2.0.5.dev0

### `stix.report` Module

#### Overview

The `stix.report` module implements `Report`.

A Report defines a contextual wrapper for a grouping of STIX content.

#### Documentation Resources

- [Report Data Model](#)

#### Classes

```
class stix.report.Report(id=None, idref=None, timestamp=None, header=None,
                        courses_of_action=None, exploit_targets=None, indicators=None, observables=None, incidents=None, threat_actors=None, ttps=None, campaigns=None, related_reports=None)
```

Bases: `stix.base.Entity`

A STIX Report Object.

##### Parameters

- **id** (*optional*) – An identifier. If None, a value will be generated via `mixbox.idgen.create_id()`. If set, this will unset the `idref` property.
- **idref** (*optional*) – An identifier reference. If set this will unset the `id_` property.
- **timestamp** (*optional*) – A timestamp value. Can be an instance of `datetime.datetime` or `str`.
- **header** – A Report `Header` object.
- **campaigns** – A collection of `Campaign` objects.
- **course\_of\_action** – A collection of `CourseOfAction` objects.
- **exploit\_targets** – A collection of `ExploitTarget` objects.
- **incidents** – A collection of `Incident` objects.
- **indicators** – A collection of `Indicator` objects.
- **threat\_actors** – A collection of `ThreatActor` objects.
- **ttps** – A collection of `TTP` objects.
- **related\_reports** – A collection of `RelatedReport` objects.

**add** (*entity*)

Adds *entity* to a top-level collection. For example, if *entity* is an `Indicator` object, the *entity* will be added to the `indicators` top-level collection.

**add\_campaign** (*campaign*)

Adds a Campaign object to the campaigns collection.

**add\_course\_of\_action** (*course\_of\_action*)

Adds an *CourseOfAction* object to the courses\_of\_action collection.

**add\_exploit\_target** (*exploit\_target*)

Adds an *ExploitTarget* object to the exploit\_targets collection.

**add\_incident** (*incident*)

Adds an *Incident* object to the incidents collection.

**add\_indicator** (*indicator*)

Adds an *Indicator* object to the indicators collection.

**add\_observable** (*observable*)

Adds an Observable object to the observables collection.

If *observable* is not an Observable instance, an effort will be made to convert it to one.

**add\_related\_report** (*related\_report*)

Adds an *RelatedReport* object to the related\_reports collection.

**add\_threat\_actor** (*threat\_actor*)

Adds an *ThreatActor* object to the threat\_actors collection.

**add\_ttp** (*ttp*)

Adds an *TTP* object to the ttps collection.

Version: 1.2.0.5.dev0

**stix.report.header Module****Classes**

**class** `stix.report.header.Header` (*title=None, description=None, short\_description=None, handling=None, intents=None, information\_source=None*)

Bases: `stix.base.Entity`

The Report Header.

**Parameters**

- **handling** – The data marking section of the Header.
- **information\_source** – The *InformationSource* section of the Header.
- **intents** – A collection of *VocabString* defining the intent of the parent *Report*.
- **description** – A description of the intent or purpose of the parent *Report*.
- **short\_description** – A short description of the intent or purpose of the parent *Report*.
- **title** – The title of the *Report*.

**title**

The title of the parent *Report*.

**add\_description** (*description*)

Adds a description to the descriptions collection.

This is the same as calling “foo.descriptions.add(bar)”.

**add\_intent** (*intent*)

Adds *VocabString* object to the intents collection.

If the input is not an instance of *VocabString*, an effort will be made to convert it into an instance of *ReportIntent*.

**add\_short\_description** (*description*)

Adds a description to the short\_descriptions collection.

This is the same as calling “foo.short\_descriptions.add(bar)”.

**description**

A single description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**short\_description**

A single short description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one short description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

## STIX Threat Actor

Modules located in the `stix.threat_actor` package

**Version:** 1.2.0.5.dev0

### `stix.threat_actor` Module

#### Overview

The `stix.threat_actor` module implements *ThreatActor*.

ThreatActors are characterizations of malicious actors (or adversaries) representing a cyber attack threat including presumed intent and historically observed behavior.

#### Documentation Resources

- [Threat Actor Data Model](#)

## Classes

**class** `stix.threat_actor.ThreatActor` (*id=None, idref=None, timestamp=None, title=None, description=None, short\_description=None*)

Bases: `stix.base.BaseCoreComponent`

Implementation of the STIX Threat Actor.

### Parameters

- **id** (*optional*) – An identifier. If `None`, a value will be generated via `mixbox.idgen.create_id()`. If set, this will unset the `idref` property.
- **idref** (*optional*) – An identifier reference. If set this will unset the `id_` property.
- **timestamp** (*optional*) – A timestamp value. Can be an instance of `datetime.datetime` or `str`.
- **description** – A description of the purpose or intent of this object.
- **short\_description** – A short description of the intent or purpose of this object.
- **title** – The title of this object.

**add\_description** (*description*)

Adds a description to the `descriptions` collection.

This is the same as calling “`foo.descriptions.add(bar)`”.

**add\_intended\_effect** (*value*)

Adds a *Statement* object to the `intended_effects` collection.

If *value* is a string, an attempt will be made to convert it into an instance of *Statement*.

**add\_motivation** (*value*)

Adds a *Motivation* object to the `motivations` collection.

**add\_planning\_and\_operational\_support** (*value*)

Adds a *VocabString* object to the `planning_and_operational_supports` collection.

If *value* is a string, an attempt will be made to convert it to an instance of *PlanningAndOperationalSupport*.

**add\_short\_description** (*description*)

Adds a description to the `short_descriptions` collection.

This is the same as calling “`foo.short_descriptions.add(bar)`”.

**add\_sophistication** (*value*)

Adds a *VocabString* object to the `sophistications` collection.

If *value* is a string, an attempt will be made to convert it to an instance of *ThreatActorSophistication*.

**add\_type** (*value*)

Adds a *VocabString* object to the `types` collection.

If set to a string, an attempt will be made to convert it into an instance of *ThreatActorType*.

**description**

A single description about the contents or purpose of this object.

Default Value: `None`

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**find** (*id\_*)

Searches the children of a *Entity* implementation for an object with an *id\_* property that matches *id\_*.

**short\_description**

A single short description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one short description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**to\_dict** ()

Convert to a dict

Subclasses can override this function.

**Returns** Python dict with keys set from this *Entity*.

**to\_json** ()

Export an object as a JSON String.

**to\_obj** (*ns\_info=None*)

Convert to a GenerateDS binding object.

Subclasses can override this function.

**Returns** An instance of this *Entity*'s *\_binding\_class* with properties set from this *Entity*.

**class** *stix.threat\_actor.AssociatedActors* (*scope=None, \*args*)  
Bases: *stix.common.related.GenericRelationshipList*

**class** *stix.threat\_actor.AssociatedCampaigns* (*scope=None, \*args*)  
Bases: *stix.common.related.GenericRelationshipList*

**class** *stix.threat\_actor.ObservedTTPs* (*scope=None, \*args*)  
Bases: *stix.common.related.GenericRelationshipList*

## STIX Tactics, Techniques, and Procedures (TTP)

Modules located in the *stix.ttp* package

**Version:** 1.2.0.5.dev0

### **stix.ttp** Module

#### Overview

The *stix.ttp* module implements *TTP*.



TTPs are representations of the behavior or modus operandi of cyber adversaries.

## Documentation Resources

- [TTP Data Model](#)

## Classes

```
class stix.ttp.TTP (id=None, idref=None, timestamp=None, title=None, description=None,  
                  short_description=None)  
Bases: stix.base.BaseCoreComponent
```

Implementation of the STIX TTP.

### Parameters

- **id** (*optional*) – An identifier. If `None`, a value will be generated via `mixbox.idgen.create_id()`. If set, this will unset the `idref` property.
- **idref** (*optional*) – An identifier reference. If set this will unset the `id_` property.
- **timestamp** (*optional*) – A timestamp value. Can be an instance of `datetime.datetime` or `str`.
- **description** – A description of the purpose or intent of this object.
- **short\_description** – A short description of the intent or purpose of this object.
- **title** – The title of this object.

**add\_description** (*description*)

Adds a description to the `descriptions` collection.

This is the same as calling “`foo.descriptions.add(bar)`”.

**add\_intended\_effect** (*value*)

Adds a *Statement* object to the `intended_effects` collection.

If *value* is a string, an attempt will be made to convert it into an instance of *Statement*.

**add\_kill\_chain\_phase** (*value*)

Adds a *KillChainPhaseReference* to the `kill_chain_phases` collection.

**Parameters value** – A *KillChainPhase*, *KillChainPhaseReference* or a `str` representing the `phase_id` of. Note that you if you are defining a custom Kill Chain, you need to add it to the STIX package separately.

**add\_related\_package** (*value*)

Adds a *RelatedPackageRef* object to the `related_packages` collection.

**Parameters value** – A *RelatedPackageRef* or a *STIXPackage* object.

**add\_short\_description** (*description*)

Adds a description to the `short_descriptions` collection.

This is the same as calling “`foo.short_descriptions.add(bar)`”.

**description**

A single description about the contents or purpose of this object.

Default Value: `None`

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**find** (*id\_*)

Searches the children of a *Entity* implementation for an object with an *id\_* property that matches *id\_*.

**short\_description**

A single short description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one short description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**to\_dict** ()

Convert to a dict

Subclasses can override this function.

**Returns** Python dict with keys set from this *Entity*.

**to\_json** ()

Export an object as a JSON String.

**to\_obj** (*ns\_info=None*)

Convert to a GenerateDS binding object.

Subclasses can override this function.

**Returns** An instance of this *Entity*'s *\_binding\_class* with properties set from this *Entity*.

**Version:** 1.2.0.5.dev0

## stix.ttp.attack\_pattern Module

### Classes

**class** `stix.ttp.attack_pattern.AttackPattern` (*id\_=None, idref=None, title=None, description=None, short\_description=None*)

Bases: *stix.base.Entity*

**add\_description** (*description*)

Adds a description to the *descriptions* collection.

This is the same as calling “foo.descriptions.add(bar)”.

**add\_short\_description** (*description*)

Adds a description to the *short\_descriptions* collection.

This is the same as calling “foo.short\_descriptions.add(bar)”.

**description**

A single description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**short\_description**

A single short description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one short description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**Version:** 1.2.0.5.dev0

**stix.ttp.behavior Module****Classes**

**class** `stix.ttp.behavior.Behavior` (*malware\_instances=None*, *attack\_patterns=None*, *exploits=None*)

Bases: *stix.base.Entity*

**Version:** 1.2.0.5.dev0

**stix.ttp.exploit Module****Classes**

**class** `stix.ttp.exploit.Exploit` (*id=None*, *idref=None*, *title=None*, *description=None*, *short\_description=None*)

Bases: *stix.base.Entity*

**add\_description** (*description*)

Adds a description to the `descriptions` collection.

This is the same as calling “`foo.descriptions.add(bar)`”.

**add\_short\_description** (*description*)

Adds a description to the `short_descriptions` collection.

This is the same as calling “`foo.short_descriptions.add(bar)`”.

**description**

A single description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**short\_description**

A single short description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one short description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**Version:** 1.2.0.5.dev0

**stix.ttp.exploit\_targets Module**

**Classes**

**class** `stix.ttp.exploit_targets.ExploitTargets` (*scope=None, \*args*)

Bases: *stix.common.related.GenericRelationshipList*

**Version:** 1.2.0.5.dev0

**stix.ttp.infrastructure Module**

**Classes**

**class** `stix.ttp.infrastructure.Infrastructure` (*id=None, idref=None, title=None, description=None, short\_description=None*)

Bases: *stix.base.Entity*

**add\_description** (*description*)

Adds a description to the `descriptions` collection.

This is the same as calling “`foo.descriptions.add(bar)`”.

**add\_short\_description** (*description*)

Adds a description to the `short_descriptions` collection.

This is the same as calling “`foo.short_descriptions.add(bar)`”.

**description**

A single description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**short\_description**

A single short description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one short description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**Version:** 1.2.0.5.dev0

## stix.ttp.malware\_instance Module

### Classes

**class** stix.ttp.malware\_instance.**MalwareInstance** (*id\_=None*, *idref=None*, *title=None*, *description=None*, *short\_description=None*)

Bases: *stix.base.Entity*

**add\_description** (*description*)

Adds a description to the descriptions collection.

This is the same as calling “foo.descriptions.add(bar)”.

**add\_short\_description** (*description*)

Adds a description to the short\_descriptions collection.

This is the same as calling “foo.short\_descriptions.add(bar)”.

**description**

A single description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

**short\_description**

A single short description about the contents or purpose of this object.

Default Value: None

---

**Note:** If this object has more than one short description set, this will return the description with the lowest ordinality value.

---

**Returns** An instance of *StructuredText*

## Functions

`stix.ttp.malware_instance.add_extension(cls)`

Registers a `stix.Entity` class as an implementation of an xml type.

Classes must have an `_XSI_TYPE` class attributes to be registered. The value of this attribute must be a valid `xsi:type`.

---

**Note:** This was designed for internal use.

---

**Version:** 1.2.0.5.dev0

## `stix.ttp.related_ttps` Module

### Classes

**class** `stix.ttp.related_ttps.RelatedTTPs` (*scope=None, \*args*)

Bases: `stix.common.related.GenericRelationshipList`

**Version:** 1.2.0.5.dev0

## `stix.ttp.resource` Module

### Classes

**class** `stix.ttp.resource.Resource` (*tools=None, infrastructure=None, personas=None*)

Bases: `stix.base.Entity`

**Version:** 1.2.0.5.dev0

## `stix.ttp.victim_targeting` Module

### Classes

**class** `stix.ttp.victim_targeting.VictimTargeting`

Bases: `stix.base.Entity`

## STIX Utils

Modules located in the `stix.utils` package

**Version:** 1.2.0.5.dev0

## `stix.utils` Module

### Functions

`stix.utils.is_cdata(text)`

Returns True if `text` contains a CDATA block.

**Example**

```
>>> is_cdata("<![CDATA[Foo]]>")
True
>>> is_cdata("NOPE")
False
```

`stix.utils.strip_cdata(text)`

Removes all CDATA blocks from *text* if it contains them.

---

**Note:** If the function contains escaped XML characters outside of a CDATA block, they will be unescaped.

---

**Parameters** *string containing one or more CDATA blocks.* (A) –

**Returns** An XML unescaped string with CDATA block qualifiers removed.

`stix.utils.cdata(text)`

Wraps the input *text* in a `<![CDATA[ ]>` block.

If the text contains CDATA sections already, they are stripped and replaced by the application of an outer-most CDATA block.

**Parameters** *text* – A string to wrap in a CDATA block.

**Returns** The *text* value wrapped in `<![CDATA[ ]>`

`stix.utils.raise_warnings(func)`

Function decorator that causes all Python warnings to be raised as exceptions in the wrapped function.

**Example**

```
>>> @raise_warnings
>>> def foo():
>>>     warnings.warn("this will raise an exception")
```

`stix.utils.silence_warnings(func)`

Function decorator that silences/ignores all Python warnings in the wrapped function.

**Example**

```
>>> @silence_warnings
>>> def foo():
>>>     warnings.warn("this will not appear")
```

`stix.utils.xml_bool(value)`

Returns True if *value* is an acceptable xs:boolean True value. Returns False if *value* is an acceptable xs:boolean False value. If *value* is None, this function will return None.

**Version:** 1.2.0.5.dev0

**stix.utils.dates Module**

## Functions

`stix.utils.dates.parse_value(value)`

Attempts to parse *value* into an instance of `datetime.datetime`. If *value* is `None`, this function will return `None`.

**Parameters** *value* – A timestamp. This can be a string or `datetime.datetime` value.

`stix.utils.dates.serialize_value(value)`

Attempts to convert *value* into an ISO8601-compliant timestamp string. If *value* is `None`, `None` will be returned.

**Parameters** *value* – A `datetime.datetime` value.

**Returns** An ISO8601 formatted timestamp string.

`stix.utils.dates.parse_date(value)`

Attempts to parse *value* into an instance of `datetime.date`. If *value* is `None`, this function will return `None`.

**Parameters** *value* – A timestamp. This can be a string, `datetime.date`, or `datetime.datetime` value.

`stix.utils.dates.serialize_value(value)`

Attempts to convert *value* into an ISO8601-compliant timestamp string. If *value* is `None`, `None` will be returned.

**Parameters** *value* – A `datetime.datetime` value.

**Returns** An ISO8601 formatted timestamp string.

`stix.utils.dates.now()`

Returns the current UTC `datetime.datetime` timestamp.

**Version:** 1.2.0.5.dev0

## `stix.utils.nsparser` Module

### Constants

`stix.utils.nsparser.NS_CAMPAIGN_OBJECT = Namespace(name='http://stix.mitre.org/Campaign-1', prefix='campaign')`

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

`stix.utils.nsparser.NS_CAPEC_OBJECT = Namespace(name='http://capec.mitre.org/capec-2', prefix='capec', schema_)`

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

`stix.utils.nsparser.NS_CIQIDENTITY_OBJECT = Namespace(name='http://stix.mitre.org/extensions/Identity#CIQID)`

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

`stix.utils.nsparser.NS_COA_OBJECT = Namespace(name='http://stix.mitre.org/CourseOfAction-1', prefix='coa', sche)`

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

`stix.utils.nsparser.NS_CVRF_OBJECT = Namespace(name='http://www.icas.org/CVRF/schema/cvrf/1.1', prefix='cvrf')`

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace



URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

```
stix.utils.nsparser.NS_ET_OBJECT = Namespace(name='http://stix.mitre.org/ExploitTarget-1', prefix='et', schema_lo
```

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

```
stix.utils.nsparser.NS_GENERICSTRUCTUREDCOA_OBJECT = Namespace(name='http://stix.mitre.org/extensions/Str
```

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

```
stix.utils.nsparser.NS_GENERICTM_OBJECT = Namespace(name='http://stix.mitre.org/extensions/TestMechanism#G
```

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

```
stix.utils.nsparser.NS_INCIDENT_OBJECT = Namespace(name='http://stix.mitre.org/Incident-1', prefix='incident', s
```

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

```
stix.utils.nsparser.NS_INDICATOR_OBJECT = Namespace(name='http://stix.mitre.org/Indicator-2', prefix='indicator
```

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

```
stix.utils.nsparser.NS_IOC_OBJECT = Namespace(name='http://schemas.mandiant.com/2010/ioc', prefix='ioc', schem
```

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

```
stix.utils.nsparser.NS_IOCTR_OBJECT = Namespace(name='http://schemas.mandiant.com/2010/ioc/TR/', prefix='ioc
```

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

```
stix.utils.nsparser.NS_MARKING_OBJECT = Namespace(name='http://data-marking.mitre.org/Marking-1', prefix='m
```

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

```
stix.utils.nsparser.NS_OVALDEF_OBJECT = Namespace(name='http://oval.mitre.org/XMLSchema/oval-definitions-5'
```

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

```
stix.utils.nsparser.NS_OVALVAR_OBJECT = Namespace(name='http://oval.mitre.org/XMLSchema/oval-variables-5'
```

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

```
stix.utils.nsparser.NS_REPORT_OBJECT = Namespace(name='http://stix.mitre.org/Report-1', prefix='report', schem
```

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

```
stix.utils.nsparser.NS_SIMPLEMARKING_OBJECT = Namespace(name='http://data-marking.mitre.org/extensions/Ma
```

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace

URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

`stix.utils.nsparser.NS_SNORTTM_OBJECT = Namespace(name='http://stix.mitre.org/extensions/TestMechanism#Snort')`

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

`stix.utils.nsparser.NS_STIX_OBJECT = Namespace(name='http://stix.mitre.org/stix-1', prefix='stix', schema_location='')`

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

`stix.utils.nsparser.NS_STIXCAPEC_OBJECT = Namespace(name='http://stix.mitre.org/extensions/AP#CAPEC2.7-1', prefix='stix')`

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

`stix.utils.nsparser.NS_STIXCIQADDRESS_OBJECT = Namespace(name='http://stix.mitre.org/extensions/Address#CIQAddress', prefix='stix')`

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

`stix.utils.nsparser.NS_STIXCVRF_OBJECT = Namespace(name='http://stix.mitre.org/extensions/Vulnerability#CVRF', prefix='stix')`

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

`stix.utils.nsparser.NS_STIXMAEC_OBJECT = Namespace(name='http://stix.mitre.org/extensions/Malware#MAEC4.1', prefix='stix')`

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

`stix.utils.nsparser.NS_STIXOPENIOC_OBJECT = Namespace(name='http://stix.mitre.org/extensions/TestMechanism#OpenIOC', prefix='stix')`

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

`stix.utils.nsparser.NS_STIXOVAL_OBJECT = Namespace(name='http://stix.mitre.org/extensions/TestMechanism#OVAL', prefix='stix')`

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

`stix.utils.nsparser.NS_STIXCOMMON_OBJECT = Namespace(name='http://stix.mitre.org/common-1', prefix='stixCommon')`

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

`stix.utils.nsparser.NS_STIXVOCABS_OBJECT = Namespace(name='http://stix.mitre.org/default_vocabularies-1', prefix='stixVocabs')`

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

`stix.utils.nsparser.NS_TA_OBJECT = Namespace(name='http://stix.mitre.org/ThreatActor-1', prefix='ta', schema_location='')`

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

`stix.utils.nsparser.NS_TLPMARKING_OBJECT = Namespace(name='http://data-marking.mitre.org/extensions/Marking', prefix='stix')`

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace

URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

```
stix.utils.nsparser.NS_TOUMARKING_OBJECT = Namespace(name='http://data-marking.mitre.org/extensions/Marking')
```

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

```
stix.utils.nsparser.NS_TTP_OBJECT = Namespace(name='http://stix.mitre.org/TTP-1', prefix='ttp', schema_location')
```

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

```
stix.utils.nsparser.NS_XAL_OBJECT = Namespace(name='urn:oasis:names:tc:ciq:xal:3', prefix='xal', schema_location')
```

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

```
stix.utils.nsparser.NS_XNL_OBJECT = Namespace(name='urn:oasis:names:tc:ciq:xnl:3', prefix='xnl', schema_location')
```

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

```
stix.utils.nsparser.NS_XPIL_OBJECT = Namespace(name='urn:oasis:names:tc:ciq:xpil:3', prefix='xpil', schema_location')
```

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

```
stix.utils.nsparser.NS_YARATM_OBJECT = Namespace(name='http://stix.mitre.org/extensions/TestMechanism#YARA')
```

A convenience class which represents simplified XML namespace info, consisting of exactly one namespace URI, and an optional prefix and schema location URI. This is handy for building up big tables of namespace data.

**Version:** 1.2.0.5.dev0

## stix.utils.parser Module

### Classes

```
class stix.utils.parser.UnsupportedVersionError (message, expected=None, found=None)
```

Bases: `exceptions.Exception`

A parsed document is a version unsupported by the parser.

```
class stix.utils.parser.UnknownVersionError
```

Bases: `exceptions.Exception`

A parsed document contains no version information.

```
stix.utils.parser.UnsupportedRootElement
```

alias of `UnsupportedRootElementError`

```
class stix.utils.parser.EntityParser
```

Bases: `mixbox.parser.EntityParser`

**Version:** 1.2.0.5.dev0

## API Coverage

The *python-stix* APIs currently provide partial coverage of all STIX-defined constructs. Development is ongoing toward the goal of providing full STIX language support in the APIs. Until such time that full coverage is provided, an overview of which constructs are available in these APIs will be maintained below.

---

**Note:** Many STIX constructs can contain **CyBOX** constructs. The **python-cybox** project provides its own APIs for interacting with the **CyBOX** specification. Please see the [CyBOX API Documentation](#) for information about CyBOX API coverage.

---

### STIX Core

STIX Construct	API Coverage	Documentation
STIX Package	Full	<i>stix.core.stix_package.STIXPackage</i>
STIX Header	Full	<i>stix.core.stix_header.STIXHeader</i>
Related Packages	Full	<i>stix.core.stix_package.RelatedPackages</i>

### STIX Top-level Constructs

STIX Construct	API Coverage	Documentation
Campaign	Full	<i>stix.campaign.Campaign</i>
Course of Action	Full	<i>stix.coa.CourseOfAction</i>
Exploit Target	Full	<i>stix.exploit_target.ExploitTarget</i>
Incident	Partial	<i>stix.incident.Incident</i>
Indicator	Full	<i>stix.indicator.indicator.Indicator</i>
Observable	<i>Provided by CyBOX</i>	
Threat Actor	Full	<i>stix.threat_actor.ThreatActor</i>
TTP	Partial	<i>stix.ttp.TTP</i>

### STIX Features

STIX Construct	API Coverage	Documentation
Confidence	Partial	<i>stix.common.confidence.Confidence</i>
Handling	Full	<i>stix.data_marking.Marking</i>
Markup in Structured Text	× None	
Relationships	Full	

## STIX Extensions

STIX Construct	API Coverage	Documentation
<b>Address Extensions</b>		
CIQ Address	× None	
<b>Attack Pattern Extensions</b>		
CAPEC 2.7	× None	
<b>Identity Extensions</b>		
CIQ Identity	Partial	<a href="#">stix.extensions.identity.ciq_identity</a>
<b>Malware Extensions</b>		
MAEC	Full	<a href="#">stix.extensions.malware.maec_4_1_maec</a>
<b>Marking Extensions</b>		
Simple Marking	Full	<a href="#">stix.extensions.marking.simple_marking</a>
TLP	Full	<a href="#">stix.extensions.marking.tlp.TLPMarking</a>
Terms of Use	Full	<a href="#">stix.extensions.marking.terms_of_use</a>
<b>Structured COA Extensions</b>		
Generic Structured COA	Full	<a href="#">stix.extensions.structured_coa.generic_structured_coa</a>
<b>Test Mechanism Extensions</b>		
Generic Test Mechanism	Full	<a href="#">stix.extensions.test_mechanism.generic_test_mechanism</a>
OVAL	× None	
OpenIOC	Full	<a href="#">stix.extensions.test_mechanism.openioc</a>
SNORT	Full	<a href="#">stix.extensions.test_mechanism.snort</a>
YARA	Full	<a href="#">stix.extensions.test_mechanism.yara</a>
<b>Vulnerability Extensions</b>		
CVRF	× None	

## STIX Vocabularies

STIX Construct	API Coverage	Documentation
AssetTypeVocab-1.0	Full	<code>stix.common.vocabs.AssetType_1_0</code>
AttackerInfrastructureTypeVocab-1.0	Full	<code>stix.common.vocabs.AttackerInfrastructureType_1_0</code>
AttackerToolTypeVocab-1.0	Full	<code>stix.common.vocabs.AttackerToolType_1_0</code>
AvailabilityLossTypeVocab-1.0	Full	<code>stix.common.vocabs.AvailabilityLossType_1_0</code>
AvailabilityLossTypeVocab-1.1.1	Full	<code>stix.common.vocabs.AvailabilityLossType_1_1_1</code>
COAStageVocab-1.0	Full	<code>stix.common.vocabs.COAStage_1_0</code>
CampaignStatusVocab-1.0	Full	<code>stix.common.vocabs.CampaignStatus_1_0</code>
CourseOfActionTypeVocab-1.0	Full	<code>stix.common.vocabs.CourseOfActionType_1_0</code>
DiscoveryMethodVocab-1.0	Full	<code>stix.common.vocabs.DiscoveryMethod_1_0</code>
DiscoveryMethodVocab-2.0	Full	<code>stix.common.vocabs.DiscoveryMethod_2_0</code>
HighMediumLowVocab-1.0	Full	<code>stix.common.vocabs.HighMediumLow_1_0</code>
ImpactQualificationVocab-1.0	Full	<code>stix.common.vocabs.ImpactQualification_1_0</code>
ImpactRatingVocab-1.0	Full	<code>stix.common.vocabs.ImpactRating_1_0</code>
IncidentCategoryVocab-1.0	Full	<code>stix.common.vocabs.IncidentCategory_1_0</code>
IncidentEffectVocab-1.0	Full	<code>stix.common.vocabs.IncidentEffect_1_0</code>
IncidentStatusVocab-1.0	Full	<code>stix.common.vocabs.IncidentStatus_1_0</code>
IndicatorTypeVocab-1.0	Full	<code>stix.common.vocabs.IndicatorType_1_0</code>
IndicatorTypeVocab-1.1	Full	<code>stix.common.vocabs.IndicatorType_1_1</code>
InformationSourceRoleVocab-1.0	Full	<code>stix.common.vocabs.InformationSourceRole_1_0</code>
InformationTypeVocab-1.0	Full	<code>stix.common.vocabs.InformationType_1_0</code>
IntendedEffectVocab-1.0	Full	<code>stix.common.vocabs.IntendedEffect_1_0</code>
LocationClassVocab-1.0	Full	<code>stix.common.vocabs.LocationClass_1_0</code>
LossDurationVocab-1.0	Full	<code>stix.common.vocabs.LossDuration_1_0</code>
LossPropertyVocab-1.0	Full	<code>stix.common.vocabs.LossProperty_1_0</code>
MalwareTypeVocab-1.0	Full	<code>stix.common.vocabs.MalwareType_1_0</code>
ManagementClassVocab-1.0	Full	<code>stix.common.vocabs.ManagementClass_1_0</code>
MotivationVocab-1.0	Full	<code>stix.common.vocabs.Motivation_1_0</code>
MotivationVocab-1.0.1	Full	<code>stix.common.vocabs.Motivation_1_0_1</code>
MotivationVocab-1.1	Full	<code>stix.common.vocabs.Motivation_1_1</code>
OwnershipClassVocab-1.0	Full	<code>stix.common.vocabs.OwnershipClass_1_0</code>
PackageIntentVocab-1.0	Full	<code>stix.common.vocabs.PackageIntent_1_0</code>
PlanningAndOperationalSupportVocab-1.0	Full	<code>stix.common.vocabs.PlanningAndOperationalSupport_1_0</code>
PlanningAndOperationalSupportVocab-1.0.1	Full	<code>stix.common.vocabs.PlanningAndOperationalSupport_1_0_1</code>
SecurityCompromiseVocab-1.0	Full	<code>stix.common.vocabs.SecurityCompromise_1_0</code>
SystemTypeVocab-1.0	Full	<code>stix.common.vocabs.SystemType_1_0</code>
ThreatActorSophisticationVocab-1.0	Full	<code>stix.common.vocabs.ThreatActorSophistication_1_0</code>
ThreatActorTypeVocab-1.0	Full	<code>stix.common.vocabs.ThreatActorType_1_0</code>

---

## Contributing

---

If a bug is found, a feature is missing, or something just isn't behaving the way you'd expect it to, please submit an issue to our [tracker](#). If you'd like to contribute code to our repository, you can do so by issuing a [pull request](#) and we will work with you to try and integrate that code into our repository.





---

## Indices and tables

---

- `genindex`
- `modindex`
- `search`



**S**

- stix.base, 17
- stix.campaign, 19
- stix.coa, 51
- stix.coa.objective, 52
- stix.common, 21
- stix.common.activity, 21
- stix.common.confidence, 21
- stix.common.datetimewithprecision, 22
- stix.common.identity, 22
- stix.common.information\_source, 23
- stix.common.kill\_chains, 23
- stix.common.related, 24
- stix.common.statement, 25
- stix.common.structured\_text, 26
- stix.common.tools, 28
- stix.common.vocabs, 28
- stix.core.stix\_header, 46
- stix.core.stix\_package, 47
- stix.core.ttps, 50
- stix.data\_marking, 18
- stix.exploit\_target, 53
- stix.exploit\_target.configuration, 55
- stix.exploit\_target.vulnerability, 56
- stix.exploit\_target.weakness, 57
- stix.extensions.identity.ciq\_identity\_3\_0, 58
- stix.extensions.malware.maec\_4\_1\_malware, 60
- stix.extensions.marking.simple\_marking, 61
- stix.extensions.marking.terms\_of\_use\_marking, 61
- stix.extensions.marking.tlp, 61
- stix.extensions.structured\_coa.generic\_structured\_coa, 61
- stix.extensions.test\_mechanism.generic\_test\_mechanism, 62
- stix.extensions.test\_mechanism.open\_ioc\_2010\_test\_mechanism, 62
- stix.extensions.test\_mechanism.snort\_test\_mechanism, 62
- stix.extensions.test\_mechanism.yara\_test\_mechanism, 63
- stix.incident, 63
- stix.incident.affected\_asset, 66
- stix.incident.coa, 66
- stix.incident.contributors, 67
- stix.incident.direct\_impact\_summary, 67
- stix.incident.external\_id, 67
- stix.incident.history, 67
- stix.incident.impact\_assessment, 68
- stix.incident.indirect\_impact\_summary, 68
- stix.incident.loss\_estimation, 68
- stix.incident.property\_affected, 68
- stix.incident.time, 69
- stix.incident.total\_loss\_estimation, 69
- stix.indicator.indicator, 69
- stix.indicator.sightings, 78
- stix.indicator.test\_mechanism, 79
- stix.indicator.valid\_time, 79
- stix.report, 80
- stix.report.header, 81
- stix.threat\_actor, 82
- stix.ttp, 84
- stix.ttp.attack\_pattern, 86
- stix.ttp.behavior, 87
- stix.ttp.exploit, 87
- stix.ttp.exploit\_targets, 88
- stix.ttp.infrastructure, 88
- stix.ttp.malware\_instance, 89
- stix.ttp.related\_ttps, 90
- stix.ttp.resource, 90
- stix.ttp.victim\_targeting, 90
- stix.utils, 90
- stix.utils.dates, 91
- stix.utils.nsparser, 92
- stix.utils.parser, 95



## Symbols

- `_BaseNameElement` (class in `stix.extensions.identity.ciq_identity_3_0`), 59
  - `_BaseRelated` (class in `stix.common.related`), 24
  - `_BaseTestMechanism` (class in `stix.indicator.test_mechanism`), 79
  - `__delitem__()` (`stix.common.structured_text.StructuredTextList` method), 26
  - `__getitem__()` (`stix.common.structured_text.StructuredTextList` method), 26
  - `__iter__()` (`stix.common.structured_text.StructuredTextList` method), 27
  - `__str__()` (`stix.common.structured_text.StructuredText` method), 26
  - `__unicode__()` (`stix.common.structured_text.StructuredText` method), 26
- ## A
- `Activity` (class in `stix.common.activity`), 21
  - `add()` (`stix.common.structured_text.StructuredTextList` method), 27
  - `add()` (`stix.core.stix_package.STIXPackage` method), 48
  - `add()` (`stix.report.Report` method), 80
  - `add_activity()` (`stix.campaign.Campaign` method), 19
  - `add_affected_asset()` (`stix.incident.Incident` method), 63
  - `add_alternative_id()` (`stix.indicator.indicator.Indicator` method), 70
  - `add_campaign()` (`stix.core.stix_package.STIXPackage` method), 48
  - `add_campaign()` (`stix.report.Report` method), 80
  - `add_category()` (`stix.incident.Incident` method), 63
  - `add_coa_requested()` (`stix.incident.Incident` method), 64
  - `add_coa_taken()` (`stix.incident.Incident` method), 64
  - `add_configuration()` (`stix.exploit_target.ExploitTarget` method), 53
  - `add_coordinator()` (`stix.incident.Incident` method), 64
  - `add_course_of_action()` (`stix.core.stix_package.STIXPackage` method), 48
  - `add_course_of_action()` (`stix.report.Report` method), 81
  - `add_description()` (`stix.campaign.Campaign` method), 19
  - `add_description()` (`stix.coa.CourseOfAction` method), 51
  - `add_description()` (`stix.coa.objective.Objective` method), 52
  - `add_description()` (`stix.common.activity.Activity` method), 21
  - `add_description()` (`stix.common.confidence.Confidence` method), 21
  - `add_description()` (`stix.common.information_source.InformationSource` method), 23
  - `add_description()` (`stix.common.statement.Statement` method), 25
  - `add_description()` (`stix.core.stix_header.STIXHeader` method), 47
  - `add_description()` (`stix.exploit_target.configuration.Configuration` method), 56
  - `add_description()` (`stix.exploit_target.ExploitTarget` method), 54
  - `add_description()` (`stix.exploit_target.vulnerability.Vulnerability` method), 57
  - `add_description()` (`stix.exploit_target.weakness.Weakness` method), 58
  - `add_description()` (`stix.extensions.structured_coa.generic_structured_coa.G` method), 61
  - `add_description()` (`stix.extensions.test_mechanism.generic_test_mechanism` method), 62
  - `add_description()` (`stix.incident.affected_asset.AffectedAsset` method), 66
  - `add_description()` (`stix.incident.Incident` method), 64
  - `add_description()` (`stix.indicator.indicator.Indicator` method), 70
  - `add_description()` (`stix.indicator.sightings.Sighting` method), 78
  - `add_description()` (`stix.report.header.Header` method), 81
  - `add_description()` (`stix.threat_actor.ThreatActor` method), 83
  - `add_description()` (`stix.ttp.attack_pattern.AttackPattern` method), 86
  - `add_description()` (`stix.ttp.exploit.Exploit` method), 87
  - `add_description()` (`stix.ttp.infrastructure.Infrastructure` method), 88

`add_description()` (stix.ttp.malware\_instance.MalwareInstance method), 89

`add_description()` (stix.ttp.TTP method), 85

`add_discovery_method()` (stix.incident.Incident method), 64

`add_exploit_target()` (stix.core.stix\_package.STIXPackage method), 48

`add_exploit_target()` (stix.report.Report method), 81

`add_extension()` (in module stix.common.identity), 22

`add_extension()` (in module stix.data\_marking), 18

`add_extension()` (in module stix.indicator.test\_mechanism), 79

`add_extension()` (in module stix.ttp.malware\_instance), 90

`add_external_id()` (stix.incident.Incident method), 64

`add_incident()` (stix.core.stix\_package.STIXPackage method), 49

`add_incident()` (stix.report.Report method), 81

`add_indicated_ttp()` (stix.indicator.indicator.Indicator method), 70

`add_indicator()` (stix.core.stix\_package.STIXPackage method), 49

`add_indicator()` (stix.report.Report method), 81

`add_indicator_type()` (stix.indicator.indicator.Indicator method), 70

`add_intended_effect()` (stix.incident.Incident method), 64

`add_intended_effect()` (stix.threat\_actor.ThreatActor method), 83

`add_intended_effect()` (stix.ttp.TTP method), 85

`add_intent()` (stix.report.header.Header method), 81

`add_kill_chain_phase()` (stix.indicator.indicator.Indicator method), 70

`add_kill_chain_phase()` (stix.ttp.TTP method), 85

`add_motivation()` (stix.threat\_actor.ThreatActor method), 83

`add_object()` (stix.indicator.indicator.Indicator method), 71

`add_observable()` (stix.core.stix\_package.STIXPackage method), 49

`add_observable()` (stix.indicator.indicator.Indicator method), 71

`add_observable()` (stix.report.Report method), 81

`add_package_intent()` (stix.core.stix\_header.STIXHeader method), 47

`add_planning_and_operational_support()` (stix.threat\_actor.ThreatActor method), 83

`add_profile()` (stix.core.stix\_header.STIXHeader method), 47

`add_related_campaign()` (stix.indicator.indicator.Indicator method), 71

`add_related_indicator()` (stix.incident.Incident method), 64

`add_related_indicator()` (stix.indicator.indicator.Indicator method), 72

`add_related_observable()` (stix.incident.Incident method), 64

`add_related_package()` (stix.core.stix\_package.STIXPackage method), 49

`add_related_package()` (stix.ttp.TTP method), 85

`add_related_report()` (stix.report.Report method), 81

`add_report()` (stix.core.stix\_package.STIXPackage method), 49

`add_responder()` (stix.incident.Incident method), 65

`add_short_description()` (stix.campaign.Campaign method), 19

`add_short_description()` (stix.coa.CourseOfAction method), 51

`add_short_description()` (stix.coa.objective.Objective method), 52

`add_short_description()` (stix.common.tools.ToolInformation method), 28

`add_short_description()` (stix.core.stix\_header.STIXHeader method), 47

`add_short_description()` (stix.exploit\_target.configuration.Configuration method), 56

`add_short_description()` (stix.exploit\_target.ExploitTarget method), 54

`add_short_description()` (stix.exploit\_target.vulnerability.Vulnerability method), 57

`add_short_description()` (stix.incident.Incident method), 65

`add_short_description()` (stix.indicator.indicator.Indicator method), 72

`add_short_description()` (stix.report.header.Header method), 82

`add_short_description()` (stix.threat\_actor.ThreatActor method), 83

`add_short_description()` (stix.ttp.attack\_pattern.AttackPattern method), 86

`add_short_description()` (stix.ttp.exploit.Exploit method), 87

`add_short_description()` (stix.ttp.infrastructure.Infrastructure method), 88

`add_short_description()` (stix.ttp.malware\_instance.MalwareInstance method), 89

`add_short_description()` (stix.ttp.TTP method), 85

`add_sophistication()` (stix.threat\_actor.ThreatActor method), 83

`add_test_mechanism()` (stix.indicator.indicator.Indicator method), 72

`add_threat_actor()` (stix.core.stix\_package.STIXPackage method), 49

`add_threat_actor()` (stix.report.Report method), 81

`add_ttp()` (stix.core.stix\_package.STIXPackage method), 49

`add_ttp()` (stix.report.Report method), 81

`add_type()` (stix.threat\_actor.ThreatActor method), 83

`add_valid_time_position()`

- (stix.indicator.indicator.Indicator method), 72
- add\_victim() (stix.incident.Incident method), 65
- add\_vocab() (in module stix.common.vocabs), 46
- add\_vulnerability() (stix.exploit\_target.ExploitTarget method), 54
- add\_weakness() (stix.exploit\_target.ExploitTarget method), 54
- Address (class in stix.extensions.identity.ciq\_identity\_3\_0), 59
- AdministrativeArea (class in stix.extensions.identity.ciq\_identity\_3\_0), 59
- AffectedAsset (class in stix.incident.affected\_asset), 66
- AffectedSoftware (class in stix.exploit\_target.vulnerability), 57
- AssetType (class in stix.incident.affected\_asset), 66
- AssetType (in module stix.common.vocabs), 44
- AssetType\_1\_0 (class in stix.common.vocabs), 28
- AssociatedActors (class in stix.threat\_actor), 84
- AssociatedCampaigns (class in stix.campaign), 20
- AssociatedCampaigns (class in stix.threat\_actor), 84
- AttackerInfrastructureType (in module stix.common.vocabs), 44
- AttackerInfrastructureType\_1\_0 (class in stix.common.vocabs), 30
- AttackerToolType (in module stix.common.vocabs), 44
- AttackerToolType\_1\_0 (class in stix.common.vocabs), 31
- AttackPattern (class in stix.ttp.attack\_pattern), 86
- AttributedThreatActors (class in stix.incident), 66
- Attribution (class in stix.campaign), 20
- AvailabilityLossType (in module stix.common.vocabs), 44
- AvailabilityLossType\_1\_0 (class in stix.common.vocabs), 31
- AvailabilityLossType\_1\_1\_1 (class in stix.common.vocabs), 32
- B**
- Behavior (class in stix.ttp.behavior), 87
- C**
- Campaign (class in stix.campaign), 19
- CampaignStatus (in module stix.common.vocabs), 44
- CampaignStatus\_1\_0 (class in stix.common.vocabs), 32
- cdata() (in module stix.utils), 91
- CIQIdentity3\_0Instance (class in stix.extensions.identity.ciq\_identity\_3\_0), 58
- COARequested (class in stix.incident.coa), 66
- COAStage (in module stix.common.vocabs), 44
- COAStage\_1\_0 (class in stix.common.vocabs), 32
- COATaken (class in stix.incident.coa), 66
- COATime (class in stix.incident.coa), 67
- CompositeIndicatorExpression (class in stix.indicator.indicator), 75
- Confidence (class in stix.common.confidence), 21
- Configuration (class in stix.exploit\_target.configuration), 55
- ContactNumber (class in stix.extensions.identity.ciq\_identity\_3\_0), 59
- ContactNumberElement (class in stix.extensions.identity.ciq\_identity\_3\_0), 59
- ContributingSources (class in stix.common.information\_source), 23
- Contributors (class in stix.incident.contributors), 67
- Country (class in stix.extensions.identity.ciq\_identity\_3\_0), 59
- CourseOfAction (class in stix.coa), 51
- CourseOfActionType (in module stix.common.vocabs), 45
- CourseOfActionType\_1\_0 (class in stix.common.vocabs), 32
- CVSSVector (class in stix.exploit\_target.vulnerability), 57
- D**
- DATE\_PRECISION\_VALUES (in module stix.common.datetimewithprecision), 22
- DATETIME\_PRECISION\_VALUES (in module stix.common.datetimewithprecision), 22
- DateTimeWithPrecision (class in stix.common.datetimewithprecision), 22
- description (stix.campaign.Campaign attribute), 19
- description (stix.coa.CourseOfAction attribute), 51
- description (stix.coa.objective.Objective attribute), 52
- description (stix.common.activity.Activity attribute), 21
- description (stix.common.confidence.Confidence attribute), 21
- description (stix.common.information\_source.InformationSource attribute), 23
- description (stix.common.statement.Statement attribute), 25
- description (stix.core.stix\_header.STIXHeader attribute), 47
- description (stix.exploit\_target.configuration.Configuration attribute), 56
- description (stix.exploit\_target.ExploitTarget attribute), 54
- description (stix.exploit\_target.vulnerability.Vulnerability attribute), 57
- description (stix.exploit\_target.weakness.Weakness attribute), 58
- description (stix.extensions.structured\_coa.generic\_structured\_coa.Generic attribute), 61

- description (stix.extensions.test\_mechanism.generic\_test\_mechanism.GenericTestMechanism attribute), 62
- description (stix.incident.affected\_asset.AffectedAsset attribute), 66
- description (stix.incident.Incident attribute), 65
- description (stix.indicator.indicator.Indicator attribute), 72
- description (stix.indicator.sightings.Sighting attribute), 79
- description (stix.report.header.Header attribute), 82
- description (stix.threat\_actor.ThreatActor attribute), 83
- description (stix.ttp.attack\_pattern.AttackPattern attribute), 86
- description (stix.ttp.exploit.Exploit attribute), 87
- description (stix.ttp.infrastructure.Infrastructure attribute), 88
- description (stix.ttp.malware\_instance.MalwareInstance attribute), 89
- description (stix.ttp.TTP attribute), 85
- description\_of\_effect (stix.incident.property\_affected.PropertyAffected attribute), 68
- DirectImpactSummary (class in stix.incident.direct\_impact\_summary), 67
- DiscoveryMethod (in module stix.common.vocabs), 45
- DiscoveryMethod\_1\_0 (class in stix.common.vocabs), 33
- DiscoveryMethod\_2\_0 (class in stix.common.vocabs), 33
- ## E
- ElectronicAddressIdentifier (class in stix.extensions.identity.ciq\_identity\_3\_0), 59
- EncodedCDATA (class in stix.common), 21
- Entity (class in stix.base), 17
- EntityList (class in stix.base), 18
- EntityParser (class in stix.utils.parser), 95
- Exploit (class in stix.ttp.exploit), 87
- ExploitTarget (class in stix.exploit\_target), 53
- ExploitTargets (class in stix.ttp.exploit\_targets), 88
- ExternalID (class in stix.incident.external\_id), 67
- ## F
- find() (stix.base.Entity method), 17
- find() (stix.campaign.Campaign method), 20
- find() (stix.coa.CourseOfAction method), 51
- find() (stix.core.stix\_package.STIXPackage method), 49
- find() (stix.exploit\_target.ExploitTarget method), 54
- find() (stix.incident.Incident method), 65
- find() (stix.indicator.indicator.Indicator method), 73
- find() (stix.threat\_actor.ThreatActor method), 84
- find() (stix.ttp.TTP method), 86
- FreeTextAddress (class in stix.extensions.identity.ciq\_identity\_3\_0), 59
- FreeTextLine (class in stix.extensions.identity.ciq\_identity\_3\_0), 59
- GenericRelationship (class in stix.common.related), 24
- GenericRelationshipList (class in stix.common.related), 24
- GenericStructuredCOA (class in stix.extensions.structured\_coa.generic\_structured\_coa), 61
- GenericTestMechanism (class in stix.extensions.test\_mechanism.generic\_test\_mechanism), 62
- get\_produced\_time() (stix.indicator.indicator.Indicator method), 73
- get\_received\_time() (stix.indicator.indicator.Indicator method), 73
- ## G
- ## H
- Header (class in stix.report.header), 81
- HighMediumLow (in module stix.common.vocabs), 45
- HighMediumLow\_1\_0 (class in stix.common.vocabs), 34
- History (class in stix.incident.history), 67
- HistoryItem (class in stix.incident.history), 67
- ## I
- id\_ (stix.common.structured\_text.StructuredText attribute), 26
- Identity (class in stix.common.identity), 22
- ImpactAssessment (class in stix.incident.impact\_assessment), 68
- ImpactQualification (in module stix.common.vocabs), 45
- ImpactQualification\_1\_0 (class in stix.common.vocabs), 34
- ImpactRating (in module stix.common.vocabs), 45
- ImpactRating\_1\_0 (class in stix.common.vocabs), 34
- Incident (class in stix.incident), 63
- IncidentCategory (in module stix.common.vocabs), 45
- IncidentCategory\_1\_0 (class in stix.common.vocabs), 34
- IncidentEffect (in module stix.common.vocabs), 45
- IncidentEffect\_1\_0 (class in stix.common.vocabs), 34
- IncidentStatus (in module stix.common.vocabs), 45
- IncidentStatus\_1\_0 (class in stix.common.vocabs), 35
- Indicator (class in stix.indicator.indicator), 69
- IndicatorType (in module stix.common.vocabs), 45
- IndicatorType\_1\_0 (class in stix.common.vocabs), 35
- IndicatorType\_1\_1 (class in stix.common.vocabs), 35
- IndicatorTypes (class in stix.indicator.indicator), 78
- IndirectImpactSummary (class in stix.incident.indirect\_impact\_summary), 68
- InformationSource (class in stix.common.information\_source), 23



- InformationSourceRole (in module stix.common.vocabs), 45
- InformationSourceRole\_1\_0 (class in stix.common.vocabs), 36
- InformationType (in module stix.common.vocabs), 45
- InformationType\_1\_0 (class in stix.common.vocabs), 36
- Infrastructure (class in stix.ttp.infrastructure), 88
- insert() (stix.common.structured\_text.StructuredTextList method), 27
- IntendedEffect (in module stix.common.vocabs), 45
- IntendedEffect\_1\_0 (class in stix.common.vocabs), 36
- is\_cdata() (in module stix.utils), 90
- is\_plain() (stix.common.vocabs.VocabString method), 44
- is\_plain() (stix.incident.affected\_asset.AssetType method), 66
- ## J
- JournalEntry (class in stix.incident.history), 67
- ## K
- KillChain (class in stix.common.kill\_chains), 23
- KillChainPhase (class in stix.common.kill\_chains), 23
- KillChainPhaseReference (class in stix.common.kill\_chains), 23
- KillChainPhasesReference (class in stix.common.kill\_chains), 23
- KillChains (class in stix.common.kill\_chains), 23
- ## L
- Language (class in stix.extensions.identity.ciq\_identity\_3\_0), 59
- LeveragedTTPs (class in stix.incident), 66
- LocationClass (in module stix.common.vocabs), 45
- LocationClass\_1\_0 (class in stix.common.vocabs), 37
- LossDuration (in module stix.common.vocabs), 45
- LossDuration\_1\_0 (class in stix.common.vocabs), 37
- LossEstimation (class in stix.incident.loss\_estimation), 68
- LossProperty (in module stix.common.vocabs), 45
- LossProperty\_1\_0 (class in stix.common.vocabs), 38
- ## M
- MAECInstance (class in stix.extensions.malware.maec\_4\_1\_malware), 61
- MalwareInstance (class in stix.ttp.malware\_instance), 89
- MalwareType (in module stix.common.vocabs), 45
- MalwareType\_1\_0 (class in stix.common.vocabs), 38
- ManagementClass (in module stix.common.vocabs), 45
- ManagementClass\_1\_0 (class in stix.common.vocabs), 38
- Marking (class in stix.data\_marking), 18
- MarkingSpecification (class in stix.data\_marking), 18
- MarkingStructure (class in stix.data\_marking), 18
- Motivation (in module stix.common.vocabs), 45
- Motivation\_1\_0 (class in stix.common.vocabs), 38
- Motivation\_1\_0\_1 (class in stix.common.vocabs), 39
- Motivation\_1\_1 (class in stix.common.vocabs), 39
- ## N
- NameElement (class in stix.extensions.identity.ciq\_identity\_3\_0), 59
- NameLine (class in stix.extensions.identity.ciq\_identity\_3\_0), 59
- Names (class in stix.campaign), 20
- next\_ordinality (stix.common.structured\_text.StructuredTextList attribute), 27
- NonPublicDataCompromised (class in stix.incident.property\_affected), 68
- now() (in module stix.utils.dates), 92
- NS\_CAMPAIGN\_OBJECT (in module stix.utils.nsparser), 92
- NS\_CAPEC\_OBJECT (in module stix.utils.nsparser), 92
- NS\_CIQIDENTITY\_OBJECT (in module stix.utils.nsparser), 92
- NS\_COA\_OBJECT (in module stix.utils.nsparser), 92
- NS\_CVRF\_OBJECT (in module stix.utils.nsparser), 92
- NS\_ET\_OBJECT (in module stix.utils.nsparser), 93
- NS\_GENERICSTRUCTUREDCOA\_OBJECT (in module stix.utils.nsparser), 93
- NS\_GENERICTM\_OBJECT (in module stix.utils.nsparser), 93
- NS\_INCIDENT\_OBJECT (in module stix.utils.nsparser), 93
- NS\_INDICATOR\_OBJECT (in module stix.utils.nsparser), 93
- NS\_IOC\_OBJECT (in module stix.utils.nsparser), 93
- NS\_IOCTLR\_OBJECT (in module stix.utils.nsparser), 93
- NS\_MARKING\_OBJECT (in module stix.utils.nsparser), 93
- NS\_OVALDEF\_OBJECT (in module stix.utils.nsparser), 93
- NS\_OVALVAR\_OBJECT (in module stix.utils.nsparser), 93
- NS\_REPORT\_OBJECT (in module stix.utils.nsparser), 93
- NS\_SIMPLEMARKING\_OBJECT (in module stix.utils.nsparser), 93
- NS\_SNORTTM\_OBJECT (in module stix.utils.nsparser), 94
- NS\_STIX\_OBJECT (in module stix.utils.nsparser), 94
- NS\_STIXCAPEC\_OBJECT (in module stix.utils.nsparser), 94
- NS\_STIXCIQADDRESS\_OBJECT (in module stix.utils.nsparser), 94

NS\_STIXCOMMON\_OBJECT (in module PackageIntent\_1\_0 (class in stix.common.vocabs), 40  
stix.utils.nsparser), 94

NS\_STIXCVRF\_OBJECT (in module parse\_date() (in module stix.utils.dates), 92  
stix.utils.nsparser), 94

NS\_STIXMAEC\_OBJECT (in module parse\_value() (in module stix.utils.dates), 92  
stix.utils.nsparser), 94

NS\_STIXOPENIOC\_OBJECT (in module PartyName (class in stix.extensions.identity.ciq\_identity\_3\_0),  
stix.utils.nsparser), 94

NS\_STIXOVAL\_OBJECT (in module 60  
stix.utils.nsparser), 94

NS\_STIXVOCABS\_OBJECT (in module 60  
stix.utils.nsparser), 94

NS\_TA\_OBJECT (in module stix.utils.nsparser), 94

NS\_TLPMARKING\_OBJECT (in module stix.utils.nsparser), 94

NS\_TOUMARKING\_OBJECT (in module stix.utils.nsparser), 95

NS\_TTP\_OBJECT (in module stix.utils.nsparser), 95

NS\_XAL\_OBJECT (in module stix.utils.nsparser), 95

NS\_XNL\_OBJECT (in module stix.utils.nsparser), 95

NS\_XPIL\_OBJECT (in module stix.utils.nsparser), 95

NS\_YARATM\_OBJECT (in module stix.utils.nsparser),  
95

## O

Objective (class in stix.coa.objective), 52

observables (stix.indicator.indicator.Indicator attribute),  
73

ObservedTTPs (class in stix.threat\_actor), 84

OP\_AND (stix.indicator.indicator.CompositeIndicatorExpression  
attribute), 75

OP\_OR (stix.indicator.indicator.CompositeIndicatorExpression  
attribute), 75

OpenIOCTestMechanism (class in stix.extensions.test\_mechanism.open\_ioc\_2010\_test\_mechanism),  
62

operator (stix.indicator.indicator.CompositeIndicatorExpression  
attribute), 75

OPERATORS (stix.indicator.indicator.CompositeIndicatorExpression  
attribute), 75

OrganisationInfo (class in stix.extensions.identity.ciq\_identity\_3\_0),  
60

OrganisationName (class in stix.extensions.identity.ciq\_identity\_3\_0),  
60

OrganisationNameElement (class in stix.extensions.identity.ciq\_identity\_3\_0),  
60

OwnershipClass (in module stix.common.vocabs), 45

OwnershipClass\_1\_0 (class in stix.common.vocabs), 40

## P

PackageIntent (in module stix.common.vocabs), 45

PackageIntent\_1\_0 (class in stix.common.vocabs), 40

parse\_date() (in module stix.utils.dates), 92

parse\_value() (in module stix.utils.dates), 92

PartyName (class in stix.extensions.identity.ciq\_identity\_3\_0),  
60

PersonName (class in stix.extensions.identity.ciq\_identity\_3\_0),  
60

PersonNameElement (class in stix.extensions.identity.ciq\_identity\_3\_0),  
60

PlanningAndOperationalSupport (in module stix.common.vocabs), 45

PlanningAndOperationalSupport\_1\_0 (class in stix.common.vocabs), 40

PlanningAndOperationalSupport\_1\_0\_1 (class in stix.common.vocabs), 41

PotentialCOAs (class in stix.exploit\_target), 55

profiles (stix.core.stix\_header.STIXHeader attribute), 47

PropertyAffected (class in stix.incident.property\_affected), 68

## R

raise\_warnings() (in module stix.utils), 91

register\_vocab() (in module stix.common.vocabs), 46

RelatedCampaign (class in stix.common.related), 24

RelatedCampaignRefs (class in stix.indicator.indicator),  
77

RelatedCOA (class in stix.common.related), 24

RelatedCOAs (class in stix.coa), 52

RelatedExploitTarget (class in stix.common.related), 25

RelatedExploitTargets (class in stix.exploit\_target), 55

RelatedIdentities (class in stix.common.identity), 22

RelatedIdentity (class in stix.common.related), 25

RelatedIncidents (class in stix.common.related), 25

RelatedIncidents (class in stix.campaign), 20

RelatedIncidents (class in stix.incident), 66

RelatedIndicator (class in stix.common.related), 25

RelatedIndicators (class in stix.campaign), 20

RelatedIndicators (class in stix.incident), 66

RelatedIndicators (class in stix.indicator.indicator), 76

RelatedObservable (class in stix.common.related), 25

RelatedObservables (class in stix.incident), 66

RelatedObservables (class in stix.indicator.sightings), 79

RelatedPackageRef (class in stix.common.related), 24

RelatedPackageRefs (class in stix.common.related), 24

RelatedPackages (class in stix.core.stix\_package), 50

RelatedReport (class in stix.common.related), 25

RelatedReports (class in stix.common.related), 25

RelatedThreatActor (class in stix.common.related), 25

RelatedTTP (class in stix.common.related), 25

RelatedTTPs (class in stix.campaign), 20

RelatedTTPs (class in stix.ttp.related\_ttps), 90

- remove() (stix.common.structured\_text.StructuredTextList method), 27
- Report (class in stix.report), 80
- ReportIntent\_1\_0 (class in stix.common.vocabs), 42
- reset() (stix.common.structured\_text.StructuredTextList method), 27
- Resource (class in stix.ttp.resource), 90
- ## S
- scope (stix.indicator.indicator.RelatedIndicators attribute), 76
- scope (stix.indicator.indicator.SuggestedCOAs attribute), 77
- SecurityCompromise (in module stix.common.vocabs), 46
- SecurityCompromise\_1\_0 (class in stix.common.vocabs), 42
- serialize\_value() (in module stix.utils.dates), 92
- set\_produced\_time() (stix.indicator.indicator.Indicator method), 73
- set\_producer\_identity() (stix.indicator.indicator.Indicator method), 74
- set\_received\_time() (stix.indicator.indicator.Indicator method), 74
- short\_description (stix.campaign.Campaign attribute), 20
- short\_description (stix.coa.CourseOfAction attribute), 52
- short\_description (stix.coa.objective.Objective attribute), 53
- short\_description (stix.common.tools.ToolInformation attribute), 28
- short\_description (stix.core.stix\_header.STIXHeader attribute), 47
- short\_description (stix.exploit\_target.configuration.Configuration attribute), 56
- short\_description (stix.exploit\_target.ExploitTarget attribute), 54
- short\_description (stix.exploit\_target.vulnerability.Vulnerability attribute), 57
- short\_description (stix.incident.Incident attribute), 65
- short\_description (stix.indicator.indicator.Indicator attribute), 74
- short\_description (stix.report.header.Header attribute), 82
- short\_description (stix.threat\_actor.ThreatActor attribute), 84
- short\_description (stix.ttp.attack\_pattern.AttackPattern attribute), 87
- short\_description (stix.ttp.exploit.Exploit attribute), 88
- short\_description (stix.ttp.infrastructure.Infrastructure attribute), 89
- short\_description (stix.ttp.malware\_instance.MalwareInstance attribute), 89
- short\_description (stix.ttp.TTP attribute), 86
- Sighting (class in stix.indicator.sightings), 78
- Sightings (class in stix.indicator.sightings), 79
- silence\_warnings() (in module stix.utils), 91
- SimpleMarkingStructure (class in stix.extensions.marking.simple\_marking), 61
- SnortTestMechanism (class in stix.extensions.test\_mechanism.snort\_test\_mechanism), 62
- sorted (stix.common.structured\_text.StructuredTextList attribute), 27
- Statement (class in stix.common.statement), 25
- stix.base (module), 17
- stix.campaign (module), 19
- stix.coa (module), 51
- stix.coa.objective (module), 52
- stix.common (module), 21
- stix.common.activity (module), 21
- stix.common.confidence (module), 21
- stix.common.datetimewithprecision (module), 22
- stix.common.identity (module), 22
- stix.common.information\_source (module), 23
- stix.common.kill\_chains (module), 23
- stix.common.related (module), 24
- stix.common.statement (module), 25
- stix.common.structured\_text (module), 26
- stix.common.tools (module), 28
- stix.common.vocabs (module), 28
- stix.core.stix\_header (module), 46
- stix.core.stix\_package (module), 47
- stix.core.ttps (module), 50
- stix.data\_marking (module), 18
- stix.exploit\_target (module), 53
- stix.exploit\_target.configuration (module), 55
- stix.exploit\_target.vulnerability (module), 56
- stix.exploit\_target.weakness (module), 57
- stix.extensions.identity.ciq\_identity\_3\_0 (module), 58
- stix.extensions.malware.maec\_4\_1\_malware (module), 60
- stix.extensions.marking.simple\_marking (module), 61
- stix.extensions.marking.terms\_of\_use\_marking (module), 61
- stix.extensions.marking.tlp (module), 61
- stix.extensions.structured\_coa.generic\_structured\_coa (module), 61
- stix.extensions.test\_mechanism.generic\_test\_mechanism (module), 62
- stix.extensions.test\_mechanism.open\_ioc\_2010\_test\_mechanism (module), 62
- stix.extensions.test\_mechanism.snort\_test\_mechanism (module), 62
- stix.extensions.test\_mechanism.yara\_test\_mechanism (module), 63
- stix.incident (module), 63
- stix.incident.affected\_asset (module), 66
- stix.incident.coa (module), 66

- stix.incident.contributors (module), 67  
 stix.incident.direct\_impact\_summary (module), 67  
 stix.incident.external\_id (module), 67  
 stix.incident.history (module), 67  
 stix.incident.impact\_assessment (module), 68  
 stix.incident.indirect\_impact\_summary (module), 68  
 stix.incident.loss\_estimation (module), 68  
 stix.incident.property\_affected (module), 68  
 stix.incident.time (module), 69  
 stix.incident.total\_loss\_estimation (module), 69  
 stix.indicator.indicator (module), 69  
 stix.indicator.sightings (module), 78  
 stix.indicator.test\_mechanism (module), 79  
 stix.indicator.valid\_time (module), 79  
 stix.report (module), 80  
 stix.report.header (module), 81  
 stix.threat\_actor (module), 82  
 stix.ttp (module), 84  
 stix.ttp.attack\_pattern (module), 86  
 stix.ttp.behavior (module), 87  
 stix.ttp.exploit (module), 87  
 stix.ttp.exploit\_targets (module), 88  
 stix.ttp.infrastructure (module), 88  
 stix.ttp.malware\_instance (module), 89  
 stix.ttp.related\_ttps (module), 90  
 stix.ttp.resource (module), 90  
 stix.ttp.victim\_targeting (module), 90  
 stix.utils (module), 90  
 stix.utils.dates (module), 91  
 stix.utils.nsparser (module), 92  
 stix.utils.parser (module), 95  
 STIXCIQIdentity3\_0 (class in stix.extensions.identity.ciq\_identity\_3\_0), 58  
 STIXHeader (class in stix.core.stix\_header), 46  
 STIXPackage (class in stix.core.stix\_package), 48  
 strip\_cdata() (in module stix.utils), 91  
 StructuredText (class in stix.common.structured\_text), 26  
 StructuredTextList (class in stix.common.structured\_text), 26  
 structuring\_format (stix.common.structured\_text.StructuredText attribute), 26  
 SubDivisionName (class in stix.extensions.identity.ciq\_identity\_3\_0), 60  
 SuggestedCOAs (class in stix.indicator.indicator), 77  
 SystemType (in module stix.common.vocabs), 46  
 SystemType\_1\_0 (class in stix.common.vocabs), 43
- ## T
- TERM\_ACCELERATION (stix.common.vocabs.AvailabilityLossType\_1\_1\_1 attribute), 31  
 TERM\_ACCELERATION (stix.common.vocabs.AvailabilityLossType\_1\_1\_1 attribute), 32  
 TERM\_ACCESS\_READER (stix.common.vocabs.AssetType\_1\_0 attribute), 28  
 TERM\_ACCOUNT\_TAKEOVER (stix.common.vocabs.IntendedEffect\_1\_0 attribute), 36  
 TERM\_ACCOUNTABILITY (stix.common.vocabs.LossProperty\_1\_0 attribute), 38  
 TERM\_ADMINISTRATOR (stix.common.vocabs.AssetType\_1\_0 attribute), 28  
 TERM\_ADVANTAGE (stix.common.vocabs.IntendedEffect\_1\_0 attribute), 36  
 TERM\_ADVANTAGE\_ECONOMIC (stix.common.vocabs.IntendedEffect\_1\_0 attribute), 36  
 TERM\_ADVANTAGE\_MILITARY (stix.common.vocabs.IntendedEffect\_1\_0 attribute), 37  
 TERM\_ADVANTAGE\_POLITICAL (stix.common.vocabs.IntendedEffect\_1\_0 attribute), 37  
 TERM\_ADWARE (stix.common.vocabs.MalwareType\_1\_0 attribute), 38  
 TERM\_AGENT\_DISCLOSURE (stix.common.vocabs.DiscoveryMethod\_1\_0 attribute), 33  
 TERM\_AGENT\_DISCLOSURE (stix.common.vocabs.DiscoveryMethod\_2\_0 attribute), 33  
 TERM\_AGGREGATOR (stix.common.vocabs.InformationSourceRole\_1\_0 attribute), 36  
 TERM\_ANONYMIZATION (stix.common.vocabs.AttackerInfrastructureType\_1\_0 attribute), 30  
 TERM\_ANONYMIZATION (stix.common.vocabs.IndicatorType\_1\_0 attribute), 35  
 TERM\_ANONYMIZATION (stix.common.vocabs.IndicatorType\_1\_1 attribute), 36  
 TERM\_ANONYMIZATION\_PROXY (stix.common.vocabs.AttackerInfrastructureType\_1\_0 attribute), 30  
 TERM\_ANONYMIZATION\_TOR\_NETWORK (stix.common.vocabs.AttackerInfrastructureType\_1\_0 attribute), 30  
 TERM\_ANONYMIZATION\_VPN (stix.common.vocabs.AttackerInfrastructureType\_1\_0 attribute), 30

- attribute), 31
- TERM\_ANTIVIRUS (stix.common.vocabs.DiscoveryMethod\_1\_0 attribute), 28
- attribute), 33
- TERM\_ANTIVIRUS (stix.common.vocabs.DiscoveryMethod\_2\_0 attribute), 35
- attribute), 33
- TERM\_APPLICATION\_SCANNER (stix.common.vocabs.AttackerToolType\_1\_0 attribute), 31
- TERM\_ASPIRANT (stix.common.vocabs.ThreatActorSophistication\_1\_0 attribute), 29
- attribute), 43
- TERM\_ATM (stix.common.vocabs.AssetType\_1\_0 attribute), 28
- TERM\_ATTACK\_PATTERN\_CHARACTERIZATION (stix.common.vocabs.PackageIntent\_1\_0 attribute), 40
- TERM\_ATTACK\_PATTERN\_CHARACTERIZATION (stix.common.vocabs.ReportIntent\_1\_0 attribute), 42
- TERM\_AUDIT (stix.common.vocabs.DiscoveryMethod\_1\_0 attribute), 33
- TERM\_AUDIT (stix.common.vocabs.DiscoveryMethod\_2\_0 attribute), 33
- TERM\_AUDITOR (stix.common.vocabs.AssetType\_1\_0 attribute), 28
- TERM\_AUTH\_TOKEN (stix.common.vocabs.AssetType\_1\_0 attribute), 28
- TERM\_AUTHENTICATION\_COOKIES (stix.common.vocabs.InformationType\_1\_0 attribute), 36
- TERM\_AUTOMATED\_TRANSFER\_SCRIPTS (stix.common.vocabs.MalwareType\_1\_0 attribute), 38
- TERM\_AVAILABILITY (stix.common.vocabs.LossProperty\_1\_0 attribute), 38
- TERM\_BACKUP (stix.common.vocabs.AssetType\_1\_0 attribute), 28
- TERM\_BOT (stix.common.vocabs.MalwareType\_1\_0 attribute), 38
- TERM\_BOT\_CREDENTIAL\_THEFT (stix.common.vocabs.MalwareType\_1\_0 attribute), 38
- TERM\_BOT\_DDOS (stix.common.vocabs.MalwareType\_1\_0 attribute), 38
- TERM\_BOT\_LOADER (stix.common.vocabs.MalwareType\_1\_0 attribute), 38
- TERM\_BOT\_SPAM (stix.common.vocabs.MalwareType\_1\_0 attribute), 38
- TERM\_BRAND\_DAMAGE (stix.common.vocabs.IntendedEffect\_1\_0 attribute), 37
- TERM\_BRAND\_OR\_IMAGE\_DEGRADATION (stix.common.vocabs.IncidentEffect\_1\_0 attribute), 34
- TERM\_BROADBAND (stix.common.vocabs.AssetType\_1\_0 attribute), 28
- TERM\_C2 (stix.common.vocabs.IndicatorType\_1\_0 attribute), 35
- TERM\_C2 (stix.common.vocabs.IndicatorType\_1\_1 attribute), 36
- TERM\_CALL\_CENTER (stix.common.vocabs.AssetType\_1\_0 attribute), 29
- TERM\_CAMERA (stix.common.vocabs.AssetType\_1\_0 attribute), 29
- TERM\_CAMPAIN\_CHARACTERIZATION (stix.common.vocabs.PackageIntent\_1\_0 attribute), 40
- TERM\_CAMPAIN\_CHARACTERIZATION (stix.common.vocabs.ReportIntent\_1\_0 attribute), 42
- TERM\_CASHIER (stix.common.vocabs.AssetType\_1\_0 attribute), 29
- TERM\_CATASTROPHIC (stix.common.vocabs.ImpactQualification\_1\_0 attribute), 34
- TERM\_CLOSED (stix.common.vocabs.IncidentStatus\_1\_0 attribute), 35
- TERM\_COLLECTIVE\_THREAT\_INTELLIGENCE (stix.common.vocabs.PackageIntent\_1\_0 attribute), 40
- TERM\_COLLECTIVE\_THREAT\_INTELLIGENCE (stix.common.vocabs.ReportIntent\_1\_0 attribute), 42
- TERM\_COLOCATED (stix.common.vocabs.LocationClass\_1\_0 attribute), 37
- TERM\_COMANAGEMENT (stix.common.vocabs.ManagementClass\_1\_0 attribute), 38
- TERM\_COMMUNICATIONS (stix.common.vocabs.AttackerInfrastructureType\_1\_0 attribute), 31
- TERM\_COMMUNICATIONS\_BLOGS (stix.common.vocabs.AttackerInfrastructureType\_1\_0 attribute), 31
- TERM\_COMMUNICATIONS\_FORUMS (stix.common.vocabs.AttackerInfrastructureType\_1\_0 attribute), 31
- TERM\_COMMUNICATIONS\_INTERNET\_RELAY\_CHAT (stix.common.vocabs.AttackerInfrastructureType\_1\_0 attribute), 31
- TERM\_COMMUNICATIONS\_MICROBLOGS (stix.common.vocabs.AttackerInfrastructureType\_1\_0 attribute), 31
- TERM\_COMMUNICATIONS\_MOBILE\_COMMUNICATIONS (stix.common.vocabs.AttackerInfrastructureType\_1\_0 attribute), 31
- TERM\_COMMUNICATIONS\_SOCIAL\_NETWORKS



- (stix.common.vocabs.CourseOfActionType\_1\_0 attribute), 32
- TERM\_DIRECTORY (stix.common.vocabs.AssetType\_1\_0 attribute), 29
- TERM\_DISGRUNTLED\_CUSTOMER\_OR\_USER (stix.common.vocabs.ThreatActorType\_1\_0 attribute), 44
- TERM\_DISK\_DRIVE (stix.common.vocabs.AssetType\_1\_0 attribute), 29
- TERM\_DISK\_MEDIA (stix.common.vocabs.AssetType\_1\_0 attribute), 29
- TERM\_DISRUPTION (stix.common.vocabs.IntendedEffect\_1\_0 attribute), 37
- TERM\_DISRUPTION\_OF\_SERVICE\_OR\_OPERATION (stix.common.vocabs.IncidentEffect\_1\_0 attribute), 35
- TERM\_DISTRACTING (stix.common.vocabs.ImpactQualifier\_1\_0 attribute), 34
- TERM\_DNS (stix.common.vocabs.AssetType\_1\_0 attribute), 29
- TERM\_DOCUMENTS (stix.common.vocabs.AssetType\_1\_0 attribute), 29
- TERM\_DOMAIN\_REGISTRATION (stix.common.vocabs.AttackerInfrastructureType\_1\_0 attribute), 31
- TERM\_DOMAIN\_REGISTRATION\_DYNAMIC\_DNS\_SERVICE (stix.common.vocabs.AttackerInfrastructureType\_1\_0 attribute), 31
- TERM\_DOMAIN\_REGISTRATION\_LEGITIMATE\_DOMAIN\_REGISTRATION\_SERVICES (stix.common.vocabs.AttackerInfrastructureType\_1\_0 attribute), 31
- TERM\_DOMAIN\_REGISTRATION\_MALICIOUS\_DOMAIN\_REGISTRATION\_SERVICES (stix.common.vocabs.AttackerInfrastructureType\_1\_0 attribute), 31
- TERM\_DOMAIN\_REGISTRATION\_TOPLEVEL\_DOMAIN\_REGISTRATION\_SERVICES (stix.common.vocabs.AttackerInfrastructureType\_1\_0 attribute), 31
- TERM\_DOMAIN\_WATCHLIST (stix.common.vocabs.IndicatorType\_1\_0 attribute), 35
- TERM\_DOMAIN\_WATCHLIST (stix.common.vocabs.IndicatorType\_1\_1 attribute), 36
- TERM\_DOS\_OR\_DDOS (stix.common.vocabs.MalwareType\_1\_0 attribute), 38
- TERM\_DOS\_OR\_DDOS\_PARTICIPATORY (stix.common.vocabs.MalwareType\_1\_0 attribute), 38
- TERM\_DOS\_OR\_DDOS\_SCRIPT (stix.common.vocabs.MalwareType\_1\_0 attribute), 38
- TERM\_DOS\_OR\_DDOS\_STRESS\_TEST\_TOOLS (stix.common.vocabs.MalwareType\_1\_0 attribute), 38
- TERM\_ECRIME\_ACTOR\_CREDENTIAL\_THEFT\_BOTNET\_OPERATOR (stix.common.vocabs.ThreatActorType\_1\_0 attribute), 44
- TERM\_ECRIME\_ACTOR\_CREDENTIAL\_THEFT\_BOTNET\_SERVICE (stix.common.vocabs.ThreatActorType\_1\_0 attribute), 44
- TERM\_ECRIME\_ACTOR\_MALWARE\_DEVELOPER (stix.common.vocabs.ThreatActorType\_1\_0 attribute), 44
- TERM\_ECRIME\_ACTOR\_MONEY\_LAUNDERING\_NETWORK (stix.common.vocabs.ThreatActorType\_1\_0 attribute), 44
- TERM\_ECRIME\_ACTOR\_ORGANIZED\_CRIME\_ACTOR (stix.common.vocabs.ThreatActorType\_1\_0 attribute), 44
- TERM\_ECRIME\_ACTOR\_SPAM\_SERVICE (stix.common.vocabs.ThreatActorType\_1\_0 attribute), 44
- TERM\_ECRIME\_ACTOR\_TRAFFIC\_SERVICE (stix.common.vocabs.ThreatActorType\_1\_0 attribute), 44
- TERM\_ECRIME\_ACTOR\_UNDERGROUND\_CALL\_SERVICE (stix.common.vocabs.ThreatActorType\_1\_0 attribute), 44
- TERM\_EGO (stix.common.vocabs.Motivation\_1\_0 attribute), 38
- TERM\_EGO (stix.common.vocabs.Motivation\_1\_0\_1 attribute), 39
- TERM\_EGO (stix.common.vocabs.Motivation\_1\_1 attribute), 39
- TERM\_ELECTRONIC\_PAYMENT\_METHODS (stix.common.vocabs.AttackerInfrastructureType\_1\_0 attribute), 31
- TERM\_EMPLOYEEOWNED (stix.common.vocabs.OwnershipClass\_1\_0 attribute), 40
- TERM\_ENDUSER (stix.common.vocabs.AssetType\_1\_0 attribute), 29
- TERM\_ENTERPRISE\_SYSTEMS (stix.common.vocabs.SystemType\_1\_0 attribute), 43
- TERM\_ENTERPRISE\_SYSTEMS\_APPLICATION\_LAYER (stix.common.vocabs.SystemType\_1\_0 attribute), 43
- TERM\_ENTERPRISE\_SYSTEMS\_DATABASE\_LAYER (stix.common.vocabs.SystemType\_1\_0 attribute), 43
- TERM\_ENTERPRISE\_SYSTEMS\_ENTERPRISE\_TECHNOLOGIES\_APPLICATION\_LAYER (stix.common.vocabs.SystemType\_1\_0 attribute), 43

TERM_ENTERPRISE_SYSTEMS_NETWORK_SYSTEMS (stix.common.vocabs.SystemType_1_0 tribute), 43	attribute), 35	TERM_FILE_HASH_WATCHLIST (stix.common.vocabs.IndicatorType_1_1 tribute), 36
TERM_ENTERPRISE_SYSTEMS_NETWORKING_DEVICES (stix.common.vocabs.SystemType_1_0 tribute), 43	at-	TERM_FINANCE (stix.common.vocabs.AssetType_1_0 tribute), 29
TERM_ENTERPRISE_SYSTEMS_VOIP (stix.common.vocabs.SystemType_1_0 tribute), 43	at-	TERM_FINANCIAL_AUDIT (stix.common.vocabs.DiscoveryMethod_1_0 tribute), 33
TERM_ENTERPRISE_SYSTEMS_WEB_LAYER (stix.common.vocabs.SystemType_1_0 tribute), 43	at-	TERM_FINANCIAL_AUDIT (stix.common.vocabs.DiscoveryMethod_2_0 tribute), 33
TERM_ERADICATION (stix.common.vocabs.CourseOfActionType_1_0 tribute), 32		TERM_FINANCIAL_LOSS (stix.common.vocabs.IncidentEffect_1_0 tribute), 35
TERM_EXECUTIVE (stix.common.vocabs.AssetType_1_0 tribute), 29		TERM_FINANCIAL_OR_ECONOMIC (stix.common.vocabs.Motivation_1_0 tribute), 38
TERM_EXERCISEORNETWORK_DEFENSE_TESTING (stix.common.vocabs.IncidentCategory_1_0 tribute), 34		TERM_FINANCIAL_OR_ECONOMIC (stix.common.vocabs.Motivation_1_0_1 tribute), 39
TERM_EXFILTRATION (stix.common.vocabs.IndicatorType_1_0 tribute), 35		TERM_FINANCIAL_OR_ECONOMIC (stix.common.vocabs.Motivation_1_1 tribute), 39
TERM_EXFILTRATION (stix.common.vocabs.IndicatorType_1_1 tribute), 36		TERM_FINANCIAL_RESOURCES (stix.common.vocabs.PlanningAndOperationalSupport_1_0 tribute), 41
TERM_EXPERT (stix.common.vocabs.ThreatActorSophistication_1_0 tribute), 43		TERM_FINANCIAL_RESOURCES (stix.common.vocabs.PlanningAndOperationalSupport_1_0_1 tribute), 41
TERM_EXPLOIT_CHARACTERIZATION (stix.common.vocabs.PackageIntent_1_0 tribute), 40		TERM_FINANCIAL_RESOURCES_ACADEMIC (stix.common.vocabs.PlanningAndOperationalSupport_1_0 tribute), 41
TERM_EXPLOIT_CHARACTERIZATION (stix.common.vocabs.ReportIntent_1_0 tribute), 42	at-	TERM_FINANCIAL_RESOURCES_ACADEMIC (stix.common.vocabs.PlanningAndOperationalSupport_1_0_1 tribute), 41
TERM_EXPLOIT_KITS (stix.common.vocabs.MalwareType_1_0 tribute), 38		TERM_FINANCIAL_RESOURCES_COMMERCIAL (stix.common.vocabs.PlanningAndOperationalSupport_1_0 tribute), 41
TERM_EXPOSURE (stix.common.vocabs.IntendedEffect_1_0 tribute), 37		TERM_FINANCIAL_RESOURCES_COMMERCIAL (stix.common.vocabs.PlanningAndOperationalSupport_1_0_1 tribute), 41
TERM_EXTERNAL_FRAUD_DETECTION (stix.common.vocabs.DiscoveryMethod_2_0 tribute), 33		TERM_FINANCIAL_RESOURCES_GOVERNMENT (stix.common.vocabs.PlanningAndOperationalSupport_1_0 tribute), 41
TERM_EXTERNALLYLOCATED (stix.common.vocabs.LocationClass_1_0 tribute), 37		TERM_FINANCIAL_RESOURCES_GOVERNMENT (stix.common.vocabs.PlanningAndOperationalSupport_1_0_1 tribute), 41
TERM_EXTERNALLYMANAGEMENT (stix.common.vocabs.ManagementClass_1_0 tribute), 38		TERM_FINANCIAL_RESOURCES_HACKTIVIST_OR_GRASSROOT (stix.common.vocabs.PlanningAndOperationalSupport_1_0 tribute), 41
TERM_EXTORTION (stix.common.vocabs.IntendedEffect_1_0 tribute), 37		TERM_FINANCIAL_RESOURCES_HACKTIVIST_OR_GRASSROOT (stix.common.vocabs.PlanningAndOperationalSupport_1_0_1 tribute), 41
TERM_FILE (stix.common.vocabs.AssetType_1_0 tribute), 29	at-	
TERM_FILE_HASH_WATCHLIST (stix.common.vocabs.IndicatorType_1_0 tribute), 35		



TERM_FINANCIAL_RESOURCES_NONATTRIBUTABLE	(stix.common.vocabs.PlanningAndOperationalSupport_1_0 attribute), 41	TERM_FINANCIAL_RESOURCES_NONATTRIBUTABLE	(stix.common.vocabs.PlanningAndOperationalSupport_1_0 attribute), 41
TERM_FINANCIAL_RESOURCES_NONATTRIBUTABLE	(stix.common.vocabs.PlanningAndOperationalSupport_1_0 attribute), 41	TERM_FINANCIAL_RESOURCES_NONATTRIBUTABLE	(stix.common.vocabs.PlanningAndOperationalSupport_1_0 attribute), 41
TERM_FIREWALL	(stix.common.vocabs.AssetType_1_0 attribute), 29	TERM_HOSTING	(stix.common.vocabs.AttackerInfrastructureType_1_0 attribute), 31
TERM_FLASH_DRIVE	(stix.common.vocabs.AssetType_1_0 attribute), 29	TERM_HOSTING_BULLETPROOF_OR_ROGUE_HOSTING	(stix.common.vocabs.AttackerInfrastructureType_1_0 attribute), 31
TERM_FORMER_EMPLOYEE	(stix.common.vocabs.AssetType_1_0 attribute), 29	TERM_HOSTING_CLOUD_HOSTING	(stix.common.vocabs.AttackerInfrastructureType_1_0 attribute), 31
TERM_FRAUD	(stix.common.vocabs.IntendedEffect_1_0 attribute), 37	TERM_HOSTING_COMPROMISED_SERVER	(stix.common.vocabs.AttackerInfrastructureType_1_0 attribute), 31
TERM_FRAUD_DETECTION	(stix.common.vocabs.DiscoveryMethod_1_0 attribute), 33	TERM_HOSTING_FAST_FLUX_BOTNET_HOSTING	(stix.common.vocabs.AttackerInfrastructureType_1_0 attribute), 31
TERM_FUTURE	(stix.common.vocabs.CampaignStatus_1_0 attribute), 32	TERM_HOSTING_LEGITIMATE_HOSTING	(stix.common.vocabs.AttackerInfrastructureType_1_0 attribute), 31
TERM_GAS_TERMINAL	(stix.common.vocabs.AssetType_1_0 attribute), 29	TERM_HOURS	(stix.common.vocabs.LossDuration_1_0 attribute), 37
TERM_GUARD	(stix.common.vocabs.AssetType_1_0 attribute), 29	TERM_HSM	(stix.common.vocabs.AssetType_1_0 attribute), 29
TERM_HACKER	(stix.common.vocabs.ThreatActorType_1_0 attribute), 44	TERM_HUMAN_RESOURCES	(stix.common.vocabs.AssetType_1_0 attribute), 29
TERM_HACKER_BLACK_HAT	(stix.common.vocabs.ThreatActorType_1_0 attribute), 44	TERM_ICS_CONTROL	(stix.common.vocabs.IntendedEffect_1_0 attribute), 37
TERM_HACKER_GRAY_HAT	(stix.common.vocabs.ThreatActorType_1_0 attribute), 44	TERM_IDEOLOGICAL	(stix.common.vocabs.Motivation_1_0 attribute), 39
TERM_HACKER_WHITE_HAT	(stix.common.vocabs.ThreatActorType_1_0 attribute), 44	TERM_IDEOLOGICAL	(stix.common.vocabs.Motivation_1_0_1 attribute), 39
TERM_HACKTIVIST	(stix.common.vocabs.ThreatActorType_1_0 attribute), 44	TERM_IDEOLOGICAL	(stix.common.vocabs.Motivation_1_1 attribute), 39
TERM_HARASSMENT	(stix.common.vocabs.IntendedEffect_1_0 attribute), 37	TERM_IDEOLOGICAL_RELIGIOUS	(stix.common.vocabs.Motivation_1_0_1 attribute), 39
TERM_HARDENING	(stix.common.vocabs.CourseOfAction_1_0 attribute), 32	TERM_IDEOLOGICAL_ANTI_CORRUPTION	(stix.common.vocabs.Motivation_1_0_1 attribute), 39
TERM_HELPDESK	(stix.common.vocabs.AssetType_1_0 attribute), 29	TERM_IDEOLOGICAL_ANTI_ESTABLISHMENT	(stix.common.vocabs.Motivation_1_0_1 attribute), 39
TERM_HIGH	(stix.common.vocabs.HighMediumLow_1_0 attribute), 34	TERM_IDEOLOGICAL_ANTICORRUPTION	(stix.common.vocabs.Motivation_1_0 attribute), 39
TERM_HIPS	(stix.common.vocabs.DiscoveryMethod_1_0 attribute), 33		
TERM_HIPS	(stix.common.vocabs.DiscoveryMethod_2_0 attribute), 33		
TERM_HISTORIC	(stix.common.vocabs.CampaignStatus_1_0 attribute), 32		

TERM_IDEOLOGICAL_ANTICORRUPTION (stix.common.vocabs.Motivation_1_1 tribute), 39	at-	TERM_IDEOLOGICAL_SECURITY_AWARENESS (stix.common.vocabs.Motivation_1_0_1 tribute), 39	at-
TERM_IDEOLOGICAL_ANTIESTABLISHMENT (stix.common.vocabs.Motivation_1_1 tribute), 39	at-	TERM_IDEOLOGICAL_SECURITY_AWARENESS (stix.common.vocabs.Motivation_1_1 tribute), 40	at-
TERM_IDEOLOGICAL_ANTIESTABLISHMENT (stix.common.vocabs.Motivation_1_0 tribute), 39	at-	TERM_IDS (stix.common.vocabs.AssetType_1_0 attribute), 29	
TERM_IDEOLOGICAL_ENVIRONMENTAL (stix.common.vocabs.Motivation_1_0 tribute), 39	at-	TERM_IMEI_WATCHLIST (stix.common.vocabs.IndicatorType_1_1 attribute), 36	
TERM_IDEOLOGICAL_ENVIRONMENTAL (stix.common.vocabs.Motivation_1_0_1 attribute), 39		TERM_IMPROPER_USAGE (stix.common.vocabs.IncidentCategory_1_0 attribute), 34	
TERM_IDEOLOGICAL_ENVIRONMENTAL (stix.common.vocabs.Motivation_1_1 tribute), 39	at-	TERM_IMSI_WATCHLIST (stix.common.vocabs.IndicatorType_1_1 attribute), 36	
TERM_IDEOLOGICAL_ETHNIC_NATIONALIST (stix.common.vocabs.Motivation_1_0 tribute), 39	at-	TERM_INCIDENT (stix.common.vocabs.PackageIntent_1_0 attribute), 40	
TERM_IDEOLOGICAL_ETHNIC_NATIONALIST (stix.common.vocabs.Motivation_1_0_1 tribute), 39	at-	TERM_INCIDENT (stix.common.vocabs.ReportIntent_1_0 attribute), 42	
TERM_IDEOLOGICAL_ETHNIC_NATIONALIST (stix.common.vocabs.Motivation_1_1 tribute), 39	at-	TERM_INCIDENT_REPORTED (stix.common.vocabs.IncidentStatus_1_0 attribute), 35	
TERM_IDEOLOGICAL_ETHNIC_NATIONALIST (stix.common.vocabs.Motivation_1_0 tribute), 39	at-	TERM_INCIDENT_RESPONSE (stix.common.vocabs.DiscoveryMethod_1_0 attribute), 33	
TERM_IDEOLOGICAL_HUMAN_RIGHTS (stix.common.vocabs.Motivation_1_0 tribute), 39	at-	TERM_INCIDENT_RESPONSE (stix.common.vocabs.DiscoveryMethod_2_0 attribute), 33	
TERM_IDEOLOGICAL_HUMAN_RIGHTS (stix.common.vocabs.Motivation_1_0_1 attribute), 39		TERM_INDICATORS (stix.common.vocabs.PackageIntent_1_0 attribute), 40	
TERM_IDEOLOGICAL_HUMAN_RIGHTS (stix.common.vocabs.Motivation_1_1 tribute), 40	at-	TERM_INDICATORS (stix.common.vocabs.ReportIntent_1_0 attribute), 42	
TERM_IDEOLOGICAL_INFORMATION_FREEDOM (stix.common.vocabs.Motivation_1_0 tribute), 39	at-	TERM_INDICATORS_ENDPOINT_CHARACTERISTICS (stix.common.vocabs.PackageIntent_1_0 tribute), 40	at-
TERM_IDEOLOGICAL_INFORMATION_FREEDOM (stix.common.vocabs.Motivation_1_0_1 tribute), 39	at-	TERM_INDICATORS_ENDPOINT_CHARACTERISTICS (stix.common.vocabs.ReportIntent_1_0 tribute), 42	at-
TERM_IDEOLOGICAL_INFORMATION_FREEDOM (stix.common.vocabs.Motivation_1_1 tribute), 40	at-	TERM_INDICATORS_MALWARE_ARTIFACTS (stix.common.vocabs.PackageIntent_1_0 tribute), 40	
TERM_IDEOLOGICAL_RELIGIOUS (stix.common.vocabs.Motivation_1_0 tribute), 39	at-	TERM_INDICATORS_MALWARE_ARTIFACTS (stix.common.vocabs.ReportIntent_1_0 tribute), 42	at-
TERM_IDEOLOGICAL_RELIGIOUS (stix.common.vocabs.Motivation_1_1 tribute), 40	at-	TERM_INDICATORS_NETWORK_ACTIVITY (stix.common.vocabs.PackageIntent_1_0 tribute), 40	
TERM_IDEOLOGICAL_SECURITY_AWARENESS (stix.common.vocabs.Motivation_1_0 tribute), 39	at-	TERM_INDICATORS_NETWORK_ACTIVITY (stix.common.vocabs.ReportIntent_1_0 tribute), 42	at-
		TERM_INDICATORS_PHISHING (stix.common.vocabs.PackageIntent_1_0 tribute), 42	

- attribute), 40
- TERM\_INDICATORS\_PHISHING (stix.common.vocabs.ReportIntent\_1\_0 attribute), 42
- TERM\_INDICATORS\_WATCHLIST (stix.common.vocabs.PackageIntent\_1\_0 attribute), 40
- TERM\_INDICATORS\_WATCHLIST (stix.common.vocabs.ReportIntent\_1\_0 attribute), 42
- TERM\_INDUSTRIAL\_CONTROL\_SYSTEMS (stix.common.vocabs.SystemType\_1\_0 attribute), 43
- TERM\_INDUSTRIAL\_CONTROL\_SYSTEMS\_EQUIPMENT\_UNDER\_CONTROL (stix.common.vocabs.SystemType\_1\_0 attribute), 43
- TERM\_INDUSTRIAL\_CONTROL\_SYSTEMS\_OPERATIONS\_MANAGEMENT (stix.common.vocabs.SystemType\_1\_0 attribute), 43
- TERM\_INDUSTRIAL\_CONTROL\_SYSTEMS\_SAFETY\_PROTECTION\_AND\_LOCAL\_CONTROL (stix.common.vocabs.SystemType\_1\_0 attribute), 43
- TERM\_INDUSTRIAL\_CONTROL\_SYSTEMS\_SUPERVISORY\_CONTROL (stix.common.vocabs.SystemType\_1\_0 attribute), 43
- TERM\_INFORMATION\_ASSETS (stix.common.vocabs.InformationType\_1\_0 attribute), 36
- TERM\_INFORMATION\_ASSETS\_CORPORATE\_EMPLOYEE\_INFORMATION (stix.common.vocabs.InformationType\_1\_0 attribute), 36
- TERM\_INFORMATION\_ASSETS\_CUSTOMER\_PII (stix.common.vocabs.InformationType\_1\_0 attribute), 36
- TERM\_INFORMATION\_ASSETS\_EMAIL\_LISTS\_OR\_ARCHIVES (stix.common.vocabs.InformationType\_1\_0 attribute), 36
- TERM\_INFORMATION\_ASSETS\_FINANCIAL\_DATA (stix.common.vocabs.InformationType\_1\_0 attribute), 36
- TERM\_INFORMATION\_ASSETS\_INTELLECTUAL\_PROPERTY (stix.common.vocabs.InformationType\_1\_0 attribute), 36
- TERM\_INFORMATION\_ASSETS\_MOBILE\_PHONE\_CONTACTS (stix.common.vocabs.InformationType\_1\_0 attribute), 36
- TERM\_INFORMATION\_ASSETS\_USER\_CREDENTIALS (stix.common.vocabs.InformationType\_1\_0 attribute), 36
- TERM\_INITIAL\_AUTHOR (stix.common.vocabs.InformationSourceRole\_1\_0 attribute), 36
- TERM\_INNOVATOR (stix.common.vocabs.ThreatActorSophistication\_1\_0 attribute), 43
- TERM\_INSIDER\_THREAT (stix.common.vocabs.ThreatActorType\_1\_0 attribute), 44
- TERM\_INSIGNIFICANT (stix.common.vocabs.ImpactQualification\_1\_0 attribute), 34
- TERM\_INTEGRITY (stix.common.vocabs.LossProperty\_1\_0 attribute), 38
- TERM\_INTERNAL\_BLOCKING (stix.common.vocabs.CourseOfActionType\_1\_0 attribute), 32
- TERM\_INTERNAL\_FRAUD\_DETECTION (stix.common.vocabs.DiscoveryMethod\_2\_0 attribute), 33
- TERM INTERNALLYLOCATED (stix.common.vocabs.LocationClass\_1\_0 attribute), 33
- TERM INTERNALLYMANAGED (stix.common.vocabs.ManagementClass\_1\_0 attribute), 33
- TERM INTERNALLYOWNED (stix.common.vocabs.OwnershipClass\_1\_0 attribute), 33
- TERM\_INTERRUPTION (stix.common.vocabs.AvailabilityLossType\_1\_0 attribute), 31
- TERM\_INTERRUPTION (stix.common.vocabs.AvailabilityLossType\_1\_1\_1 attribute), 31
- TERM INVESTIGATION (stix.common.vocabs.IncidentCategory\_1\_0 attribute), 34
- TERM\_IP\_WATCHLIST (stix.common.vocabs.IndicatorType\_1\_0 attribute), 35
- TERM\_IP\_WATCHLIST (stix.common.vocabs.IndicatorType\_1\_1 attribute), 36
- TERM\_IT\_AUDIT (stix.common.vocabs.DiscoveryMethod\_1\_0 attribute), 33
- TERM\_IT\_AUDIT (stix.common.vocabs.DiscoveryMethod\_2\_0 attribute), 33
- TERM\_KIOSK (stix.common.vocabs.AssetType\_1\_0 attribute), 29
- TERM\_LAN (stix.common.vocabs.AssetType\_1\_0 attribute), 29
- TERM LAPTOP (stix.common.vocabs.AssetType\_1\_0 attribute), 29
- TERM\_LAW\_ENFORCEMENT (stix.common.vocabs.DiscoveryMethod\_1\_0 attribute), 33
- TERM\_LAW\_ENFORCEMENT (stix.common.vocabs.DiscoveryMethod\_2\_0 attribute), 33

TERM\_LOG (stix.common.vocabs.AssetType\_1\_0 attribute), 29  
 TERM\_LOG\_REVIEW (stix.common.vocabs.DiscoveryMethod\_1\_0 (stix.common.vocabs.IndicatorType\_1\_1 attribute), 33  
 TERM\_LOG\_REVIEW (stix.common.vocabs.DiscoveryMethod\_1\_0 attribute), 33  
 TERM\_LOGICAL\_ACCESS\_RESTRICTIONS (stix.common.vocabs.CourseOfActionType\_1\_0 attribute), 32  
 TERM\_LOGIN\_NAME (stix.common.vocabs.IndicatorType\_1\_1 attribute), 36  
 TERM\_LOSS (stix.common.vocabs.AvailabilityLossType\_1\_0 attribute), 31  
 TERM\_LOSS (stix.common.vocabs.AvailabilityLossType\_1\_0 attribute), 32  
 TERM\_LOSS\_OF\_COMPETITIVE\_ADVANTAGE (stix.common.vocabs.IncidentEffect\_1\_0 attribute), 35  
 TERM\_LOSS\_OF\_COMPETITIVE\_ADVANTAGE\_ECONOMIC (stix.common.vocabs.IncidentEffect\_1\_0 attribute), 35  
 TERM\_LOSS\_OF\_COMPETITIVE\_ADVANTAGE\_MILITARY (stix.common.vocabs.IncidentEffect\_1\_0 attribute), 35  
 TERM\_LOSS\_OF\_COMPETITIVE\_ADVANTAGE\_POLITICAL (stix.common.vocabs.IncidentEffect\_1\_0 attribute), 35  
 TERM\_LOSS\_OF\_CONFIDENTIAL\_OR\_PROPRIETARY\_INFORMATION\_OR\_INTELLECTUAL\_PROPERTY (stix.common.vocabs.IncidentEffect\_1\_0 attribute), 35  
 TERM\_LOW (stix.common.vocabs.HighMediumLow\_1\_0 attribute), 34  
 TERM\_MAIL (stix.common.vocabs.AssetType\_1\_0 attribute), 29  
 TERM\_MAINFRAME (stix.common.vocabs.AssetType\_1\_0 attribute), 29  
 TERM\_MAINTENANCE (stix.common.vocabs.AssetType\_1\_0 attribute), 29  
 TERM\_MAJOR (stix.common.vocabs.ImpactRating\_1\_0 attribute), 34  
 TERM\_MALICIOUS\_CODE (stix.common.vocabs.IncidentCategory\_1\_0 attribute), 34  
 TERM\_MALICIOUS\_EMAIL (stix.common.vocabs.IndicatorType\_1\_0 attribute), 35  
 TERM\_MALICIOUS\_EMAIL (stix.common.vocabs.IndicatorType\_1\_1 attribute), 36  
 TERM\_MALWARE (stix.common.vocabs.AttackerToolType\_1\_0 attribute), 31  
 TERM\_MALWARE\_ARTIFACTS (stix.common.vocabs.IndicatorType\_1\_0 attribute), 35  
 TERM\_MALWARE\_ARTIFACTS  
 TERM\_MALWARE\_CHARACTERIZATION (stix.common.vocabs.PackageIntent\_1\_0 attribute), 40  
 TERM\_MALWARE\_CHARACTERIZATION (stix.common.vocabs.ReportIntent\_1\_0 attribute), 42  
 TERM\_MALWARE\_SAMPLES (stix.common.vocabs.PackageIntent\_1\_0 attribute), 40  
 TERM\_MALWARE\_SAMPLES (stix.common.vocabs.ReportIntent\_1\_0 attribute), 42  
 TERM\_MANAGER (stix.common.vocabs.AssetType\_1\_0 attribute), 29  
 TERM\_MEDIA (stix.common.vocabs.AssetType\_1\_0 attribute), 29  
 TERM\_MEDIUM (stix.common.vocabs.HighMediumLow\_1\_0 attribute), 34  
 TERM\_MILITARY (stix.common.vocabs.Motivation\_1\_0 attribute), 39  
 TERM\_MILITARY (stix.common.vocabs.Motivation\_1\_0\_1 attribute), 39  
 TERM\_MILITARY (stix.common.vocabs.Motivation\_1\_1 attribute), 39  
 TERM\_MINOR (stix.common.vocabs.ImpactRating\_1\_0 attribute), 34  
 TERM\_MINUTES (stix.common.vocabs.LossDuration\_1\_0 attribute), 37  
 TERM\_MOBILE (stix.common.vocabs.LocationClass\_1\_0 attribute), 37  
 TERM\_MOBILE\_PHONE (stix.common.vocabs.AssetType\_1\_0 attribute), 29  
 TERM\_MOBILE\_SYSTEMS (stix.common.vocabs.SystemType\_1\_0 attribute), 43  
 TERM\_MOBILE\_SYSTEMS\_MOBILE\_DEVICES (stix.common.vocabs.SystemType\_1\_0 attribute), 43  
 TERM\_MOBILE\_SYSTEMS\_MOBILE\_OPERATING\_SYSTEMS (stix.common.vocabs.SystemType\_1\_0 attribute), 43  
 TERM\_MOBILE\_SYSTEMS\_NEAR\_FIELD\_COMMUNICATIONS (stix.common.vocabs.SystemType\_1\_0 attribute), 43  
 TERM\_MODERATE (stix.common.vocabs.ImpactRating\_1\_0 attribute), 34  
 TERM\_MONITORING (stix.common.vocabs.CourseOfActionType\_1\_0 attribute), 32  
 TERM\_MONITORING\_SERVICE

- (stix.common.vocabs.DiscoveryMethod\_1\_0 attribute), 33
- TERM\_MONITORING\_SERVICE (stix.common.vocabs.DiscoveryMethod\_2\_0 attribute), 33
- TERM\_NETWORK (stix.common.vocabs.AssetType\_1\_0 attribute), 30
- TERM\_NEW (stix.common.vocabs.IncidentStatus\_1\_0 attribute), 35
- TERM\_NIDS (stix.common.vocabs.DiscoveryMethod\_1\_0 attribute), 33
- TERM\_NIDS (stix.common.vocabs.DiscoveryMethod\_2\_0 attribute), 33
- TERM\_NO (stix.common.vocabs.SecurityCompromise\_1\_0 attribute), 42
- TERM\_NONE (stix.common.vocabs.HighMediumLow\_1\_0 attribute), 34
- TERM\_NONE (stix.common.vocabs.ImpactRating\_1\_0 attribute), 34
- TERM\_NONREPUDIATION (stix.common.vocabs.LossProperty\_1\_0 attribute), 38
- TERM\_NOVICE (stix.common.vocabs.ThreatActorSophistication\_1\_0 attribute), 43
- TERM\_OBSCURATION (stix.common.vocabs.AvailabilityLossType\_1\_0 attribute), 32
- TERM\_OBSCURATION (stix.common.vocabs.AvailabilityLossType\_1\_1\_1 attribute), 32
- TERM\_OBSERVATIONS (stix.common.vocabs.PackageIntent\_1\_0 attribute), 40
- TERM\_OBSERVATIONS (stix.common.vocabs.ReportIntent\_1\_0 attribute), 42
- TERM\_OBSERVATIONS\_EMAIL (stix.common.vocabs.PackageIntent\_1\_0 attribute), 40
- TERM\_OBSERVATIONS\_EMAIL (stix.common.vocabs.ReportIntent\_1\_0 attribute), 42
- TERM\_ONGOING (stix.common.vocabs.CampaignStatus\_1\_0 attribute), 32
- TERM\_OPEN (stix.common.vocabs.IncidentStatus\_1\_0 attribute), 35
- TERM\_OPPORTUNISTIC (stix.common.vocabs.Motivation\_1\_0 attribute), 39
- TERM\_OPPORTUNISTIC (stix.common.vocabs.Motivation\_1\_0\_1 attribute), 39
- TERM\_OPPORTUNISTIC (stix.common.vocabs.Motivation\_1\_1 attribute), 39
- tribute), 40
- TERM\_OTHER (stix.common.vocabs.CourseOfActionType\_1\_0 attribute), 32
- TERM\_PAINFUL (stix.common.vocabs.ImpactQualification\_1\_0 attribute), 34
- TERM\_PARTNER (stix.common.vocabs.AssetType\_1\_0 attribute), 30
- TERM\_PARTNEROWNED (stix.common.vocabs.OwnershipClass\_1\_0 attribute), 40
- TERM\_PASSWORD\_CRACKING (stix.common.vocabs.AttackerToolType\_1\_0 attribute), 31
- TERM\_PATCHING (stix.common.vocabs.CourseOfActionType\_1\_0 attribute), 32
- TERM\_PAYMENT\_CARD (stix.common.vocabs.AssetType\_1\_0 attribute), 30
- TERM\_PAYMENT\_SWITCH (stix.common.vocabs.AssetType\_1\_0 attribute), 30
- TERM\_PBX (stix.common.vocabs.AssetType\_1\_0 attribute), 30
- TERM\_PED\_PAD (stix.common.vocabs.AssetType\_1\_0 attribute), 30
- TERM\_PENETRATION\_TESTING (stix.common.vocabs.AttackerToolType\_1\_0 attribute), 31
- TERM\_PERIMETER\_BLOCKING (stix.common.vocabs.CourseOfActionType\_1\_0 attribute), 32
- TERM\_PERIPHERAL (stix.common.vocabs.AssetType\_1\_0 attribute), 30
- TERM\_PERMANENT (stix.common.vocabs.LossDuration\_1\_0 attribute), 37
- TERM\_PERSON (stix.common.vocabs.AssetType\_1\_0 attribute), 30
- TERM\_PHYSICAL\_ACCESS\_RESTRICTIONS (stix.common.vocabs.CourseOfActionType\_1\_0 attribute), 32
- TERM\_PLANNING (stix.common.vocabs.PlanningAndOperationalSupport\_1\_0 attribute), 41
- TERM\_PLANNING (stix.common.vocabs.PlanningAndOperationalSupport\_1\_0 attribute), 41
- TERM\_PLANNING\_OPEN\_SOURCE\_INTELLIGENCE\_OSINT\_GETH (stix.common.vocabs.PlanningAndOperationalSupport\_1\_0 attribute), 41
- TERM\_PLANNING\_OPENSOURCE\_INTELLIGENCE\_OSINT\_GATHE (stix.common.vocabs.PlanningAndOperationalSupport\_1\_0\_1 attribute), 41
- TERM\_PLANNING\_OPERATIONAL\_COVER\_PLAN (stix.common.vocabs.PlanningAndOperationalSupport\_1\_0 attribute), 41
- TERM\_PLANNING\_OPERATIONAL\_COVER\_PLAN

(stix.common.vocabs.PlanningAndOperationalSupport\_1\_0 attribute), 38  
 attribute), 41

TERM\_PLANNING\_PRE\_OPERATIONAL\_SURVEILLANCE\_AND\_RECONNAISSANCE  
 (stix.common.vocabs.PlanningAndOperationalSupport\_1\_0 attribute), 41

TERM\_PLANNING\_PREOPERATIONAL\_SURVEILLANCE\_AND\_RECONNAISSANCE\_POT  
 (stix.common.vocabs.PlanningAndOperationalSupport\_1\_0 attribute), 42

TERM\_PLANNING\_TARGET\_SELECTION (stix.common.vocabs.PlanningAndOperationalSupport\_1\_0 attribute), 41

TERM\_PLANNING\_TARGET\_SELECTION (stix.common.vocabs.PlanningAndOperationalSupport\_1\_0 attribute), 42

TERM\_PLC (stix.common.vocabs.AssetType\_1\_0 attribute), 30

TERM\_POLICITAL (stix.common.vocabs.Motivation\_1\_0 attribute), 39

TERM\_POLICITAL (stix.common.vocabs.Motivation\_1\_0 attribute), 39

TERM\_POLICY\_ACTIONS (stix.common.vocabs.CourseOfActionType\_1\_0 attribute), 32

TERM\_POLITICAL (stix.common.vocabs.Motivation\_1\_1 attribute), 40

TERM\_PORT\_SCANNER (stix.common.vocabs.AttackerToolType\_1\_0 attribute), 31

TERM\_POS\_CONTROLLER (stix.common.vocabs.AssetType\_1\_0 attribute), 30

TERM\_POS\_OR\_ATM\_MALWARE (stix.common.vocabs.MalwareType\_1\_0 attribute), 38

TERM\_POS\_TERMINAL (stix.common.vocabs.AssetType\_1\_0 attribute), 30

TERM\_PRACTITIONER (stix.common.vocabs.ThreatActorSophistication\_1\_0 attribute), 43

TERM\_PRINT (stix.common.vocabs.AssetType\_1\_0 attribute), 30

TERM\_PRIVATE\_WAN (stix.common.vocabs.AssetType\_1\_0 attribute), 30

TERM\_PROXY (stix.common.vocabs.AssetType\_1\_0 attribute), 30

TERM\_PUBLIC\_DISCLOSURE (stix.common.vocabs.CourseOfActionType\_1\_0 attribute), 32

TERM\_PUBLIC\_WAN (stix.common.vocabs.AssetType\_1\_0 attribute), 30

TERM\_RANSOMWARE (stix.common.vocabs.MalwareType\_1\_0 attribute), 38

TERM\_REBUILDING (stix.common.vocabs.CourseOfActionType\_1\_0 attribute), 32

TERM\_REDIRECTION (stix.common.vocabs.CourseOfActionType\_1\_0 attribute), 32

TERM\_REDIRECTION\_ON\_SSH\_KEY\_POT (stix.common.vocabs.CourseOfActionType\_1\_0 attribute), 32

TERM\_REGULATORY\_COMPLIANCE\_OR\_LEGAL\_IMPACT (stix.common.vocabs.IncidentEffect\_1\_0 attribute), 35

TERM\_REJECTED (stix.common.vocabs.IncidentStatus\_1\_0 attribute), 35

TERM\_REMEDY (stix.common.vocabs.COASStage\_1\_0 attribute), 32

TERM\_REMOTE\_ACCESS (stix.common.vocabs.AssetType\_1\_0 attribute), 30

TERM\_REMOTE\_ACCESS\_TROJAN (stix.common.vocabs.MalwareType\_1\_0 attribute), 38

TERM\_RESPONSE (stix.common.vocabs.COASStage\_1\_0 attribute), 32

TERM\_RESTITUTION\_ACHIEVED (stix.common.vocabs.IncidentStatus\_1\_0 attribute), 35

TERM\_REVOKES (stix.common.vocabs.Versioning\_1\_0 attribute), 44

TERM\_ROGUE\_ANTIVIRUS (stix.common.vocabs.MalwareType\_1\_0 attribute), 38

TERM\_ROOTKIT (stix.common.vocabs.MalwareType\_1\_0 attribute), 38

TERM\_ROUTER\_OR\_SWITCH (stix.common.vocabs.AssetType\_1\_0 attribute), 30

TERM\_RTU (stix.common.vocabs.AssetType\_1\_0 attribute), 30

TERM\_SAN (stix.common.vocabs.AssetType\_1\_0 attribute), 30

TERM\_SCADA (stix.common.vocabs.AssetType\_1\_0 attribute), 30

TERM\_SCANSORPROBESORATTEMPTED\_ACCESS (stix.common.vocabs.IncidentCategory\_1\_0 attribute), 34

TERM\_SECONDS (stix.common.vocabs.LossDuration\_1\_0 attribute), 37

TERM\_SECURITY\_ALARM (stix.common.vocabs.DiscoveryMethod\_1\_0 attribute), 33

TERM\_SECURITY\_ALARM (stix.common.vocabs.DiscoveryMethod\_2\_0 attribute), 33

TERM\_SERVER (stix.common.vocabs.AssetType\_1\_0 attribute), 30



TERM_TRAFFIC_DIVERSION (stix.common.vocabs.IntendedEffect_1_0 attribute), 37	TERM_UNKNOWN (stix.common.vocabs.SecurityCompromise_1_0 attribute), 42
TERM_TRAFFIC_SCANNER (stix.common.vocabs.AttackerToolType_1_0 attribute), 31	TERM_UNRELATED_PARTY (stix.common.vocabs.DiscoveryMethod_1_0 attribute), 33
TERM_TRAINING (stix.common.vocabs.CourseOfActionType_1_0 attribute), 33	TERM_UNRELATED_PARTY (stix.common.vocabs.DiscoveryMethod_2_0 attribute), 34
TERM_TRANSFORMERORTRANSLATOR (stix.common.vocabs.InformationSourceRole_1_0 attribute), 36	TERM_UPDATE_CORRECTS (stix.common.vocabs.Versioning_1_0 attribute), 44
TERM_TTP_INFRASTRUCTURE (stix.common.vocabs.PackageIntent_1_0 attribute), 40	TERM_UPDATES_REVISES (stix.common.vocabs.Versioning_1_0 attribute), 44
TERM_TTP_INFRASTRUCTURE (stix.common.vocabs.ReportIntent_1_0 attribute), 42	TERM_URL_WATCHLIST (stix.common.vocabs.IndicatorType_1_0 attribute), 35
TERM_TTP_TOOLS (stix.common.vocabs.PackageIntent_1_0 attribute), 40	TERM_URL_WATCHLIST (stix.common.vocabs.IndicatorType_1_1 attribute), 36
TERM_TTP_TOOLS (stix.common.vocabs.ReportIntent_1_0 attribute), 42	TERM_USER (stix.common.vocabs.DiscoveryMethod_1_0 attribute), 33
TERM_UNAUTHORIZED_ACCESS (stix.common.vocabs.IncidentCategory_1_0 attribute), 34	TERM_USER (stix.common.vocabs.DiscoveryMethod_2_0 attribute), 34
TERM_UNAUTHORIZED_ACCESS (stix.common.vocabs.IntendedEffect_1_0 attribute), 37	TERM_USER_DATA_LOSS (stix.common.vocabs.IncidentEffect_1_0 attribute), 35
TERM_UNINTENDED_ACCESS (stix.common.vocabs.IncidentEffect_1_0 attribute), 35	TERM_USER_DEVICE (stix.common.vocabs.AssetType_1_0 attribute), 30
TERM_UNKNOWN (stix.common.vocabs.AssetType_1_0 attribute), 30	TERM_USERS (stix.common.vocabs.SystemType_1_0 attribute), 43
TERM_UNKNOWN (stix.common.vocabs.AvailabilityLossType_1_0 attribute), 32	TERM_USERS_APPLICATION_AND_SOFTWARE (stix.common.vocabs.SystemType_1_0 attribute), 43
TERM_UNKNOWN (stix.common.vocabs.AvailabilityLossType_1_1 attribute), 32	TERM_USERS_REMOVABLE_MEDIA (stix.common.vocabs.SystemType_1_0 attribute), 43
TERM_UNKNOWN (stix.common.vocabs.DiscoveryMethod_1_0 attribute), 33	TERM_USERS_WORKSTATION (stix.common.vocabs.SystemType_1_0 attribute), 43
TERM_UNKNOWN (stix.common.vocabs.DiscoveryMethod_1_1 attribute), 34	TERM_VOIP_ADAPTER (stix.common.vocabs.AssetType_1_0 attribute), 30
TERM_UNKNOWN (stix.common.vocabs.HighMediumLow_1_0 attribute), 34	TERM_VOIP_PHONE (stix.common.vocabs.AssetType_1_0 attribute), 30
TERM_UNKNOWN (stix.common.vocabs.ImpactQualification_1_0 attribute), 34	TERM_VULNERABILITY_SCANNER (stix.common.vocabs.AttackerToolType_1_0 attribute), 31
TERM_UNKNOWN (stix.common.vocabs.ImpactRating_1_0 attribute), 34	TERM_WEB_APPLICATION (stix.common.vocabs.AssetType_1_0 attribute), 30
TERM_UNKNOWN (stix.common.vocabs.LocationClass_1_0 attribute), 37	TERM_WEEKS (stix.common.vocabs.LossDuration_1_0 attribute), 37
TERM_UNKNOWN (stix.common.vocabs.LossDuration_1_0 attribute), 37	
TERM_UNKNOWN (stix.common.vocabs.ManagementClass_1_0 attribute), 38	
TERM_UNKNOWN (stix.common.vocabs.OwnershipClass_1_0 attribute), 40	



- TERM\_WLAN (stix.common.vocabs.AssetType\_1\_0 attribute), 30
- TERM\_YES (stix.common.vocabs.SecurityCompromise\_1\_0 attribute), 43
- TermsOfUseMarkingStructure (class in stix.extensions.marking.terms\_of\_use\_marking), 61
- ThreatActor (class in stix.threat\_actor), 83
- ThreatActorSophistication (in module stix.common.vocabs), 46
- ThreatActorSophistication\_1\_0 (class in stix.common.vocabs), 43
- ThreatActorType (in module stix.common.vocabs), 46
- ThreatActorType\_1\_0 (class in stix.common.vocabs), 44
- Time (class in stix.incident.time), 69
- TIME\_PRECISION\_VALUES (in module stix.common.datetimewithprecision), 22
- title (stix.core.stix\_header.STIXHeader attribute), 47
- title (stix.report.header.Header attribute), 81
- TLPMarkingStructure (class in stix.extensions.marking.tlp), 61
- to\_dict() (stix.campaign.Campaign method), 20
- to\_dict() (stix.coa.CourseOfAction method), 52
- to\_dict() (stix.common.structured\_text.StructuredText method), 26
- to\_dict() (stix.common.structured\_text.StructuredTextList method), 27
- to\_dict() (stix.core.stix\_package.STIXPackage method), 49
- to\_dict() (stix.exploit\_target.ExploitTarget method), 55
- to\_dict() (stix.incident.Incident method), 65
- to\_dict() (stix.indicator.indicator.Indicator method), 74
- to\_dict() (stix.threat\_actor.ThreatActor method), 84
- to\_dict() (stix.ttp.TTP method), 86
- to\_json() (stix.campaign.Campaign method), 20
- to\_json() (stix.coa.CourseOfAction method), 52
- to\_json() (stix.core.stix\_package.STIXPackage method), 49
- to\_json() (stix.exploit\_target.ExploitTarget method), 55
- to\_json() (stix.incident.Incident method), 65
- to\_json() (stix.indicator.indicator.Indicator method), 74
- to\_json() (stix.threat\_actor.ThreatActor method), 84
- to\_json() (stix.ttp.TTP method), 86
- to\_obj() (stix.campaign.Campaign method), 20
- to\_obj() (stix.coa.CourseOfAction method), 52
- to\_obj() (stix.common.structured\_text.StructuredText method), 26
- to\_obj() (stix.common.structured\_text.StructuredTextList method), 27
- to\_obj() (stix.core.stix\_package.STIXPackage method), 49
- to\_obj() (stix.exploit\_target.ExploitTarget method), 55
- to\_obj() (stix.incident.Incident method), 65
- to\_obj() (stix.indicator.indicator.CompositeIndicatorExpression method), 75
- to\_obj() (stix.indicator.indicator.Indicator method), 74
- to\_obj() (stix.indicator.indicator.RelatedCampaignRefs method), 77
- to\_obj() (stix.indicator.indicator.RelatedIndicators method), 76
- to\_obj() (stix.indicator.indicator.SuggestedCOAs method), 78
- to\_obj() (stix.threat\_actor.ThreatActor method), 84
- to\_obj() (stix.ttp.TTP method), 86
- to\_xml() (stix.base.Entity method), 17
- to\_xml() (stix.core.stix\_package.STIXPackage method), 50
- ToolInformation (class in stix.common.tools), 28
- TotalLossEstimation (class in stix.incident.total\_loss\_estimation), 69
- TTP (class in stix.ttp), 85
- TTPs (class in stix.core.ttps), 50

## U

- UnknownVersionError (class in stix.utils.parser), 95
- UnsupportedRootElement (in module stix.utils.parser), 95
- UnsupportedVersionError (class in stix.utils.parser), 95
- update() (stix.common.structured\_text.StructuredTextList method), 27

## V

- ValidTime (class in stix.indicator.valid\_time), 79
- value (stix.common.structured\_text.StructuredText attribute), 26
- Versioning\_1\_0 (class in stix.common.vocabs), 44
- VictimTargeting (class in stix.ttp.victim\_targeting), 90
- VocabString (class in stix.common.vocabs), 44
- Vulnerability (class in stix.exploit\_target.vulnerability), 56

## W

- Weakness (class in stix.exploit\_target.weakness), 58

## X

- xml\_bool() (in module stix.utils), 91
- XML\_NS\_STIX\_EXT (in module stix.extensions.identity.ciq\_identity\_3\_0), 60
- XML\_NS\_XAL (in module stix.extensions.identity.ciq\_identity\_3\_0), 60
- XML\_NS\_XNL (in module stix.extensions.identity.ciq\_identity\_3\_0), 60
- XML\_NS\_XPIL (in module stix.extensions.identity.ciq\_identity\_3\_0), 60

## Y

YaraTestMechanism (class in  
stix.extensions.test\_mechanism.yara\_test\_mechanism),  
[63](#)