

---

# **yq Documentation**

**Andrey Kislyuk**

**Jun 29, 2018**



---

## Contents

---

<b>1</b>	<b>Installation</b>	<b>1</b>
<b>2</b>	<b>Synopsis</b>	<b>3</b>
<b>3</b>	<b>XML support</b>	<b>5</b>
<b>4</b>	<b>Authors</b>	<b>7</b>
<b>5</b>	<b>Links</b>	<b>9</b>
5.1	Bugs .....	9
<b>6</b>	<b>License</b>	<b>11</b>
<b>7</b>	<b>API documentation</b>	<b>13</b>
<b>8</b>	<b>Release Notes</b>	<b>15</b>
<b>9</b>	<b>Changes for v2.6.0 (2018-04-28)</b>	<b>17</b>
<b>10</b>	<b>Changes for v2.5.0 (2018-04-02)</b>	<b>19</b>
<b>11</b>	<b>Changes for v2.4.1 (2018-02-13)</b>	<b>21</b>
<b>12</b>	<b>Changes for v2.4.0 (2018-02-08)</b>	<b>23</b>
<b>13</b>	<b>Changes for v2.3.7 (2018-02-07)</b>	<b>25</b>
<b>14</b>	<b>Changes for v2.3.6 (2018-01-29)</b>	<b>27</b>
<b>15</b>	<b>Changes for v2.3.5 (2018-01-29)</b>	<b>29</b>
<b>16</b>	<b>Changes for v2.3.4 (2017-12-26)</b>	<b>31</b>
<b>17</b>	<b>Changes for v2.3.3 (2017-09-30)</b>	<b>33</b>
<b>18</b>	<b>Changes for v2.3.2 (2017-09-25)</b>	<b>35</b>
<b>19</b>	<b>Changes for v2.3.1 (2017-09-25)</b>	<b>37</b>

<b>20</b>	<b>Changes for v2.3.0 (2017-08-27)</b>	<b>39</b>
<b>21</b>	<b>Changes for v2.2.0 (2017-07-07)</b>	<b>41</b>
<b>22</b>	<b>Changes for v2.1.2 (2017-06-27)</b>	<b>43</b>
<b>23</b>	<b>Changes for v2.1.1 (2017-05-02)</b>	<b>45</b>
<b>24</b>	<b>Changes for v2.1.0 (2017-05-02)</b>	<b>47</b>
<b>25</b>	<b>Changes for v2.0.2 (2017-01-16)</b>	<b>49</b>
<b>26</b>	<b>Changes for v2.0.1 (2017-01-14)</b>	<b>51</b>
<b>27</b>	<b>Changes for v2.0.0 (2017-01-14)</b>	<b>53</b>
<b>28</b>	<b>Table of Contents</b>	<b>55</b>

# CHAPTER 1

---

## Installation

---

```
pip install yq
```

Before using `yq`, you also have to install its dependency, `jq`. See the [jq installation instructions](#) for details and directions specific to your platform.



---

### Synopsis

---

`yq` takes YAML input, converts it to JSON, and pipes it to `jq`:

```
cat input.yml | yq .foo.bar
```

Like in `jq`, you can also specify input filename(s) as arguments:

```
yq .foo.bar input.yml
```

By default, no conversion of `jq` output is done. Use the `--yaml-output/-y` argument to convert it back into YAML:

```
cat input.yml | yq -y .foo.bar
```

Use the `--width/-w` argument to pass the line wrap width for string literals. All other command line arguments are forwarded to `jq`. `yq` forwards the exit code `jq` produced, unless there was an error in YAML parsing, in which case the exit code is 1. See the [jq manual](#) for more details on `jq` features and options.

YAML `tags` in the input are ignored (any nested data is treated as untagged). Key order is preserved.





## CHAPTER 3

---

### XML support

---

`yc` also supports XML. The `yc` package installs an executable, `xq`, which transcodes XML to JSON using `xmltodict` and pipes it to `jq`. Roundtrip transcoding is available with the `xq --xml-output/xq -x` option. Multiple XML documents can be passed in separate files/streams as `xq a.xml b.xml`. Entity expansion and DTD resolution is disabled to avoid XML parsing vulnerabilities.

---

#### Compatibility note

This package's release series available on PyPI begins with version 2.0.0. Versions of `yc` prior to 2.0.0 are distributed by <https://github.com/abesto/yc> and are not related to this package. No guarantees of compatibility are made between `abesto/yc` and `kislyuk/yc`. This package follows the [Semantic Versioning 2.0.0](#) standard. To ensure proper operation, declare dependency version ranges according to SemVer.

---



## CHAPTER 4

---

### Authors

---

- Andrey Kislyuk



- [Project home page \(GitHub\)](#)
- [Documentation \(Read the Docs\)](#)
- [Package distribution \(PyPI\)](#)
- [Change log](#)
- [jq - the command-line JSON processor utility powering yq](#)

## 5.1 Bugs

Please report bugs, issues, feature requests, etc. on [GitHub](#).



## CHAPTER 6

---

License

---

Licensed under the terms of the [Apache License, Version 2.0](#).





## CHAPTER 7

---

API documentation

---



## CHAPTER 8

---

Release Notes

---



## CHAPTER 9

---

### Changes for v2.6.0 (2018-04-28)

---

- Packaging: Replace scripts with entry-points
- Packaging: Package the license file



## CHAPTER 10

---

### Changes for v2.5.0 (2018-04-02)

---

- Parse unrecognized tags instead of dropping them. Fixes #23





# CHAPTER 11

---

## Changes for v2.4.1 (2018-02-13)

---

- Ignore unrecognized YAML tags instead of crashing
- Explicitly disable XML entity expansion and mention in docs
- xq -x: Raise understandable error on non-dict conversion failure



## CHAPTER 12

---

Changes for v2.4.0 (2018-02-08)

---

- Support XML parsing with xmldict



## CHAPTER 13

---

### Changes for v2.3.7 (2018-02-07)

---

- Fix for the `-from-file/-f` argument: Re-route `jq_filter` to files when using `-from-file`. Fixes #19.



## CHAPTER 14

---

### Changes for v2.3.6 (2018-01-29)

---

- Parse and pass multiple positional-consuming jq args





## CHAPTER 15

---

### Changes for v2.3.5 (2018-01-29)

---

- Support jq arguments that consume subsequent positionals (such as `-arg k v`) (#16).



## CHAPTER 16

---

### Changes for v2.3.4 (2017-12-26)

---

- Support bare YAML dates and times. Fixes #10



## CHAPTER 17

---

### Changes for v2.3.3 (2017-09-30)

---

- Avoid buffering all input docs in memory with no -y
- End all json.dump output with newlines. Close all input streams. Fixes #8. Thanks to @bubbleattic for reporting.



## CHAPTER 18

---

Changes for v2.3.2 (2017-09-25)

---

- Fix test suite on Python 3





## CHAPTER 19

---

### Changes for v2.3.1 (2017-09-25)

---

- Add support for multiple yaml files in arguments. Thanks to @bubbleattic (PR #7)



## CHAPTER 20

---

### Changes for v2.3.0 (2017-08-27)

---

- Handle multi-document streams. Fixes #6
- Report version via `yq -version`



## CHAPTER 21

---

### Changes for v2.2.0 (2017-07-07)

---

- Stringify datetimes loaded from YAML. Fixes #5



## CHAPTER 22

---

### Changes for v2.1.2 (2017-06-27)

---

- Fix ResourceWarning: unclosed file
- Internal: Make usage of loader argument consistent
- Documentation improvements





## CHAPTER 23

---

### Changes for v2.1.1 (2017-05-02)

---

- Fix release script. Release is identical to v2.1.0.



## CHAPTER 24

---

### Changes for v2.1.0 (2017-05-02)

---

- `yq` now supports emitting YAML (round-trip YAML support) using `"yq -y"`. Fixes #2.
- Key order is now preserved in mappings/objects/dictionaries.
- Passing input files by filename as an argument is now supported (in addition to providing data on standard input).



## CHAPTER 25

---

Changes for v2.0.2 (2017-01-16)

---

- Test and documentation improvements



## CHAPTER 26

---

Changes for v2.0.1 (2017-01-14)

---

- Fix description in setup.py





---

### Changes for v2.0.0 (2017-01-14)

---

- Begin 2.0.0 release series. This package's release series available on PyPI begins with version 2.0.0. Versions of `yq` prior to 2.0.0 are distributed by <https://github.com/abesto/yq> and are not related to this package. No guarantees of compatibility are made between `abesto/yq` and `kislyuk/yq`. This package follows the Semantic Versioning 2.0.0 [<http://semver.org/>](http://semver.org/) standard. To ensure proper operation, declare dependency version ranges according to SemVer. See the Readme for more information.



## CHAPTER 28

---

### Table of Contents

---

- genindex
- modindex
- search